



Maximum Permissible Exposure (MPE) & Exposure evaluation

Report identification number: 1-9697/19-01-07 MPE (FCC_ISED)

Certification numbers and labeling requirements	
FCC ID	IYZMU2
ISED number	2701A-MU2
HVIN (Hardware Version Identification Number)	MU2
PMN (Product Marketing Name)	MU2
FVIN (Firmware Version Identification Number)	-/-
HMN (Host Marketing Name)	-/-

This report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:

cn=Alexander Hnatovskiy, o=CTC
advanced GmbH, ou=HNA-161129,
email=Alexander.Hnatovskiy@ctcadvanced
.com, c=DE
2020.04.16 08:12:57 +02'00'

Alexander Hnatovskiy
Lab Manager
Radio Communications & EMC

cn=Marco Scigliano, o=CTC advanced
GmbH, ou=SCI-161125,
email=marco.scigliano@ctcadvanced.c
om, c=DE
2020.04.16 08:13:37 +02'00'

Marco Scigliano
Testing Manager
Radio Communications & EMC

EUT technologies:

Technologies:	Max. power [dBm]		Antenna gain max.: [dBi]	Declared by customer	#
	measured	EIRP			
UWB 6.520 to 7.560 GHz	max. -41.3 dBm/MHz	-13.33	--	<< 0 dBm	A

Details and origins of the measurements shown in the table above:

#	Results from:	Additional information
A	1-9697/19-01-06 CTC Advanced GmbH	UWB max. bandwidth page 19 (627.68 MHz)

Note:

Max. power for UWB calculated with -41.3dBm/MHz EIRP
 $-41.3 + 10 \cdot \log_{10}(627.68) \text{ dB} = \mathbf{-13.33 \text{ dBm}}$

Prediction of MPE limit at given distance - FCC

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density
 P = Power input to the antenna
 G = Antenna gain
 R = Distance to the center of radiation of the antenna
 PG = Output Power including antenna gain

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

Prediction: worst case

Technologies:		UWB	
	Frequency (MHz)	7040	
PG	Declared max power (EIRP)	0	dBm
R	Distance	20	cm
S	MPE limit for uncontrolled exposure	1	mW/cm ²
	Calculated Power density:	0.0002	mW/cm ²
	Calculated percentage of Limit:	0.02%	

The power density levels for FCC at a distance of 20 cm are below the maximum levels allowed by regulations.

Prediction of MPE limit at given distance - ISED

RSS-102, Issue 5, 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

Prediction: worst case

		UWB	
	Frequency	7040	MHz
R	Distance	20	cm
PG	Maximum EIRP	0	dBm
PG	Maximum EIRP	1.0	mW
	Exclusion Limit from above:	5.00	W
	Calculated percentage of Limit:	0.02%	

Conclusion: RF exposure evaluation is not required.