

Over view

Model: CRD-BP1500U is the CD-RW Drive with Max. signal transfer rate: X40 speed. This device is provided USB2.0 interface and installed internal of the Personal Computer.

< Specifications >

Recording/playback speed

Recording	:	x2 ,x4,x8,x12,x16,x24(Write)
		x2 ,x4,x8,x10(Rewrite)
Playback & Data reading	:	x1 ~ x40 speed

Signal transfer rate

x1 speed (CLV)	:	150kB/s	
x2 speed (CLV)	:	300kB/s	x16 ~x40 speed(CAV) : 2400kB/s~6000kB/s
x4 speed (CLV)	:	600kB/s	
x8 speed (CLV)	:	1200kB/s	
x12 speed (CLV)	:	1800kB/s	

Connectors

Interface connector	:	4-pin	
DC connector:	:	4-pin, +5V, +12V	(for Internal use)
	:	5-pin, +5V, +12V	(for External use)
Analog Audio connector	:	4-pin	(for Internal use)
(Line Out)	:	3.5mm stereo mini-jack	(for External use)
Digital Audio connector	:	2-pin	(for Internal use)
Headphone	:	3.5mm stereo mini-jack	

Audio

Headphone Output level	:	90mV (1kHz, 28dB)
Line Out Output level	:	70mV (1kHz, 70dB)

Loading method: Tray loading

Dimensions: (WxDxH) 146 x 188.5 x 41.3 mm

Weight: 1040g