

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                          |                                                                                           |                                          |                                                  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|------------------------------------------|--------------------------------------------------|
| <b>Prüfbericht-Nr.:</b><br><i>Test Report No.:</i>                                                                                                                                                                                                                                                                                                                                                                                                                  | <b>50213465 001</b>                                                                                                                      | <b>Auftrags-Nr.:</b><br><i>Order No.:</i>                                                 | <b>114084462</b>                         | <b>Seite 1 von 34</b><br><i>Page 1 of 34</i>     |
| <b>Kunden-Referenz-Nr.:</b><br><i>Client Reference No.:</i>                                                                                                                                                                                                                                                                                                                                                                                                         | <b>N/A</b>                                                                                                                               | <b>Auftragsdatum:</b><br><i>Order date:</i>                                               | <b>30-Nov-2018</b>                       |                                                  |
| <b>Auftraggeber:</b><br><i>Client:</i>                                                                                                                                                                                                                                                                                                                                                                                                                              | <b>Kingston Technology Company, Inc.</b><br>17600 Newhope St., Fountain Valley, CA, 92708 USA                                            |                                                                                           |                                          |                                                  |
| <b>Prüfgegenstand:</b><br><i>Test item:</i>                                                                                                                                                                                                                                                                                                                                                                                                                         | <b>HyperX Pulsefire Dart Wireless Adapter</b>                                                                                            |                                                                                           |                                          |                                                  |
| <b>Bezeichnung / Typ-Nr.:</b><br><i>Identification / Type No.:</i>                                                                                                                                                                                                                                                                                                                                                                                                  | <b>HXS-MCWA1,HXS-MCWA1-XXXXXX</b><br>(Where "X" is difference of color or shipping location and may be alphanumeric characters or blank) |                                                                                           |                                          |                                                  |
| <b>Auftrags-Inhalt:</b><br><i>Order content:</i>                                                                                                                                                                                                                                                                                                                                                                                                                    | <b>FCC/IC Test report</b>                                                                                                                |                                                                                           |                                          |                                                  |
| <b>Prüfgrundlage:</b><br><i>Test specification:</i>                                                                                                                                                                                                                                                                                                                                                                                                                 | <b>FCC 47CFR Part 15: Subpart C Section 15.247(DTS)</b><br><b>RSS-247 ISSUE 2 FEB 2017</b>                                               |                                                                                           |                                          |                                                  |
| <b>Wareneingangsdatum:</b><br><i>Date of receipt:</i>                                                                                                                                                                                                                                                                                                                                                                                                               | <b>11-Dec-2018</b>                                                                                                                       |                                                                                           |                                          |                                                  |
| <b>Prüfmuster-Nr.:</b><br><i>Test sample No.:</i>                                                                                                                                                                                                                                                                                                                                                                                                                   | <b>A000847937-003</b><br><b>A000847937-002</b>                                                                                           |                                                                                           |                                          |                                                  |
| <b>Prüfzeitraum:</b><br><i>Testing period:</i>                                                                                                                                                                                                                                                                                                                                                                                                                      | <b>7-Dec-2018 - 19-Dec-2018</b>                                                                                                          |                                                                                           |                                          |                                                  |
| <b>Ort der Prüfung:</b><br><i>Place of testing:</i>                                                                                                                                                                                                                                                                                                                                                                                                                 | <b>EMC/RF Laboratory Taipei</b>                                                                                                          |                                                                                           |                                          |                                                  |
| <b>Prüflaboratorium:</b><br><i>Testing laboratory:</i>                                                                                                                                                                                                                                                                                                                                                                                                              | <b>TUV Rheinland Taiwan Ltd.</b>                                                                                                         |                                                                                           |                                          |                                                  |
| <b>Prüfergebnis*:</b><br><i>Test result*:</i>                                                                                                                                                                                                                                                                                                                                                                                                                       | <b>Pass</b>                                                                                                                              |                                                                                           |                                          |                                                  |
| <b>geprüft von / tested by:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                          | <b>kontrolliert von / reviewed by:</b>                                                    |                                          |                                                  |
|                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                          |       |                                          |                                                  |
| <b>2019-01-17</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                   | <b>Mars Y.J. Lin/Project Engineer</b>                                                                                                    | <b>2019-01-17</b>                                                                         | <b>Ryan W. T. Chen / Project Manager</b> |                                                  |
| <b>Datum</b><br><i>Date</i>                                                                                                                                                                                                                                                                                                                                                                                                                                         | <b>Name / Stellung</b><br><i>Name / Position</i>                                                                                         | <b>Unterschrift</b><br><i>Signature</i>                                                   | <b>Datum</b><br><i>Date</i>              | <b>Name / Stellung</b><br><i>Name / Position</i> |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                          |                                                                                           |                                          | <b>Unterschrift</b><br><i>Signature</i>          |
| <b>Sonstiges / Other:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                                                          |                                                                                           |                                          |                                                  |
| <b>Zustand des Prüfgegenstandes bei Anlieferung:</b><br><i>Condition of the test item at delivery:</i>                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                                          | <b>Prüfmuster vollständig und unbeschädigt</b><br><i>Test item complete and undamaged</i> |                                          |                                                  |
| <p>* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft<br/> P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet</p> <p>Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor<br/> P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested</p>                    |                                                                                                                                          |                                                                                           |                                          |                                                  |
| <p><b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b><br/> <b>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</b></p> |                                                                                                                                          |                                                                                           |                                          |                                                  |

## TEST SUMMARY

**5.1.1 ANTENNA REQUIREMENT***RESULT: Passed***5.1.2 PEAK OUTPUT POWER***RESULT: Passed***5.1.3 6dB BANDWIDTH***RESULT: Passed***5.1.4 POWER DENSITY***RESULT: Passed***5.1.5 CONDUCTED SPURIOUS EMISSIONS AND FREQUENCY BAND EDGE MEASURED IN  
100kHz BANDWIDTH***RESULT: Passed***5.1.6 SPURIOUS EMISSION***RESULT: Passed***5.2.1 MAINS CONDUCTED EMISSIONS***RESULT: Passed***6.1.1 ELECTROMAGNETIC FIELDS***RESULT: Passed*

## Contents

|            |                                                                                               |           |
|------------|-----------------------------------------------------------------------------------------------|-----------|
| <b>1.</b>  | <b>GENERAL REMARKS .....</b>                                                                  | <b>5</b>  |
| <b>1.1</b> | <b>COMPLEMENTARY MATERIALS.....</b>                                                           | <b>5</b>  |
| <b>1.2</b> | <b>DECISION RULE OF CONFORMITY .....</b>                                                      | <b>5</b>  |
| <b>2.</b>  | <b>TEST SITES .....</b>                                                                       | <b>6</b>  |
| <b>2.1</b> | <b>TEST LABORATORY .....</b>                                                                  | <b>6</b>  |
| <b>2.2</b> | <b>TEST FACILITY.....</b>                                                                     | <b>6</b>  |
| <b>2.3</b> | <b>LIST OF TEST AND MEASUREMENT INSTRUMENTS.....</b>                                          | <b>7</b>  |
| <b>2.4</b> | <b>TRACEABILITY .....</b>                                                                     | <b>8</b>  |
| <b>2.5</b> | <b>CALIBRATION .....</b>                                                                      | <b>8</b>  |
| <b>2.6</b> | <b>MEASUREMENT UNCERTAINTY .....</b>                                                          | <b>8</b>  |
| <b>3.</b>  | <b>GENERAL PRODUCT INFORMATION.....</b>                                                       | <b>9</b>  |
| <b>3.1</b> | <b>PRODUCT FUNCTION AND INTENDED USE .....</b>                                                | <b>9</b>  |
| <b>3.2</b> | <b>SYSTEM DETAILS AND RATINGS.....</b>                                                        | <b>9</b>  |
| <b>3.3</b> | <b>INDEPENDENT OPERATION MODES.....</b>                                                       | <b>10</b> |
| <b>3.4</b> | <b>NOISE GENERATING AND NOISE SUPPRESSING PARTS .....</b>                                     | <b>10</b> |
| <b>3.5</b> | <b>SUBMITTED DOCUMENTS.....</b>                                                               | <b>10</b> |
| <b>4.</b>  | <b>TEST SET-UP AND OPERATION MODES.....</b>                                                   | <b>11</b> |
| <b>4.1</b> | <b>PRINCIPLE OF CONFIGURATION SELECTION .....</b>                                             | <b>11</b> |
| <b>4.2</b> | <b>TEST OPERATION AND TEST SOFTWARE.....</b>                                                  | <b>11</b> |
| <b>4.3</b> | <b>SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT .....</b>                                      | <b>11</b> |
| <b>4.4</b> | <b>COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....</b>                                         | <b>12</b> |
| <b>4.5</b> | <b>TEST SETUP DIAGRAM .....</b>                                                               | <b>12</b> |
| <b>5.</b>  | <b>TEST RESULTS .....</b>                                                                     | <b>14</b> |
| <b>5.1</b> | <b>TRANSMITTER REQUIREMENT &amp; TEST SUITES .....</b>                                        | <b>14</b> |
| 5.1.1      | <i>Antenna Requirement .....</i>                                                              | <i>14</i> |
| 5.1.2      | <i>Peak Output Power .....</i>                                                                | <i>15</i> |
| 5.1.3      | <i>6dB Bandwidth .....</i>                                                                    | <i>16</i> |
| 5.1.4      | <i>Power Density .....</i>                                                                    | <i>20</i> |
| 5.1.5      | <i>Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth.....</i> | <i>23</i> |
| 5.1.6      | <i>Spurious Emission .....</i>                                                                | <i>27</i> |
| <b>5.2</b> | <b>MAINS EMISSIONS.....</b>                                                                   | <b>28</b> |
| 5.2.1      | <i>Mains Conducted Emissions.....</i>                                                         | <i>28</i> |
| <b>6.</b>  | <b>SAFETY HUMAN EXPOSURE .....</b>                                                            | <b>29</b> |

|            |                                                  |           |
|------------|--------------------------------------------------|-----------|
| <b>6.1</b> | <b>RADIO FREQUENCY EXPOSURE COMPLIANCE .....</b> | <b>29</b> |
| 6.1.1      | Electromagnetic Fields.....                      | 29        |
| <b>7.</b>  | <b>PHOTOGRAPHS OF THE TEST SET-UP.....</b>       | <b>30</b> |
| <b>8.</b>  | <b>LIST OF TABLES .....</b>                      | <b>34</b> |
| <b>9.</b>  | <b>LIST OF PHOTOGRAPHS.....</b>                  | <b>34</b> |

## 1. General Remarks

### 1.1 Complementary Materials

These attachments are integral parts of this test report:

**Appendix P: Photo Documentation internal view**  
(File Name: 50213465APPENDIX P)

**Appendix D: Test Result of Radiated Emissions**  
(File Name: 50213465APPENDIX D)

Test Specifications

The following standards were applied.

**Table 1: Applied Standard and Test Levels**

| Radio                                                                                                                                                              |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FCC CFR47 Part 15: Subpart C Section 15.247<br>RSS-247 Issue 2 Feb 2017<br>RSS-Gen, Issue 5, April 2018<br>ANSI C63.10:2013<br>KDB558074 D01 DTS Meas Guidance v05 |

### 1.2 Decision Rule of conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard

## 2. Test Sites

### 2.1 Test Laboratory

TUV Rheinland Taiwan Ltd.  
Taichung Branch Office

No.9, Lane 36, Minsheng Rd., Sec. 3, Daya District,  
Taichung City 428  
Taiwan (R.O.C.)

### 2.2 Test Facility

TUV Rheinland Taiwan Ltd.  
Taipei Office

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.  
Taipei City 105  
Taiwan (R.O.C.)

FCC RegistrationNo.: 340738  
IC Canada Registration No.: 9465A-1  
TAF Accredited NCC Test Lab. No.:0759  
TAF ISO17025 Certification effective periods: 2016-Jul-1st to 2019-Jun-30th



**Testing Laboratory**  
**0759**

## 2.3 List of Test and Measurement Instruments

**Table 2: List of Test and Measurement Equipment**

| Kind of Equipment             | Manu-facturer   | Type         | S/N         | Last Calibration | Next Calibration |
|-------------------------------|-----------------|--------------|-------------|------------------|------------------|
| Test Software                 | Farad           | EZ_EMC       | Ver. TUV3A1 | N/A              | N/A              |
| EMI Test Receiver             | R&S             | ESR 7        | 101549      | 2018/11/12       | 2019/11/10       |
| Spectrum Analyzer             | R&S             | FSV 40       | 100921      | 2018/05/02       | 2019/05/02       |
| EXA Signal Analyzer           | KEYSIGHT        | N9010A       | MY52221334  | 2018/02/05       | 2019/02/04       |
| Preamplifier (30MHz -1GHz)    | Hewlett Packard | 8447D        | 2944A06641  | 2017/12/26       | 2018/12/26       |
| Preamplifier (18 GHz -40 GHz) | COM-POWER       | PAM-840      | 461257      | 2018/01/18       | 2019/01/17       |
| Pre-Amplifier (1GHz~18GHz)    | EM Electronics  | EM01G18G     | 60649       | 2018/08/24       | 2019/08/24       |
| Bilog Antenna                 | TESEQ           | CBL6111D     | 29804       | 2018/07/02       | 2019/07/02       |
| Horn Antenna                  | ETS-Lindgren    | 3117         | 138160      | 2018/06/01       | 2019/06/01       |
| Horn Antenna (18GHz~40GHz)    | COM-POWER       | AH-840       | 101031      | 2018/01/16       | 2019/01/16       |
| Loop Antenna                  | Schwarzbeck     | FMZB 1513    | 1513-076    | 2018/06/14       | 2019/06/13       |
| EMI Test Receiver             | R&S             | ESR 7        | 101549      | 2018/11/12       | 2019/11/10       |
| Temp. & Humid. Chamber        | Giant Force     | GCT-099-40-S | MAF0103-007 | 2017/03/09       | 2019/03/09       |
| LISN (1 phase)                | R&S             | ENV216       | 101243      | 2018/06/18       | 2019/06/17       |
| LISN                          | R&S             | ENV216       | 101262      | 2018/06/22       | 2019/06/21       |
| Spectrum Analyzer             | Agilent         | N9010A       | MY53470241  | 2018/06/04       | 2019/06/03       |

## 2.4 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

## 2.5 Calibration

Equipment requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular schedule using in house standards or comparisons.

## 2.6 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements .

**Table 3: Emission Measurement Uncertainty**

| Parameter                     | Uncertainty   |
|-------------------------------|---------------|
| Radio Frequency               | $\pm 0.1$ ppm |
| RF power, conducted           | $\pm 1.5$ dB  |
| RF power density, conducted   | $\pm 3$ dB    |
| spurious emissions, conducted | $\pm 3$ dB    |
| all emissions, radiated       | $\pm 6$ dB    |
| Temperature                   | $\pm 1$ °C    |
| Humidity                      | $\pm 5$ %     |
| DC and low frequency voltages | $\pm 3$ %     |

### 3. General Product Information

#### 3.1 Product Function and Intended Use

The EUT is a Wireless dongle. It contains a 2.4GHz compatible module enabling the user to communicate data through a Wireless interface.  
For details refer to the User Guide, Data Sheet and Circuit Diagram.

#### 3.2 System Details and Ratings

**Table 4: Basic Information of EUT**

| Item                        | EUT information                                                                                                                   |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Kind of Equipment/Test Item | HyperX Pulsefire Dart Wireless Adapter                                                                                            |
| Type Identification         | HXS-MCWA1,HXS-MCWA1-XXXXXX<br>(Where “X” is difference of color or shipping location and may be alphanumeric characters or blank) |
| Brand Name                  | HyperX                                                                                                                            |
| FCC ID                      | JIC-MCWA1                                                                                                                         |
| Canada ID                   | 3880A-MCWA1                                                                                                                       |
| Canada HVIN                 | HXS-MCWA1                                                                                                                         |

**Table 5: Technical Specification of EUT**

| Technical Specification | Value        |
|-------------------------|--------------|
| Operating Frequencies   | 2402-2479MHz |
| Channel Spacing         | 1 MHz        |
| Channel number          | 78           |
| Operation Voltage       | 3.7 Vdc      |
| Modulation              | PWM          |
| Antenna gain            | 2.5 dBi      |

### 3.3 Independent Operation Modes

Basic operation modes are:

- A. Transmitting
  - 1. Low channel
  - 2. Middle channel
  - 3. High channel
- B. Receiving

### 3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

### 3.5 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

## **4. Test Set-up and Operation Modes**

### **4.1 Principle of Configuration Selection**

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

### **4.2 Test Operation and Test Software**

Setup for testing: Test samples are provided with a modified software which makes it possible to control them through a button on the dongle.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed in section 3.3 as appropriate.

The samples were used as follows:

Conducted: A000847937-002

Radiation: A000847937-003

Full test was applied on all test modes, but only worst case was shown

### **4.3 Special Accessories and Auxiliary Equipment**

The product has been tested together with the following additional accessories:


N/A

## 4.4 Countermeasures to achieve EMC Compliance


The test sample which has been tested contained the noise suppression parts as described in the Constructional Data Form or the Technical Construction File. No additional measures were employed to achieve compliance.

## 4.5 Test Setup Diagram

**Diagram of Measurement Configuration for Radiation Test**



Note: Measurements above 1 GHz are done with a table height of 1.5m and absorbing Material on the floor

**Diagram of Measurement Equipment Configuration for Conducted Transmitter Measurement**

## 5. Test Results

### 5.1 Transmitter Requirement & Test Suites

#### 5.1.1 Antenna Requirement

**RESULT:****Passed**

|               |   |                                                                                          |
|---------------|---|------------------------------------------------------------------------------------------|
| Test standard | : | LP0002(2018): 2.2, 3.10.1, (3)<br>FCC Part 15.247(b)(4), Part 15.203 and RSS-<br>Gen 8.3 |
| Requirement   | : | use of approved antennas only with directional gains that<br>do not exceed 6 dBi         |

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 2.5 dBi. The antenna is a Chip Antenna soldered to the PCB with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

Refer to EUT photo for details.

## 5.1.2 Peak Output Power

**RESULT:**
**Passed**

Test standard : LP0002(2018): 3.10.1.2  
 FCC Part 15.247(b)(3), RSS-247 5.4(4)  
 Basic standard : ANSI C63.10:2013, KDB558074  
 Limit : 1 Watt  
 Kind of test site : Shielded room

**Test setup**

Test Channel : Low/ Middle/ High  
 Operation Mode : A  
  
 Ambient temperature : 20-24 °C  
 Relative humidity : 50-65 %  
 Atmospheric pressure : 100-103 kPa

**Table 6: Test result of Peak Output Power**

| Channel        | Channel Frequency (MHz) | Output Power |         | Limit |
|----------------|-------------------------|--------------|---------|-------|
|                |                         | (dBm)        | (W)     | (W)   |
| Low Channel    | 2402                    | -2.30        | 0.00059 | 1     |
| Middle Channel | 2441                    | -2.25        | 0.00060 | 1     |
| High Channel   | 2479                    | -2.23        | 0.00060 | 1     |

Pmax: 0.5984 mW

### 5.1.3 6dB Bandwidth

**RESULT:**
**Passed**

Test standard : LP0002(2018): 3.10.1.5  
 FCC Part 15.247(a)(2), RSS-247 5.2(1)  
 Basic standard : ANSI C63.10:2013, KDB558074  
 Kind of test site : Shielded room

**Test setup**

Test Channel : Low/ Middle/ High  
 Operation Mode : A

Ambient temperature : 20-24°C  
 Relative humidity : 50-65%  
 Atmospheric pressure : 100-103 kPa

**Table 7: Test result of 6dB Bandwidth**

| Channel      | Channel Frequency (MHz) | 6dB Bandwidth (kHz) | Limit (kHz) | Result |
|--------------|-------------------------|---------------------|-------------|--------|
| Low Channel  | 2402                    | 854.8               | >500        | Pass   |
| Mid Channel  | 2441                    | 817.1               | >500        | Pass   |
| High Channel | 2479                    | 869.5               | >500        | Pass   |

**Table 8: Test result of 99% Bandwidth,**

| Channel     | Channel Frequency (MHz) | 99% Bandwidth (kHz) |
|-------------|-------------------------|---------------------|
| Mid Channel | 2441                    | 1823.7              |

## Test Plot of 6dB Bandwidth

### Low Channel



### Middle Channel




### High Channel



## Test Plot of 99% Bandwidth

### Middle Channel



### 5.1.4 Power Density

**RESULT:****Passed**

Test standard : LP0002(2018): 3.10.1.6.2.2  
FCC Part 15.247(e) , RSS-247 5.2(2)  
Basic standard : ANSI C63.10:2013, KDB558074  
Kind of test site : Shielded room

**Test setup**


Test Channel : Low/ Middle/ High  
Operation Mode : A  
Ambient temperature : 20-24°C  
Relative humidity : 50-65%  
Atmospheric pressure : 100-103 kPa

**Table 9: Test result of Power Density**

| Channel        | Channel Frequency (MHz) | Power Density | Limit |
|----------------|-------------------------|---------------|-------|
|                |                         | (dBm)         | (dBm) |
| Low Channel    | 2402                    | -12.91        | 8     |
| Middle Channel | 2441                    | -12.97        | 8     |
| High Channel   | 2479                    | -11.878       | 8     |

## Test Plot of Power Density

### Low Channel



### Middle Channel



### High Channel



**5.1.5 Conducted spurious emissions and Frequency Band Edge  
measured in 100kHz Bandwidth****RESULT:****Passed**


|                   |   |                                                                                                                   |
|-------------------|---|-------------------------------------------------------------------------------------------------------------------|
| Test standard     | : | LP0002(2018): 3.10.1.5<br>FCC part 15.247(d), RSS-247 5.5                                                         |
| Basic standard    | : | ANSI C63.10:2013, KDB558074                                                                                       |
| Limit             | : | 20dB (below that in the 100kHz bandwidth within the<br>band that contains the highest level of the desired power) |
| Kind of test site | : | Shielded room                                                                                                     |


**Test setup**

|                      |   |                                                                                         |
|----------------------|---|-----------------------------------------------------------------------------------------|
| Test Channel         | : | Low/ Middle/ High for Conducted Spurious Emissions<br>Low/ High for Frequency Band Edge |
| Operation Mode       | : | A                                                                                       |
| Ambient temperature  | : | 20-24°C                                                                                 |
| Relative humidity    | : | 50-65%                                                                                  |
| Atmospheric pressure | : | 100-103 kPa                                                                             |

All emissions are more than 20dB below fundamental, details refer to following test plot, and compliance is achieved as well.


Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.






## Test Plot 100kHz RBW of Band Edge

### Low Channel



### High Channel



### 5.1.6 Spurious Emission

**RESULT:****Passed**

|                   |   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test standard     | : | FCC part 15.247(d), FCC 15.205, FCC 15.209 and RSS-Gen 8.9                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Basic standard    | : | LP0002(2018): 3.10.1.5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Limits            | : | ANSI C63.10: 2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|                   | : | Radiated emissions which fall in the restricted bands, as defined in FCC 15.205(a) and RSS-Gen i5, 8.10 (Table 7), must comply with the radiated emission limits specified in FCC 15.209(a) and RSS-Gen 5, 8.9 (Table 5 and 6).<br>Radiated emissions which fall in the restricted bands, as defined in LP0002(2018): 2.7 , must comply with the radiated emission limits specified in LP0002(2018): 2.8<br>Emission radiated outside the restricted and authorized frequency bands must either comply with the radiated emission limits specified for the restricted bands or in FCC15.247(d) and RSS-247 i2, 5.5<br>Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in LP0002(2018): 2.8 |
| Kind of test site | : | 3m Semi-Anechoic Chamber                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

**Test setup**

|                |   |                   |
|----------------|---|-------------------|
| Test Channel   | : | Low/ Middle/ High |
| Operation mode | : | A, B              |

Remark: Testing was carried out within frequency range 30MHz to the tenth harmonic.

For details refer to Appendix D.

Testing was carried out within frequency range 30MHz to the tenth harmonic. For details refer to Appendix D. The Radiated Emissions testing was performed in the X, Y and Z axis orientation. The worst-case Axis orientation is recorded in this test report. Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.

## 5.2 Mains Emissions

### 5.2.1 Mains Conducted Emissions

**RESULT:****Passed**

|                      |   |                                                                                                                                   |
|----------------------|---|-----------------------------------------------------------------------------------------------------------------------------------|
| Test standard        | : | FCC Part 15.207<br>FCC Part 15.107<br>RSS-Gen 8.8<br>LP0002: 2.3                                                                  |
| Limits               | : | Mains Conducted emissions as defined in<br>above test standards must comply with the<br>mains conducted emission limits specified |
| Kind of test site    | : | Shielded Room                                                                                                                     |
| <b>Test setup</b>    |   |                                                                                                                                   |
| Test Channel         | : | Normal link                                                                                                                       |
| Operation mode       | : | Normal link                                                                                                                       |
| Ambient temperature  | : | 20-24 °C                                                                                                                          |
| Relative humidity    | : | 50-65 %                                                                                                                           |
| Atmospheric pressure | : | 100-103 kPa                                                                                                                       |

Remark: For details refer to Appendix D.

## 6. Safety Human exposure

### 6.1 Radio Frequency Exposure Compliance

#### 6.1.1 Electromagnetic Fields

**RESULT:****Passed**

Test standard : FCC KDB Publication 447498 D01 v06  
RSS-102 issue 5, Table 1

FCC:

Since maximum peak output power of the transmitter is 0.5984 mW < 10mW, hence the EUT is excluded from SAR evaluation according to FCC KDB publication 447498: Mobile Portable RF Exposure

Canada:

Maximum conducted peak power: 0.5984 mW

-----  
Antenna Gain: 2.5 dbi -> x 1.78

Maximum EIRP available 1.065 mW

=====  
Maximum Power available: 1.065 mW  
(higher of EIRP or conducted)

Since maximum output power of the transmitter is 1.065 mW < 4mW, hence the EUT is excluded from SAR evaluation according to Table 1 in RSS-102

## 8. List of Tables

|                                                       |    |
|-------------------------------------------------------|----|
| Table 1: Applied Standard and Test Levels .....       | 5  |
| Table 2: List of Test and Measurement Equipment ..... | 7  |
| Table 3: Emission Measurement Uncertainty.....        | 8  |
| Table 4: Basic Information of EUT .....               | 9  |
| Table 5: Technical Specification of EUT .....         | 9  |
| Table 6: Test result of Peak Output Power .....       | 15 |
| Table 7: Test result of 6dB Bandwidth .....           | 16 |
| Table 8: Test result of 99% Bandwidth.....            | 16 |
| Table 9: Test result of Power Density .....           | 20 |

## 9. List of Photographs

|                                                                 |    |
|-----------------------------------------------------------------|----|
| Photograph 1: Set-up for Spurious Emissions (Front View).....   | 30 |
| Photograph 2: Set-up for Spurious Emissions (Back View 1) ..... | 31 |
| Photograph 3: Set-up for Spurious Emissions (Back View 2).....  | 31 |
| Photograph 4: Set-up for Conducted testing .....                | 32 |
| Photograph 5: Set-up for for Mains Conducted testing Back ..... | 32 |
| Photograph 6: Set-up for for Mains Conducted testing Front..... | 33 |