

Appendix H. SAR Test Result

SAR Results for Head Exposure Condition.

Head SAR Test Result														
System & Position						DUT & Accessory	SAR							
Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Channel	Sample	Duty Cycle	Crest Factor	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
1	BT	BR / EDR	Rear Face	0	0	Left Earbud	76.56	1.31	12.50	12.36	1.03	-0.11	0.018	0.02
	BT	BR / EDR	Left Side	0	0	Left Earbud	76.56	1.31	12.50	12.36	1.03	0.17	0.109	0.15
	BT	BR / EDR	Right Side	0	0	Left Earbud	76.56	1.31	12.50	12.36	1.03	0.1	0.117	0.16
	BT	BR / EDR	Top Side	0	0	Left Earbud	76.56	1.31	12.50	12.36	1.03	0.07	0.077	0.10
	BT	BR / EDR	Bottom Side	0	0	Left Earbud	76.56	1.31	12.50	12.36	1.03	0.15	0.039	0.05
	BT	BR / EDR	Right Side	0	39	Left Earbud	76.56	1.31	12.50	12.09	1.10	0.01	0.097	0.14
	BT	BR / EDR	Right Side	0	78	Left Earbud	76.56	1.31	12.50	11.82	1.17	0.15	0.09	0.14
2	BT	BR / EDR	Rear Face	0	0	Right Earbud	76.56	1.31	12.50	12.36	1.03	0.03	0.011	0.01
	BT	BR / EDR	Left Side	0	0	Right Earbud	76.56	1.31	12.50	12.36	1.03	0.03	0.106	0.14
	BT	BR / EDR	Right Side	0	0	Right Earbud	76.56	1.31	12.50	12.36	1.03	0.1	0.091	0.12
	BT	BR / EDR	Top Side	0	0	Right Earbud	76.56	1.31	12.50	12.36	1.03	0.17	0.082	0.11
	BT	BR / EDR	Bottom Side	0	0	Right Earbud	76.56	1.31	12.50	12.36	1.03	-0.16	0.03	0.04
	BT	BR / EDR	Left Side	0	39	Right Earbud	76.56	1.31	12.50	12.09	1.10	0.07	0.079	0.11
	BT	BR / EDR	Left Side	0	78	Right Earbud	76.56	1.31	12.50	11.82	1.17	0.1	0.088	0.13