

FCC Test Report

Report No.: RF170417E07

FCC ID: JNZCU0017

Test Model: C-U0017

Received Date: Apr. 17, 2017

Test Date: June 19 to 27, 2017

Issued Date: July 04, 2017

Applicant: LOGITECH FAR EAST LTD.

Address: #2 Creation Rd. 4, Science-Based Ind. Park Hsinchu Taiwan, R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location (1): E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	5
2.2 Modification Record	5
3 General Information	6
3.1 General Description of EUT	6
3.2 Description of Test Modes	6
3.2.1 Test Mode Applicability and Tested Channel Detail	7
3.3 Duty Cycle of Test Signal	9
3.4 Description of Support Units	10
3.4.1 Configuration of System under Test	10
3.5 General Description of Applied Standards	11
4 Test Types and Results	12
4.1 Radiated Emission Measurement	12
4.1.1 Limits of Radiated Emission Measurement	12
4.1.2 Test Instruments	13
4.1.3 Test Procedures	14
4.1.4 Deviation from Test Standard	14
4.1.5 Test Setup	15
4.1.6 EUT Operating Conditions	15
4.1.7 Test Results	16
4.2 20dB Bandwidth Measurement	19
4.2.1 Limits of 20dB Bandwidth Measurement	19
4.2.2 Test Setup	19
4.2.3 Test Instruments	19
4.2.4 Test Procedure	19
4.2.5 Deviation from Test Standard	19
4.2.6 EUT Operating Conditions	19
4.2.7 Test Result	20
4.3 Deactivation Time Measurement	21
4.3.1 Limits of Deactivation Time Measurement	21
4.3.2 Test Setup	21
4.3.3 Test Instruments	21
4.3.4 Test Procedures	21
4.3.5 Deviation from Test Standard	21
4.3.6 EUT Operating Conditions	21
4.3.7 Test Results	22
5 Pictures of Test Arrangements	23
Appendix – Information on the Testing Laboratories	24

Release Control Record

Issue No.	Description	Date Issued
RF170417E07	Original release.	July 04, 2017

1 Certificate of Conformity

Product: USB Transceiver

Brand: Logitech

Test Model: C-U0017

Sample Status: ENGINEERING SAMPLE

Applicant: LOGITECH FAR EAST LTD.

Test Date: June 19 to 27, 2017

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.231)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Cindy Hsin , **Date:** July 04, 2017
Cindy Hsin / Specialist

Approved by : May Chen , **Date:** July 04, 2017
May Chen / Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (SECTION 15.231)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	NA	Without AC power port of the EUT.
15.209 15.231(b)	Radiated Emission Test	PASS	Meet the requirement of limit. Minimum passing margin is -0.7dB at 433.92MHz.
15.231(c)	Emission Bandwidth Measurement	PASS	Meet the requirement of limit.
15.231(a)	De-activation	PASS	Meet the requirement of limit.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.32 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.14 dB
	6GHz ~ 18GHz	5.04 dB
	18GHz ~ 40GHz	5.25 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	USB Transceiver
Brand	Logitech
Test Model	C-U0017
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	5Vdc (Host equipment)
Modulation Type	FSK
Transfer Rate	2.4kbps
Operating Frequency	433.92MHz
Number of Channel	1
Antenna Type	Chip antenna with 0.83 dBi gain
Accessory Device	NA
Data Cable Supplied	NA

Note:

1. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

One channel was provided to this EUT:

Channel	FREQ. (MHz)
1	433.92

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO					DESCRIPTION
	RE ≥ 1G	RE < 1G	PLC	EB	DT	
-	√	√	-	√	√	-

Where

RE≥1G: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

EB: 20dB Bandwidth measurement

DT: Deactivation Time measurement

NOTE: 1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.

NOTE: 2. "-" means no effect.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
1	1	FSK

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
1	1	FSK

Emission Bandwidth Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
1	1	FSK

Deactivation Time Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
1	1	FSK

TEST CONDITION:

Applicable To	Environmental Conditions	Input Power	Tested By
RE $\geq$ 1G	25deg. C, 64%RH	DC 5V	Andy Ho
RE<1G	25deg. C, 69%RH	DC 5V	Weiwei Lo
EB	25deg. C, 60%RH	DC 5V	Robert Cheng
DT	25deg. C, 60%RH	DC 5V	Anderson Chen

3.3 Duty Cycle of Test Signal

Duty cycle of test signal is < 98 %


Duty cycle = 24.5 ms/100 ms = 0.245

Tx1=2.6ms

Tx2=4.9ms

Tx3=2.4ms

Tx total= Tx1*1+Tx2*3+Tx3*3=24.5ms




3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Wireless Presenter	Logitech	R-R0011	NA	JNZRR0011	Supplied by client

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.231)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

Note: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC).
The test report has been issued separately.

4 Test Types and Results

4.1 Radiated Emission Measurement

4.1.1 Limits of Radiated Emission Measurement

Fundamental Frequency (MHz)	Field Strength of Fundamental		Field Strength of Spurious	
	uV/meter	dBuV/meter	uV/meter	dBuV/meter
40.66 ~ 40.70	2250	67.04	225	48.04
70 ~ 130	1250	61.94	125	41.94
130 ~ 174	1250 ~ 3750	61.94 ~ 71.48	125 ~ 375	41.94 ~ 51.48
174 ~ 260	3750	71.48	375	51.48
260 ~ 470	3750 ~ 12500	71.48 ~ 81.94	375 ~ 1250	51.48 ~ 61.94
Above 470	12500	81.94	1250	61.94

NOTE:

- Where F is the frequency in MHz, the formula for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, $\mu\text{V/m}$ at 3 meters = $56.81818(F) - 6136.3636$; for the band 260-470 MHz, $\mu\text{V/m}$ at 3 meters = $41.6667(F) - 7083.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.
- The above field strength limits are specified at a distance of 3meters. The tighter limits apply at the band edges.

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	$2400/F(\text{kHz})$	300
0.490 ~ 1.705	$24000/F(\text{kHz})$	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

- The lower limit shall apply at the transition frequencies.
- Emission level (dBuV/m) = $20 \log$ Emission level ($\mu\text{V/m}$).
- For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY50010156	Aug. 18, 2016	Aug. 17, 2017
Pre-Amplifier ^(*) EMCI	EMC001340	980142	Jan. 20, 2016	Jan. 19, 2018
Loop Antenna ^(*) Electro-Metrics	EM-6879	264	Dec. 16, 2016	Dec. 15, 2018
RF Cable	NA	LOOPCAB-001 LOOPCAB-002	Jan. 17, 2017	Jan. 16, 2018
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-05	May 06, 2017	May 05, 2018
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Dec. 29, 2016	Dec. 28, 2017
RF Cable	8D	966-3-1 966-3-2 966-3-3	Apr. 01, 2017	Mar. 31, 2018
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-3-01	Oct. 05, 2016	Oct. 04, 2017
Horn Antenna SCHWARZBECK	BBHA9120-D	9120D-406	Dec. 28, 2016	Dec. 27, 2017
Pre-Amplifier EMCI	EMC12630SE	980384	Feb. 02, 2017	Feb. 01, 2018
RF Cable	EMC104-SM-SM-1200 EMC104-SM-SM-2000 EMC104-SM-SM-5000	160922 150317 150322	Feb. 02, 2017 Mar. 29, 2017 Mar. 29, 2017	Feb. 01, 2018 Mar. 28, 2018 Mar. 28, 2018
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. *The calibration interval of the above test instruments is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in 966 Chamber No. 3.
4. The FCC Site Registration No. is 147459
5. The CANADA Site Registration No. is 20331-1
6. Tested Date: June 20 to 21, 2017

4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) and peak detection (PK) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Set the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

ABOVE 1GHz DATA :

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 10GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1301.76	34.9 PK	74.0	-39.1	1.00 H	300	39.9	-5.0
2	1301.76	22.7 AV	54.0	-31.3	1.00 H	300	27.7	-5.0
3	#1735.68	45.1 PK	74.0	-28.9	1.75 H	44	48.8	-3.7
4	#1735.68	32.9 AV	54.0	-21.1	1.75 H	44	36.6	-3.7
5	#2169.60	46.3 PK	74.0	-27.7	1.41 H	305	48.7	-2.4
6	#2169.60	34.1 AV	54.0	-19.9	1.41 H	305	36.5	-2.4
7	#2603.52	54.3 PK	74.0	-19.7	1.00 H	317	55.4	-1.1
8	#2603.52	42.1 AV	54.0	-11.9	1.00 H	317	43.2	-1.1
9	#3037.44	52.1 PK	74.0	-21.9	1.00 H	321	52.3	-0.2
10	#3037.44	39.9 AV	54.0	-14.1	1.00 H	321	40.1	-0.2
11	#3471.36	51.3 PK	74.0	-22.7	1.36 H	20	50.7	0.6
12	#3471.36	39.1 AV	54.0	-14.9	1.36 H	20	38.5	0.6
13	3905.28	58.5 PK	74.0	-15.5	1.30 H	24	57.3	1.2
14	3905.28	46.3 AV	54.0	-7.7	1.30 H	24	45.1	1.2
15	4339.20	50.0 PK	74.0	-24.0	1.22 H	360	48.0	2.0
16	4339.20	37.8 AV	54.0	-16.2	1.22 H	360	35.8	2.0
17	4773.12	40.1 PK	74.0	-33.9	1.01 H	18	37.2	2.9
18	4773.12	27.9 AV	54.0	-26.1	1.01 H	18	25.0	2.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. The average value of harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty factor is calculated from following formula:

$$20 \log (\text{Duty cycle}) = 20 \log (24.5 \text{ ms} / 100 \text{ ms}) = -12.2 \text{ dB}$$

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 10GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1301.76	33.0 PK	74.0	-41.0	1.54 V	218	38.0	-5.0
2	1301.76	20.8 AV	54.0	-33.2	1.54 V	218	25.8	-5.0
3	#1735.68	35.8 PK	74.0	-38.2	1.54 V	96	39.5	-3.7
4	#1735.68	23.6 AV	54.0	-30.4	1.54 V	96	27.3	-3.7
5	#2169.60	45.0 PK	74.0	-29.0	3.65 V	355	47.4	-2.4
6	#2169.60	32.8 AV	54.0	-21.2	3.65 V	355	35.2	-2.4
7	#2603.52	49.9 PK	74.0	-24.1	2.76 V	345	51.0	-1.1
8	#2603.52	37.7 AV	54.0	-16.3	2.76 V	345	38.8	-1.1
9	#3037.44	47.3 PK	74.0	-26.7	1.08 V	94	47.5	-0.2
10	#3037.44	35.1 AV	54.0	-18.9	1.08 V	94	35.3	-0.2
11	#3471.36	48.1 PK	74.0	-25.9	3.60 V	357	47.5	0.6
12	#3471.36	35.9 AV	54.0	-18.1	3.60 V	357	35.3	0.6
13	3905.28	58.0 PK	74.0	-16.0	1.07 V	184	56.8	1.2
14	3905.28	45.8 AV	54.0	-8.2	1.07 V	184	44.6	1.2
15	4339.20	47.6 PK	74.0	-26.4	3.01 V	347	45.6	2.0
16	4339.20	35.4 AV	54.0	-18.6	3.01 V	347	33.4	2.0
17	4773.12	38.4 PK	74.0	-35.6	1.49 V	288	35.5	2.9
18	4773.12	26.2 AV	54.0	-27.8	1.49 V	288	23.3	2.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. The average value of harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty factor is calculated from following formula:

$$20 \log (\text{Duty cycle}) = 20 \log (24.5 \text{ ms} / 100 \text{ ms}) = -12.2 \text{ dB}$$

BELOW 1GHz DATA

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		Peak (PK) Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	31.65	20.2 QP	40.0	-19.8	1.00 H	280	29.6	-9.4
2	196.11	20.7 QP	43.5	-22.8	1.00 H	178	31.9	-11.2
3	229.09	20.0 QP	46.0	-26.0	2.00 H	316	30.8	-10.8
4	311.81	19.9 QP	46.0	-26.1	1.00 H	234	27.0	-7.1
5	* 433.92	92.3 PK	100.8	-8.5	2.32 H	352	96.4	-4.1
6	* 433.92	80.1 AV	80.8	-0.7	2.32 H	352	84.2	-4.1
7	651.67	25.5 QP	46.0	-20.5	2.00 H	0	25.6	-0.1
8	780.29	27.5 QP	46.0	-18.5	2.00 H	116	25.4	2.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	31.84	25.3 QP	40.0	-14.7	1.00 V	218	34.7	-9.4
2	39.89	23.5 QP	40.0	-16.5	1.00 V	201	32.3	-8.8
3	229.12	20.7 QP	46.0	-25.3	2.00 V	149	31.5	-10.8
4	* 433.92	83.1 PK	100.8	-17.7	2.65 V	272	87.2	-4.1
5	* 433.92	70.9 AV	80.8	-9.9	2.65 V	272	75.0	-4.1
6	558.43	25.5 QP	46.0	-20.5	1.00 V	277	27.4	-1.9
7	644.35	27.9 QP	46.0	-18.1	2.00 V	268	28.1	-0.2
8	867.76	32.2 QP	46.0	-13.8	1.00 V	76	29.7	2.5

REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " * ": Fundamental frequency.
- The average value of fundamental frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty factor is calculated from following formula:
20 log (Duty cycle) = 20 log (24.5 ms / 100 ms) = -12.2 dB


4.2 20dB Bandwidth Measurement

4.2.1 Limits of 20dB Bandwidth Measurement

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for device operating above 70 MHz and below 900 MHz.

Fundamental Frequency (MHz)	Limit of Emission Bandwidth (kHz)
433.92	1084.8

4.2.2 Test Setup



4.2.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.2.4 Test Procedure

- The EUT was placed on the turn table.
- The signal was coupled to the spectrum analyzer through an antenna.
- Set the resolution bandwidth to 3 kHz and video bandwidth to 10 kHz then select Peak function to scan the channel frequency.
- The emission bandwidth was measured and recorded.

4.2.5 Deviation from Test Standard


No deviation.

4.2.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.2.7 Test Result

Channel	Frequency (MHz)	20dB Bandwidth (kHz)	Maximum Limit (kHz)	Pass / Fail
1	433.92	76.123	1084.8	Pass




4.3 Deactivation Time Measurement

4.3.1 Limits of Deactivation Time Measurement

A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedures

- The EUT was placed on the turning table.
- The signal was coupled to the spectrum analyzer through an antenna.
- Set the resolution bandwidth to 100kHz and video bandwidth to 300kHz. The spectrum analyser was turned to the centre frequency of the transmitter's and the analyser's marker function was used to determine the duration of transmission.
- The transmission duration was measured and recorded.

4.3.5 Deviation from Test Standard


No deviation.

4.3.6 EUT Operating Conditions

Same as Item 4.2.6.

4.3.7 Test Results

Channel	Frequency (MHz)	Transmission Time (Sec)	Maximum Limit (Sec)	Pass/Fail
1	433.92	0.63	5	Pass



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---