FCC TEST REPORT

REPORT NO.:	RF140729E06
MODEL NO.:	S-00147
FCC ID:	JNZS00147
RECEIVED:	July 29, 2014
TESTED:	Aug. 06 to 13, 2014
ISSUED:	Aug. 21, 2014

APPLICANT:	LOGITECH FAR EAST LTD.
ADDRESS:	#2 Creation Rd. 4, Science-Based Ind. Park Hsinchu Taiwan, R.O.C.

ISSUED BY:	Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory
LAB ADDRESS:	No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.
TEST LOCATION (1):	No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, Taiwan, R.O.C.
TEST LOCATION (2):	No.49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD 5
1 CERTIFICATION 6
2 SUMMARY OF TEST RESULTS 7
2.1 MEASUREMENT UNCERTAINTY 9
3 GENERAL INFORMATION 10
3.1 GENERAL DESCRIPTION OF EUT 10
3.2 DESCRIPTION OF TEST MODES 12
3.3 TEST MODE APPLICABLITY AND TESTED CHANNEL DETAIL: 13
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS 17
3.5 DUTY CYCLE OF TEST SIGNAL 18
3.6 DESCRIPTION OF SUPPORT UNITS 19
3.7 CONFIGURATION OF SYSTEM UNDER TEST 19
4 TEST PROCEDURES AND RESULTS (BT-EDR) 20
4.1 CONDUCTED EMISSION MEASUREMENT 20
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 20
4.1.2 TEST INSTRUMENTS 20
4.1.3 TEST PROCEDURES 21
4.1.4 DEVIATION FROM TEST STANDARD 21
4.1.5 TEST SETUP 21
4.1.6 EUT OPERATING CONDITIONS 22
4.1.7 TEST RESULTS 23
4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT 25
4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 25
4.2.2 TEST INSTRUMENTS 26
4.2.3 TEST PROCEDURES 28
4.2.4 DEVIATION FROM TEST STANDARD 28
4.2.5 TEST SETUP 29
4.2.6 EUT OPERATING CONDITIONS 29
4.2.7 TEST RESULTS 30
4.3 NUMBER OF HOPPING FREQUENCY USED 37
4.3.1 LIMIT OF HOPPING FREQUENCY USED 37
4.3.2 TEST INSTRUMENTS 37
4.3.3 TEST PROCEDURES 37
4.3.4 DEVIATION FROM TEST STANDARD 37
4.3.5 TEST SETUP 38
4.3.6 TEST RESULTS 38
4.4 DWELL TIME ON EACH CHANNEL 39
4.4.1 LIMIT OF DWELL TIME USED 39
4.4.2 TEST INSTRUMENTS 39
4.4.3 TEST PROCEDURES 39
4.4.4 DEVIATION FROM TEST STANDARD 40
4.4.5 TEST SETUP 40
4.4.6 TEST RESULTS 41

4.5 CHANNEL BANDWIDTH 45
4.5.1 LIMITS OF CHANNEL BANDWIDTH 45
4.5.2 TEST INSTRUMENTS 45
4.5.3 TEST PROCEDURE 45
4.5.4 DEVIATION FROM TEST STANDARD 45
4.5.5 TEST SETUP 46
4.5.6 EUT OPERATING CONDITION 46
4.5.7 TEST RESULTS 47
4.6 HOPPING CHANNEL SEPARATION 48
4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION 48
4.6.2 TEST INSTRUMENTS 48
4.6.3 TEST PROCEDURES 48
4.6.4 DEVIATION FROM TEST STANDARD 48
4.6.5 TEST SETUP 48
4.6.6 TEST RESULTS 49
4.7 MAXIMUM PEAK OUTPUT POWER 50
4.7.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT 50
4.7.2 INSTRUMENTS 50
4.7.3 TEST PROCEDURES 50
4.7.4 DEVIATION FROM TEST STANDARD 50
4.7.5 TEST SETUP 51
4.7.6 EUT OPERATING CONDITION 51
4.7.7 TEST RESULTS 52
4.8 CONDUCTED OUT-BAND EMISSION MEASUREMENT 53
4.8.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT 53
4.8.2 TEST INSTRUMENTS 53
4.8.3 TEST PROCEDURE 53
4.8.4 DEVIATION FROM TEST STANDARD 53
4.8.5 TEST SETUP 53
4.8.6 EUT OPERATING CONDITION 53
4.8.7 TEST RESULTS 54
5 TEST TYPES AND RESULTS (BT-LE) 57
5.1 CONDUCTED EMISSION MEASUREMENT 57
5.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 57
5.1.2 TEST INSTRUMENTS 57
5.1.3 TEST PROCEDURES 58
5.1.4 DEVIATION FROM TEST STANDARD 58
5.1.5 TEST SETUP 58
5.1.6 EUT OPERATING CONDITIONS 58
5.1.7 TEST RESULTS 59
5.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT 61
5.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 61
5.2.2 TEST INSTRUMENTS 62
5.2.3 TEST PROCEDURES 63
5.2.4 DEVIATION FROM TEST STANDARD 64
5.2.5 TEST SETUP 64
5.2.6 EUT OPERATING CONDITIONS 64
5.2.7 TEST RESULTS 65

5.3 6DB BANDWIDTH MEASUREMENT 69
5.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT 69
5.3.2 TEST INSTRUMENTS 69
5.3.3 TEST PROCEDURE 69
5.3.4 DEVIATION FROM TEST STANDARD 69
5.3.5 TEST SETUP 69
5.3.6 EUT OPERATING CONDITIONS 69
5.3.7 TEST RESULTS 70
5.4 CONDUCTED OUTPUT POWER MEASUREMENT 71
5.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT 71
5.4.2 TEST INSTRUMENTS 71
5.4.3 TEST PROCEDURES 71
5.4.4 DEVIATION FROM TEST STANDARD 72
5.4.5 TEST SETUP 72
5.4.6 EUT OPERATING CONDITIONS 72
5.4.7 TEST RESULTS 73
5.5 POWER SPECTRAL DENSITY MEASUREMENT 74
5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT 74
5.5.2 TEST INSTRUMENTS 74
5.5.3 TEST PROCEDURE 74
5.5.4 DEVIATION FROM TEST STANDARD 74
5.5.5 TEST SETUP 74
5.5.6 EUT OPERATING CONDITION 74
5.5.7 TEST RESULTS 75
5.6 CONDUCTED OUT-BAND EMISSION MEASUREMENT 76
5.6.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT 76
5.6.2 TEST INSTRUMENTS 76
5.6.3 TEST PROCEDURE 76
5.6.4 DEVIATION FROM TEST STANDARD 77
5.6.5 TEST SETUP 77
5.6.6 EUT OPERATING CONDITION 77
5.6.7 TEST RESULTS 77
6 PHOTOGRAPHS OF THE TEST CONFIGURATION 79
7 INFORMATION ON THE TESTING LABORATORIES 80
8 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 81

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF140729E06	Original release	Aug. 21, 2014

1 CERTIFICATION

PRODUCT :	Wireless Speaker
BRAND NAME :	Ue
MODEL NO. :	S-00147
TEST SAMPLE :	ENGINEERING SAMPLE
APPLICANT :	LOGITECH FAR EAST LTD.
TESTED DATE :	Aug. 06 to 13, 2014
STANDARDS :	**FCC Part 15, Subpart C (Section 15.247)** ANSI C63.10-2009

The above equipment (Model: S-00147) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : _____ , **DATE:** *Aug. 21, 2014*
(Midoli Peng, Specialist)

APPROVED BY : _____ , **DATE:** *Aug. 21, 2014*
(May Chen, Manager)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

For BT-EDR mode:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**REMARK**
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -9.67dB at 0.19297MHz.
15.247(a)(1) (iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1) (iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -3.4dB at 39.55MHz
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

NOTE: Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

For BT-LE mode:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**REMARK**
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -8.29dB at 0.19154MHz
15.247(d) 15.209	Radiated Emissions & Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -3.4dB at 39.55MHz
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	**Value**
Conducted emissions	2.86 dB
Radiated emissions (30MHz-1GHz)	5.43 dB
Radiated emissions (1GHz -6GHz) – Chamber G	3.65 dB
Radiated emissions (6GHz -18GHz) – Chamber G	3.88 dB
Radiated emissions (18GHz -40GHz) – Chamber G	4.11 dB
Radiated emissions (1GHz -6GHz) – Chamber H	3.72 dB
Radiated emissions (6GHz -18GHz) – Chamber H	4.00 dB
Radiated emissions (18GHz -40GHz) – Chamber H	4.11 dB

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless Speaker
MODEL NO.	S-00147
POWER SUPPLY	DC 7.2V from battery or DC 12V from power adapter or DC 5V from USB interface
MODULATION TYPE	GFSK, π/4-DQPSK, 8DPSK for FHSS GFSK for DTS
MODULATION TECHNOLOGY	FHSS, DTS
DATE RATE	Up to 3Mbps for BT-EDR mode Up to 1Mbps for BT-LE mode
FREQUENCY RANGE	2402MHz ~ 2480MHz
NUMBER OF CHANNEL	BT-EDR mode: 79 BT-LE mode: 40
MAX. OUTPUT POWER	BT-EDR mode: 8.810mW BT-LE mode: 5.702mW
ANTENNA TYPE	PCB printed antenna (Gain: 2.5dBi)
DATA CABLE	USB cable (shielded, 1.2m) x 1
I/O PORTS	Refer to user's manual
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT has a lot of colors for marketing requirement.
2. The EUT could be supplied with DC 7.2V battery or power adapter as the following table:

Item	Brand	Model No.	Spec.
Battery	Li-ion	533-000116	3130mAh 22.5Wh, 7.2V
Adapter	Ue	AD2026J20	AC input: 100-240V, 50/60Hz, 0.5A DC output: 5V, 2A or 9V, 2A or 12V, 1.5A DC output cable: Shielded, 1.2m

3. There is one NFC tag be installed to this EUT, please refer to the following table:

Brand	Model	Function
NXP Semiconductors	NTAG203F	NFC tag

4. The EUT was pre-tested under following test modes :

Pre-test Mode	Power
Mode A	Battery mode
Mode B	**Adapter mode**

From the above modes, the worst radiated emission was found in **Mode B**.
Therefore only the test data of the modes were recorded in this report.

5. The USB port of the EUT is only for charging the rechargeable battery. And the EUT has Bluetooth function under charging mode.

6. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

79 channels are provided for BT-EDR mode

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

40 channels are provided for BT-LE mode:

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

3.3 TEST MODE APPLICABLITY AND TESTED CHANNEL DETAIL:

For BT-EDR mode:

EUT CONFIGURE MODE	APPLICABLE TO					DESCRIPTION
	PLC	RE < 1G	RE ³ 1G	APCM	OB	
-	√	√	√	√	√	-

Where **PLC:** Power Line Conducted Emission **RE < 1G:** Radiated Emission below 1GHz

RE ³ 1G: Radiated Emission above 1GHz **APCM:** Antenna Port Conducted Measurement

OB: Conducted Out-Band Emission Measurement

NOTE: For radiated emission, the EUT had been pre-tested on the positioned of each 2 axis. The worst case was found when positioned on **Y-plane.**

POWER LINE CONDUCTED EMISSION:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	39	FHSS	GFSK	DH5

RADIATED EMISSION TEST (BELOW 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	39	FHSS	GFSK	DH5

RADIATED EMISSION TEST (ABOVE 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

CONDUCTED OUT-BAND EMISSION MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0, 78	FHSS	GFSK	DH5
0 to 78	0, 78	FHSS	8DPSK	3DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
PLC	30deg. C,70%RH	120Vac, 60Hz	Mike Hsieh
RE<1G	22deg. C, 65%RH	120Vac, 60Hz	Andy Ho
RE³1G	22deg. C, 67%RH	120Vac, 60Hz	Robert Cheng
APCM	25deg. C, 60%RH	120Vac, 60Hz	James Chan
OB	25deg. C, 60%RH	120Vac, 60Hz	James Chan

For BT-LE mode:

EUT CONFIGURE MODE	APPLICABLE TO					DESCRIPTION
	PLC	RE < 1G	RE ³ 1G	APCM	OB	
-	√	√	√	√	√	-

Where **PLC:** Power Line Conducted Emission **RE < 1G:** Radiated Emission below 1GHz

RE ³ 1G: Radiated Emission above 1GHz **APCM:** Antenna Port Conducted Measurement

OB: Conducted Out-Band Emission Measurement

NOTE: For radiated emission, the EUT had been pre-tested on the positioned of each 2 axis. The worst case was found when positioned on **Y-plane.**

POWER LINE CONDUCTED EMISSION TEST:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
BT-LE	0 to 39	19	DTS	GFSK	1

RADIATED EMISSION TEST (BELOW 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
BT-LE	0 to 39	19	DTS	GFSK	1

RADIATED EMISSION TEST (ABOVE 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
BT-LE	0 to 39	0, 19, 39	DTS	GFSK	1

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
BT-LE	0 to 39	0, 19, 39	DTS	GFSK	1

CONDUCTED OUT-BAND EMISSION MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
BT-LE	0 to 39	0, 19, 39	DTS	GFSK	1

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
PLC	30deg. C,70%RH	120Vac, 60Hz	Mike Hsieh
RE<1G	22deg. C, 65%RH	120Vac, 60Hz	Andy Ho
RE³1G	24deg. C, 68%RH	120Vac, 60Hz	Robert Cheng
APCM	25deg. C, 60%RH	120Vac, 60Hz	James Chan
OB	25deg. C, 60%RH	120Vac, 60Hz	James Chan

3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

558074 D01 DTS Meas Guidance v03r02

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

Note: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.5 DUTY CYCLE OF TEST SIGNAL

Duty cycle of test signal is < 98 %, duty factor shall be considered.

For BT_LE-GFSK:

Duty cycle = 0.039 ms/0.657 ms = 0.594

BT_LE-GFSK



3.6 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Cable	Qty.	Length (m)	Shielded (Yes/ No)	Cores (Number)	Remark
1	USB	1	1.2	Yes	0	Supplied by Client

3.7 CONFIGURATION OF SYSTEM UNDER TEST



4 TEST PROCEDURES AND RESULTS (BT-EDR)

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

NOTE:
1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS 30	100375	Apr. 29, 2014	Apr. 28, 2015
Line-Impedance Stabilization Network (for EUT) SCHWARZBECK	NSLK8127	8127-522	Sep. 12, 2013	Sep. 11, 2014
Line-Impedance Stabilization Network (for Peripheral)	ENV216	100071	Nov. 13, 2013	Nov. 12, 2014
RF Cable (JYEBAO)	5DFB	COCCAB-001	Mar. 10, 2014	Mar. 09, 2015
50 ohms Terminator	N/A	EMC-03	Sep. 24, 2013	Sep. 23, 2014
50 ohms Terminator	N/A	EMC-02	Oct. 01, 2013	Sep. 30, 2014
Software ADT	BV ADT_Cond_V7.3.7.3	NA	NA	NA

Note:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
3 The VCCI Con C Registration No. is C-3611.
4 Tested Date: Aug. 06, 2014

4.1.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN.
b. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
c. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
d. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit – 20dB) were not recorded.

NOTE: The resolution bandwidth of test receiver is 9kHz for Quasi-peak detection (QP) & Average detection (AV).

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

1. Turn on the power of EUT.
2. The EUT runs test program “Blue Test3.exe” under transmission/receiving condition continuously at specific channel frequency.

4.1.7 TEST RESULTS

PHASE	Line (L)	DETECTOR FUNCTION	Quasi-Peak (QP) / Average (AV)

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)] Q.P.	Reading Value [dB (uV)] AV.	Emission Level [dB (uV)] Q.P.	Emission Level [dB (uV)] AV.	Limit [dB (uV)] Q.P.	Limit [dB (uV)] AV.	Margin (dB) Q.P.	Margin (dB) AV.
1	0.15000	0.07	47.99	19.80	48.06	19.87	66.00	56.00	-17.94	-36.13
2	**0.19297**	**0.07**	**54.17**	**41.39**	**54.24**	**41.46**	**63.91**	**53.91**	**-9.67**	**-12.45**
3	0.24766	0.07	51.27	36.45	51.34	36.52	61.84	51.84	-10.49	-15.31
4	0.38047	0.09	42.08	29.26	42.17	29.35	58.27	48.27	-16.10	-18.92
5	3.23828	0.23	34.38	17.07	34.61	17.30	56.00	46.00	-21.39	-28.70
6	17.17578	0.64	44.28	37.79	44.92	38.43	60.00	50.00	-15.08	-11.57

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission Level – Limit value
4. Correction Factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



PHASE	Neutral (N)	DETECTOR FUNCTION	Quasi-Peak (QP) / Average (AV)

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)] Q.P.	Reading Value [dB (uV)] AV.	Emission Level [dB (uV)] Q.P.	Emission Level [dB (uV)] AV.	Limit [dB (uV)] Q.P.	Limit [dB (uV)] AV.	Margin (dB) Q.P.	Margin (dB) AV.
1	0.19687	0.07	53.87	38.98	53.94	39.05	63.74	53.74	-9.80	-14.69
2	0.24766	0.07	51.98	38.71	52.05	38.78	61.84	51.84	-9.78	-13.05
3	0.37266	0.09	44.15	32.34	44.24	32.43	58.44	48.44	-14.20	-16.01
4	3.24609	0.23	36.43	18.46	36.66	18.69	56.00	46.00	-19.34	-27.31
5	12.22656	0.51	33.30	24.80	33.81	25.31	60.00	50.00	-26.19	-24.69
6	18.06250	0.66	44.24	37.96	44.90	38.62	60.00	50.00	-15.10	-11.38

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission Level – Limit value
4. Correction Factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB.

4.2.2 TEST INSTRUMENTS

For Below 1GHz test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
MXE EMI Receiver Agilent	N9038A	MY50010156	Jan. 15, 2014	Jan. 14, 2015
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-04	Nov. 13, 2013	Nov. 12, 2014
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Feb. 27, 2014	Feb. 26, 2015
RF Cable	NA	CHHCAB_001	Oct. 06, 2013	Oct. 05, 2014
Spectrum Analyzer R&S	FSV40	100964	July 05, 2014	July 04, 2015
Horn_Antenna AISI	AIH.8018	0000220091110	Dec. 06, 2013	Dec. 05, 2014
Pre-Amplifier Agilent	8449B	3008A01923	Oct. 29, 2013	Oct. 28, 2014
RF Cable	NA	RF104-205 RF104-207 RF104-202	Dec. 12, 2013	Dec. 11, 2014
Spectrum Analyzer Agilent	E4446A	MY48250253	Aug. 28, 2013	Aug. 27, 2014
Pre-Amplifier SPACEK LABS	SLKKa-48-6	9K16	Nov. 13, 2013	Nov. 12, 2014
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 08, 2013	Oct. 07, 2014
Software	ADT_Radiated _V8.7.07	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3 The test was performed in 966 Chamber No. H.
4. The FCC Site Registration No. is 797305.
5 The CANADA Site Registration No. is IC 7450H-3.
6 Tested Date: Aug. 08, 2014

For Above 1GHz test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
MXE EMI Receiver Agilent	N9038A	MY51210105	July 21, 2014	July 20, 2015
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-03	Nov. 13, 2013	Nov. 12, 2014
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-360	Feb. 26, 2014	Feb. 25, 2015
RF Cable	NA	CHGCAB_001	Oct. 05, 2013	Oct. 04, 2014
Spectrum Analyzer R&S	FSV40	100964	July 05, 2014	July 04, 2015
Horn_Antenna AISI	AIH.8018	0000320091110	Nov. 18, 2013	Nov. 17, 2014
Pre-Amplifier Agilent	8449B	3008A02578	June 24, 2014	June 23, 2015
RF Cable	NA	RF104-201 RF104-203 RF104-204	Dec. 12, 2013	Dec. 11, 2014
Spectrum Analyzer Agilent	E4446A	MY48250253	Aug. 28, 2013	Aug. 27, 2014
Pre-Amplifier SPACEK LABS	SLKKa-48-6	9K16	Nov. 13, 2013	Nov. 12, 2014
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 08, 2013	Oct. 07, 2014
Software	ADT_Radiated _V8.7.07	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3 The test was performed in 966 Chamber No. G.
4. The FCC Site Registration No. is 966073.
5 The VCCI Site Registration No. is G-137.
6 The CANADA Site Registration No. is IC 7450H-2.
7 Tested Date: Aug. 09, 2014

4.2.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

f. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 1MHz for Peak detection at frequency above 1GHz.
3. All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

BT_GFSK

CHANNEL	TX Channel 39	**DETECTOR FUNCTION**	Quasi-Peak (QP)
FREQUENCY RANGE	Below 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	79.62	35.7 QP	40.0	-4.3	2.00 H	203	53.09	-17.42
2	113.23	35.1 QP	43.5	-8.4	1.50 H	121	50.37	-15.27
3	158.14	32.1 QP	43.5	-11.4	1.50 H	80	44.66	-12.52
4	247.52	35.5 QP	46.0	-10.5	1.00 H	19	49.23	-13.69
5	322.46	37.5 QP	46.0	-8.5	1.00 H	92	48.34	-10.80
6	940.98	33.9 QP	46.0	-12.1	2.00 H	324	32.55	1.37
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	**39.55**	**36.6 QP**	**40.0**	**-3.4**	**1.00 V**	**245**	**50.09**	**-13.48**
2	110.37	34.5 QP	43.5	-9.0	1.50 V	82	50.02	-15.55
3	246.31	37.1 QP	46.0	-9.0	1.50 V	328	50.76	-13.71
4	322.99	42.6 QP	46.0	-3.4	1.50 V	257	53.38	-10.79
5	857.99	34.4 QP	46.0	-11.6	1.50 V	107	34.59	-0.23
6	956.98	34.2 QP	46.0	-11.9	1.00 V	246	32.58	1.57

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

ABOVE 1GHz DATA

BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	47.1 PK	74.0	-26.9	1.16 H	159	49.57	-2.47
2	2390.00	17.0 AV	54.0	-37.0	1.16 H	159	19.47	-2.47
3	*2402.00	103.4 PK			1.16 H	159	105.81	-2.41
4	*2402.00	73.3 AV			1.16 H	159	75.71	-2.41
5	4804.00	52.7 PK	74.0	-21.3	1.38 H	27	47.08	5.62
6	4804.00	22.6 AV	54.0	-31.4	1.38 H	27	16.98	5.62
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	46.0 PK	74.0	-28.0	1.28 V	215	48.47	-2.47
2	2390.00	15.9 AV	54.0	-38.1	1.28 V	215	18.37	-2.47
3	*2402.00	102.8 PK			1.28 V	215	105.21	-2.41
4	*2402.00	72.7 AV			1.28 V	215	75.11	-2.41
5	4804.00	57.0 PK	74.0	-17.0	1.00 V	210	51.38	5.62
6	4804.00	26.9 AV	54.0	-27.1	1.00 V	210	21.28	5.62

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. Average value = peak reading + 20log(duty cycle).

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	103.5 PK			1.16 H	159	105.74	-2.24
2	*2441.00	73.4 AV			1.16 H	159	75.64	-2.24
3	4882.00	52.3 PK	74.0	-21.7	1.40 H	36	46.36	5.94
4	4882.00	22.2 AV	54.0	-31.8	1.40 H	36	16.26	5.94
5	7323.00	53.2 PK	74.0	-20.8	1.00 H	230	40.02	13.18
6	7323.00	23.1 AV	54.0	-30.9	1.00 H	230	9.92	13.18
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	102.9 PK			1.28 V	215	105.14	-2.24
2	*2441.00	72.8 AV			1.28 V	215	75.04	-2.24
3	4882.00	56.8 PK	74.0	-17.2	1.01 V	211	50.86	5.94
4	4882.00	26.7 AV	54.0	-27.3	1.01 V	211	20.76	5.94
5	7323.00	53.9 PK	74.0	-20.1	1.00 V	216	40.72	13.18
6	7323.00	23.8 AV	54.0	-30.2	1.00 V	216	10.62	13.18

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. Average value = peak reading + 20log(duty cycle).

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	103.1 PK			1.08 H	161	105.16	-2.06
2	*2480.00	73.0 AV			1.08 H	161	75.06	-2.06
3	2483.50	58.2 PK	74.0	-15.8	1.08 H	161	60.23	-2.03
4	2483.50	28.1 AV	54.0	-25.9	1.08 H	161	30.13	-2.03
5	4960.00	52.2 PK	74.0	-21.8	1.43 H	41	45.94	6.26
6	4960.00	22.1 AV	54.0	-31.9	1.43 H	41	15.84	6.26
7	7440.00	53.6 PK	74.0	-20.4	1.00 H	214	40.47	13.13
8	7440.00	23.5 AV	54.0	-30.5	1.00 H	214	10.37	13.13
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	102.4 PK			1.28 V	215	104.46	-2.06
2	*2480.00	72.3 AV			1.28 V	215	74.36	-2.06
3	2483.50	57.1 PK	74.0	-16.9	1.28 V	215	59.13	-2.03
4	2483.50	27.0 AV	54.0	-27.0	1.28 V	215	29.03	-2.03
5	4960.00	56.3 PK	74.0	-17.7	1.00 V	196	50.04	6.26
6	4960.00	26.2 AV	54.0	-27.8	1.00 V	196	19.94	6.26
7	7440.00	54.2 PK	74.0	-19.8	1.00 V	201	41.07	13.13
8	7440.00	24.1 AV	54.0	-29.9	1.00 V	201	10.97	13.13

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. Average value = peak reading + 20log(duty cycle).

BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	47.7 PK	74.0	-26.3	1.18 H	162	50.17	-2.47
2	2390.00	17.6 AV	54.0	-36.4	1.18 H	162	20.07	-2.47
3	*2402.00	102.2 PK			1.18 H	162	104.61	-2.41
4	*2402.00	72.1 AV			1.18 H	162	74.51	-2.41
5	4804.00	52.5 PK	74.0	-21.5	1.38 H	45	46.88	5.62
6	4804.00	22.4 AV	54.0	-31.6	1.38 H	45	16.78	5.62
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	45.9 PK	74.0	-28.1	1.28 V	215	48.37	-2.47
2	2390.00	15.8 AV	54.0	-38.2	1.28 V	215	18.27	-2.47
3	*2402.00	101.6 PK			1.28 V	215	104.01	-2.41
4	*2402.00	71.5 AV			1.28 V	215	73.91	-2.41
5	4804.00	56.2 PK	74.0	-17.8	1.05 V	208	50.58	5.62
6	4804.00	26.1 AV	54.0	-27.9	1.05 V	208	20.48	5.62

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. Average value = peak reading + 20log(duty cycle).

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	102.3 PK			1.18 H	162	104.54	-2.24
2	*2441.00	72.2 AV			1.18 H	162	74.44	-2.24
3	4882.00	52.4 PK	74.0	-21.6	1.44 H	52	46.46	5.94
4	4882.00	22.3 AV	54.0	-31.7	1.44 H	52	16.36	5.94
5	7323.00	53.9 PK	74.0	-20.1	1.00 H	222	40.72	13.18
6	7323.00	23.8 AV	54.0	-30.2	1.00 H	222	10.62	13.18
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	101.7 PK			1.28 V	215	103.94	-2.24
2	*2441.00	71.6 AV			1.28 V	215	73.84	-2.24
3	4882.00	56.0 PK	74.0	-18.0	1.00 V	196	50.06	5.94
4	4882.00	25.9 AV	54.0	-28.1	1.00 V	196	19.96	5.94
5	7323.00	54.4 PK	74.0	-19.6	1.00 V	220	41.22	13.18
6	7323.00	24.3 AV	54.0	-29.7	1.00 V	220	11.12	13.18

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. Average value = peak reading + 20log(duty cycle).

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	102.0 PK			1.08 H	163	104.06	-2.06
2	*2480.00	71.9 AV			1.08 H	163	73.96	-2.06
3	2483.50	50.1 PK	74.0	-23.9	1.08 H	163	52.13	-2.03
4	2483.50	20.0 AV	54.0	-34.0	1.08 H	163	22.03	-2.03
5	4960.00	52.3 PK	74.0	-21.7	1.45 H	53	46.04	6.26
6	4960.00	22.2 AV	54.0	-31.8	1.45 H	53	15.94	6.26
7	7440.00	53.4 PK	74.0	-20.6	1.00 H	223	40.27	13.13
8	7440.00	23.3 AV	54.0	-30.7	1.00 H	223	10.17	13.13
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	101.3 PK			1.28 V	215	103.36	-2.06
2	*2480.00	71.2 AV			1.28 V	215	73.26	-2.06
3	2483.50	56.4 PK	74.0	-17.6	1.28 V	215	58.43	-2.03
4	2483.50	26.3 AV	54.0	-27.7	1.28 V	215	28.33	-2.03
5	4960.00	56.6 PK	74.0	-17.4	1.00 V	188	50.34	6.26
6	4960.00	26.5 AV	54.0	-27.5	1.00 V	188	20.24	6.26
7	7440.00	54.7 PK	74.0	-19.3	1.00 V	226	41.57	13.13
8	7440.00	24.6 AV	54.0	-29.4	1.00 V	226	11.47	13.13

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. Average value = peak reading + 20log(duty cycle).

4.3 NUMBER OF HOPPING FREQUENCY USED

4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 hopping frequencies, and should be equally spaced.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER R&S	FSV 40	100964	July 05, 2014	July 04, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 08, 2014

4.3.3 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.

d. Set the SA on View mode and then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were complete.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer the test result. On the plots, it shows that the hopping frequencies are equally spaced.

GFSK





8DPSK





4.4 DWELL TIME ON EACH CHANNEL

4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER R&S	FSV 40	100964	July 05, 2014	July 04, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 08, 2014

4.4.3 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.

d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.

e. Repeat above procedures until all different time-slot modes have been completed.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 TEST RESULTS

For GFSK:

Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	51 times / 5 sec) *6.32=322.32 times	0.456	146.98	400
DH3	25 (times / 5 sec) *6.32=158 times	1.75	276.5	400
DH5	17 (times / 5 sec) *6.32=107.44 times	3.008	323.18	400

NOTE: Test plots of the transmitting time slot are shown on next page.

DH1


RBW 100 kHz
VBW 100 kHz
SWT 5 s
[T1] MP CLRWR
Ref 20.5 dBm
Att 20 dB
Offset 10.5 dB
Center 2.441 GHz
500 ms/


RBW 100 kHz
VBW 100 kHz
SWT 3 ms
[T1] MP VIEW
Ref 20.5 dBm
Att 20 dB
Offset 10.5 dB
Marker 1 [T1]
-60.10 dBm
1.260000 ms
Delta 2 [T1]
0.33 dB
456.000000 us
Center 2.441 GHz
300 us/

DH3


RBW 100 kHz
VBW 300 kHz
SWT 5 s
[T1] MP CLRWR
Ref 20.5 dBm
Att 20 dB
Offset 10.5 dB
Center 2.441 GHz
500 ms/


RBW 100 kHz
VBW 300 kHz
SWT 5 ms
[T1] MP VIEW
Ref 20.5 dBm
Att 20 dB
Offset 10.5 dB
Marker 1 [T1]
-56.48 dBm
1.600000 ms
Delta 2 [T1]
3.27 dB
1.750000 ms
Center 2.441 GHz
500 us/

DH5


RBW 100 kHz
VBW 300 kHz
SWT 5 s
[T1] MP CLRWR
Ref 20.5 dBm
Att 20 dB
Offset 10.5 dB
Center 2.441 GHz
500 ms/


RBW 100 kHz
VBW 300 kHz
SWT 8 ms
[T1] MP VIEW
Ref 20.5 dBm
Att 20 dB
Offset 10.5 dB
Marker 1 [T1]
-58.85 dBm
2.464000 ms
Delta 2 [T1]
2.49 dB
3.008000 ms
Center 2.441 GHz
800 us/

For 8DPSK:

Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
3DH1	51 (times / 5 sec) *6.32=322.32 times	0.486	156.65	400
3DH3	26 (times / 5 sec) *6.32=164.32 times	1.73	284.27	400
3DH5	17 (times / 5 sec) *6.32=107.44 times	3.072	330.06	400

NOTE: Test plots of the transmitting time slot are shown on next page.

3DH1





3DH3





3DH5





4.5 CHANNEL BANDWIDTH

4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER R&S	FSV 40	100964	July 05, 2014	July 04, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 08, 2014

4.5.3 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.

d. Repeat above procedures until all frequencies measured were complete.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	20dB BANDWIDTH (MHz)	
		GFSK	8DPSK
0	2402	0.95	1.28
39	2441	0.94	1.27
78	2480	0.94	1.27

SPECTRUM PLOT OF WORST VALUE	
GFSK / CH0	8DPSK / CH0
	

4.6 HOPPING CHANNEL SEPARATION

4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25 kHz or two-thirds of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER R&S	FSV 40	100964	July 05, 2014	July 04, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 08, 2014

4.6.3 TEST PROCEDURES

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.

c. By using the MaxHold function record the separation of two adjacent channels.

d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were complete.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 TEST SETUP



4.6.6 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)		20dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)		PASS / FAIL
		GFSK	8DPSK	GFSK	8DPSK	GFSK	8DPSK	
0	2402	1.00	1.01	0.95	1.28	0.64	0.86	PASS
39	2441	1.00	1.00	0.94	1.27	0.63	0.85	PASS
78	2480	1.01	1.01	0.94	1.27	0.63	0.85	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

SPECTRUM PLOT OF WORST VALUE	
GFSK / CH78	8DPSK / CH78
	

4.7 MAXIMUM PEAK OUTPUT POWER

4.7.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Limit is 125mW.

4.7.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER R&S	FSV 40	100964	July 05, 2014	July 04, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 08, 2014

4.7.3 TEST PROCEDURES

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.

d. Measure the captured power within the band and recording the plot.

e. Repeat above procedures until all frequencies required were complete.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation

4.7.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.7.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.7.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	OUTPUT POWER (mW)		OUTPUT POWER (dBm)		POWER LIMIT (mW)	PASS / FAIL
		GFSK	8DPSK	GFSK	8DPSK		
0	2402	6.637	4.721	8.22	6.74	125	PASS
39	2441	8.810	5.741	9.45	7.59	125	PASS
78	2480	7.586	5.309	8.80	7.25	125	PASS

SPECTRUM PLOT OF WORST VALUE

GFSK / CH39



8DPSK / CH39



4.8 CONDUCTED OUT-BAND EMISSION MEASUREMENT

4.8.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.8.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER R&S	FSV 40	100964	July 05, 2014	July 04, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 08, 2014

4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set RBW a of spectrum analyzer to 100 kHz and VBW of spectrum analyzer to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 DEVIATION FROM TEST STANDARD

No deviation

4.8.5 TEST SETUP



4.8.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.8.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

GFSK

Hopping disabled_ Low Channel





Hopping disabled_ High Channel





Hopping enabled_ Low Channel





Hopping enabled_ High Channel





8DPSK

Hopping disabled_ Low Channel





Hopping disabled_ High Channel





Hopping enabled_ Low Channel





Hopping enabled_ High Channel





5 TEST TYPES AND RESULTS (DTS)

5.1 CONDUCTED EMISSION MEASUREMENT

5.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5 0.5-5 5-30	66 to 56 56 60	56 to 46 46 50

NOTE: 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS 30	100375	Apr. 29, 2014	Apr. 28, 2015
Line-Impedance Stabilization Network (for EUT) SCHWARZBECK	NSLK8127	8127-522	Sep. 12, 2013	Sep. 11, 2014
Line-Impedance Stabilization Network (for Peripheral)	ENV216	100071	Nov. 13, 2013	Nov. 12, 2014
RF Cable (JYEBAO)	5DFB	COCCAB-001	Mar. 10, 2014	Mar. 09, 2015
50 ohms Terminator	N/A	EMC-03	Sep. 24, 2013	Sep. 23, 2014
50 ohms Terminator	N/A	EMC-02	Oct. 01, 2013	Sep. 30, 2014
Software ADT	BV ADT_Cond_V7.3.7.3	NA	NA	NA

Note:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
3 The VCCI Con C Registration No. is C-3611.
4 Tested Date: Aug. 06, 2014

5.1.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN.
b. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
c. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
d. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

NOTE:

1. The resolution bandwidth of test receiver is 9kHz for Quasi-peak detection (QP) & Average detection (AV).

5.1.4 DEVIATION FROM TEST STANDARD

No deviation

5.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

5.1.6 EUT OPERATING CONDITIONS

Same 4.1.6

5.1.7 TEST RESULTS

PHASE	Line (L)	DETECTOR FUNCTION	Quasi-Peak (QP) / Average (AV)

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)] Q.P.	Reading Value [dB (uV)] AV.	Emission Level [dB (uV)] Q.P.	Emission Level [dB (uV)] AV.	Limit [dB (uV)] Q.P.	Limit [dB (uV)] AV.	Margin (dB) Q.P.	Margin (dB) AV.
1	0.15000	0.07	48.52	23.15	48.59	23.22	66.00	56.00	-17.41	-32.78
2	**0.19154**	**0.07**	**55.61**	**42.78**	**55.68**	**42.85**	**63.97**	**53.97**	**-8.29**	**-11.12**
3	0.24868	0.07	52.47	39.14	52.54	39.21	61.80	51.80	-9.26	-12.59
4	0.38047	0.09	43.51	31.69	43.60	31.78	58.27	48.27	-14.67	-16.49
5	3.23828	0.23	36.25	23.41	36.48	23.64	56.00	46.00	-19.52	-22.36
6	17.17578	0.64	45.78	38.56	46.42	39.20	60.00	50.00	-13.58	-10.80

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission Level – Limit value
4. Correction Factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



PHASE	Neutral (N)	DETECTOR FUNCTION	Quasi-Peak (QP) / Average (AV)

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)] Q.P.	Reading Value [dB (uV)] AV.	Emission Level [dB (uV)] Q.P.	Emission Level [dB (uV)] AV.	Limit [dB (uV)] Q.P.	Limit [dB (uV)] AV.	Margin (dB) Q.P.	Margin (dB) AV.
1	0.19687	0.07	52.35	39.66	52.42	39.73	63.74	53.74	-11.32	-14.01
2	0.24895	0.07	52.56	37.51	52.63	37.58	61.79	51.79	-9.16	-14.21
3	0.37266	0.09	45.38	33.62	45.47	33.71	58.44	48.44	-12.97	-14.73
4	3.26136	0.23	37.89	20.54	38.12	20.77	56.00	46.00	-17.88	-25.23
5	12.22656	0.51	35.78	26.13	36.29	26.64	60.00	50.00	-23.71	-23.36
6	18.06250	0.66	46.98	36.41	47.64	37.07	60.00	50.00	-12.36	-12.93

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission Level – Limit value
4. Correction Factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



5.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

5.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB.

5.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
MXE EMI Receiver Agilent	N9038A	MY50010156	Jan. 15, 2014	Jan. 14, 2015
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-04	Nov. 13, 2013	Nov. 12, 2014
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Feb. 27, 2014	Feb. 26, 2015
RF Cable	NA	CHHCAB_001	Oct. 06, 2013	Oct. 05, 2014
Spectrum Analyzer R&S	FSV40	100964	July 05, 2014	July 04, 2015
Horn_Antenna AISI	AIH.8018	0000220091110	Dec. 06, 2013	Dec. 05, 2014
Pre-Amplifier Agilent	8449B	3008A01923	Oct. 29, 2013	Oct. 28, 2014
RF Cable	NA	RF104-205 RF104-207 RF104-202	Dec. 12, 2013	Dec. 11, 2014
Spectrum Analyzer Agilent	E4446A	MY48250253	Aug. 28, 2013	Aug. 27, 2014
Pre-Amplifier SPACEK LABS	SLKKa-48-6	9K16	Nov. 13, 2013	Nov. 12, 2014
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 08, 2013	Oct. 07, 2014
Software	ADT_Radiated _V8.7.07	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3 The test was performed in 966 Chamber No. H.
4. The FCC Site Registration No. is 797305.
5 The CANADA Site Registration No. is IC 7450H-3.
6 Tested Date: Aug. 08 to 13, 2014

5.2.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98%) or 10Hz (Duty cycle ≥ 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

5.2.4 DEVIATION FROM TEST STANDARD

No deviation

5.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

5.2.6 EUT OPERATING CONDITIONS

Same as 5.1.6

5.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

BT_LE-GFSK

CHANNEL	TX Channel 19	**DETECTOR FUNCTION**	Quasi-Peak (QP)
FREQUENCY RANGE	Below 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	79.62	35.7 QP	40.0	-4.3	2.00 H	156	53.10	-17.42
2	113.23	35.1 QP	43.5	-8.4	1.00 H	247	50.39	-15.27
3	158.14	34.1 QP	43.5	-9.4	1.50 H	223	46.66	-12.52
4	247.52	38.5 QP	46.0	-7.5	1.00 H	214	52.21	-13.69
5	322.46	37.6 QP	46.0	-8.4	1.00 H	203	48.36	-10.80
6	940.98	35.9 QP	46.0	-10.1	2.00 H	324	34.56	1.37
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	**39.55**	**36.6 QP**	**40.0**	**-3.4**	**1.00 V**	**148**	**50.10**	**-13.48**
2	110.37	35.5 QP	43.5	-8.0	1.50 V	309	51.07	-15.55
3	246.31	37.1 QP	46.0	-8.9	1.50 V	159	50.85	-13.71
4	322.99	42.6 QP	46.0	-3.4	1.50 V	223	53.39	-10.79
5	857.99	36.4 QP	46.0	-9.6	1.50 V	122	36.64	-0.23
6	956.98	37.2 QP	46.0	-8.8	1.00 V	233	35.65	1.57

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

ABOVE 1GHz DATA

BT_LE-GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	52.1 PK	74.0	-21.9	1.04 H	155	57.70	-5.60
2	2390.00	44.6 AV	54.0	-9.4	1.04 H	155	50.20	-5.60
3	*2402.00	103.0 PK			1.04 H	155	108.59	-5.59
4	*2402.00	95.1 AV			1.04 H	155	100.69	-5.59
5	4804.00	51.3 PK	74.0	-22.7	1.02 H	167	47.41	3.89
6	4804.00	42.3 AV	54.0	-11.7	1.02 H	167	38.41	3.89
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	49.5 PK	74.0	-24.5	1.15 V	139	55.10	-5.60
2	2390.00	40.3 AV	54.0	-13.7	1.15 V	139	45.90	-5.60
3	*2402.00	102.2 PK			1.15 V	139	107.79	-5.59
4	*2402.00	94.5 AV			1.15 V	139	100.09	-5.59
5	4804.00	48.1 PK	74.0	-25.9	1.00 V	144	44.21	3.89
6	4804.00	38.9 AV	54.0	-15.1	1.00 V	144	35.01	3.89

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	102.8 PK			1.02 H	131	108.21	-5.41
2	*2440.00	94.8 AV			1.02 H	131	100.21	-5.41
3	4880.00	51.0 PK	74.0	-23.0	1.00 H	148	47.20	3.80
4	4880.00	41.8 AV	54.0	-12.2	1.00 H	148	38.00	3.80
5	7320.00	54.5 PK	74.0	-19.5	1.03 H	105	46.23	8.27
6	7320.00	43.0 AV	54.0	-11.0	1.03 H	105	34.73	8.27
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	102.6 PK			1.08 V	134	108.01	-5.41
2	*2440.00	94.3 AV			1.08 V	134	99.71	-5.41
3	4880.00	47.5 PK	74.0	-26.5	1.00 V	146	43.70	3.80
4	4880.00	38.5 AV	54.0	-15.5	1.00 V	146	34.70	3.80
5	7320.00	54.3 PK	74.0	-19.7	1.00 V	279	46.03	8.27
6	7320.00	42.6 AV	54.0	-11.4	1.00 V	279	34.33	8.27

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	103.1 PK			1.05 H	144	108.33	-5.23
2	*2480.00	95.1 AV			1.05 H	144	100.33	-5.23
3	2483.50	52.2 PK	74.0	-21.8	1.05 H	144	57.40	-5.20
4	2483.50	44.6 AV	54.0	-9.4	1.05 H	144	49.80	-5.20
5	4960.00	52.1 PK	74.0	-21.9	1.02 H	166	48.27	3.83
6	4960.00	42.7 AV	54.0	-11.3	1.02 H	166	38.87	3.83
7	7440.00	54.7 PK	74.0	-19.3	1.00 H	80	46.02	8.68
8	7440.00	43.1 AV	54.0	-10.9	1.00 H	80	34.42	8.68
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	102.5 PK			1.12 V	130	107.73	-5.23
2	*2480.00	94.3 AV			1.12 V	130	99.53	-5.23
3	2483.50	49.4 PK	74.0	-24.6	1.12 V	130	54.60	-5.20
4	2483.50	40.4 AV	54.0	-13.6	1.12 V	130	45.60	-5.20
5	4960.00	47.5 PK	74.0	-26.5	1.03 V	159	43.67	3.83
6	4960.00	38.4 AV	54.0	-15.6	1.03 V	159	34.57	3.83
7	7440.00	54.4 PK	74.0	-19.6	1.00 V	303	45.72	8.68
8	7440.00	42.9 AV	54.0	-11.1	1.00 V	303	34.22	8.68

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

5.3 6dB BANDWIDTH MEASUREMENT

5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

5.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER R&S	FSV 40	100964	July 05, 2014	July 04, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : July 01, 2014

5.3.3 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 100kHz.
2. Set the video bandwidth (VBW) ≥ 3 x RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

5.3.4 DEVIATION FROM TEST STANDARD

No deviation

5.3.5 TEST SETUP



5.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

5.3.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	0.70	0.5	PASS
19	2440	0.70	0.5	PASS
39	2480	0.70	0.5	PASS

SPECTRUM PLOT OF WORST VALUE

BT_LE-GFSK / CH19



5.4 CONDUCTED OUTPUT POWER MEASUREMENT

5.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

5.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Power meter Anritsu	ML2495A	1014008	Apr. 30, 2014	Apr. 29, 2015
Power sensor Anritsu	MA2411B	0917122	Apr. 30, 2014	Apr. 29, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 13, 2014

5.4.3 TEST PROCEDURES

The peak / average power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak / average power sensor. Record the peak power level.

5.4.4 DEVIATION FROM TEST STANDARD

No deviation.

5.4.5 TEST SETUP



5.4.6 EUT OPERATING CONDITIONS

Same as Item 5.3.6

5.4.7 TEST RESULTS

FOR PEAK POWER
BT_LE-GFSK

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
0	2402	4.688	6.71	30	PASS
19	2440	5.702	7.56	30	PASS
39	2480	5.105	7.08	30	PASS

FOR AVERAGE POWER
BT_LE-GFSK

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (mW)	AVERAGE POWER (dBm)
0	2402	4.446	6.48
19	2440	5.559	7.45
39	2480	4.864	6.87

5.5 POWER SPECTRAL DENSITY MEASUREMENT

5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

5.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER R&S	FSV 40	100964	July 05, 2014	July 04, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 13, 2014

5.5.3 TEST PROCEDURE

1. Set the RBW = 3 kHz, VBW =10 kHz, Detector = peak.
2. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
3. Use the peak marker function to determine the maximum amplitude level.

5.5.4 DEVIATION FROM TEST STANDARD

No deviation

5.5.5 TEST SETUP



5.5.6 EUT OPERATING CONDITION

Same as Item 5.3.6

5.5.7 TEST RESULTS

BT_LE-GFSK

Channel	FREQUENCY (MHz)	PSD (dBm)	LIMIT (dBm)	PASS /FAIL
0	2402	-9.82	8	PASS
19	2440	-9.05	8	PASS
39	2480	-9.50	8	PASS

SPECTRUM PLOT OF WORST VALUE

BT_LE-GFSK / CH19



5.6 CONDUCTED OUT-BAND EMISSION MEASUREMENT

5.6.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

5.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER R&S	FSV 40	100964	July 05, 2014	July 04, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 13, 2014

5.6.3 TEST PROCEDURE

Measurement Procedure - Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW ≥ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

Measurement Procedure –Unwanted Emission Level

1. Set RBW = 100 kHz.
2. Set VBW ≥ 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.
7. Use the peak marker function to determine the maximum amplitude level.

5.6.4 DEVIATION FROM TEST STANDARD

No deviation

5.6.5 TEST SETUP



5.6.6 EUT OPERATING CONDITION

Same as Item 5.3.6

5.6.7 TEST RESULTS

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

BT_LE-GFSK

CH 0





CH 19





CH 39





CH 0 Band edge



CH 39 Band edge



6 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

7 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

8 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---