TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: **47 CFR FCC Part 15, Subpart C (Section 15.247)**

Report No.: RFBDKG-WTW-P22030324

FCC ID: JNZSR0192

Model No.: SR0192

Received Date: 2022/3/16

Test Date: 2022/4/17 ~ 2022/4/19

Issued Date: 2022/5/3

Applicant: LOGITECH FAR EAST LTD.

Address: 7700 Gateway Boulevard Newark California United States

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan

FCC Registration / Designation Number: 723255 / TW2022

Approved by: _____ , **Date:** 2022/5/3

May Chen / Manager

This test report consists of 52 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Cherry Chuo / Specialist

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record **4**

1 Certificate **5**

2 Summary of Test Results **6**

2.1 Measurement Uncertainty 6
2.2 Supplementary Information 6

3 General Information **7**

3.1 General Description 7
3.2 Antenna Description of EUT 7
3.3 Channel List 8
3.4 Test Mode Applicability and Tested Channel Detail 9
3.5 Duty Cycle of Test Signal 10
3.6 Test Program Used and Operation Descriptions 11
3.7 Connection Diagram of EUT and Peripheral Devices 11
3.8 Configuration of Peripheral Devices and Cable Connections 12

4 Test Instruments **13**

4.1 RF Output Power 13
4.2 Number of Hopping Frequency Used 13
4.3 Dwell Time on Each Channel 13
4.4 Hopping Channel Separation 13
4.5 20 dB Bandwidth 13
4.6 Conducted Out of Band Emissions 13
4.7 AC Power Conducted Emissions 14
4.8 Unwanted Emissions below 1 GHz 14
4.9 Unwanted Emissions above 1 GHz 15

5 Limits of Test Items **16**

5.1 RF Output Power 16
5.2 Number of Hopping Frequency Used 16
5.3 Dwell Time on Each Channel 16
5.4 Hopping Channel Separation 16
5.5 20 dB Bandwidth 16
5.6 Conducted Out of Band Emissions 16
5.7 AC Power Conducted Emissions 16
5.8 Unwanted Emissions below 1 GHz 17
5.9 Unwanted Emissions above 1 GHz 17

6 Test Arrangements **18**

6.1 RF Output Power 18
6.1.1 Test Setup 18
6.1.2 Test Procedure 18
6.2 Number of Hopping Frequency Used 18
6.2.1 Test Setup 18
6.2.2 Test Procedure 18
6.3 Dwell Time on Each Channel 19
6.3.1 Test Setup 19
6.3.2 Test Procedure 19
6.4 Hopping Channel Separation 19
6.4.1 Test Setup 19
6.4.2 Test Procedure 19
6.5 20 dB Bandwidth 20
6.5.1 Test Setup 20
6.5.2 Test Procedure 20
6.6 Conducted Out of Band Emissions 20
6.6.1 Test Setup 20
6.6.2 Test Procedure 20
6.7 AC Power Conducted Emissions 21

6.7.1 Test Setup 21
6.7.2 Test Procedure 21
6.8 Unwanted Emissions below 1 GHz 22
6.8.1 Test Setup 22
6.8.2 Test Procedure 23
6.9 Unwanted Emissions above 1 GHz 24
6.9.1 Test Setup 24
6.9.2 Test Procedure 24

7 Test Results of Test Item 25

7.1 RF Output Power 25
7.2 Number of Hopping Frequency Used 26
7.3 Dwell Time on Each Channel 27
7.4 Hopping Channel Separation 29
7.5 20 dB Bandwidth 30
7.6 Conducted Out of Band Emissions 31
7.7 AC Power Conducted Emissions 33
7.8 Unwanted Emissions below 1 GHz 35
7.9 Unwanted Emissions above 1 GHz 37

8 Pictures of Test Arrangements 51

9 Information of the Testing Laboratories 52

Release Control Record

Issue No.	Description	Date Issued
RFBDKG-WTW-P22030324	Original release.	2022/5/3

1 Certificate

Product:	Bluetooth speaker
Brand:	ULTIMATE EARS
Test Model:	SR0192
Sample Status:	Engineering sample
Applicant:	LOGITECH FAR EAST LTD.
Test Date:	2022/4/17 ~ 2022/4/19
Standard:	47 CFR FCC Part 15, Subpart C (Section 15.247)
Measurement procedure:	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
Standard / Clause	Test Item	Result	Remark
15.247(b)	RF Output Power	Pass	Meet the requirement of limit.
15.247(a)(1) (iii)	Number of Hopping Frequency Used	Pass	Meet the requirement of limit.
15.247(a)(1) (iii)	Dwell Time on Each Channel	Pass	Meet the requirement of limit.
15.247(a)(1)	Hopping Channel Separation	Pass	Meet the requirement of limit.
15.247(a)(1)	20 dB Bandwidth	-	Refer to Note 1
15.247(d)	Conducted Out of Band Emissions	Pass	Meet the requirement of limit.
15.207	AC Power Conducted Emissions	Pass	Minimum passing margin is -24.96 dB at 0.72813 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -7.8 dB at 42.97 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -7.9 dB at 2373.12, 2376.87 MHz
15.203	Antenna Requirement	Pass	No antenna connector is used.

Notes:

1. If the Frequency Hopping System operating in 2400-2483.5 MHz band and the output power less than 125 mW. The hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of the 20 dB bandwidth of hopping channel whichever is greater.
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)
Conducted Out of Band Emissions	9 kHz ~ 40 GHz	2.5 dB
AC Power Conducted Emissions	150 kHz ~ 30 MHz	1.9 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	3.1 dB
	30 MHz ~ 1 GHz	5.4 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 18 GHz	5.0 dB
	18 GHz ~ 40 GHz	5.3 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description

Product	Bluetooth speaker
Brand	ULTIMATE EARS
Test Model	SR0192
FW Version	PB2
Status of EUT	Engineering sample
Power Supply Rating	DC 3.8V from battery or DC 5V from USB interface
Modulation Type	GFSK, π/4-DQPSK, 8DPSK
Modulation Technology	FHSS
Transfer Rate	Up to 3 Mbps
Operating Frequency	2402 ~ 2480 MHz
Number of Channel	79
Output Power	6.339 mW (8.02 dBm)

Note:

1. The EUT may have a lot of colors for marketing requirement.
2. The EUT uses following accessories.

Cable	Shielded	Length (m)	Core	Quantity
USB to Micro USB Cable	Y	0.6	0	1

3. The EUT must be supplied with a battery as the following table:

No.	Brand	Model	Specification
1	HIGHPOWER Technology	533-000139 or 944643	3.8Vdc, 2100mAh, 7.98Wh

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Brand	Model	Antenna Gain (dBi)	Frequency range (GHz)	Antenna Type	Connector Type
Logitech	SR0192	0.9	2.4~2.4835	Printed antenna	None

*The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

3.3 Channel List

79 channels are provided for BT-EDR:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. EUT can be used in the following ways: XYZ 3-axis. Pre-scan in these ways and find the worst case as a representative test condition. 2. For Unwanted Emission below 1 GHz has Battery / AC Adapter mode of power supply. Pre-scan these modes and find the worst case as a representative test condition. 3. For AC Power Conducted Emission items: Laptop / AC Adapter mode of power supply. Pre-scan these modes and find the worst case as a representative test condition.
Worst Case:	1. X/ Y/ Z Worst Condition: Y Axis for Unwanted Emission above 1GHz and Unwanted Emission below 1GHz. 2. For Unwanted Emission the AC Adapter mode is the worst case of power supply. 3. For AC Power Conducted Emission the AC Adapter mode is the worst case of power supply. 4. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below:

Test Item	Mode	Tested Channel	Modulation	Data Rate Parameter
AC Power Conducted Emissions	BT BR	0	GFSK	DH5
Unwanted Emissions below 1 GHz	BT BR	0	GFSK	DH5
Unwanted Emissions above 1 GHz	BT BR	0, 39, 78	GFSK	DH5
	BT EDR	0, 39, 78	8DPSK	3DH5
RF Output Power	BT BR	0, 39, 78	GFSK	DH5
	BT EDR	0, 39, 78	8DPSK	3DH5
Hopping Channel Separation / 20 dB Bandwidth	BT BR	0, 39, 78	GFSK	DH5
	BT EDR	0, 39, 78	8DPSK	3DH5
Number of Hopping Frequency Used / Conducted Out of Band Emissions	BT BR	0, 39, 78	GFSK	DH5
	BT EDR	0, 39, 78	8DPSK	3DH5
Dwell Time on Each Channel	BT BR	0, 39, 78	GFSK	DH5
	BT EDR	0, 39, 78	8DPSK	3DH5

3.5 Duty Cycle of Test Signal

GFSK: Duty cycle = 3.5 ms / 100 ms x 100% = 3.5%
8DPSK: Duty cycle = 3.6 ms / 100 ms x 100% = 3.6%



GFSK



8DPSK

3.6 Test Program Used and Operation Descriptions

Controlling software (eaglecomV0765 + WCN_Combo_Tool) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Adapter	Samsung	EP-TA20JBS	N/A	N/A	Provided by Lab

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	USB to Micro USB Cable	1	0.6	Yes	0	Supplied by applicant

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
AC Power Source GOOD WILL	6905S	1991551	N/A	N/A
Attenuator WOKEN	MDCS18N-10	MDCS18N-10-01	2022/4/5	2023/4/4
DC POWER SUPPLY Topward	6603D	795558	N/A	N/A
Power Meter Anritsu	ML2495A	1529002	2021/6/21	2022/6/20
Pulse Power Sensor Anritsu	MA2411B	1339443	2021/5/31	2022/5/30
Software	ADT_RF Test Software V6.6.5.4	N/A	N/A	N/A
Spectrum Analyzer R&S	FSV40	100964	2021/5/31	2022/5/30
Temperature & Humidity Chamber Giant Force	GTH-150-40-SP-AR	MAA0812-008	2022/1/14	2023/1/13
True RMS Clamp Meter Fluke	325	31130711WS	2021/6/2	2022/6/1

Notes:

1. The test was performed in Oven room 2.
2. Tested Date: 2022/4/18

4.2 Number of Hopping Frequency Used

Refer to section 4.1 to get information of the instruments.

4.3 Dwell Time on Each Channel

Refer to section 4.1 to get information of the instruments.

4.4 Hopping Channel Separation

Refer to section 4.1 to get information of the instruments.

4.5 20 dB Bandwidth

Refer to section 4.1 to get information of the instruments.

4.6 Conducted Out of Band Emissions

Refer to section 4.1 to get information of the instruments.

4.7 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohms Terminator	50	3	2021/10/27	2022/10/26
Fixed attenuator STI	STI02-2200-10	005	2021/8/27	2022/8/26
LISN R&S	ESH3-Z5	848773/004	2021/10/29	2022/10/28
RF Coaxial Cable JYEBO	5D-FB	COCCAB-001	2021/9/25	2022/9/24
Software BVADT	BVADT_Cond_V7.3.7.4	N/A	N/A	N/A
TEST RECEIVER R&S	ESCS 30	847124/029	2021/10/13	2022/10/12

Notes:

1. The test was performed in Conduction 1
2. Tested Date: 2022/4/17

4.8 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	N/A	N/A
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-3-01	2021/9/23	2022/9/22
Loop Antenna TESEQ	HLA 6121	45745	2021/7/21	2022/7/20
MXE EMI Receiver(20 Hz to 44 GHz) Keysight	N9038A	MY54450088	2021/7/6	2022/7/5
Pre_Amplifier EMCI	EMC001340	980142	2021/5/24	2022/5/23
Pre_Amplifier Mini-Circuits	ZFL-1000VH2	QA0838008	2021/10/19	2022/10/18
RF Coaxial Cable JYEBO	5D-FB	LOOPCAB-001	2022/1/6	2023/1/5
		LOOPCAB-002	2022/1/6	2023/1/5
RF Coaxial Cable COMMATE/PEWC	8D	001	2022/2/26	2023/2/25
		966-3-2	2022/2/26	2023/2/25
		966-3-3	2022/2/26	2023/2/25
Software	ADT_Radiated_V8.7.08	N/A	N/A	N/A
Spectrum Analyzer KEYSIGHT	N9030B	MY57142938	2021/4/26	2022/4/25
Trilog Broadband Antenna Schwarzbeck	VULB 9168	9168-361	2021/10/26	2022/10/25

Notes:

1. The test was performed in 966 Chamber No. 3.
2. Tested Date: 2022/4/17

4.9 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	N/A	N/A
Fix tool for Boresight antenna tower BV	FBA-01	FBA_SIP01	N/A	N/A
Horn Antenna Schwarzbeck	BBHA9120-D	9120D-406	2021/11/14	2022/11/13
	BBHA 9170	9170-739	2021/11/14	2022/11/13
MXE EMI Receiver(20 Hz to 44 GHz) Keysight	N9038A	MY54450088	2021/7/6	2022/7/5
Pre_Amplifier EMCI	EMC12630SE	980384	2022/1/10	2023/1/9
	EMC184045SE	980387	2022/1/10	2023/1/9
RF Cable EMCI	EMC104-SM-SM-6000	210201	2021/5/13	2022/5/12
RF Cable-Frequency range: 1-40GHz EMCI	EMC102-KM-KM-1200	160924	2022/1/10	2023/1/9
RF Coaxial Cable EMCI	EMC104-SM-SM-1500	180504	2021/4/26	2022/4/25
	EMC104-SM-SM-2000	180601	2021/6/8	2022/6/7
	EMC-KM-KM-4000	200214	2022/3/8	2023/3/7
Software	ADT_Radiated_V8.7.08	N/A	N/A	N/A
Spectrum Analyzer KEYSIGHT	N9030B	MY57142938	2021/4/26	2022/4/25
Spectrum Analyzer Keysight	N9030A	MY54490679	2021/7/9	2022/7/8

Notes:

1. The test was performed in 966 Chamber No. 3.
2. Tested Date: 2022/4/17 ~ 2022/4/19

5 Limits of Test Items

5.1 RF Output Power

The Maximum Output Power Measurement is 125 mW (21 dBm).

5.2 Number of Hopping Frequency Used

At least 15 channels frequencies, and should be equally spaced.

5.3 Dwell Time on Each Channel

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

5.4 Hopping Channel Separation

At least 25 kHz or two-third of 20 dB hopping channel bandwidth (whichever is greater).

5.5 20 dB Bandwidth

Maximum bandwidth is not specified.

5.6 Conducted Out of Band Emissions

Below 20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

5.7 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.8 Unwanted Emissions below 1 GHz

Radiated emissions up to 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.9 Unwanted Emissions above 1 GHz

Radiated emissions above 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

6 Test Arrangements

6.1 RF Output Power

6.1.1 Test Setup



6.1.2 Test Procedure

Peak Power:
A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average Power:
Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

6.2 Number of Hopping Frequency Used

6.2.1 Test Setup



6.2.2 Test Procedure

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
d. Set the SA on View mode and then plot the result on SA screen.
e. Repeat above procedures until all frequencies measured were complete.

6.3 Dwell Time on Each Channel

6.3.1 Test Setup



6.3.2 Test Procedure

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
e. Repeat above procedures until all different time-slot modes have been completed.

6.4 Hopping Channel Separation

6.4.1 Test Setup



6.4.2 Test Procedure

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
c. By using the MaxHold function record the separation of two adjacent channels.
d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
e. Repeat above procedures until all frequencies measured were complete.

6.5 20 dB Bandwidth

6.5.1 Test Setup



6.5.2 Test Procedure

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
c. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
d. Repeat above procedures until all frequencies measured were complete.

6.6 Conducted Out of Band Emissions

6.6.1 Test Setup



6.6.2 Test Procedure

MEASUREMENT PROCEDURE REF

a. Set the RBW = 100 kHz.
b. Set the VBW ≥ 300 kHz.
c. Detector = peak.
d. Sweep time = auto couple.
e. Trace mode = max hold.
f. Allow trace to fully stabilize.
g. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

a. Set RBW = 100 kHz.
b. Set VBW ≥ 300 kHz.
c. Detector = peak.
d. Sweep = auto couple.
e. Trace Mode = max hold.
f. Allow trace to fully stabilize.
g. Use the peak marker function to determine the maximum amplitude level.

6.7 AC Power Conducted Emissions

6.7.1 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.2 Test Procedure

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note:
The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.

6.8 Unwanted Emissions below 1 GHz

6.8.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



6.8.2 Test Procedure

For Radiated emission below 30 MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

6.9 Unwanted Emissions above 1 GHz

6.9.1 Test Setup

For Radiated emission above 1 GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.9.2 Test Procedure

a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

1. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
2. According to ANSI C63.10 section 6.6.4 and 4.1.4.2.2. For fundamental and harmonic signal measurement, according to ANSI C63.10 section 7.5, the average value = peak value + duty cycle correction factor. For duty cycle correction factor values, see the Test Signal Duty Cycle section in this report.
3. All modes of operation were investigated and the worst-case emissions are reported.

7 Test Results of Test Item

7.1 RF Output Power

Input Power:	3.8 Vdc	Environmental Conditions:	24°C, 66% RH	Tested By:	Eric Peng

For Peak Power

GFSK

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
0	2402	6.339	8.02	21	Pass
39	2441	6.152	7.89	21	Pass
78	2480	5.754	7.60	21	Pass

Note: The antenna gain is 0.9 dBi < 6 dBi, so the output power limit shall not be reduced.

8DPSK

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
0	2402	5.715	7.57	21	Pass
39	2441	5.521	7.42	21	Pass
78	2480	5.07	7.05	21	Pass

Note: The antenna gain is 0.9 dBi < 6 dBi, so the output power limit shall not be reduced.

For Average Power

GFSK

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	6.166	7.90
39	2441	5.998	7.78
78	2480	5.572	7.46

8DPSK

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	3.221	5.08
39	2441	3.076	4.88
78	2480	2.773	4.43

7.2 Number of Hopping Frequency Used

Input Power:	3.8 Vdc	Environmental Conditions:	24°C, 66% RH	Tested By:	Eric Peng

GFSK





Note: There are 79 hopping frequencies in the hopping mode. On the plots, it shows that the hopping frequencies are equally spaced.

8DPSK





Note: There are 79 hopping frequencies in the hopping mode. On the plots, it shows that the hopping frequencies are equally spaced.

7.3 Dwell Time on Each Channel

Input Power:	3.8 Vdc	Environmental Conditions:	24°C, 66% RH	Tested By:	Eric Peng

GFSK

Mode	Number of transmission in 31.6 sec	Length of transmission time (msec)	Result (msec)	Limit (msec)	Test Result
DH1	51 (times / 5 sec) * 6.32 = 323 times	0.402	129.85	400	Pass
DH3	27 (times / 5 sec) * 6.32 = 171 times	1.66	283.86	400	Pass
DH5	17 (times / 5 sec) * 6.32 = 108 times	2.968	320.54	400	Pass

Spectrum plots of Dwell Time



GFSK DH1



GFSK DH1



GFSK DH3



GFSK DH3



GFSK DH5



GFSK DH5

8DPSK

Mode	Number of transmission in 31.6 sec	Length of transmission time (msec)	Result (msec)	Limit (msec)	Test Result
3DH1	50 (times / 5 sec) * 6.32 = 316 times	0.42	132.72	400	Pass
3DH3	25 (times / 5 sec) * 6.32 = 158 times	1.665	263.07	400	Pass
3DH5	18 (times / 5 sec) * 6.32 = 114 times	2.96	337.44	400	Pass

Spectrum plots of Dwell Time



8DPSK 3DH1



8DPSK 3DH1



8DPSK 3DH3



8DPSK 3DH3



8DPSK 3DH5



8DPSK 3DH5

7.4 Hopping Channel Separation

Input Power:	3.8 Vdc	Environmental Conditions:	24°C, 66% RH	Tested By:	Eric Peng

GFSK

Channel	Frequency (MHz)	Hopping Channel Separation (MHz)	Minimum Limit (MHz)	Test Result
0	2402	1	0.64	Pass
39	2441	1	0.64	Pass
78	2480	1	0.64	Pass

Note: The minimum limit is two-third 20dB bandwidth.

8DPSK

Channel	Frequency (MHz)	Hopping Channel Separation (MHz)	Minimum Limit (MHz)	Test Result
0	2402	1	0.86	Pass
39	2441	1	0.86	Pass
78	2480	1	0.87	Pass

Note: The minimum limit is two-third 20dB bandwidth.

Spectrum Plot of Minimum Value



GFSK : CH 0



8DPSK : CH 0

7.5 20 dB Bandwidth

Input Power:	3.8 Vdc	Environmental Conditions:	24°C, 66% RH	Tested By:	Eric Peng

GFSK

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
0	2402	0.96
39	2441	0.95
78	2480	0.96

8DPSK

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
0	2402	1.28
39	2441	1.29
78	2480	1.3

Spectrum Plot of Maximum Value



GFSK : CH 0



8DPSK : CH 78

7.6 Conducted Out of Band Emissions

Input Power:	3.8 Vdc	Environmental Conditions:	24°C, 66% RH	Tested By:	Eric Peng

GFSK



Hopping disabled (Low Channel)



Hopping disabled (Low Channel)



Hopping disabled (High Channel)



Hopping disabled (High Channel)



Hopping enabled (Low Channel)



Hopping enabled (Low Channel)



Hopping enabled (High Channel)



Hopping enabled (High Channel)

8DPSK



Hopping disabled (Low Channel)



Hopping disabled (Low Channel)



Hopping disabled (High Channel)



Hopping disabled (High Channel)



Hopping enabled (Low Channel)



Hopping enabled (Low Channel)



Hopping enabled (High Channel)



Hopping enabled (High Channel)

7.7 AC Power Conducted Emissions

RF Mode	TX BT_GFSK	**Channel**	CH 0：2402 MHz
Frequency Range	150 kHz ~ 30 MHz	**Detector Function & Resolution Bandwidth**	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power (System)	120Vac, 60Hz	**Environmental Conditions**	25°C, 75% RH
Tested By	Ryan Du		

Phase Of Power : Line (L)										
No	**Frequency (MHz)**	**Correction Factor (dB)**	**Reading Value (dBuV)**		**Emission Level (dBuV)**		**Limit (dBuV)**		**Margin (dB)**	
			Q.P.	**AV.**	**Q.P.**	**AV.**	**Q.P.**	**AV.**	**Q.P.**	**AV.**
1	0.15000	10.07	28.52	3.77	38.59	13.84	66.00	56.00	-27.41	-42.16
2	**0.72813**	**10.13**	**20.91**	**6.43**	**31.04**	**16.56**	**56.00**	**46.00**	**-24.96**	**-29.44**
3	1.03906	10.15	14.01	0.21	24.16	10.36	56.00	46.00	-31.84	-35.64
4	1.49219	10.18	13.87	0.07	24.05	10.25	56.00	46.00	-31.95	-35.75
5	1.83594	10.20	12.96	-0.75	23.16	9.45	56.00	46.00	-32.84	-36.55
6	2.25000	10.23	13.12	-1.43	23.35	8.80	56.00	46.00	-32.65	-37.20

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



RF Mode	TX BT_GFSK	**Channel**	CH 0：2402 MHz
Frequency Range	150 kHz ~ 30 MHz	**Detector Function & Resolution Bandwidth**	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power (System)	120Vac, 60Hz	**Environmental Conditions**	25°C, 75% RH
Tested By	Ryan Du		

Phase Of Power : Neutral (N)										
No	**Frequency (MHz)**	**Correction Factor (dB)**	**Reading Value (dBuV)**		**Emission Level (dBuV)**		**Limit (dBuV)**		**Margin (dB)**	
			Q.P.	**AV.**	**Q.P.**	**AV.**	**Q.P.**	**AV.**	**Q.P.**	**AV.**
1	0.15391	10.05	27.24	2.20	37.29	12.25	65.79	55.79	-28.50	-43.54
2	0.31406	10.09	16.85	-6.33	26.94	3.76	59.86	49.86	-32.92	-46.10
3	0.63047	10.11	9.83	-5.01	19.94	5.10	56.00	46.00	-36.06	-40.90
4	0.98984	10.14	4.68	-7.15	14.82	2.99	56.00	46.00	-41.18	-43.01
5	4.64844	10.37	6.15	-0.85	16.52	9.52	56.00	46.00	-39.48	-36.48
6	8.15234	10.57	5.96	-7.13	16.53	3.44	60.00	50.00	-43.47	-46.56

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



7.8 Unwanted Emissions below 1 GHz

RF Mode	TX BT_GFSK	**Channel**	CH 0：2402 MHz
Frequency Range	9 kHz ~ 1 GHz	**Detector Function & Bandwidth**	(QP) RB = 120kHz
Input Power (System)	120Vac, 60Hz	**Environmental Conditions**	20°C, 70% RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	34.42	26.1 QP	40.0	-13.9	1.00 H	89	35.4	-9.3
2	63.11	16.5 QP	40.0	-23.5	1.00 H	354	25.9	-9.4
3	148.41	28.3 QP	43.5	-15.2	1.00 H	47	36.4	-8.1
4	223.07	22.9 QP	46.0	-23.1	1.00 H	287	34.3	-11.4
5	321.11	22.2 QP	46.0	-23.8	1.00 H	342	29.0	-6.8
6	447.81	24.1 QP	46.0	-21.9	1.00 H	149	27.9	-3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The emission levels were very low against the limit of frequency range 9 kHz ~ 30 MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



RF Mode	TX BT_GFSK	**Channel**	CH 0：2402 MHz
Frequency Range	9 kHz ~ 1 GHz	**Detector Function & Bandwidth**	(QP) RB = 120kHz
Input Power (System)	120Vac, 60Hz	**Environmental Conditions**	20°C, 70% RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	**42.97**	**32.2 QP**	**40.0**	**-7.8**	**1.00 V**	**85**	**40.5**	**-8.3**
2	74.57	25.8 QP	40.0	-14.2	1.00 V	58	37.2	-11.4
3	128.07	26.2 QP	43.5	-17.3	1.00 V	287	35.5	-9.3
4	246.15	18.9 QP	46.0	-27.1	1.00 V	78	28.6	-9.7
5	379.52	21.4 QP	46.0	-24.6	1.00 V	215	27.3	-5.9
6	537.20	24.6 QP	46.0	-21.4	1.00 V	79	26.8	-2.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The emission levels were very low against the limit of frequency range 9 kHz ~ 30 MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



7.9 Unwanted Emissions above 1 GHz

RF Mode	TX BT_GFSK	**Channel**	CH 0：2402 MHz
Frequency Range	1 GHz ~ 25 GHz	**Detector Function & Bandwidth**	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power (System)	120Vac, 60Hz	**Environmental Conditions**	19°C, 71% RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	2383.12	54.9 PK	74.0	-19.1	1.30 H	244	55.9	-1.0
2	2383.12	45.8 AV	54.0	-8.2	1.30 H	244	46.8	-1.0
3	*2402.00	101.3 PK			1.30 H	244	102.4	-1.1
4	*2402.00	72.2 AV			1.30 H	244	73.3	-1.1
5	4804.00	44.6 PK	74.0	-29.4	2.13 H	339	40.9	3.7
6	4804.00	15.5 AV	54.0	-38.5	2.13 H	339	11.8	3.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(3.5 ms / 100 ms) = -29.1 dB



RF Mode	TX BT_GFSK	Channel	CH 0：2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	19°C, 71% RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2386.74	56.0 PK	74.0	-18.0	1.75 V	49	57.0	-1.0
2	2386.74	45.9 AV	54.0	-8.1	1.75 V	49	46.9	-1.0
3	*2402.00	99.4 PK			1.75 V	49	100.5	-1.1
4	*2402.00	70.3 AV			1.75 V	49	71.4	-1.1
5	4804.00	43.9 PK	74.0	-30.1	2.15 V	285	40.2	3.7
6	4804.00	14.8 AV	54.0	-39.2	2.15 V	285	11.1	3.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(3.5 ms / 100 ms) = -29.1 dB



RF Mode	TX BT_GFSK	**Channel**	CH 39：2441 MHz
Frequency Range	1 GHz ~ 25 GHz	**Detector Function & Bandwidth**	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power (System)	120Vac, 60Hz	**Environmental Conditions**	19°C, 71% RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	*2441.00	100.8 PK			1.38 H	243	102.0	-1.2
2	*2441.00	71.7 AV			1.38 H	243	72.9	-1.2
3	4882.00	45.0 PK	74.0	-29.0	2.03 H	316	41.4	3.6
4	4882.00	15.9 AV	54.0	-38.1	2.03 H	316	12.3	3.6
5	7323.00	45.5 PK	74.0	-28.5	1.64 H	254	35.8	9.7
6	7323.00	16.4 AV	54.0	-37.6	1.64 H	254	6.7	9.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(3.5 ms / 100 ms) = -29.1 dB



RF Mode	TX BT_GFSK	**Channel**	CH 39：2441 MHz
Frequency Range	1 GHz ~ 25 GHz	**Detector Function & Bandwidth**	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power (System)	120Vac, 60Hz	**Environmental Conditions**	19°C, 71% RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	*2441.00	98.4 PK			1.49 V	42	99.6	-1.2
2	*2441.00	69.3 AV			1.49 V	42	70.5	-1.2
3	4882.00	44.3 PK	74.0	-29.7	2.14 V	297	40.7	3.6
4	4882.00	15.2 AV	54.0	-38.8	2.14 V	297	11.6	3.6
5	7323.00	44.6 PK	74.0	-29.4	1.87 V	180	34.9	9.7
6	7323.00	15.5 AV	54.0	-38.5	1.87 V	180	5.8	9.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(3.5 ms / 100 ms) = -29.1 dB



RF Mode	TX BT_GFSK	Channel	CH 78：2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	19°C, 71% RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	100.2 PK			1.42 H	241	101.4	-1.2
2	*2480.00	71.1 AV			1.42 H	241	72.3	-1.2
3	2484.61	54.7 PK	74.0	-19.3	1.42 H	241	56.0	-1.3
4	2484.61	45.6 AV	54.0	-8.4	1.42 H	241	46.9	-1.3
5	4960.00	44.9 PK	74.0	-29.1	2.09 H	329	41.2	3.7
6	4960.00	15.8 AV	54.0	-38.2	2.09 H	329	12.1	3.7
7	7440.00	45.4 PK	74.0	-28.6	1.67 H	261	35.2	10.2
8	7440.00	16.3 AV	54.0	-37.7	1.67 H	261	6.1	10.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(3.5 ms / 100 ms) = -29.1 dB



RF Mode	TX BT_GFSK	Channel	CH 78：2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	19°C, 71% RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	97.9 PK			1.28 V	45	99.1	-1.2
2	*2480.00	68.8 AV			1.28 V	45	70.0	-1.2
3	2486.10	54.9 PK	74.0	-19.1	1.28 V	45	56.2	-1.3
4	2486.10	45.4 AV	54.0	-8.6	1.28 V	45	46.7	-1.3
5	4960.00	44.4 PK	74.0	-29.6	2.12 V	304	40.7	3.7
6	4960.00	15.3 AV	54.0	-38.7	2.12 V	304	11.6	3.7
7	7440.00	45.2 PK	74.0	-28.8	1.92 V	186	35.0	10.2
8	7440.00	16.1 AV	54.0	-37.9	1.92 V	186	5.9	10.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(3.5 ms / 100 ms) = -29.1 dB



RF Mode	TX BT_8DPSK	Channel	CH 0：2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	19°C, 71% RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2376.87	55.4 PK	74.0	-18.6	2.30 H	237	56.4	-1.0
2	**2376.87**	**46.1 AV**	**54.0**	**-7.9**	**2.30 H**	**237**	**47.1**	**-1.0**
3	*2402.00	99.2 PK			2.30 H	237	100.3	-1.1
4	*2402.00	70.3 AV			2.30 H	237	71.4	-1.1
5	4804.00	45.1 PK	74.0	-28.9	2.16 H	354	41.4	3.7
6	4804.00	16.2 AV	54.0	-37.8	2.16 H	354	12.5	3.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(3.6 ms / 100 ms) = -28.9 dB



RF Mode	TX BT_8DPSK	Channel	CH 0：2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	19°C, 71% RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2373.12	56.2 PK	74.0	-17.8	1.75 V	50	57.2	-1.0
2	**2373.12**	**46.1 AV**	**54.0**	**-7.9**	**1.75 V**	**50**	**47.1**	**-1.0**
3	*2402.00	97.9 PK			1.75 V	50	99.0	-1.1
4	*2402.00	69.0 AV			1.75 V	50	70.1	-1.1
5	4804.00	44.3 PK	74.0	-29.7	2.12 V	296	40.6	3.7
6	4804.00	15.4 AV	54.0	-38.6	2.12 V	296	11.7	3.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(3.6 ms / 100 ms) = -28.9 dB



RF Mode	TX BT_8DPSK	Channel	CH 39：2441 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	19°C, 71% RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	98.3 PK			1.39 H	239	99.5	-1.2
2	*2441.00	69.4 AV			1.39 H	239	70.6	-1.2
3	4882.00	44.6 PK	74.0	-29.4	2.04 H	330	41.0	3.6
4	4882.00	15.7 AV	54.0	-38.3	2.04 H	330	12.1	3.6
5	7323.00	45.4 PK	74.0	-28.6	1.69 H	277	35.7	9.7
6	7323.00	16.5 AV	54.0	-37.5	1.69 H	277	6.8	9.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(3.6 ms / 100 ms) = -28.9 dB



RF Mode	TX BT_8DPSK	Channel	CH 39：2441 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	19°C, 71% RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	97.1 PK			1.34 V	47	98.3	-1.2
2	*2441.00	68.2 AV			1.34 V	47	69.4	-1.2
3	4882.00	45.2 PK	74.0	-28.8	2.16 V	319	41.6	3.6
4	4882.00	16.3 AV	54.0	-37.7	2.16 V	319	12.7	3.6
5	7323.00	44.6 PK	74.0	-29.4	1.96 V	178	34.9	9.7
6	7323.00	15.7 AV	54.0	-38.3	1.96 V	178	6.0	9.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(3.6 ms / 100 ms) = -28.9 dB



RF Mode	TX BT_8DPSK	Channel	CH 78：2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	19°C, 71% RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	97.7 PK			1.42 H	238	98.9	-1.2
2	*2480.00	68.8 AV			1.42 H	238	70.0	-1.2
3	2487.60	54.8 PK	74.0	-19.2	1.42 H	238	56.1	-1.3
4	2487.60	45.6 AV	54.0	-8.4	1.42 H	238	46.9	-1.3
5	4960.00	45.3 PK	74.0	-28.7	2.07 H	321	41.6	3.7
6	4960.00	16.4 AV	54.0	-37.6	2.07 H	321	12.7	3.7
7	7440.00	45.2 PK	74.0	-28.8	1.68 H	249	35.0	10.2
8	7440.00	16.3 AV	54.0	-37.7	1.68 H	249	6.1	10.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(3.6 ms / 100 ms) = -28.9 dB



RF Mode	TX BT_8DPSK	Channel	CH 78：2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power (System)	120Vac, 60Hz	Environmental Conditions	19°C, 71% RH
Tested By	Ryan Du		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	96.3 PK			1.29 V	49	97.5	-1.2
2	*2480.00	67.4 AV			1.29 V	49	68.6	-1.2
3	2491.32	54.5 PK	74.0	-19.5	1.29 V	49	55.8	-1.3
4	2491.32	45.8 AV	54.0	-8.2	1.29 V	49	47.1	-1.3
5	4960.00	44.5 PK	74.0	-29.5	2.15 V	291	40.8	3.7
6	4960.00	15.6 AV	54.0	-38.4	2.15 V	291	11.9	3.7
7	7440.00	45.4 PK	74.0	-28.6	1.88 V	175	35.2	10.2
8	7440.00	16.5 AV	54.0	-37.5	1.88 V	175	6.3	10.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(3.6 ms / 100 ms) = -28.9 dB



Plot of Band Edge

BT_GFSK Channel 0	
Horizontal (Peak)	**Horizontal (Average)**
	
Vertical (Peak)	**Vertical (Average)**
	
BT_GFSK Channel 78	
Horizontal (Peak)	**Horizontal (Average)**
	
Vertical (Peak)	**Vertical (Average)**
	

BT_8DPSK Channel 0

Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)



BT_8DPSK Channel 78

Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)



8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab
Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@bureauveritas.com
Web Site: http://ee.bureauveritas.com.tw

The address and road map of all our labs can be found in our web site also.

--- END ---