FCC Test Report (BT-LE)

Report No.:	RF190527E06-1
FCC ID:	JNZYR0073
Test Model:	YR0073
Received Date:	May 28, 2019
Test Date:	June 01 to 03, 2019
Issued Date:	June 19, 2019
Applicant:	LOGITECH FAR EAST LTD.
Address:	#2 Creation Rd. 4, Science-Based Ind. Park Hsinchu Taiwan, R.O.C.
Issued By:	Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory
Lab Address:	E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan R.O.C.
Test Location:	E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan R.O.C.
FCC Registration / Designation Number:	723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record 4

1 Certificate of Conformity 5

2 Summary of Test Results 6

2.1 Measurement Uncertainty 6
2.2 Modification Record 6

3 General Information 7

3.1 General Description of EUT (BT-LE) 7
3.2 Description of Test Modes 8
3.2.1 Test Mode Applicability and Tested Channel Detail 9
3.3 Duty Cycle of Test Signal 11
3.4 Description of Support Units 12
3.4.1 Configuration of System under Test 13
3.5 General Description of Applied Standards 14

4 Test Types and Results 15

4.1 Radiated Emission and Bandedge Measurement 15
4.1.1 Limits of Radiated Emission and Bandedge Measurement 15
4.1.2 Test Instruments 16
4.1.3 Test Procedures 17
4.1.4 Deviation from Test Standard 18
4.1.5 Test Setup 18
4.1.6 EUT Operating Conditions 19
4.1.7 Test Results 20
4.2 Conducted Emission Measurement 28
4.2.1 Limits of Conducted Emission Measurement 28
4.2.2 Test Instruments 28
4.2.3 Test Procedures 29
4.2.4 Deviation from Test Standard 29
4.2.5 Test Setup 29
4.2.6 EUT Operating Conditions 29
4.2.7 Test Results 30
4.3 6dB Bandwidth Measurement 32
4.3.1 Limits of 6dB Bandwidth Measurement 32
4.3.2 Test Setup 32
4.3.3 Test Instruments 32
4.3.4 Test Procedure 32
4.3.5 Deviation from Test Standard 32
4.3.6 EUT Operating Conditions 32
4.3.7 Test Results 33
4.4 Conducted Output Power Measurement 35
4.4.1 Limits of Conducted Output Power Measurement 35
4.4.2 Test Setup 35
4.4.3 Test Instruments 35
4.4.4 Test Procedures 35
4.4.5 Deviation from Test Standard 35
4.4.6 EUT Operating Conditions 35
4.4.7 Test Results 36
4.5 Power Spectral Density Measurement 37
4.5.1 Limits of Power Spectral Density Measurement 37
4.5.2 Test Setup 37
4.5.3 Test Instruments 37
4.5.4 Test Procedure 37
4.5.5 Deviation from Test Standard 37
4.5.6 EUT Operating Condition 37

4.5.7 Test Results 38
4.6 Conducted Out of Band Emission Measurement 40
4.6.1 Limits of Conducted Out of Band Emission Measurement 40
4.6.2 Test Setup 40
4.6.3 Test Instruments 40
4.6.4 Test Procedure 40
4.6.5 Deviation from Test Standard 40
4.6.6 EUT Operating Condition 40
4.6.7 Test Results 40

5 Pictures of Test Arrangements 44

Appendix – Information of the Testing Laboratories 45

Release Control Record

Issue No.	Description	Date Issued
RF190527E06-1	Original release.	June 19, 2019

1 Certificate of Conformity

Product: Wireless Keyboard

Brand: logitech

Test Model: YR0073

Sample Status: ENGINEERING SAMPLE

Applicant: LOGITECH FAR EAST LTD.

Test Date: June 01 to 03, 2019

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : _____ , **Date:** June 19, 2019
Wendy Wu / Specialist

Approved by : _____ , **Date:** June 19, 2019
May Chen / Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -11.83dB at 0.15000MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -11.0dB at 7320.00MHz .
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

Note:
Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.8 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	4.8 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.0 dB
	6GHz ~ 18GHz	5.0 dB
	18GHz ~ 40GHz	5.3 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT (BT-LE)

Product	Wireless Keyboard
PMN	MX KEYS
Brand	logitech
Test Model	YR0073
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	3.7Vdc from battery or 5Vdc from USB interface
Modulation Type	GFSK
Modulation Technology	DTS
Transfer Rate	**BT 5.0:** Up to 2Mbps (*Note 1)
Operating Frequency	**BT 5.0:** 2402MHz ~ 2480MHz (*Note 1)
Number of Channel	**BT 5.0:** 40 (*Note 1)
Output Power	**BT 5.0 1M:** 2.46mW **BT 5.0 2M:** 2.438mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	NA
Data Cable Supplied	USB Type C cable x 1 (Shielded, 1.35m / Brand: logitech, P/N: DWS-502-001235)

Note:

1. BT 5.0 technique supports 1Mbps and 2Mbps data rates, both have been evaluated in this test report. Refer to "**section 3.2 Description of Test Modes**" for more detail specification.
2. The EUT may have a lot of colors for marketing requirement.
3. The EUT could be supplied with rechargeable battery as the following table:

Brand	Model No.	Spec.
Springpower Technology(Shenzhen) or Logitech	802085 or 533-000177	3.7V, 1500mAh, 5.55Wh

4. The antenna provided to the EUT, please refer to the following table:

Antenna Gain (dBi)	Frequency range(GHz)	Antenna Type	Connector Type
4.86	2.4~2.4835	Printed Antenna	None

5. For radiated emissions, the EUT was pre-tested under the following modes:

Test Mode	Description
Mode A	**Power from USB interface**
Mode B	Power from Battery
Note: From the above modes, the worst case was found in **Mode A**. Therefore only the test data of the mode was recorded in this report.	

6. For AC power conducted emissions, the EUT was pre-tested under the following modes:

Test Mode	Description
Mode A	Power from USB interface
Mode B	**Power from Laptop**
Note: From the above modes, the worst case was found in **Mode B**. Therefore only the test data of the mode was recorded in this report.	

7. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

BT-LE channels:

RF Channel	RF Center Frequency	Channel Index	Channels Type for BT 5.x		Channels Type for BT 4.x
			Maximum Data Rate 2Mbps	Maximum Data Rate 1Mbps	Maximum Data Rate 1Mbps
0	2402 MHz	37		●	●
1	2404 MHz	0	●		●
2	2406 MHz	1	●		●
3	2408 MHz	2	●		●
4	2410 MHz	3	●		●
5	2412 MHz	4	●		●
6	2414 MHz	5	●		●
7	2416 MHz	6	●		●
8	2418 MHz	7	●		●
9	2420 MHz	8	●		●
10	2422 MHz	9	●		●
11	2424 MHz	10	●		●
12	2426 MHz	38		●	●
13	2428 MHz	11	●		●
14	2430 MHz	12	●		●
15	2432 MHz	13	●		●
16	2434 MHz	14	●		●
17	2436 MHz	15	●		●
18	2438 MHz	16	●		●
19	2440 MHz	17	●		●
20	2442 MHz	18	●		●
21	2444 MHz	19	●		●
22	2446 MHz	20	●		●
23	2448 MHz	21	●		●
24	2450 MHz	22	●		●
25	2452 MHz	23	●		●
26	2454 MHz	24	●		●
27	2456 MHz	25	●		●
28	2458 MHz	26	●		●
29	2460 MHz	27	●		●
30	2462 MHz	28	●		●
31	2464 MHz	29	●		●
32	2466 MHz	30	●		●
33	2468 MHz	31	●		●
34	2470 MHz	32	●		●
35	2472 MHz	33	●		●
36	2474 MHz	34	●		●
37	2476 MHz	35	●		●
38	2478 MHz	36	●		●
39	2480 MHz	39		●	●

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE≥1G:** Radiated Emission above 1GHz & Bandedge Measurement **RE<1G:** Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

Radiated Emission Test (Above 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	0, 19, 39	GFSK	1
1 to 38	1, 19, 38	GFSK	2

Radiated Emission Test (Below 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	0	GFSK	1

Power Line Conducted Emission Test:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	0	GFSK	1

Antenna Port Conducted Measurement:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	0, 19, 39	GFSK	1
1 to 38	1, 19, 38	GFSK	2

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
RE≥1G	21deg. C, 65%RH	120Vac, 60Hz	Robert Cheng
RE<1G	22deg. C, 63%RH	120Vac, 60Hz	Robert Cheng
PLC	24deg. C, 75%RH	120Vac, 60Hz	Andy Ho
APCM	25deg. C, 67%RH	120Vac, 60Hz	Jyunchun Lin

3.3 Duty Cycle of Test Signal

BT 5.0 1M

Duty cycle = 0.344 ms/7.056 ms = 0.049



Note: This is highest operational duty cycle.

BT 5.0 2M

Duty cycle = 0.169 ms/7.056 ms = 0.024



Note: This is highest operational duty cycle.

3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	USB Adapter	ASUS	AD876320	NA	NA	Provided by Lab
B.	Laptop	DELL	Inspiron 7570	DW3CSJ2	NA	Provided by Lab

Note:

1. All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	USB type C Cable	1	1.35	Yes	0	Supplied by client

3.4.1 Configuration of System under Test

For conducted emissions test:



For other test:



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
KDB 558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver ESR7 R&S	ESR7	102026	Apr. 24, 2019	Apr. 23, 2020
Spectrum Analyzer Keysight	N9030B	MY57141948	May 25, 2019	May 24, 2020
Pre-Amplifier EMCI	EMC001340	980142	Jan. 25, 2019	Jan. 24, 2020
Loop Antenna Electro-Metrics	EM-6879	269	Sep. 07, 2018	Sep. 06, 2019
RF Cable	NA	LOOPCAB-001	Jan. 14, 2019	Jan. 13, 2020
RF Cable	NA	LOOPCAB-002	Jan. 14, 2019	Jan. 13, 2020
Pre-Amplifier EMCI	EMC330N	980538	Apr. 30, 2019	Apr. 29, 2020
Trilog Broadband Antenna SCHWARZBECK	VULB9168	9168-0842	Nov. 21, 2018	Nov. 20, 2019
RF Cable	8D	966-5-1	May 03, 2019	May 02, 2020
RF Cable	8D	966-5-2	May 03, 2019	May 02, 2020
RF Cable	8D	966-5-3	May 03, 2019	May 02, 2020
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-ATT5-02	Jan. 28, 2019	Jan. 27, 2020
Horn_Antenna SCHWARZBECK	BBHA 9120D	9120D-1819	Nov. 25, 2018	Nov. 24, 2019
Pre-Amplifier EMCI	EMC12630SE	980509	May 03, 2019	May 02, 2020
RF Cable EMCI	EMC104-SM-SM-1500	180503	May 03, 2019	May 02, 2020
RF Cable EMCI	EMC104-SM-SM-2000	180501	May 03, 2019	May 02, 2020
RF Cable EMCI	EMC104-SM-SM-6000	180505	May 03, 2019	May 02, 2020
Pre-Amplifier EMCI	EMC184045SE	980387	Jan. 28, 2019	Jan. 27, 2020
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170519	Nov. 25, 2018	Nov. 24, 2019
RF Cable	EMC102-KM-KM-1200	160924	Jan. 28, 2019	Jan. 27, 2020
RF Cable	EMC102-KM-KM-1200	160925	Jan. 28, 2019	Jan. 27, 2020
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	NA	NA
Spectrum Analyzer R&S	FSV40	100964	June 20, 2018	June 19, 2019
Power meter Anritsu	ML2495A	1014008	May 13, 2019	May 12, 2020
Power sensor Anritsu	MA2411B	0917122	May 13, 2019	May 12, 2020

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 5.
3. Loop antenna was used for all emissions below 30 MHz.
4. Tested Date: June 01 to 02, 2019

4.1.3 Test Procedures

For Radiated emission below 30MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard

No deviation.

4.1.5 Test Setup

For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

a. Placed the EUT on the testing table.
b. Controlling software (RF Sample with Receiver [Number Lock]) has been activated to set the EUT under transmission condition continuously.
   - BLE1M TX Modulated high duty 2402MHz
   - BLE1M TX Modulated high duty 2440MHz
   - BLE1M TX Modulated high duty 2480MHz
   - BLE2M TX Modulated high duty 2404MHz
   - BLE2M TX Modulated high duty 2440MHz
   - BLE2M TX Modulated high duty 2478MHz

4.1.7 Test Results

BT 5.0 1M

Above 1GHz Data:

CHANNEL	TX Channel 0	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	2390.00	54.2 PK	74.0	-19.8	1.13 H	48	57.4	-3.2
2	2390.00	42.8 AV	54.0	-11.2	1.13 H	48	46.0	-3.2
3	*2402.00	100.5 PK			1.13 H	48	103.7	-3.2
4	*2402.00	95.2 AV			1.13 H	48	98.4	-3.2
5	4804.00	45.2 PK	74.0	-28.8	1.00 H	355	44.4	0.8
6	4804.00	38.2 AV	54.0	-15.8	1.00 H	355	37.4	0.8
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	2390.00	53.1 PK	74.0	-20.9	2.85 V	106	56.3	-3.2
2	2390.00	39.4 AV	54.0	-14.6	2.85 V	106	42.6	-3.2
3	*2402.00	99.0 PK			2.85 V	106	102.2	-3.2
4	*2402.00	94.1 AV			2.85 V	106	97.3	-3.2
5	4804.00	44.0 PK	74.0	-30.0	2.59 V	234	43.2	0.8
6	4804.00	37.0 AV	54.0	-17.0	2.59 V	234	36.2	0.8

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	100.9 PK			1.22 H	59	104.0	-3.1
2	*2440.00	95.7 AV			1.22 H	59	98.8	-3.1
3	4880.00	45.2 PK	74.0	-28.8	1.00 H	355	44.5	0.7
4	4880.00	38.2 AV	54.0	-15.8	1.00 H	355	37.5	0.7
5	7320.00	47.8 PK	74.0	-26.2	1.15 H	29	41.1	6.7
6	7320.00	35.1 AV	54.0	-18.9	1.15 H	29	28.4	6.7
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	99.8 PK			2.78 V	92	102.9	-3.1
2	*2440.00	94.8 AV			2.78 V	92	97.9	-3.1
3	4880.00	45.0 PK	74.0	-29.0	2.58 V	225	44.3	0.7
4	4880.00	37.8 AV	54.0	-16.2	2.58 V	225	37.1	0.7
5	7320.00	52.0 PK	74.0	-22.0	1.08 V	189	45.3	6.7
6	7320.00	41.9 AV	54.0	-12.1	1.08 V	189	35.2	6.7

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	101.6 PK			1.22 H	59	104.7	-3.1
2	*2480.00	95.8 AV			1.22 H	59	98.9	-3.1
3	2483.50	62.8 PK	74.0	-11.2	1.22 H	59	65.9	-3.1
4	2483.50	37.8 AV	54.0	-16.2	1.22 H	59	40.9	-3.1
5	4960.00	45.2 PK	74.0	-28.8	1.00 H	355	44.2	1.0
6	4960.00	38.2 AV	54.0	-15.8	1.00 H	355	37.2	1.0
7	7440.00	47.8 PK	74.0	-26.2	1.15 H	29	40.8	7.0
8	7440.00	35.1 AV	54.0	-18.9	1.15 H	29	28.1	7.0
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	99.7 PK			2.83 V	97	102.8	-3.1
2	*2480.00	94.9 AV			2.83 V	97	98.0	-3.1
3	2483.50	61.6 PK	74.0	-12.4	2.83 V	97	64.7	-3.1
4	2483.50	37.1 AV	54.0	-16.9	2.83 V	97	40.2	-3.1
5	4960.00	44.7 PK	74.0	-29.3	2.54 V	239	43.7	1.0
6	4960.00	37.5 AV	54.0	-16.5	2.54 V	239	36.5	1.0
7	7440.00	51.6 PK	74.0	-22.4	1.05 V	200	44.6	7.0
8	7440.00	41.8 AV	54.0	-12.2	1.05 V	200	34.8	7.0

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

Below 1GHz Data:

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	44.62	21.6 QP	40.0	-18.4	1.22 H	98	34.7	-13.1
2	150.62	21.7 QP	43.5	-21.8	1.36 H	277	34.5	-12.8
3	236.95	30.1 QP	46.0	-15.9	1.49 H	268	44.5	-14.4
4	261.27	32.9 QP	46.0	-13.1	1.25 H	57	46.5	-13.6
5	317.22	30.1 QP	46.0	-15.9	1.96 H	37	41.8	-11.7
6	773.24	28.2 QP	46.0	-17.8	1.41 H	163	30.7	-2.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



CHANNEL	TX Channel 0	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	41.47	27.8 QP	40.0	-12.2	1.25 V	23	41.1	-13.3
2	63.22	24.1 QP	40.0	-15.9	1.33 V	39	38.1	-14.0
3	114.05	19.6 QP	43.5	-23.9	1.77 V	352	35.2	-15.6
4	259.62	24.9 QP	46.0	-21.1	1.41 V	198	38.6	-13.7
5	398.28	23.7 QP	46.0	-22.3	1.80 V	304	33.7	-10.0
6	821.11	28.6 QP	46.0	-17.4	1.00 V	241	30.8	-2.2

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



BT 5.0 2M

Above 1GHz Data:

CHANNEL	TX Channel 1	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	2390.00	54.3 PK	74.0	-19.7	1.27 H	72	57.5	-3.2
2	2390.00	41.9 AV	54.0	-12.1	1.27 H	72	45.1	-3.2
3	*2404.00	101.1 PK			1.27 H	72	104.3	-3.2
4	*2404.00	89.0 AV			1.27 H	72	92.2	-3.2
5	4808.00	46.0 PK	74.0	-28.0	1.00 H	340	45.2	0.8
6	4808.00	36.7 AV	54.0	-17.3	1.00 H	340	35.9	0.8
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	2390.00	52.9 PK	74.0	-21.1	2.86 V	83	56.1	-3.2
2	2390.00	39.4 AV	54.0	-14.6	2.86 V	83	42.6	-3.2
3	*2404.00	99.8 PK			2.86 V	83	103.0	-3.2
4	*2404.00	87.8 AV			2.86 V	83	91.0	-3.2
5	4808.00	44.0 PK	74.0	-30.0	2.52 V	259	43.2	0.8
6	4808.00	34.0 AV	54.0	-20.0	2.52 V	259	33.2	0.8

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	101.4 PK			1.27 H	97	104.5	-3.1
2	*2440.00	89.2 AV			1.27 H	97	92.3	-3.1
3	4880.00	45.9 PK	74.0	-28.1	1.00 H	330	45.2	0.7
4	4880.00	36.7 AV	54.0	-17.3	1.00 H	330	36.0	0.7
5	7320.00	48.5 PK	74.0	-25.5	1.12 H	42	41.8	6.7
6	7320.00	35.8 AV	54.0	-18.2	1.12 H	42	29.1	6.7
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	99.9 PK			2.82 V	112	103.0	-3.1
2	*2440.00	87.5 AV			2.82 V	112	90.6	-3.1
3	4880.00	43.8 PK	74.0	-30.2	2.54 V	251	43.1	0.7
4	4880.00	33.9 AV	54.0	-20.1	2.54 V	251	33.2	0.7
5	7320.00	54.8 PK	74.0	-19.2	1.12 V	223	48.1	6.7
6	**7320.00**	**43.0 AV**	**54.0**	**-11.0**	**1.12 V**	**223**	**36.3**	**6.7**

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 38	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2478.00	102.0 PK			1.24 H	81	105.1	-3.1
2	*2478.00	89.8 AV			1.24 H	81	92.9	-3.1
3	2483.50	59.8 PK	74.0	-14.2	1.24 H	81	62.9	-3.1
4	2483.50	37.5 AV	54.0	-16.5	1.24 H	81	40.6	-3.1
5	4956.00	45.5 PK	74.0	-28.5	1.00 H	342	44.5	1.0
6	4956.00	36.4 AV	54.0	-17.6	1.00 H	342	35.4	1.0
7	7434.00	47.9 PK	74.0	-26.1	1.12 H	42	40.8	7.1
8	7434.00	35.3 AV	54.0	-18.7	1.12 H	42	28.2	7.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2478.00	100.1 PK			2.87 V	85	103.2	-3.1
2	*2478.00	88.7 AV			2.87 V	85	91.8	-3.1
3	2483.50	58.4 PK	74.0	-15.6	2.87 V	85	61.5	-3.1
4	2483.50	37.0 AV	54.0	-17.0	2.87 V	85	40.1	-3.1
5	4956.00	44.1 PK	74.0	-29.9	2.55 V	246	43.1	1.0
6	4956.00	34.1 AV	54.0	-19.9	2.55 V	246	33.1	1.0
7	7434.00	54.1 PK	74.0	-19.9	1.08 V	216	47.0	7.1
8	7434.00	42.6 AV	54.0	-11.4	1.08 V	216	35.5	7.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1.The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 24, 2018	Oct. 23, 2019
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 22, 2018	Oct. 21, 2019
Line-Impedance Stabilization Network (for Peripheral) R&S	ESH3-Z5	835239/001	Mar. 17, 2019	Mar. 16, 2020
50 ohms Terminator	N/A	3	Oct. 22, 2018	Oct. 21, 2019
RF Cable	5D-FB	COCCAB-001	Sep. 28, 2018	Sep. 27, 2019
Fixed attenuator EMCI	STI02-2200-10	003	Mar. 14, 2019	Mar. 13, 2020
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
3 Tested Date: June 03, 2019

4.2.3 Test Procedures

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

a. Placed the EUT on the testing table.

b. Controlling software (RF Sample with Receiver [Number Lock]) has been activated to set the EUT under transmission condition continuously.

- ◆ BLE1M TX Modulated high duty 2402MHz

4.2.7 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.93	38.71	26.68	48.64	36.61	66.00	56.00	-17.36	-19.39
2	0.18125	9.94	34.13	23.24	44.07	33.18	64.43	54.43	-20.36	-21.25
3	0.25938	9.95	24.11	12.94	34.06	22.89	61.45	51.45	-27.39	-28.56
4	0.45859	9.96	29.06	23.68	39.02	33.64	56.72	46.72	-17.70	-13.08
5	16.90234	10.91	26.97	18.87	37.88	29.78	60.00	50.00	-22.12	-20.22
6	21.76563	11.18	26.64	18.84	37.82	30.02	60.00	50.00	-22.18	-19.98

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	**0.15000**	**9.93**	**44.24**	**28.65**	**54.17**	**38.58**	**66.00**	**56.00**	**-11.83**	**-17.42**
2	0.16172	9.93	39.65	27.16	49.58	37.09	65.38	55.38	-15.80	-18.29
3	0.26719	9.95	25.08	14.13	35.03	24.08	61.20	51.20	-26.17	-27.12
4	5.13281	10.20	15.13	3.45	25.33	13.65	60.00	50.00	-34.67	-36.35
5	15.42578	10.65	19.17	10.83	29.82	21.48	60.00	50.00	-30.18	-28.52
6	21.32813	10.89	27.07	18.51	37.96	29.40	60.00	50.00	-22.04	-20.60

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

a. Set resolution bandwidth (RBW) = 100kHz
b. Set the video bandwidth (VBW) ≥ 3 x RBW, Detector = Peak.
c. Trace mode = max hold.
d. Sweep = auto couple.
e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

- BLE1M TX Modulated high duty 2402MHz
- BLE1M TX Modulated high duty 2440MHz
- BLE1M TX Modulated high duty 2480MHz
- BLE2M TX Modulated high duty 2404MHz
- BLE2M TX Modulated high duty 2440MHz
- BLE2M TX Modulated high duty 2478MHz

4.3.7 Test Results

BT 5.0 1M

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	0.71	0.5	Pass
19	2440	0.70	0.5	Pass
39	2480	0.70	0.5	Pass

Spectrum Plot of Worst Value

CH 19



BT 5.0 2M

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2404	1.16	0.5	Pass
19	2440	1.17	0.5	Pass
38	2478	1.14	0.5	Pass

Spectrum Plot of Worst Value

CH 38



4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

- BLE1M TX Modulated high duty 2402MHz
- BLE1M TX Modulated high duty 2440MHz
- BLE1M TX Modulated high duty 2480MHz
- BLE2M TX Modulated high duty 2404MHz
- BLE2M TX Modulated high duty 2440MHz
- BLE2M TX Modulated high duty 2478MHz

4.4.7 Test Results

BT 5.0 1M

FOR PEAK POWER

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
0	2402	2.46	3.91	30	Pass
19	2440	2.404	3.81	30	Pass
39	2480	2.35	3.71	30	Pass

FOR AVERAGE POWER

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	2.443	3.88
19	2440	2.393	3.79
39	2480	2.339	3.69

BT 5.0 2M

FOR PEAK POWER

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
1	2404	2.438	3.87	30	Pass
19	2440	2.393	3.79	30	Pass
38	2478	2.328	3.67	30	Pass

FOR AVERAGE POWER

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
1	2404	2.421	3.84
19	2440	2.377	3.76
38	2478	2.317	3.65

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

a. Set analyzer center frequency to DTS channel center frequency.
b. Set the span to 1.5 times the DTS bandwidth.
c. Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
d. Set the VBW ≥ 3 × RBW.
e. Detector = peak.
f. Sweep time = auto couple.
g. Trace mode = max hold.
h. Allow trace to fully stabilize.
i. Use the peak marker function to determine the maximum amplitude level within the RBW.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

- BLE1M TX Modulated high duty 2402MHz
- BLE1M TX Modulated high duty 2440MHz
- BLE1M TX Modulated high duty 2480MHz
- BLE2M TX Modulated high duty 2404MHz
- BLE2M TX Modulated high duty 2440MHz
- BLE2M TX Modulated high duty 2478MHz

4.5.7 Test Results

BT 5.0 1M

Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	2402	1.12	8	Pass
19	2440	1.29	8	Pass
39	2480	1.31	8	Pass

Spectrum Plot of Worst Value

CH 39



BT 5.0 2M

Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
1	2404	-2.58	8	Pass
19	2440	-2.58	8	Pass
38	2478	-2.66	8	Pass

Spectrum Plot of Worst Value

CH 1



4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW ≥ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

1. Set RBW = 100 kHz.
2. Set VBW ≥ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest and highest channel frequencies individually.

- BLE1M TX Modulated high duty 2402MHz
- BLE1M TX Modulated high duty 2440MHz
- BLE1M TX Modulated high duty 2480MHz
- BLE2M TX Modulated high duty 2404MHz
- BLE2M TX Modulated high duty 2440MHz
- BLE2M TX Modulated high duty 2478MHz

4.6.7 Test Results

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

BT 5.0 1M

CH 0





CH 19





CH 39





CH 0 Band edge



CH 39 Band edge



BT 5.0 2M

CH 1





CH 19





CH 38





CH 1 Band edge



CH 38 Band edge



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab
Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---