TEST REPORT

CERTIFICATE OF CONFORMITY

Standard:	**47 CFR FCC Part 15, Subpart C (Section 15.247)**
Report No.:	RFBDKG-WTW-P23030757
FCC ID:	JNZYR0096
Product:	Wireless Keyboard
Brand:	Logitech , logi , logitech
Model No.:	YR0096
Received Date:	2023/3/28
Test Date:	2023/4/6 ~ 2023/4/13
Issued Date:	2023/5/3
Applicant:	Logitech Far East Ltd.
Address:	3930 North First Street, San Jose, California 95134
Issued By:	Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory
Lab Address:	E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan
Test Location:	E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan
FCC Registration / Designation Number:	723255 / TW2022

Approved by: _____ , **Date:** **2023/5/3**

May Chen / Manager

This test report consists of 66 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Vito Lung / Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record **4**

1 Certificate **5**

2 Summary of Test Results **6**

2.1 Measurement Uncertainty 6
2.2 Supplementary Information 6

3 General Information **7**

3.1 General Description 7
3.2 Antenna Description of EUT 8
3.3 Channel List 9
3.4 Test Mode Applicability and Tested Channel Detail 10
3.5 Duty Cycle of Test Signal 11
3.6 Test Program Used and Operation Descriptions 13
3.7 Connection Diagram of EUT and Peripheral Devices 13
3.8 Configuration of Peripheral Devices and Cable Connections 13

4 Test Instruments **14**

4.1 RF Output Power 14
4.2 Power Spectral Density 14
4.3 6 dB Bandwidth 14
4.4 Conducted Out of Band Emissions 14
4.5 Unwanted Emissions below 1 GHz 15
4.6 Unwanted Emissions above 1 GHz 16

5 Limits of Test Items **17**

5.1 RF Output Power 17
5.2 Power Spectral Density 17
5.3 6 dB Bandwidth 17
5.4 Conducted Out of Band Emissions 17
5.5 Unwanted Emissions below 1 GHz 17
5.6 Unwanted Emissions above 1 GHz 17

6 Test Arrangements **18**

6.1 RF Output Power 18
6.1.1 Test Setup 18
6.1.2 Test Procedure 18
6.2 Power Spectral Density 18
6.2.1 Test Setup 18
6.2.2 Test Procedure 18
6.3 6 dB Bandwidth 19
6.3.1 Test Setup 19
6.3.2 Test Procedure 19
6.4 Conducted Out of Band Emissions 19
6.4.1 Test Setup 19
6.4.2 Test Procedure 19
6.5 Unwanted Emissions below 1 GHz 20
6.5.1 Test Setup 20
6.5.2 Test Procedure 21
6.6 Unwanted Emissions above 1 GHz 22
6.6.1 Test Setup 22
6.6.2 Test Procedure 22

7 Test Results of Test Item **23**

7.1 RF Output Power 23
7.2 Power Spectral Density 25
7.3 6 dB Bandwidth 27
7.4 Conducted Out of Band Emissions 29
7.5 Unwanted Emissions below 1 GHz 33

7.6 Unwanted Emissions above 1 GHz 37
8 Pictures of Test Arrangements 65
9 Information of the Testing Laboratories 66

Release Control Record

Issue No.	Description	Date Issued
RFBDKG-WTW-P23030757	Original release.	2023/5/3

1 Certificate

Product:	Wireless Keyboard
Brand:	Logitech , logi , logitech
Test Model:	YR0096
Sample Status:	Engineering sample
Applicant:	Logitech Far East Ltd.
Test Date:	2023/4/6 ~ 2023/4/13
Standard:	47 CFR FCC Part 15, Subpart C (Section 15.247)
Measurement procedure:	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
Standard / Clause	Test Item	Result	Remark
15.247(b)	RF Output Power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.
15.247(d)	Conducted Out of Band Emissions	Pass	Meet the requirement of limit.
15.205 / 15.209 / 15.247(d)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -11.3 dB at 31.07 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -6.4 dB at 2390.00 MHz
15.203	Antenna Requirement	Pass	No antenna connector is used.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)
Conducted Out of Band Emissions	9 kHz ~ 40 GHz	2.5 dB
AC Power Conducted Emissions	150 kHz ~ 30 MHz	1.9 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	3.1 dB
	30 MHz ~ 1 GHz	5.4 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 18 GHz	5.1 dB
	18 GHz ~ 40 GHz	5.3 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description

Product	Wireless Keyboard
Brand	Logitech , logi , logitech
Test Model	YR0096
Status of EUT	Engineering sample
Power Supply Rating	3 Vdc from battery
Modulation Type	GFSK
Modulation Technology	DTS
Transfer Rate	Up to 2 Mbps (*Note 1)
Operating Frequency	2.402 GHz ~ 2.48 GHz (*Note 1)
Number of Channel	40 (*Note 1)
Output Power	**BT-LE function:** **BT-LE 1M:** 2.618 mW (4.18 dBm) **BT-LE 2M:** 2.612 mW (4.17 dBm) **Logi Bolt function:** **logi bolt-1M:** 2.606 mW (4.16 dBm) **logi bolt-2M:** 2.606 mW (4.16 dBm)

Note:

1. BT-LE technique supports 1Mbps and 2Mbps data rates, both have been evaluated in this test report. Refer to "**section 3.3 Channel List**" for more detail specification.
2. The EUT may have a lot of colors for marketing requirement.
3. This device has BT-LE and logi bolt functions. logi bolt is the same technology as BT-LE then enhancement secure protocol.
4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Antenna Gain (dBi)	Frequency range (GHz)	Antenna Type	Connector Type
2.77	2.4~2.4835	Printed monopole antenna	none

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

3.3 Channel List

BT-LE & logi bolt channels:

RF Channel	RF Center Frequency	Channel Index	Channels Type for BT 5.x		Channels Type for BT 4.x
			Maximum Data Rate 2Mbps	Maximum Data Rate 1Mbps	Maximum Data Rate 1Mbps
0	2402 MHz	37		●	●
1	2404 MHz	0	●		●
2	2406 MHz	1	●		●
3	2408 MHz	2	●		●
4	2410 MHz	3	●		●
5	2412 MHz	4	●		●
6	2414 MHz	5	●		●
7	2416 MHz	6	●		●
8	2418 MHz	7	●		●
9	2420 MHz	8	●		●
10	2422 MHz	9	●		●
11	2424 MHz	10	●		●
12	2426 MHz	38		●	●
13	2428 MHz	11	●		●
14	2430 MHz	12	●		●
15	2432 MHz	13	●		●
16	2434 MHz	14	●		●
17	2436 MHz	15	●		●
18	2438 MHz	16	●		●
19	2440 MHz	17	●		●
20	2442 MHz	18	●		●
21	2444 MHz	19	●		●
22	2446 MHz	20	●		●
23	2448 MHz	21	●		●
24	2450 MHz	22	●		●
25	2452 MHz	23	●		●
26	2454 MHz	24	●		●
27	2456 MHz	25	●		●
28	2458 MHz	26	●		●
29	2460 MHz	27	●		●
30	2462 MHz	28	●		●
31	2464 MHz	29	●		●
32	2466 MHz	30	●		●
33	2468 MHz	31	●		●
34	2470 MHz	32	●		●
35	2472 MHz	33	●		●
36	2474 MHz	34	●		●
37	2476 MHz	35	●		●
38	2478 MHz	36	●		●
39	2480 MHz	39		●	●

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below:

Test Item	Mode	Tested Channel	Modulation	Data Rate Parameter
RF Output Power / Power Spectral Density	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
	BT-LE 2M	1, 19, 38	GFSK	2Mb/s
	logi bolt-1M	0, 19, 39	GFSK	1Mb/s
	logi bolt-2M	1, 19, 38	GFSK	2Mb/s
6 dB Bandwidth / Conducted Out of Band Emissions	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
	BT-LE 2M	1, 19, 38	GFSK	2Mb/s
	logi bolt-1M	0, 19, 39	GFSK	1Mb/s
	logi bolt-2M	1, 19, 38	GFSK	2Mb/s
Unwanted Emissions below 1 GHz	BT-LE 1M	39	GFSK	1Mb/s
	logi bolt-1M	19	GFSK	1Mb/s
Unwanted Emissions above 1 GHz	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
	BT-LE 2M	1, 19, 38	GFSK	2Mb/s
	logi bolt-1M	0, 19, 39	GFSK	1Mb/s
	logi bolt-2M	1, 19, 38	GFSK	2Mb/s

3.5 Duty Cycle of Test Signal

BT-LE 1M: Duty cycle = 0.357 ms / 7.047 ms x 100% = 5.1%, duty factor = 10 * log (1/Duty cycle) = 12.95 dB
BT-LE 2M: Duty cycle = 0.187 ms / 7.047 ms x 100% = 2.7%, duty factor = 10 * log (1/Duty cycle) = 15.76 dB
Logi Bolt 1M: Duty cycle = 0.359 ms / 7.043 ms x 100% = 5.1%, duty factor = 10 * log (1/Duty cycle) = 12.93 dB
Logi Bolt 2M: Duty cycle = 0.187 ms / 7.053 ms x 100% = 2.7%, duty factor = 10 * log (1/Duty cycle) = 15.77 dB



BT-LE 1M



BT-LE 2M



Logi Bolt 1M



Logi Bolt 2M

3.6 Test Program Used and Operation Descriptions

Controlling software (RF Sample with Receiver [Number Lock]) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Battery*2	Duracell	AAA	N/A	N/A	Provided by Lab

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Power Meter Anritsu	ML2495A	1529002	2022/6/22	2023/6/21
Pulse Power Sensor Anritsu	MA2411B	1726434	2022/6/22	2023/6/21

Notes:

1. The test was performed in Oven room 2.
2. Tested Date: 2023/4/13

4.2 Power Spectral Density

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Attenuator WOKEN	MDCS18N-10	MDCS18N-10-01	2023/3/27	2024/3/26
Software	ADT_RF Test Software V6.6.5.4	N/A	N/A	N/A
Spectrum Analyzer Keysight	N9020B	MY60112409	2023/2/18	2024/2/17

Notes:

1. The test was performed in Oven room 2.
2. Tested Date: 2023/4/13

4.3 6 dB Bandwidth

Refer to section 4.2 to get information of the instruments.

4.4 Conducted Out of Band Emissions

Refer to section 4.2 to get information of the instruments.

4.5 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	N/A	N/A
Fix tool for Boresight antenna tower BV	FBA-01	FBA_SIP01	N/A	N/A
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-3-01	2022/9/14	2023/9/13
LOOP ANTENNA Electro-Metrics	EM-6879	264	2023/2/21	2024/2/20
Pre_Amplifier Agilent	8447D	2944A10636	2023/3/12	2024/3/11
Pre_Amplifier Mini-Circuits	ZFL-1000VH2	QA0838008	2022/10/4	2023/10/3
RF Coaxial Cable COMMATE/PEWC	8D	966-3-2	2023/2/17	2024/2/16
		966-4-1	2023/2/18	2024/2/17
		966-3-3	2023/2/17	2024/2/16
RF Coaxial Cable JYEBO	5D-FB	LOOPCAB-001	2022/12/19	2023/12/18
		LOOPCAB-002	2022/12/19	2023/12/18
Software	ADT_Radiated_V8.7.08	N/A	N/A	N/A
Spectrum Analyzer KEYSIGHT	N9030B	MY57142938	2022/4/26	2023/4/25
Test Receiver KEYSIGHT	N9038A	MY59050100	2022/6/20	2023/6/19
Trilog Broadband Antenna Schwarzbeck	VULB 9168	9168-361	2022/10/21	2023/10/20

Notes:

1. The test was performed in 966 Chamber No. 3.
2. Tested Date: 2023/4/13

4.6 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	N/A	N/A
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	N/A	N/A
Fix tool for Boresight antenna tower BV	FBA-01	FBA_SIP01	N/A	N/A
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-783	2022/11/13	2023/11/12
	BBHA 9170	9170-739	2022/11/13	2023/11/12
	BBHA9120-D	9120D-406	2022/11/13	2023/11/12
Pre_Amplifier EMCI	EMC12630SE	980384	2022/12/28	2023/12/27
		980688	2022/10/4	2023/10/3
	EMC184045SE	980387	2022/12/28	2023/12/27
RF Cable EMCI	EMC104-SM-SM-6000	210201	2022/5/10	2023/5/9
RF Cable-Frequency Range : 1-26.5GHz EMCI	EMC104-SM-SM-1200	160922	2022/12/15	2023/12/14
RF Cable-Frequency range: 1-40GHz EMCI	EMC102-KM-KM-1200	160924	2022/12/28	2023/12/27
RF Coaxial Cable EMCI	EMC-KM-KM-4000	200214	2023/2/20	2024/2/19
	EMC104-SM-SM-1500	180504	2023/3/27	2024/3/26
	EMC104-SM-SM-2000	180502	2023/3/27	2024/3/26
		180601	2022/6/6	2023/6/5
	EMC104-SM-SM-6000	210704	2022/11/4	2023/11/3
Software	ADT_Radiated_V8.7.08	N/A	N/A	N/A
Spectrum Analyzer KEYSIGHT	N9030B	MY57142938	2022/4/26	2023/4/25
Test Receiver KEYSIGHT	N9038A	MY59050100	2022/6/20	2023/6/19

Notes:

1. The test was performed in 966 Chamber No. 3.
2. Tested Date: 2023/4/6 ~ 2023/4/13

5 Limits of Test Items

5.1 RF Output Power

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

5.2 Power Spectral Density

The Maximum of Power Spectral Density Measurement is 8 dBm in any 3 kHz.

5.3 6 dB Bandwidth

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

5.4 Conducted Out of Band Emissions

Below 20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

5.5 Unwanted Emissions below 1 GHz

Radiated emissions up to 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.6 Unwanted Emissions above 1 GHz

Radiated emissions above 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

6 Test Arrangements

6.1 RF Output Power

6.1.1 Test Setup



6.1.2 Test Procedure

Peak Power:
A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average Power:
Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

6.2 Power Spectral Density

6.2.1 Test Setup



6.2.2 Test Procedure

a. Set analyzer center frequency to DTS channel center frequency.
b. Set the span to 1.5 times the DTS bandwidth.
c. Set the RBW to: 3 kHz.
d. Set the VBW ≥ 3 × RBW.
e. Detector = peak.
f. Sweep time = auto couple.
g. Trace mode = max hold.
h. Allow trace to fully stabilize.
i. Use the peak marker function to determine the maximum amplitude level within the RBW.

6.3 6 dB Bandwidth

6.3.1 Test Setup



6.3.2 Test Procedure

a. Set resolution bandwidth (RBW) = 100 kHz.
b. Set the video bandwidth (VBW) ≥ 3 x RBW, Detector = Peak.
c. Trace mode = max hold.
d. Sweep = auto couple.
e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.4 Conducted Out of Band Emissions

6.4.1 Test Setup



6.4.2 Test Procedure

MEASUREMENT PROCEDURE REF

a. Set the RBW = 100 kHz.
b. Set the VBW ≥ 300 kHz.
c. Detector = peak.
d. Sweep time = auto couple.
e. Trace mode = max hold.
f. Allow trace to fully stabilize.
g. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

a. Set RBW = 100 kHz.
b. Set VBW ≥ 300 kHz.
c. Detector = peak.
d. Sweep = auto couple.
e. Trace Mode = max hold.
f. Allow trace to fully stabilize.
g. Use the peak marker function to determine the maximum amplitude level.

6.5 Unwanted Emissions below 1 GHz

6.5.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.5.2 Test Procedure

For Radiated emission below 30 MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

6.6 Unwanted Emissions above 1 GHz

6.6.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.6.2 Test Procedure

a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

1. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
2. For fundamental and harmonic signal measurement, according to KDB 558074 D01 15.247 Meas Guidance v05r02 section 8.1(c)(3), The spectrum analyzer settings meets the requirements of 11.12.2.4 in ANSI C63.10 for making a Peak measurement, the average value = Peak value + duty cycle correction factor. The duty cycle measurement refer to FCC 47 CFR Part 15C section 15.35 (c). For duty cycle correction factor values, see the Test Signal Duty Cycle section in this report.
3. All modes of operation were investigated and the worst-case emissions are reported.

7 Test Results of Test Item

7.1 RF Output Power

Input Power:	3 Vdc	Environmental Conditions:	22°C, 61% RH	Tested By:	Katina Lu

For Peak Power

BT-LE 1M

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
0	2402	2.57	4.10	30	Pass
19	2440	2.612	4.17	30	Pass
39	2480	2.618	4.18	30	Pass

Note: The antenna gain is 2.77 dBi < 6 dBi, so the output power limit shall not be reduced.

BT-LE 2M

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
1	2404	2.594	4.14	30	Pass
19	2440	2.6	4.15	30	Pass
38	2478	2.612	4.17	30	Pass

Note: The antenna gain is 2.77 dBi < 6 dBi, so the output power limit shall not be reduced.

Logi Bolt 1M

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
0	2402	2.559	4.08	30	Pass
19	2440	2.606	4.16	30	Pass
39	2480	2.6	4.15	30	Pass

Note: The antenna gain is 2.77 dBi < 6 dBi, so the output power limit shall not be reduced.

Logi Bolt 2M

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
1	2404	2.588	4.13	30	Pass
19	2440	2.594	4.14	30	Pass
38	2478	2.606	4.16	30	Pass

Note: The antenna gain is 2.77 dBi < 6 dBi, so the output power limit shall not be reduced.

For Average Power

BT-LE 1M

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	2.553	4.07
19	2440	2.588	4.13
39	2480	2.594	4.14

BT-LE 2M

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
1	2404	2.576	4.11
19	2440	2.582	4.12
38	2478	2.588	4.13

Logi Bolt 1M

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	2.541	4.05
19	2440	2.582	4.12
39	2480	2.576	4.11

Logi Bolt 2M

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
1	2404	2.57	4.10
19	2440	2.576	4.11
38	2478	2.582	4.12

7.2 Power Spectral Density

Input Power:	3 Vdc	Environmental Conditions:	22°C, 61% RH	Tested By:	Katina Lu

BT-LE 1M

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
0	2402	0.88	8	Pass
19	2440	0.84	8	Pass
39	2480	0.72	8	Pass

Note: The antenna gain is 2.77 dBi < 6 dBi, so the power density limit shall not be reduced.

BT-LE 2M

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
1	2404	-3.37	8	Pass
19	2440	-3.09	8	Pass
38	2478	-3.17	8	Pass

Note: The antenna gain is 2.77 dBi < 6 dBi, so the power density limit shall not be reduced.

Logi Bolt 1M

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
0	2402	1.02	8	Pass
19	2440	0.93	8	Pass
39	2480	1.03	8	Pass

Note: The antenna gain is 2.77 dBi < 6 dBi, so the power density limit shall not be reduced.

Logi Bolt 2M

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
1	2404	-3.36	8	Pass
19	2440	-3.65	8	Pass
38	2478	-3.64	8	Pass

Note: The antenna gain is 2.77 dBi < 6 dBi, so the power density limit shall not be reduced.

Spectrum Plot of Maximum Value



BT-LE 1M : CH 0



BT-LE 2M : CH 19



Logi Bolt 1M : CH 39



Logi Bolt 2M : CH 1

7.3 6 dB Bandwidth

Input Power:	3 Vdc	Environmental Conditions:	22°C, 61% RH	Tested By:	Katina Lu

BT-LE 1M

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
0	2402	0.69	0.5	Pass
19	2440	0.7	0.5	Pass
39	2480	0.7	0.5	Pass

BT-LE 2M

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
1	2404	1.1	0.5	Pass
19	2440	1.11	0.5	Pass
38	2478	1.12	0.5	Pass

Logi Bolt 1M

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
0	2402	0.69	0.5	Pass
19	2440	0.71	0.5	Pass
39	2480	0.7	0.5	Pass

Logi Bolt 2M

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
1	2404	1.14	0.5	Pass
19	2440	1.15	0.5	Pass
38	2478	1.17	0.5	Pass

Spectrum Plot of Minimum Value



BT-LE 1M : CH 0



BT-LE 2M : CH 1



Logi Bolt 1M : CH 0



Logi Bolt 2M : CH 1

7.4 Conducted Out of Band Emissions

Input Power:	3 Vdc	Environmental Conditions:	22°C, 61% RH	Tested By:	Katina Lu

BT-LE 1M



CH 0



CH 0



CH 19



CH 19



CH 39



CH 39



CH 0 Band edge



CH 39 Band edge

BT-LE 2M



CH 1



CH 1



CH 19



CH 19



CH 38



CH 38



CH 1 Band edge



CH 38 Band edge

Logi Bolt 1M



CH 0



CH 0



CH 19



CH 19



CH 39



CH 39



CH 0 Band edge



CH 39 Band edge

Logi Bolt 2M



CH 1



CH 1



CH 19



CH 19



CH 38



CH 38



CH 1 Band edge



CH 38 Band edge

7.5 Unwanted Emissions below 1 GHz

RF Mode	BT-LE 1M	**Channel**	CH 39：2480 MHz
Frequency Range	30 MHz ~ 1 GHz	**Detector Function & Bandwidth**	(QP) RB = 120kHz
Input Power	3 Vdc	**Environmental Conditions**	22°C, 65% RH
Tested By	Sampson Chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	31.07	20.5 QP	40.0	-19.5	1.50 H	214	29.6	-9.1
2	161.87	17.8 QP	43.5	-25.7	1.50 H	93	25.8	-8.0
3	337.03	19.7 QP	46.0	-26.3	2.00 H	64	25.8	-6.1
4	443.17	22.7 QP	46.0	-23.3	1.00 H	232	26.0	-3.3
5	646.51	26.3 QP	46.0	-19.7	1.00 H	288	25.1	1.2
6	818.08	29.4 QP	46.0	-16.6	2.00 H	208	25.6	3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The emission levels were very low against the limit of frequency range 9 kHz ~ 30 MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



RF Mode	BT-LE 1M	Channel	CH 39：2480 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	(QP) RB = 120kHz
Input Power	3 Vdc	Environmental Conditions	22°C, 65% RH
Tested By	Sampson Chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	31.20	28.5 QP	40.0	-11.5	1.00 V	23	37.5	-9.0
2	147.27	18.2 QP	43.5	-25.3	1.50 V	333	26.0	-7.8
3	349.58	19.8 QP	46.0	-26.2	1.00 V	64	25.8	-6.0
4	430.74	22.0 QP	46.0	-24.0	1.00 V	141	25.5	-3.5
5	645.00	25.7 QP	46.0	-20.3	1.00 V	266	24.5	1.2
6	800.10	28.5 QP	46.0	-17.5	1.50 V	56	25.1	3.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The emission levels were very low against the limit of frequency range 9 kHz ~ 30 MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



RF Mode	logi bolt 1M	**Channel**	CH 19：2440 MHz
Frequency Range	30 MHz ~ 1 GHz	**Detector Function & Bandwidth**	(QP) RB = 120kHz
Input Power	3 Vdc	**Environmental Conditions**	22°C, 65% RH
Tested By	Sampson Chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	31.19	20.4 QP	40.0	-19.6	1.50 H	255	29.4	-9.0
2	162.10	17.9 QP	43.5	-25.6	1.50 H	101	25.9	-8.0
3	337.27	20.0 QP	46.0	-26.0	2.00 H	78	26.1	-6.1
4	443.41	23.0 QP	46.0	-23.0	1.00 H	250	26.3	-3.3
5	646.27	26.1 QP	46.0	-19.9	1.00 H	297	24.9	1.2
6	818.40	29.2 QP	46.0	-16.8	2.00 H	222	25.4	3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The emission levels were very low against the limit of frequency range 9 kHz ~ 30 MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



RF Mode	logi bolt 1M	**Channel**	CH 19：2440 MHz
Frequency Range	30 MHz ~ 1 GHz	**Detector Function & Bandwidth**	(QP) RB = 120kHz
Input Power	3 Vdc	**Environmental Conditions**	22°C, 65% RH
Tested By	Sampson Chen		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	**31.07**	**28.7 QP**	**40.0**	**-11.3**	**1.00 V**	**10**	**37.8**	**-9.1**
2	147.47	18.3 QP	43.5	-25.2	1.50 V	350	26.1	-7.8
3	349.83	19.5 QP	46.0	-26.5	1.00 V	52	25.5	-6.0
4	430.42	21.6 QP	46.0	-24.4	1.00 V	113	25.1	-3.5
5	644.74	25.9 QP	46.0	-20.1	1.00 V	244	24.7	1.2
6	799.94	28.8 QP	46.0	-17.2	1.50 V	48	25.4	3.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The emission levels were very low against the limit of frequency range 9 kHz ~ 30 MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



7.6 Unwanted Emissions above 1 GHz

RF Mode	BT-LE 1M	**Channel**	CH 0：2402 MHz
Frequency Range	1 GHz ~ 25 GHz	**Detector Function & Bandwidth**	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	**Environmental Conditions**	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	2390.00	56.7 PK	74.0	-17.3	1.18 H	126	57.6	-0.9
2	**2390.00**	**47.6 AV**	**54.0**	**-6.4**	**1.18 H**	**126**	**48.5**	**-0.9**
3	*2402.00	102.6 PK			1.18 H	126	103.4	-0.8
4	*2402.00	76.7 AV			1.18 H	126	77.5	-0.8
5	4804.00	51.5 PK	74.0	-22.5	1.00 H	156	47.7	3.8
6	4804.00	25.6 AV	54.0	-28.4	1.00 H	156	21.8	3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.357 ms / 7.047 ms) = -25.9 dB



RF Mode	BT-LE 1M	Channel	CH 0：2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.1 PK	74.0	-16.9	3.90 V	294	58.0	-0.9
2	2390.00	45.5 AV	54.0	-8.5	3.90 V	294	46.4	-0.9
3	*2402.00	97.7 PK			3.90 V	294	98.5	-0.8
4	*2402.00	71.8 AV			3.90 V	294	72.6	-0.8
5	4804.00	45.4 PK	74.0	-28.6	1.21 V	96	41.6	3.8
6	4804.00	19.5 AV	54.0	-34.5	1.21 V	96	15.7	3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.357 ms / 7.047 ms) = -25.9 dB



RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	102.9 PK			1.11 H	124	103.7	-0.8
2	*2440.00	77.0 AV			1.11 H	124	77.8	-0.8
3	4880.00	51.1 PK	74.0	-22.9	1.02 H	160	47.4	3.7
4	4880.00	25.2 AV	54.0	-28.8	1.02 H	160	21.5	3.7
5	7320.00	47.1 PK	74.0	-26.9	3.29 H	103	36.7	10.4
6	7320.00	21.2 AV	54.0	-32.8	3.29 H	103	10.8	10.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.357 ms / 7.047 ms) = -25.9 dB



RF Mode	BT-LE 1M	Channel	CH 19：2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	96.7 PK			3.83 V	282	97.5	-0.8
2	*2440.00	70.8 AV			3.83 V	282	71.6	-0.8
3	4880.00	46.0 PK	74.0	-28.0	1.20 V	102	42.3	3.7
4	4880.00	20.1 AV	54.0	-33.9	1.20 V	102	16.4	3.7
5	7320.00	46.3 PK	74.0	-27.7	1.06 V	235	35.9	10.4
6	7320.00	20.4 AV	54.0	-33.6	1.06 V	235	10.0	10.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.357 ms / 7.047 ms) = -25.9 dB



RF Mode	BT-LE 1M	Channel	CH 39：2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	102.9 PK			1.17 H	123	103.8	-0.9
2	*2480.00	77.0 AV			1.17 H	123	77.9	-0.9
3	2483.50	66.2 PK	74.0	-7.8	1.17 H	123	67.1	-0.9
4	2483.50	46.7 AV	54.0	-7.3	1.17 H	123	47.6	-0.9
5	4960.00	51.3 PK	74.0	-22.7	1.00 H	156	47.4	3.9
6	4960.00	25.4 AV	54.0	-28.6	1.00 H	156	21.5	3.9
7	7440.00	46.7 PK	74.0	-27.3	3.24 H	98	36.2	10.5
8	7440.00	20.8 AV	54.0	-33.2	3.24 H	98	10.3	10.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.357 ms / 7.047 ms) = -25.9 dB



RF Mode	BT-LE 1M	Channel	CH 39：2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	97.2 PK			3.98 V	296	98.1	-0.9
2	*2480.00	71.3 AV			3.98 V	296	72.2	-0.9
3	2483.50	61.1 PK	74.0	-12.9	3.98 V	296	62.0	-0.9
4	2483.50	45.3 AV	54.0	-8.7	3.98 V	296	46.2	-0.9
5	4960.00	45.5 PK	74.0	-28.5	1.17 V	94	41.6	3.9
6	4960.00	19.6 AV	54.0	-34.4	1.17 V	94	15.7	3.9
7	7440.00	46.0 PK	74.0	-28.0	1.02 V	248	35.5	10.5
8	7440.00	20.1 AV	54.0	-33.9	1.02 V	248	9.6	10.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.357 ms / 7.047 ms) = -25.9 dB



RF Mode	BT-LE 2M	Channel	CH 1：2404 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.5 PK	74.0	-16.5	1.18 H	120	58.4	-0.9
2	2390.00	46.0 AV	54.0	-8.0	1.18 H	120	46.9	-0.9
3	*2404.00	102.6 PK			1.18 H	120	103.4	-0.8
4	*2404.00	71.1 AV			1.18 H	120	71.9	-0.8
5	4808.00	51.3 PK	74.0	-22.7	1.03 H	141	47.5	3.8
6	4808.00	19.8 AV	54.0	-34.2	1.03 H	141	16.0	3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.187 ms / 7.047 ms) = -31.5 dB



RF Mode	BT-LE 2M	Channel	CH 1：2404 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.6 PK	74.0	-16.4	3.87 V	290	58.5	-0.9
2	2390.00	44.9 AV	54.0	-9.1	3.87 V	290	45.8	-0.9
3	*2404.00	97.9 PK			3.87 V	290	98.7	-0.8
4	*2404.00	66.4 AV			3.87 V	290	67.2	-0.8
5	4808.00	45.4 PK	74.0	-28.6	1.18 V	98	41.6	3.8
6	4808.00	13.9 AV	54.0	-40.1	1.18 V	98	10.1	3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.187 ms / 7.047 ms) = -31.5 dB



RF Mode	BT-LE 2M	Channel	CH 19：2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	102.6 PK			1.12 H	116	103.4	-0.8
2	*2440.00	71.1 AV			1.12 H	116	71.9	-0.8
3	4880.00	51.3 PK	74.0	-22.7	1.04 H	170	47.6	3.7
4	4880.00	19.8 AV	54.0	-34.2	1.04 H	170	16.1	3.7
5	7320.00	47.0 PK	74.0	-27.0	3.22 H	108	36.6	10.4
6	7320.00	15.5 AV	54.0	-38.5	3.22 H	108	5.1	10.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.187 ms / 7.047 ms) = -31.5 dB



RF Mode	BT-LE 2M	Channel	CH 19：2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	97.7 PK			3.83 V	282	98.5	-0.8
2	*2440.00	66.2 AV			3.83 V	282	67.0	-0.8
3	4880.00	45.3 PK	74.0	-28.7	1.21 V	84	41.6	3.7
4	4880.00	13.8 AV	54.0	-40.2	1.21 V	84	10.1	3.7
5	7320.00	46.7 PK	74.0	-27.3	1.03 V	248	36.3	10.4
6	7320.00	15.2 AV	54.0	-38.8	1.03 V	248	4.8	10.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.187 ms / 7.047 ms) = -31.5 dB



RF Mode	BT-LE 2M	Channel	CH 38：2478 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2478.00	103.1 PK			1.18 H	109	104.0	-0.9
2	*2478.00	71.6 AV			1.18 H	109	72.5	-0.9
3	2483.50	64.1 PK	74.0	-9.9	1.18 H	109	65.0	-0.9
4	2483.50	46.9 AV	54.0	-7.1	1.18 H	109	47.8	-0.9
5	4956.00	51.2 PK	74.0	-22.8	1.06 H	142	47.3	3.9
6	4956.00	19.7 AV	54.0	-34.3	1.06 H	142	15.8	3.9
7	7434.00	46.7 PK	74.0	-27.3	3.19 H	92	36.2	10.5
8	7434.00	15.2 AV	54.0	-38.8	3.19 H	92	4.7	10.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.187 ms / 7.047 ms) = -31.5 dB



RF Mode	BT-LE 2M	Channel	CH 38：2478 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2478.00	97.2 PK			3.90 V	293	98.1	-0.9
2	*2478.00	65.7 AV			3.90 V	293	66.6	-0.9
3	2483.50	59.1 PK	74.0	-14.9	3.90 V	293	60.0	-0.9
4	2483.50	45.6 AV	54.0	-8.4	3.90 V	293	46.5	-0.9
5	4956.00	45.7 PK	74.0	-28.3	1.16 V	85	41.8	3.9
6	4956.00	14.2 AV	54.0	-39.8	1.16 V	85	10.3	3.9
7	7434.00	46.3 PK	74.0	-27.7	1.03 V	253	35.8	10.5
8	7434.00	14.8 AV	54.0	-39.2	1.03 V	253	4.3	10.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.187 ms / 7.047 ms) = -31.5 dB



RF Mode	logi bolt 1M	Channel	CH 0：2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.7 PK	74.0	-16.3	1.19 H	142	58.6	-0.9
2	2390.00	47.4 AV	54.0	-6.6	1.19 H	142	48.3	-0.9
3	*2402.00	102.6 PK			1.19 H	142	103.4	-0.8
4	*2402.00	76.7 AV			1.19 H	142	77.5	-0.8
5	4804.00	51.2 PK	74.0	-22.8	1.02 H	163	47.4	3.8
6	4804.00	25.3 AV	54.0	-28.7	1.02 H	163	21.5	3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.359 ms / 7.043 ms) = -25.9 dB



RF Mode	logi bolt 1M	**Channel**	CH 0：2402 MHz
Frequency Range	1 GHz ~ 25 GHz	**Detector Function & Bandwidth**	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	**Environmental Conditions**	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	2390.00	57.2 PK	74.0	-16.8	3.88 V	290	58.1	-0.9
2	2390.00	45.2 AV	54.0	-8.8	3.88 V	290	46.1	-0.9
3	*2402.00	97.5 PK			3.88 V	290	98.3	-0.8
4	*2402.00	71.6 AV			3.88 V	290	72.4	-0.8
5	4804.00	45.6 PK	74.0	-28.4	1.12 V	85	41.8	3.8
6	4804.00	19.7 AV	54.0	-34.3	1.12 V	85	15.9	3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.359 ms / 7.043 ms) = -25.9 dB



RF Mode	logi bolt 1M	Channel	CH 19：2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	103.0 PK			1.17 H	113	103.8	-0.8
2	*2440.00	77.1 AV			1.17 H	113	77.9	-0.8
3	4880.00	51.3 PK	74.0	-22.7	1.01 H	169	47.6	3.7
4	4880.00	25.4 AV	54.0	-28.6	1.01 H	169	21.7	3.7
5	7320.00	46.1 PK	74.0	-27.9	3.22 H	112	35.7	10.4
6	7320.00	20.2 AV	54.0	-33.8	3.22 H	112	9.8	10.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.359 ms / 7.043 ms) = -25.9 dB



RF Mode	logi bolt 1M	**Channel**	CH 19：2440 MHz
Frequency Range	1 GHz ~ 25 GHz	**Detector Function & Bandwidth**	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	**Environmental Conditions**	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	*2440.00	97.2 PK			3.90 V	269	98.0	-0.8
2	*2440.00	71.3 AV			3.90 V	269	72.1	-0.8
3	4880.00	45.5 PK	74.0	-28.5	1.19 V	90	41.8	3.7
4	4880.00	19.6 AV	54.0	-34.4	1.19 V	90	15.9	3.7
5	7320.00	47.0 PK	74.0	-27.0	1.07 V	248	36.6	10.4
6	7320.00	21.1 AV	54.0	-32.9	1.07 V	248	10.7	10.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.359 ms / 7.043 ms) = -25.9 dB



RF Mode	logi bolt 1M	Channel	CH 39：2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	103.2 PK			1.16 H	109	104.1	-0.9
2	*2480.00	77.3 AV			1.16 H	109	78.2	-0.9
3	2483.50	67.2 PK	74.0	-6.8	1.16 H	109	68.1	-0.9
4	2483.50	47.1 AV	54.0	-6.9	1.16 H	109	48.0	-0.9
5	4960.00	51.6 PK	74.0	-22.4	1.00 H	168	47.7	3.9
6	4960.00	25.7 AV	54.0	-28.3	1.00 H	168	21.8	3.9
7	7440.00	46.2 PK	74.0	-27.8	3.26 H	107	35.7	10.5
8	7440.00	20.3 AV	54.0	-33.7	3.26 H	107	9.8	10.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.359 ms / 7.043 ms) = -25.9 dB



RF Mode	logi bolt 1M	Channel	CH 39：2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	97.0 PK			3.95 V	303	97.9	-0.9
2	*2480.00	71.1 AV			3.95 V	303	72.0	-0.9
3	2483.50	59.9 PK	74.0	-14.1	3.95 V	303	60.8	-0.9
4	2483.50	45.5 AV	54.0	-8.5	3.95 V	303	46.4	-0.9
5	4960.00	45.6 PK	74.0	-28.4	1.19 V	78	41.7	3.9
6	4960.00	19.7 AV	54.0	-34.3	1.19 V	78	15.8	3.9
7	7440.00	46.8 PK	74.0	-27.2	1.02 V	238	36.3	10.5
8	7440.00	20.9 AV	54.0	-33.1	1.02 V	238	10.4	10.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.359 ms / 7.043 ms) = -25.9 dB



RF Mode	logi bolt 2M	**Channel**	CH 1：2404 MHz
Frequency Range	1 GHz ~ 25 GHz	**Detector Function & Bandwidth**	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	**Environmental Conditions**	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	2390.00	56.5 PK	74.0	-17.5	1.15 H	125	57.4	-0.9
2	2390.00	45.5 AV	54.0	-8.5	1.15 H	125	46.4	-0.9
3	*2404.00	102.6 PK			1.15 H	125	103.4	-0.8
4	*2404.00	71.1 AV			1.15 H	125	71.9	-0.8
5	4808.00	51.7 PK	74.0	-22.3	1.05 H	165	47.9	3.8
6	4808.00	20.2 AV	54.0	-33.8	1.05 H	165	16.4	3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.187 ms / 7.053 ms) = -31.5 dB



RF Mode	logi bolt 2M	Channel	CH 1：2404 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.9 PK	74.0	-16.1	3.85 V	281	58.8	-0.9
2	2390.00	45.1 AV	54.0	-8.9	3.85 V	281	46.0	-0.9
3	*2404.00	97.8 PK			3.85 V	281	98.6	-0.8
4	*2404.00	66.3 AV			3.85 V	281	67.1	-0.8
5	4808.00	45.3 PK	74.0	-28.7	1.11 V	97	41.5	3.8
6	4808.00	13.8 AV	54.0	-40.2	1.11 V	97	10.0	3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.187 ms / 7.053 ms) = -31.5 dB



RF Mode	logi bolt 2M	**Channel**	CH 19：2440 MHz
Frequency Range	1 GHz ~ 25 GHz	**Detector Function & Bandwidth**	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	**Environmental Conditions**	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	*2440.00	103.2 PK			1.17 H	110	104.0	-0.8
2	*2440.00	71.7 AV			1.17 H	110	72.5	-0.8
3	4880.00	51.3 PK	74.0	-22.7	1.04 H	159	47.6	3.7
4	4880.00	19.8 AV	54.0	-34.2	1.04 H	159	16.1	3.7
5	7320.00	46.2 PK	74.0	-27.8	3.20 H	91	35.8	10.4
6	7320.00	14.7 AV	54.0	-39.3	3.20 H	91	4.3	10.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.187 ms / 7.053 ms) = -31.5 dB



RF Mode	logi bolt 2M	**Channel**	CH 19：2440 MHz
Frequency Range	1 GHz ~ 25 GHz	**Detector Function & Bandwidth**	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	**Environmental Conditions**	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	**Frequency (MHz)**	**Emission Level (dBuV/m)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Height (m)**	**Table Angle (Degree)**	**Raw Value (dBuV)**	**Correction Factor (dB/m)**
1	*2440.00	97.7 PK			3.85 V	297	98.5	-0.8
2	*2440.00	66.2 AV			3.85 V	297	67.0	-0.8
3	4880.00	45.5 PK	74.0	-28.5	1.20 V	81	41.8	3.7
4	4880.00	14.0 AV	54.0	-40.0	1.20 V	81	10.3	3.7
5	7320.00	46.7 PK	74.0	-27.3	1.03 V	243	36.3	10.4
6	7320.00	15.2 AV	54.0	-38.8	1.03 V	243	4.8	10.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.187 ms / 7.053 ms) = -31.5 dB



RF Mode	logi bolt 2M	Channel	CH 38：2478 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2478.00	103.2 PK			1.16 H	118	104.1	-0.9
2	*2478.00	71.7 AV			1.16 H	118	72.6	-0.9
3	2483.50	65.1 PK	74.0	-8.9	1.16 H	118	66.0	-0.9
4	2483.50	46.8 AV	54.0	-7.2	1.16 H	118	47.7	-0.9
5	4956.00	50.9 PK	74.0	-23.1	1.05 H	154	47.0	3.9
6	4956.00	19.4 AV	54.0	-34.6	1.05 H	154	15.5	3.9
7	7434.00	46.2 PK	74.0	-27.8	3.27 H	101	35.7	10.5
8	7434.00	14.7 AV	54.0	-39.3	3.27 H	101	4.2	10.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.187 ms / 7.053 ms) = -31.5 dB



RF Mode	logi bolt 2M	Channel	CH 38：2478 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 3 MHz
Input Power	3 Vdc	Environmental Conditions	25°C, 70% RH
Tested By	Nelson Teng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2478.00	97.1 PK			3.94 V	291	98.0	-0.9
2	*2478.00	65.6 AV			3.94 V	291	66.5	-0.9
3	2483.50	58.9 PK	74.0	-15.1	3.94 V	291	59.8	-0.9
4	2483.50	45.3 AV	54.0	-8.7	3.94 V	291	46.2	-0.9
5	4956.00	45.0 PK	74.0	-29.0	1.19 V	93	41.1	3.9
6	4956.00	13.5 AV	54.0	-40.5	1.19 V	93	9.6	3.9
7	7434.00	46.2 PK	74.0	-27.8	1.01 V	232	35.7	10.5
8	7434.00	14.7 AV	54.0	-39.3	1.01 V	232	4.2	10.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
   20 log(Duty cycle) = 20 log(0.187 ms / 7.053 ms) = -31.5 dB



Plot of Band Edge

BT-LE 1M Channel 0



Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

BT-LE 1M Channel 39



Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

BT-LE 2M Channel 1



Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

BT-LE 2M Channel 38



Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

logi bolt 1M Channel 0



Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

logi bolt 1M Channel 39



Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

logi bolt 2M Channel 1



Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

logi bolt 2M Channel 38



Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab
Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@bureauveritas.com
Web Site: http://ee.bureauveritas.com.tw

The address and road map of all our labs can be found in our web site also.

--- END ---