TEST REPORT

DT&C Co., Ltd.
42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRRFCC1911-0119
2. Customer
   - Name : Kyocera Corporation
   - Address : Yokohama Office 2-1-1 Kagahara, Tsuzuki-ku Yokohama-shi, Kanagawa, Japan
3. Use of Report : FCC Original Grant
4. Product Name / Model Name : Mobile Phone / CB70
   FCC ID : JOYCB70
5. Test Method Used : IEEE 1528-2013, FCC SAR KDB Publications (Details in test report)
   Test Specification : CFR §2.1093
6. Date of Test : 2019.11.13 ~ 2019.11.21
7. Testing Environment : Refer to appended test report.
8. Test Result : Refer to attached test report.

Affirmation	Tested by Name : BumJun Park (Signature)	Reviewed by Name : HakMin Kim (Signature)

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose. This test report shall not be reproduced except in full, without the written approval of DT&C Co., Ltd.

2019 . 11 . 25 .

DT&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

Test Report Version

Test Report No.	Date	Description
DRRFCC1911-0119	Nov. 25, 2019	Initial issue

Table of Contents

1. DESCRIPTION OF DEVICE 5
1.1 General Information 5
1.2 Power Reduction for SAR 6
1.3 Nominal and Maximum Output Power Specifications 6
1.4 DUT Antenna Locations 6
1.5 Simultaneous Transmission Capabilities 6
1.6 Miscellaneous SAR Test Considerations 6
1.7 Guidance Applied 7
1.8 Device Serial Numbers 7
2. LTE INFORMATION 8
3. INTROCUCTION 9
4. DOSIMETRIC ASSESSMENT 10
4.1 Measurement Procedure 10
5. DEFINITION OF REFERENCE POINTS 12
5.1 Ear Reference Point 12
5.2 Handset Reference Points 12
6. TEST CONFIGURATION POSITIONS FOR HANDSETS 13
6.1 Device Holder 13
6.2 Positioning for Cheek/Touch 13
6.3 Positioning for Ear / 15 ° Tilt 13
6.4 Body-Worn Accessory Configurations 14
6.5 Extremity Exposure Configurations 14
6.6 Wireless Router Configurations 15
6.7 Phablet Configurations 15
7. RF EXPOSURE LIMITS 16
8. FCC MEASUREMENT PROCEDURES 17
8.1 Measured and Reported SAR 17
8.2 Procedures Used to Establish RF Signal for SAR 17
8.3 SAR Measurement Conditions for WCDMA (UMTS) 17
8.3.1 Output Power Verification 17
8.3.2 Head SAR Measurements for Handsets 17
8.3.3 Body SAR Measurements 18
8.3.4 Release 5 HSDPA Data Devices 18
8.3.5 Release 6 HSUPA Data Devices 18
8.4 SAR Measurement Conditions for LTE 19
8.4.1 Spectrum Plots for RB Configurations 19
8.4.2 MPR 19
8.4.3 A-MPR 19
8.4.4 Required RB Size and RB Offsets for SAR Testing 19
8.4.5 64QAM uplink 20
8.5 SAR Testing with 802.11 Transmitters 20
8.5.1 General Device Setup 20
8.5.2 U-NII and U-NII-2A 20
8.5.3 U-NII-2C and U-NII-3 20
8.5.4 Initial Test Position Procedure 21
8.5.5 2.4 GHz SAR Test Requirements 21
8.5.6 OFDM Transmission Mode and SAR Test Channel Selection 21
8.5.7 Initial Test Configuration Procedure 21
8.5.8 Subsequent Test Configuration Procedures 21
9. RF CONDUCTED POWERS 22
9.1 GSM Nominal and Maximum Output Power Spec and Conducted Powers 22
9.2 WCDMA Nominal and Maximum Output Power Spec and Conducted Powers 23
9.3 LTE Nominal and Maximum Output Power Spec and Conducted Powers 24
9.4 WLAN Nominal and Maximum Output Power Spec and Conducted Powers 25
9.5 Bluetooth Conducted Powers 27
10. SYSTEM VERIFICATION 28
10.1 Tissue Verification 28
10.2 Test System Verification 29

11. SAR TEST RESULTS **30**
11.1 Head SAR Results 30
11.2 Standalone Body-Worn SAR Worn SAR Results 32
11.3 Standalone Hotspot SAR Results 34
11.4 Standalone Phablet SAR Results 36
11.5 SAR Test Notes 36
12. FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS **39**
12.1 Introduction 39
12.2 Simultaneous Transmission Procedures 39
12.3 Simultaneous Transmission Capabilities 39
12.4 Head SAR Simultaneous Transmission Analysis 41
12.5 Body-Worn Simultaneous Transmission Analysis 43
12.6 Hotspot SAR Simultaneous Transmission Analysis 44
12.7 Phablet SAR Simultaneous Transmission Analysis 46
12.8 Simultaneous Transmission Conclusion 46
13. SAR MEASUREMENT VARIABILITY **47**
13.1 Measurement Variability 47
13.2 Measurement Uncertainty 47
14. EQUIPMENT LIST **48**
15. MEASUREMENT UNCERTAINTIES **49**
16. CONCLUSION **57**
17. REFERENCES **58**
APPENDIX A. – Probe Calibration Data **60**
APPENDIX B. – Dipole Calibration Data **80**
APPENDIX C. – SAR Tissue Specifications **129**
APPENDIX D. – SAR SYSTEM VALIDATION **131**
APPENDIX E. – Description of Test Equipment **133**

1. DESCRIPTION OF DEVICE

1.1 General Information

EUT type	Mobile Phone				
FCC ID	JOYCB70				
Equipment model name	CB70				
Equipment add model name	N/A				
Equipment serial no.	Identical prototype				
Mode(s) of Operation	GSM 850, GSM 1900, WCDMA 850, LTE Band 17, 2.4 G W-LAN (802.11b/g/n-HT20), 5 G W-LAN (802.11a/n-HT20/n-HT40/ac-VHT20/ac-VHT40/ac-VHT80), Bluetooth				
	Band	**Mode**	**Operating Modes**	**Bandwidth**	**Frequency**
TX Frequency Range	GSM 850	GSM/GPRS	Voice/Data	-	824.2 ~ 848.8 MHz
	GSM 1900	GSM/GPRS	Voice/Data	-	1850.2 ~ 1909.8 MHz
	WCDMA 850	WCDMA	Voice/Data	-	826.4 ~ 846.6 MHz
	LTE Band 17	LTE	Voice/Data	5/10MHz	706.5 ~ 713.5 MHz
	2.4 GHz W-LAN	802.11b/g/n	Voice/Data	HT20	2412 ~ 2462 MHz
	5.2 GHz W-LAN	802.11a/n/ac	Voice/Data	HT20/VHT20	5180 ~ 5240 MHz
		802.11n/ac	Voice/Data	HT40/VHT40	5190 ~ 5230 MHz
		802.11ac	Voice/Data	VHT80	5210 MHz
	5.3 GHz W-LAN	802.11a/n/ac	Voice/Data	HT20/VHT20	5260 ~ 5320 MHz
		802.11n/ac	Voice/Data	HT40/VHT40	5270 ~ 5310 MHz
		802.11ac	Voice/Data	VHT80	5290 MHz
	5.6 GHz W-LAN	802.11a/n/ac	Voice/Data	HT20/VHT20	5500 ~ 5700 MHz
		802.11n/ac	Voice/Data	HT40/VHT40	5510 ~ 5670 MHz
		802.11ac	Voice/Data	VHT80	5530 MHz
	Bluetooth	-	Data	-	2402 ~ 2480 MHz
RX Frequency Range	GSM 850	GSM/GPRS	Voice/Data	-	869.2 ~ 893.8 MHz
	GSM 1900	GSM/GPRS	Voice/Data	-	1930.2 ~ 1989.8 MHz
	WCDMA 850	WCDMA	Voice/Data	-	871.4 ~ 891.6 MHz
	LTE Band 17	LTE	Voice/Data	5/10MHz	736.5 ~ 743.5 MHz
	2.4 GHz W-LAN	802.11b/g/n	Voice/Data	HT20	2412 ~ 2462 MHz
	5.2 GHz W-LAN	802.11a/n/ac	Voice/Data	HT20/VHT20	5180 ~ 5240 MHz
		802.11n/ac	Voice/Data	HT40/VHT40	5190 ~ 5230 MHz
		802.11ac	Voice/Data	VHT80	5210 MHz
	5.3 GHz W-LAN	802.11a/n/ac	Voice/Data	HT20/VHT200	5260 ~ 5320 MHz
		802.11n/ac	Voice/Data	HT40/VHT40	5270 ~ 5310 MHz
		802.11ac	Voice/Data	VHT80	5290 MHz
	5.6 GHz W-LAN	802.11a/n/ac	Voice/Data	HT20/VHT20	5500 ~ 5700 MHz
		802.11n/ac	Voice/Data	HT40/VHT40	5510 ~ 5670 MHz
		802.11ac	Voice/Data	VHT80	5530 MHz
	Bluetooth	-	Data	-	2402 ~ 2480 MHz

Equipment Class	Band	Reported SAR			
		1g SAR (W/kg)			10g SAR (W/kg)
		Head	Body-Worn	Hotspot	Phablet
PCE	GSM 850	0.52	0.64	-	-
PCE	GPRS 850	0.67	0.97	0.97	
PCE	GSM 1900	0.40	0.60	-	
PCE	GPRS 1900	0.33	0.50	0.50	-
PCE	WCDMA 850	0.53	0.76	0.76	-
PCE	LTE Band 17	< 0.1	0.16	0.16	-
DTS	2.4 GHz W-LAN	0.53	0.13	0.13	-
U-NII-1	5.2 GHz W-LAN	-	-	-	-
U-NII-2A	5.3 GHz W-LAN	0.39	0.30	0.30	-
U-NII-2C	5.6 GHz W-LAN	0.66	0.45	0.45	-
DSS	Bluetooth	0.21	< 0.1	< 0.1	-
Simultaneous SAR per KDB 690783 D01v01r03		1.53	1.46	1.46	-

FCC Equipment Class	Licensed Portable Transmitter Held to Ear (PCE) Part 15 Spread Spectrum Transmitter(DSS) Digital Transmission System(DTS) Unlicensed National Information Infrastructure (UNII)
Date(s) of Tests	2019.11.13 ~ 2019.11.21
Antenna Type	Internal Antenna
Functions	● GSM/GPRS (GPRS Class: 12) supported. * DTM not supported. ● No simultaneous transmission between BT & 2.4GHz WLAN ● Simultaneous transmission between [GSM, WCDMA voice & WLAN], [GPRS, WCDMA & WLAN], [LTE & WLAN]. ● VoIP is supported. ● W-LAN 2.4GHz is supported Hotspot. ● W-LAN 5 GHz is supported Hotspot.

1.2 Power Reduction for SAR

There is no power reduction used for any band/mode implemented in this device for SAR purposes.

1.3 Nominal and Maximum Output Power Specifications

The Nominal and Maximum Output Power Specifications are in section 9 of this test report.

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. A diagram showing the location of the device of the device antenna can be found in JOYDB05_Antenna Location. Since the diagonal dimension of this device is > 160 mm and < 200 mm. it is considered a "phablet".

Mode	Device Sides for SAR Testing					
	Top	Bottom	Front	Rear	Right	Left
GSM/GPRS 850	X	O	O	O	O	X
GSM/GPRS 1900	X	O	O	O	X	O
WCDMA 850	X	O	O	O	O	X
LTE Band 17	X	O	O	O	O	X
2.4G W-LAN	O	X	O	O	O	X
5G W-LAN	O	X	O	O	O	X

Note 1: Particular DUT edges were not required to be evaluated for Hotspot SAR or Phablet SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 648474 D04v01r03.The antenna document shows the distances between the transmit antennas and the edges of the device.

Note 2: O - Test / X - Not test.

1.5 Simultaneous Transmission Capabilities

The Simultaneous Transmission Capabilities are in section 12 of this test report.

1.6 Miscellaneous SAR Test Considerations

(A) BT

Per FCC KDB 447498 D01v06, the 1g SAR exclusion threshold for distances < 50 mm is defined by the following equation:

$$\frac{Max\ Power\ of\ Channel\ (mW)}{Test\ Separation\ Dist\ (mm)} * \sqrt{Frequency(GHz)} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn and hotspot **Bluetooth SAR were not required; [(15/10)*√2.480] = 2.4 (< 3.0)**. Per KDB Publication 447498 D01 v06, the maximum power of the channel was rounded to the nearest mW before calculation.

Per FCC KDB 447498 D01v06, the 10g SAR exclusion threshold for distance < 50 mm is defined by the following equation:

$$\frac{Max\ Power\ of\ Channel\ (mW)}{Test\ Separation\ Dist\ (mm)} * \sqrt{Frequency(GHz)} \leq 7.5$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, phablet **Bluetooth SAR was not required; [(15/5)*√2.480] = 4.8 (< 7.5)**. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

(B) Licensed Transmitter(s)

GSM/GPRS DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS Data.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

Per FCC KDB Publication 648474 D04 v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160 mm and less than 200 mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg.

1.7 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01 (3G SAR Procedures)
- FCC KDB Publication 941225 D05v02r05 (SAR for LTE Devices)
- FCC KDB Publication 941225 D05Av01r02 (LTE Rel.10 KDB Inquiry Sheet)
- FCC KDB Publication 941225 D06v02r01(Hotspot Mode)
- FCC KDB Publication 248227 D01v02r02 (802.11 Wi-Fi SAR)
- FCC KDB Publication 447498 D01v06 (General RF Exposure Guidance)
- FCC KDB Publication 648474 D04v01r03 (Handset SAR)
- FCC KDB Publication 690783 D01v01r03 (SAR Listings on Grants)
- FCC KDB Publication 865664 D01v01r04 (SAR Measurement 100 MHz to 6 GHz)
- FCC KDB Publication 865664 D02v01r02 (RF Exposure Reporting)
- October 2013 TCB Workshop Notes (GPRS testing criteria)
- April 2015 TCB Workshop Notes (Simultaneous transmission summation clarified)
- October 2016 TCB Workshop Notes (Bluetooth Duty Factor)
- April 2019 TCB Workshop Notes (Tissue Simulating Liquids)

1.8 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 11.

2. LTE INFORMATION

LTE Information					
FCC ID	**JOYCB70**				
Form Factor	Mobile Phone				
Frequency Range of each LTE transmission Band	LTE Band 17 (706.5 ~ 713.5 MHz)				
Channel Bandwidths	LTE Band 17 : 5 MHz, 10 MHz				
Channel Number and Frequencies(MHz)	Low	Low-Mid	Mid	Mid-High	High
LTE Band 17: 5 MHz	706.5(23755)	N/A	710.0(23790)[Note1]	N/A	713.5(23825)
LTE Band 17: 10 MHz	709.0(23780)	N/A	710.0(23790)[Note1]	N/A	711.0(23800)
UE Category	UE Cat 4				
Modulations Supported in UL	QPSK, 16QAM, 64QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3~6.2.5? (manufacturer attestation to be provided)	Yes				
A-MPR (Additional MPR) disabled for SAR Testing?	Yes				
LTE Carrier Aggregation	This device does not support both UL and DL carrier aggregation.				

Note(s)
1. LTE B17 can not contain three non-overlapping channels of 10 MHz/5 MHz bandwidth.
Per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

3. INTROCUCTION

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices.

The FCC has adopted the guidelines for evaluating the environmental effects of radio frequency radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave is used for guidance in measuring SAR due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields," NCRP Report No. 86 NCRP, 1986, Bethesda, MD 20814. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ) It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Fig. 3.1)

$$SAR = \frac{d}{dt}\left(\frac{dU}{dm}\right) = \frac{d}{dt}\left(\frac{dU}{\rho dv}\right)$$

Fig. 3.1 SAR Mathematical Equation

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

σ = conductivity of the tissue-simulating material (S/m)
ρ = mass density of the tissue-simulating material (kg/m^3)
E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relations to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.

4. DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4.1) and IEEE1528-2013.

2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.



Figure 4.1
Sample SAR Area Scan

3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4.1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):

   a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4.1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).

   b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.

   c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 mm ± 1 mm	½·δ·ln(2) mm ± 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: Δx_{Area}, Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom}, Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	≤ 1.5·$\Delta z_{Zoom}(n-1)$ mm	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB Publication 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

Table 4.1 Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

5. DEFINITION OF REFERENCE POINTS

5.1 Ear Reference Point

Figure 5.1 shows the front, back and side views of the SAM Twin Phantom. The point"M" is the reference point for the center of the mouth, "LE" is the left ear reference point(ERP), and "RE" is the right ERP. The ERPs are 15 mm posterior to the entrance to the Ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5.1. The plane Passing, through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck- Front) is perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 5.1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning.



Figure 5.1 Close-up side view of ERP

5.2 Handset Reference Points

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the "test device reference point" located along the "vertical centerline" on the front of the device aligned to the "ear reference point" (See Fig. 5.3). The "test device reference point" was than located at the same level as the center of the ear reference point. The test device was positioned so that the "vertical centerline" was bisecting the front surface of the handset at it's top and bottom edges, positioning the "ear reference point" on the outer surface of the both the left and right head phantoms on the ear reference point.

Figure 5.2 Front, back and side view SAM Twin Phantom



Figure 5.3 Handset Vertical Center & Horizontal Line Reference Points

6. TEST CONFIGURATION POSITIONS FOR HANDSETS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity ε = 3 and loss tangent δ = 0.02.

6.2 Positioning for Cheek/Touch

1. The test device was positioned with the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6.1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.

Figure 6.1 Front, Side and Top View of Cheek/Touch Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the ear.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the plane normal to MB-NF including the line MB (reference plane).
4. The phone was hen rotated around the vertical centerline until the phone (horizontal line) was symmetrical was respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the phone contact with the ear, the handset was rotated about the line NF until any point on the handset made contact with a phantom point below the ear (cheek). (See Figure 6.2)

6.3 Positioning for Ear / 15 ° Tilt

With the test device aligned in the “Cheek/Touch Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degree.
2. The phone was then rotated around the horizontal line by 15 degree.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the phone touches the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. The tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6.3).



Figure 6.2 Side view w/relevant markings

Figure 6.3 Front, Side and Top View of Ear/15º Position

6.4 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6.4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.



Figure 6.4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented.
Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.5 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.6 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets (L x W ≥ 9 cm x 5 cm) are based on a composite test separation distance of 10 mm from the front the front, rear and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative test separation distance configuration may be used to support both SAR conditions.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitter often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each KDB Publication 447498 D01v06 procedures. The “Portable Hotspot” feature on the handset was not activated during SAR assessment, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

6.7 Phablet Configurations

For smart phones with a display diagonal > 150 mm or an overall diagonal dimension > 160 mm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the phablets procedures outlined in KDB Publication 648474 D04v01r03 should be applied to evaluate SAR compliance. A device marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance. In addition to the normally required head and body-worn accessory SAR test procedures required for handsets, the UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna ≤ 25mm from that surface or edge, in direct contact with the phantom, for 10g SAR. The UMPC mini-tablet 1g SAR at 5 mm is not required. When hotspot mode applies, 10g SAR is required only for the surfaces and edges with hotspot mode 1g SAR > 1.2 W/kg.

7. RF EXPOSURE LIMITS

Uncontrolled Environment:

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Controlled Environment:

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7.1.SAR Human Exposure Specified in ANSI/IEEE C95.1-1992

	HUMAN EXPOSURE LIMITS	
	General Public Exposure (W/kg) or (mW/g)	Occupational Exposure (W/kg) or (mW/g)
SPATIAL PEAK SAR * (Brain)	1.60	8.00
SPATIAL AVERAGE SAR ** (Whole Body)	0.08	0.40
SPATIAL PEAK SAR *** (Hands / Feet / Ankle / Wrist)	4.00	20.0

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e.as a result of employment or occupation).

8. FCC MEASUREMENT PROCEDURES

Power measurements were performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, When SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as reported SAR. The highest reported SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01.

The device was placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test were evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device was tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviated by more than 5%, the SAR test and drift measurements were repeated.

8.3 SAR Measurement Conditions for WCDMA (UMTS)

8.3.1 Output Power Verification

Maximum output power is measured on the High, Middle and Low channels for each applicable transmission band according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all “1s”.

Maximum output power is verified on the High, Middle and Low channels according to the general, descriptions in section 5.2 of 3GPP TS 34.121 (release 5), using the appropriate RMC with TPC,(transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

8.3.2 Head SAR Measurements for Handsets

SAR for head exposure configurations is measured using the 12.2 kbps RMC with TPC bits configured to all “1s”. SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than 0.25 dB higher than that measured in12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2 AMR with a 3.4 kbps SRB (signaling radio bearer) using the exposure configuration that resulted in the highest SAR for that RF channel in the 12.2 kbps RMC mode.

8.3.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all“1s”.

8.3.4 Release 5 HSDPA Data Devices

The following procedures are applicable to HSDPA data devices operating under 3GPP Release 5. SAR is required for devices in body-worn accessory and other body exposure conditions, including handsets and data modems operating in various electronic devices. HSDPA operates in conjunction with WCDMA and requires an active DPCCH. The default test configuration is to measure SAR in WCDMA with HSDPA remain inactive, to establish a radio link between the test device and a communication test set using a 12.2 kbps RMC configured in Test Loop Mode 1. SAR for HSDPA is selectively measured using the highest reported SAR configuration in WCDMA, with an FRC in H-set 1 and a 12.2 kbps RMC. SAR is selectively confirmed for other physical channel configurations (DPCCH & DPDCHn) according to exposure conditions, device operating capabilities and maximum output power specified for production units, including tune-up tolerance by applying the 3G SAR test reduction procedures. Maximum output power is verified according to the applicable versions of 3GPP TS 34.121. SAR must be measured based on these maximum output conditions and requirements in KDB Publication 447498, with respect to the UE Categories, and explained in the SAR report. When Maximum Power Reduction (MPR) applies, the implementations must be clearly identified in the SAR report to support test results according to Cubic Metric (CM) and, as appropriate, Enhanced MPR (E-MPR) requirements.

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (1)	CM (dB)(2)
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15(3)	15/15(3)	64	12/15(3)	24/15	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

Note 1: Δ_{ACK}, Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$
Note 2: CM = 1 for β_c/β_d =12/15, β_{hs}/β_c=24/15.
Note 3: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to β_c = 11/15 and β_d = 15/15.

Figure 8.1 Table 1

8.3.5 Release 6 HSUPA Data Devices

The following procedures are applicable to HSPA (HSUPA/HSDPA) data devices operating under 3GPP Release 6. SAR is required for devices in body-worn accessory and other body exposure conditions, including handsets and data modems operating in various electronic devices. HSUPA operates in conjunction with WCDMA and HSDPA. SAR is initially measured in WCDMA test configurations with HSPA remain inactive. The default test configuration is to establish a radio link between the test device and a communication test set to configure a 12.2 kbps RMC in Test Loop Mode 1. SAR for HSPA is selectively measured with HS-DPCCH, E-DPCCH and E-DPDCH, all enabled, along with a 12.2 kbps RMC using the highest reported SAR configuration in WCDMA with 12.2 kbps RMC only.
An FRC is configured according to HS-DPCCH Sub-test 1 using H-set 1 and QPSK. HSPA is configured according to E-DCH Sub-test 5 requirements. SAR for other HSPA sub-test configurations is confirmed selectively according to exposure conditions, E-DCH UE Category and maximum output power of production units, including tune-up tolerance by applying the 3G SAR test reduction procedure. Maximum output power is verified according to procedures in applicable versions of 3GPP TS 34.121. SAR must be measured based on these maximum output conditions and requirements in KDB Publication 447498, with respect to the UE Categories for HS-DPCCH and HSPA, and explained in the SAR report. When Maximum Power Reduction (MPR) applies, the implementations must be clearly identified in the SAR report to support test results according to Cubic Metric (CM) and, as appropriate, Enhanced MPR (E-MPR) requirements.

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (1)	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM (2) (dB)	MPR (dB)	AG (4) Index	E-TFCI
1	11/15 (3)	15/15 (3)	64	11/15 (3)	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1}: 47/15 β_{ed2}: 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 (4)	15/15 (4)	64	15/15 (4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK}, Δ_{NACK} and Δ_{CQI} = 8 ⇔ $A_{hs} = \beta_{hs}/\beta_c$ = 30/15 ⇔ β_{hs}= 30/15 *β_c.
Note 2: CM = 1 for β_c/β_d =12/15, β_{hs}/β_c=24/15. For all other combinations of DPDCH, DPCCH, HS- DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.
Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to β_c = 10/15 and β_d = 15/15.
Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to β_c = 14/15 and β_d = 15/15.
Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.
Note 6: β_{ed} cannot be set directly; it is set by Absolute Grant Value.

Figure 8.2 Table 2

8.4 SAR Measurement Conditions for LTE

LTE modes were tested according to FCC KDB 941225 D05v02r05 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR. The call simulator was used for LTE output power measurement and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.4.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.4.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36. 101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

8.4.3 A-MPR

A-MPR (Addition MPR) has been disable for all SAR tests by setting NS=01 on the base station simulator.

8.4.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r05:

a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
   i. The required channel and offset combination with the highest maximum output power is required for SAR.
   ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channel is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
   iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to 0.5 dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.4.5 64QAM uplink

(1) Per KDB 941225 D05 V02r05, we'll measure conducted powers per Section 5.1 for all uplink modulations (QPSK, 16QAM, 64QAM) and include in the test report.

(2) From these power measurements, we will apply the procedures in Section 5.2.4 ("Higher Order Modulations") to determine SAR test reduction for 16QAM and 64QAM test cases.

8.5 SAR Testing with 802.11 Transmitters

The normal network operating configurations are not suitable for measuring the SAR of 802.11 b/g/n transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227D01v02r02 for more details.

8.5.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the in the transmission, a maximum transmission duty factor of 92-96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.5.2 U-NII and U-NII-2A

For devices that operate in only one of the U-NII-1 and U-NII-2A bands, the normally required SAR procedures for OFDM configurations are applied. For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following, with respect to the highest reported SAR and maximum output power specified for production units. The procedures are applied independently to each exposure configuration; for example, head, body, hotspot mode etc.

1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.
2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, each band is tested independently for SAR.

8.5.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements.

When Terminal Doppler Weather Rader (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification.

Unless band gap channels are permanently disabled, SAR must be considered for these channels. When band gap channels are disabled, each band is tested independently according to the normally required OFDM SAR measurements and probe calibration frequency points requirements.

8.5.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all position in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR position until the reported SAR result is ≤ 0.8 W/kg or all test position are measured.

8.5.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
2) When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

8.5.6 OFDM Transmission Mode and SAR Test Channel Selection

For the 2.4 GHz and 5 GHz bands, when the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a and 802.11n or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 80211n or 802.11g then 802.11n is used for SAR measurement. When the maximum output power ware the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

8.5.7 Initial Test Configuration Procedure

For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, and lowest data rate. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required.
Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured.

8.5.8 Subsequent Test Configuration Procedures

For OFDM configurations, in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure, when applicable. When the highest reported SAR for the initial test configuration, adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power is ≤ 1.2 W/kg, no additional SAR testing for the subsequent test configurations is required.

9. RF CONDUCTED POWERS

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

9.1 GSM Nominal and Maximum Output Power Spec and Conducted Powers

Band & Mode		Voice[dBm]	Burst Average GMSK [dBm]			
		1 TX Slot	1 TX Slot	2 TX Slot	3 TX Slot	4 TX Slot
GSM/GPRS 850	Maximum	33.90	33.90	30.90	29.10	27.90
	Nominal	32.50	32.50	29.50	27.70	26.50
GSM/GPRS 1900	Maximum	30.90	30.90	27.90	26.10	24.90
	Nominal	29.50	29.50	26.50	24.70	23.50

Table 9.1.1 GSM Nominal and Maximum Output Power Spec

Band	Channel	Maximum Burst-Averaged Output Power(dBm)				
		Voice	GPRS Data (GMSK)			
		GSM CS 1 Slot	GPRS 1 TX Slot	GPRS 2 TX Slot	GPRS 3 TX Slot	GPRS 4 TX Slot
GSM850	128	32.60	32.60	29.80	27.90	27.20
	190	33.90	33.00	30.30	28.50	27.30
	251	32.70	32.70	29.90	27.90	26.90
PCS 1900	512	30.00	30.00	27.30	25.40	24.30
	661	29.90	29.90	27.30	25.50	24.50
	810	29.90	29.90	27.40	25.60	24.40
Band	**Channel**	**Calculated Maximum Frame-Averaged Output Power(dBm)**				
		Voice	**GPRS Data (GMSK)**			
		GSM CS 1 Slot	**GPRS 1 TX Slot**	**GPRS 2 TX Slot**	**GPRS 3 TX Slot**	**GPRS 4 TX Slot**
GSM850	128	23.57	23.57	23.78	23.64	24.19
	190	24.87	23.97	24.28	24.24	24.29
	251	23.67	23.67	23.88	23.64	23.89
PCS 1900	512	20.97	20.97	21.28	21.14	21.29
	661	20.87	20.87	21.28	21.24	21.49
	810	20.87	20.87	21.38	21.34	21.39
GSM850	**Frame Avg. Targets:**	23.47	23.47	23.48	23.44	23.49
PCS 1900		20.47	20.47	20.48	20.44	20.49

Note:

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. GPRS (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.

GPRS Multislot class: 12 (max 4 TX Uplink slots)
DTM Multislot Class: N/A

Figure 9.1 Power Measurement Setup

9.2 WCDMA Nominal and Maximum Output Power Spec and Conducted Powers

3GPP Release Version	Mode			Cellular Band (dBm)	3GPP MPR (dB)
99	WCDMA	Voice	Maximum	24.2	-
			Nominal	23.7	
5	HSDPA	Subtest 1	Maximum	23.2	0
			Nominal	22.7	
5		Subtest 2	Maximum	23.2	0
			Nominal	22.7	
5		Subtest 3	Maximum	22.7	0.5
			Nominal	22.2	
5		Subtest 4	Maximum	22.7	0.5
			Nominal	22.2	
6	HSUPA	Subtest 1	Maximum	23.2	0
			Nominal	22.7	
6		Subtest 2	Maximum	21.2	2
			Nominal	20.7	
6		Subtest 3	Maximum	22.2	1
			Nominal	21.7	
6		Subtest 4	Maximum	21.2	2
			Nominal	20.7	
6		Subtest 5	Maximum	23.2	0
			Nominal	22.7	

Table 9.2.1 WCDMA Nominal and Maximum Output Power Spec

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band (dBm)			3GPP MPR (dB)
			4132	4183	4233	
99	WCDMA	12.2 kbps RMC	23.51	23.63	23.57	-
99		12.2 kbps AMR	23.52	23.63	23.57	-
5	HSDPA	Subtest 1	22.55	22.66	22.59	0
5		Subtest 2	22.53	22.64	22.56	0
5		Subtest 3	22.03	22.15	22.07	0.5
5		Subtest 4	22.02	22.14	22.05	0.5
6	HSUPA	Subtest 1	21.56	21.67	21.60	0
6		Subtest 2	20.56	20.67	20.59	2
6		Subtest 3	21.52	21.65	21.56	1
6		Subtest 4	20.07	20.17	20.12	2
6		Subtest 5	21.50	21.62	21.54	0

Table 9.2.2 WCDMA Conducted Power

WCDMA SAR was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.

The manufacturer declares that the HSDPA and HSUPA transmitter's power will not exceed the R99 maximum transmit power in devices based on Qualcomm's HSPA chipset solutions.

Figure 9.2 Power Measurement Setup

9.3 LTE Nominal and Maximum Output Power Spec and Conducted Powers

Band & Mode		Modulated Average[dBm]
LTE Band 17	Maximum	24.2
	Nominal	23.0

Table 9.3.1.1 Nominal and Maximum Output Power Spec

1) LTE Band 17

LTE Band 17 Conducted Power– 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel 23790 (710.0 MHz) Conducted Power (dBm)	MPR Allowed Per 3GPP(dB)	MPR (dB)
QPSK	**1**	**0**	**22.91**	≤ 1	0
	1	25	22.85		
	1	49	22.77		
	25	0	22.00		1
	25	12	21.91		
	25	**25**	**22.02**		
	50	0	22.02		1
16QAM	1	0	22.03	≤ 1	1
	1	25	22.05		
	1	49	21.96		
	25	0	21.02	≤ 2	2
	25	12	20.94		
	25	25	21.02		
	50	0	21.03		2
64QAM	1	0	20.95	≤ 2	2
	1	25	20.91		
	1	49	20.87		
	25	0	20.03	≤ 3	3
	25	12	19.95		
	25	25	20.05		
	50	0	20.01		

Table 9.3.1.2 LTE Conducted Power

Note : LTE B17 can not contain three non-overlapping channels of 10 MHz bandwidth.
Per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

LTE Band 17 Conducted Power– 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel 23790 (710.0 MHz) Conducted Power (dBm)	MPR Allowed Per 3GPP(dB)	MPR (dB)
QPSK	1	0	22.78	≤ 1	0
	1	12	22.82		
	1	24	22.75		
	12	0	21.86		1
	12	6	21.87		
	12	13	21.87		
	25	0	21.86		1
16QAM	1	0	21.89	≤ 1	1
	1	12	21.99		
	1	24	21.81		
	12	0	20.89	≤ 2	2
	12	6	20.91		
	12	13	20.87		
	25	0	20.88		2
64QAM	1	0	20.81	≤ 2	2
	1	12	20.87		
	1	24	20.88		
	12	0	19.91	≤ 3	3
	12	6	19.91		
	12	13	19.92		
	15	0	19.88		

Table 9.3.1.3 LTE Conducted Power

Note : LTE B17 can not contain three non-overlapping channels of 5 MHz bandwidth.
Per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

9.4 WLAN Nominal and Maximum Output Power Spec and Conducted Powers

Band (GHz)	Mode	Modulated Average[dBm]	
		Maximum	Nominal
2.4	802.11b	16.0	14.0
	802.11g	13.0	11.0
	802.11n	13.0	11.0

Table 9.4.1 Nominal and Maximum Output Power Spec

Mode	Freq. (MHz)	Channel	IEEE 802.11 (2.4 GHz) Conducted Power [dBm]
802.11b	**2412**	**1**	15.88
	2437	6	15.73
	2462	11	15.75
802.11g	2412	1	12.66
	2437	6	12.71
	2462	11	12.77
802.11n (HT-20)	2412	1	12.96
	2437	6	12.77
	2462	11	12.97

Table 9.4.2 IEEE 802.11 Average RF Power

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, duo to an even number of channels, both channels were measured.
- Output Power and SAR is not required for 802.11 g/n HT20/ac VHT20 channels when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjust SAR is ≤ 1.2 W/kg.
- The underlined data rate and channel above were tested for SAR.

The average output powers of this device were tested by below configuration.



Figure 9.4.1 Power Measurement Setup

Band (GHz)	Mode	Modulated Average[dBm]	
		Maximum	Nominal
5 (UNII)	802.11a	13.0	11.0
	802.11n/ac (20MHz)	13.0	11.0
	802.11n/ac (40MHz)	13.0	11.0
	802.11ac (80MHz)	13.0	11.0

Table 9.4.3 Nominal and Maximum Output Power Spec

Mode	Freq. (MHz)	Channel	IEEE 802.11a (5 GHz) Conducted Power [dBm]
802.11a	5180	36	12.69
	5200	40	12.97
	5220	44	12.93
	5240	48	12.65
	5260	52	12.58
	5280	56	12.87
	5300	60	12.60
	5320	64	12.92
	5500	100	12.84
	5600	120	12.92
	5660	132	12.97
	5700	140	12.92

Table 9.4.4 IEEE 802.11a Average RF Power

Mode	Freq. (MHz)	Channel	IEEE 802.11n HT20 (5 GHz) Conducted Power [dBm]
802.11n (HT-20)	5180	36	12.64
	5200	40	12.82
	5220	44	12.80
	5240	48	12.73
	5260	52	12.98
	5280	56	12.79
	5300	60	12.71
	5320	64	12.78
	5500	100	12.72
	5600	120	12.92
	5660	132	12.74
	5700	140	12.69

Table 9.4.5 IEEE 802.11n HT20 Average RF Power

Mode	Freq. (MHz)	Channel	IEEE 802.11ac VHT20 (5 GHz) Conducted Power [dBm]
802.11ac (VHT-20)	5180	36	12.97
	5200	40	12.94
	5220	44	12.65
	5240	48	12.66
	5260	52	12.83
	5280	56	12.81
	5300	60	12.76
	5320	64	12.85
	5500	100	12.67
	5600	120	12.91
	5660	132	12.77
	5700	140	12.89

Table 9.4.6 IEEE 802.11ac VHT20 Average RF Power

Mode	Freq. (MHz)	Channel	IEEE 802.11n HT40 (5 GHz) Conducted Power [dBm]
802.11n (HT-40)	5190	38	12.62
	5230	46	12.52
	5270	54	12.57
	5310	62	12.58
	5510	102	12.78
	5590	118	12.61
	5670	134	12.75

Table 9.4.7 IEEE 802.11n HT40 Average RF Power

Mode	Freq. (MHz)	Channel	IEEE 802.11ac VHT40 (5 GHz) Conducted Power [dBm]
802.11ac (VHT-40)	5190	38	12.75
	5230	46	12.90
	5270	54	12.63
	5310	62	12.60
	5510	102	12.96
	5590	118	12.58
	5670	134	12.75

Table 9.4.8 IEEE 802.11ac VHT40 Average RF Power

Mode	Freq. (MHz)	Channel	IEEE 802.11ac VHT80 (5 GHz) Conducted Power [dBm]
802.11ac (VHT-80)	5210	42	12.85
	5290	**58**	**12.90**
	5530	106	12.58
	5610	**122**	**12.83**
	5690	138	12.81

Table 9.4.9 IEEE 802.11ac VHT80 Average RF Power

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, duo to an even number of channels, both channels were measured.
- Output Power and SAR is not required for 802.11 g/n HT20/ac VHT20 channels when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjust SAR is ≤ 1.2 W/kg.
- The underlined data rate and channel above were tested for SAR.

The average output powers of this device were tested by below configuration.

Figure 9.4.2 Power Measurement Setup

9.5 Bluetooth Conducted Powers

Frame Modulated Average[dBm]		
Bluetooth 1 Mbps	Maximum	11.80
	Nominal	10.80
Bluetooth 2 Mbps	Maximum	8.50
	Nominal	7.50
Bluetooth 3 Mbps	Maximum	8.50
	Nominal	7.50
Bluetooth (LE)	Maximum	6.80
	Nominal	5.80

Table 9.5.1 Nominal and Maximum Output Power Spec (Frame)

Channel	Frequency (MHz)	Frame AVG Output Power (1Mbps)) (dBm)	Frame AVG Output Power (2Mbps) (dBm)	Frame AVG Output Power (3Mbps) (dBm)
Low	2402	8.27	5.46	6.12
Mid	2441	9.38	6.73	7.84
High	2480	9.55	5.99	7.53

Table 9.5.2 Bluetooth Burst and Frame Average RF Power

Channel	Frequency (MHz)	Frame AVG Output Power(LE) (dBm)
Low	2402	2.31
Mid	2440	3.74
High	2480	3.09

Table 9.5.3 Bluetooth LE Burst and Frame Average RF Power

- **Bluetooth Conducted Powers procedures**

1. Bluetooth (BDR, EDR)
   1) Enter DUT mode in EUT and operate it.
      When it operating, The EUT is transmitting at maximum power level and duty cycle fixed.
   2) Instruments and EUT were connected like Figure 9.5.1(A).
   3) The maximum output powers of BDR(1 Mbps), EDR(2, 3 Mbps) and each frequency were set by a Bluetooth Tester.
   4) Power levels were measured by a Power Meter.

2. Bluetooth (LE)
   1) Enter LE mode in EUT and operate it.
      When it operating, The EUT is transmitting at maximum power level and duty cycle fixed.
   2) Instruments and EUT were connected like Figure 9.5.1(B).
   3) The average conducted output powers of LE and each frequency can measurement according to setting program in EUT.
   4) Power levels were measured by a Power Meter.



Figure 9.5.1 Average Power Measurement Setup

10. SYSTEM VERIFICATION

10.1 Tissue Verification

MEASURED TISSUE PARAMETERS										
Date(s)	Tissue Type	Ambient Temp.[°C]	Liquid Temp.[°C]	Measured Frequency [MHz]	Target Dielectric Constant, εr	Target Conductivity, σ (S/m)	Measured Dielectric Constant, εr	Measured Conductivity, σ (S/m)	Er Deviation [%]	σ Deviation [%]
Nov. 13. 2019	750 Head	21.2	21.6	710.0	42.113	0.887	43.733	0.864	3.85	-2.59
				750.0	41.900	0.890	43.203	0.910	3.11	2.25
Nov. 20. 2019	835 Head	21.4	21.2	824.2	41.552	0.899	43.142	0.883	3.83	-1.78
				835.0	41.500	0.900	43.032	0.894	3.69	-0.67
				836.6	41.500	0.901	43.016	0.896	3.65	-0.55
				848.8	41.500	0.914	42.893	0.908	3.36	-0.66
Nov. 21. 2019	835 Head	22.8	22.5	826.4	41.542	0.899	41.650	0.881	0.26	-2.00
				835.0	41.500	0.900	41.550	0.890	0.12	-1.11
				836.6	41.500	0.901	41.527	0.891	0.07	-1.11
				846.6	41.500	0.912	41.414	0.900	-0.21	-1.32
Nov. 19. 2019	1900 Head	21.9	22.1	1850.2	40.000	1.400	39.883	1.350	-0.29	-3.57
				1880.0	40.000	1.400	39.824	1.376	-0.44	-1.71
				1900.0	40.000	1.400	39.672	1.391	-0.82	-0.64
				1909.8	40.000	1.400	39.419	1.391	-1.45	-0.64
Nov. 18. 2019	2450 Head	22.4	22.5	2402.0	39.282	1.757	40.068	1.762	2.00	0.28
				2412.0	39.265	1.766	40.035	1.773	1.96	0.40
				2437.0	39.222	1.788	39.954	1.802	1.87	0.78
				2441.0	39.215	1.792	39.940	1.807	1.85	0.84
				2450.0	39.200	1.800	39.914	1.817	1.82	0.94
				2462.0	39.184	1.813	39.881	1.831	1.78	0.99
				2472.0	39.171	1.823	39.885	1.841	1.82	0.99
				2480.0	39.160	1.832	39.827	1.851	1.70	1.04
Nov. 20. 2019	5300 Head	20.8	20.5	5260.0	35.940	4.720	36.420	4.636	1.34	-1.78
				5270.0	35.930	4.730	36.401	4.648	1.31	-1.73
				5280.0	35.920	4.740	36.386	4.658	1.30	-1.73
				5290.0	35.910	4.750	36.368	4.668	1.28	-1.73
				5300.0	35.900	4.760	36.344	4.682	1.24	-1.64
				5310.0	35.890	4.770	36.331	4.700	1.23	-1.47
				5320.0	35.880	4.780	36.328	4.714	1.25	-1.38
Nov. 21. 2019	5600 Head	21.5	21.4	5500.0	35.650	4.965	36.968	5.043	3.70	1.57
				5510.0	35.635	4.976	36.929	5.053	3.63	1.55
				5530.0	35.605	4.997	36.866	5.090	3.54	1.86
				5550.0	35.575	5.018	36.864	5.117	3.62	1.97
				5580.0	35.530	5.049	36.847	5.148	3.71	1.96
				5590.0	35.515	5.060	36.843	5.158	3.74	1.94
				5600.0	35.500	5.070	36.827	5.163	3.74	1.83
				5610.0	35.490	5.080	36.809	5.171	3.72	1.79
				5660.0	35.440	5.130	36.667	5.241	3.46	2.16
				5670.0	35.430	5.140	36.659	5.253	3.47	2.20
				5690.0	35.410	5.160	36.655	5.280	3.52	2.33
				5700.0	35.400	5.170	36.656	5.290	3.55	2.32

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB 865664 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

Measurement Procedure for Tissue verification:

1) The network analyzer and probe system was configured and calibrated.
2) The probe was immersed in the sample which was placed in a nonmetallic container. Trapped air bubbles beneath the flange were minimized by placing the probe at a slight angle.
3) The complex admittance with respect to the probe aperture was measured
4) The complex relative permittivity , for example from the below equation (Pournaropoulos and Misra):

$$Y = \frac{j2\omega\varepsilon_r\varepsilon_0}{[\ln(b/a)]^2}\int_a^b\int_a^b\int_0^\pi \cos\phi' \frac{\exp\left[-j\omega r(\mu_0\varepsilon_r'\varepsilon_0)^{1/2}\right]}{r} d\phi' d\rho' d\rho$$

where Y is the admittance of the probe in contact with the sample, the primed and unprimed coordinates refer to source and observation points, respectively, $r^2 = \rho^2 + \rho'^2 - 2\rho\rho'\cos\phi'$, ω is the angular frequency, and $j = \sqrt{-1}$.

10.2 Test System Verification

Prior to assessment, the system is verified to the ± 10 % of the specifications at using the SAR Dipole kit(s). (Graphic Plots Attached)

Table 10.2.1 System Verification Results (1g)

SYSTEM DIPOLE VERIFICATION TARGET & MEASURED												
SAR System #	Freq. [MHz]	SAR Dipole kits	Date(s)	Tissue Type	Ambient Temp. [°C]	Liquid Temp. [°C]	Probe S/N	Input Power (mW)	1 W Target SAR_{1g} (W/kg)	Measured SAR_{1g} (W/kg)	1 W Normalized SAR_{1g} (W/kg)	Deviation [%]
A	750	D750V3, SN:1049	Nov. 13. 2019	Head	21.2	21.6	3328	250	8.38	2.22	8.88	5.97
A	835	D835V2, SN:464	Nov. 20. 2019	Head	21.4	21.2	3328	250	9.59	2.35	9.40	-1.98
A	835	D835V2, SN:464	Nov. 21. 2019	Head	22.8	22.5	3328	250	9.59	2.31	9.24	-3.65
A	1900	D1900V2, SN:5d029	Nov. 19. 2019	Head	21.9	22.1	3328	100	40.4	4.01	40.10	-0.74
B	2450	D2450V2, SN: 726	Nov. 18. 2019	Head	22.4	22.5	7368	100	51.2	5.17	51.70	0.98
B	5300	D5GHzV2, SN:1103	Nov. 20. 2019	Head	20.8	20.5	7368	100	82.4	8.01	80.10	-2.79
B	5500	D5GHzV2, SN:1103	Nov. 21. 2019	Head	21.5	21.4	7368	100	84.0	8.45	84.50	0.60

Note1 : System Verification was measured with input 250 mW, 100 mW and normalized to 1W.
Note2 : Full system validation status and results can be found in Attachment 3.



Figure 10.1 Dipole Verification Test Setup Diagram & Photo

11. SAR TEST RESULTS

11.1 Head SAR Results

Table 11.1.1 GSM/GPRS 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY MHz	FREQUENCY Ch	Mode/ Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	# of Time Slots	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
836.6	190	GSM850	GSM	33.90	33.90	0.000	Left Touch	FCC #1	1	1:8.3	0.518	1.000	0.518	
836.6	190	GSM850	GSM	33.90	33.90	0.040	Right Touch	FCC #1	1	1:8.3	0.519	1.000	**0.519**	A1
836.6	190	GSM850	GSM	33.90	33.90	0.150	Left Tilt	FCC #1	1	1:8.3	0.298	1.000	0.298	
836.6	190	GSM850	GSM	33.90	33.90	0.090	Right Tilt	FCC #1	1	1:8.3	0.286	1.000	0.286	
836.6	190	GSM850	GPRS	27.90	27.30	0.030	Left Touch	FCC #1	4	1:2.075	0.578	1.148	0.664	
836.6	190	GSM850	GPRS	27.90	27.30	0.170	Right Touch	FCC #1	4	1:2.075	0.583	1.148	**0.669**	A2
836.6	190	GSM850	GPRS	27.90	27.30	0.120	Left Tilt	FCC #1	4	1:2.075	0.322	1.148	0.370	
836.6	190	GSM850	GPRS	27.90	27.30	0.050	Right Tilt	FCC #1	4	1:2.075	0.308	1.148	0.354	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								Head 1.6 W/kg (mW/g) averaged over 1 gram						

Table 11.1.2 PCS/GPRS 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY MHz	FREQUENCY Ch	Mode/ Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	# of Time Slots	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
1880.0	661	PCS1900	PCS	30.90	29.90	0.110	Left Touch	FCC #1	1	1:8.3	0.321	1.259	**0.404**	A3
1880.0	661	PCS1900	PCS	30.90	29.90	0.170	Right Touch	FCC #1	1	1:8.3	0.187	1.259	0.235	
1880.0	661	PCS1900	PCS	30.90	29.90	0.110	Left Tilt	FCC #1	1	1:8.3	0.188	1.259	0.237	
1880.0	661	PCS1900	PCS	30.90	29.90	0.090	Right Tilt	FCC #1	1	1:8.3	0.114	1.259	0.144	
1880.0	661	PCS1900	GPRS	24.90	24.50	0.070	Left Touch	FCC #1	4	1:2.075	0.300	1.096	**0.329**	A4
1880.0	661	PCS1900	GPRS	24.90	24.50	0.040	Right Touch	FCC #1	4	1:2.075	0.174	1.096	0.191	
1880.0	661	PCS1900	GPRS	24.90	24.50	0.080	Left Tilt	FCC #1	4	1:2.075	0.178	1.096	0.195	
1880.0	661	PCS1900	GPRS	24.90	24.50	0.070	Right Tilt	FCC #1	4	1:2.075	0.102	1.096	0.112	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								Head 1.6 W/kg (mW/g) averaged over 1 gram						

Table 11.1.3 WCDMA 850 Head SAR

MEASUREMENT RESULTS													
FREQUENCY MHz	FREQUENCY Ch	Mode/ Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
836.6	4183	WCDMA 850	RMC	24.20	23.63	0.160	Left Touch	FCC #1	1:1	0.462	1.140	**0.527**	A5
836.6	4183	WCDMA 850	RMC	24.20	23.63	0.190	Right Touch	FCC #1	1:1	0.242	1.140	0.276	
836.6	4183	WCDMA 850	RMC	24.20	23.63	-0.100	Left Tilt	FCC #1	1:1	0.152	1.140	0.173	
836.6	4183	WCDMA 850	RMC	24.20	23.63	0.140	Right Tilt	FCC #1	1:1	0.133	1.140	0.152	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								Head 1.6 W/kg (mW/g) averaged over 1 gram					

Table 11.1.4 LTE Band 17 Head SAR

MEASUREMENT RESULTS																	
FREQUENCY MHz	FREQUENCY Ch	Mode/ Band	BW [MHz]	Max Allowed Power [dBm]	Cond. PWR [dBm]	Drift Power [dB]	MPR	Position	Device Serial Number	Mod.	RB Size	RB Offs.	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
710.0	23790	LTE B17	10	24.20	22.91	0.030	0	Left Touch	FCC #1	QPSK	1	0	1:1	0.059	1.346	0.079	
710.0	23790	LTE B17	10	23.20	22.02	0.080	1	Left Touch	FCC #1	QPSK	25	0	1:1	0.053	1.312	0.070	
710.0	23790	LTE B17	10	24.20	22.91	0.190	0	Right Touch	FCC #1	QPSK	1	0	1:1	0.060	1.346	**0.081**	A6
710.0	23790	LTE B17	10	23.20	22.02	0.190	1	Right Touch	FCC #1	QPSK	25	0	1:1	0.052	1.312	0.068	
710.0	23790	LTE B17	10	24.20	22.91	0.050	0	Left Tilt	FCC #1	QPSK	1	0	1:1	0.031	1.346	0.042	
710.0	23790	LTE B17	10	23.20	22.02	0.190	1	Left Tilt	FCC #1	QPSK	25	0	1:1	0.029	1.312	0.038	
710.0	23790	LTE B17	10	24.20	22.91	0.130	0	Right Tilt	FCC #1	QPSK	1	0	1:1	0.035	1.346	0.047	
710.0	23790	LTE B17	10	23.20	22.02	0.180	1	Right Tilt	FCC #1	QPSK	25	0	1:1	0.031	1.312	0.041	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure									Head 1.6 W/kg (mW/g) averaged over 1 gram								

Table 11.1.5 DTS Head SAR

MEASUREMENT RESULTS															
FREQUENCY MHz	FREQUENCY Ch	Mode (Antenna)	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
2412.0	1	802.11b	16.00	15.88	0.110	Left Touch	FCC #2	0.514	1	96.1	0.494	1.028	1.041	**0.528**	A7
2412.0	1	802.11b	16.00	15.88	0.090	Right Touch	FCC #2	0.224	1	96.1	0.204	1.028	1.041	0.218	
2412.0	1	802.11b	16.00	15.88	-0.050	Left Tilt	FCC #2	0.423	1	96.1	0.426	1.028	1.041	0.456	
2412.0	1	802.11b	16.00	15.88	0.110	Right Tilt	FCC #2	0.211	1	96.1	0.195	1.028	1.041	0.209	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								Head 1.6 W/kg (mW/g) averaged over 1 gram							

Adjusted SAR results for OFDM SAR												
FREQUENCY MHz	FREQUENCY Ch	Mode/ Antenna	Service	Maximum Allowed Power [dBm]	1g Scaled SAR (W/kg)	FREQUENCY [MHz]	Mode	Service	Maximum Allowed Power [dBm	Ratio of OFDM to DSSS	1g Adjusted SAR (W/kg)	Determine OFDM SAR
2412.0	1	802.11b	DSSS	16.0	0.528	2462.0	802.11g	OFDM	13.0	0.501	**0.265**	X
2412.0	1	802.11b	DSSS	16.0	0.528	2462.0	802.11n	OFDM	13.0	0.501	**0.265**	X
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure						Head 1.6 W/kg (mW/g) averaged over 1 gram						

Note: SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

Table 11.1.6 UNII Head SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode (Antenna)	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch														
5290.0	58	802.11ac	13.00	12.90	-0.140	Left Touch	FCC #2	0.346	MCS0	89.9	0.346	1.023	1.112	**0.394**	A8
5290.0	58	802.11ac	13.00	12.90	0.080	Right Touch	FCC #2	0.170	MCS0	89.9	0.175	1.023	1.112	0.199	
5290.0	58	802.11ac	13.00	12.90	0.000	Left Tilt	FCC #2	0.287	MCS0	89.9	0.288	1.023	1.112	0.328	
5290.0	58	802.11ac	13.00	12.90	0.140	Right Tilt	FCC #2	0.096	MCS0	89.9	0.089	1.023	1.112	0.101	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								**Head 1.6 W/kg (mW/g)** averaged over 1 gram							

Adjusted SAR results for UNII-1 and UNII-2A SAR												
FREQUENCY		Mode/ Antenna	Service	Maximum Allowed Power [dBm]	1g Scaled SAR (W/kg)	FREQUENCY [MHz]	Mode	Service	Maximum Allowed Power [dBm	Adjusted Factor	1g Adjusted SAR (W/kg)	**SAR for** the band with lower maximum output power
MHz	Ch											
5290.0	58	802.11ac	OFDM	13.0	0.394	5210	802.11ac	OFDM	13.0	1.000	**0.394**	X
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure						**Head 1.6 W/kg (mW/g)** averaged over 1 gram						

Note: U-NII-1 and U-NII-2A Bands: When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration.

Table 11.1.7 UNII Head SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode (Antenna)	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch														
5610.0	122	802.11ac	13.00	12.83	0.180	Left Touch	FCC #2	0.636	MCS0	89.9	0.570	1.040	1.112	**0.659**	A9
5610.0	122	802.11ac	13.00	12.83	0.150	Right Touch	FCC #2	0.301	MCS0	89.9	0.307	1.040	1.112	0.355	
5610.0	122	802.11ac	13.00	12.83	0.050	Left Tilt	FCC #2	0.558	MCS0	89.9	0.494	1.040	1.112	0.571	
5610.0	122	802.11ac	13.00	12.83	0.030	Right Tilt	FCC #2	0.299	MCS0	89.9	0.301	1.040	1.112	0.348	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								**Head 1.6 W/kg (mW/g)** averaged over 1 gram							

Table 11.1.8 Bluetooth Head SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Rate [Mbps]	Duty Cycle (%)	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch													
2441.0	39	Bluetooth	11.80	9.38	0.030	Left Touch	FCC #2	1	76.8	0.091	1.746	1.302	**0.207**	A10
2441.0	39	Bluetooth	11.80	9.38	0.190	Right Touch	FCC #2	1	76.8	0.035	1.746	1.302	0.080	
2441.0	39	Bluetooth	11.80	9.38	0.020	Left Tilt	FCC #2	1	76.8	0.069	1.746	1.302	0.157	
2441.0	39	Bluetooth	11.80	9.38	0.140	Right Tilt	FCC #2	1	76.8	0.032	1.746	1.302	0.073	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								**Head 1.6 W/kg (mW/g)** averaged over 1 gram							

11.2 Standalone Body-Worn SAR Worn SAR Results

Table 11.2.1 GSM/PCS/GPRS/WCDMA Body-Worn SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/ Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Spacing [Side]	Device Serial Number	# of Time Slots	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
MHz	Ch													
836.6	190	GSM850	GSM	33.90	33.90	-0.060	10 mm [Front]	FCC #1	1	1:8.3	0.465	1.000	0.465	
836.6	190	GSM850	GSM	33.90	33.90	0.020	10 mm [Rear]	FCC #1	1	1:8.3	0.635	1.000	**0.635**	A11
836.6	190	GSM850	GPRS	27.90	27.30	0.000	10 mm [Front]	FCC #1	4	1:2.075	0.538	1.148	0.618	
824.2	128	GSM850	GPRS	27.90	27.20	-0.020	10 mm [Rear]	FCC #1	4	1:2.075	0.610	1.175	0.717	
836.6	190	GSM850	GPRS	27.90	27.30	-0.060	10 mm [Rear]	FCC #1	4	1:2.075	0.795	1.148	0.913	
848.8	251	GSM850	GPRS	27.90	26.90	0.030	10 mm [Rear]	FCC #1	4	1:2.075	0.767	1.259	**0.966**	A12
1880.0	661	PCS1900	PCS	30.90	29.90	-0.040	10 mm [Front]	FCC #1	1	1:8.3	0.480	1.259	**0.604**	A13
1880.0	661	PCS1900	PCS	30.90	29.90	-0.010	10 mm [Rear]	FCC #1	1	1:8.3	0.458	1.259	0.577	
1880.0	661	PCS1900	GPRS	24.90	24.50	0.030	10 mm [Front]	FCC #1	4	1:2.075	0.453	1.096	**0.496**	A14
1880.0	661	PCS1900	GPRS	24.90	24.50	0.010	10 mm [Rear]	FCC #1	4	1:2.075	0.428	1.096	0.469	
836.6	4183	WCDMA 850	RMC	24.20	23.63	-0.010	10 mm [Front]	FCC #1	N/A	1:1	0.664	1.140	**0.757**	A15
836.6	4183	WCDMA 850	RMC	24.20	23.63	0.000	10 mm [Rear]	FCC #1	N/A	1:1	0.629	1.140	0.717	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								Body 1.6 W/kg (mW/g) averaged over 1 gram						

Table 11.2.2 LTE B17 Body-Worn SAR

MEASUREMENT RESULTS																	
FREQUENCY		Mode/ Band	BW [MHz]	Max Allowed Power [dBm]	Cond. PWR [dBm]	Drift Power [dB]	MPR	Position	Device Serial Number	Mod.	RB Size	RB Offs.	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
MHz	Ch																
710.0	23790	LTE B17	10	24.20	22.91	-0.080	0	10 mm [Front]	FCC #1	QPSK	1	0	1:1	0.090	1.346	0.121	
710.0	23790	LTE B17	10	23.20	22.02	0.080	1	10 mm [Front]	FCC #1	QPSK	25	0	1:1	0.078	1.312	0.102	
710.0	23790	LTE B17	10	24.20	22.91	0.050	0	10 mm [Rear]	FCC #1	QPSK	1	0	1:1	0.116	1.346	**0.156**	A16
710.0	23790	LTE B17	10	23.20	22.02	0.020	1	10 mm [Rear]	FCC #1	QPSK	25	0	1:1	0.102	1.312	0.134	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure									Body 1.6 W/kg (mW/g) averaged over 1 gram								

Table 11.2.3 DTS Body-Worn SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	SAR (W/kg)	Plots #
MHz	Ch														
2412.0	1	802.11b	16.00	15.88	0.060	10 mm [Front]	FCC #2	0.108	1	96.1	0.101	1.028	1.041	0.108	
2412.0	1	802.11b	16.00	15.88	0.030	10 mm [Rear]	FCC #2	0.137	1	96.1	0.125	1.028	1.041	**0.134**	A17
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								Body 1.6 W/kg (mW/g) averaged over 1 gram							

Adjusted SAR results for OFDM SAR												
FREQUENCY		Mode/ Antenna	Service	Maximum Allowed Power [dBm]	1g Scaled SAR (W/kg)	FREQUENCY [MHz]	Mode	Service	Maximum Allowed Power [dBm	Ratio of OFDM to DSSS	1g Adjusted SAR (W/kg)	Determine OFDM SAR
MHz	Ch											
2412.0	1	802.11b	DSSS	16.0	0.134	2462.0	802.11g	OFDM	13.0	0.501	**0.067**	X
2412.0	1	802.11b	DSSS	16.0	0.134	2462.0	802.11n	OFDM	13.0	0.501	**0.067**	X
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure						Body 1.6 W/kg (mW/g) averaged over 1 gram						

Note: SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

Table 11.2.4 UNII Body-Worn SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch														
5290.0	58	802.11ac	13.00	12.90	-0.140	10 mm [Front]	FCC #2	0.047	MCS0	89.9	0.036	1.023	1.112	0.041	
5290.0	58	802.11ac	13.00	12.90	0.190	10 mm [Rear]	FCC #2	0.269	MCS0	89.9	0.264	1.023	1.112	**0.300**	A18
ANSI / IEEE C95.1-2005– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								Body 1.6 W/kg (mW/g) averaged over 1 gram							

Adjusted SAR results for UNII-1 and UNII-2A SAR												
FREQUENCY		Mode/ Antenna	Service	Maximum Allowed Power [dBm]	1g Scaled SAR (W/kg)	FREQUENCY [MHz]	Mode	Service	Maximum Allowed Power [dBm	Adjusted Factor	1g Adjusted SAR (W/kg)	SAR for the band with lower maximum output power
MHz	Ch											
5290.0	58	802.11ac	OFDM	13.0	0.300	5210	802.11ac	OFDM	13.0	1.000	**0.300**	X
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure						Body 1.6 W/kg (mW/g) averaged over 1 gram						

Note: U-NII-1 and U-NII-2A Bands: When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration

Table 11.2.5 UNII Body-Worn SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch														
5610.0	122	802.11ac	13.00	12.83	-0.070	10 mm [Front]	FCC #2	0.126	MCS0	89.9	0.118	1.040	1.112	0.137	
5610.0	122	802.11ac	13.00	12.83	-0.080	10 mm [Rear]	FCC #2	0.369	MCS0	89.9	0.391	1.040	1.112	**0.452**	A19
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								Body 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11.2.6 Bluetooth Body-Worn SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Rate [Mbps]	Duty Cycle (%)	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch													
2441.0	39	Bluetooth	11.80	9.38	0.000	10 mm [Front]	FCC #2	1	76.8	0.011	1.746	1.302	0.025	
2441.0	39	Bluetooth	11.80	9.38	0.000	10 mm [Rear]	FCC #2	1	76.8	0.018	1.746	1.302	**0.041**	A20
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								Body 1.6 W/kg (mW/g) averaged over 1 gram							

11.3 Standalone Hotspot SAR Results

Table 11.3.1 GPRS/WCDMA Hotspot SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/ Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Spacing [Side]	Device Serial Number	# of Time Slots	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
MHz	Ch													
836.6	190	GSM850	GPRS	27.90	27.30	-0.050	10 mm [Bottom]	FCC #1	4	1:2.075	0.486	1.148	0.558	
836.6	190	GSM850	GPRS	27.90	27.30	0.000	10 mm [Front]	FCC #1	4	1:2.075	0.538	1.148	0.618	
824.2	128	GSM850	GPRS	27.90	27.20	-0.020	10 mm [Rear]	FCC #1	4	1:2.075	0.610	1.175	0.717	
836.6	190	GSM850	GPRS	27.90	27.30	-0.060	10 mm [Rear]	FCC #1	4	1:2.075	0.795	1.148	0.913	
848.8	251	GSM850	GPRS	27.90	26.90	0.030	10 mm [Rear]	FCC #1	4	1:2.075	0.767	1.259	**0.966**	A12
836.6	190	GSM850	GPRS	27.90	27.30	0.060	10 mm [Right]	FCC #1	4	1:2.075	0.518	1.148	0.595	
1880.0	661	PCS1900	GPRS	24.90	24.50	-0.040	10 mm [Bottom]	FCC #1	4	1:2.075	0.116	1.096	0.127	
1880.0	661	PCS1900	GPRS	24.90	24.50	0.030	10 mm [Front]	FCC #1	4	1:2.075	0.453	1.096	**0.496**	A14
1880.0	661	PCS1900	GPRS	24.90	24.50	0.010	10 mm [Rear]	FCC #1	4	1:2.075	0.428	1.096	0.469	
1880.0	661	PCS1900	GPRS	24.90	24.50	-0.010	10 mm [Left]	FCC #1	4	1:2.075	0.391	1.096	0.429	
836.6	4183	WCDMA 850	RMC	24.20	23.63	0.070	10 mm [Bottom]	FCC #1	N/A	1:1	0.407	1.140	0.464	
836.6	4183	WCDMA 850	RMC	24.20	23.63	-0.010	10 mm [Front]	FCC #1	N/A	1:1	0.664	1.140	**0.757**	A15
836.6	4183	WCDMA 850	RMC	24.20	23.63	0.000	10 mm [Rear]	FCC #1	N/A	1:1	0.629	1.140	0.717	
846.6	4233	WCDMA 850	RMC	24.20	23.57	0.040	10 mm [Right]	FCC #1	N/A	1:1	0.074	1.156	0.086	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								**Body 1.6 W/kg (mW/g) averaged over 1 gram**						

Table 11.3.2 LTE B17 Hotspot SAR

MEASUREMENT RESULTS																	
FREQUENCY		Mode/ Band	BW [MHz]	Max Allowed Power [dBm]	Cond. PWR [dBm]	Drift Power [dB]	MPR	Position	Device Serial Number	Mod.	RB Size	RB Offs.	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
MHz	Ch																
710.0	23790	LTE B12	10	24.20	22.91	0.010	0	10 mm [Bottom]	FCC #1	QPSK	1	0	1:1	0.039	1.346	0.052	
710.0	23790	LTE B12	10	23.20	22.02	-0.060	1	10 mm [Bottom]	FCC #1	QPSK	25	0	1:1	0.034	1.312	0.045	
710.0	23790	LTE B12	10	24.20	22.91	-0.080	0	10 mm [Front]	FCC #1	QPSK	1	0	1:1	0.090	1.346	0.121	
710.0	23790	LTE B12	10	23.20	22.02	0.080	1	10 mm [Front]	FCC #1	QPSK	25	0	1:1	0.078	1.312	0.102	
710.0	23790	LTE B12	10	24.20	22.91	0.050	0	10 mm [Rear]	FCC #1	QPSK	1	0	1:1	0.116	1.346	**0.156**	A16
710.0	23790	LTE B12	10	23.20	22.02	0.020	1	10 mm [Rear]	FCC #1	QPSK	25	0	1:1	0.102	1.312	0.134	
710.0	23790	LTE B12	10	24.20	22.91	0.000	0	10 mm [Right]	FCC #1	QPSK	1	0	1:1	0.096	1.346	0.129	
710.0	23790	LTE B12	10	23.20	22.02	0.050	1	10 mm [Right]	FCC #1	QPSK	25	0	1:1	0.082	1.312	0.108	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure									**Body 1.6 W/kg (mW/g) averaged over 1 gram**								

Table 11.3.3 DTS Hotspot SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	SAR (W/kg)	Plots #
MHz	Ch														
2412.0	1	802.11b	16.00	15.88	0.070	10 mm [Top]	FCC #2	0.050	1	96.1	0.042	1.028	1.041	0.045	
2412.0	1	802.11b	16.00	15.88	0.060	10 mm [Front]	FCC #2	0.108	1	96.1	0.101	1.028	1.041	0.108	
2412.0	1	802.11b	16.00	15.88	0.030	10 mm [Rear]	FCC #2	0.137	1	96.1	0.125	1.028	1.041	**0.134**	A17
2412.0	1	802.11b	16.00	15.88	0.170	10 mm [Right]	FCC #2	0.108	1	96.5	0.102	1.028	1.036	0.109	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								**Body 1.6 W/kg (mW/g) averaged over 1 gram**							

Adjusted SAR results for OFDM SAR												
FREQUENCY		Mode/ Antenna	Service	Maximum Allowed Power [dBm]	1g Scaled SAR (W/kg)	FREQUENCY [MHz]	Mode	Service	Maximum Allowed Power [dBm	Ratio of OFDM to DSSS	1g Adjusted SAR (W/kg)	Determine OFDM SAR
MHz	Ch											
2412.0	1	802.11b	DSSS	16.0	0.134	2462.0	802.11g	OFDM	13.0	0.501	**0.067**	X
2412.0	1	802.11b	DSSS	16.0	0.134	2462.0	802.11n	OFDM	13.0	0.501	**0.067**	X
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure						**Body 1.6 W/kg (mW/g) averaged over 1 gram**						

Note: SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

Table 11.3.4 UNII Hotspot SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch														
5290.0	58	802.11ac	13.00	12.90	-0.020	10 mm [Top]	FCC #2	0.098	MCS0	89.9	0.093	1.023	1.112	0.106	
5290.0	58	802.11ac	13.00	12.90	-0.140	10 mm [Front]	FCC #2	0.047	MCS0	89.9	0.036	1.023	1.112	0.041	
5290.0	58	802.11ac	13.00	12.90	0.190	10 mm [Rear]	FCC #2	0.269	MCS0	89.9	0.264	1.023	1.112	**0.300**	A18
5290.0	58	802.11ac	13.00	12.90	-0.010	10 mm [Right]	FCC #2	0.185	MCS0	89.9	0.175	1.023	1.112	0.199	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								**Body 1.6 W/kg (mW/g) averaged over 1 gram**							

Adjusted SAR results for UNII-1 and UNII-2A SAR												
FREQUENCY		Mode/ Antenna	Service	Maximum Allowed Power [dBm]	1g Scaled SAR (W/kg)	FREQUENCY [MHz]	Mode	Service	Maximum Allowed Power [dBm	Adjusted Factor	1g Adjusted SAR (W/kg)	SAR for the band with lower maximum output power
MHz	Ch											
5290.0	58	802.11ac	OFDM	13.0	0.300	5210	802.11ac	OFDM	13.0	1.000	**0.300**	X
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure						**Body 1.6 W/kg (mW/g) averaged over 1 gram**						

Note: U-NII-1 and U-NII-2A Bands: When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration

Table 11.3.5 UNII Hotspot SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch														
5610.0	122	802.11ac	13.00	12.83	-0.010	10 mm [Top]	FCC #2	0.194	MCS0	89.9	0.189	1.040	1.112	0.219	
5610.0	122	802.11ac	13.00	12.83	-0.070	10 mm [Front]	FCC #2	0.126	MCS0	89.9	0.118	1.040	1.112	0.137	
5610.0	122	802.11ac	13.00	12.83	-0.080	10 mm [Rear]	FCC #2	0.369	MCS0	89.9	0.391	1.040	1.112	**0.452**	A19
5610.0	122	802.11ac	13.00	12.83	-0.060	10 mm [Right]	FCC #2	0.386	MCS0	89.9	0.389	1.040	1.112	0.450	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								Body 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11.3.6 Bluetooth Hotspot SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Rate [Mbps]	Duty Cycle (%)	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch														
2441.0	39	Bluetooth	11.80	9.38	0.000	10 mm [Top]	FCC #2	1	76.8	0.006	1.746	1.302	0.014	
2441.0	39	Bluetooth	11.80	9.38	0.000	10 mm [Front]	FCC #2	1	76.8	0.011	1.746	1.302	0.025	
2441.0	39	Bluetooth	11.80	9.38	0.000	10 mm [Rear]	FCC #2	1	76.8	0.018	1.746	1.302	**0.041**	A20
2441.0	39	Bluetooth	11.80	9.38	0.000	10 mm [Right]	FCC #2	1	76.8	0.014	1.746	1.302	0.032	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								Body 1.6 W/kg (mW/g) averaged over 1 gram							

11.4 Standalone Phablet SAR Results

Per FCC KDB Publication 648474 D04 Handset SAR, Phablet SAR tests were not required of Hotspot 1g SAR (scaled to maximum output power, including tolerance) < 1.2 W/kg.

11.5 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements. A standard battery was used for all SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 10 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated with a headset connected to the device. Since the standalone reported boy-worn SAR was > 1.2 W/kg, additional body-worn SAR evaluations using a headset cable were performed.
8. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated.
9. SAR measurements were performed using the DASY5 automated system. The procedure for spatial peak SAR evaluation has been implemented according to the IEEE 1528 standard. During a maximum search, global and local maxima searches are automatically performed in 2-D after each area scan measurement. The algorithm will find the global maximum and all local maxima within 2 dB of the global maxima for all SAR distributions. All local maxima within 2 dB of the global maximum were searched and passed for the Zoom Scan measurement.

GSM Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. This device supports GSM VOIP in the head and body-worn configurations; therefore GPRS was additionally evaluated for head and body-worn compliance.
3. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR.
4. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). Since the maximum output power variation across the required test channels is not > ½ dB, the middle channel was used for testing.

WCDMA (UMTS) Notes:

1. WCDMA (UMTS) mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is > ½ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r05. The general test procedures used for testing can be found in Section 8.4.4.
2. According to FCC KDB 941225 D05v02r05, when the reported SAR is ≤ 0.8 W/kg, testing of the 100% RB allocation and required test channels is not required.
   Otherwise, SAR is required for the remaining required test channels using the 1 RB, 50% RB and 100% RB allocation with highest output power for that channel.
   Only one channel, and as reported SAR values for 1 RB allocation and 50% RB allocation were less than 1.45 W/kg only the highest power RB offset for each allocation was required.
3. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36. 101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
4. A-MPR was disabled for all SAR tests by setting NS=1 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
5. SAR test reduction is applied using the following criteria:
   Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB, and 50% RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is > 0.8 W/kg, testing for other channels is performed at the highest output power level for 1 RB, and 50% RB configuration for that channel. Testing for 100% RB configuration is performed at the highest output power level for 100% RB configuration across the Low, Mid and High channel when the highest reported SAR for 1 RB and 50% RB are > 0.8 W/kg, Testing for the remaining required channels is not needed because the reported SAR for 100% RB Allocation < 1.45 W/kg. Testing for 16QAM modulation is not required because the reported SAR for QPSK is < 1.45 W/kg and its output power is not more than 0.5 dB higher than that a QPSK. Testing for the other channel bandwidths is not required because the reported SAR for the highest channel bandwidth is < 1.45 W/kg and its output power is not more than 0.5 dB higher than that of the highest channel bandwidth.

WLAN Notes:

1. The initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required duo to the maximum allowed powers and the highest reported DSSS SAR when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output and the adjust SAR is ≤ 1.2 W/kg.
3. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg.
4. When the maximum reported 1g averaged SAR ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg or all test channels were measured.
5. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor to determine compliance.

Bluetooth Notes:

1. Bluetooth SAR was measured with the device connected to a call with hopping disabled with DH5 operation and Tx test mode type. Per October 2016 TCB Workshop Notes, the reported SAR was scaled to the 100% transmission duty factor to determine compliance.
2. Head and hotspot Bluetooth SAR were evaluated for BT tethering applications.

12. FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to handsets with built-in unlicensed transmitters such as 802.11b/g/n and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2,simultaneous transmission SAR test exclusion may be applied when the sum of the sum 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is $\leq$ 1.6 W/kg. The different test positon in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1-g or 10-g SAR.

12.3 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds.

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06.

Table 12.3.1 Simultaneous Transmission Scenarios

No.	Capable TX Configuration	GSM850/1900 (Voice)	GPRS850/1900 (Data)	WCDMAB5 (Voice/Data)	LTE B17	WIFI 2.4GHz(802.11b/g/n)	WIFI 5GHz(802.11a/n/ac)	Bluetooth
1	GSM850/1900(Voice)		No	No	No	Yes	Yes	Yes
2	GPRS850/1900(Data)	No		No	No	Yes	Yes	Yes
3	WCDMAB5(Voice/Data)	No	No		No	Yes	Yes	Yes
4	LTE B17	No	No	No		Yes	Yes	Yes
5	WIFI 2.4GHz(802.11b/g/n)	Yes	Yes	Yes	Yes		No	No
6	WIFI 5GHz(802.11a/n/ac)	Yes	Yes	Yes	Yes	No		Yes
7	Bluetooth	Yes	Yes	Yes	Yes	No	Yes	

Table 12.3.2 Simultaneous SAR Cases

No.	Capable Transmit Configuration	Head SAR	Body-Worn SAR	Hotspot SAR	Phablet SAR	Note
1	GSM Voice + Wi-Fi 2.4 GHz	Yes	Yes	N/A	Yes	
2	GSM Voice + Wi-Fi 5 GHz	Yes	Yes	N/A	Yes	
3	GSM Voice + Bluetooth 2.4 GHz	Yes	Yes	N/A	Yes	
4	GSM Voice + Bluetooth 2.4 GHz + Wi-Fi 5GHz	Yes	Yes	N/A	Yes	
5	WCDMA + Wi-Fi 2.4 GHz	Yes	Yes	Yes	Yes	
6	WCDMA + Wi-Fi 5 GHz	Yes	Yes	Yes	Yes	
7	WCDMA + Bluetooth 2.4 GHz	Yes	Yes	Yes	Yes	
8	WCMDA + Bluetooth 2.4 GHz + Wi-Fi 5GHz	Yes	Yes	Yes	Yes	
9	LTE + Wi-Fi 2.4 GHz	Yes	Yes	Yes	Yes	
10	LTE + Wi-Fi 5 GHz	Yes	Yes	Yes	Yes	
11	LTE + Bluetooth 2.4 GHz	Yes	Yes	Yes	Yes	
12	LTE + Bluetooth 2.4 GHz + Wi-Fi 5GHz	Yes	Yes	Yes	Yes	
13	GPRS + Wi-Fi 2.4 GHz	Yes	Yes	Yes	Yes	
14	GPRS + Wi-Fi 5 GHz	Yes	Yes	Yes	Yes	
15	GPRS + Bluetooth 2.4 GHz	Yes	Yes	Yes	Yes	
16	GPRS + Bluetooth 2.4 GHz + Wi-Fi 5GHz	Yes	Yes	Yes	Yes	

Notes:

1. WiFi 2.4GHz is supported Hotspot.
2. WiFi 5GHz is supported Hotspot.
3. LTE, WCDMA, GPRS is supported Hotspot.
4. VoIP is supported in LTE, WCDMA, GSM
5. GSM, WCDMA and LTE can not transmit simultaneously since they share the same chip.

12.4 Head SAR Simultaneous Transmission Analysis

Table 12.4.1 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth + 5.3 GHz W-LAN (Held to Ear)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	5.3G W-LAN SAR (W/kg)	ΣSAR (W/kg)		
			1	2	3	1+2	1+3	1+2+3
Head SAR	GSM 850	Left Touch	0.518	0.207	0.394	0.725	0.912	**1.119**
		Right Touch	0.519	0.080	0.199	0.599	0.718	0.798
		Left Tilt	0.298	0.157	0.328	0.455	0.626	0.783
		Right Tilt	0.286	0.073	0.101	0.359	0.387	0.460
	GPRS 850	Left Touch	0.664	0.207	0.394	0.871	1.058	**1.265**
		Right Touch	0.669	0.080	0.199	0.749	0.868	0.948
		Left Tilt	0.370	0.157	0.328	0.527	0.698	0.855
		Right Tilt	0.354	0.073	0.101	0.427	0.455	0.528
	GSM 1900	Left Touch	0.404	0.207	0.394	0.611	0.798	**1.005**
		Right Touch	0.235	0.080	0.199	0.315	0.434	0.514
		Left Tilt	0.237	0.157	0.328	0.394	0.565	0.722
		Right Tilt	0.144	0.073	0.101	0.217	0.245	0.318
	GPRS 1900	Left Touch	0.329	0.207	0.394	0.536	0.723	**0.930**
		Right Touch	0.191	0.080	0.199	0.271	0.390	0.470
		Left Tilt	0.195	0.157	0.328	0.352	0.523	0.680
		Right Tilt	0.112	0.073	0.101	0.185	0.213	0.286
	WCDMA 850	Left Touch	0.527	0.207	0.394	0.734	0.921	**1.128**
		Right Touch	0.276	0.080	0.199	0.356	0.475	0.555
		Left Tilt	0.173	0.157	0.328	0.330	0.501	0.658
		Right Tilt	0.152	0.073	0.101	0.225	0.253	0.326
	LTE Band 17	Left Touch	0.079	0.207	0.394	0.286	0.473	**0.680**
		Right Touch	0.081	0.080	0.199	0.161	0.280	0.360
		Left Tilt	0.042	0.157	0.328	0.199	0.370	0.527
		Right Tilt	0.047	0.073	0.101	0.120	0.148	0.221

Table 12.4.2 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth + 5.6 GHz W-LAN (Held to Ear)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	5.6G W-LAN SAR (W/kg)	ΣSAR (W/kg)		
			1	2	3	1+2	1+3	1+2+3
Head SAR	GSM 850	Left Touch	0.518	0.207	0.659	0.725	1.177	**1.384**
		Right Touch	0.519	0.080	0.355	0.599	0.874	0.954
		Left Tilt	0.298	0.157	0.571	0.455	0.869	1.026
		Right Tilt	0.286	0.073	0.348	0.359	0.634	0.707
	GPRS 850	**Left Touch**	**0.664**	**0.207**	**0.659**	**0.871**	**1.323**	**1.530**
		Right Touch	0.669	0.080	0.355	0.749	1.024	1.104
		Left Tilt	0.370	0.157	0.571	0.527	0.941	1.098
		Right Tilt	0.354	0.073	0.348	0.427	0.702	0.775
	GSM 1900	**Left Touch**	0.404	0.207	0.659	0.611	1.063	**1.270**
		Right Touch	0.235	0.080	0.355	0.315	0.590	0.670
		Left Tilt	0.237	0.157	0.571	0.394	0.808	0.965
		Right Tilt	0.144	0.073	0.348	0.217	0.492	0.565
	GPRS 1900	Left Touch	0.329	0.207	0.659	0.536	0.988	**1.195**
		Right Touch	0.191	0.080	0.355	0.271	0.546	0.626
		Left Tilt	0.195	0.157	0.571	0.352	0.766	0.923
		Right Tilt	0.112	0.073	0.348	0.185	0.460	0.533
	WCDMA 850	Left Touch	0.527	0.207	0.659	0.734	1.186	**1.393**
		Right Touch	0.276	0.080	0.355	0.356	0.631	0.711
		Left Tilt	0.173	0.157	0.571	0.330	0.744	0.901
		Right Tilt	0.152	0.073	0.348	0.225	0.500	0.573
	LTE Band 17	Left Touch	0.079	0.207	0.659	0.286	0.738	**0.945**
		Right Touch	0.081	0.080	0.355	0.161	0.436	0.516
		Left Tilt	0.042	0.157	0.571	0.199	0.613	0.770
		Right Tilt	0.047	0.073	0.348	0.120	0.395	0.468

Table 12.4.3 Simultaneous Transmission Scenario : 2G/3G/4G + 2.4 GHz W-LAN (Held to Ear)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	2.4G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Head SAR	GSM 850	Left Touch	0.518	0.528	**1.046**
		Right Touch	0.519	0.218	0.737
		Left Tilt	0.298	0.456	0.754
		Right Tilt	0.286	0.209	0.495
	GPRS 850	Left Touch	0.664	0.528	**1.192**
		Right Touch	0.669	0.218	0.887
		Left Tilt	0.370	0.456	0.826
		Right Tilt	0.354	0.209	0.563
	GSM 1900	Left Touch	0.404	0.528	**0.932**
		Right Touch	0.235	0.218	0.453
		Left Tilt	0.237	0.456	0.693
		Right Tilt	0.144	0.209	0.353
	GPRS 1900	Left Touch	0.329	0.528	**0.857**
		Right Touch	0.191	0.218	0.409
		Left Tilt	0.195	0.456	0.651
		Right Tilt	0.112	0.209	0.321
	WCDMA 850	Left Touch	0.527	0.528	**1.055**
		Right Touch	0.276	0.218	0.494
		Left Tilt	0.173	0.456	0.629
		Right Tilt	0.152	0.209	0.361
	LTE Band 17	Left Touch	0.079	0.528	**0.607**
		Right Touch	0.081	0.218	0.299
		Left Tilt	0.042	0.456	0.498
		Right Tilt	0.047	0.209	0.256

Table 12.4.4 Simultaneous Transmission Scenario : 2G/3G/4G + 5.3 GHz W-LAN (Held to Ear)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	5.3G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Head SAR	GSM 850	Left Touch	0.518	0.394	**0.912**
		Right Touch	0.519	0.199	0.718
		Left Tilt	0.298	0.328	0.626
		Right Tilt	0.286	0.101	0.387
	GPRS 850	Left Touch	0.664	0.394	**1.058**
		Right Touch	0.669	0.199	0.868
		Left Tilt	0.370	0.328	0.698
		Right Tilt	0.354	0.101	0.455
	GSM 1900	Left Touch	0.404	0.394	**0.798**
		Right Touch	0.235	0.199	0.434
		Left Tilt	0.237	0.328	0.565
		Right Tilt	0.144	0.101	0.245
	GPRS 1900	Left Touch	0.329	0.394	**0.723**
		Right Touch	0.191	0.199	0.390
		Left Tilt	0.195	0.328	0.523
		Right Tilt	0.112	0.101	0.213
	WCDMA 850	Left Touch	0.527	0.394	**0.921**
		Right Touch	0.276	0.199	0.475
		Left Tilt	0.173	0.328	0.501
		Right Tilt	0.152	0.101	0.253
	LTE Band 17	Left Touch	0.079	0.394	**0.473**
		Right Touch	0.081	0.199	0.280
		Left Tilt	0.042	0.328	0.370
		Right Tilt	0.047	0.101	0.148

Table 12.4.5 Simultaneous Transmission Scenario : 2G/3G/4G + 5.6 GHz W-LAN (Held to Ear)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	5.6G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Head SAR	GSM 850	Left Touch	0.518	0.659	**1.177**
		Right Touch	0.519	0.355	0.874
		Left Tilt	0.298	0.571	0.869
		Right Tilt	0.286	0.348	0.634
	GPRS 850	Left Touch	0.664	0.659	**1.323**
		Right Touch	0.669	0.355	1.024
		Left Tilt	0.370	0.571	0.941
		Right Tilt	0.354	0.348	0.702
	GSM 1900	Left Touch	0.404	0.659	**1.063**
		Right Touch	0.235	0.355	0.590
		Left Tilt	0.237	0.571	0.808
		Right Tilt	0.144	0.348	0.492
	GPRS 1900	Left Touch	0.329	0.659	**0.988**
		Right Touch	0.191	0.355	0.546
		Left Tilt	0.195	0.571	0.766
		Right Tilt	0.112	0.348	0.460
	WCDMA 850	Left Touch	0.527	0.659	**1.186**
		Right Touch	0.276	0.355	0.631
		Left Tilt	0.173	0.571	0.744
		Right Tilt	0.152	0.348	0.500
	LTE Band 17	Left Touch	0.079	0.659	**0.738**
		Right Touch	0.081	0.355	0.436
		Left Tilt	0.042	0.571	0.613
		Right Tilt	0.047	0.348	0.395

Table 12.4.6 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth (Held to Ear)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Head SAR	GSM 850	Left Touch	0.518	0.207	**0.725**
		Right Touch	0.519	0.080	0.599
		Left Tilt	0.298	0.157	0.455
		Right Tilt	0.286	0.073	0.359
	GPRS 850	Left Touch	0.664	0.207	**0.871**
		Right Touch	0.669	0.080	0.749
		Left Tilt	0.370	0.157	0.527
		Right Tilt	0.354	0.073	0.427
	GSM 1900	Left Touch	0.404	0.207	**0.611**
		Right Touch	0.235	0.080	0.315
		Left Tilt	0.237	0.157	0.394
		Right Tilt	0.144	0.073	0.217
	GPRS 1900	Left Touch	0.329	0.207	**0.536**
		Right Touch	0.191	0.080	0.271
		Left Tilt	0.195	0.157	0.352
		Right Tilt	0.112	0.073	0.185
	WCDMA 850	Left Touch	0.527	0.207	**0.734**
		Right Touch	0.276	0.080	0.356
		Left Tilt	0.173	0.157	0.330
		Right Tilt	0.152	0.073	0.225
	LTE Band 17	Left Touch	0.079	0.207	**0.286**
		Right Touch	0.081	0.080	0.161
		Left Tilt	0.042	0.157	0.199
		Right Tilt	0.047	0.073	0.120

Table 12.4.7 Simultaneous Transmission Scenario : Bluetooth + 5 GHz W-LAN (Held to Ear)

Exposure Condition	Mode	Configuration	Bluetooth SAR (W/kg)	5G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Head SAR	5.3G W-LAN	Left Touch	0.207	0.394	**0.601**
		Right Touch	0.080	0.199	0.279
		Left Tilt	0.157	0.328	0.485
		Right Tilt	0.073	0.101	0.174
	5.6G W-LAN	Left Touch	0.207	0.659	**0.866**
		Right Touch	0.080	0.355	0.435
		Left Tilt	0.157	0.571	0.728
		Right Tilt	0.073	0.348	0.421

12.5 Body-Worn Simultaneous Transmission Analysis

Table 12.5.1 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth + 5.3 GHz W-LAN (Body-Worn at 10 mm)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	5.3G W-LAN SAR (W/kg)	ΣSAR (W/kg)		
			1	2	3	1+2	1+3	1+2+3
Body-Worn SAR	GSM 850	Front	0.465	0.025	0.041	0.490	0.506	0.531
		Rear	0.635	0.041	0.300	0.676	0.935	**0.976**
	GPRS 850	Front	0.618	0.025	0.041	0.643	0.659	0.684
		Rear	0.966	0.041	0.300	1.007	1.266	**1.307**
	GSM 1900	Front	0.604	0.025	0.041	0.629	0.645	0.670
		Rear	0.577	0.041	0.300	0.618	0.877	**0.918**
	GPRS 1900	Front	0.496	0.025	0.041	0.521	0.537	0.562
		Rear	0.469	0.041	0.300	0.510	0.769	**0.810**
	WCDMA 850	Front	0.757	0.025	0.041	0.782	0.798	0.823
		Rear	0.717	0.041	0.300	0.758	1.017	**1.058**
	LTE Band 17	Front	0.121	0.025	0.041	0.146	0.162	0.187
		Rear	0.156	0.041	0.300	0.197	0.456	**0.497**

Table 12.5.2 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth + 5.6 GHz W-LAN (Body-Worn at 10 mm)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	5.6G W-LAN SAR (W/kg)	ΣSAR (W/kg)		
			1	2	3	1+2	1+3	1+2+3
Body-Worn SAR	GSM 850	Front	0.465	0.025	0.137	0.490	0.602	0.627
		Rear	0.635	0.041	0.452	0.676	1.087	**1.128**
	GPRS 850	Front	0.618	0.025	0.137	0.643	0.755	0.780
		Rear	**0.966**	**0.041**	**0.452**	**1.007**	**1.418**	**1.459**
	GSM 1900	Front	0.604	0.025	0.137	0.629	0.741	0.766
		Rear	0.577	0.041	0.452	0.618	1.029	**1.070**
	GPRS 1900	Front	0.496	0.025	0.137	0.521	0.633	0.658
		Rear	0.469	0.041	0.452	0.510	0.921	**0.962**
	WCDMA 850	Front	0.757	0.025	0.137	0.782	0.894	0.919
		Rear	0.717	0.041	0.452	0.758	1.169	**1.210**
	LTE Band 17	Front	0.121	0.025	0.137	0.146	0.258	0.283
		Rear	0.156	0.041	0.452	0.197	0.608	**0.649**

Table 12.5.3 Simultaneous Transmission Scenario : 2G/3G/4G + 2.4 GHz W-LAN (Body-Worn at 10 mm)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	2.4G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Body-Worn SAR	GSM 850	Front	0.465	0.108	0.573
		Rear	0.635	0.134	**0.769**
	GPRS 850	Front	0.618	0.108	0.726
		Rear	0.966	0.134	**1.100**
	GSM 1900	Front	0.604	0.108	**0.712**
		Rear	0.577	0.134	0.711
	GPRS 1900	Front	0.496	0.108	**0.604**
		Rear	0.469	0.134	0.603
	WCDMA 850	Front	0.757	0.108	**0.865**
		Rear	0.717	0.134	0.851
	LTE Band 17	Front	0.121	0.108	0.229
		Rear	0.156	0.134	**0.290**

Table 12.5.4 Simultaneous Transmission Scenario : 2G/3G/4G + 5.3 GHz W-LAN (Body-Worn at 10 mm)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	5.3G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Body-Worn SAR	GSM 850	Front	0.465	0.041	0.506
		Rear	0.635	0.300	**0.935**
	GPRS 850	Front	0.618	0.041	0.659
		Rear	0.966	0.300	**1.266**
	GSM 1900	Front	0.604	0.041	0.645
		Rear	0.577	0.300	**0.877**
	GPRS 1900	Front	0.496	0.041	0.537
		Rear	0.469	0.300	**0.769**
	WCDMA 850	Front	0.757	0.041	0.798
		Rear	0.717	0.300	**1.017**
	LTE Band 17	Front	0.121	0.041	0.162
		Rear	0.156	0.300	**0.456**

Table 12.5.5 Simultaneous Transmission Scenario : 2G/3G/4G + 5.6 GHz W-LAN (Body-Worn at 10 mm)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	5.6G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Body-Worn SAR	GSM 850	Front	0.465	0.137	0.602
		Rear	0.635	0.452	**1.087**
	GPRS 850	Front	0.618	0.137	0.755
		Rear	0.966	0.452	**1.418**
	GSM 1900	Front	0.604	0.137	0.741
		Rear	0.577	0.452	**1.029**
	GPRS 1900	Front	0.496	0.137	0.633
		Rear	0.469	0.452	**0.921**
	WCDMA 850	Front	0.757	0.137	0.894
		Rear	0.717	0.452	**1.169**
	LTE Band 17	Front	0.121	0.137	0.258
		Rear	0.156	0.452	**0.608**

Table 12.5.6 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth (Body-Worn at 10 mm)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Body-Worn SAR	GSM 850	Front	0.465	0.025	0.490
		Rear	0.635	0.041	**0.676**
	GPRS 850	Front	0.618	0.025	0.643
		Rear	0.966	0.041	**1.007**
	GSM 1900	Front	0.604	0.025	**0.629**
		Rear	0.577	0.041	0.618
	GPRS 1900	Front	0.496	0.025	**0.521**
		Rear	0.469	0.041	0.510
	WCDMA 850	Front	0.757	0.025	**0.782**
		Rear	0.717	0.041	0.758
	LTE Band 17	Front	0.121	0.025	0.146
		Rear	0.156	0.041	**0.197**

Table 12.5.7 Simultaneous Transmission Scenario : Bluetooth + 5 GHz W-LAN (Body-Worn at 10 mm)

Exposure Condition	Mode	Configuration	Bluetooth SAR (W/kg)	5G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Body-Worn SAR	5.3G W-LAN	Front	0.025	0.041	0.066
		Rear	0.041	0.300	**0.341**
	5.6G W-LAN	Front	0.025	0.137	0.162
		Rear	0.041	0.452	**0.493**

12.6 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v02r01, the device edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR ("-").

Table 12.6.1 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth + 5.3 GHz W-LAN (Hotspot at 10 mm)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	5.3G W-LAN SAR (W/kg)	ΣSAR (W/kg)		
			1	2	3	1+2	1+3	1+2+3
Hotspot SAR	GPRS 850	Top	0.000	0.014	0.106	0.014	0.106	0.120
		Bottom	0.558	0.000	0.000	0.558	0.558	0.558
		Front	0.618	0.025	0.041	0.643	0.659	0.684
		Rear	0.966	0.041	0.300	1.007	1.266	**1.307**
		Right	0.595	0.032	0.199	0.627	0.794	0.826
		Left	0.000	0.000	0.000	0.000	0.000	0.000
	GPRS 1900	Top	0.000	0.014	0.106	0.014	0.106	0.120
		Bottom	0.127	0.000	0.000	0.127	0.127	0.127
		Front	0.496	0.025	0.041	0.521	0.537	0.562
		Rear	0.469	0.041	0.300	0.510	0.769	**0.810**
		Right	0.000	0.032	0.199	0.032	0.199	0.231
		Left	0.429	0.000	0.000	0.429	0.429	0.429
	WCDMA 850	Top	0.000	0.014	0.106	0.014	0.106	0.120
		Bottom	0.464	0.000	0.000	0.464	0.464	0.464
		Front	0.757	0.025	0.041	0.782	0.798	0.823
		Rear	0.717	0.041	0.300	0.758	1.017	**1.058**
		Right	0.086	0.032	0.199	0.118	0.285	0.317
		Left	0.000	0.000	0.000	0.000	0.000	0.000
	LTE Band 17	Top	0.007	0.014	0.106	0.021	0.113	0.127
		Bottom	0.052	0.000	0.000	0.052	0.052	0.052
		Front	0.121	0.025	0.041	0.146	0.162	0.187
		Rear	0.156	0.041	0.300	0.197	0.456	**0.497**
		Right	0.129	0.032	0.199	0.161	0.328	0.360
		Left	0.075	0.000	0.000	0.075	0.075	0.075

Table 12.6.2 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth + 5.6 GHz W-LAN (Hotspot at 10 mm)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	5.6G W-LAN SAR (W/kg)	ΣSAR (W/kg)		
			1	2	3	1+2	1+3	1+2+3
Hotspot SAR	GPRS 850	Top	0.000	0.014	0.219	0.014	0.219	0.233
		Bottom	0.558	0.000	0.000	0.558	0.558	0.558
		Front	0.618	0.025	0.137	0.643	0.755	0.780
		Rear	**0.966**	**0.041**	**0.452**	**1.007**	**1.418**	1.459
		Right	0.595	0.032	0.000	0.627	0.595	0.627
		Left	0.000	0.000	0.450	0.000	0.450	0.450
	GPRS 1900	Top	0.000	0.014	0.219	0.014	0.219	0.233
		Bottom	0.127	0.000	0.000	0.127	0.127	0.127
		Front	0.496	0.025	0.137	0.521	0.633	0.658
		Rear	0.469	0.041	0.452	0.510	0.921	**0.962**
		Right	0.000	0.032	0.000	0.032	0.000	0.032
		Left	0.429	0.000	0.450	0.429	0.879	0.879
	WCDMA 850	Top	0.000	0.014	0.219	0.014	0.219	0.233
		Bottom	0.464	0.000	0.000	0.464	0.464	0.464
		Front	0.757	0.025	0.137	0.782	0.894	0.919
		Rear	0.717	0.041	0.452	0.758	1.169	**1.210**
		Right	0.086	0.032	0.000	0.118	0.086	0.118
		Left	0.000	0.000	0.450	0.000	0.450	0.450
	LTE Band 17	Top	0.007	0.014	0.219	0.021	0.226	0.240
		Bottom	0.052	0.000	0.000	0.052	0.052	0.052
		Front	0.121	0.025	0.137	0.146	0.258	0.283
		Rear	0.156	0.041	0.452	0.197	0.608	**0.649**
		Right	0.129	0.032	0.000	0.161	0.129	0.161
		Left	0.075	0.000	0.450	0.075	0.525	0.525

Table 12.6.3 Simultaneous Transmission Scenario : 2G/3G/4G + 2.4 GHz W-LAN (Hotspot at 10 mm)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	2.4G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Hotspot SAR	GPRS 850	Top	0.000	0.045	0.045
		Bottom	0.558	0.000	0.558
		Front	0.618	0.108	0.726
		Rear	0.966	0.134	**1.100**
		Right	0.595	0.000	0.595
		Left	0.000	0.109	0.109
	GPRS 1900	Top	0.000	0.045	0.045
		Bottom	0.127	0.000	0.127
		Front	0.496	0.108	**0.604**
		Rear	0.469	0.134	0.603
		Right	0.000	0.000	0.000
		Left	0.429	0.109	0.538
	WCDMA 850	Top	0.000	0.045	0.045
		Bottom	0.464	0.000	0.464
		Front	0.757	0.108	**0.865**
		Rear	0.717	0.134	0.851
		Right	0.086	0.000	0.086
		Left	0.000	0.109	0.109
	LTE Band 17	Top	0.007	0.045	0.052
		Bottom	0.052	0.000	0.052
		Front	0.121	0.108	0.229
		Rear	0.156	0.134	**0.290**
		Right	0.129	0.000	0.129
		Left	0.075	0.109	0.184

Table 12.6.4 Simultaneous Transmission Scenario : 2G/3G/4G + 5.3 GHz W-LAN (Hotspot at 10 mm)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	5.3G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Hotspot SAR	GPRS 850	Top	0.000	0.106	0.106
		Bottom	0.558	0.000	0.558
		Front	0.618	0.041	0.659
		Rear	0.966	0.300	**1.266**
		Right	0.595	0.199	0.794
		Left	0.000	0.000	0.000
	GPRS 1900	Top	0.000	0.106	0.106
		Bottom	0.127	0.000	0.127
		Front	0.496	0.041	0.537
		Rear	0.469	0.300	**0.769**
		Right	0.000	0.199	0.199
		Left	0.429	0.000	0.429
	WCDMA 850	Top	0.000	0.106	0.106
		Bottom	0.464	0.000	0.464
		Front	0.757	0.041	0.798
		Rear	0.717	0.300	**1.017**
		Right	0.086	0.199	0.285
		Left	0.000	0.000	0.000
	LTE Band 17	Top	0.007	0.106	0.113
		Bottom	0.052	0.000	0.052
		Front	0.121	0.041	0.162
		Rear	0.156	0.300	**0.456**
		Right	0.129	0.199	0.328
		Left	0.075	0.000	0.075

Table 12.6.5 Simultaneous Transmission Scenario : 2G/3G/4G + 5.6 GHz W-LAN (Hotspot at 10 mm)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	5.6G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Hotspot SAR	GPRS 850	Top	0.000	0.219	0.219
		Bottom	0.558	0.000	0.558
		Front	0.618	0.137	0.755
		Rear	0.966	0.452	**1.418**
		Right	0.595	0.450	1.045
		Left	0.000	0.000	0.000
	GPRS 1900	Top	0.000	0.219	0.219
		Bottom	0.127	0.000	0.127
		Front	0.496	0.137	0.633
		Rear	0.469	0.452	**0.921**
		Right	0.000	0.450	0.450
		Left	0.429	0.000	0.429
	WCDMA 850	Top	0.000	0.219	0.219
		Bottom	0.464	0.000	0.464
		Front	0.757	0.137	0.894
		Rear	0.717	0.452	**1.169**
		Right	0.086	0.450	0.536
		Left	0.000	0.000	0.000
	LTE Band 17	Top	0.007	0.219	0.226
		Bottom	0.052	0.000	0.052
		Front	0.121	0.137	0.258
		Rear	0.156	0.452	**0.608**
		Right	0.129	0.450	0.579
		Left	0.075	0.000	0.075

Table 12.6.6 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth (Hotspot at 10 mm)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Hotspot SAR	GPRS 850	Top	0.000	0.014	0.014
		Bottom	0.558	0.000	0.558
		Front	0.618	0.025	0.643
		Rear	0.966	0.041	**1.007**
		Right	0.595	0.032	0.627
		Left	0.000	0.000	0.000
	GPRS 1900	Top	0.000	0.014	0.014
		Bottom	0.127	0.000	0.127
		Front	0.496	0.025	**0.521**
		Rear	0.469	0.041	0.510
		Right	0.000	0.032	0.032
		Left	0.429	0.000	0.429
	WCDMA 850	Top	0.000	0.014	0.014
		Bottom	0.464	0.000	0.464
		Front	0.757	0.025	**0.782**
		Rear	0.717	0.041	0.758
		Right	0.086	0.032	0.118
		Left	0.000	0.000	0.000
	LTE Band 17	Top	0.007	0.014	0.021
		Bottom	0.052	0.000	0.052
		Front	0.121	0.025	0.146
		Rear	0.156	0.041	**0.197**
		Right	0.129	0.032	0.161
		Left	0.075	0.000	0.075

Table 12.6.7 Simultaneous Transmission Scenario : Bluetooth + 5 GHz W-LAN (Hotspot at 10 mm)

Exposure Condition	Mode	Configuration	Bluetooth SAR (W/kg)	5G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Hotspot SAR	5.3G W-LAN	Top	0.014	0.106	0.120
		Bottom	0.000	0.000	0.000
		Front	0.025	0.041	0.066
		Rear	0.041	0.300	**0.341**
		Right	0.032	0.199	0.231
		Left	0.000	0.000	0.000
	5.6G W-LAN	Top	0.014	0.219	0.233
		Bottom	0.000	0.000	0.000
		Front	0.025	0.137	0.162
		Rear	0.041	0.452	**0.493**
		Right	0.032	0.450	0.482
		Left	0.000	0.000	0.000

12.7 Phablet SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 648474 D04 Handset SAR, Phablet SAR tests were not required of Hotspot 1g SAR (scaled to maximum output power, including tolerance) < 1.2 W/kg. Therefore no further analysis was required to for Phablet Simultaneous Transmission Analysis.

12.8 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2.

13. SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

1. When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
2. A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
3. A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.
4. Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg
5. The same procedures should be adapted for measurements according to extremity exposure limits by applying a factor of 2.5 for extremity exposure to the corresponding SAR thresholds.

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for 1g and < 3.75 W/kg for 10g for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

14. EQUIPMENT LIST

Table 14.1.1 Test Equipment Calibration

	Type	Manufacturer	Model	Cal.Date	Next.Cal.Date	S/N
☒	SEMITEC Engineering	SEMITEC	N/A	N/A	N/A	Shield Room
☒	SEMITEC Engineering	SEMITEC	N/A	N/A	N/A	Shield Room
☒	Robot	SPEAG	TX60L	N/A	N/A	F12/5LP5A1/A/01
☒	Robot	SPEAG	TX60L	N/A	N/A	F14/5VR2A1/A/01
☒	Robot Controller	SPEAG	CS8C	N/A	N/A	F12/5LP5A1/C/01
☒	Robot Controller	SPEAG	CS8C	N/A	N/A	F14/5VR2A1/C/01
☒	Joystick	SPEAG	N/A	N/A	N/A	S-12030401
☒	Joystick	SPEAG	N/A	N/A	N/A	D21142605A
☒	Intel Core i7-2600 3.40 GHz Windows 7 Professional	N/A	N/A	N/A	N/A	N/A
☒	Intel Core i7-4770 3.40 GHz Windows 7 Professional	N/A	N/A	N/A	N/A	N/A
☒	Probe Alignment Unit LB	N/A	N/A	N/A	N/A	SE UKS 030 AA
☒	Probe Alignment Unit LB	N/A	N/A	N/A	N/A	SE UKS 030 AA
☒	Device Holder	SPEAG	SD000H01KA	N/A	N/A	N/A
☒	Device Holder	SPEAG	SD000H01HA	N/A	N/A	N/A
☒	Twin SAM Phantom	SPEAG	QD000P40CD	N/A	N/A	1679
☒	Twin SAM Phantom	SPEAG	QD000P40CD	N/A	N/A	1220
☒	Data Acquisition Electronics	SPEAG	DAE3V1	2019-01-24	2020-01-24	519
☒	Data Acquisition Electronics	SPEAG	DAE4V1	2019-05-23	2020-05-23	1392
☒	Dosimetric E-Field Probe	SPEAG	ES3DV3	2019-03-28	2020-03-28	3328
☒	Dosimetric E-Field Probe	SPEAG	EX3DV4	2019-08-27	2020-08-27	7368
☒	750MHz SAR Dipole	SPEAG	D750V3	2019-01-25	2021-01-25	1049
☒	835MHz SAR Dipole	SPEAG	D835V2	2019-07-18	2020-07-18	464
☒	1900MHz SAR Dipole	SPEAG	D1900V2	2019-07-17	2020-07-17	5d029
☒	2450MHz SAR Dipole	SPEAG	D2450V2	2019-09-19	2021-09-19	726
☒	5GHz SAR Dipole	SPEAG	D5GHzV2	2019-02-28	2021-02-28	1103
☒	Network Analyzer	Agilent	E5071C	2018-12-19	2019-12-19	MY46111534
☒	Signal Generator	Agilent	E4438C	2019-06-24	2020-06-24	US41461520
☒	Amplifier	RFBAY.Inc	MPA-40-40	2018-12-20	2019-12-20	21151801
☒	Amplifier	EMPOWER	BBS3Q7ELU	2019-06-24	2020-06-24	1020
☒	High Power RF Amplifier	EMPOWER	BBS3Q8CCJ	2019-06-24	2020-06-24	1005
☒	Power Meter	HP	EPM-442A	2018-12-19	2019-12-19	GB37170267
☒	Power Meter	HP	EPM-442A	2018-12-18	2019-12-18	GB37170413
☒	Power Sensor	HP	8481A	2018-12-18	2019-12-18	US37294267
☒	Power Sensor	HP	8481A	2018-12-19	2019-12-19	3318A96566
☒	Power Sensor	HP	8481A	2018-12-19	2019-12-19	2702A65976
☒	Dual Directional Coupler	Agilent	778D-012	2018-12-19	2019-12-19	50228
☒	Directional Coupler	HP	772D	2019-06-24	2020-06-24	2889A01064
☒	Low Pass Filter 1GHz	Wainwright Instruments	WLK6-1000-1400-9000-60SS	2019-06-24	2020-06-24	165
☒	Low Pass Filter 1.5GHz	Micro LAB	LA-15N	2019-06-24	2020-06-24	2
☒	Low Pass Filter 3.0GHz	Micro LAB	LA-30N	2019-06-24	2020-06-24	2
☒	Low Pass Filter 6.0GHz	Micro LAB	LA-60N	2018-12-19	2019-12-19	03942
☒	Attenuators(10 dB)	WEINSCHEL	23-10-34	2018-12-19	2019-12-19	BP4387
☒	Attenuators	Cernexwave	CFADC2603U5	2019-06-27	2020-06-27	C11740
☒	Dielectric Probe kit	SPEAG	DAK-3.5	2018-11-20	2019-11-20	1092
☒	8960 Series 10 Wireless Comms. Test Set	Agilent	E5515C	2019-06-28	2020-06-28	GB41321164
☒	Wideband Radio Communication Tester	Rohde Schwarz	CMW500	2018-12-19	2019-12-19	101414
☒	Power Splitter	Anritsu	K241B	2018-12-18	2019-12-18	1301183

NOTE(S):

1. The E-field probe was calibrated by SPEAG, by temperature measurement procedure. Dipole Verification measurement is performed by DT&C before each test. The brain and muscle simulating material are calibrated by DT&C using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the brain and muscle-equivalent material. Each equipment item was used solely within its respective calibration period.
2. CBT(Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

15. MEASUREMENT UNCERTAINTIES

750 MHz Head (SN: 3328)

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1g	(Ci) 10g	Standard (1g)	Standard (10g)	vi 2 or Veff
Measurement System								
Probe calibration	± 6.0	Normal	1	1	1	± 6.0 %	± 6.0 %	∞
Isotropy	± 1.3	Normal	1	1	1	± 1.3 %	± 1.3 %	∞
Boundary Effects	± 2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %	∞
Probe Linearity	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Probe modulation response	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Detection limits	± 0.25	Rectangular	√3	1	1	± 0.14 %	± 0.14 %	∞
Readout Electronics	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Response time	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Integration time	± 2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Conditions – Noise	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
RF Ambient Conditions – Reflections	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Probe Positioning	± 6.7	Rectangular	√3	1	1	± 3.9 %	± 3.9 %	∞
Algorithms for Max. SAR Eval.	± 4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	∞
Test Sample Related								
Device Positioning	± 2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	± 3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	5
Power Drift	± 5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %	∞
SAR Scaling	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Physical Parameters								
Phantom Shell	± 7.6	Rectangular	√3	1	1	± 4.4 %	± 4.4 %	∞
SAR correction	± 0.0	Normal	1	1	0.84	± 0.0 %	± 0.0 %	∞
Liquid conductivity (Target)	± 5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %	∞
Liquid conductivity (Meas.)	± 3.8	Normal	1	0.78	0.71	± 3.0 %	± 2.7 %	10
Liquid permittivity (Target)	± 5.0	Rectangular	√3	0.60	0.49	± 1.7 %	± 1.4 %	∞
Liquid permittivity (Meas.)	± 4.2	Normal	1	0.23	0.26	± 1.0 %	± 1.1 %	10
Temp. unc. - Conductivity	± 1.8	Rectangular	√3	0.78	0.71	± 0.8 %	± 0.7 %	∞
Temp. unc. - Permittivity	± 1.9	Rectangular	√3	0.23	0.26	± 0.3%	± 0.3 %	∞
Combined Standard Uncertainty						**± 11.6 %**	**± 11.4 %**	330
Expanded Uncertainty (k=2)						**± 23.2 %**	**± 22.8 %**	

The above measurement uncertainties are according to IEEE Std 1528

835 MHz Head (SN: 3328)

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1g	(Ci) 10g	Standard (1g)	Standard (10g)	vi 2 or Veff
Measurement System								
Probe calibration	± 6.0	Normal	1	1	1	± 6.0 %	± 6.0 %	∞
Isotropy	± 1.3	Normal	1	1	1	± 1.3 %	± 1.3 %	∞
Boundary Effects	± 2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %	∞
Probe Linearity	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Probe modulation response	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Detection limits	± 0.25	Rectangular	√3	1	1	± 0.14 %	± 0.14 %	∞
Readout Electronics	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Response time	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Integration time	± 2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Conditions – Noise	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
RF Ambient Conditions – Reflections	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Probe Positioning	± 6.7	Rectangular	√3	1	1	± 3.9 %	± 3.9 %	∞
Algorithms for Max. SAR Eval.	± 4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	∞
Test Sample Related								
Device Positioning	± 2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	± 3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	5
Power Drift	± 5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %	∞
SAR Scaling	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Physical Parameters								
Phantom Shell	± 7.6	Rectangular	√3	1	1	± 4.4 %	± 4.4 %	∞
SAR correction	± 0.0	Normal	1	1	0.84	± 0.0 %	± 0.0 %	∞
Liquid conductivity (Target)	± 5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %	∞
Liquid conductivity (Meas.)	± 4.0	Normal	1	0.78	0.71	± 3.1 %	± 2.8 %	10
Liquid permittivity (Target)	± 5.0	Rectangular	√3	0.60	0.49	± 1.7 %	± 1.4 %	∞
Liquid permittivity (Meas.)	± 4.1	Normal	1	0.23	0.26	± 0.9 %	± 1.1 %	10
Temp. unc. - Conductivity	± 1.9	Rectangular	√3	0.78	0.71	± 0.9 %	± 0.8 %	∞
Temp. unc. - Permittivity	± 1.9	Rectangular	√3	0.23	0.26	± 0.3%	± 0.3 %	∞
Combined Standard Uncertainty						**± 11.6 %**	**± 11.4 %**	330
Expanded Uncertainty (k=2)						**± 23.2 %**	**± 22.8 %**	

The above measurement uncertainties are according to IEEE Std 1528

1900 MHz Head (SN: 3328)

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1g	(Ci) 10g	Standard (1g)	Standard (10g)	vi 2 or Veff
Measurement System								
Probe calibration	± 6.0	Normal	1	1	1	± 6.0 %	± 6.0 %	∞
Isotropy	± 1.3	Normal	1	1	1	± 1.3 %	± 1.3 %	∞
Boundary Effects	± 2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %	∞
Probe Linearity	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Probe modulation response	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Detection limits	± 0.25	Rectangular	√3	1	1	± 0.14 %	± 0.14 %	∞
Readout Electronics	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Response time	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Integration time	± 2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Conditions – Noise	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
RF Ambient Conditions – Reflections	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Probe Positioning	± 6.7	Rectangular	√3	1	1	± 3.9 %	± 3.9 %	∞
Algorithms for Max. SAR Eval.	± 4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	∞
Test Sample Related								
Device Positioning	± 2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	± 3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	5
Power Drift	± 5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %	∞
SAR Scaling	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Physical Parameters								
Phantom Shell	± 7.6	Rectangular	√3	1	1	± 4.4 %	± 4.4 %	∞
SAR correction	± 0.0	Normal	1	1	0.84	± 0.0 %	± 0.0 %	∞
Liquid conductivity (Target)	± 5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %	∞
Liquid conductivity (Meas.)	± 3.7	Normal	1	0.78	0.71	± 2.9 %	± 2.6 %	10
Liquid permittivity (Target)	± 5.0	Rectangular	√3	0.60	0.49	± 1.7 %	± 1.4 %	∞
Liquid permittivity (Meas.)	± 4.2	Normal	1	0.23	0.26	± 1.0 %	± 1.1 %	10
Temp. unc. - Conductivity	± 1.9	Rectangular	√3	0.78	0.71	± 0.9 %	± 0.8 %	∞
Temp. unc. - Permittivity	± 1.9	Rectangular	√3	0.23	0.26	± 0.3 %	± 0.3 %	∞
Combined Standard Uncertainty						**± 11.6 %**	**± 11.4 %**	330
Expanded Uncertainty (k=2)						**± 23.2 %**	**± 22.8 %**	

The above measurement uncertainties are according to IEEE Std 1528

2450 MHz Head (SN: 7368)

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1g	(Ci) 10g	Standard (1g)	Standard (10g)	vi 2 or Veff
Measurement System								
Probe calibration	± 6.0	Normal	1	1	1	± 6.0 %	± 6.0 %	∞
Isotropy	± 1.3	Normal	1	1	1	± 1.3 %	± 1.3 %	∞
Boundary Effects	± 2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %	∞
Probe Linearity	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Probe modulation response	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Detection limits	± 0.25	Rectangular	√3	1	1	± 0.14 %	± 0.14 %	∞
Readout Electronics	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Response time	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Integration time	± 2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Conditions – Noise	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
RF Ambient Conditions – Reflections	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Probe Positioning	± 6.7	Rectangular	√3	1	1	± 3.9 %	± 3.9 %	∞
Algorithms for Max. SAR Eval.	± 4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	∞
Test Sample Related								
Device Positioning	± 2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	± 3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	5
Power Drift	± 5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %	∞
SAR Scaling	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Physical Parameters								
Phantom Shell	± 7.6	Rectangular	√3	1	1	± 4.4 %	± 4.4 %	∞
SAR correction	± 0.0	Normal	1	1	0.84	± 0.0 %	± 0.0 %	∞
Liquid conductivity (Target)	± 5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %	∞
Liquid conductivity (Meas.)	± 4.1	Normal	1	0.78	0.71	± 3.2 %	± 2.9 %	10
Liquid permittivity (Target)	± 5.0	Rectangular	√3	0.60	0.49	± 1.7 %	± 1.4 %	∞
Liquid permittivity (Meas.)	± 3.8	Normal	1	0.23	0.26	± 0.9 %	± 1.0 %	10
Temp. unc. - Conductivity	± 1.9	Rectangular	√3	0.78	0.71	± 0.9 %	± 0.8 %	∞
Temp. unc. - Permittivity	± 1.9	Rectangular	√3	0.23	0.26	± 0.3 %	± 0.3 %	∞
Combined Standard Uncertainty						**± 11.6 %**	**± 11.4 %**	330
Expanded Uncertainty (k=2)						**± 23.2 %**	**± 22.8 %**	

The above measurement uncertainties are according to IEEE Std 1528

5200 MHz Head (SN: 7368)

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1g	(Ci) 10g	Standard (1g)	Standard (10g)	vi 2 or Veff
Measurement System								
Probe calibration	± 6.55	Normal	1	1	1	± 6.6 %	± 6.6 %	∞
Isotropy	± 1.3	Normal	1	1	1	± 1.3 %	± 1.3 %	∞
Boundary Effects	± 2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %	∞
Probe Linearity	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Probe modulation response	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Detection limits	± 0.25	Rectangular	√3	1	1	± 0.14 %	± 0.14 %	∞
Readout Electronics	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Response time	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Integration time	± 2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Conditions – Noise	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
RF Ambient Conditions – Reflections	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Probe Positioning	± 6.7	Rectangular	√3	1	1	± 3.9 %	± 3.9 %	∞
Algorithms for Max. SAR Eval.	± 4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	∞
Test Sample Related								
Device Positioning	± 2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	± 3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	5
Power Drift	± 5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %	∞
SAR Scaling	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Physical Parameters								
Phantom Shell	± 7.6	Rectangular	√3	1	1	± 4.4 %	± 4.4 %	∞
SAR correction	± 0.0	Normal	1	1	0.84	± 0.0 %	± 0.0 %	∞
Liquid conductivity (Target)	± 5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %	∞
Liquid conductivity (Meas.)	± 3.9	Normal	1	0.78	0.71	± 3.0 %	± 2.8 %	10
Liquid permittivity (Target)	± 5.0	Rectangular	√3	0.60	0.49	± 1.7 %	± 1.4 %	∞
Liquid permittivity (Meas.)	± 3.7	Normal	1	0.23	0.26	± 0.9 %	± 1.0 %	10
Temp. unc. - Conductivity	± 2.0	Rectangular	√3	0.78	0.71	± 0.9 %	± 0.8 %	∞
Temp. unc. - Permittivity	± 2.0	Rectangular	√3	0.23	0.26	± 0.3 %	± 0.3 %	∞
Combined Standard Uncertainty						**± 11.9 %**	**± 11.7 %**	330
Expanded Uncertainty (k=2)						**± 23.8 %**	**± 23.4 %**	

The above measurement uncertainties are according to IEEE Std 1528

5300 MHz Body (SN: 7368)

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1g	(Ci) 10g	Standard (1g)	Standard (10g)	vi 2 or Veff
Measurement System								
Probe calibration	± 6.55	Normal	1	1	1	± 6.6 %	± 6.6 %	∞
Isotropy	± 1.3	Normal	1	1	1	± 1.3 %	± 1.3 %	∞
Boundary Effects	± 2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %	∞
Probe Linearity	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Probe modulation response	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Detection limits	± 0.25	Rectangular	√3	1	1	± 0.14 %	± 0.14 %	∞
Readout Electronics	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Response time	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Integration time	± 2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Conditions – Noise	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
RF Ambient Conditions – Reflections	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Probe Positioning	± 6.7	Rectangular	√3	1	1	± 3.9 %	± 3.9 %	∞
Algorithms for Max. SAR Eval.	± 4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	∞
Test Sample Related								
Device Positioning	± 2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	± 3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	5
Power Drift	± 5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %	∞
SAR Scaling	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Physical Parameters								
Phantom Shell	± 7.6	Rectangular	√3	1	1	± 4.4 %	± 4.4 %	∞
SAR correction	± 0.0	Normal	1	1	0.84	± 0.0 %	± 0.0 %	∞
Liquid conductivity (Target)	± 5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %	∞
Liquid conductivity (Meas.)	± 4.0	Normal	1	0.78	0.71	± 3.1 %	± 2.8 %	10
Liquid permittivity (Target)	± 5.0	Rectangular	√3	0.60	0.49	± 1.7 %	± 1.4 %	∞
Liquid permittivity (Meas.)	± 4.3	Normal	1	0.23	0.26	± 1.0 %	± 1.1 %	10
Temp. unc. - Conductivity	± 1.9	Rectangular	√3	0.78	0.71	± 0.9 %	± 0.8 %	∞
Temp. unc. - Permittivity	± 1.7	Rectangular	√3	0.23	0.26	± 0.2 %	± 0.3 %	∞
Combined Standard Uncertainty						**± 11.9 %**	**± 11.7 %**	330
Expanded Uncertainty (k=2)						**± 23.8 %**	**± 23.4 %**	

The above measurement uncertainties are according to IEEE Std 1528

5500 MHz Body (SN: 7368)

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1g	(Ci) 10g	Standard (1g)	Standard (10g)	vi 2 or Veff
Measurement System								
Probe calibration	± 6.55	Normal	1	1	1	± 6.6 %	± 6.6 %	∞
Isotropy	± 1.3	Normal	1	1	1	± 1.3 %	± 1.3 %	∞
Boundary Effects	± 2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %	∞
Probe Linearity	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Probe modulation response	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Detection limits	± 0.25	Rectangular	√3	1	1	± 0.14 %	± 0.14 %	∞
Readout Electronics	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Response time	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Integration time	± 2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Conditions – Noise	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
RF Ambient Conditions – Reflections	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Probe Positioning	± 6.7	Rectangular	√3	1	1	± 3.9 %	± 3.9 %	∞
Algorithms for Max. SAR Eval.	± 4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	∞
Test Sample Related								
Device Positioning	± 2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	± 3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	5
Power Drift	± 5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %	∞
SAR Scaling	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Physical Parameters								
Phantom Shell	± 7.6	Rectangular	√3	1	1	± 4.4 %	± 4.4 %	∞
SAR correction	± 0.0	Normal	1	1	0.84	± 0.0 %	± 0.0 %	∞
Liquid conductivity (Target)	± 5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %	∞
Liquid conductivity (Meas.)	± 3.9	Normal	1	0.78	0.71	± 3.0 %	± 2.8 %	10
Liquid permittivity (Target)	± 5.0	Rectangular	√3	0.60	0.49	± 1.7 %	± 1.4 %	∞
Liquid permittivity (Meas.)	± 4.0	Normal	1	0.23	0.26	± 0.9 %	± 1.0 %	10
Temp. unc. - Conductivity	± 1.9	Rectangular	√3	0.78	0.71	± 0.9 %	± 0.8 %	∞
Temp. unc. - Permittivity	± 1.9	Rectangular	√3	0.23	0.26	± 0.3 %	± 0.3 %	∞
Combined Standard Uncertainty						**± 11.9 %**	**± 11.7 %**	330
Expanded Uncertainty (k=2)						**± 23.8 %**	**± 23.4 %**	

The above measurement uncertainties are according to IEEE Std 1528

5600 MHz Head (SN: 7368)

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1g	(Ci) 10g	Standard (1g)	Standard (10g)	vi 2 or Veff
Measurement System								
Probe calibration	± 6.55	Normal	1	1	1	± 6.6 %	± 6.6 %	∞
Isotropy	± 1.3	Normal	1	1	1	± 1.3 %	± 1.3 %	∞
Boundary Effects	± 2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %	∞
Probe Linearity	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Probe modulation response	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Detection limits	± 0.25	Rectangular	√3	1	1	± 0.14 %	± 0.14 %	∞
Readout Electronics	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Response time	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Integration time	± 2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Conditions – Noise	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
RF Ambient Conditions – Reflections	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Probe Positioning	± 6.7	Rectangular	√3	1	1	± 3.9 %	± 3.9 %	∞
Algorithms for Max. SAR Eval.	± 4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	∞
Test Sample Related								
Device Positioning	± 2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	± 3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	5
Power Drift	± 5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %	∞
SAR Scaling	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Physical Parameters								
Phantom Shell	± 7.6	Rectangular	√3	1	1	± 4.4 %	± 4.4 %	∞
SAR correction	± 0.0	Normal	1	1	0.84	± 0.0 %	± 0.0 %	∞
Liquid conductivity (Target)	± 5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %	∞
Liquid conductivity (Meas.)	± 4.1	Normal	1	0.78	0.71	± 3.2 %	± 2.9 %	10
Liquid permittivity (Target)	± 5.0	Rectangular	√3	0.60	0.49	± 1.7 %	± 1.4 %	∞
Liquid permittivity (Meas.)	± 4.3	Normal	1	0.23	0.26	± 1.0 %	± 1.1 %	10
Temp. unc. - Conductivity	± 1.8	Rectangular	√3	0.78	0.71	± 0.8 %	± 0.7 %	∞
Temp. unc. - Permittivity	± 1.9	Rectangular	√3	0.23	0.26	± 0.3 %	± 0.3 %	∞
Combined Standard Uncertainty						**± 11.9 %**	**± 11.7 %**	330
Expanded Uncertainty (k=2)						**± 23.8 %**	**± 23.4 %**	

The above measurement uncertainties are according to IEEE Std 1528

16. CONCLUSION

Measurement Conclusion

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the FCC. These measurements are taken to simulate the RF effects exposure under the worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters subject to the test. The test results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are every complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role impossible biological effect are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease).

Because innumerable factors may interact to determine the specific biological outcome of an exposure to electromagnetic fields, any protection guide shall consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables.

17. REFERENCES

[1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.

[2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radiofrequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.

[3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radiofrequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.

[4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.

[5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2003,Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices.

[6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for Radio Frequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.

[7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.

[8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. -124.

[9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.

[10] Schmid& Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.

[11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct.1996, pp. 1865-1873.

[12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.

[13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bio electromagnetics, Canada: 1987, pp. 29-36.

[14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.

[15] W. Gander, Computer mathematick, Birkhaeuser, Basel, 1992.

[16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.

[17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

[18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.

[19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hoschschule Zürich, Dosimetric Evaluation of the Cellular Phone.

[20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300MHz to 3 GHz), Feb. 2005.

[21] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radio communication Apparatus (All Frequency Bands) Issue 5, March 2015.

[22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009

[23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225,D01-D07

[24] SAR Measurement procedures for IEEE 802.11a/b/g KDB Publication 248227 D01v02

[25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474D02-D04

[26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04

[27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02

[28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02

[29] 615223 D01 802 16e WI-Max SAR Guidance v01, Nov. 13, 2009

[30] Anexo à Resolução No. 533, de 10 de September de 2009.

[31] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body(frequency range of 30 MHz to 6 GHz), Mar. 2010.

APPENDIX A. – Probe Calibration Data

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **DT&C (Dymstec)**

Certificate No: ES3-3328_Mar19

CALIBRATION CERTIFICATE

Object	ES3DV3 - SN:3328
Calibration procedure(s)	QA CAL-01.v9, QA CAL-12.v9, QA CAL-14.v5, QA CAL-23.v5, QA CAL-25.v7 Calibration procedure for dosimetric E-field probes
Calibration date:	March 28, 2019

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-18 (No. 217-02682)	Apr-19
DAE4	SN: 660	19-Dec-18 (No. DAE4-660_Dec18)	Dec-19
Reference Probe ES3DV2	SN: 3013	31-Dec-18 (No. ES3-3013_Dec18)	Dec-19
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-18)	In house check: Jun-20
Network Analyzer E8358A	SN: US41080477	31-Mar-14 (in house check Oct-18)	In house check: Oct-19

	Name	Function	Signature
Calibrated by:	Claudio Leubler	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: March 28, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Glossary:

TSL	tissue simulating liquid
NORMx,y,z	sensitivity in free space
ConvF	sensitivity in TSL / NORMx,y,z
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., ϑ = 0 is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
b) IEC 62209-1, ", "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- *NORMx,y,z:* Assessed for E-field polarization ϑ = 0 (f ≤ 900 MHz in TEM-cell; f > 1800 MHz: R22 waveguide). NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMx,y,z does not affect the E^2-field uncertainty inside TSL (see below *ConvF*).
- *NORM(f)x,y,z = NORMx,y,z * frequency_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- *DCPx,y,z:* DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- *PAR:* PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- *Ax,y,z; Bx,y,z; Cx,y,z; Dx,y,z; VRx,y,z: A, B, C, D* are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. *VR* is the maximum calibration range expressed in RMS voltage across the diode.
- *ConvF and Boundary Effect Parameters:* Assessed in flat phantom using E-field (or Temperature Transfer Standard for f ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to *NORMx,y,z * ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- *Spherical isotropy (3D deviation from isotropy)*: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- *Sensor Offset*: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- *Connector Angle*: The angle is assessed using the information gained by determining the *NORMx* (no uncertainty required).

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3328

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu V/(V/m)^2$)[A]	1.03	1.05	1.08	± 10.1 %
DCP (mV)[B]	106.5	105.2	105.6	

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB$\sqrt{\mu V}$	C	D dB	VR mV	Max dev.	Unc[E] (k=2)
0	CW	X	0.0	0.0	1.0	0.00	191.9	±3.5 %	± 4.7 %
		Y	0.0	0.0	1.0		191.3		
		Y	0.0	0.0	1.0		191.2		

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

[A] The uncertainties of Norm X,Y,Z do not affect the E^2-field uncertainty inside TSL (see Pages 5 and 6).
[B] Numerical linearization parameter: uncertainty not required.
[E] Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3328

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-22.1
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3328

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) [C]	Relative Permittivity [F]	Conductivity (S/m) [F]	ConvF X	ConvF Y	ConvF Z	Alpha [G]	Depth [G] (mm)	Unc (k=2)
750	41.9	0.89	6.53	6.53	6.53	0.34	1.73	± 12.0 %
835	41.5	0.90	6.26	6.26	6.26	0.62	1.27	± 12.0 %
900	41.5	0.97	6.16	6.16	6.16	0.43	1.56	± 12.0 %
1750	40.1	1.37	5.42	5.42	5.42	0.80	1.12	± 12.0 %
1900	40.0	1.40	5.10	5.10	5.10	0.67	1.28	± 12.0 %
2450	39.2	1.80	4.67	4.67	4.67	0.80	1.30	± 12.0 %
2600	39.0	1.96	4.46	4.46	4.46	0.75	1.35	± 12.0 %

[C] Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4-9 MHz, and ConvF assessed at 13 MHz is 9-19 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.
[F] At frequencies below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.
[G] Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3328

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) [C]	Relative Permittivity [F]	Conductivity (S/m) [F]	ConvF X	ConvF Y	ConvF Z	Alpha [G]	Depth [G] (mm)	Unc (k=2)
750	55.5	0.96	6.26	6.26	6.26	0.56	1.33	± 12.0 %
835	55.2	0.97	6.14	6.14	6.14	0.80	1.17	± 12.0 %
900	55.0	1.05	6.26	6.26	6.26	0.54	1.43	± 12.0 %
1750	53.4	1.49	5.01	5.01	5.01	0.58	1.40	± 12.0 %
1900	53.3	1.52	4.81	4.81	4.81	0.61	1.44	± 12.0 %
2450	52.7	1.95	4.43	4.43	4.43	0.80	1.20	± 12.0 %
2600	52.5	2.16	4.26	4.26	4.26	0.80	1.20	± 12.0 %

[C] Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4-9 MHz, and ConvF assessed at 13 MHz is 9-19 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.
[F] At frequencies below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.
[G] Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

ES3DV3– SN:3328 March 28, 2019

Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: ± 6.3% (k=2)

ES3DV3– SN:3328 March 28, 2019

Receiving Pattern (ϕ), ϑ = 0°

f=600 MHz,TEM



f=1800 MHz,R22





Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)

ES3DV3– SN:3328 March 28, 2019

Dynamic Range f(SAR$_{head}$)
(TEM cell , f_{eval}= 1900 MHz)





Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Certificate No: ES3-3328_Mar19 Page 9 of 10

ES3DV3– SN:3328 March 28, 2019

Conversion Factor Assessment

f = 835 MHz,WGLS R9 (H_convF)



f = 1900 MHz,WGLS R22 (H_convF)



Deviation from Isotropy in Liquid

Error (ϕ, ϑ), f = 900 MHz





Uncertainty of Spherical Isotropy Assessment: ± 2.6% (k=2)

Certificate No: ES3-3328_Mar19 Page 10 of 10

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **DT&C (Dymstec)** Certificate No: **EX3-7368_Aug19**

CALIBRATION CERTIFICATE

Object	EX3DV4 - SN:7368
Calibration procedure(s)	QA CAL-01.v9, QA CAL-14.v5, QA CAL-23.v5, QA CAL-25.v7 Calibration procedure for dosimetric E-field probes
Calibration date:	August 27, 2019

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	03-Apr-19 (No. 217-02892/02893)	Apr-20
Power sensor NRP-Z91	SN: 103244	03-Apr-19 (No. 217-02892)	Apr-20
Power sensor NRP-Z91	SN: 103245	03-Apr-19 (No. 217-02893)	Apr-20
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-19 (No. 217-02894)	Apr-20
DAE4	SN: 660	19-Dec-18 (No. DAE4-660_Dec18)	Dec-19
Reference Probe ES3DV2	SN: 3013	31-Dec-18 (No. ES3-3013_Dec18)	Dec-19
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-18)	In house check: Jun-20
Network Analyzer E8358A	SN: US41080477	31-Mar-14 (in house check Oct-18)	In house check: Oct-19

	Name	Function	Signature
Calibrated by:	Leif Klysner	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: August 29, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
NORMx,y,z	sensitivity in free space
ConvF	sensitivity in TSL / NORMx,y,z
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., ϑ = 0 is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
b) IEC 62209-1, ", "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- *NORMx,y,z:* Assessed for E-field polarization ϑ = 0 (f ≤ 900 MHz in TEM-cell; f > 1800 MHz: R22 waveguide). NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMx,y,z does not affect the E^2-field uncertainty inside TSL (see below *ConvF*).
- *NORM(f)x,y,z = NORMx,y,z * frequency_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- *DCPx,y,z:* DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- *PAR:* PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- *Ax,y,z; Bx,y,z; Cx,y,z; Dx,y,z; VRx,y,z: A, B, C, D* are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. *VR* is the maximum calibration range expressed in RMS voltage across the diode.
- *ConvF and Boundary Effect Parameters:* Assessed in flat phantom using E-field (or Temperature Transfer Standard for f ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to *NORMx,y,z * ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- *Spherical isotropy (3D deviation from isotropy)*: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- *Sensor Offset*: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- *Connector Angle*: The angle is assessed using the information gained by determining the *NORMx* (no uncertainty required).

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7368

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu V/(V/m)^2$)[A]	0.49	0.42	0.44	± 10.1 %
DCP (mV)[B]	99.8	103.4	99.6	

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB√μV	C	D dB	VR mV	Max dev.	Unc[E] (k=2)
0	CW	X	0.0	0.0	1.0	0.00	183.4	±3.5 %	± 4.7 %
		Y	0.0	0.0	1.0		175.0		
		Z	0.0	0.0	1.0		177.6		

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

[A] The uncertainties of Norm X,Y,Z do not affect the E^2-field uncertainty inside TSL (see Page 5).
[B] Numerical linearization parameter: uncertainty not required.
[E] Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7368

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	19.3
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7368

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) [C]	Relative Permittivity [F]	Conductivity (S/m) [F]	ConvF X	ConvF Y	ConvF Z	Alpha [G]	Depth [G] (mm)	Unc (k=2)
750	41.9	0.89	10.12	10.12	10.12	0.50	0.80	± 12.0 %
835	41.5	0.90	9.83	9.83	9.83	0.35	1.02	± 12.0 %
900	41.5	0.97	9.63	9.63	9.63	0.51	0.85	± 12.0 %
1750	40.1	1.37	8.45	8.45	8.45	0.40	0.85	± 12.0 %
1900	40.0	1.40	8.06	8.06	8.06	0.31	0.85	± 12.0 %
2450	39.2	1.80	7.61	7.61	7.61	0.32	0.95	± 12.0 %
2600	39.0	1.96	7.52	7.52	7.52	0.46	0.88	± 12.0 %
3500	37.9	2.91	7.01	7.01	7.01	0.30	1.35	± 13.1 %
3700	37.7	3.12	6.97	6.97	6.97	0.30	1.35	± 13.1 %
5200	36.0	4.66	5.19	5.19	5.19	0.40	1.80	± 13.1 %
5300	35.9	4.76	4.97	4.97	4.97	0.40	1.80	± 13.1 %
5500	35.6	4.96	4.90	4.90	4.90	0.40	1.80	± 13.1 %
5600	35.5	5.07	4.66	4.66	4.66	0.40	1.80	± 13.1 %
5800	35.3	5.27	4.61	4.61	4.61	0.40	1.80	± 13.1 %

[C] Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4-9 MHz, and ConvF assessed at 13 MHz is 9-19 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.
[F] At frequencies below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.
[G] Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4– SN:7368 August 27, 2019

Frequency Response of E-Field
(TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: ± 6.3% (k=2)

EX3DV4– SN:7368 August 27, 2019

Receiving Pattern (ϕ), ϑ = 0°

f=600 MHz,TEM



f=1800 MHz,R22





Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)

EX3DV4– SN:7368 August 27, 2019

Dynamic Range f(SAR$_{head}$)
(TEM cell , f_{eval}= 1900 MHz)





Uncertainty of Linearity Assessment: ± 0.6% (k=2)

EX3DV4– SN:7368 August 27, 2019

Conversion Factor Assessment

f = 835 MHz,WGLS R9 (H_convF)



f = 1900 MHz,WGLS R22 (H_convF)



Deviation from Isotropy in Liquid

Error (ϕ, ϑ), f = 900 MHz



Uncertainty of Spherical Isotropy Assessment: ± 2.6% (k=2)

Certificate No: EX3-7368_Aug19 Page 9 of 9

APPENDIX B. – Dipole Calibration Data

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **DT&C (Dymstec)**

Certificate No: D750V3-1049_Jan19

CALIBRATION CERTIFICATE

Object	D750V3 - SN:1049
Calibration procedure(s)	QA CAL-05.v11 Calibration Procedure for SAR Validation Sources between 0.7-3 GHz
Calibration date:	January 25, 2019

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-18 (No. 217-02682)	Apr-19
Type-N mismatch combination	SN: 5047.2 / 06327	04-Apr-18 (No. 217-02683)	Apr-19
Reference Probe EX3DV4	SN: 7349	31-Dec-18 (No. EX3-7349_Dec18)	Dec-19
DAE4	SN: 601	04-Oct-18 (No. DAE4-601_Oct18)	Oct-19

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-18)	In house check: Oct-20
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-18)	In house check: Oct-20
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-18)	In house check: Oct-20
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-18)	In house check: Oct-20
Network Analyzer Agilent E8358A	SN: US41080477	31-Mar-14 (in house check Oct-18)	In house check: Oct-19

	Name	Function	Signature
Calibrated by:	Claudio Leubler	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: January 25, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

e) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.2
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	750 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	**Permittivity**	**Conductivity**
Nominal Head TSL parameters	22.0 °C	41.9	0.89 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	41.5 ± 6 %	0.89 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.10 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	**8.38 W/kg ± 17.0 % (k=2)**

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.38 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	**5.51 W/kg ± 16.5 % (k=2)**

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	**Permittivity**	**Conductivity**
Nominal Body TSL parameters	22.0 °C	55.5	0.96 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	54.8 ± 6 %	0.96 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.18 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	**8.70 W/kg ± 17.0 % (k=2)**

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.44 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	**5.75 W/kg ± 16.5 % (k=2)**

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	54.9 Ω - 1.8 jΩ
Return Loss	- 26.1 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	50.0 Ω - 5.2 jΩ
Return Loss	- 25.7 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.037 ns

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.
No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG

DASY5 Validation Report for Head TSL

Date: 25.01.2019

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1049

Communication System: UID 0 - CW; Frequency: 750 MHz
Medium parameters used: f = 750 MHz; σ = 0.89 S/m; ε_r = 41.5; ρ = 1000 kg/m^3
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.32, 10.32, 10.32) @ 750 MHz; Calibrated: 31.12.2018
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.10.2018
- Phantom: Flat Phantom 4.9 (front); Type: QD 00L P49 AA; Serial: 1001
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 59.22 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 3.17 W/kg
SAR(1 g) = 2.1 W/kg; SAR(10 g) = 1.38 W/kg
Maximum value of SAR (measured) = 2.78 W/kg



0 dB = 2.78 W/kg = 4.44 dBW/kg

Impedance Measurement Plot for Head TSL



DASY5 Validation Report for Body TSL

Date: 25.01.2019

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 750 MHz; Type: D750V3; Serial: D750V3 - SN:1049

Communication System: UID 0 - CW; Frequency: 750 MHz
Medium parameters used: f = 750 MHz; σ = 0.96 S/m; ε_r = 54.8; ρ = 1000 kg/m^3
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.29, 10.29, 10.29) @ 750 MHz; Calibrated: 31.12.2018
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.10.2018
- Phantom: Flat Phantom 4.9 (Back); Type: QD 00R P49 AA; Serial: 1005
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 56.84 V/m; Power Drift = 0.00 dB
Peak SAR (extrapolated) = 3.25 W/kg
SAR(1 g) = 2.18 W/kg; SAR(10 g) = 1.44 W/kg
Maximum value of SAR (measured) = 2.89 W/kg



0 dB = 2.89 W/kg = 4.61 dBW/kg

Impedance Measurement Plot for Body TSL



Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **DT&C (Dymstec)**

Certificate No: **D835V2-464_Jul19**

CALIBRATION CERTIFICATE

Object	D835V2 - SN:464
Calibration procedure(s)	QA CAL-05.v11 Calibration Procedure for SAR Validation Sources between 0.7-3 GHz
Calibration date:	July 18, 2019

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	03-Apr-19 (No. 217-02892/02893)	Apr-20
Power sensor NRP-Z91	SN: 103244	03-Apr-19 (No. 217-02892)	Apr-20
Power sensor NRP-Z91	SN: 103245	03-Apr-19 (No. 217-02893)	Apr-20
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-19 (No. 217-02894)	Apr-20
Type-N mismatch combination	SN: 5047.2 / 06327	04-Apr-19 (No. 217-02895)	Apr-20
Reference Probe EX3DV4	SN: 7349	29-May-19 (No. EX3-7349_May19)	May-20
DAE4	SN: 601	30-Apr-19 (No. DAE4-601_Apr19)	Apr-20

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB39512475	30-Oct-14 (in house check Feb-19)	In house check: Oct-20
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-18)	In house check: Oct-20
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-18)	In house check: Oct-20
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-18)	In house check: Oct-20
Network Analyzer Agilent E8358A	SN: US41080477	31-Mar-14 (in house check Oct-18)	In house check: Oct-19

	Name	Function	Signature
Calibrated by:	Claudio Leubler	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: July 19, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

e) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.2
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	**Permittivity**	**Conductivity**
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	42.0 ± 6 %	0.91 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm^3 (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.41 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	**9.59 W/kg ± 17.0 % (k=2)**

SAR averaged over 10 cm^3 (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.56 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	**6.21 W/kg ± 16.5 % (k=2)**

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	**Permittivity**	**Conductivity**
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	54.9 ± 6 %	0.99 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm^3 (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.46 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	**9.68 W/kg ± 17.0 % (k=2)**

SAR averaged over 10 cm^3 (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.60 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	**6.32 W/kg ± 16.5 % (k=2)**

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	49.5 Ω - 2.2 jΩ
Return Loss	- 32.9 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	47.0 Ω - 3.0 jΩ
Return Loss	- 27.2 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.382 ns

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.
No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG

DASY5 Validation Report for Head TSL

Date: 18.07.2019

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:464

Communication System: UID 0 - CW; Frequency: 835 MHz
Medium parameters used: f = 835 MHz; σ = 0.91 S/m; ε_r = 42; ρ = 1000 kg/m^3
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(9.89, 9.89, 9.89) @ 835 MHz; Calibrated: 29.05.2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.04.2019
- Phantom: Flat Phantom 4.9 (front); Type: QD 00L P49 AA; Serial: 1001
- DASY52 52.10.2(1504); SEMCAD X 14.6.12(7470)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 63.02 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 3.57 W/kg
SAR(1 g) = 2.41 W/kg; SAR(10 g) = 1.56 W/kg
Maximum value of SAR (measured) = 3.18 W/kg



0 dB = 3.18 W/kg = 5.02 dBW/kg

Impedance Measurement Plot for Head TSL



DASY5 Validation Report for Body TSL

Date: 18.07.2019

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:464

Communication System: UID 0 - CW; Frequency: 835 MHz
Medium parameters used: f = 835 MHz; σ = 0.99 S/m; ε_r = 54.9; ρ = 1000 kg/m^3
Phantom section: Flat Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.16, 10.16, 10.16) @ 835 MHz; Calibrated: 29.05.2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.04.2019
- Phantom: Flat Phantom 4.9 (Back); Type: QD 00R P49 AA; Serial: 1005
- DASY52 52.10.2(1504); SEMCAD X 14.6.12(7470)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 57.99 V/m; Power Drift = 0.00 dB
Peak SAR (extrapolated) = 3.65 W/kg
SAR(1 g) = 2.46 W/kg; SAR(10 g) = 1.6 W/kg
Maximum value of SAR (measured) = 3.27 W/kg



0 dB = 3.27 W/kg = 5.15 dBW/kg

Impedance Measurement Plot for Body TSL