

TEST REPORT

Report number : JPD-TR-17100-0

Issue date : May 15, 2017

The device, as described herewith, was tested pursuant to applicable test procedure and complies with the requirements of;

FCC Part15 Subpart C

The test results are traceable to the international or national standards.

Applicant	: KYOCERA Corporation
Equipment under test (EUT)	: Mobile Phone
Model number	: DA58
FCC ID	: JOYDA58

Date of test : March 21, 27, 28, 29, 2017
April 6, 17, 18, 2017
Test place : TÜV SÜD Zacta Ltd. Yonezawa Testing Center
5-4149-7, Hachimanpara, Yonezawa-shi,
Yamagata, 992-1128 Japan
Phone: +81-238-28-2881 Fax: +81-238-28-2888
Test results : Complied

The results in this report are applicable only to the equipment tested.
This report shall not be re-produced except in full without the written approval of TÜV SÜD Zacta Ltd.
This test report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, ILAC-MRA, or any agency of the federal government.

Tested by : Taiki Watanabe Tadahiro Seino
Taiki Watanabe Tadahiro Seino

Approved by : Hiroaki Suzuki
Hiroaki Suzuki
Lab Manager of RF Lab



Table of contents

	Page
1. Summary of Test	4
1.1 Purpose of test	4
1.2 Standards	4
1.3 List of applied test to the EUT	4
1.4 Modification to the EUT by laboratory	4
2. Equipment Under Test	5
2.1 General Description of equipment	5
2.2 EUT information	5
2.3 Variation of the family model(s)	6
2.4 Operating channels and frequencies	6
2.5 Operating mode	6
2.6 Operating flow	7
3. Configuration of equipment	8
3.1 Equipment(s) used	8
3.2 Cable(s) used	8
3.3 System configuration	8
4. DTS Bandwidth / Occupied Bandwidth (99%)	9
4.1 Measurement procedure	9
4.2 Limit	9
4.3 Measurement result	9
4.4 Trace data	10
5. Maximum conducted (average) output power	13
5.1 Measurement procedure	13
5.2 Limit	13
5.3 Measurement result	13
5.4 Trace data	15
6. Band Edge Compliance of RF Conducted Emissions	18
6.1 Measurement procedure	18
6.2 Limit	18
6.3 Measurement result	19
6.4 Trace data	20
7. Spurious emissions - Conducted -	23
7.1 Measurement procedure	23
7.2 Limit	23
7.3 Measurement result	23
8. Spurious Emissions - Radiated -	33
8.1 Measurement procedure	33
8.2 Calculation method	34
8.3 Limit	34
8.4 Test data	35
9. Restricted Band of Operation	57
9.1 Measurement procedure	57
9.2 Limit	57



Zacta

9.3 Measurement Result.....	58
9.4 Test data.....	58
10. Transmitter Power Spectral Density.....	65
10.1 Measurement procedure.....	65
10.2 Limit.....	65
10.3 Measurement result.....	65
11. AC Power Line Conducted Emissions.....	70
11.1 Measurement procedure.....	70
11.2 Calculation method.....	70
11.3 Limit.....	71
11.4 Test data.....	71
12. Antenna requirement.....	72
13. Uncertainty of measurement.....	73
14. Laboratory Information.....	74
Appendix A. Test equipment.....	75
Appendix B. Duty Cycle.....	76

1. Summary of Test

1.1 Purpose of test

It is the original test in order to verify conformance to FCC Part 15 Subpart C.

1.2 Standards

CFR47 FCC Part 15 Subpart C

1.2.1 Test Methods

ANSI C63.10-2013, KDB 558074 D01 DTS Meas Guidance v04

1.2.2 Deviation from standards

None

1.3 List of applied test to the EUT

Test items Section	Test items	Condition	Result
15.247(a)(2)	DTS Bandwidth / Occupied Bandwidth (99%)	Conducted	PASS
15.247(b)(3)	Maximum conducted (average) output power	Conducted	PASS
15.247(d)	Band Edge Compliance of RF Conducted Emissions	Conducted	PASS
15.247(d) 15.205 15.209	Spurious Emissions	Conducted Radiated	PASS
15.247(d) 15.205 15.209	Restricted Bands of Operation	Radiated	PASS
15.247(e)	Transmitter Power Spectral Density	Conducted	PASS
15.207	AC Power Line Conducted Emissions	Conducted	PASS

1.3.1 Test set up

Table-Top

1.4 Modification to the EUT by laboratory

None

2. Equipment Under Test

2.1 General Description of equipment

EUT is the Mobile Phone.

2.2 EUT information

Applicant	: KYOCERA Corporation Yokohama Office 2-1-1 Kagahara, Tsuzuki-ku Yokohama-shi, Kanagawa, Japan Phone: +81-45-943-6253 Fax: +81-45-943-6314
Equipment under test	: Mobile Phone
Trade name	: Kyocera
Model number	: DA58
Serial number	: N/A
EUT condition	: Pre-Production
Power ratings	: Battery: DC 3.8V
Size	: (W) 71.0 × (D) 13.6 × (H) 145.0 mm
Environment	: Indoor and Outdoor use
Terminal limitation	: -20°C to 60°C
RF Specification Protocol	: IEEE802.11b, IEEE802.11g, IEEE802.11n (HT20)
Frequency range	: IEEE802.11b /11g/11n (HT20): 2412MHz-2462MHz
Number of RF Channels	: 11 Channels
Modulation type	: IEEE802.11b: DSSS (DBPSK, DQPSK, CCK) IEEE802.11g / n (HT20) : OFDM (BPSK, QPSK, 16QAM, 64QAM)
Data rate	: IEEE802.11b: 1, 2, 5.5, 11Mbps IEEE802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps IEEE802.11n (HT20 LGI): 6.5, 13, 19.5, 26, 39, 52, 58.5, 65Mbps IEEE802.11n (HT20 SGI): 7.2, 14.4, 21.7, 28.9, 43.3, 57.8, 65, 72.2Mbps
Channel separation	: 5MHz
Output power	: 27.925mW (IEEE802.11b) 17.179mW (IEEE802.11g) 17.458mW (IEEE802.11n: HT20)
Antenna type	: Internal antenna
Antenna gain	: -5.8dBi

2.3 Variation of the family model(s)

Not applicable

2.4 Operating channels and frequencies

Channel	Frequency [MHz]
1	2412
2	2417
3	2422
4	2427
5	2432
6	2437
7	2442
8	2447
9	2452
10	2457
11	2462

2.5 Operating mode

The EUT had been tested under operating condition.
There are three channels have been tested as following:

Tested Channel	Frequency [MHz]
Low	2412
Middle	2437
High	2462

The pre-test has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates.

Tested Channel	Modulation Type	Data Rate
Low, Middle, High	IEEE802.11b: DSSS	1Mbps
Low, Middle, High	IEEE802.11g: OFDM	6Mbps
Low, Middle, High	IEEE802.11n (HT20 LGI): OFDM	MCS0 (6.5Mbps)

The field strength of spurious emissions was measured at each position of all three axis X, Y and Z to compare the level, and the maximum noise.

The worst emission was found in X axis and the worst case recorded.

2.6 Operating flow

[Tx mode]

- i) Test program setup to the DM tool
- ii) Select a Test mode
[IEEE802.11b, IEEE802.11g, IEEE802.11n (HT20)]
Operating frequency: Channel Low: 2412MHz, Channel Middle: 2437MHz, Channel High: 2462MHz
- iii) Start test mode

[Rx mode]

- i) Test program setup to the DM tool
- ii) Select a Test mode
[IEEE802.11b, IEEE802.11g, IEEE802.11n (HT20)]
Operating frequency: Channel Low: 2412MHz, Channel Middle: 2437MHz, Channel High: 2462MHz
- iii) Start test mode

3. Configuration of equipment

3.1 Equipment(s) used

No.	Equipment	Company	Model No.	Serial No.	FCC ID / DoC	Comment
1	Mobile Phone	KYOCERA	DA58	N/A	JOYDA58	EUT
2	AC Adapter	au	N/A	N/A	N/A	*


*: AC power line Conducted Emission Test.

3.2 Cable(s) used

No.	Cable	Length[m]	Shield	Connector	Comment
a	Micro USB cable (for AC Adapter)	1.0	Yes	Metal	*

*: AC power line Conducted Emission Test.

3.3 System configuration



Note1: Numbers assigned to equipment or cables on this diagram correspond to the list in "3.1 Equipment(s) used" and "3.2 Cable(s) used".

4. DTS Bandwidth / Occupied Bandwidth (99%)

4.1 Measurement procedure


[FCC 15.247(a)(2), KDB 558074 D01 v04, Section 8.2]

The bandwidth at 6dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;

- a) RBW = 100kHz.
- b) VBW $\geq 3 \times$ RBW.
- c) Sweep time = auto-couple.
- d) Detector = peak.
- e) Trace mode = max hold.

- Test configuration



4.2 Limit

The minimum permissible 6dB bandwidth is 500kHz.

4.3 Measurement result

Date : March 21, 2017
 Temperature : 23.6 [°C]
 Humidity : 47.1 [%]
 Test place : Shielded room No.4

Test engineer : Tadahiro Seino


[IEEE802.11b, IEEE802.11g, IEEE802.11n (HT20)]

Channel	Frequency [MHz]	DTS Bandwidth [MHz]		
		IEEE802.11b	IEEE802.11g	IEEE802.11n (HT20)
Low	2412	8.570	16.417	17.632
Middle	2437	8.574	16.425	17.617
High	2462	8.584	16.397	17.596


Channel	Frequency [MHz]	Occupied Bandwidth (99%) [MHz]		
		IEEE802.11b	IEEE802.11g	IEEE802.11n (HT20)
Low	2412	13.244	16.551	17.696
Middle	2437	13.155	16.519	17.694
High	2462	13.228	16.541	17.694

4.4 Trace data
[IEEE802.11b]


Channel Low



Channel Middle




Channel High




[IEEE802.11g]


Channel Low



Channel Middle




Channel High




[IEEE802.11n (HT20)]


Channel Low



Channel Middle



Channel High



5. Maximum conducted (average) output power

5.1 Measurement procedure


[FCC 15.247(b)(3), KDB 558074 D01 v04, Section 9.2.2.2 Method AVGSA-1]

The peak power is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;

- a) RBW = 1-5% of the OBW, not to exceed 1MHz.
- b) VBW $\geq 3 \times$ RBW.
- c) Span ≥ 1.5 times the OBW.
- d) Sweep time = auto-couple.
- e) Detector = RMS.
- f) Trace mode = Clear/Write, Single, 100 count
- g) Points $\geq 2 \times$ Span / RBW

- Test configuration



5.2 Limit

1W (1000mW) or less

5.3 Measurement result

Date : March 21, 2017
 Temperature : 23.6 [°C]
 Humidity : 47.1 [%]
 Test place : Shielded room No.4

Test engineer :
 Tadahiro Seino

[IEEE802.11b]
Battery Full

Channel	Center Frequency (MHz)	Reading (dBm)	Factor (dB)	Level (dBm)	Output Power (mW)	Limit (mW)	Result
Low	2412	3.98	10.48	14.46	27.925	≤ 1000	PASS
Middle	2437	3.53	10.48	14.01	25.177	≤ 1000	PASS
High	2462	3.78	10.48	14.26	26.669	≤ 1000	PASS

[IEEE802.11g]
Battery Full

Channel	Center Frequency (MHz)	Reading (dBm)	Factor (dB)	Level (dBm)	Output Power (mW)	Limit (mW)	Result
Low	2412	1.87	10.48	12.35	17.179	≤ 1000	PASS
Middle	2437	1.32	10.48	11.80	15.136	≤ 1000	PASS
High	2462	1.79	10.48	12.27	16.866	≤ 1000	PASS

[IEEE802.11n (HT20)]
Battery Full

Channel	Center Frequency (MHz)	Reading (dBm)	Factor (dB)	Level (dBm)	Output Power (mW)	Limit (mW)	Result
Low	2412	1.94	10.48	12.42	17.458	≤ 1000	PASS
Middle	2437	1.62	10.48	12.10	16.218	≤ 1000	PASS
High	2462	1.88	10.48	12.36	17.219	≤ 1000	PASS


Calculation;

$$\text{Reading (dBm)} + \text{Factor (dB)} = \text{Level (dBm)}$$


$$10\log P = \text{Level (dBm)}$$

$$P = 10^{(\text{Maximum Peak Output Power} / 10)} \text{ (mW)}$$


5.4 Trace data
[IEEE802.11b]
[Battery Full]
Channel Low




Channel Middle




Channel High




[IEEE802.11g]
[Battery Full]
Channel Low




Channel Middle




Channel High




[IEEE802.11n (HT20)]
[Battery Full]
Channel Low



Channel Middle



Channel High



6. Band Edge Compliance of RF Conducted Emissions

6.1 Measurement procedure


[FCC 15.247(d), KDB 558074 D01 v04, Section 11.0]

The Band Edge is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;

- a) Span = Arbitrary setting. (Setting suitable for measurement.)
- b) RBW = 100kHz.
- c) VBW $\geq 3 \times$ RBW
- d) Sweep time = auto-couple.
- e) Detector = peak.
- f) Trace mode = max hold.

- Test configuration



6.2 Limit

In any 100kHz bandwidth outside the frequency band the radio frequency power that is produced by the intentional radiator shall be at least 30dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

6.3 Measurement result

Date : March 21, 2017
 Temperature : 23.6 [°C]
 Humidity : 47.1 [%]
 Test place : Shielded room No.4

Test engineer : Tadahiro Seino

[IEEE802.11b]

Channel	Frequency (MHz)	RF Power Level (dBm)	Band-edge Frequency (MHz)	Band-edge Level (dBm)	Difference Level (dBm)	Limit (dBm)	Result
Low	2412	-3.63	2399.04	-50.19	46.56	At least 30dB below from peak of RF	PASS
High	2462	-3.68	2487.58	-64.46	60.78	At least 30dB below from peak of RF	PASS

[IEEE802.11g]


Channel	Frequency (MHz)	RF Power Level (dBm)	Band-edge Frequency (MHz)	Band-edge Level (dBm)	Difference Level (dBm)	Limit (dBm)	Result
Low	2412	-8.83	2399.84	-42.13	33.30	At least 30dB below from peak of RF	PASS
High	2462	-8.91	2483.50	-54.95	46.04	At least 30dB below from peak of RF	PASS

[IEEE802.11n (HT20)]


Channel	Frequency (MHz)	RF Power Level (dBm)	Band-edge Frequency (MHz)	Band-edge Level (dBm)	Difference Level (dBm)	Limit (dBm)	Result
Low	2412	-9.07	2399.76	-43.26	34.19	At least 30dB below from peak of RF	PASS
High	2462	-8.83	2483.90	-53.69	44.86	At least 30dB below from peak of RF	PASS

6.4 Trace data
[IEEE802.11b]

Channel Low




Channel High




[IEEE802.11g]

Channel Low




Channel High




[IEEE802.11n (HT20)]

Channel Low



Channel High



7. Spurious emissions - Conducted -

7.1 Measurement procedure


[FCC 15.247(d), KDB 558074 D01 v04, Section 11.0]

The spurious emissions (Conducted) are measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;

- a) Span = wide enough to fully capture the emission being measured.
- b) RBW = 100 kHz.
- c) VBW $\geq$ RBW.
- d) Sweep time = auto-couple.
- e) Detector = peak.
- f) Trace mode = max hold.

- Test configuration



7.2 Limit

In any 100kHz bandwidth outside the frequency band the radio frequency power that is produced by the intentional radiator shall be at least 30dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

7.3 Measurement result

Date : March 21, 2017
 Temperature : 23.6 [°C]
 Humidity : 47.1 [%]
 Test place : Shielded room No.4

Test engineer :
 Tadahiro Seino

[IEEE802.11b, IEEE802.11g, IEEE802.11n (HT20)]


Channel	Frequency [MHz]	Limit [dB]	Results Chart	Result
Low	2412	At least 30dB below from peak of RF	See the trace Data	PASS
Middle	2437	At least 30dB below from peak of RF	See the trace Data	PASS
High	2462	At least 30dB below from peak of RF	See the trace Data	PASS

7.4 Trace data


[IEEE802.11b]

Channel Low


30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz




15GHz-20GHz




20GHz-25GHz




Channel Middle 30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz




15GHz-20GHz




20GHz-25GHz




Channel High 30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz




15GHz-20GHz




20GHz-25GHz




[IEEE802.11g] Channel Low 30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz




15GHz-20GHz




20GHz-25GHz




Channel Middle 30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz




15GHz-20GHz




20GHz-25GHz




Channel High 30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz




15GHz-20GHz




20GHz-25GHz




[IEEE802.11n (HT20)] Channel Low 30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz




15GHz-20GHz




20GHz-25GHz




Channel Middle 30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz




15GHz-20GHz




20GHz-25GHz




Channel High 30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz



15GHz-20GHz



20GHz-25GHz



8. Spurious Emissions - Radiated -

8.1 Measurement procedure

[FCC 15.247(d), 15.205, 15.209, KDB 558074 D01 v04, Section 12.1]

Test was applied by following conditions.

Test method	: ANSI C63.10
Frequency range	: 9kHz to 25GHz
Test place	: 3m Semi-anechoic chamber
EUT was placed on	: Styrofoam table / (W)1.0m × (D)1.0m × (H)0.8m (below 1GHz) Styrofoam table / (W)0.6m × (D)0.6m × (H)1.5m (above 1GHz)
Antenna distance	: 3m
Test receiver setting	Below 1GHz
- Detector	: Average (9kHz-90kHz, 110kHz-490kHz), Quasi-peak
- Bandwidth	: 200Hz, 120kHz
Spectrum analyzer setting	Above 1GHz
- Peak	: RBW=1MHz, VBW=3MHz, Span=0Hz, Sweep=auto
- Average	: RBW=1MHz, VBW=10Hz, Span=0Hz, Sweep=auto Display mode=Linear

Average Measurement Setting [VBW]

Mode	Duty Cycle (%)	T _{on} (us)	T _{off} (us)	Determined VBW Setting
IEEE802.11b	99.03	1022	10	10Hz (Duty Cycle ≥ 98%)
IEEE802.11g	99.27	1362	10	10Hz (Duty Cycle ≥ 98%)
IEEE802.11n(HT20)	99.38	1276	8	10Hz (Duty Cycle ≥ 98%)


Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open area test site.

Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 937606.

Radiated emission measurements are performed at 3m distance with the broadband antenna (Loop antenna, Biconical antenna, Log periodic antenna and Double ridged guide antenna). The antenna is positioned both the horizontal and vertical planes of polarization and height is varied 1m to 4m and stopped at height producing the maximum emission. As for the Loop antenna, it is positioned with its plane vertical, and the center of the Loop antenna is 1m above the ground plane.

The EUT is Placed on a turntable, which is 0.8m/1.5m above ground plane. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. The test results represent the worst case emission for each emission with manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation. Sufficient time for the EUT, support equipment, and test equipment are allowed in order for them to warm up to their normal operating condition.

- Test configuration



8.2 Calculation method

[9kHz to 150kHz]

Emission level = Reading + (Ant. factor + Cable system loss)

Margin = Limit – Emission level

[150kHz to 25GHz]

Emission level = Reading + (Ant. factor + Cable system loss – Amp. Gain)

Margin = Limit – Emission level

Example:

Limit @ 4824.0MHz : 74.0dBuV/m (Peak Limit)

S.A Reading = 49.5dBuV Cable system loss = 8.4dB

Result = 49.5 + 8.4 = 45.1dBuV/m

Margin = 74.0 - 45.1 = 16.1dB

8.3 Limit

Frequency [MHz]	Field strength		Distance [m]
	[uV/m]	[dBuV/m]	
0.009-0.490	2400 / F [kHz]	20logE [uV/m]	300
0.490-1.705	24000 / F [kHz]	20logE [uV/m]	30
1.705-30	30	29.5	30
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level [dBuV/m] = 20log Emission [uV/m]
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition modulation.


8.4 Test data

Date	:	March 27, 2017		
Temperature	:	20.3 [°C]		
Humidity	:	45.6 [%]	Test engineer	:
Test place	:	3m Semi-anechoic chamber		<u>Taiki Watanabe</u>
Date	:	March 28, 2017		
Temperature	:	20.3 [°C]		
Humidity	:	45.2 [%]	Test engineer	:
Test place	:	3m Semi-anechoic chamber		<u>Taiki Watanabe</u>
Date	:	March 29, 2017		
Temperature	:	20.1 [°C]		
Humidity	:	45.3 [%]	Test engineer	:
Test place	:	3m Semi-anechoic chamber		<u>Taiki Watanabe</u>
Date	:	April 18, 2017		
Temperature	:	23.9 [°C]		
Humidity	:	49.1 [%]	Test engineer	:
Test place	:	3m Semi-anechoic chamber		<u>Taiki Watanabe</u>

11.4.1 Transmission mode

[11b]
Channel Low
BELOW 1GHz

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

[11b]
Channel Low
ABOVE 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result


No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]	Remark
1	4824.000	H	50.6	37.6	8.3	58.9	45.9	74.0	15.1	8.1	161.0	130.0	
2	4824.000	V	50.9	37.6	8.3	59.2	45.9	74.0	14.8	8.1	130.0	216.0	

Note:

- Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
- No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

[11b]
Channel Middle
BELOW 1GHz

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result

No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:


1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.



Zacta

**[11b]
Channel Middle
ABOVE 1GHz**

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]	Remark
1	4874.000	H	50.9	37.9	8.5	59.4	46.4	74.0	14.6	7.6	153.0	198.0	
2	4874.000	V	50.6	38.0	8.5	59.1	46.5	74.0	14.9	7.5	130.0	216.0	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

**[11b]
Channel High
BELOW 1GHz**

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

**[11b]
Channel High
ABOVE 1GHz**

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]	Remark
1	4924.000	H	50.8	38.0	8.7	59.5	46.7	74.0	14.5	7.3	139.0	345.0	
2	4924.000	V	50.7	38.0	8.7	59.4	46.7	74.0	14.6	7.3	139.0	291.0	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

**[11g]
Channel Low
BELOW 1GHz**

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

**[11g]
Channel Low
ABOVE 1GHz**

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]	Remark
1	4824.000	H	50.2	37.5	8.3	58.5	45.8	74.0	15.5	8.2	149.0	118.0	
2	4824.000	V	50.8	37.5	8.3	59.1	45.8	74.0	14.9	8.2	160.0	106.0	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

[11g]
Channel Middle
BELOW 1GHz

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

**[11g]
Channel Middle
ABOVE 1GHz**

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]	Remark
1	4874.000	H	50.5	37.6	8.5	59.0	46.1	74.0	15.0	7.9	152.0	253.0	
2	4874.000	V	50.4	37.5	8.5	58.9	46.0	74.0	15.1	8.0	140.0	178.0	

Note:

- Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
- No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

[11g] Channel High

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result

No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

BELOW 1GHz

Note:


1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.



Zacta

**[11g]
Channel High
ABOVE 1GHz**

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]	Remark
1	4924.000	H	50.5	38.0	8.7	59.2	46.7	74.0	14.8	7.3	138.0	256.0	
2	4924.000	V	51.1	37.6	8.7	59.8	46.3	74.0	14.2	7.7	130.0	288.0	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable - Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

[11n(HT20)]
Channel Low
BELOW 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result


No.	Frequency (P) [MHz]	c.f [dB(1/m)]	Height [cm]	Angle [°]	Remark
-----	------------------------	------------------	----------------	--------------	--------

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

[11n(HT20)]
Channel Low
ABOVE 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result


No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]	Remark
1	4824.000	H	50.3	37.5	8.3	58.6	45.8	74.0	15.4	8.2	134.0	147.0	
2	4824.000	V	50.0	37.5	8.3	58.3	45.8	74.0	15.7	8.2	135.0	346.0	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

[11n(HT20)]
Channel Middle
BELOW 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

[11n(HT20)]
Channel Middle
ABOVE 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result


No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]	Remark
1	4874.000	H	50.8	37.6	8.5	59.3	46.1	74.0	14.7	7.9	130.0	162.0	
2	4874.000	V	50.0	37.7	8.5	58.5	46.2	74.0	15.5	7.8	147.0	234.0	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

[11n(HT20)]
Channel High
BELOW 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

[11n(HT20)]
Channel High
ABOVE 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c. f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]	Remark
1	4924.000	H	50.3	37.6	8.7	59.0	46.3	74.0	15.0	7.7	143.0	210.0	
2	4924.000	V	50.0	37.6	8.7	58.7	46.3	74.0	15.3	7.7	135.0	183.0	


Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

11.4.2 Receive mode

Channel Low BELOW 1GHz

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz and 1GHz to 25GHz at the 3 meters distance.

Channel Middle BELOW 1GHz

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz and 1GHz to 25GHz at the 3 meters distance.

Channel High BELOW 1GHz

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result

No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz and 1GHz to 25GHz at the 3 meters distance.