

July 9, 2026

DTS-UNII Device Declaration Letter

To whom it may concern,

We have declared below featured for FCC equipment authorization,

Device FCC ID: **JOYEB1236**

- (1) DFS Device -- ☐ Master ☐ Client with Radar detection capability ,
☒ Client without radar detection capability ☐ N/A

- (2) Active / Passive Scanning , ad-hoc mode access point capability

Frequency Band (MHz)	Active Scanning (the device can transmit a probe (beacon))	passive scanning (where the device is can listen only with no probes)	Ad Hoc Mode or WIFI Direct capability	Access point capability
5150-5250	☐ Yes , ☒ No	☒ Yes , ☐ No	☐ Yes , ☒ No	☐ Yes , ☒ No
5250-5350	☐ Yes , ☒ No	☒ Yes , ☐ No	☐ Yes , ☒ No	☐ Yes , ☒ No
5470-5725	☐ Yes , ☒ No	☒ Yes , ☐ No	☐ Yes , ☒ No	☐ Yes , ☒ No
5725-5850	☐ Yes , ☒ No	☐ Yes , ☒ No	☐ Yes , ☒ No	☐ Yes , ☒ No

- (3) Country code selection ability - ☒ Yes , ☐ No

If yes, please explain how it was implemented: (please also help to provide detail of options for each country selection)

Mobile phones obtain the country code via the cellular network or IEEE 802.11d. If the country code is Japan or a country within the CE region, channels 12 and 13 are enabled. On the other hand, if the country code is a country within the FCC region, channels 12 and 13 are disabled. For the DFS band, there are no changes in control, and no autonomous transmissions occur in any case.

- (4) Meet 15.202 requirement - ☒ Yes, ☐ No,

Please check below:

☐ A master device is defined as a device operating in a mode in which it has the capability to transmit without receiving an enabling signal. In this mode it is able to select a channel and initiate a network by sending enabling signals to other devices

☒ A client device is defined as a device operating in a mode in which the transmissions of the device are under control of the master. A device in client mode is not able to initiate a network.

- (5) For client devices that have software configuration control to operate in different modes (active scanning in some and passive scanning in others) in different bands (devices with multiple equipment classes or those that operate on non-DFS frequencies) or modular devices which configure the modes of operations through software, the application must provide software and operations description on how the software and / or hardware is implemented to ensure that proper operations modes cannot be modified by end user or an installer.
☒ Apply, ☐ No Apply, (If apply, please help to provide explanation on it was implement, and how software was controlled)

Kyocera Corporation
2-1-1 Kagahara, Tsuzuki-ku, Yokohama-shi, Kanagawa, 224-8502, Japan

Factory set only.

A handwritten signature in cursive script, reading "Hideki Yoshida". The signature is written in black ink and is positioned above a horizontal line.

Contact Name: Hideki Yoshida

Kyocera Corporation

Tel: +81-90-6100-4946

E-mail: hideki.yoshida.gt@kyocera.jp