

EMC TEST REPORT


Applicant:	KYOCERA Corporation
Address:	Yokohama Office 2-1-1 Kagahara, Tsuzuki-ku Yokohama-shi, Kanagawa, Japan

Manufacturer or Supplier:	KYOCERA Corporation
Address:	Yokohama Office 2-1-1 Kagahara, Tsuzuki-ku Yokohama-shi, Kanagawa, Japan
Product:	Mobile Phone
Brand Name:	KYOCERA
Model Name:	EB1236
FCC ID:	JOYEB1236
Date of tests:	May. 13, 2026 - Jul. 02, 2026

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

- ☐ FCC Part 15, Subpart B, Class A
☒ FCC Part 15, Subpart B, Class B
☒ ANSI C63.4:2014

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Carl Xie Engineer / Mobile Department	Approved by Simon Wang Manager / Mobile Department
	
Date: Jul. 02, 2026	Date: Jul. 02, 2026

Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

TABLE OF CONTENTS	2
RELEASE CONTROL RECORD	3
1 GENERAL INFORMATION.....	4
1.1 GENERAL DESCRIPTION OF EUT	4
1.2 SUMMARY OF TEST RESULTS	6
1.3 MEASUREMENT UNCERTAINTY	7
1.4 DESCRIPTION OF TEST MODES	8
1.5 DESCRIPTION OF SUPPORT UNITS	9
2 EMISSION TEST.....	10
2.1 CONDUCTED EMISSION MEASUREMENT	10
2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	10
2.1.2 TEST INSTRUMENTS	10
2.1.3 TEST PROCEDURES	11
2.1.4 DEVIATION FROM TEST STANDARD	11
2.1.5 TEST SETUP	12
2.1.6 EUT OPERATING CONDITIONS	12
2.1.7 TEST RESULTS	13
2.2 RADIATED EMISSION MEASUREMENT	15
2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	15
2.2.2 TEST INSTRUMENTS	16
2.2.3 TEST PROCEDURE	17
2.2.4 DEVIATION FROM TEST STANDARD	18
2.2.5 TEST SETUP	19
2.2.6 EUT OPERATING CONDITIONS	19
2.2.7 TEST RESULTS	20
3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	24



Test Report No.: EMC260626B001

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
EMC260626B001	Original release	Jul. 02, 2026

1 GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Mobile Phone	
BRAND NAME	KYOCERA	
MODEL NAME	EB1236	
NOMINAL VOLTAGE	3.89Vdc	
MODULATION TYPE	BT_LE	GFSK
	Bluetooth	GFSK, $\pi/4$ -DQPSK, 8DPSK
	NFC	ASK
	WLAN	DSSS, OFDM, OFDMA
	GPS/GALILEO/GLONASS/BDS	BPSK
	GSM/GPRS	GMSK
	WCDMA	QPSK/16QAM
	LTE	QPSK/16QAM/64QAM
OPERATING FREQUENCY	Bluetooth/BT_LE	2402MHz ~ 2480MHz
	NFC	13.56 MHz
	WLAN	2412 ~ 2462MHz for 11b/g/n(HT20)/ax(HE20)/ax(HE20M RU26/52/106/242) 5180 ~ 5240MHz, 5260 ~ 5320 MHz, 5500 ~ 5720MHz for 11a/ n(HT20)/ n(HT40) / ac(VHT20)/ ac(VHT40) / ac(VHT80)/ ax(HE20/40/80) 5925 ~ 6425MHz for 802.11ax(HE20/40/80/160) 921-927MHz for 802.11ah 1M 923.5-926.5MHz for 802.11ah 2M 924.5-925.5MHz for 802.11ah 4M
	GSM	824.2MHz ~ 848.8MHz (FOR GSM 850) 1850.2MHz ~ 1909.8MHz (FOR GSM 1900)
	WCDMA	1852.4MHz ~ 1907.6MHz(FOR WCDMA Band 2) 1712.4MHz ~ 1752.6MHz(FOR WCDMA Band 4) 826.4MHz ~ 846.6MHz (FOR WCDMA Band 5)
	LTE	1850.7MHz ~ 1909.3MHz (FOR LTE Band2) 1710.7MHz ~ 1754.3MHz (FOR LTE Band4) 824.7MHz ~ 848.3MHz (FOR LTE Band5) 699.7MHz ~ 715.3MHz (FOR LTE Band12) 2498.5MHz ~ 2687.5MHz (FOR LTE Band41)

Test Report No.: EMC260626B001

		CA_41C
HW VERSION	DMT2	
SW VERSION	V0.252EX.0052.a	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	N/A	
ACCESSORY DEVICES	Refer to note as below	

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in the test report.
3. According to the Statement of differences provided by the applicant, the procurement of memory from multiple suppliers. EB1236 source MCP(ROM and RAM) from two different vendors each and use them interchangeably. MCP is procured from Micron and Samsung.
MCP(ROM and RAM)
Micron: MT30AZZZCD94TKXL-023 W.237
Samsung: KM9YC001XM-B627

1.2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart B			
Standard Section	Test Item	Result	Test lab*
FCC Part 15, Subpart B, Class B ANSI C63.4:2014	Conducted Test	Compliance	A
	Radiated Emission Test (30MHz ~ 1GHz)	Compliance	A
	Radiated Emission Test (Above 1GHz)	Compliance	A

*Test Lab Information Reference

Lab A:

BOOMWAVE TEST (SHENZHEN) CO., LTD.

Lab Address:

Room B38, Warehouse A5(Chiwan No.1), No.3 Chiwan 4th Road, Chiwan Community, Zhaoshang St
Nanshan District, Shenzhen, Guangdong, P.R. CHINA

Accredited Test Lab Cert 7607.01


The FCC Site Registration No. is 646781; The Designation No. is CN1429.

1.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz ~ 30MHz	±2.70dB
Radiated emissions	30MHz~1GHz	±4.98dB
	1GHz ~6GHz	±4.70dB
	6GHz ~18GHz	±4.60dB
	18GHz ~40GHz	±4.12dB



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.

1.4 DESCRIPTION OF TEST MODES

Test Mode	Test Condition
Radiated emission test	
1	GSM850 Idle+Adapter +USB cable +SD+Front Camera On
2	WCDMA BAND5+Adapter +USB cable +SD+Front Camera On
3	LTE B5 Idle+Adapter +USB cable +SD+Data Transmission+PC to EUT
4	LTE B12 Idle+Adapter +USB cable +SD+Data Transmission+PC to SD
5	Worst of 1-4 Memory 2

Test Mode	Test Condition
Conducted emission test	
1	GSM850 Idle+Adapter +USB cable +SD+Front Camera On
2	WCDMA BAND5+Adapter +USB cable +SD+Front Camera On
3	LTE B5 Idle+Adapter +USB cable +SD+Data Transmission+PC to EUT
4	LTE B12 Idle+Adapter +USB cable +SD+Data Transmission+PC to SD
5	Worst of 1-4 Memory 2
NOTE: - For radiated emission test, Pre-scan all mode, test mode 1 was the worst case and only this mode was presented in this report - For conducted emission test, Pre-scan all mode, mode 1 was the worst case and only this mode was presented in this report.	

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

FOR ALL TESTS

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	Thinkpad E14	SL10W47313	N/A
2	Adapter	Juniper	MK-P301EXC	N/A	N/A
3	Earphone	Xiaomi	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	USB Line: Shielded, Detachable 1m;

2 EMISSION TEST

2.1 CONDUCTED EMISSION MEASUREMENT

2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107 a CLASS B)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107 b CLASS A)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	79	66
0.5 ~ 30	73	60

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors

and apparatus connected thereto, shall not exceed the level of field strengths specified above.

2.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pulse limiter	SCHWARZBECK	VTSD 9561F	01579	2025/7/22	2027/7/21
ESR.EMI TEST RECEIVER	Rohde&SCHWARZ	ESR	101405	2025/6/30	2027/6/29
LISN	SCHWARZBECK	NSLK 8127	01216	2025/8/27	2027/8/26
Cable	Tonscend	/	/	2025/7/22	2027/7/21

NOTE: 1. The test was performed in CE shielded room.

2. The calibration interval of the above test instruments is 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA

2.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

2.1.4 DEVIATION FROM TEST STANDARD

No deviation.

2.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

2.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the use type described in the manufacturer's specifications or the user's manual.

2.1.7 TEST RESULTS


TEST VOLTAGE	Input 120 Vac, 60 Hz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	26deg. C, 51%RH	TESTED BY	Carl Xie

Final Data List

NO.	Frequency [MHz]	Factor [dB]	Phase	QP Reading [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.1500	10.07	L	41.89	51.96	66.00	14.04	25.55	35.62	56.00	20.38	PASS
2	0.1905	10.07	L	36.62	46.69	64.01	17.32	21.02	31.09	54.01	22.92	PASS
3	0.6045	10.08	L	21.53	31.61	56.00	24.39	12.20	22.28	46.00	23.72	PASS
4	12.6060	10.88	L	23.88	34.76	60.00	25.24	15.02	25.90	50.00	24.10	PASS
5	17.7360	11.19	L	27.03	38.22	60.00	21.78	18.48	29.67	50.00	20.33	PASS
6	25.1070	11.54	L	32.80	44.34	60.00	15.66	15.40	26.94	50.00	23.06	PASS

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Limit value- Emission level
4. Correction factor = Insertion loss + Cable loss + Attenuate
5. Emission Level = Correction Factor + Reading Value.




TEST VOLTAGE	Input 120 Vac, 60 Hz	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	26deg. C, 51%RH	TESTED BY	Carl Xie

Final Data List

NO.	Frequency [MHz]	Factor [dB]	Phase	QP Reading [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.1860	10.10	N	36.05	46.15	64.21	18.06	18.97	29.07	54.21	25.14	PASS
2	0.2625	10.10	N	28.73	38.83	61.35	22.52	12.58	22.68	51.35	28.67	PASS
3	0.6045	10.11	N	22.79	32.90	56.00	23.10	13.41	23.52	46.00	22.48	PASS
4	4.9740	10.31	N	14.97	25.28	56.00	30.72	8.63	18.94	46.00	27.06	PASS
5	14.8740	11.22	N	32.59	43.81	60.00	16.19	23.49	34.71	50.00	15.29	PASS
6	24.7560	11.58	N	32.43	44.01	60.00	15.99	14.14	25.72	50.00	24.28	PASS

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Limit value- Emission level
4. Correction factor = Insertion loss + Cable loss + Attenuate
5. Emission Level = Correction Factor + Reading Value.



2.2 RADIATED EMISSION MEASUREMENT

2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.109)

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 3 meters (dB μ V/m)		
Frequencies (MHz)	FCC 15B Class A	FCC 15B Class B
30-88	49.54	40
88-216	53.98	43.5
216-960	56.9	46
960-1000	60	54
Above 1000	Avg: 60 Peak: 80	Avg: 54 Peak: 74

Frequency Range (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
 4. QP detector shall be applied if not specified.

2.2.2 TEST INSTRUMENTS

Frequency range below 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
BiConiLog Antenna	ETS-LINDGREN	3143B	161965	2025/7/17	2027/7/16
Preamplifier	Tonscend	TPA001330	806JSAPO40804251015	2025/6/30	2027/6/29
Attenuator 6DB	SHX	TS2-6-6-A	230927166	2025/6/30	2027/6/29
Cable 1	N/A	N/A	N/A	N/A	N/A
MXE EMI Receiver	keysight	N9038B	MY50018017	2025/6/31	2027/6/30
Active Receive Loop Antenna	SCHWARZBECK	FMZB 1519 B	00173	2025/11/29	2027/11/28

Frequency range above 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Horn Antenna	SCHWARZBECK	BBHA9120D	3297	2025/9/27	2027/9/26
Horn Antenna	STEATITE	QWH-SL-18-40-K-SG QMS-00361	15433	2025/7/19	2027/7/18
Preamplifier	Tonscend	TPA184045	'AP24L8060388	2025/7/3	2027/7/2
Preamplifier	Tonscend	TPA011845	'AP24L8060392	2025/6/30	2027/6/29
MXE EMI Receiver	keysight	N9038B	MY50018017	2025/7/1	2027/6/30
Attenuator 6DB	SHX	TS2-6-6-A	230927166	2025/6/30	2027/6/29
HIGH pass FILTER_1-18	EWT	EWT-57-0222	EWT-57-0222	2025/6/30	2027/6/29
HIGH pass FILTER_7-18	EWT	EWT-57-0223	EWT-57-0223	2025/6/30	2027/6/29
HIGH pass FILTER_3-18	EWT	EWT-57-0221	EWT-57-0221	2025/6/30	2027/6/29
DC~1GHz Lowpass Filter	EWT	EWT-56-0649	EWT-56-0649	2025/7/3	2027/7/2
Cable 2	N/A	N/A	N/A	2025/9/28	2027/9/27
Cable 3	N/A	N/A	N/A	2025/9/28	2027/9/27

NOTE: 1. The calibration interval of the above test instruments is 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Chamber.

2.2.3 TEST PROCEDURE

<Frequency Range below 1GHz>

The basic test procedure was in accordance with ANSI C63.4:2014 (section 12).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
3. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
4. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier).
5. Margin value = Limit value -Emission level.

<Frequency Range above 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. The bore sight should be used during the test above 1GHz.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz

NOTE:


1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth of test receiver/spectrum analyzer is 1Hz for Average detection (AV) at frequency above 1GHz.
3. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.
4. $\text{Emission level(dBuV/m)} = \text{Raw Value(dBuV)} + \text{Correction Factor(dB/m)}$
5. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)}$ (if the raw value not contains the amplifier);
6. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)} - \text{Amplifier Gain(dB)}$ (if the raw value contains the amplifier)
7. $\text{Margin value} = \text{Limit value} - \text{Emission level}$.

2.2.4 DEVIATION FROM TEST STANDARD


No deviation.

2.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna depends on the EUT height and the antenna 3dB bandwidth both, refer to section 7.3 of CISPR 16-2-3.

2.2.6 EUT OPERATING CONDITIONS

Same as item 2.1.6.

2.2.7 TEST RESULTS


TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120 kHz
TESTED BY	Carl Xie		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Suspected Data List											
NO.	Frequency [MHz]	Reading [dBuV]	Level [dBuV/m]	Factor [dB/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Det	Pol	Verdict
1	91.1712	54.73	22.68	-32.05	43.50	20.82	100	2	PK	Hori	PASS
2	242.6426	54.98	28.86	-26.12	46.00	17.14	100	270	PK	Hori	PASS
3	377.6076	49.00	27.36	-21.64	46.00	18.64	100	74	PK	Hori	PASS
4	530.0501	41.84	25.30	-16.54	46.00	20.70	100	89	PK	Hori	PASS
5	812.6026	40.77	28.21	-12.56	46.00	17.79	100	205	PK	Hori	PASS
6	945.6256	39.35	29.30	-10.05	46.00	16.70	100	354	PK	Hori	PASS

REMARKS:

1. Emission level(dBuV/m)=Read Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) -Amplifier Gain
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission level.



TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120 kHz
TESTED BY	Carl Xie		


ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Suspected Data List

NO.	Frequency [MHz]	Reading [dBuV]	Level [dBuV/m]	Factor [dB/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Det	Pol	Verdict
1	39.7097	56.84	28.71	-28.13	40.00	11.29	100	358	PK	Vert	PASS
2	87.2873	70.03	36.46	-33.57	40.00	3.54	100	6	PK	Vert	PASS
3	212.5425	53.43	25.83	-27.60	43.50	17.67	100	358	PK	Vert	PASS
4	634.9149	41.99	27.02	-14.97	46.00	18.98	100	314	PK	Vert	PASS
5	800.9510	40.19	27.54	-12.65	46.00	18.46	100	10	PK	Vert	PASS
6	933.0030	39.68	29.88	-9.80	46.00	16.12	100	187	PK	Vert	PASS

REMARKS:

1. Emission level(dBuV/m)=Read Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) -Amplifier Gain
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission level.



TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Carl Xie		


ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Suspected Data List

NO.	Frequency [MHz]	Reading [dBuV]	Level [dBuV/m]	Factor [dB/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Det	Pol	Verdict
1	1312.0624	55.78	39.07	-16.71	74.00	34.93	100	304	PK	Hori	PASS
2	1312.0624	44.50	27.79	-16.71	54.00	26.21	100	320	AV	Hori	PASS
3	2486.2973	41.56	28.44	-13.12	54.00	25.56	100	228	AV	Hori	PASS
4	2495.8992	51.92	38.94	-12.98	74.00	35.06	100	357	PK	Hori	PASS
5	3418.8838	58.63	47.42	-11.21	74.00	26.58	100	295	PK	Hori	PASS
6	3419.4839	52.85	41.64	-11.21	54.00	12.36	100	295	AV	Hori	PASS

REMARKS:

1. Peak detector quick scan is shown on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 1GHz to 5th harmonic of the highest frequency or 40GHz, whichever is lower. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.
4. Only emissions significantly above the equipment noise floor are reported.



TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Carl Xie		


ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Suspected Data List

NO.	Frequency [MHz]	Reading [dBuV]	Level [dBuV/m]	Factor [dB/m]	Limit [dBuV/m]	Margin [dB]	Height [cm]	Angle [°]	Det	Pol	Verdict
1	1171.6343	44.68	26.97	-17.71	54.00	27.03	100	1	AV	Vert	PASS
2	1176.8354	57.23	39.57	-17.66	74.00	34.43	100	16	PK	Vert	PASS
3	1812.5625	55.25	39.80	-15.45	74.00	34.20	100	239	PK	Vert	PASS
4	1812.9626	47.56	32.11	-15.45	54.00	21.89	100	42	AV	Vert	PASS
5	3498.0996	54.13	42.86	-11.27	74.00	31.14	100	309	PK	Vert	PASS
6	3498.6997	48.42	37.15	-11.27	54.00	16.85	100	309	AV	Vert	PASS

REMARKS:

1. Peak detector quick scan is shown on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 1GHz to 5th harmonic of the highest frequency or 40GHz, whichever is lower. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.
4. Only emissions significantly above the equipment noise floor are reported.



3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---