TEST REPORT

DT&C Co., Ltd.
42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRRFCC1809-0097
2. Customer
   - Name : Kyocera Corporation
   - Address : Yokohama Office 2-1-1 Kagahara, Tsuzuki-ku Yokohama-shi, Kanagawa, Japan
3. Use of Report : FCC Original Grant
4. Product Name / Model Name : Mobile Phone / JA28
   FCC ID : JOYJA28
5. Test Method Used : IEEE 1528-2013, FCC SAR KDB Publications (Details in test report)
   Test Specification : CFR §2.1093
6. Date of Test : 2018.08.20 ~ 2018.08.24
7. Testing Environment : Refer to appended test report.
8. Test Result : Refer to attached test report.

Affirmation	Tested by Name : BumJun Park (Signature)	Reviewed by Name : HakMin Kim (Signature)

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose. This test report shall not be reproduced except in full, without the written approval of DT&C Co., Ltd.

2018 . 09 . 11 .

DT&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

Test Report Version

Test Report No.	Date	Description
DRRFCC1809-0097	Sep. 11, 2018	Initial issue

Table of Contents

1. DESCRIPTION OF DEVICE 5
1.1 General Information 5
1.2 Power Reduction for SAR 6
1.3 Nominal and Maximum Output Power Specifications 6
1.4 DUT Antenna Locations 6
1.5 Simultaneous Transmission Capabilities 6
1.6 Miscellaneous SAR Test Considerations 7
1.7 Guidance Applied 7
1.8 Device Serial Numbers 7
2. INTROCUCTION 8
3. DOSIMETRIC ASSESSMENT 9
3.1 Measurement Procedure 9
4. DEFINITION OF REFERENCE POINTS 11
4.1 Ear Reference Point 11
4.2 Handset Reference Points 11
5. TEST CONFIGURATION POSITIONS FOR HANDSETS 12
5.1 Device Holder 12
5.2 Positioning for Cheek/Touch 12
5.3 Positioning for Ear / 15 ° Tilt 12
5.4 Body-Worn Accessory Configurations 13
5.5 Wireless Router Configurations 13
6. RF EXPOSURE LIMITS 14
7. FCC MEASUREMENT PROCEDURES 15
7.1 Measured and Reported SAR 15
7.2 Procedures Used to Establish RF Signal for SAR 15
7.3 SAR Measurement Conditions for WCDMA (UMTS) 15
7.3.1 Output Power Verification 15
7.3.2 Head SAR Measurements for Handsets 15
7.3.3 Body SAR Measurements 16
7.3.4 Release 5 HSDPA Data Devices 16
7.3.5 Release 6 HSUPA Data Devices 16
7.4 SAR Testing with 802.11 Transmitters 17
7.4.1 General Device Setup 17
7.4.2 Initial Test Position Procedure 17
7.4.3 2.4 GHz SAR Test Requirements 18
7.4.4 OFDM Transmission Mode and SAR Test Channel Selection 18
7.4.5 Initial Test Configuration Procedure 18
7.4.6 Subsequent Test Configuration Procedures 18
8. RF CONDUCTED POWERS 19
8.1 GSM Nominal and Maximum Output Power Spec and Conducted Powers 19
8.2 WCDMA Nominal and Maximum Output Power Spec and Conducted Powers 20
8.3 WLAN Nominal and Maximum Output Power Spec and Conducted Powers 21
8.4 Bluetooth Conducted Powers 22
9. SYSTEM VERIFICATION 23
9.1 Tissue Verification 23
9.2 Test System Verification 24
10. SAR TEST RESULTS 25
10.1 Head SAR Results 25
10.2 Standalone Body-Worn SAR Worn SAR Results 27
10.3 Standalone Hotspot SAR Results 28
10.4 SAR Test Notes 30

11. FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS....32
11.1 Introduction....32
11.2 Simultaneous Transmission Procedures....32
11.3 Simultaneous Transmission Capabilities....32
11.4 Head SAR Simultaneous Transmission Analysis....34
11.5 Body-Worn Simultaneous Transmission Analysis....35
11.6 Hotspot SAR Simultaneous Transmission Analysis....36
11.7 Simultaneous Transmission Conclusion....36
12. SAR MEASUREMENT VARIABILITY....37
12.1 Measurement Variability....37
12.2 Measurement Uncertainty....37
13. EQUIPMENT LIST....38
14. MEASUREMENT UNCERTAINTIES....39
15. CONCLUSION....45
16. REFERENCES....46
APPENDIX A. – Probe Calibration Data....48
APPENDIX B. – Dipole Calibration Data....71
APPENDIX C. – SAR Tissue Specifications....96
APPENDIX D. – SAR SYSTEM VALIDATION....98
APPENDIX E. – Description of Test Equipment....100

1. DESCRIPTION OF DEVICE

1.1 General Information

EUT type	Mobile Phone				
FCC ID	JOYJA28				
Equipment model name	JA28				
Equipment add model name	N/A				
Equipment serial no.	Identical prototype				
Mode(s) of Operation	GSM 850, GSM 1900, WCDMA 850, 2.4 G W-LAN (802.11b/g/n-HT20), Bluetooth				
TX Frequency Range	**Band**	**Mode**	**Operating Modes**	**Bandwidth**	**Frequency**
	GSM 850	GSM/GPRS	Voice/Data	-	824.2 ~ 848.8 MHz
	GSM 1900	GSM/GPRS	Voice/Data	-	1850.2 ~ 1909.8 MHz
	WCDMA 850	WCDMA	Voice/Data	-	826.4 ~ 846.6 MHz
	2.4 GHz W-LAN	802.11b/g/n	Voice/Data	HT20	2412 ~ 2472 MHz
	Bluetooth	-	Data	-	2402 ~ 2480 MHz
RX Frequency Range	GSM 850	GSM/GPRS	Voice/Data	-	869.2 ~ 893.8 MHz
	GSM 1900	GSM/GPRS	Voice/Data	-	1930.2 ~ 1989.8 MHz
	WCDMA 850	WCDMA	Voice/Data	-	871.4 ~ 891.6 MHz
	2.4 GHz W-LAN	802.11b/g/n	Voice/Data	HT20	2412 ~ 2472 MHz
	Bluetooth	-	Data	-	2402 ~ 2480 MHz

Equipment Class	**Band**	**Reported SAR**		
		1g SAR (W/kg)		
		Head	**Body-Worn**	**Hotspot**
PCE	GSM 850	0.66	0.74	-
PCE	GPRS 850	0.70	0.71	0.84
PCE	GSM 1900	0.14	0.62	-
PCE	GPRS 1900	0.17	0.73	0.79
PCE	WCDMA 850	0.64	0.68	0.91
DTS	2.4 GHz W-LAN	0.20	0.15	0.15
DSS	Bluetooth	0.45[Note]	0.23[Note]	0.23[Note]
Simultaneous SAR per KDB 690783 D01v01r03		1.15	0.96	1.13

FCC Equipment Class	Licensed Portable Transmitter Held to Ear (PCE) Part 15 Spread Spectrum Transmitter(DSS) Digital Transmission System(DTS)
Date(s) of Tests	2018.08.20 ~ 2018.08.24
Antenna Type	Internal Antenna
Note	Bluetooth SAR was estimated.
Functions	● GSM/GPRS (GPRS Class: 12) supported. * DTM not supported. ● No simultaneous transmission between BT & 2.4GHz WLAN ● Simultaneous transmission between GSM, WCDMA voice & WLAN / GPRS, WCDMA & WLAN. ● VoIP is supported. ● W-LAN 2.4GHz is supported Hotspot.

1.2 Power Reduction for SAR

There is no power reduction used for any band/mode implemented in this device for SAR purposes.

1.3 Nominal and Maximum Output Power Specifications

The Nominal and Maximum Output Power Specifications are in section 8 of this test report.

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. A diagram showing the location of the device of the device antenna can be found in JOYJA28_Antenna Location. Since the diagonal dimension of this device is < 160 mm and the diagonal display is < 150 mm, it is not considered a “phablet”.

Mode	Device Sides for SAR Testing					
	Top	Bottom	Front	Rear	Right	Left
GSM/GPRS 850	X	O	O	O	O	O
GSM/GPRS 1900	X	O	O	O	O	O
WCDMA 850	X	O	O	O	O	O
2.4G W-LAN	O	X	O	O	X	O

Note 1: Particular DUT edges were not required to be evaluated for Hotspot SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01. The antenna document shows the distances between the transmit antennas and the edges of the device.

Note 2: O - Test / X - Not test.

1.5 Simultaneous Transmission Capabilities

The Simultaneous Transmission Capabilities are in section 11 of this test report.

1.6 Miscellaneous SAR Test Considerations

(A) WiFI/BT

Since Wireless Router operations are not allowed by the chipset firmware using 2.4GHz WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02r01.

Per FCC KDB 447498 D01v06, the 1g SAR exclusion threshold for distances < 50 mm is defined by the following equation:

$$\frac{Max\ Power\ of\ Channel\ (mW)}{Test\ Separation\ Dist\ (mm)} * \sqrt{Frequency(GHz)} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn and hotspot **Bluetooth SAR were not required; [(11/10)*√2.480] = 1.7 (< 3.0)**. Per KDB Publication 447498 D01 v06, the maximum power of the channel was rounded to the nearest mW before calculation.

(B) Licensed Transmitter(s)

GSM/GPRS DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS Data.

1.7 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01 (3G SAR Procedures)
- FCC KDB Publication 941225 D06v02r01(Hotspot Mode)
- FCC KDB Publication 248227 D01v02r02 (802.11 Wi-Fi SAR)
- FCC KDB Publication 447498 D01v06 (General RF Exposure Guidance)
- FCC KDB Publication 648474 D04v01r03 (Handset SAR)
- FCC KDB Publication 690783 D01v01r03 (SAR Listings on Grants)
- FCC KDB Publication 865664 D01v01r04 (SAR Measurement 100 MHz to 6 GHz)
- FCC KDB Publication 865664 D02v01r02 (RF Exposure Reporting)
- October 2013 TCB Workshop Notes (GPRS testing criteria)
- April 2015 TCB Workshop Notes (Simultaneous transmission summation clarified)

1.8 Device Serial Numbers

The serial numbers used for each test are indicated alongside the results in Section 10.

2. INTROCUCTION

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices.

The FCC has adopted the guidelines for evaluating the environmental effects of radio frequency radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave is used for guidance in measuring SAR due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields," NCRP Report No. 86 NCRP, 1986, Bethesda, MD 20814. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ) It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Fig. 3.1)

$$SAR = \frac{d}{dt}\left(\frac{dU}{dm}\right) = \frac{d}{dt}\left(\frac{dU}{\rho dv}\right)$$

Fig. 2.1 SAR Mathematical Equation

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

σ = conductivity of the tissue-simulating material (S/m)
ρ = mass density of the tissue-simulating material (kg/m^3)
E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relations to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.

3. DOSIMETRIC ASSESSMENT

3.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 3.1) and IEEE1528-2013.

2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.



Figure 3.1
Sample SAR Area Scan

3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 3.1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):

   a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 3.1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).

   b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.

   c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 mm ± 1 mm	½·δ·ln(2) mm ± 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: Δx_{Area}, Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom}, Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	≤ 1.5·$\Delta z_{Zoom}(n-1)$ mm	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB Publication 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

Table 3.1 Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

4. DEFINITION OF REFERENCE POINTS

4.1 Ear Reference Point

Figure 5.1 shows the front, back and side views of the SAM Twin Phantom. The point"M" is the reference point for the center of the mouth, "LE" is the left ear reference point(ERP), and "RE" is the right ERP. The ERPs are 15mm posterior to the entrance to the Ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 4.1. The plane Passing, through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck- Front) is perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 4.1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning.



Figure 4.1 Close-up side view of ERP

4.2 Handset Reference Points

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the "test device reference point" located along the "vertical centerline" on the front of the device aligned to the "ear reference point" (See Fig. 4.3). The "test device reference point" was than located at the same level as the center of the ear reference point. The test device was positioned so that the "vertical centerline" was bisecting the front surface of the handset at it's top and bottom edges, positioning the "ear reference point" on the outer surface of the both the left and right head phantoms on the ear reference point.

Figure 4.2 Front, back and side view SAM Twin Phantom



Figure 4.3 Handset Vertical Center & Horizontal Line Reference Points

5. TEST CONFIGURATION POSITIONS FOR HANDSETS

5.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity ε = 3 and loss tangent δ = 0.02.

5.2 Positioning for Cheek/Touch

1. The test device was positioned with the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 5.1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.

Figure 5.1 Front, Side and Top View of Cheek/Touch Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the ear.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the plane normal to MB-NF including the line MB (reference plane).
4. The phone was hen rotated around the vertical centerline until the phone (horizontal line) was symmetrical was respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the phone contact with the ear, the handset was rotated about the line NF until any point on the handset made contact with a phantom point below the ear (cheek). (See Figure 5.2)

5.3 Positioning for Ear / 15 ° Tilt

With the test device aligned in the “Cheek/Touch Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degree.
2. The phone was then rotated around the horizontal line by 15 degree.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the phone touches the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. The tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 5.3).



Figure 5.2 Side view w/relevant markings

Figure 5.3 Front, Side and Top View of Ear/15° Position

5.4 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 5.4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.



Figure 5.4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented.
Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

5.5 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets (L x W ≥ 9 cm x 5 cm) are based on a composite test separation distance of 10 mm from the front the front, rear and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative test separation distance configuration may be used to support both SAR conditions.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitter often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was not activated during SAR assessment, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

6. RF EXPOSURE LIMITS

Uncontrolled Environment:

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Controlled Environment:

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 6.1.SAR Human Exposure Specified in ANSI/IEEE C95.1-1992

	HUMAN EXPOSURE LIMITS	
	General Public Exposure (W/kg) or (mW/g)	Occupational Exposure (W/kg) or (mW/g)
SPATIAL PEAK SAR * (Brain)	1.60	8.00
SPATIAL AVERAGE SAR ** (Whole Body)	0.08	0.40
SPATIAL PEAK SAR *** (Hands / Feet / Ankle / Wrist)	4.00	20.0

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e.as a result of employment or occupation).

7. FCC MEASUREMENT PROCEDURES

Power measurements were performed using a base station simulator under digital average power.

7.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, When SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as reported SAR. The highest reported SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

7.2 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01.

The device was placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test were evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device was tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviated by more than 5%, the SAR test and drift measurements were repeated.

7.3 SAR Measurement Conditions for WCDMA (UMTS)

7.3.1 Output Power Verification

Maximum output power is measured on the High, Middle and Low channels for each applicable transmission band according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all “1s”.

Maximum output power is verified on the High, Middle and Low channels according to the general, descriptions in section 5.2 of 3GPP TS 34.121 (release 5), using the appropriate RMC with TPC,(transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

7.3.2 Head SAR Measurements for Handsets

SAR for head exposure configurations is measured using the 12.2 kbps RMC with TPC bits configured to all “1s”. SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than 0.25 dB higher than that measured in12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2 AMR with a 3.4 kbps SRB (signaling radio bearer) using the exposure configuration that resulted in the highest SAR for that RF channel in the 12.2 kbps RMC mode.

7.3.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all“1s”.

7.3.4 Release 5 HSDPA Data Devices

The following procedures are applicable to HSDPA data devices operating under 3GPP Release 5. SAR is required for devices in body-worn accessory and other body exposure conditions, including handsets and data modems operating in various electronic devices. HSDPA operates in conjunction with WCDMA and requires an active DPCCH. The default test configuration is to measure SAR in WCDMA with HSDPA remain inactive, to establish a radio link between the test device and a communication test set using a 12.2 kbps RMC configured in Test Loop Mode 1. SAR for HSDPA is selectively measured using the highest reported SAR configuration in WCDMA, with an FRC in H-set 1 and a 12.2 kbps RMC. SAR is selectively confirmed for other physical channel configurations (DPCCH & DPDCHn) according to exposure conditions, device operating capabilities and maximum output power specified for production units, including tune-up tolerance by applying the 3G SAR test reduction procedures. Maximum output power is verified according to the applicable versions of 3GPP TS 34.121. SAR must be measured based on these maximum output conditions and requirements in KDB Publication 447498, with respect to the UE Categories, and explained in the SAR report. When Maximum Power Reduction (MPR) applies, the implementations must be clearly identified in the SAR report to support test results according to Cubic Metric (CM) and, as appropriate, Enhanced MPR (E-MPR) requirements.

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (1)	CM (dB)(2)
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15(3)	15/15(3)	64	12/15(3)	24/15	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

Note 1: Δ_{ACK}, Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$
Note 2: CM = 1 for β_c/β_d =12/15, β_{hs}/β_c=24/15.
Note 3: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to β_c = 11/15 and β_d = 15/15.

Figure 7.1 Table 1

7.3.5 Release 6 HSUPA Data Devices

The following procedures are applicable to HSPA (HSUPA/HSDPA) data devices operating under 3GPP Release 6. SAR is required for devices in body-worn accessory and other body exposure conditions, including handsets and data modems operating in various electronic devices. HSUPA operates in conjunction with WCDMA and HSDPA. SAR is initially measured in WCDMA test configurations with HSPA remain inactive. The default test configuration is to establish a radio link between the test device and a communication test set to configure a 12.2 kbps RMC in Test Loop Mode 1. SAR for HSPA is selectively measured with HS-DPCCH, E-DPCCH and E-DPDCH, all enabled, along with a 12.2 kbps RMC using the highest reported SAR configuration in WCDMA with 12.2 kbps RMC only.
An FRC is configured according to HS-DPCCH Sub-test 1 using H-set 1 and QPSK. HSPA is configured according to E-DCH Sub-test 5 requirements. SAR for other HSPA sub-test configurations is confirmed selectively according to exposure conditions, E-DCH UE Category and maximum output power of production units, including tune-up tolerance by applying the 3G SAR test reduction procedure. Maximum output power is verified according to procedures in applicable versions of 3GPP TS 34.121. SAR must be measured based on these maximum output conditions and requirements in KDB Publication 447498, with respect to the UE Categories for HS-DPCCH and HSPA, and explained in the SAR report. When Maximum Power Reduction (MPR) applies, the implementations must be clearly identified in the SAR report to support test results according to Cubic Metric (CM) and, as appropriate, Enhanced MPR (E-MPR) requirements.

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (1)	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM(2) (dB)	MPR (dB)	AG(4) Index	E-TFCI
1	11/15(3)	15/15(3)	64	11/15(3)	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1}: 47/15 β_{ed2}: 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15(4)	15/15(4)	64	15/15(4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK}, Δ_{NACK} and Δ_{CQI} = 8 ⇔ $A_{hs} = \beta_{hs}/\beta_c$ = 30/15 ⇔ β_{hs}= 30/15 *β_c.
Note 2: CM = 1 for β_c/β_d =12/15, β_{hs}/β_c=24/15. For all other combinations of DPDCH, DPCCH, HS- DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.
Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to β_c = 10/15 and β_d = 15/15.
Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to β_c = 14/15 and β_d = 15/15.
Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.
Note 6: β_{ed} cannot be set directly; it is set by Absolute Grant Value.

Figure 7.2 Table 2

7.4 SAR Testing with 802.11 Transmitters

The normal network operating configurations are not suitable for measuring the SAR of 802.11 b/g/n transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227D01v02r02 for more details.

7.4.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the in the transmission, a maximum transmission duty factor of 92-96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

7.4.2 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all position in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR position until the reported SAR result is ≤ 0.8 W/kg or all test position are measured.

7.4.3 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
2) When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

7.4.4 OFDM Transmission Mode and SAR Test Channel Selection

For the 2.4 GHz bands, when the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11g then 802.11n is used for SAR measurement. When the maximum output power ware the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

7.4.5 Initial Test Configuration Procedure

For OFDM, in 2.4 GHz bands, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, and lowest data rate. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required.
Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured.

7.4.6 Subsequent Test Configuration Procedures

For OFDM configurations, in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure, when applicable. When the highest reported SAR for the initial test configuration, adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power is ≤ 1.2 W/kg, no additional SAR testing for the subsequent test configurations is required.

8. RF CONDUCTED POWERS

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06

8.1 GSM Nominal and Maximum Output Power Spec and Conducted Powers

Band & Mode		Voice[dBm]	Burst Average GMSK [dBm]			
		1 TX Slot	1 TX Slot	2 TX Slot	3 TX Slot	4 TX Slot
GSM/GPRS 850	Maximum	34.0	34.0	31.0	29.2	28.0
	Nominal	32.5	32.5	29.5	27.7	26.5
GSM/GPRS 1900	Maximum	31.0	31.0	28.5	26.7	25.5
	Nominal	29.5	29.5	27.0	25.2	24.0

Table 8.1.1 GSM Nominal and Maximum Output Power Spec

Band	Channel	Maximum Burst-Averaged Output Power (dBm)				
		Voice	GPRS Data (GMSK)			
		GSM CS 1 Slot	GPRS 1 TX Slot	GPRS 2 TX Slot	GPRS 3 TX Slot	GPRS 4 TX Slot
GSM850	128	33.01	33.01	30.27	28.78	27.65
	190	33.25	33.26	30.47	28.81	27.67
	251	32.90	32.91	30.33	28.73	27.56
PCS 1900	512	29.78	29.79	27.47	25.49	24.54
	661	29.76	29.78	27.34	25.41	24.53
	810	29.85	29.86	27.37	25.30	24.61
Band	**Channel**	**Calculated Maximum Frame-Averaged Output Power (dBm)**				
		Voice	**GPRS Data (GMSK)**			
		GSM CS 1 Slot	**GPRS 1 TX Slot**	**GPRS 2 TX Slot**	**GPRS 3 TX Slot**	**GPRS 4 TX Slot**
GSM850	128	23.98	23.98	24.25	24.52	24.64
	190	24.22	24.23	24.45	24.55	24.66
	251	23.87	23.88	24.31	24.47	24.55
PCS 1900	512	20.75	20.76	21.45	21.23	21.53
	661	20.73	20.75	21.32	21.15	21.52
	810	20.82	20.83	21.35	21.04	21.60
GSM850	**Frame Avg. Targets:**	23.67	23.67	25.18	24.94	24.19
PCS 1900		20.67	20.67	22.18	21.94	21.69

Table 8.1.2 GSM Conducted Power

Note:

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 time slots.
2. GPRS (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.

GPRS Multislot class: 12 (max 4 TX Uplink slots)
EDGE Multislot class: N/A
DTM Multislot Class: N/A

Figure 8.1 Power Measurement Setup

8.2 WCDMA Nominal and Maximum Output Power Spec and Conducted Powers

3GPP Release Version	Mode			Cellular Band (dBm)	3GPP MPR (dB)
99	WCDMA	Voice	Maximum	24.5	-
			Nominal	23.0	
5	HSDPA	Subtest 1	Maximum	23.5	0
			Nominal	22.0	
5		Subtest 2	Maximum	23.5	0
			Nominal	22.0	
5		Subtest 3	Maximum	23.0	0.5
			Nominal	21.5	
5		Subtest 4	Maximum	23.0	0.5
			Nominal	21.5	
6	HSUPA	Subtest 1	Maximum	23.5	0
			Nominal	22.0	
6		Subtest 2	Maximum	22.0	2
			Nominal	20.5	
6		Subtest 3	Maximum	22.5	1
			Nominal	21.0	
6		Subtest 4	Maximum	23.0	2
			Nominal	21.5	
6		Subtest 5	Maximum	23.5	0
			Nominal	22.0	

Table 8.2.1 WCDMA Nominal and Maximum Output Power Spec

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band (dBm)			3GPP MPR (dB)
			4132	4183	4233	
99	WCDMA	12.2 kbps RMC	24.13	23.98	24.08	-
99		12.2 kbps AMR	24.10	23.98	23.98	-
5	HSDPA	Subtest 1	23.05	22.97	22.97	0
5		Subtest 2	23.08	22.95	23.04	0
5		Subtest 3	22.59	22.52	22.54	0.5
5		Subtest 4	22.60	22.52	22.53	0.5
6	HSUPA	Subtest 1	23.08	22.67	23.01	0
6		Subtest 2	21.47	21.42	21.42	2
6		Subtest 3	21.52	21.63	21.98	1
6		Subtest 4	22.47	22.22	22.07	2
6		Subtest 5	23.00	22.94	22.92	0

Table 8.2.2 WCDMA Conducted Power

WCDMA SAR was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.

The manufacturer declares that the HSDPA and HSUPA transmitter's power will not exceed the R99 maximum transmit power in devices based on Qualcomm's HSPA chipset solutions.

Figure 8.2 Power Measurement Setup

8.3 WLAN Nominal and Maximum Output Power Spec and Conducted Powers

Band (GHz)	Mode	Ch	Modulated Average[dBm]	
			Maximum	Nominal
2.4	802.11b	1~11	16.0	14.0
	802.11g	1~11	12.0	10.0
	802.11n	1~11	12.0	10.0

Table 8.3.1 Nominal and Maximum Output Power Spec

Mode	Freq. (MHz)	Channel	IEEE 802.11 (2.4 GHz) Conducted Power[dBm]
802.11b	**2412**	**1**	14.11
	2437	**6**	15.28
	2462	11	14.09
802.11g	2412	1	10.13
	2437	6	11.62
	2462	11	10.19
802.11n (HT-20)	2412	1	10.10
	2437	6	11.59
	2462	11	10.25

Table 8.3.2 IEEE 802.11 Average RF Power

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, duo to an even number of channels, both channels were measured.
- Output Power and SAR is not required for 802.11 g/n HT20 channels when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjust SAR is ≤ 1.2 W/kg.
- The underlined data rate and channel above were tested for SAR.

The average output powers of this device were tested by below configuration.



Figure 8.3 Power Measurement Setup

8.4 Bluetooth Conducted Powers

Modulated Average[dBm]		
Bluetooth 1 Mbps	Maximum	10.3
	Nominal	6.6
Bluetooth 2 Mbps	Maximum	8.7
	Nominal	5.0
Bluetooth 3 Mbps	Maximum	8.7
	Nominal	5.0
Bluetooth LE	Maximum	1.8
	Nominal	-1.9

Table 8.4.1 Nominal and Maximum Output Power Spec

Channel	Frequency	Frame AVG Output Power (1Mbps)	Frame AVG Output Power (2Mbps)	Frame AVG Output Power (3Mbps)
	(MHz)	(dBm)	(dBm)	(dBm)
Low	2402	8.73	7.43	7.44
Mid	2441	8.71	7.42	7.43
High	2480	7.74	6.41	6.42

Table 8.4.2 Bluetooth Frame Average RF Power

Channel	Frequency	Frame AVG Output Power(LE)
	(MHz)	(dBm)
Low	2402	-1.16
Mid	2440	-1.65
High	2480	-2.20

Table 8.4.3 Bluetooth LE Frame Average RF Power

- **Bluetooth Conducted Powers procedures**

1. Bluetooth (BDR, EDR)
   1) Enter DUT mode in EUT and operate it.
      When it operating, The EUT is transmitting at maximum power level and duty cycle fixed.
   2) Instruments and EUT were connected like Figure 8.4.1(A).
   3) The maximum output powers of BDR(1 Mbps), EDR(2, 3 Mbps) and each frequency were set by a Bluetooth Tester.
   4) Power levels were measured by a Power Meter.

2. Bluetooth (LE)
   1) Enter LE mode in EUT and operate it.
      When it operating, The EUT is transmitting at maximum power level and duty cycle fixed.
   2) Instruments and EUT were connected like Figure 8.4.1(B).
   3) The average conducted output powers of LE and each frequency can measurement according to setting program in EUT.
   4) Power levels were measured by a Power Meter.



Figure 8.4.1 Average Power Measurement Setup

The average conducted output powers of Bluetooth were measured using above test setup and a wideband gated RF power meter when the EUT is transmitting at its maximum power level.

9. SYSTEM VERIFICATION

9.1 Tissue Verification

MEASURED TISSUE PARAMETERS										
Date(s)	Tissue Type	Ambient Temp.[°C]	Liquid Temp.[°C]	Measured Frequency [MHz]	Target Dielectric Constant, εr	Target Conductivity, σ (S/m)	Measured Dielectric Constant, εr	Measured Conductivity, σ (S/m)	Er Deviation [%]	σ Deviation [%]
Aug. 20. 2018	835 Head	21.5	21.6	824.2	41.552	0.899	41.879	0.905	0.79	0.67
				826.4	41.542	0.899	41.852	0.907	0.75	0.89
				835.0	41.500	0.900	41.725	0.914	0.54	1.56
				836.6	41.500	0.901	41.703	0.915	0.49	1.55
				846.6	41.500	0.912	41.548	0.923	0.12	1.21
				848.8	41.500	0.914	41.517	0.924	0.04	1.09
Aug. 21. 2018	835 Body	21.7	21.9	824.2	55.243	0.969	54.068	0.980	-2.13	1.14
				826.4	55.235	0.969	54.053	0.982	-2.14	1.34
				835.0	55.200	0.970	53.981	0.989	-2.21	1.96
				836.6	55.197	0.971	53.969	0.991	-2.22	2.06
				846.6	55.166	0.984	53.881	1.000	-2.33	1.63
				848.8	55.160	0.986	53.862	1.002	-2.35	1.62
Aug. 22. 2018	1900 Head	21.4	21.7	1850.2	40.000	1.400	40.252	1.382	0.63	-1.29
				1880.0	40.000	1.400	40.130	1.411	0.33	0.79
				1900.0	40.000	1.400	40.040	1.430	0.10	2.14
				1909.8	40.000	1.400	40.000	1.440	0.00	2.86
Aug. 23. 2018	1900 Body	21.5	21.9	1850.2	53.300	1.520	51.942	1.483	-2.55	-2.43
				1880.0	53.300	1.520	51.886	1.510	-2.65	-0.66
				1900.0	53.300	1.520	51.830	1.528	-2.76	0.53
				1909.8	53.300	1.520	51.805	1.537	-2.80	1.12
Aug. 24. 2018	2450 Head	21.3	21.7	2402.0	39.282	1.757	39.479	1.779	0.50	1.25
				2412.0	39.265	1.766	39.439	1.789	0.44	1.30
				2437.0	39.222	1.788	39.358	1.819	0.35	1.73
				2441.0	39.215	1.792	39.343	1.824	0.33	1.79
				2450.0	39.200	1.800	39.313	1.835	0.29	1.94
				2462.0	39.184	1.813	39.283	1.850	0.25	2.04
				2472.0	39.171	1.823	39.251	1.862	0.20	2.14
				2480.0	39.160	1.832	39.226	1.871	0.17	2.13
Aug. 24. 2018	2450 Body	21.3	21.8	2402.0	52.764	1.904	51.809	1.851	-1.81	-2.78
				2412.0	52.751	1.914	51.779	1.861	-1.84	-2.77
				2437.0	52.717	1.938	51.719	1.890	-1.89	-2.48
				2441.0	52.712	1.941	51.708	1.895	-1.90	-2.37
				2450.0	52.700	1.950	51.686	1.906	-1.92	-2.26
				2462.0	52.685	1.967	51.665	1.921	-1.94	-2.34
				2472.0	52.672	1.981	51.643	1.934	-1.95	-2.37
				2480.0	52.662	1.993	51.621	1.944	-1.98	-2.46

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB 865664 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

Measurement Procedure for Tissue verification:

1) The network analyzer and probe system was configured and calibrated.
2) The probe was immersed in the sample which was placed in a nonmetallic container. Trapped air bubbles beneath the flange were minimized by placing the probe at a slight angle.
3) The complex admittance with respect to the probe aperture was measured
4) The complex relative permittivity , for example from the below equation (Pournaropoulos and Misra):

$$Y = \frac{j2\omega\varepsilon_r\varepsilon_0}{[\ln(b/a)]^2}\int_a^b\int_a^b\int_0^\pi \cos\phi' \frac{\exp\left[-j\omega r(\mu_0\varepsilon_r'\varepsilon_0)^{1/2}\right]}{r} d\phi' d\rho' d\rho$$

where Y is the admittance of the probe in contact with the sample, the primed and unprimed coordinates refer to source and observation points, respectively, $r^2 = \rho^2 + \rho'^2 - 2\rho\rho'\cos\phi'$, ω is the angular frequency, and $j = \sqrt{-1}$.

9.2 Test System Verification

Prior to assessment, the system is verified to the ± 10 % of the specifications at using the SAR Dipole kit(s). (Graphic Plots Attached)

Table 9.2.1 System Verification Results (1g)

SYSTEM DIPOLE VERIFICATION TARGET & MEASURED												
SAR System #	Freq. [MHz]	SAR Dipole kits	Date(s)	Tissue Type	Ambient Temp. [°C]	Liquid Temp. [°C]	Probe S/N	Input Power (mW)	1 W Target SAR_{1g} (W/kg)	Measured SAR_{1g} (W/kg)	1 W Normalized SAR_{1g} (W/kg)	Deviation [%]
B	835	D835V2, SN:464	Aug. 20. 2018	Head	21.5	21.6	7337	250	9.38	2.31	9.24	-1.49
B	835	D835V2, SN:464	Aug. 21. 2018	Body	21.7	21.9	7337	250	9.45	2.45	9.80	3.70
B	1900	D1900V2, SN:5d029	Aug. 22. 2018	Head	21.4	21.7	7337	100	39.2	4.07	40.70	3.83
B	1900	D1900V2, SN:5d029	Aug. 23. 2018	Body	21.5	21.9	7337	100	39.6	4.04	40.40	2.02
B	2450	D2450V2, SN: 726	Aug. 24. 2018	Head	21.3	21.7	7337	100	51.9	5.13	51.30	-1.16
B	2450	D2450V2, SN: 726	Aug. 24. 2018	Body	21.3	21.8	7337	100	50.3	4.91	49.10	-2.39

Note1 : System Verification was measured with input 250 mW, 100 mW and normalized to 1W.
Note2 : Full system validation status and results can be found in Attachment 3.



Figure 9.1 Dipole Verification Test Setup Diagram & Photo

10. SAR TEST RESULTS

10.1 Head SAR Results

Table 10.1.1 GSM/GPRS 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/ Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	# of Time Slots	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
MHz	Ch													
836.6	190	GSM850	GSM	34.00	33.25	-0.130	Left Touch	FCC #1	1	1:8.3	0.476	1.189	0.566	
836.6	190	GSM850	GSM	34.00	33.25	0.140	Right Touch	FCC #1	1	1:8.3	0.553	1.189	**0.658**	A1
836.6	190	GSM850	GSM	34.00	33.25	0.050	Left Tilt	FCC #1	1	1:8.3	0.208	1.189	0.247	
836.6	190	GSM850	GSM	34.00	33.25	-0.020	Right Tilt	FCC #1	1	1:8.3	0.267	1.189	0.317	
836.6	190	GSM850	GPRS	28.00	27.67	0.070	Left Touch	FCC #1	4	1:2.075	0.615	1.079	0.664	
836.6	190	GSM850	GPRS	28.00	27.67	-0.070	Right Touch	FCC #1	4	1:2.075	0.651	1.079	**0.702**	A2
836.6	190	GSM850	GPRS	28.00	27.67	-0.150	Left Tilt	FCC #1	4	1:2.075	0.212	1.079	0.229	
836.6	190	GSM850	GPRS	28.00	27.67	0.010	Right Tilt	FCC #1	4	1:2.075	0.331	1.079	0.357	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								**Head 1.6 W/kg (mW/g)** averaged over 1 gram						

Table 10.1.2 PCS/GPRS 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/ Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	# of Time Slots	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
MHz	Ch													
1880.0	661	PCS1900	PCS	31.00	29.76	-0.060	Left Touch	FCC #1	1	1:8.3	0.088	1.330	0.117	
1880.0	661	PCS1900	PCS	31.00	29.76	-0.040	Right Touch	FCC #1	1	1:8.3	0.108	1.330	**0.144**	A3
1880.0	661	PCS1900	PCS	31.00	29.76	0.100	Left Tilt	FCC #1	1	1:8.3	0.047	1.330	0.063	
1880.0	661	PCS1900	PCS	31.00	29.76	0.040	Right Tilt	FCC #1	1	1:8.3	0.089	1.330	0.118	
1880.0	661	PCS1900	GPRS	25.50	24.53	-0.050	Left Touch	FCC #1	4	1:2.075	0.108	1.250	0.135	
1880.0	661	PCS1900	GPRS	25.50	24.53	0.080	Right Touch	FCC #1	4	1:2.075	0.132	1.250	**0.165**	A4
1880.0	661	PCS1900	GPRS	25.50	24.53	0.090	Left Tilt	FCC #1	4	1:2.075	0.071	1.250	0.089	
1880.0	661	PCS1900	GPRS	25.50	24.53	0.190	Right Tilt	FCC #1	4	1:2.075	0.080	1.250	0.100	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								**Head 1.6 W/kg (mW/g)** averaged over 1 gram						

Table 10.1.3 WCDMA 850 Head SAR

MEASUREMENT RESULTS													
FREQUENCY		Mode/ Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
MHz	Ch												
836.6	4183	WCDMA 850	RMC	24.50	23.98	-0.170	Left Touch	FCC #1	1:1	0.567	1.127	0.639	
836.6	4183	WCDMA 850	RMC	24.50	23.98	0.020	Right Touch	FCC #1	1:1	0.571	1.127	**0.644**	A5
836.6	4183	WCDMA 850	RMC	24.50	23.98	0.030	Left Tilt	FCC #1	1:1	0.303	1.127	0.341	
836.6	4183	WCDMA 850	RMC	24.50	23.98	0.020	Right Tilt	FCC #1	1:1	0.300	1.127	0.338	
ANSI / IEEE C95.1-2005– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								**Head 1.6 W/kg (mW/g)** averaged over 1 gram					

Table 10.1.4 DTS Head SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode (Antenna)	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	1g Scaled SAR (W/kg)	Plots #
MHz	Ch														
2437.0	6	802.11b	16.00	15.28	0.100	Left Touch	FCC #1	0.170	1	99.2	0.170	1.180	1.008	**0.202**	A6
2437.0	6	802.11b	16.00	15.28	0.120	Right Touch	FCC #1	0.142	1	99.2	0.141	1.180	1.008	0.168	
2437.0	6	802.11b	16.00	15.28	0.120	Left Tilt	FCC #1	0.160	1	99.2	0.159	1.180	1.008	0.189	
2437.0	6	802.11b	0.00	15.28	0.140	Right Tilt	FCC #1	0.147	1	99.2	0.147	0.030	1.008	0.004	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								**Head 1.6 W/kg (mW/g)** averaged over 1 gram							

Adjusted SAR results for OFDM SAR												
FREQUENCY		Mode/ Antenna	Service	Maximum Allowed Power [dBm]	1g Scaled SAR (W/kg)	FREQUENCY [MHz]	Mode	Service	Maximum Allowed Power [dBm	Ratio of OFDM to DSSS	1g Adjusted SAR (W/kg)	Determine OFDM SAR
MHz	Ch											
2437.0	6	802.11b	DSSS	16.0	0.202	2437	802.11g	OFDM	12.0	0.398	0.080	X
2437.0	6	802.11b	DSSS	16.0	0.202	2437	802.11n	OFDM	12.0	0.398	0.080	X
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure						**Head 1.6 W/kg (mW/g)** averaged over 1 gram						

Note: SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

10.2 Standalone Body-Worn SAR Worn SAR Results

Table 10.2.1 GSM/PCS/GPRS/WCDMA Body-Worn SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/ Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Spacing [Side]	Device Serial Number	# of Time Slots	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
MHz	Ch													
836.6	190	GSM850	GSM	34.00	33.25	0.040	10 mm [Front]	FCC #1	1	1:8.3	0.621	1.189	**0.738**	A7
836.6	190	GSM850	GSM	34.00	33.25	-0.020	10 mm [Rear]	FCC #1	1	1:8.3	0.510	1.189	0.606	
836.6	190	GSM850	GPRS	28.00	27.67	-0.040	10 mm [Front]	FCC #1	4	1:2.075	0.596	1.079	0.643	
836.6	190	GSM850	GPRS	28.00	27.67	-0.010	10 mm [Rear]	FCC #1	4	1:2.075	0.660	1.079	**0.712**	A8
1880.0	661	PCS1900	PCS	31.00	29.76	-0.010	10 mm [Front]	FCC #1	1	1:8.3	0.463	1.330	**0.616**	A9
1880.0	661	PCS1900	PCS	31.00	29.76	-0.130	10 mm [Rear]	FCC #1	1	1:8.3	0.316	1.330	0.420	
1880.0	661	PCS1900	GPRS	25.50	24.53	0.010	10 mm [Front]	FCC #1	4	1:2.075	0.457	1.250	0.571	
1880.0	661	PCS1900	GPRS	25.50	24.53	-0.040	10 mm [Rear]	FCC #1	4	1:2.075	0.580	1.250	**0.725**	A10
836.6	4183	WCDMA 850	RMC	24.50	23.98	-0.030	10 mm [Front]	FCC #1	N/A	1:1	0.600	1.127	**0.676**	A11
836.6	4183	WCDMA 850	RMC	24.50	23.98	-0.130	10 mm [Rear]	FCC #1	N/A	1:1	0.582	1.127	0.656	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								**Body 1.6 W/kg (mW/g)** averaged over 1 gram						

Table 10.2.2 DTS Body-Worn SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	SAR (W/kg)	Plots #
MHz	Ch														
2437.0	6	802.11b	16.00	15.28	0.060	10 mm [Front]	FCC #1	0.061	1	99.2	0.059	1.180	1.008	0.070	
2437.0	6	802.11b	16.00	15.28	-0.050	10 mm [Rear]	FCC #1	0.133	1	99.2	0.125	1.180	1.008	**0.149**	A12
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								**Body 1.6 W/kg (mW/g)** averaged over 1 gram							

Adjusted SAR results for OFDM SAR												
FREQUENCY		Mode/ Antenna	Service	Maximum Allowed Power [dBm]	1g Scaled SAR (W/kg)	FREQUENCY [MHz]	Mode	Service	Maximum Allowed Power [dBm	Ratio of OFDM to DSSS	1g Adjusted SAR (W/kg)	Determine OFDM SAR
MHz	Ch											
2437.0	6	802.11b	DSSS	16.0	0.149	2437	802.11g	OFDM	12.0	0.398	0.059	X
2437.0	6	802.11b	DSSS	16.0	0.149	2437	802.11n	OFDM	12.0	0.398	0.059	X
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure						**Body 1.6 W/kg (mW/g)** averaged over 1 gram						

Note: SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

10.3 Standalone Hotspot SAR Results

Table 10.3.1 GPRS/WCDMA Hotspot SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/ Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Spacing [Side]	Device Serial Number	# of Time Slots	Duty Cycle	1g SAR (W/kg)	Scaling Factor	1g Scaled SAR (W/kg)	Plots #
MHz	Ch													
836.6	190	GSM850	GPRS	28.00	27.67	0.100	10 mm [Bottom]	FCC #1	4	1:2.075	0.031	1.079	0.033	
836.6	190	GSM850	GPRS	28.00	27.67	-0.040	10 mm [Front]	FCC #1	4	1:2.075	0.596	1.079	0.643	
836.6	190	GSM850	GPRS	28.00	27.67	-0.010	10 mm [Rear]	FCC #1	4	1:2.075	0.660	1.079	0.712	
836.6	190	GSM850	GPRS	28.00	27.67	0.010	10 mm [Right]	FCC #1	4	1:2.075	0.411	1.079	0.443	
824.2	128	GSM850	GPRS	28.00	27.65	-0.080	10 mm [Left]	FCC #1	4	1:2.075	0.778	1.084	**0.843**	A13
836.6	190	GSM850	GPRS	28.00	27.67	0.020	10 mm [Left]	FCC #1	4	1:2.075	0.769	1.079	0.830	
848.8	251	GSM850	GPRS	28.00	27.56	-0.010	10 mm [Left]	FCC #1	4	1:2.075	0.593	1.107	0.656	
1880.0	661	PCS1900	GPRS	25.50	24.53	-0.080	10 mm [Bottom]	FCC #1	4	1:2.075	0.315	1.250	0.394	
1880.0	661	PCS1900	GPRS	25.50	24.53	0.010	10 mm [Front]	FCC #1	4	1:2.075	0.457	1.250	0.571	
1880.0	661	PCS1900	GPRS	25.50	24.53	-0.040	10 mm [Rear]	FCC #1	4	1:2.075	0.580	1.250	0.725	
1880.0	661	PCS1900	GPRS	25.50	24.53	0.070	10 mm [Right]	FCC #1	4	1:2.075	0.284	1.250	0.355	
1880.0	661	PCS1900	GPRS	25.50	24.53	-0.040	10 mm [Left]	FCC #1	4	1:2.075	0.629	1.250	**0.786**	A14
836.6	4183	WCDMA 850	RMC	24.50	23.98	0.080	10 mm [Bottom]	FCC #1	N/A	1:1	0.044	1.127	0.050	
836.6	4183	WCDMA 850	RMC	24.50	23.98	-0.030	10 mm [Front]	FCC #1	N/A	1:1	0.600	1.127	0.676	
836.6	4183	WCDMA 850	RMC	24.50	23.98	-0.130	10 mm [Rear]	FCC #1	N/A	1:1	0.582	1.127	0.656	
836.6	4183	WCDMA 850	RMC	24.50	23.98	0.010	10 mm [Right]	FCC #1	N/A	1:1	0.451	1.127	0.508	
826.4	4132	WCDMA 850	RMC	24.50	24.13	0.090	10 mm [Left]	FCC #1	N/A	1:1	0.831	1.089	**0.905**	A15
836.6	4183	WCDMA 850	RMC	24.50	23.98	0.030	10 mm [Left]	FCC #1	N/A	1:1	0.727	1.127	0.819	
846.6	4233	WCDMA 850	RMC	24.50	24.08	-0.020	10 mm [Left]	FCC #1	N/A	1:1	0.680	1.102	0.749	
826.4	4132	WCDMA 850	RMC	24.50	24.13	0.100	10 mm [Left]	FCC #1	N/A	1:1	0.820	1.089	0.893	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								**Body 1.6 W/kg (mW/g)** averaged over 1 gram						

Table 10.3.2 DTS Hotspot SAR

MEASUREMENT RESULTS																
FREQUENCY		Mode	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Drift Power [dB]	Phantom Position	Device Serial Number	Peak SAR of Area Scan	Data Rate [Mbps]	Duty Cycle	1g SAR (W/kg)	Scaling Factor	Scaling Factor (Duty Cycle)	SAR (W/kg)	Plots #
MHz	Ch														
2437.0	6	802.11b	16.00	15.28	-0.160	10 mm [Top]	FCC #1	0.098	1	99.2	0.092	1.180	1.008	0.109	
2437.0	6	802.11b	16.00	15.28	0.060	10 mm [Front]	FCC #1	0.061	1	99.2	0.059	1.180	1.008	0.070	
2437.0	6	802.11b	16.00	15.28	-0.050	10 mm [Rear]	FCC #1	0.133	1	99.2	0.125	1.180	1.008	**0.149**	A12
2437.0	6	802.11b	16.00	15.28	-0.170	10 mm [Right]	FCC #1	0.023	1	99.2	0.019	1.180	1.008	0.023	
2437.0	6	802.11b	16.00	15.28	-0.060	10 mm [Left]	FCC #1	0.043	1	99.2	0.040	1.180	1.008	0.048	
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure								**Body 1.6 W/kg (mW/g)** averaged over 1 gram							

Adjusted SAR results for OFDM SAR												
FREQUENCY		Mode/ Antenna	Service	Maximum Allowed Power [dBm]	1g Scaled SAR (W/kg)	FREQUENCY [MHz]	Mode	Service	Maximum Allowed Power [dBm	Ratio of OFDM to DSSS	1g Adjusted SAR (W/kg)	Determine OFDM SAR
MHz	Ch											
2437.0	6	802.11b	DSSS	16.0	0.149	2437	802.11g	OFDM	12.0	0.398	0.059	X
2437.0	6	802.11b	DSSS	16.0	0.149	2437	802.11n	OFDM	12.0	0.398	0.059	X
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure						**Body 1.6 W/kg (mW/g)** averaged over 1 gram						

Note: SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

10.4 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements. A standard battery was used for all SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 10 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported boy-worn SAR was not > 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were performed.
8. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated.
9. SAR measurements were performed using the DASY5 automated system. The procedure for spatial peak SAR evaluation has been implemented according to the IEEE 1528 standard. During a maximum search, global and local maxima searches are automatically performed in 2-D after each area scan measurement. The algorithm will find the global maximum and all local maxima within 2 dB of the global maxima for all SAR distributions. All local maxima within 2 dB of the global maximum were searched and passed for the Zoom Scan measurement.

GSM Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. This device supports GSM VOIP in the head and body-worn configurations; therefore GPRS was additionally evaluated for head and body-worn compliance.
3. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR.
4. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). Since the maximum output power variation across the required test channels is not > ½ dB, the middle channel was used for testing.

WCDMA (UMTS) Notes:

1. WCDMA (UMTS) mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is > ½ dB, instead of the middle channel, the highest output power channel was used.

WLAN Notes:

1. The initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required duo to the maximum allowed powers and the highest reported DSSS SAR when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output and the adjust SAR is ≤ 1.2 W/kg.
3. When the maximum reported 1g averaged SAR ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg or all test channels were measured.
4. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor to determine compliance.

11. FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

11.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to handsets with built-in unlicensed transmitters such as 802.11b/g/n and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

11.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2,simultaneous transmission SAR test exclusion may be applied when the sum of the sum 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is ≤ 1.6 W/kg. The different test positon in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1-g or 10-g SAR.

Table 11.2.1 Estimated SAR (Head)

Mode	Frequency	Maximum Allowed Power		Separation Distance (Hand)	Estimated SAR (Body)
	[MHz]	[dBm]	[mW]	[mm]	[W/kg]
Bluetooth	2480	10.3	11	5	0.450

Table 11.2.2 Estimated SAR (Body)

Mode	Frequency	Maximum Allowed Power		Separation Distance (Hand)	Estimated SAR (Body)
	[MHz]	[dBm]	[mW]	[mm]	[W/kg]
Bluetooth	2480	10.3	11	10	0.225

11.3 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 11.1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.

Figure 11.1 Simultaneous Transmission Paths

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06.

Table 11.3.1 Simultaneous Transmission Scenarios

No.	Capable TX Configuration	GSM 850/1900 (Voice)	GPRS 850/1900 (Data)	WCDMA B5 (Voice)	WCDMA B5 (Data)	WIFI 2.4GHz 802.11b/g/n	Bluetooth 2.4GHz
1	GSM 850/1900 (Voice)		No	No	No	Yes	Yes
2	GPRS 850/1900 (Data)	No		No	No	Yes	Yes
3	WCDMA B5 (Voice)	No	No		No	Yes	Yes
4	WCDMA B5 (Data)	No	No	No		Yes	Yes
5	WIFI 2.4GHz 802.11b/g/n	Yes	Yes	Yes	Yes		No
6	Bluetooth 2.4GHz	Yes	Yes	Yes	Yes	No	

Table 11.3.2 Simultaneous SAR Cases

No.	Capable Transmit Configuration	Head SAR	Body-Worn SAR	Hotspot SAR	Note
1	GSM Voice + Wi-Fi 2.4 GHz	Yes	Yes	N/A	
2	GSM Voice + Bluetooth 2.4 GHz	Yes	Yes	N/A	
3	WCDMA + Wi-Fi 2.4 GHz	Yes	Yes	Yes	
4	WCDMA + Bluetooth 2.4 GHz	Yes	Yes	Yes	
5	GPRS + Wi-Fi 2.4 GHz	Yes	Yes	Yes	
6	GPRS + Bluetooth 2.4 GHz	Yes	Yes	Yes	

Notes:

1. WiFi 2.4GHz is supported Hotspot
2. WCDMA, GPRS is supported Hotspot.
3. VoIP is supported in WCDMA, GSM
4. Bluetooth and WiFi can not transmit simultaneously at 2.4G band.
5. GSM and WCDMA can not transmit simultaneously since they share the same chip.
6. When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.

11.4 Head SAR Simultaneous Transmission Analysis

Table 11.4.1 Simultaneous Transmission Scenario : 2G/3G/4G + 2.4 GHz W-LAN (Held to Ear)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	2.4G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Head SAR	GSM 850	Left Touch	0.566	0.202	0.768
		Right Touch	0.658	0.168	**0.826**
		Left Tilt	0.247	0.189	0.436
		Right Tilt	0.317	0.004	0.321
	GPRS 850	Left Touch	0.664	0.202	0.866
		Right Touch	0.702	0.168	**0.870**
		Left Tilt	0.229	0.189	0.418
		Right Tilt	0.357	0.004	0.361
	GSM 1900	Left Touch	0.117	0.202	**0.319**
		Right Touch	0.144	0.168	0.312
		Left Tilt	0.063	0.189	0.252
		Right Tilt	0.118	0.004	0.122
	GPRS 1900	Left Touch	0.135	0.202	**0.337**
		Right Touch	0.165	0.168	0.333
		Left Tilt	0.089	0.189	0.278
		Right Tilt	0.100	0.004	0.104
	WCDMA 850	Left Touch	0.639	0.202	**0.841**
		Right Touch	0.644	0.168	0.812
		Left Tilt	0.341	0.189	0.530
		Right Tilt	0.338	0.004	0.342

Table 11.4.2 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth (Held to Ear)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Head SAR	GSM 850	Left Touch	0.566	0.450	1.016
		Right Touch	0.658	0.450	**1.108**
		Left Tilt	0.247	0.450	0.697
		Right Tilt	0.317	0.450	0.767
	GPRS 850	Left Touch	0.664	0.450	1.114
		Right Touch	**0.702**	**0.450**	**1.152**
		Left Tilt	0.229	0.450	0.679
		Right Tilt	0.357	0.450	0.807
	GSM 1900	Left Touch	0.117	0.450	0.567
		Right Touch	0.144	0.450	**0.594**
		Left Tilt	0.063	0.450	0.513
		Right Tilt	0.118	0.450	0.568
	GPRS 1900	Left Touch	0.135	0.450	0.585
		Right Touch	0.165	0.450	**0.615**
		Left Tilt	0.089	0.450	0.539
		Right Tilt	0.100	0.450	0.550
	WCDMA 850	Left Touch	0.639	0.450	1.089
		Right Touch	0.644	0.450	**1.094**
		Left Tilt	0.341	0.450	0.791
		Right Tilt	0.338	0.450	0.788

11.5 Body-Worn Simultaneous Transmission Analysis

Table 11.5.1 Simultaneous Transmission Scenario : 2G/3G/4G + 2.4 GHz W-LAN (Body-Worn at 10 mm)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	2.4G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Body-Worn SAR	GSM 850	Front	0.738	0.070	**0.808**
		Rear	0.606	0.149	0.755
	GPRS 850	Front	0.643	0.070	0.713
		Rear	0.712	0.149	**0.861**
	GSM 1900	Front	0.616	0.070	**0.686**
		Rear	0.420	0.149	0.569
	GPRS 1900	Front	0.571	0.070	0.641
		Rear	0.725	0.149	**0.874**
	WCDMA 850	Front	0.676	0.070	0.746
		Rear	0.656	0.149	**0.805**

Table 11.5.2 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth (Body-Worn at 10 mm)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Body-Worn SAR	GSM 850	**Front**	**0.738**	**0.225**	**0.963**
		Rear	0.606	0.225	0.831
	GPRS 850	Front	0.643	0.225	0.868
		Rear	0.712	0.225	**0.937**
	GSM 1900	Front	0.616	0.225	**0.841**
		Rear	0.420	0.225	0.645
	GPRS 1900	Front	0.571	0.225	0.796
		Rear	0.725	0.225	**0.950**
	WCDMA 850	Front	0.676	0.225	**0.901**
		Rear	0.656	0.225	0.881

11.6 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v02r01, the device edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR ("-").

Table 11.6.1 Simultaneous Transmission Scenario : 2G/3G/4G + 2.4 GHz W-LAN (Hotspot at 10 mm)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	2.4G W-LAN SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Hotspot SAR	GPRS 850	Top	-	0.109	0.109
		Bottom	0.033	-	0.033
		Front	0.643	0.070	0.713
		Rear	0.712	0.149	0.861
		Right	0.443	0.023	0.466
		Left	0.843	0.048	**0.891**
	GPRS 1900	Top	-	0.109	0.109
		Bottom	0.394	-	0.394
		Front	0.571	0.070	0.641
		Rear	0.725	0.149	**0.874**
		Right	0.355	0.023	0.378
		Left	0.786	0.048	0.834
	WCDMA 850	Top	-	0.109	0.109
		Bottom	0.050	-	0.050
		Front	0.676	0.070	0.746
		Rear	0.656	0.149	0.805
		Right	0.508	0.023	0.531
		Left	0.905	0.048	**0.953**

Table 11.6.2 Simultaneous Transmission Scenario : 2G/3G/4G + Bluetooth (Hotspot at 10 mm)

Exposure Condition	Mode	Configuration	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	ΣSAR (W/kg)
			1	2	1+2
Hotspot SAR	GPRS 850	Top	-	0.225	0.225
		Bottom	0.033	0.225	0.258
		Front	0.643	0.225	0.868
		Rear	0.712	0.225	0.937
		Right	0.443	0.225	0.668
		Left	0.843	0.225	**1.068**
	GPRS 1900	Top	-	0.225	0.225
		Bottom	0.394	0.225	0.619
		Front	0.571	0.225	0.796
		Rear	0.725	0.225	0.950
		Right	0.355	0.225	0.580
		Left	0.786	0.225	**1.011**
	WCDMA 850	Top	-	0.225	0.225
		Bottom	0.050	0.225	0.275
		Front	0.676	0.225	0.901
		Rear	0.656	0.225	0.881
		Right	0.508	0.225	0.733
		Left	**0.905**	**0.225**	**1.130**

11.7 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2.

12. SAR MEASUREMENT VARIABILITY

12.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

1. When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
2. A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
3. A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.
4. Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg
5. The same procedures should be adapted for measurements according to extremity exposure limits by applying a factor of 2.5 for extremity exposure to the corresponding SAR thresholds.

Table 13.1 Body SAR Measurement Variability Results

Frequency		Mode	Service	# of Time Slots	Spacing [Side]	Measured SAR (1g)	1st Repeated SAR(1g)	Ratio	2nd Repeated SAR(1g)	Ratio	3rd Repeated SAR(1g)	Ratio
MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
826.4	4132	WCDMA 850	RMC	-	10 mm [Left]	0.831	0.820	1.01	-	-	-	-
ANSI / IEEE C95.1-1992– SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population Exposure							Body 1.6 W/kg (mW/g) averaged over 1 gram					

12.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for 1g for 10g for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

13. EQUIPMENT LIST

Table 13.1.1 Test Equipment Calibration

	Type	Manufacturer	Model	Cal.Date	Next.Cal.Date	S/N
☒	SEMITEC Engineering	SEMITEC	N/A	N/A	N/A	Shield Room
☒	Robot	SCHMID	TX60L	N/A	N/A	F14/5VR2A1/A/01
☒	Robot Controller	SCHMID	CS8C	N/A	N/A	F14/5VR2A1/C/01
☒	Joystick	SCHMID	N/A	N/A	N/A	D21142605A
☒	Intel Core i7-4770 3.40 GHz Windows 7 Professional	N/A	N/A	N/A	N/A	N/A
☒	Probe Alignment Unit LB	N/A	N/A	N/A	N/A	SE UKS 030 AA
☒	Mounting Device	SCHMID	SD000H01KA	N/A	N/A	N/A
☒	Twin SAM Phantom	SCHMID	TP1220	N/A	N/A	N/A
☒	Data Acquisition Electronics	SCHMID	DAE4V1	2018-04-24	2019-04-24	1391
☒	Data Acquisition Electronics	SCHMID	DAE4V1	2017-09-19	2018-09-19	1453
☒	Dosimetric E-Field Probe	SCHMID	EX3DV4	2017-11-28	2018-11-28	7337
☒	Dosimetric E-Field Probe	SCHMID	EX3DV4	2018-04-25	2019-04-25	3916
☒	835MHz SAR Dipole	SCHMID	D835V2	2017-09-21	2019-09-21	464
☒	1900MHz SAR Dipole	SCHMID	D1900V2	2017-09-20	2019-09-20	5d029
☒	2450MHz SAR Dipole	SCHMID	D2450V2	2017-09-19	2019-09-19	726
☒	Network Analyzer	Agilent	E5071C	2018-02-02	2019-02-02	MY46111534
☒	Signal Generator	Agilent	E4438C	2018-07-04	2019-07-04	US41461520
☒	Amplifier	EMPOWER	BBS3Q7ELU	2018-07-10	2019-07-10	1020
☒	High Power RF Amplifier	EMPOWER	BBS3Q8CCJ	2018-07-06	2019-07-06	1005
☒	Power Meter	HP	EPM-442A	2017-12-27	2018-12-27	GB37170267
☒	Power Meter	HP	EPM-442A	2017-12-27	2018-12-27	GB37170413
☒	Power Meter	Anritsu	ML2495A	2018-07-04	2019-07-04	1435003
☒	Power Sensor	Anritsu	MA2490A	2018-07-04	2019-07-04	1409034
☒	Power Sensor	HP	8481A	2017-12-27	2018-12-27	US37294267
☒	Power Sensor	HP	8481A	2017-12-27	2018-12-27	3318A96566
☒	Power Sensor	HP	8481A	2017-12-27	2018-12-27	2702A65976
☒	Dual Directional Coupler	Agilent	778D-012	2017-12-27	2018-12-27	50228
☒	Directional Coupler	HP	772D	2018-07-03	2019-07-03	2889A01064
☒	Low Pass Filter 1.5GHz	Micro LAB	LA-15N	2017-12-27	2018-12-27	N/A
☒	Low Pass Filter 3.0GHz	Micro LAB	LA-30N	2018-07-05	2019-07-05	N/A
☒	Attenuators(3 dB)	Agilent	8491B	2017-12-27	2018-12-27	MY39260700
☒	Attenuators(10 dB)	WEINSCHEL	23-10-34	2017-12-27	2018-12-27	BP4387
☒	Dielectric Probe kit	SCHMID	DAK-3.5	2017-11-21	2018-11-21	1092
☒	8960 Series 10 Wireless Comms. Test Set	Agilent	E5515C	2018-07-04	2019-07-04	GB41321164
☒	Wideband Radio Communication Tester	Rohde Schwarz	CMW500	2018-02-05	2019-02-05	101414
☒	Power Splitter	Anritsu	K241B	2017-12-27	2018-12-27	1301183
☒	Bluetooth Tester	TESCOM	TC-3000B	2017-12-26	2018-12-26	3000B770243

NOTE(S):

1. The E-field probe was calibrated by SPEAG, by temperature measurement procedure. Dipole Verification measurement is performed by DT&C before each test. The brain and muscle simulating material are calibrated by DT&C using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the brain and muscle-equivalent material. Each equipment item was used solely within its respective calibration period.
2. CBT(Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

14. MEASUREMENT UNCERTAINTIES

835 MHz Head (S/N : 7337)

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1g	(Ci) 10g	Standard (1g)	Standard (10g)	vi 2 or Veff
Measurement System								
Probe calibration	± 6.0	Normal	1	1	1	± 6.0 %	± 6.0 %	∞
Isotropy	± 1.3	Normal	1	1	1	± 1.3 %	± 1.3 %	∞
Boundary Effects	± 2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %	∞
Probe Linearity	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Probe modulation response	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Detection limits	± 0.25	Rectangular	√3	1	1	± 0.14 %	± 0.14 %	∞
Readout Electronics	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Response time	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Integration time	± 2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Conditions – Noise	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
RF Ambient Conditions – Reflections	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Probe Positioning	± 6.7	Rectangular	√3	1	1	± 3.9 %	± 3.9 %	∞
Algorithms for Max. SAR Eval.	± 4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	∞
Test Sample Related								
Device Positioning	± 2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	± 3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	5
Power Drift	± 5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %	∞
SAR Scaling	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Physical Parameters								
Phantom Shell	± 7.6	Rectangular	√3	1	1	± 4.4 %	± 4.4 %	∞
SAR correction	± 0.0	Normal	1	1	0.84	± 0.0 %	± 0.0 %	∞
Liquid conductivity (Target)	± 5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %	∞
Liquid conductivity (Meas.)	± 3.9	Normal	1	0.78	0.71	± 3.0 %	± 2.8 %	10
Liquid permittivity (Target)	± 5.0	Rectangular	√3	0.60	0.49	± 1.7 %	± 1.4 %	∞
Liquid permittivity (Meas.)	± 4.1	Normal	1	0.23	0.26	± 0.9 %	± 1.1 %	10
Temp. unc. - Conductivity	± 1.8	Rectangular	√3	0.78	0.71	± 0.8 %	± 0.7 %	∞
Temp. unc. - Permittivity	± 1.8	Rectangular	√3	0.23	0.26	± 0.2%	± 0.3 %	∞
Combined Standard Uncertainty						**± 11.6 %**	**± 11.4 %**	330
Expanded Uncertainty (k=2)						**± 23.2 %**	**± 22.8 %**	

The above measurement uncertainties are according to IEEE Std 1528

835 MHz Body (S/N : 7337)

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1g	(Ci) 10g	Standard (1g)	Standard (10g)	vi 2 or Veff
Measurement System								
Probe calibration	± 6.0	Normal	1	1	1	± 6.0 %	± 6.0 %	∞
Isotropy	± 1.3	Normal	1	1	1	± 1.3 %	± 1.3 %	∞
Boundary Effects	± 2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %	∞
Probe Linearity	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Probe modulation response	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Detection limits	± 0.25	Rectangular	√3	1	1	± 0.14 %	± 0.14 %	∞
Readout Electronics	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Response time	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Integration time	± 2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Conditions – Noise	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
RF Ambient Conditions – Reflections	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Probe Positioning	± 6.7	Rectangular	√3	1	1	± 3.9 %	± 3.9 %	∞
Algorithms for Max. SAR Eval.	± 4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	∞
Test Sample Related								
Device Positioning	± 2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	± 3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	5
Power Drift	± 5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %	∞
SAR Scaling	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Physical Parameters								
Phantom Shell	± 7.6	Rectangular	√3	1	1	± 4.4 %	± 4.4 %	∞
SAR correction	± 0.0	Normal	1	1	0.84	± 0.0 %	± 0.0 %	∞
Liquid conductivity (Target)	± 5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %	∞
Liquid conductivity (Meas.)	± 4.0	Normal	1	0.78	0.71	± 3.1 %	± 2.8 %	10
Liquid permittivity (Target)	± 5.0	Rectangular	√3	0.60	0.49	± 1.7 %	± 1.4 %	∞
Liquid permittivity (Meas.)	± 3.8	Normal	1	0.23	0.26	± 0.9 %	± 1.0 %	10
Temp. unc. - Conductivity	± 1.9	Rectangular	√3	0.78	0.71	± 0.9 %	± 0.8 %	∞
Temp. unc. - Permittivity	± 1.9	Rectangular	√3	0.23	0.26	± 0.3 %	± 0.3 %	∞
Combined Standard Uncertainty						**± 11.6 %**	**± 11.4 %**	330
Expanded Uncertainty (k=2)						**± 23.2 %**	**± 22.8 %**	

The above measurement uncertainties are according to IEEE Std 1528

1900 MHz Head (S/N : 7337)

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1g	(Ci) 10g	Standard (1g)	Standard (10g)	vi 2 or Veff
Measurement System								
Probe calibration	± 6.0	Normal	1	1	1	± 6.0 %	± 6.0 %	∞
Isotropy	± 1.3	Normal	1	1	1	± 1.3 %	± 1.3 %	∞
Boundary Effects	± 2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %	∞
Probe Linearity	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Probe modulation response	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Detection limits	± 0.25	Rectangular	√3	1	1	± 0.14 %	± 0.14 %	∞
Readout Electronics	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Response time	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Integration time	± 2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Conditions – Noise	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
RF Ambient Conditions – Reflections	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Probe Positioning	± 6.7	Rectangular	√3	1	1	± 3.9 %	± 3.9 %	∞
Algorithms for Max. SAR Eval.	± 4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	∞
Test Sample Related								
Device Positioning	± 2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	± 3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	5
Power Drift	± 5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %	∞
SAR Scaling	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Physical Parameters								
Phantom Shell	± 7.6	Rectangular	√3	1	1	± 4.4 %	± 4.4 %	∞
SAR correction	± 0.0	Normal	1	1	0.84	± 0.0 %	± 0.0 %	∞
Liquid conductivity (Target)	± 5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %	∞
Liquid conductivity (Meas.)	± 3.5	Normal	1	0.78	0.71	± 2.7 %	± 2.5 %	10
Liquid permittivity (Target)	± 5.0	Rectangular	√3	0.60	0.49	± 1.7 %	± 1.4 %	∞
Liquid permittivity (Meas.)	± 3.8	Normal	1	0.23	0.26	± 0.9 %	± 1.0 %	10
Temp. unc. - Conductivity	± 1.8	Rectangular	√3	0.78	0.71	± 0.8 %	± 0.7 %	∞
Temp. unc. - Permittivity	± 1.9	Rectangular	√3	0.23	0.26	± 0.3 %	± 0.3 %	∞
Combined Standard Uncertainty						**± 11.5 %**	**± 11.3 %**	330
Expanded Uncertainty (k=2)						**± 23.0 %**	**± 22.6 %**	

The above measurement uncertainties are according to IEEE Std 1528

1900 MHz Body (S/N : 7337)

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1g	(Ci) 10g	Standard (1g)	Standard (10g)	vi 2 or Veff
Measurement System								
Probe calibration	± 6.0	Normal	1	1	1	± 6.0 %	± 6.0 %	∞
Isotropy	± 1.3	Normal	1	1	1	± 1.3 %	± 1.3 %	∞
Boundary Effects	± 2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %	∞
Probe Linearity	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Probe modulation response	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Detection limits	± 0.25	Rectangular	√3	1	1	± 0.14 %	± 0.14 %	∞
Readout Electronics	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Response time	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Integration time	± 2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Conditions – Noise	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
RF Ambient Conditions – Reflections	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Probe Positioning	± 6.7	Rectangular	√3	1	1	± 3.9 %	± 3.9 %	∞
Algorithms for Max. SAR Eval.	± 4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	∞
Test Sample Related								
Device Positioning	± 2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	± 3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	5
Power Drift	± 5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %	∞
SAR Scaling	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Physical Parameters								
Phantom Shell	± 7.6	Rectangular	√3	1	1	± 4.4 %	± 4.4 %	∞
SAR correction	± 0.0	Normal	1	1	0.84	± 0.0 %	± 0.0 %	∞
Liquid conductivity (Target)	± 5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %	∞
Liquid conductivity (Meas.)	± 4.0	Normal	1	0.78	0.71	± 3.1 %	± 2.8 %	10
Liquid permittivity (Target)	± 5.0	Rectangular	√3	0.60	0.49	± 1.7 %	± 1.4 %	∞
Liquid permittivity (Meas.)	± 3.7	Normal	1	0.23	0.26	± 0.9 %	± 1.0 %	10
Temp. unc. - Conductivity	± 1.8	Rectangular	√3	0.78	0.71	± 0.8 %	± 0.7 %	∞
Temp. unc. - Permittivity	± 1.8	Rectangular	√3	0.23	0.26	± 0.2 %	± 0.3 %	∞
Combined Standard Uncertainty						**± 11.6 %**	**± 11.4 %**	330
Expanded Uncertainty (k=2)						**± 23.2 %**	**± 22.8 %**	

The above measurement uncertainties are according to IEEE Std 1528

2450 MHz Head (S/N : 3916)

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1g	(Ci) 10g	Standard (1g)	Standard (10g)	vi 2 or Veff
Measurement System								
Probe calibration	± 6.0	Normal	1	1	1	± 6.0 %	± 6.0 %	∞
Isotropy	± 1.3	Normal	1	1	1	± 1.3 %	± 1.3 %	∞
Boundary Effects	± 2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %	∞
Probe Linearity	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Probe modulation response	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Detection limits	± 0.25	Rectangular	√3	1	1	± 0.14 %	± 0.14 %	∞
Readout Electronics	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Response time	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Integration time	± 2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Conditions – Noise	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
RF Ambient Conditions – Reflections	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Probe Positioning	± 6.7	Rectangular	√3	1	1	± 3.9 %	± 3.9 %	∞
Algorithms for Max. SAR Eval.	± 4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	∞
Test Sample Related								
Device Positioning	± 2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	± 3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	5
Power Drift	± 5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %	∞
SAR Scaling	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Physical Parameters								
Phantom Shell	± 7.6	Rectangular	√3	1	1	± 4.4 %	± 4.4 %	∞
SAR correction	± 0.0	Normal	1	1	0.84	± 0.0 %	± 0.0 %	∞
Liquid conductivity (Target)	± 5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %	∞
Liquid conductivity (Meas.)	± 4.0	Normal	1	0.78	0.71	± 3.1 %	± 2.8 %	10
Liquid permittivity (Target)	± 5.0	Rectangular	√3	0.60	0.49	± 1.7 %	± 1.4 %	∞
Liquid permittivity (Meas.)	± 3.9	Normal	1	0.23	0.26	± 0.9 %	± 1.0 %	10
Temp. unc. - Conductivity	± 1.8	Rectangular	√3	0.78	0.71	± 0.8 %	± 0.7 %	∞
Temp. unc. - Permittivity	± 1.8	Rectangular	√3	0.23	0.26	± 0.2 %	± 0.3 %	∞
Combined Standard Uncertainty						**± 11.6 %**	**± 11.4 %**	330
Expanded Uncertainty (k=2)						**± 23.2 %**	**± 22.8 %**	

The above measurement uncertainties are according to IEEE Std 1528

2450 MHz Body (S/N : 3916)

Error Description	Uncertainty value ±%	Probability Distribution	Divisor	(Ci) 1g	(Ci) 10g	Standard (1g)	Standard (10g)	vi 2 or Veff
Measurement System								
Probe calibration	± 6.0	Normal	1	1	1	± 6.0 %	± 6.0 %	∞
Isotropy	± 1.3	Normal	1	1	1	± 1.3 %	± 1.3 %	∞
Boundary Effects	± 2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %	∞
Probe Linearity	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Probe modulation response	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Detection limits	± 0.25	Rectangular	√3	1	1	± 0.14 %	± 0.14 %	∞
Readout Electronics	± 0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Response time	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Integration time	± 2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Conditions – Noise	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
RF Ambient Conditions – Reflections	± 3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner	± 0.8	Rectangular	√3	1	1	± 0.46 %	± 0.46 %	∞
Probe Positioning	± 6.7	Rectangular	√3	1	1	± 3.9 %	± 3.9 %	∞
Algorithms for Max. SAR Eval.	± 4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %	∞
Test Sample Related								
Device Positioning	± 2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	± 3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	5
Power Drift	± 5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %	∞
SAR Scaling	± 0.0	Rectangular	√3	1	1	± 0.0 %	± 0.0 %	∞
Physical Parameters								
Phantom Shell	± 7.6	Rectangular	√3	1	1	± 4.4 %	± 4.4 %	∞
SAR correction	± 0.0	Normal	1	1	0.84	± 0.0 %	± 0.0 %	∞
Liquid conductivity (Target)	± 5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %	∞
Liquid conductivity (Meas.)	± 4.0	Normal	1	0.78	0.71	± 3.1 %	± 2.8 %	10
Liquid permittivity (Target)	± 5.0	Rectangular	√3	0.60	0.49	± 1.7 %	± 1.4 %	∞
Liquid permittivity (Meas.)	± 3.8	Normal	1	0.23	0.26	± 0.9 %	± 1.0 %	10
Temp. unc. - Conductivity	± 1.9	Rectangular	√3	0.78	0.71	± 0.9 %	± 0.8 %	∞
Temp. unc. - Permittivity	± 1.8	Rectangular	√3	0.23	0.26	± 0.2 %	± 0.3 %	∞
Combined Standard Uncertainty						**± 11.6 %**	**± 11.4 %**	330
Expanded Uncertainty (k=2)						**± 23.2 %**	**± 22.8 %**	

The above measurement uncertainties are according to IEEE Std 1528

15. CONCLUSION

Measurement Conclusion

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the FCC. These measurements are taken to simulate the RF effects exposure under the worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters subject to the test. The test results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are every complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role impossible biological effect are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease).

Because innumerable factors may interact to determine the specific biological outcome of an exposure to electromagnetic fields, any protection guide shall consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables.

16. REFERENCES

[1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.

[2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radiofrequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.

[3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radiofrequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.

[4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.

[5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2003,Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices.

[6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for Radio Frequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.

[7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.

[8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. -124.

[9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.

[10] Schmid& Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.

[11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct.1996, pp. 1865-1873.

[12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.

[13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bio electromagnetics, Canada: 1987, pp. 29-36.

[14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.

[15] W. Gander, Computer mathematick, Birkhaeuser, Basel, 1992.

[16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.

[17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

[18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.

[19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hoschschule Zürich, Dosimetric Evaluation of the Cellular Phone.

[20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300MHz to 3 GHz), Feb. 2005.

[21] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radio communication Apparatus (All Frequency Bands) Issue 5, March 2015.

[22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009

[23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225,D01-D07

[24] SAR Measurement procedures for IEEE 802.11a/b/g KDB Publication 248227 D01v02

[25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474D02-D04

[26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04

[27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02

[28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02

[29] 615223 D01 802 16e WI-Max SAR Guidance v01, Nov. 13, 2009

[30] Anexo à Resolução No. 533, de 10 de September de 2009.

[31] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body(frequency range of 30 MHz to 6 GHz), Mar. 2010.

APPENDIX A. – Probe Calibration Data

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **DT&C (Dymstec)**

Certificate No: EX3-7337_Nov17

CALIBRATION CERTIFICATE

Object	EX3DV4 - SN:7337
Calibration procedure(s)	QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6 Calibration procedure for dosimetric E-field probes
Calibration date:	November 28, 2017

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02525)	Apr-18
Reference 20 dB Attenuator	SN: S5277 (20x)	07-Apr-17 (No. 217-02528)	Apr-18
Reference Probe ES3DV2	SN: 3013	31-Dec-16 (No. ES3-3013_Dec16)	Dec-17
DAE4	SN: 660	7-Dec-16 (No. DAE4-660_Dec16)	Dec-17
Secondary Standards	**ID**	**Check Date (in house)**	**Scheduled Check**
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-16)	In house check: Jun-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

	Name	Function	Signature
Calibrated by:	Michael Weber	Laboratory Technician	M. Weber
Approved by:	Katja Pokovic	Technical Manager	

Issued: November 28, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Glossary:

TSL	tissue simulating liquid
NORMx,y,z	sensitivity in free space
ConvF	sensitivity in TSL / NORMx,y,z
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., ϑ = 0 is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
b) IEC 62209-1, ", "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- *NORMx,y,z:* Assessed for E-field polarization ϑ = 0 (f ≤ 900 MHz in TEM-cell; f > 1800 MHz: R22 waveguide). NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMx,y,z does not affect the E^2-field uncertainty inside TSL (see below *ConvF*).
- *NORM(f)x,y,z = NORMx,y,z * frequency_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- *DCPx,y,z:* DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- *PAR:* PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- *Ax,y,z; Bx,y,z; Cx,y,z; Dx,y,z; VRx,y,z: A, B, C, D* are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. *VR* is the maximum calibration range expressed in RMS voltage across the diode.
- *ConvF and Boundary Effect Parameters:* Assessed in flat phantom using E-field (or Temperature Transfer Standard for f ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to *NORMx,y,z * ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- *Spherical isotropy (3D deviation from isotropy)*: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- *Sensor Offset*: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- *Connector Angle*: The angle is assessed using the information gained by determining the *NORMx* (no uncertainty required).

Probe EX3DV4

SN:7337

Manufactured:	July 23, 2014
Repaired:	November 23, 2017
Calibrated:	November 28, 2017

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

EX3DV4– SN:7337

November 28, 2017

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7337

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm (μV/(V/m)^2)[A]	0.53	0.59	0.56	± 10.1 %
DCP (mV)[B]	100.4	99.5	99.1	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB√μV	C	D dB	VR mV	Unc[E] (k=2)
0	CW	X	0.0	0.0	1.0	0.00	149.4	±3.3 %
		Y	0.0	0.0	1.0		137.6	
		Z	0.0	0.0	1.0		145.5	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

[A] The uncertainties of Norm X,Y,Z do not affect the E^2-field uncertainty inside TSL (see Pages 5 and 6).
[B] Numerical linearization parameter: uncertainty not required.
[E] Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4– SN:7337

November 28, 2017

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7337

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) [C]	Relative Permittivity [F]	Conductivity (S/m) [F]	ConvF X	ConvF Y	ConvF Z	Alpha [G]	Depth [G] (mm)	Unc (k=2)
835	41.5	0.90	10.27	10.27	10.27	0.52	0.80	± 12.0 %
900	41.5	0.97	10.03	10.03	10.03	0.44	0.85	± 12.0 %
1750	40.1	1.37	9.00	9.00	9.00	0.37	0.80	± 12.0 %
1900	40.0	1.40	8.46	8.46	8.46	0.36	0.84	± 12.0 %
2450	39.2	1.80	7.70	7.70	7.70	0.34	0.87	± 12.0 %
2600	39.0	1.96	7.48	7.48	7.48	0.44	0.85	± 12.0 %
5200	36.0	4.66	5.81	5.81	5.81	0.35	1.80	± 13.1 %
5300	35.9	4.76	5.61	5.61	5.61	0.35	1.80	± 13.1 %
5500	35.6	4.96	5.10	5.10	5.10	0.40	1.80	± 13.1 %
5600	35.5	5.07	4.89	4.89	4.89	0.40	1.80	± 13.1 %
5800	35.3	5.27	5.00	5.00	5.00	0.40	1.80	± 13.1 %

[C] Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

[F] At frequencies below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

[G] Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4– SN:7337

November 28, 2017

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7337

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) [C]	Relative Permittivity [F]	Conductivity (S/m) [F]	ConvF X	ConvF Y	ConvF Z	Alpha [G]	Depth [G] (mm)	Unc (k=2)
835	55.2	0.97	10.29	10.29	10.29	0.35	1.05	± 12.0 %
900	55.0	1.05	10.13	10.13	10.13	0.47	0.86	± 12.0 %
1750	53.4	1.49	8.52	8.52	8.52	0.38	0.80	± 12.0 %
1900	53.3	1.52	8.20	8.20	8.20	0.35	0.80	± 12.0 %
2450	52.7	1.95	7.88	7.88	7.88	0.40	0.85	± 12.0 %
2600	52.5	2.16	7.52	7.52	7.52	0.37	0.89	± 12.0 %
5200	49.0	5.30	5.41	5.41	5.41	0.40	1.90	± 13.1 %
5300	48.9	5.42	5.10	5.10	5.10	0.45	1.90	± 13.1 %
5500	48.6	5.65	4.50	4.50	4.50	0.45	1.90	± 13.1 %
5600	48.5	5.77	4.42	4.42	4.42	0.45	1.90	± 13.1 %
5800	48.2	6.00	4.61	4.61	4.61	0.45	1.90	± 13.1 %

[C] Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

[F] At frequencies below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

[G] Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4– SN:7337

November 28, 2017

Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: ± 6.3% (k=2)

EX3DV4– SN:7337

November 28, 2017

Receiving Pattern (ϕ), ϑ = 0°

f=600 MHz,TEM



f=1800 MHz,R22



Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)

EX3DV4– SN:7337

November 28, 2017

Dynamic Range f(SAR$_{head}$)
(TEM cell , f_{eval}= 1900 MHz)





Uncertainty of Linearity Assessment: ± 0.6% (k=2)

EX3DV4– SN:7337

November 28, 2017

Conversion Factor Assessment

f = 835 MHz,WGLS R9 (H_convF)



f = 1900 MHz,WGLS R22 (H_convF)



Deviation from Isotropy in Liquid

Error (ϕ, ϑ), f = 900 MHz





Uncertainty of Spherical Isotropy Assessment: ± 2.6% (k=2)

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7337

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	59.8
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **DT&C (Dymstec)** Certificate No: **EX3-3916_Apr18**

CALIBRATION CERTIFICATE

Object	EX3DV4 - SN:3916
Calibration procedure(s)	QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6 Calibration procedure for dosimetric E-field probes
Calibration date:	April 25, 2018

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-18 (No. 217-02682)	Apr-19
Reference Probe ES3DV2	SN: 3013	30-Dec-17 (No. ES3-3013_Dec17)	Dec-18
DAE4	SN: 660	21-Dec-17 (No. DAE4-660_Dec17)	Dec-18
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-16)	In house check: Jun-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

	Name	Function	Signature
Calibrated by:	Claudio Leubler	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: April 26, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Glossary:

TSL	tissue simulating liquid
NORMx,y,z	sensitivity in free space
ConvF	sensitivity in TSL / NORMx,y,z
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., ϑ = 0 is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
b) IEC 62209-1, ", "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- *NORMx,y,z:* Assessed for E-field polarization ϑ = 0 (f ≤ 900 MHz in TEM-cell; f > 1800 MHz: R22 waveguide). NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMx,y,z does not affect the E^2-field uncertainty inside TSL (see below *ConvF*).
- *NORM(f)x,y,z = NORMx,y,z * frequency_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- *DCPx,y,z:* DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- *PAR:* PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- *Ax,y,z; Bx,y,z; Cx,y,z; Dx,y,z; VRx,y,z: A, B, C, D* are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. *VR* is the maximum calibration range expressed in RMS voltage across the diode.
- *ConvF and Boundary Effect Parameters:* Assessed in flat phantom using E-field (or Temperature Transfer Standard for f ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to *NORMx,y,z * ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- *Spherical isotropy (3D deviation from isotropy)*: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- *Sensor Offset*: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- *Connector Angle*: The angle is assessed using the information gained by determining the *NORMx* (no uncertainty required).

Probe EX3DV4

SN:3916

Manufactured: December 18, 2012
Calibrated: April 25, 2018

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3916

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu V/(V/m)^2$)[A]	0.56	0.47	0.52	± 10.1 %
DCP (mV)[B]	99.6	101.3	99.8	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB√μV	C	D dB	VR mV	Unc[E] (k=2)
0	CW	X	0.0	0.0	1.0	0.00	148.6	±3.5 %
		Y	0.0	0.0	1.0		159.6	
		Z	0.0	0.0	1.0		142.3	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

[A] The uncertainties of Norm X,Y,Z do not affect the E^2-field uncertainty inside TSL (see Pages 5 and 6).
[B] Numerical linearization parameter: uncertainty not required.
[E] Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3916

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) [C]	Relative Permittivity [F]	Conductivity (S/m) [F]	ConvF X	ConvF Y	ConvF Z	Alpha [G]	Depth [G] (mm)	Unc (k=2)
2450	39.2	1.80	7.72	7.72	7.72	0.36	0.85	± 12.0 %
2600	39.0	1.96	7.51	7.51	7.51	0.37	0.84	± 12.0 %
5200	36.0	4.66	5.38	5.38	5.38	0.35	1.80	± 13.1 %
5300	35.9	4.76	5.04	5.04	5.04	0.40	1.80	± 13.1 %
5500	35.6	4.96	5.01	5.01	5.01	0.40	1.80	± 13.1 %
5600	35.5	5.07	4.84	4.84	4.84	0.40	1.80	± 13.1 %
5800	35.3	5.27	4.94	4.94	4.94	0.40	1.80	± 13.1 %

[C] Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

[F] At frequencies below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

[G] Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3916

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) [C]	Relative Permittivity [F]	Conductivity (S/m) [F]	ConvF X	ConvF Y	ConvF Z	Alpha [G]	Depth [G] (mm)	Unc (k=2)
2450	52.7	1.95	7.69	7.69	7.69	0.36	0.90	± 12.0 %
2600	52.5	2.16	7.42	7.42	7.42	0.41	0.90	± 12.0 %
5200	49.0	5.30	4.66	4.66	4.66	0.50	1.90	± 13.1 %
5300	48.9	5.42	4.44	4.44	4.44	0.50	1.90	± 13.1 %
5500	48.6	5.65	4.23	4.23	4.23	0.50	1.90	± 13.1 %
5600	48.5	5.77	4.02	4.02	4.02	0.50	1.90	± 13.1 %
5800	48.2	6.00	4.31	4.31	4.31	0.50	1.90	± 13.1 %

[C] Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

[F] At frequencies below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

[G] Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4– SN:3916 April 25, 2018

Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: ± 6.3% (k=2)

EX3DV4– SN:3916 April 25, 2018

Receiving Pattern (ϕ), ϑ = 0°

f=600 MHz,TEM



f=1800 MHz,R22





Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)

EX3DV4– SN:3916 April 25, 2018

Dynamic Range f(SAR_{head})
(TEM cell , f_{eval}= 1900 MHz)





Uncertainty of Linearity Assessment: ± 0.6% (k=2)

EX3DV4– SN:3916 April 25, 2018

Conversion Factor Assessment

f = 2450 MHz,WGLS R22 (H_convF)



f = 2450 MHz,WGLS R22 (M_convF)



Deviation from Isotropy in Liquid

Error (ϕ, ϑ), f = 900 MHz





Uncertainty of Spherical Isotropy Assessment: ± 2.6% (k=2)

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3916

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	88.3
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm