

October 7, 2019

Lutron Electronics Co., Inc.
7200 Suter Road
Coopersburg, PA 18036

Dear Keith Kennedy,

Enclosed is the EMC Wireless test report for compliance testing of the Lutron Electronics Co., Inc., Ketra RF Module as tested to the requirements of Title 47 of the CFR, Ch. 1 (10-1-06 ed.), Part 15 Subpart C for Intentional Radiators.

Thank you for using the services of Eurofins MET Labs, Inc. If you have any questions regarding these results or if MET can be of further service to you, please feel free to contact me.

Sincerely yours,
EUROFINS MET LABS, INC.



Joel Huna
Documentation Department

Reference: (\\Lutron Electronics Co., Inc.\\EMC104252A-FCC247 Rev. 3)

Certificates and reports shall not be reproduced except in full, without the written permission of Eurofins MET Labs, Inc. While use of the A2LA logo in this report reflects MET accreditation under these programs, the report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the Federal Government. This letter of transmittal is not a part of the attached report.



Electromagnetic Compatibility Criteria Test Report

for the

Lutron Electronics Co., Inc.
Ketra RF Module

Tested under
the FCC Certification Rules
contained in
15.247 Subpart C for Intentional Radiators

MET Report: EMC104252A-FCC247 Rev. 3

October 7, 2019

Prepared For:

Lutron Electronics Co., Inc.
7200 Suter Road
Coopersburg, PA 18036

Prepared By:
Eurofins MET Labs, Inc.
914 West Patapsco Avenue,
Baltimore, MD 21230

Electromagnetic Compatibility Criteria Test Report

for the

Lutron Electronics Co., Inc.
Ketra RF Module

Tested under
the FCC Certification Rules
contained in
15.247 Subpart C for Intentional Radiators



Deepak Giri, Project Engineer
Electromagnetic Compatibility Lab



Joel Huna
Documentation Department

Engineering Statement: The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules Part 15.247 under normal use and maintenance.



Christopher Dennison,
Manager, Electromagnetic Compatibility Lab

Report Status Sheet

Revision	Report Date	Reason for Revision
Ø	August 13, 2019	Initial Issue.
1	August 18, 2019	Update to Plots
2	September 13, 2019	FCC ID Addition.
3	October 7, 2019	Corrections for TCB.

Table of Contents

I.	Executive Summary	1
	A. Purpose of Test	2
	B. Executive Summary	2
II.	Equipment Configuration	3
	A. Overview.....	4
	B. References.....	5
	C. Test Site	5
	D. Measurement Uncertainty	5
	E. Description of Test Sample.....	6
	F. Equipment Configuration.....	6
	G. Support Equipment	6
	H. Ports and Cabling Information.....	6
	I. Mode of Operation.....	6
	J. Method of Monitoring EUT Operation	7
	K. Modifications.....	7
	a) Modifications to EUT.....	7
	b) Modifications to Test Standard.....	7
	L. Disposition of EUT.....	7
III.	Electromagnetic Compatibility Criteria for Intentional Radiators.....	8
	§ 15.203 Antenna Requirement	9
	§ 15.207(a) Conducted Emissions Limits.....	10
	§ 15.247(a)(a) 6 dB and 99% Bandwidth	13
	§ 15.247(b) Peak Power Output	15
	§ 15.247(d) Radiated Spurious Emissions Requirements and Band Edge	18
	§ 15.247(c) Spurious Emissions in Non-restricted Bands	36
	§ 15.247(e) Peak Power Spectral Density	41
	§ 15.247(i) Maximum Permissible Exposure	43
IV.	Test Equipment	44
V.	Certification & User's Manual Information.....	46
	A. Certification Information	47
	B. Label and User's Manual Information	51

List of Tables

Table 1. Executive Summary of EMC Part 15.247 Compliance Testing	2
Table 2. EUT Summary Table.....	4
Table 3. References	5
Table 4. Uncertainty Calculations Summary.....	5
Table 5. Equipment Configuration	6
Table 6. Ports and Cabling Information	6
Table 7. Antenna List	9
Table 8. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a)	10
Table 9. Conducted Emissions, 15.207(a), Phase Line, Test Results	11
Table 10. Conducted Emissions, 15.207(a), Neutral Line, Test Results	12
Table 11. 6 dB Occupied Bandwidth, Test Results	13
Table 12. Output Power Requirements from §15.247(b)	15
Table 13. Peak Power Output, Test Results	16
Table 14. Restricted Bands of Operation.....	18
Table 15. Radiated Emissions Limits Calculated from FCC Part 15, § 15.209 (a)	19
Table 16. Peak Power Spectral Density, Test Results	41
Table 17. Test Equipment List	45

List of Figures

Figure 1. Block Diagram of Test Configuration.....	6
Figure 2: Conducted Emissions, Plot, Phase BLE.....	11
Figure 3: Conducted Emissions, Plot, Neutral BLE	12
Figure 5. Block Diagram, Occupied Bandwidth Test Setup.....	13
Figure 6: 6 dB Occupied Bandwidth, BLE Low Channel	14
Figure 7: 6 dB Occupied Bandwidth, 6 dB DTS Bandwidth, BLE Mid Channel	14
Figure 8: 6 dB Occupied Bandwidth, BLE High Channel	14
Figure 9: Power Output, BLE Low Channel, Peak Conducted Power	17
Figure 10: Power Output, BLE Mid Channel, Peak Conducted Power.....	17
Figure 11: Power Output, BLE High Channel, Peak Conducted Power	17
Figure 12: Radiated Emissions, BLE Low Channel, 30 MHz - 1 GHz, Antenna 1.....	20
Figure 13: Radiated Emissions, BLE Low Channel, Average, 7.2 GHz emission, Antenna 1	20
Figure 14: Radiated Emissions, BLE Low Channel, 1GHz - 18GHz, Average, Antenna 1.....	20
Figure 15: Radiated Emissions, BLE Low Channel, 18GHz - 25GHz, Average, Antenna 1.....	21
Figure 16: Radiated Emissions, BLE Low Channel, 1GHz - 18GHz, Peak, Antenna 1.....	21
Figure 17: Radiated Emissions, BLE Low Channel, 18GHz - 25GHz, Peak, Antenna 1.....	21
Figure 18: Radiated Emissions, BLE Mid Channel, 30 MHz - 1 GHz Antenna 1	22
Figure 19: Radiated Emissions, BLE Mid Channel, 1GHz - 18GHz, Average, Antenna 1	22
Figure 20: Radiated Emissions, BLE Mid Channel, 18GHz - 25GHz, Average, Antenna 1	22
Figure 21: Radiated Emissions, BLE Mid Channel, 1GHz - 18GHz, Peak, Antenna 1	23
Figure 22: Radiated Emissions, BLE Mid Channel, 18GHz - 25GHz, Peak, Antenna 1	23
Figure 23: Radiated Emissions, BLE High Channel, 30 MHz - 1 GHz Antenna 1	23
Figure 24: Radiated Emissions, BLE High Channel, 1GHz - 18GHz, Average, Antenna 1	24
Figure 25: Radiated Emissions, BLE High Channel, 18GHz - 25GHz, Average, Antenna 1	24
Figure 26: Radiated Emissions, BLE High Channel, 1GHz - 18GHz, Peak, Antenna 1.....	24
Figure 27: Radiated Emissions, BLE High Channel, 18GHz - 25GHz, Peak, Antenna 1.....	25
Figure 28: Radiated Emissions, BLE Low Channel, 30 MHz - 1 GHz, Antenna 2.....	25
Figure 29: Radiated Emissions, BLE Low Channel, 1GHz - 6 GHz, Average, Antenna 2.....	25

Figure 30: Radiated Emissions, BLE Low Channel, Average, 7.2 GHz, emission, Antenna 2.....	26
Figure 31: Radiated Emissions, BLE Low Channel 6GHz - 18GHz, Average, Antenna 2.....	26
Figure 32: Radiated Emissions, BLE Low Channel 18GHz - 25GHz, Average, Antenna 2.....	26
Figure 33: Radiated Emissions, BLE Low Channel 1GHz - 6 GHz, Peak, Antenna 2.....	27
Figure 34: Radiated Emissions, BLE Low Channel 6GHz - 18GHz, Peak, Antenna 2.....	27
Figure 35: Radiated Emissions, BLE Low Channel 18GHz - 25GHz, Peak, Antenna 2.....	27
Figure 36: Radiated Emissions, BLE Mid Channel, 30 MHz - 1 GHz Antenna 2	28
Figure 37: Radiated Emissions, BLE Mid Channel, 1GHz - 6 GHz, Average, Antenna 2	28
Figure 38: Radiated Emissions, BLE Mid Channel, 6GHz - 18GHz, Average, Antenna 2	28
Figure 39: Radiated Emissions, BLE Mid Channel, 18GHz - 25GHz, Average, Antenna 2	29
Figure 40: Radiated Emissions, BLE Mid Channel, 1GHz - 6 GHz, Peak, Antenna 2	29
Figure 41: Radiated Emissions, BLE Mid Channel, 6GHz - 18GHz, Peak, Antenna 2	29
Figure 42: Radiated Emissions, BLE Mid Channel, 18GHz - 25GHz, Peak, Antenna 2	30
Figure 43: Radiated Emissions, BLE High Channel, 30 MHz - 1 GHz Antenna 2	30
Figure 44: Radiated Emissions, BLE High Channel, 1GHz - 6 GHz, Average, Antenna 2	30
Figure 45: Radiated Emissions, BLE High Channel, 6GHz - 18GHz, Average, Antenna 2	31
Figure 46: Radiated Emissions, BLE High Channel, 18GHz - 25GHz, Average, Antenna 2	31
Figure 47: Radiated Emissions, BLE High Channel, 1GHz - 6 GHz, Peak, Antenna 2.....	31
Figure 48: Radiated Emissions, BLE High Channel, 6GHz - 18GHz, Peak, Antenna 2.....	32
Figure 49: Radiated Emissions, BLE High Channel, 18GHz - 25GHz, Peak, Antenna 2.....	32
Figure 50: Radiated Emissions, BLE Low Channel, Band Edge, Average, Antenna 1.....	33
Figure 51: Radiated Emissions, BLE Low Channel, Band Edge, Peak, Antenna 1	33
Figure 52: Radiated Emissions, BLE Low Channel, Band Edge, Average, Antenna 2.....	33
Figure 53: Radiated Emissions, BLE Low Channel, Band Edge, Peak, Antenna 2	34
Figure 54: Radiated Emissions, BLE High Channel, Band Edge, Average, Antenna 1	34
Figure 55: Radiated Emissions, BLE High Channel, Band Edge, Peak, Antenna 1.....	34
Figure 56: Radiated Emissions, BLE High Channel, Band Edge, Peak, Antenna 2.....	35
Figure 57: Radiated Emissions, BLE High Channel, Band Edge, Average, Antenna 2.....	35
Figure 64: Conducted Spurious Emissions, BLE Low Channel 30 MHz - 10 GHz.....	37
Figure 65: Conducted Spurious Emissions, BLE Low Channel reference level measurement	37
Figure 66: Conducted Spurious Emissions, BLE Low Channel 10 GHz - 25 GHz	37
Figure 67: Conducted Spurious Emissions, BLE Mid Channel, 30 MHz - 10 GHz	38
Figure 68: Conducted Spurious Emissions, BLE Mid Channel, 10 GHz - 25 GHz	38
Figure 69: Conducted Spurious Emissions, BLE Mid Channel, reference level measurement.....	38
Figure 70: Conducted Spurious Emissions, BLE High Channel, 30 MHz - 10 GHz	39
Figure 71: Conducted Spurious Emissions, BLE High Channel, 10 GHz - 25 GHz.....	39
Figure 72: Conducted Spurious Emissions, BLE High Channel, reference level measurement	39
Figure 73: Conducted Spurious Emissions, BLE Low Channel band edge	40
Figure 74: Conducted Spurious Emissions, BLE High Channel, band edge.....	40
Figure 75: Power Spectral Density, BLE Low Channel.....	42
Figure 76: Power Spectral Density, BLE Mid Channel	42
Figure 77: Power Spectral Density, BLE High Channel	42

List of Terms and Abbreviations

AC	Alternating Current
ACF	Antenna Correction Factor
Cal	Calibration
<i>d</i>	Measurement Distance
dB	Decibels
dBμA	Decibels above one microamp
dBμV	Decibels above one microvolt
dBμA/m	Decibels above one microamp per meter
dBμV/m	Decibels above one microvolt per meter
DC	Direct Current
E	Electric Field
DSL	Digital Subscriber Line
ESD	Electrostatic Discharge
EUT	Equipment Under Test
<i>f</i>	Frequency
FCC	Federal Communications Commission
GRP	Ground Reference Plane
H	Magnetic Field
HCP	Horizontal Coupling Plane
Hz	Hertz
IEC	International Electrotechnical Commission
kHz	kilohertz
kPa	kilopascal
kV	kilovolt
LISN	Line Impedance Stabilization Network
MHz	Megahertz
μH	microhenry
μ	microfarad
μs	microseconds
NEBS	Network Equipment-Building System
PRF	Pulse Repetition Frequency
RF	Radio Frequency
RMS	Root-Mean-Square
TWT	Traveling Wave Tube
V/m	Volts per meter
VCP	Vertical Coupling Plane

I. Executive Summary

A. Purpose of Test

An EMC evaluation was performed to determine compliance of the Lutron Electronics Co., Inc. Ketra RF Module, with the requirements of Part 15, §15.247. All references are to the most current version of Title 47 of the Code of Federal Regulations in effect. In accordance with §2.1033, the following data is presented in support of the Certification of the Ketra RF Module. Lutron Electronics Co., Inc. should retain a copy of this document which should be kept on file for at least two years after the manufacturing of the Ketra RF Module, has been **permanently** discontinued.

B. Executive Summary

The following tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, §15.247, in accordance with Lutron Electronics Co., Inc., purchase order number 5196962. All tests were conducted using measurement procedure ANSI C63.10-2013.

FCC Reference 47 CFR Part 15.247	Description	Compliance
Title 47 of the CFR, Part 15 §15.203	Antenna Requirement	Compliant
Title 47 of the CFR, Part 15 §15.207(a)	Conducted Emission Limits	Compliant
Title 47 of the CFR, Part 15 §15.247(a)(2)	6dB Occupied Bandwidth	Compliant
Title 47 of the CFR, Part 15 §15.247(b)	Peak Power Output	Compliant
Title 47 of the CFR, Part 15 §15.247(c)	Spurious Emissions in Non-restricted Bands	Compliant
Title 47 of the CFR, Part 15 §15.247(d); §15.209; §15.205	Radiated Spurious Emissions Requirements	Compliant
Title 47 of the CFR, Part 15; §15.247(e)	Peak Power Spectral Density	Compliant
Title 47 of the CFR, Part 15 §15.247(i)	Maximum Permissible Exposure (MPE)	Compliant

Table 1. Executive Summary of EMC Part 15.247 Compliance Testing

II. Equipment Configuration

A. Overview

Eurofins MET Labs, Inc. was contracted by Lutron Electronics Co., Inc. to perform testing on the Ketra RF Module, under Lutron Electronics Co., Inc.'s purchase order number 5196962.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the Lutron Electronics Co., Inc., Ketra RF Module.

The results obtained relate only to the item(s) tested.

Model(s) Tested:	Ketra RF Module		
Model(s) Covered:	Ketra RF Module		
EUT Specifications:	Primary Power: 120VAC		
	FCC ID: JPZ0124		
	Type of Modulations:	O-QPSK	
	Equipment Code:	DTS	
	Peak RF Output Power:	19.16 dBm	
	EUT Frequency Ranges:	2402-2480 MHz	
Analysis:	The results obtained relate only to the item(s) tested.		
Environmental Test Conditions:	Temperature: 15-35° C		
	Relative Humidity: 30-60%		
	Barometric Pressure: 860-1060 mbar		
Evaluated by:	Deepak Giri		
Report Date(s):	October 7, 2019		

Table 2. EUT Summary Table

B. References

CFR 47, Part 15, Subpart C	Federal Communication Commission, Code of Federal Regulations, Title 47, Part 15: General Rules and Regulations, Allocation, Assignment, and Use of Radio Frequencies
ANSI C63.4:2014	Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical And Electronic Equipment in the Range of 9 kHz to 40 GHz
ISO/IEC 17025:2017	General Requirements for the Competence of Testing and Calibration Laboratories
ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
KDB 558074 v05r02	Guidance For Performing Compliance Measurements On Digital Transmission Systems (DTS) Operating Under Section 15.247

Table 3. References

C. Test Site

All testing was performed at Eurofins MET Labs, Inc., 914 West Patapsco Avenue, Baltimore, MD 21230. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

Radiated Emissions measurements were performed in a 3 meter semi-anechoic chamber (equivalent to an Open Area Test Site). In accordance with §2.948(a)(3), a complete site description is contained at MET Laboratories.

D. Measurement Uncertainty

Test Method	Typical Expanded Uncertainty	K	Confidence Level
RF Frequencies	±4.52 Hz	2	95%
RF Power Conducted Emissions	±2.32 dB	2	95%
RF Power Conducted Spurious Emissions	±2.25 dB	2	95%
RF Power Radiated Emissions	±3.01 dB	2	95%

Table 4. Uncertainty Calculations Summary

E. Description of Test Sample

The Lutron Electronics Co., Inc. Ketra RF Module, Equipment Under Test (EUT), is a 2.4GHz transceiver module that will be utilized in multiple end products to allow RF communication in those devices. In technological perspective, EUT considered in this report is BLE. EUT can operate with two different antennae – Integral printed Antenna with 0 dBi gain and External printed antenna with -1 dBi gain.



Figure 1. Block Diagram of Test Configuration

F. Equipment Configuration

The EUT was set up as outlined in Figure 1, Block Diagram of Test Setup. All cards, racks, etc., incorporated as part of the EUT is included in the following list.

Ref. ID	Slot #	Name / Description	Model Number	Part Number (White / Light Almond)	Serial Number	Rev. #
A.1		DUT	--	470-4614	--	B
A.2		Daughterboard	--	470-4621	--	A

Table 5. Equipment Configuration

G. Support Equipment

The EUT did not require support equipment for testing or monitoring.

H. Ports and Cabling Information

Ref. ID	Port name on EUT	Cable Description or reason for no cable	Qty	Length as tested (m)	Max Length (m)	Shielded? (Y/N)	Termination Box ID & Port Name
1	UART	2-wire	1	1	1	N	[C] FTDI
2	DC Input	2-wire	1	1	-	N	3.3VDC
3	SMA	SMA coaxial cable	1	1	-	Y	SMA
4	Antenna	N/A – Radiated	1	-	-	-	Antenna

Table 6. Ports and Cabling Information

I. Mode of Operation

The Module will be put into various operating modes (channel, etc.) to exercise simulated normal operating conditions.

Test modes include:

1. Continuous transmission – generates a stream of modulated packets at a selected frequency
2. Constant wave (unused) – generates a single unmodulated tone at a selected frequency

Both test modes will run continuously until power is cycled or “Stop current test mode” command is sent.

Continuous transmission mode was used for testing.

J. Method of Monitoring EUT Operation

1. When the DUT is functional it will send back an “ACK” (acknowledgement) back to the scripting software. There will be measurable RF transmission and a change in the current draw from the device.
2. When the DUT is not functional it will not send an “ACK” (acknowledgement) back to the scripting software and there will be no measurable RF transmission or change in current draw from the device.

K. Modifications

a) Modifications to EUT

No modifications were made to the EUT.

b) Modifications to Test Standard

No modifications were made to the test standard.

L. Disposition of EUT

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to Lutron Electronics Co., Inc. upon completion of testing.

III. Electromagnetic Compatibility Criteria for Intentional Radiators

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.203 Antenna Requirement

Test Requirement:

§ 15.203: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The structure and application of the EUT were analyzed to determine compliance with Section 15.203 of the Rules. Section 15.203 states that the subject device must meet at least one of the following criteria:

- a.) Antenna must be permanently attached to the unit.
- b.) Antenna must use a unique type of connector to attach to the EUT.
- c.) Unit must be professionally installed. Installer shall be responsible for verifying that the correct antenna is employed with the unit.

Results:

The EUT as tested is compliant the criteria of §15.203. The module (transmitter) will be soldered onto a host PCB, through which the external antenna will be connected. This will be a permanently soldered connection which will not be modifiable by the end user

Test Engineer(s):

Deepak Giri

Test Date(s):

August 5, 2019

Antenna	Integral Printed Antenna	External Printed Antenna
Gain dBi	0	-1

Table 7. Antenna List

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.207(a) Conducted Emissions Limits

Test Requirement(s): § 15.207 (a): For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency range (MHz)	§ 15.207(a), Conducted Limit (dB μ V)	
	Quasi-Peak	Average
* 0.15- 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

Table 8. Conducted Limits for Intentional Radiators from FCC Part 15 § 15.207(a)

Test Procedure: The EUT was placed on a 0.8 m-high wooden table inside a screen room. The EUT was situated such that the back of the EUT was 0.4 m from one wall of the vertical ground plane, and the remaining sides of the EUT were no closer than 0.8 m from any other conductive surface. The EUT was powered from a 50 Ω /50 μ H Line Impedance Stabilization Network (LISN). The EMC receiver scanned the frequency range from 150 kHz to 30 MHz. Conducted Emissions measurements were made in accordance with ANSI C63.10-2013 The measurements were performed over the frequency range of 0.15 MHz to 30 MHz using a 50 Ω /50 μ H LISN as the input transducer to an EMC/field intensity meter. For the purpose of this testing, the transmitter was turned on. Scans were performed with the transmitter on.

Test Results: The EUT was compliant with this requirement. EUT was tested using the power supply provided by manufacturer.

Test Engineer(s): Deepak Giri

Test Date(s): August 1, 2019

15.207(a) Conducted Emissions Test Results

Line Under Test:		Phase										
Frequency (MHz)	Uncorrected Meter Reading (dBuV) QP	Cable Loss (dB)	External Attenuation (dB)	Corrected Measurement (dBuV) QP	Limit (dBuV) QP	Margin (dB) QP	Uncorrected Meter Reading (dBuV) Avg.	Cable Loss (dB)	External Attenuation (dB)	Corrected Measurement (dBuV) AVG	Limit (dBuV) AVG	Margin (dB) AVG
0.156	39.21	0	10	49.21	65.67	-16.46	21.47	0	10	31.47	55.67	-24.2
0.187	42.31	0	10	52.31	64.17	-11.86	20.77	0	10	30.77	54.17	-23.4
0.277	38.73	0	10	48.73	60.91	-12.18	17.22	0	10	27.22	50.91	-23.69
0.49	27.47	0	10	37.47	56.17	-18.7	19.62	0	10	29.62	46.17	-16.55
1.12	17.61	0	10	27.61	56	-28.39	9.07	0	10	19.07	46	-26.93
30	18.41	0	10	28.41	60	-31.59	16.22	0	10	26.22	50	-23.78

Table 9. Conducted Emissions, 15.207(a), Phase Line, Test Results




Figure 2: Conducted Emissions, Plot, Phase BLE

15.207(a) Conducted Emissions Test Results

Line Under Test:		Neutral					Uncorrected Meter Reading (dBuV) Avg.	Cable Loss (dB)	External Attenuation (dB)	Corrected Measurement (dBuV) AVG	Limit (dBuV) AVG	Margin (dB) AVG
Frequency (MHz)	Uncorrected Meter Reading (dBuV) QP	Cable Loss (dB)	External Attenuation (dB)	Corrected Measurement (dBuV) QP	Limit (dBuV) QP	Margin (dB) QP						
0.151	45.78	0	10	55.78	65.95	-10.17	29.33	0	10	39.33	55.95	-16.62
0.181	42.31	0	10	52.31	64.44	-12.13	30.03	0	10	40.03	54.44	-14.41
0.226	39.57	0	10	49.57	62.6	-13.03	23.65	0	10	33.65	52.6	-18.95
0.781	28.22	0	10	38.22	56	-17.78	19.73	0	10	29.73	46	-16.27
2.55	19.77	0	10	29.77	56	-26.23	14.42	0	10	24.42	46	-21.58
29.99	17.19	0	10	27.19	60	-32.81	17.11	0	10	27.11	50	-22.89

Table 10. Conducted Emissions, 15.207(a), Neutral Line, Test Results




Figure 3: Conducted Emissions, Plot, Neutral BLE

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(a)(2) 6 dB Bandwidth

Test Requirements: § 15.247(a)(2): Operation under the provisions of this section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

For systems using digital modulation techniques, the EUT may operate in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

Test Procedure: The transmitter was on and transmitting at the highest output power. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using a RBW = 100kHz, VBW = 3*RBW. The 6 dB Bandwidth was measured and recorded. The measurements were performed on the low, mid and high channels according to the DTS bandwidth measurement guidance specified in ANSI C63.10 2013.

Test Results The EUT was compliant with § 15.247 (a)(2).

The 6 dB Bandwidth was determined from the plots on the following pages.

Test Engineer(s): Deepak Giri

Test Date(s): August 5, 2019




Figure 4. Block Diagram, Occupied Bandwidth Test Setup

Occupied Bandwidth Test Results

Occupied Bandwidth			
Carrier Channel	Frequency (MHz)	Measured 6 dB Bandwidth (KHz)	Limit (KHz)
Low	2402	738.5	≥500
Mid	2440	736.8	≥500
High	2480	733.8	≥500

Table 11. 6 dB Occupied Bandwidth, Test Results

6 dB Occupied Bandwidth Test Results




Figure 5: 6 dB Occupied Bandwidth, BLE Low Channel




Figure 6: 6 dB Occupied Bandwidth, 6 dB DTS Bandwidth, BLE Mid Channel




Figure 7: 6 dB Occupied Bandwidth, BLE High Channel

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(b) Peak Power Output

Test Requirements: §15.247(b): The maximum peak output power of the intentional radiator shall not exceed the following:

Digital Transmission Systems (MHz)	Output Limit (Watts)
2400–2483.5	1.000

Table 12. Output Power Requirements from §15.247(b)

§15.247(c): if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Procedure: The EUT was measured at the low, mid and high channels of each band at the maximum power level. Measurements were performed on a conducted setup. Peak conducted power measurement setup was used as specified in ANSI C63.10 2013.

Test Results: The EUT was compliant with the Peak Power Output limits of §15.247(b). No anomalies detected.


Test Engineer(s): Deepak Giri

Test Date(s): August 1, 2019


Duty Cycle

Test Procedure: The EUT was connected to a spectrum analyzer and was ran at the maximum achievable duty cycle for all modes. The duty cycle was measured in accordance with section 11.6 of ANSI C63.10-2013.

Frequency (MHz)	ON Time (ms)	Period (ms)	Duty Cycle (%)	Duty Factor (dB)
2402	1	1	100	0
2402	100	100	100	0



Duty Cycle Plot 1ms Span



Duty Cycle Plot 100ms Span

Peak Power Output Test Results

Peak Conducted Output Power				
Carrier Channel	Frequency (MHz)	Antenna Gain (dBi) Antenna 1	Antenna Gain (dBi) Antenna 2	MeasuredPeak Conducted Power (dBm)
Low	2405	0	-1	18.07
Mid	2440	0	-1	18.57
High	2480	0	-1	19.16

Table 13. Peak Power Output, Test Results

Peak Power Output Test Results




Figure 8: Power Output, BLE Low Channel, Peak Conducted Power




Figure 9: Power Output, BLE Mid Channel, Peak Conducted Power




Figure 10: Power Output, BLE High Channel, Peak Conducted Power

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.209 Radiated Spurious Emissions Requirements and Band Edge

Test Requirements: §15.247(d); §15.205: Emissions outside the frequency band.

§15.205(a): Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090–0.110-----	16.42–16.423	399.9–410	4.5–5.15
¹ 0.495–0.505-----	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905-----	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128-----	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775-----	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775-----	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218-----	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825-----	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225-----	123–138	2200–2300	14.47–14.5
8.291–8.294-----	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366-----	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675-----	156.7–156.9	2655–2900	22.01–23.12
8.41425–8.41475-----	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293-----	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025-----	240–285	3345.8–3358 36.	43–36.5
12.57675–12.57725-----	322–335.4	3600–4400	(²)

Table 14. Restricted Bands of Operation

¹ Until February 1, 1999, this restricted band shall be 0.490 – 0.510 MHz.

² Above 38.6

Test Requirement(s): § 15.209 (a): Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in Table 15.

Frequency (MHz)	§ 15.209(a), Radiated Emission Limits (dBμV) @ 3m
30 - 88	40.00
88 - 216	43.50
216 - 960	46.00
Above 960	54.00

Table 15. Radiated Emissions Limits Calculated from FCC Part 15, § 15.209 (a)

Test Procedures: The transmitter was turned on. EUT was setup in accordance with ANSI C63.10 2013. Measurements were performed of the low, mid and high Channels. The EUT was rotated orthogonally through all three axes, thus plots shown are cumulative. Average measurements were performed as stated in 11.12.1 and 4.1.4.2.3 of ANSI C63.10-2013 without reducing VBW below 1Hz. Emissions were maximized as specified in ANSI C63.10 2013. Plots shown are corrected for antenna correction factor, distance and other in-line factors and compared to a limit specified under 15.209.

Test Results: The EUT was compliant with the Radiated Spurious Emission limits of § 15.247(d) and § 15.209. Emissions close to the limit line were re-evaluated with applicable resolution and detectors and were found compliant.

Test Engineer(s): Deepak Giri

Test Date(s): August 5, 2019

Radiated Spurious Emissions, Test Results




Figure 11: Radiated Emissions, BLE Low Channel, 30 MHz - 1 GHz, Antenna 1




Figure 12: Radiated Emissions, BLE Low Channel, Average, 7.2 GHz emission, Antenna 1




Figure 13: Radiated Emissions, BLE Low Channel, 1GHz - 18GHz, Average, Antenna 1




Figure 14: Radiated Emissions, BLE Low Channel, 18GHz - 25GHz, Average, Antenna 1




Figure 15: Radiated Emissions, BLE Low Channel, 1GHz - 18GHz, Peak, Antenna 1




Figure 16: Radiated Emissions, BLE Low Channel, 18GHz - 25GHz, Peak, Antenna 1




Figure 17: Radiated Emissions, BLE Mid Channel, 30 MHz - 1 GHz Antenna 1




Figure 18: Radiated Emissions, BLE Mid Channel, 1GHz - 18GHz, Average, Antenna 1




Figure 19: Radiated Emissions, BLE Mid Channel, 18GHz - 25GHz, Average, Antenna 1




Figure 20: Radiated Emissions, BLE Mid Channel, 1GHz - 18GHz, Peak, Antenna 1




Figure 21: Radiated Emissions, BLE Mid Channel, 18GHz - 25GHz, Peak, Antenna 1




Figure 22: Radiated Emissions, BLE High Channel, 30 MHz - 1 GHz Antenna 1




Figure 23: Radiated Emissions, BLE High Channel, 1GHz - 18GHz, Average, Antenna 1




Figure 24: Radiated Emissions, BLE High Channel, 18GHz - 25GHz, Average, Antenna 1




Figure 25: Radiated Emissions, BLE High Channel, 1GHz - 18GHz, Peak, Antenna 1




Figure 26: Radiated Emissions, BLE High Channel, 18GHz - 25GHz, Peak, Antenna 1




Figure 27: Radiated Emissions, BLE Low Channel, 30 MHz - 1 GHz, Antenna 2




Figure 28: Radiated Emissions, BLE Low Channel, 1GHz - 6 GHz, Average, Antenna 2




Figure 29: Radiated Emissions, BLE Low Channel, Average, 7.2 GHz, emission, Antenna 2




Figure 30: Radiated Emissions, BLE Low Channel 6GHz - 18GHz, Average, Antenna 2




Figure 31: Radiated Emissions, BLE Low Channel 18GHz - 25GHz, Average, Antenna 2




Figure 32: Radiated Emissions, BLE Low Channel 1GHz - 6 GHz, Peak, Antenna 2




Figure 33: Radiated Emissions, BLE Low Channel 6GHz - 18GHz, Peak, Antenna 2




Figure 34: Radiated Emissions, BLE Low Channel 18GHz - 25GHz, Peak, Antenna 2




Figure 35: Radiated Emissions, BLE Mid Channel, 30 MHz - 1 GHz Antenna 2




Figure 36: Radiated Emissions, BLE Mid Channel, 1GHz - 6 GHz, Average, Antenna 2




Figure 37: Radiated Emissions, BLE Mid Channel, 6GHz - 18GHz, Average, Antenna 2




Figure 38: Radiated Emissions, BLE Mid Channel, 18GHz - 25GHz, Average, Antenna 2




Figure 39: Radiated Emissions, BLE Mid Channel, 1GHz - 6 GHz, Peak, Antenna 2




Figure 40: Radiated Emissions, BLE Mid Channel, 6GHz - 18GHz, Peak, Antenna 2




Figure 41: Radiated Emissions, BLE Mid Channel, 18GHz - 25GHz, Peak, Antenna 2




Figure 42: Radiated Emissions, BLE High Channel, 30 MHz - 1 GHz Antenna 2




Figure 43: Radiated Emissions, BLE High Channel, 1GHz - 6 GHz, Average, Antenna 2




Figure 44: Radiated Emissions, BLE High Channel, 6GHz - 18GHz, Average, Antenna 2




Figure 45: Radiated Emissions, BLE High Channel, 18GHz - 25GHz, Average, Antenna 2




Figure 46: Radiated Emissions, BLE High Channel, 1GHz - 6 GHz, Peak, Antenna 2




Figure 47: Radiated Emissions, BLE High Channel, 6GHz - 18GHz, Peak, Antenna 2




Figure 48: Radiated Emissions, BLE High Channel, 18GHz - 25GHz, Peak, Antenna 2

Radiated Band Edge Measurements

Test Procedures:

The transmitter was turned on. Measurements were performed of the low and high Channels. The EUT was rotated orthogonally through all three axes to obtain cumulative emissions. Plots shown are corrected for antenna correction factor distance and other in-line factors and compared to required limit specified under 15.209.




Figure 49: Radiated Emissions, BLE Low Channel, Band Edge, Average, Antenna 1




Figure 50: Radiated Emissions, BLE Low Channel, Band Edge, Peak, Antenna 1




Figure 51: Radiated Emissions, BLE Low Channel, Band Edge, Average, Antenna 2




Figure 52: Radiated Emissions, BLE Low Channel, Band Edge, Peak, Antenna 2




Figure 53: Radiated Emissions, BLE High Channel, Band Edge, Average, Antenna 1




Figure 54: Radiated Emissions, BLE High Channel, Band Edge, Peak, Antenna 1




Figure 55: Radiated Emissions, BLE High Channel, Band Edge, Peak, Antenna 2




Figure 56: Radiated Emissions, BLE High Channel, Band Edge, Average, Antenna 2

Electromagnetic Compatibility Criteria for Intentional Radiators**§ 15.247(d) Spurious Emissions in Non-restricted Bands**

Test Requirement: **15.247(d)** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Test Procedure: For intentional radiators with a digital device portion which operates below 10 GHz, the spectrum was investigated as per §15.33(a)(1) and §15.33(a)(4); i.e., the lowest RF signal generated or used in the device up to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

. Measurements were taken in conducted setup

Test Results: The EUT was compliant with the Spurious Emission limits of **§15.247(d)**. Emissions observed were below 20dBc.

Test Engineer(s): Deepak Giri

Test Date(s): July 30, 2019

Spurious Emissions in Non-restricted Bands, Test Results




Figure 57: Conducted Spurious Emissions, BLE Low Channel 30 MHz - 10 GHz




Figure 58: Conducted Spurious Emissions, BLE Low Channel reference level measurement




Figure 59: Conducted Spurious Emissions, BLE Low Channel 10 GHz - 25 GHz




Figure 60: Conducted Spurious Emissions, BLE Mid Channel, 30 MHz - 10 GHz




Figure 61: Conducted Spurious Emissions, BLE Mid Channel, 10 GHz - 25 GHz




Figure 62: Conducted Spurious Emissions, BLE Mid Channel, reference level measurement




Figure 63: Conducted Spurious Emissions, BLE High Channel, 30 MHz - 10 GHz




Figure 64: Conducted Spurious Emissions, BLE High Channel, 10 GHz - 25 GHz




Figure 65: Conducted Spurious Emissions, BLE High Channel, reference level measurement




Figure 66: Conducted Spurious Emissions, BLE Low Channel band edge




Figure 67: Conducted Spurious Emissions, BLE High Channel, band edge

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(e) Peak Power Spectral Density

Test Requirements: §15.247(e): For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

Test Procedure: The power level was set to the maximum level. The RBW was set to 3 kHz and a VBW set to 10 kHz. The spectrum analyzer was set to an auto sweep time and a peak detector was used. Measurements were carried out at the low, mid and high channels..

Test Results: The EUT was compliant with the peak power spectral density limits of § 15.247 (e). The peak power spectral density was determined from plots on the following page(s).

Test Engineer: Deepak Giri

Test Date: August 5, 2019

Peak Power Spectral Density Test Results

Power Spectral Density			
Carrier Channel	Frequency (MHz)	Peak Conducted PSD (dBm)	Limit (dBm)
Low	2402	2.39	8
Mid	2440	3.02	8
High	2480	3.57	8

Table 16. Peak Power Spectral Density, Test Results

Peak Power Spectral Density




Figure 68: Power Spectral Density, BLE Low Channel




Figure 69: Power Spectral Density, BLE Mid Channel




Figure 70: Power Spectral Density, BLE High Channel

Electromagnetic Compatibility Criteria for Intentional Radiators

§ 15.247(i) Maximum Permissible Exposure

RF Exposure Requirements: §1.1307(b)(1) and §1.1307(b)(2): Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

RF Radiation Exposure Limit: §1.1310: As specified in this section, the Maximum Permissible Exposure (MPE) Limit shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Sec. 2.1093 of this chapter.

MPE Limit: EUT's operating frequencies @ 2402-2480 MHz; **Limit for Uncontrolled exposure: 1 mW/cm² or 10 W/m²**

$$S = PG / 4\pi R^2 \quad \text{or} \quad R = \sqrt{(PG / 4\pi S)}$$

where, S = Power Density (mW/cm²)
P = Power Input to antenna (mW)
G = Antenna Gain (numeric value)
R = Distance (cm)

Test Results:

FCC									
Frequency (MHz)	Con. Pwr. (dBm)	Con. Pwr. (mW)	Ant. Gain (dBi)	Ant. Gain numeric	Pwr. Density (mW/cm ²)	Limit (mW/cm ²)	Margin	Distance (cm)	Result
2480	19.16	82.414	0	1	0.0164	1	0.9836	20	Pass
2480	19.16	82.414	-1	0.794	0.01302	1	0.98698	20	Pass

The safe distance where Power Density is less than the MPE Limit listed above was found to be 20 cm.

IV. Test Equipment

Test Equipment

Calibrated test equipment utilized during testing was maintained in a current state of calibration per the requirements of ISO/IEC 17025:2005.

Asset	Equipment	Manufacturer	Model	Calibration Date	Calibration Due Date
1T4300	SEMI-ANECHOIC CHAMBER (NSA)	EMC TEST SYSTEMS	NONE	06/30/2019	06/30/2020
1T4409	EMI Receiver	Rohde & Schwarz	ESIB7	01/04/2019	01/04/2021
1T4771	PSA Spectrum Analyzer	Agilent Technologies	E4446A	05/16/2018	11/16/2019
1T4612	Spectrum Analyzer	Agilent Technologies	E4407B	05/15/2018	11/15/2019
1T4744	Antenna, Horn	ETS-Lindgren	3116	11/27/2018	11/27/2019
1T4752	Pre-Amplifier	Miteq	JS44-18004000-35-8P	Func Verify	
1T4817	Preamplifier	A.H. Systems, Inc.	PAM-0118P	Func Verify	
1T4814	Comb Generator	Com-Power	CGO-5100	Func Verify	
1T4149A	HF Wireless Chamber - NSA	Ray Proof	81	06/30/2019	06/30/2020
1T4757	Antenna; Horn	ETS-Lindgren	3117	05/11/2018	11/11/2019

Table 17. Test Equipment List

Note: Functionally tested equipment is verified using calibrated instrumentation at the time of testing.

V. Certification & User's Manual Information

Certification & User's Manual Information

A. Certification Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart I — Marketing of Radio frequency devices:

§ 2.801 Radio-frequency device defined.

As used in this part, a radio-frequency device is any device which in its operation is capable of Emitting radio-frequency energy by radiation, conduction, or other means. Radio- frequency devices include, but are not limited to:

- (a) The various types of radio communication transmitting devices described throughout this chapter.
- (b) *The incidental, unintentional and intentional radiators defined in Part 15 of this chapter.*
- (c) The industrial, scientific, and medical equipment described in Part 18 of this chapter.
- (d) Any part or component thereof which in use emits radio-frequency energy by radiation, conduction, or other means.

§ 2.803 Marketing of radio frequency devices prior to equipment authorization.

- (a) Except as provided elsewhere in this chapter, no person shall sell or lease, or offer for sale or lease (including advertising for sale or lease), or import, ship or distribute for the purpose of selling or leasing or offering for sale or lease, any radio frequency device unless:
 - (1) In the case of a device subject to certification, such device has been authorized by the Commission in accordance with the rules in this chapter and is properly identified and labeled as required by §2.925 and other relevant sections in this chapter; or
 - (2) In the case of a device that is not required to have a grant of equipment authorization issued by the Commission, but which must comply with the specified technical standards prior to use, such device also complies with all applicable administrative (including verification of the equipment or authorization under a Declaration of Conformity, where required), technical, labeling and identification requirements specified in this chapter.
- (d) Notwithstanding the provisions of paragraph (a) of this section, the offer for sale solely to business, commercial, industrial, scientific or medical users (but not an offer for sale to other parties or to end users located in a residential environment) of a radio frequency device that is in the conceptual, developmental, design or pre-production stage is permitted prior to equipment authorization or, for devices not subject to the equipment authorization requirements, prior to a determination of compliance with the applicable technical requirements *provided* that the prospective buyer is advised in writing at the time of the offer for sale that the equipment is subject to the FCC rules and that the equipment will comply with the appropriate rules before delivery to the buyer or to centers of distribution.

- (e)(1) Notwithstanding the provisions of paragraph (a) of this section, prior to equipment authorization or determination of compliance with the applicable technical requirements any radio frequency device may be operated, but not marketed, for the following purposes and under the following conditions:
- (i) *Compliance testing*;
 - (ii) Demonstrations at a trade show provided the notice contained in paragraph (c) of this section is displayed in a conspicuous location on, or immediately adjacent to, the device;
 - (iii) Demonstrations at an exhibition conducted at a business, commercial, industrial, scientific or medical location, but excluding locations in a residential environment, provided the notice contained in paragraphs (c) or (d) of this section, as appropriate, is displayed in a conspicuous location on, or immediately adjacent to, the device;
 - (iv) Evaluation of product performance and determination of customer acceptability, provided such operation takes place at the manufacturer's facilities during developmental, design or pre-production states; or
 - (v) Evaluation of product performance and determination of customer acceptability where customer acceptability of a radio frequency device cannot be determined at the manufacturer's facilities because of size or unique capability of the device, provided the device is operated at a business, commercial, industrial, scientific or medical user's site, but not at a residential site, during the development, design or pre-production stages.
- (e)(2) For the purpose of paragraphs (e)(1)(iv) and (e)(1)(v) of this section, the term *manufacturer's facilities* includes the facilities of the party responsible for compliance with the regulations and the manufacturer's premises, as well as the facilities of other entities working under the authorization of the responsible party in connection with the development and manufacture, but not the marketing, of the equipment.
- (f) For radio frequency devices subject to verification and sold solely to business, commercial, industrial, scientific and medical users (excluding products sold to other parties or for operation in a residential environment), parties responsible for verification of the devices shall have the option of ensuring compliance with the applicable technical specifications of this chapter at each end user's location after installation, provided that the purchase or lease agreement includes a proviso that such a determination of compliance be made and is the responsibility of the party responsible for verification of the equipment.

Certification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart J — Equipment Authorization Procedures:

§ 2.901 Basis and Purpose

- (a) In order to carry out its responsibilities under the Communications Act and the various treaties and international regulations, and in order to promote efficient use of the radio spectrum, the Commission has developed technical standards for radio frequency equipment and parts or components thereof. The technical standards applicable to individual types of equipment are found in that part of the rules governing the service wherein the equipment is to be operated.¹ *In addition to the technical standards provided, the rules governing the service may require that such equipment be verified by the manufacturer or importer, be authorized under a Declaration of Conformity, or receive an equipment authorization from the Commission by one of the following procedures: certification or registration.*
- (b) The following sections describe the verification procedure, the procedure for a Declaration of Conformity, and the procedures to be followed in obtaining certification from the Commission and the conditions attendant to such a grant.

§ 2.907 Certification.

- (a) Certification is an equipment authorization issued by the Commission, based on representation and test data submitted by the applicant.
- (b) Certification attaches to all units subsequently marketed by the grantee which are identical (see Section 2.908) to the sample tested except for permissive changes or other variations authorized by the Commission pursuant to Section 2.1043.

¹ In this case, the equipment is subject to the rules of Part 15. More specifically, the equipment falls under Subpart B (of Part 15), which deals with unintentional radiators.

Certification & User's Manual Information

§ 2.948 Description of measurement facilities.

- (a) Each party making measurements of equipment that is subject to an equipment authorization under Part 15 or Part 18 of this chapter, regardless of whether the measurements are filed with the Commission or kept on file by the party responsible for compliance of equipment marketed within the U.S. or its possessions, shall compile a description of the measurement facilities employed.
 - (1) If the measured equipment is subject to the verification procedure, the description of the measurement facilities shall be retained by the party responsible for verification of the equipment.
 - (i) *If the equipment is verified through measurements performed by an independent laboratory, it is acceptable for the party responsible for verification of the equipment to rely upon the description of the measurement facilities retained by or placed on file with the Commission by that laboratory. In this situation, the party responsible for the verification of the equipment is not required to retain a duplicate copy of the description of the measurement facilities.*
 - (ii) If the equipment is verified based on measurements performed at the installation site of the equipment, no specific site calibration data is required. It is acceptable to retain the description of the measurement facilities at the site at which the measurements were performed.
 - (2) If the equipment is to be authorized by the Commission under the certification procedure, the description of the measurement facilities shall be filed with the Commission's Laboratory in Columbia, Maryland. The data describing the measurement facilities need only be filed once but must be updated as changes are made to the measurement facilities or as otherwise described in this section. At least every three years, the organization responsible for filing the data with the Commission shall certify that the data on file is current.

Certification & User's Manual Information

1. Label and User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart A — General:

§ 15.19 Labeling requirements.

(a) *In addition to the requirements in Part 2 of this chapter, a device subject to certification or verification shall be labeled as follows:*

- (1) Receivers associated with the operation of a licensed radio service, e.g., FM broadcast under Part 73 of this chapter, land mobile operation under Part 90, etc., shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference.

- (2) A stand-alone cable input selector switch, shall bear the following statement in a conspicuous location on the device:

This device is verified to comply with Part 15 of the FCC Rules for use with cable television service.

- (3) All other devices shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

- (4) Where a device is constructed in two or more sections connected by wires and marketed together, the statement specified under paragraph (a) of this section is required to be affixed only to the main control unit.
- (5) When the device is so small or for such use that it is not practicable to place the statement specified under paragraph (a) of this section on it, the information required by this paragraph shall be placed in a prominent location in the instruction manual or pamphlet supplied to the user or, alternatively, shall be placed on the container in which the device is marketed. However, the FCC identifier or the unique identifier, as appropriate, must be displayed on the device.

§ 15.21 Information to user.

The user's manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Verification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart B — Unintentional Radiators:

§ 15.105 Information to the user.

- (a) For a Class A digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at own expense.

- (b) For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a residential environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

End of Report