

TIMCO ENGINEERING INC.

849 NW State Road 45

Newberry, Florida 32669

<http://www.timcoengr.com>

888.472.2424 F 352.472.2030 email: sid@timcoengr.com



Test Report

Product Name: GEOMETRIX WIRELESS LOCATION SENSOR - RECEIVER

FCC ID: JTEWLS2NS

Applicant:

**Andrew Network Solutions Group
140 Vista Centre Dr
Forest, Virginia 24551 USA**

Date Receipt: NOVEMBER 21, 2003

Date Tested: NOVEMBER 25, 2003

APPLICANT: ANDREW NETWORK SOLUTIONS GROUP
FCC ID: JTEWLS2NS
REPORT #: G\GRAYSON_JTE\1562UT3\1562UT3TestReport.doc
TITLE PAGE

TIMCO ENGINEERING INC.

849 NW State Road 45

Newberry, Florida 32669

<http://www.timcoengr.com>

888.472.2424 F 352.472.2030 email: sid@timcoengr.com

TABLE OF CONTENTS LIST

APPLICANT: ANDREW NETWORK SOLUTIONS GROUP

FCC ID: JTEWLS2NS

TEST REPORT CONTAINING:

PAGE 1.....TEST EQUIPMENT LIST
PAGE 2.....TEST PROCEDURES
PAGE 3.....RADIATION INTERFERENCE TEST DATA

EXHIBITS CONTAINING:

EXHIBIT 1.....BLOCK DIAGRAM
EXHIBIT 2.....SCHEMATIC
EXHIBIT 3.....INSTRUCTION MANUAL
EXHIBIT 4.....LABEL SAMPLE
EXHIBIT 5.....LABEL LOCATION
EXHIBIT 6.....EXTERNAL PHOTOGRAPHS
EXHIBIT 7.....INTERNAL PHOTOGRAPHS
EXHIBIT 8.....CIRCUIT DESCRIPTION
EXHIBIT 9.....TEST SET UP PHOTOGRAPH

APPLICANT: ANDREW NETWORK SOLUTIONS GROUP
FCC ID: JTEWLS2NS
REPORT #: G\GRAYSON_JTE\1562UT3\1562UT3TestReport.doc
TABLE OF CONTENTS

TIMCO ENGINEERING INC.

849 NW State Road 45

Newberry, Florida 32669

<http://www.timcoengr.com>

888.472.2424 F 352.472.2030 email: sid@timcoengr.com

Equipment List

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3/10-Meter OATS	TEI	N/A	N/A	Listed 3/26/01	3/26/04
3-Meter OATS	TEI	N/A	N/A	Listed 1/13/03	1/13/06
Biconnical Antenna	Eaton	94455-1	1057	CAL 3/18/03	3/18/05
Biconnical Antenna	Eaton	94455-1	1096	CAL 10/1/01	10/1/03
Biconnical Antenna	Electro- Metrics	BIA-25	1171	CAL 4/26/01	4/26/03
Blue Tower Quasi-Peak Adapter	HP	85650A	2811A01279	CAL 4/15/03	4/15/05
Blue Tower RF Preselector	HP	85685A	2926A00983	CAL 4/15/03	4/15/05
Blue Tower Spectrum Analyzer	HP	8568B	2928A04729 2848A18049	CAL 4/15/03	4/15/05
LISN	Electro- Metrics	ANS-25/2	2604	CAL 10/9/01	10/9/03
LISN	Electro- Metrics	EM-7820	2682	CAL 3/12/03	3/12/05
Log-Periodic Antenna	Eaton	96005	1243	CAL 5/8/03	5/8/05

APPLICANT: ANDREW NETWORK SOLUTIONS GROUP

FCC ID: JTEWLS2NS

REPORT #: G\GRAYSON_JTE\1562UT3\1562UT3TestReport.doc

Page 1 of 3

TIMCO ENGINEERING INC.

849 NW State Road 45
Newberry, Florida 32669
<http://www.timcoengr.com>
888.472.2424 F 352.472.2030 email: sid@timcoengr.com

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHZ and the video bandwidth was 300KHZ. The ambient temperature of the UUT was 72°F with a humidity of 65%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS
33 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. Measurements were taken to the tenth harmonic of the fundamental frequency. The antenna was placed in both the horizontal and vertical planes.

TIMCO ENGINEERING INC.

849 NW State Road 45
Newberry, Florida 32669
<http://www.timcoengr.com>
888.472.2424 F 352.472.2030 email: sid@timcoengr.com

APPLICANT: ANEREW NETWORK SOLUTIONS GROUP

MODEL: JTEWLS2NS

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NUMBER: 15.109

REQUIREMENTS:

30 to 88 MHz:	40.0 dBuV/M @ 3 METERS
88 to 216 MHz:	43.5 dBuV/M
216 to 960 MHz:	46.0 dBuV/M
ABOVE 960 MHz:	54.0 dBuV/M

TEST RESULTS: A search was made of the spectrum from 30 to 1000 MHz and the measurements indicate that the unit DOES meet the FCC requirements.

TEST DATA: Readings were taken at the following fundamental frequencies: 824 MHz, 834 MHz, and 846 MHz. Local Oscillator Radiation was indiscernible. Spurious Radiation data more than 20 dB below the limit are not reported.

Emission Frequency MHz	Meter Reading dBuV	Ant. Polarity	Coax Loss dB	Correction Factor dB	Field Strength dBuV/m	Margin dB
157.32	19.8	V	1.46	17.95	39.21	4.29
157.32	21.2	H	1.46	16.90	39.56	3.94
161.54	17.7	H	1.49	16.78	35.97	7.53
161.54	24.1	V	1.49	17.88	43.47	0.03
196.64	21.2	H	1.77	16.26	39.23	4.27
196.64	23.3	V	1.77	17.09	42.16	1.34
200.06	16.9	H	1.80	12.00	30.70	12.80
200.06	23.8	V	1.80	12.10	37.70	5.80
235.95	18.1	V	1.94	11.70	31.74	14.26
235.95	24.6	H	1.94	12.10	38.64	7.36
240.09	12.4	V	1.96	11.91	26.27	19.73
240.09	14.0	H	1.96	12.30	28.26	17.74
314.58	20.2	V	2.29	15.96	38.45	7.55
314.58	20.3	H	2.29	16.42	39.01	6.99
353.92	25.3	V	2.52	14.82	42.64	3.36
353.92	26.9	H	2.52	15.62	45.04	0.96
600.04	14.2	V	3.40	19.00	36.60	9.40
600.04	15.2	H	3.40	19.70	38.30	7.70
658.64	12.9	V	3.58	20.73	37.21	8.79
658.64	13.1	H	3.58	21.01	37.69	8.31
733.34	10.7	H	3.80	21.80	36.30	9.70
733.34	12.8	V	3.80	21.13	37.73	8.27

SAMPLE CALCULATION: FSdBuV/m = MR(dBuV) + ACFdB.

TEST PROCEDURE: ANSI STANDARD C63.4-1992 using a Hewlett Packard Model 8566B spectrum analyzer, a Hewlett Packard Model 85685A Pre-selector, a Hewlett Packard Model 85650A Quasi-Peak adapter, and an appropriate antenna - see the test equipment list. The bandwidth of spectrum analyzer was 100 kHz with an appropriate sweep speed. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported.

PERFORMED BY: JOSEPH SCOGLIO

DATE: NOVEMBER 25, 2003

APPLICANT: ANDREW NETWORK SOLUTIONS GROUP

FCC ID: JTEWLS2NS

REPORT #: G\GRAYSON_JTE\1562UT3\1562UT3TestReport.doc

Page 3 of 3