


FCC Test Report

FCC ID : JVPU2-EW-D
Equipment : Mouse for e-Sports
Model No. : U2-EW-D
Brand Name : ZOWIE
Applicant : BENQ CORPORATION
Address : 16 Jihu Road, Neihu, Taipei 114, Taiwan
Standard : 47 CFR FCC Part 15.247
Received Date : May 22, 2026
Tested Date : Jun. 02 ~ Jun. 05, 2026

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:


Along Chen / Manager

Approved by:



Gary Chang / Manager

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	9
1.5	Test Standards	10
1.6	Reference Guidance	10
1.7	Deviation from Test Standard and Measurement Procedure.....	10
1.8	Measurement Uncertainty	10
2	TEST CONFIGURATION.....	11
2.1	Testing Facility	11
2.2	The Worst Test Modes and Channel Details	11
3	TRANSMITTER TEST RESULTS	12
3.1	6dB and Occupied Bandwidth.....	12
3.2	Conducted Output Power	13
3.3	Power Spectral Density	14
3.4	Unwanted Emissions into Restricted Frequency Bands	15
3.5	Emissions in Non-Restricted Frequency Bands.....	17
3.6	AC Power Line Conducted Emissions	18
4	TEST LABORATORY INFORMATION	19

Appendix A. 6dB and Occupied Bandwidth

Appendix B. Conducted Output Power

Appendix C. Power Spectral Density

Appendix D. Unwanted Emissions into Restricted Frequency Bands

Appendix E. Emissions in Non-Restricted Frequency Bands

Appendix F. AC Power Line Conducted Emissions

Release Record

Report No.	Version	Description	Issued Date
FR652206	Rev. 01	Initial issue	Jul. 06, 2026

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emission	[dBuV]: 0.403MHz 39.56 (Margin -8.23dB) - AV	Pass
15.247(d) 15.209	Unwanted Emissions	[dBuV/m at 3m]: 242.43MHz 42.52(Margin -3.48dB) - PK	Pass
15.247(b)(3)	Conducted Output Power	Max Power [dBm]: 4.34	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Modulation	Ch. Freq. (MHz)	Channel Number	Data Rate
2400-2483.5	GFSK	2405-2478	1-74 [74]	4Mbps

1.1.2 Antenna Details

Brand	Model	Type	Connector	Gain (dBi)
BENQ Corporation	U2-EW ANT	insert molding metal antenna	NA	2.73

1.1.3 Configuration of Equipment under Test (EUT)

Power Supply Type	3.87V from battery 5Vdc from host
-------------------	--------------------------------------

1.1.4 Accessories

Accessories		
No.	Equipment	Description
1	Battery	Brand: Future Power Model: FT452030P Rating: 310mAh, 3.87 V
2	USB cable	Brand: YUE-YANG ELECTRONIC FACTORY Model: USB TYPE A TO TYPE C 1.8m, shielded, w/o core

1.1.5 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2405	21	2425	41	2445	61	2465
2	2406	22	2426	42	2446	62	2466
3	2407	23	2427	43	2447	63	2467
4	2408	24	2428	44	2448	64	2468
5	2409	25	2429	45	2449	65	2469
6	2410	26	2430	46	2450	66	2470
7	2411	27	2431	47	2451	67	2471
8	2412	28	2432	48	2452	68	2472
9	2413	29	2433	49	2453	69	2473
10	2414	30	2434	50	2454	70	2474
11	2415	31	2435	51	2455	71	2475
12	2416	32	2436	52	2456	72	2476
13	2417	33	2437	53	2457	73	2477
14	2418	34	2438	54	2458	74	2478
15	2419	35	2439	55	2459	---	---
16	2420	36	2440	56	2460	---	---
17	2421	37	2441	57	2461	---	---
18	2422	38	2442	58	2462	---	---
19	2423	39	2443	59	2463	---	---
20	2424	40	2444	60	2464	---	---

1.1.6 Test Tool and Duty Cycle

Test Tool	radio_test_ew		
Duty Cycle and Duty Factor	Mode	Duty Cycle (%)	Duty Factor (dB)
	GFSK	100.00%	0


1.1.7 Power Index of Test Tool

Modulation Mode	Test Frequency (MHz)	Power Index
GFSK	2405	+4
GFSK	2441	+4
GFSK	2478	+4


1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Remarks
1	Laptop	DELL	Latitude 5440	DoC	---
2	Enhanced Wireless Receiver	ZOWIE	ER3-80-D	---	Provided by applicant.

1.3 Test Setup Chart



Test Setup Diagram (Charging Mode)



No.

Signal cable / Length (m)

1

USB, 1.8m shielded.

1.4 The Equipment List

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Tested Date	Jun. 02 ~ Jun. 05, 2026				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101657	Apr. 02, 2026	Apr. 01, 2027
Spectrum Analyzer	R&S	FSV40	101498	Nov. 06, 2025	Nov. 05, 2026
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 17, 2025	Nov. 16, 2026
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Sep. 05, 2025	Sep. 04, 2026
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 19, 2025	Dec. 18, 2026
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 28, 2025	Nov. 27, 2026
Preamplifier	EMC	EMC02325	980225	Jun. 13, 2025	Jun. 12, 2026
Preamplifier	EMC	EMC118A45SE	980898	Jun. 24, 2025	Jun. 23, 2026
Preamplifier	EMC	EMC184045SE	980903	Aug. 08, 2025	Aug. 07, 2026
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 01, 2025	Sep. 30, 2026
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 01, 2025	Sep. 30, 2026
LF cable 11M	EMC	EMCCFD400-NW-N W-11000	200801	Oct. 01, 2025	Sep. 30, 2026
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	160502	Oct. 01, 2025	Sep. 30, 2026
RF Cable	EMC	EMC104-35M-35M- 8000	210920	Oct. 01, 2025	Sep. 30, 2026
RF Cable	EMC	EMC104-35M-35M- 3000	210922	Oct. 01, 2025	Sep. 30, 2026
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Oct. 01, 2025	Sep. 30, 2026
Attenuator	Pasternack	PE7005-10	10-1	Oct. 01, 2025	Sep. 30, 2026
HIGHPASS FILTER 3.1-18G	WHK	WHK3.1/18G-10SS	39	Oct. 01, 2025	Sep. 30, 2026
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Jun. 05, 2026				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101910	Apr. 28, 2026	Apr. 27, 2027
Power Meter	Anritsu	ML2495A	1241002	Nov. 21, 2025	Nov. 20, 2026
Power Sensor	Anritsu	MA2411B	1207366	Nov. 21, 2025	Nov. 20, 2026
Attenuator	Pasternack	PE7005-10	10-2	Oct. 03, 2025	Oct. 02, 2026
Measurement Software	Sporton	SENSE-15247_FS	V5.11	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Tested Date	Jun. 02, 2026				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101659	Apr. 29, 2026	Apr. 28, 2027
LISN	R&S	ENV216	101579	May. 18, 2026	May. 17, 2027
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Apr. 12, 2026	Apr. 11, 2027
RF Cable-CON	EMC	EMCCFD300-BM-B M-6000	50821	Oct. 07, 2025	Oct. 06, 2026
50 ohm terminal	NA	50	01	Jun. 17, 2025	Jun. 16, 2026
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

47 CFR FCC Part 15.247

ANSI C63.10-2020 + Cor.1-2023

ANSI C63.4-2014 + C63.4a-2017

1.6 Reference Guidance

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

1.7 Deviation from Test Standard and Measurement Procedure

None

1.8 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$)).

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.130 Hz
Conducted power	± 0.808 dB
Power density	± 0.583 dB
Conducted emission	± 2.715 dB
AC conducted emission	± 2.92 dB
Unwanted Emission ≤ 1 GHz	± 3.41 dB
Unwanted Emission > 1 GHz	± 4.59 dB

2 Test Configuration

2.1 Testing Facility

Test Laboratory	International Certification Corporation
Test Site	CO01-WS, 03CH01-WS, TH01-WS
Address of Test Site	No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 33381, Taiwan (R.O.C.)

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- ISED#: 10807A
- CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate	Test Configuration
AC Power Line Conducted Emission	GFSK	2478	4 Mbps	1
	Charging	-	-	2
Unwanted Emissions ≤ 1GHz	GFSK	2478	4 Mbps	1
	Charging	-	-	2
Conducted Output Power Unwanted Emissions >1GHz 6dB bandwidth Power spectral density	GFSK	2405 / 2441 / 2478	4 Mbps	1
NOTE: 1. The test configurations are listed as follows: 1) Mode 1: Battery mode 2) Mode 2: Charging mode *Comparing charging mode with the laptop or with the power adapter, pretest test results of charging with the laptop was the worst. Therefore, this mode was selected for final test.				

3 Transmitter Test Results

3.1 6dB and Occupied Bandwidth

3.1.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.1.2 Test Procedures


6dB Bandwidth

1. Set resolution bandwidth (RBW) = 1% ~ 5 % of OBW, Video bandwidth = 3 x RBW
2. Detector = Peak, Trace mode = max hold.
3. Sweep = No faster than coupled (auto) time, Allow the trace to stabilize.
4. Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value

Occupied Bandwidth

1. Set resolution bandwidth (RBW) = 1% ~ 5 % of OBW, Video bandwidth = 3 x RBW
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.1.3 Test Setup



3.1.4 Test Results

Ambient Condition	26°C / 67%	Tested By	Roger Lu
-------------------	------------	-----------	----------

Refer to Appendix A.

3.2 Conducted Output Power

3.2.1 Limit of Conducted Output Power

Conducted power shall not exceed 1Watt.

Antenna gain $\leq 6\text{dBi}$, no any corresponding reduction is in output power limit.

3.2.2 Test Procedures

A broadband RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.2.3 Test Setup



3.2.4 Test Results

Ambient Condition	26°C / 67%	Tested By	Roger Lu
-------------------	------------	-----------	----------

Refer to Appendix B.

3.3 Power Spectral Density

3.3.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.3.2 Test Procedures

Peak PSD

1. Set the RBW = 3 kHz, VBW = 10 kHz.
2. Detector = Peak, Sweep time = auto couple.
3. Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.


Average PSD, duty cycle $\geq 98\%$

1. Set the RBW = 3 kHz, VBW = 10 kHz.
2. Detector = RMS, Sweep time = auto couple.
3. Sweep time = auto couple.
4. Employ trace averaging (RMS) mode over a minimum of 100 traces.
5. Use the peak marker function to determine the maximum amplitude level.

Average PSD, duty cycle $< 98\%$

1. Set the RBW = 3 kHz, VBW = 10 kHz
2. Detector = RMS, Sweep time = auto couple.
3. Sweep time = auto couple.
4. Employ trace averaging (RMS) mode over a minimum of 100 traces.
5. Use the peak marker function to determine the maximum amplitude level.
6. Add $10 \log (1/x)$, where x is the duty cycle.

3.3.3 Test Setup



3.3.4 Test Results

Ambient Condition	26°C / 67%	Tested By	Roger Lu
-------------------	------------	-----------	----------

Refer to Appendix C.

3.4 Unwanted Emissions into Restricted Frequency Bands

3.4.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.4.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.4.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



3.4.4 Test Results

Refer to Appendix D.

3.5 Emissions in Non-Restricted Frequency Bands

3.5.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.5.2 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.5.3 Test Setup



3.5.4 Test Results

Ambient Condition	26°C / 67%	Tested By	Roger Lu
-------------------	------------	-----------	----------

Refer to Appendix E.

3.6 AC Power Line Conducted Emissions

3.6.1 Limit of AC Power Line Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.6.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V / 60Hz.

3.6.3 Test Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.6.4 Test Results

Refer to Appendix F.

4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <https://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No.30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan
(R.O.C.)

Kwei Shan

Tel: 886-3-271-8666

No.3-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)
No.2-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

Kwei Shan Site II

Tel: 886-3-271-8640

No.14-1, Lane 19, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

Zhonghe

Tel: 886-2-2222-0288

1F, No. 6, Jiankang Road, Zhonghe
District, New Taipei City 235045,
Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0345

Email: ICC_Service@icertifi.com.tw

==END==

**Summary**

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
SRD	1.513M	4.223M	4M22F1D	881.25k	4.173M

Max-N dB = Maximum 6dB down bandwidth; Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth; Min-OBW = Minimum 99% occupied bandwidth

Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
SRD	-	-	-	-
2405MHz	Pass	500k	881.25k	4.173M
2441MHz	Pass	500k	1.106M	4.179M
2478MHz	Pass	500k	1.513M	4.223M



Port X-N dB = Port X 6dB down bandwidth;
Port X-OBW = Port X 99% occupied bandwidth



2.4-2.4835GHz_SRD

EBW-DTS



2405MHz



2.4-2.4835GHz_SRD

EBW-DTS

2441MHz







2.4-2.4835GHz_SRD

EBW-DTS

2478MHz





Conducted Output Power (Peak)

Appendix B

Summary

Mode	Total Power (dBm)	Total Power (W)
2.4-2.4835GHz	-	-
SRD	4.34	0.00272

Result

Mode	Result	Antenna Gain (dBi)	Total Power (dBm)	Power Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)
SRD	-	-	-	-	-	-
2405MHz	Pass	2.73	4.16	30.00	6.89	36.00
2441MHz	Pass	2.73	4.26	30.00	6.99	36.00
2478MHz	Pass	2.73	4.34	30.00	7.07	36.00



Conducted Output Power (Average)

Appendix B

Summary

Mode	Total Power (dBm)	Total Power (W)
2.4-2.4835GHz	-	-
SRD	4.16	0.00261

Result

Mode	Result	Antenna Gain (dBi)	Total Power (dBm)	Power Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)
SRD	-	-	-	-	-	-
2405MHz	Pass	2.73	3.99	-	6.72	-
2441MHz	Pass	2.73	4.09	-	6.82	-
2478MHz	Pass	2.73	4.16	-	6.89	-

Note: Average power is for reference only.

**Summary**

Mode	PD (dBm/3kHz)
2.4-2.4835GHz	-
SRD	-13.06

Result


Mode	Result	Antenna Gain (dBi)	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)
SRD	-	-	-	-
2405MHz	Pass	2.73	-13.59	8.00
2441MHz	Pass	2.73	-13.06	8.00
2478MHz	Pass	2.73	-14.21	8.00



2.4-2.4835GHz_SRD

PSD


2405MHz



2.4-2.4835GHz_SRD

PSD

2441MHz






2.4-2.4835GHz_SRD

PSD

2478MHz





Mode 1: Battery mode

Unwanted Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2405																																																															
Polarization	Horizontal																																																																	
Test By :Akun Chung_ Temperature(°C):25 Humidity(%):63																																																																		
Level (dBuV/m) Frequency (MHz) <table><tr><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>58.13</td><td>21.57</td><td>40.00</td><td>-18.43</td><td>30.40</td><td>-8.83</td><td>Peak</td><td>---</td></tr><tr><td>2</td><td>148.34</td><td>21.89</td><td>43.50</td><td>-21.61</td><td>30.71</td><td>-8.82</td><td>Peak</td><td>---</td></tr><tr><td>3</td><td>275.41</td><td>22.01</td><td>46.00</td><td>-23.99</td><td>30.68</td><td>-8.67</td><td>Peak</td><td>---</td></tr><tr><td>4</td><td>337.49</td><td>24.04</td><td>46.00</td><td>-21.96</td><td>31.03</td><td>-6.99</td><td>Peak</td><td>---</td></tr><tr><td>5</td><td>439.34</td><td>28.11</td><td>46.00</td><td>-17.89</td><td>32.14</td><td>-4.03</td><td>Peak</td><td>---</td></tr><tr><td>6</td><td>516.94</td><td>27.97</td><td>46.00</td><td>-18.03</td><td>30.26</td><td>-2.29</td><td>Peak</td><td>---</td></tr></table>				Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	58.13	21.57	40.00	-18.43	30.40	-8.83	Peak	---	2	148.34	21.89	43.50	-21.61	30.71	-8.82	Peak	---	3	275.41	22.01	46.00	-23.99	30.68	-8.67	Peak	---	4	337.49	24.04	46.00	-21.96	31.03	-6.99	Peak	---	5	439.34	28.11	46.00	-17.89	32.14	-4.03	Peak	---	6	516.94	27.97	46.00	-18.03	30.26	-2.29	Peak	---
Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg																																																										
1	58.13	21.57	40.00	-18.43	30.40	-8.83	Peak	---																																																										
2	148.34	21.89	43.50	-21.61	30.71	-8.82	Peak	---																																																										
3	275.41	22.01	46.00	-23.99	30.68	-8.67	Peak	---																																																										
4	337.49	24.04	46.00	-21.96	31.03	-6.99	Peak	---																																																										
5	439.34	28.11	46.00	-17.89	32.14	-4.03	Peak	---																																																										
6	516.94	27.97	46.00	-18.03	30.26	-2.29	Peak	---																																																										
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m). Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.																																																																		




Modulation	GFSK	Test Freq. (MHz)	2405																																																																						
Polarization	Vertical																																																																								
Test By :Akun Chung_ Temperature(°C):25 Humidity(%):63																																																																									
Level (dBuV/m) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>51.34</td><td>23.24</td><td>40.00</td><td>-16.76</td><td>31.42</td><td>-8.18</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>2</td><td>148.34</td><td>24.57</td><td>43.50</td><td>-18.93</td><td>33.39</td><td>-8.82</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>264.74</td><td>21.61</td><td>46.00</td><td>-24.39</td><td>30.94</td><td>-9.33</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>4</td><td>310.33</td><td>23.96</td><td>46.00</td><td>-22.04</td><td>31.57</td><td>-7.61</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>382.11</td><td>24.77</td><td>46.00</td><td>-21.23</td><td>30.39</td><td>-5.62</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>6</td><td>439.34</td><td>31.40</td><td>46.00</td><td>-14.60</td><td>35.43</td><td>-4.03</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	51.34	23.24	40.00	-16.76	31.42	-8.18	Peak	---	---	2	148.34	24.57	43.50	-18.93	33.39	-8.82	Peak	---	---	3	264.74	21.61	46.00	-24.39	30.94	-9.33	Peak	---	---	4	310.33	23.96	46.00	-22.04	31.57	-7.61	Peak	---	---	5	382.11	24.77	46.00	-21.23	30.39	-5.62	Peak	---	---	6	439.34	31.40	46.00	-14.60	35.43	-4.03	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg																																																																
1	51.34	23.24	40.00	-16.76	31.42	-8.18	Peak	---	---																																																																
2	148.34	24.57	43.50	-18.93	33.39	-8.82	Peak	---	---																																																																
3	264.74	21.61	46.00	-24.39	30.94	-9.33	Peak	---	---																																																																
4	310.33	23.96	46.00	-22.04	31.57	-7.61	Peak	---	---																																																																
5	382.11	24.77	46.00	-21.23	30.39	-5.62	Peak	---	---																																																																
6	439.34	31.40	46.00	-14.60	35.43	-4.03	Peak	---	---																																																																
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m). Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.																																																																									



Unwanted Emissions (Above 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2405
Polarization	Horizontal-Peak		
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66			
Level (dBUV/m)			



Modulation	GFSK	Test Freq. (MHz)	2405																														
Polarization	Horizontal-Average																																
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66																																	
Level (dBuV/m)  <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>4810.00</td><td>41.89</td><td>54.00</td><td>-12.11</td><td>40.87</td><td>1.02</td><td>Average</td><td>129</td><td>76</td></tr><tr><td>2</td><td>12025.00</td><td>47.18</td><td>54.00</td><td>-6.82</td><td>38.54</td><td>8.64</td><td>Average</td><td>231</td><td>359</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	4810.00	41.89	54.00	-12.11	40.87	1.02	Average	129	76	2	12025.00	47.18	54.00	-6.82	38.54	8.64	Average	231	359
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg																								
1	4810.00	41.89	54.00	-12.11	40.87	1.02	Average	129	76																								
2	12025.00	47.18	54.00	-6.82	38.54	8.64	Average	231	359																								
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																	



Modulation	GFSK	Test Freq. (MHz)	2405																														
Polarization	Vertical-Peak																																
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66																																	
Level (dBUV/m) Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBUV/m</th><th>Limit dBUV/m</th><th>Margin dB</th><th>SA reading dBUV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>4810.00</td><td>45.89</td><td>74.00</td><td>-28.11</td><td>44.87</td><td>1.02</td><td>Peak</td><td>290</td><td>142</td></tr><tr><td>2</td><td>12025.00</td><td>59.06</td><td>74.00</td><td>-14.94</td><td>50.42</td><td>8.64</td><td>Peak</td><td>232</td><td>115</td></tr></tbody></table> Note 1: Emission Level (dBUV/m) = SA Reading (dBUV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).					Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	4810.00	45.89	74.00	-28.11	44.87	1.02	Peak	290	142	2	12025.00	59.06	74.00	-14.94	50.42	8.64	Peak	232	115
	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg																								
1	4810.00	45.89	74.00	-28.11	44.87	1.02	Peak	290	142																								
2	12025.00	59.06	74.00	-14.94	50.42	8.64	Peak	232	115																								



Modulation	GFSK		Test Freq. (MHz)		2405				
Polarization	Vertical-Average								
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66									
Level (dBuV/m) Frequency (MHz)									
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn
	MHz	level			reading			High	Table
		dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg
1	4810.00	34.77	54.00	-19.23	33.75	1.02	Average	290	142
2	12025.00	46.69	54.00	-7.31	38.05	8.64	Average	232	115

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Horizontal		
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66			
Level (dBuV/m)			



Modulation	GFSK	Test Freq. (MHz)	2441																																																																						
Polarization	Vertical																																																																								
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66																																																																									
<table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>4882.00</td><td>37.16</td><td>54.00</td><td>-16.84</td><td>36.12</td><td>1.04</td><td>Average</td><td>310</td><td>111</td></tr><tr><td>2</td><td>4882.00</td><td>48.13</td><td>74.00</td><td>-25.87</td><td>47.09</td><td>1.04</td><td>Peak</td><td>310</td><td>111</td></tr><tr><td>3</td><td>7323.00</td><td>36.79</td><td>54.00</td><td>-17.21</td><td>29.96</td><td>6.83</td><td>Average</td><td>311</td><td>81</td></tr><tr><td>4</td><td>7323.00</td><td>49.38</td><td>74.00</td><td>-24.62</td><td>42.55</td><td>6.83</td><td>Peak</td><td>311</td><td>81</td></tr><tr><td>5</td><td>12205.00</td><td>44.46</td><td>54.00</td><td>-9.54</td><td>35.63</td><td>8.83</td><td>Average</td><td>220</td><td>110</td></tr><tr><td>6</td><td>12205.00</td><td>57.83</td><td>74.00</td><td>-16.17</td><td>49.00</td><td>8.83</td><td>Peak</td><td>220</td><td>110</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	4882.00	37.16	54.00	-16.84	36.12	1.04	Average	310	111	2	4882.00	48.13	74.00	-25.87	47.09	1.04	Peak	310	111	3	7323.00	36.79	54.00	-17.21	29.96	6.83	Average	311	81	4	7323.00	49.38	74.00	-24.62	42.55	6.83	Peak	311	81	5	12205.00	44.46	54.00	-9.54	35.63	8.83	Average	220	110	6	12205.00	57.83	74.00	-16.17	49.00	8.83	Peak	220	110
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg																																																																
1	4882.00	37.16	54.00	-16.84	36.12	1.04	Average	310	111																																																																
2	4882.00	48.13	74.00	-25.87	47.09	1.04	Peak	310	111																																																																
3	7323.00	36.79	54.00	-17.21	29.96	6.83	Average	311	81																																																																
4	7323.00	49.38	74.00	-24.62	42.55	6.83	Peak	311	81																																																																
5	12205.00	44.46	54.00	-9.54	35.63	8.83	Average	220	110																																																																
6	12205.00	57.83	74.00	-16.17	49.00	8.83	Peak	220	110																																																																
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																																									



Modulation	GFSK	Test Freq. (MHz)	2478
Polarization	Horizontal		
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66			
Level (dBuV/m)			



Modulation	GFSK	Test Freq. (MHz)	2478
Polarization	Vertical		
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66			
Level (dBuV/m) </			



Mode 2: Charging mode


Unwanted Emissions (Below 1GHz)

Modulation	Charging																																																																														
Polarization	Horizontal																																																																														
Test By :Tim Chan Temperature(°C):23 Humidity(%):63																																																																															
Level (dBuV/m) Frequency (MHz) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>45.52</td><td>23.29</td><td>40.00</td><td>-16.71</td><td>31.46</td><td>-8.17</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>2</td><td>115.36</td><td>29.90</td><td>43.50</td><td>-13.60</td><td>41.10</td><td>-11.20</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>128.94</td><td>28.82</td><td>43.50</td><td>-14.68</td><td>38.83</td><td>-10.01</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>4</td><td>242.43</td><td>42.52</td><td>46.00</td><td>-3.48</td><td>52.47</td><td>-9.95</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>289.96</td><td>25.86</td><td>46.00</td><td>-20.14</td><td>33.81</td><td>-7.95</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>6</td><td>425.76</td><td>27.63</td><td>46.00</td><td>-18.37</td><td>31.89</td><td>-4.26</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	45.52	23.29	40.00	-16.71	31.46	-8.17	Peak	---	---	2	115.36	29.90	43.50	-13.60	41.10	-11.20	Peak	---	---	3	128.94	28.82	43.50	-14.68	38.83	-10.01	Peak	---	---	4	242.43	42.52	46.00	-3.48	52.47	-9.95	Peak	---	---	5	289.96	25.86	46.00	-20.14	33.81	-7.95	Peak	---	---	6	425.76	27.63	46.00	-18.37	31.89	-4.26	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg																																																																						
1	45.52	23.29	40.00	-16.71	31.46	-8.17	Peak	---	---																																																																						
2	115.36	29.90	43.50	-13.60	41.10	-11.20	Peak	---	---																																																																						
3	128.94	28.82	43.50	-14.68	38.83	-10.01	Peak	---	---																																																																						
4	242.43	42.52	46.00	-3.48	52.47	-9.95	Peak	---	---																																																																						
5	289.96	25.86	46.00	-20.14	33.81	-7.95	Peak	---	---																																																																						
6	425.76	27.63	46.00	-18.37	31.89	-4.26	Peak	---	---																																																																						
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m). Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.																																																																															



Modulation	Charging																																																																																																		
Polarization	Vertical																																																																																																		
Test By :Tim Chan Temperature(°C):23 Humidity(%):63																																																																																																			
Level (dBuV/m) Frequency (MHz) <table><thead><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th>dBuV/m</th><th>dB</th><th>reading</th><th>dB/m</th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th></th><th></th><th>dBuV</th><th></th><th></th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>45.52</td><td>25.57</td><td>40.00</td><td>-14.43</td><td>33.74</td><td>-8.17</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>2</td><td>113.42</td><td>29.86</td><td>43.50</td><td>-13.64</td><td>41.15</td><td>-11.29</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>127.00</td><td>29.03</td><td>43.50</td><td>-14.47</td><td>39.24</td><td>-10.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>4</td><td>242.43</td><td>36.74</td><td>46.00</td><td>-9.26</td><td>46.69</td><td>-9.95</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>425.76</td><td>29.79</td><td>46.00</td><td>-16.21</td><td>34.05</td><td>-4.26</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>6</td><td>439.34</td><td>29.65</td><td>46.00</td><td>-16.35</td><td>33.39</td><td>-3.74</td><td>Peak</td><td>---</td><td>---</td></tr></tbody></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level	dBuV/m	dB	reading	dB/m		High	Table			dBuV/m			dBuV			cm	deg	1	45.52	25.57	40.00	-14.43	33.74	-8.17	Peak	---	---	2	113.42	29.86	43.50	-13.64	41.15	-11.29	Peak	---	---	3	127.00	29.03	43.50	-14.47	39.24	-10.21	Peak	---	---	4	242.43	36.74	46.00	-9.26	46.69	-9.95	Peak	---	---	5	425.76	29.79	46.00	-16.21	34.05	-4.26	Peak	---	---	6	439.34	29.65	46.00	-16.35	33.39	-3.74	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																										
	MHz	level	dBuV/m	dB	reading	dB/m		High	Table																																																																																										
		dBuV/m			dBuV			cm	deg																																																																																										
1	45.52	25.57	40.00	-14.43	33.74	-8.17	Peak	---	---																																																																																										
2	113.42	29.86	43.50	-13.64	41.15	-11.29	Peak	---	---																																																																																										
3	127.00	29.03	43.50	-14.47	39.24	-10.21	Peak	---	---																																																																																										
4	242.43	36.74	46.00	-9.26	46.69	-9.95	Peak	---	---																																																																																										
5	425.76	29.79	46.00	-16.21	34.05	-4.26	Peak	---	---																																																																																										
6	439.34	29.65	46.00	-16.35	33.39	-3.74	Peak	---	---																																																																																										
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m). Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.																																																																																																			



Modulation	GFSK	Test Freq. (MHz)	2405																														
Polarization	Horizontal-Peak																																
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66																																	
Level (dBUV/m)  Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBUV/m</th><th>Limit dBUV/m</th><th>Margin dB</th><th>SA reading dBUV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>2364.50</td><td>52.16</td><td>74.00</td><td>-21.84</td><td>55.46</td><td>-3.30</td><td>Peak</td><td>183</td><td>181</td></tr><tr><td>2</td><td>2488.75</td><td>51.63</td><td>74.00</td><td>-22.37</td><td>55.12</td><td>-3.49</td><td>Peak</td><td>183</td><td>181</td></tr></tbody></table>					Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	2364.50	52.16	74.00	-21.84	55.46	-3.30	Peak	183	181	2	2488.75	51.63	74.00	-22.37	55.12	-3.49	Peak	183	181
	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg																								
1	2364.50	52.16	74.00	-21.84	55.46	-3.30	Peak	183	181																								
2	2488.75	51.63	74.00	-22.37	55.12	-3.49	Peak	183	181																								
Note 1: Emission Level (dBUV/m) = SA Reading (dBUV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).																																	




Modulation	GFSK	Test Freq. (MHz)	2405																														
Polarization	Horizontal-Average																																
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66																																	
Level (dBUV/m) Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBUV/m</th><th>Limit dBUV/m</th><th>Margin dB</th><th>SA reading dBUV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>2374.75</td><td>39.81</td><td>54.00</td><td>-14.19</td><td>43.17</td><td>-3.36</td><td>Average</td><td>183</td><td>181</td></tr><tr><td>2</td><td>2497.25</td><td>39.07</td><td>54.00</td><td>-14.93</td><td>42.61</td><td>-3.54</td><td>Average</td><td>183</td><td>181</td></tr></tbody></table>					Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	2374.75	39.81	54.00	-14.19	43.17	-3.36	Average	183	181	2	2497.25	39.07	54.00	-14.93	42.61	-3.54	Average	183	181
	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg																								
1	2374.75	39.81	54.00	-14.19	43.17	-3.36	Average	183	181																								
2	2497.25	39.07	54.00	-14.93	42.61	-3.54	Average	183	181																								
Note 1: Emission Level (dBUV/m) = SA Reading (dBUV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).																																	



Modulation	GFSK	Test Freq. (MHz)	2405																														
Polarization	Vertical-Peak																																
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66																																	
<table><tr><th></th><th>Freq. MHz</th><th>Emission level dBUV/m</th><th>Limit dBUV/m</th><th>Margin dB</th><th>SA reading dBUV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>2335.50</td><td>52.52</td><td>74.00</td><td>-21.48</td><td>55.69</td><td>-3.17</td><td>Peak</td><td>233</td><td>133</td></tr><tr><td>2</td><td>2490.50</td><td>51.98</td><td>74.00</td><td>-22.02</td><td>55.46</td><td>-3.48</td><td>Peak</td><td>233</td><td>133</td></tr></table>					Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	2335.50	52.52	74.00	-21.48	55.69	-3.17	Peak	233	133	2	2490.50	51.98	74.00	-22.02	55.46	-3.48	Peak	233	133
	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg																								
1	2335.50	52.52	74.00	-21.48	55.69	-3.17	Peak	233	133																								
2	2490.50	51.98	74.00	-22.02	55.46	-3.48	Peak	233	133																								
Note 1: Emission Level (dBUV/m) = SA Reading (dBUV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).																																	



Modulation	GFSK	Test Freq. (MHz)	2405																														
Polarization	Vertical-Average																																
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66																																	
Level (dBUV/m)  Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBUV/m</th><th>Limit dBUV/m</th><th>Margin dB</th><th>SA reading dBUV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>2310.75</td><td>39.14</td><td>54.00</td><td>-14.86</td><td>42.20</td><td>-3.06</td><td>Average</td><td>233</td><td>133</td></tr><tr><td>2</td><td>2487.25</td><td>39.23</td><td>54.00</td><td>-14.77</td><td>42.74</td><td>-3.51</td><td>Average</td><td>233</td><td>133</td></tr></tbody></table>					Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	2310.75	39.14	54.00	-14.86	42.20	-3.06	Average	233	133	2	2487.25	39.23	54.00	-14.77	42.74	-3.51	Average	233	133
	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg																								
1	2310.75	39.14	54.00	-14.86	42.20	-3.06	Average	233	133																								
2	2487.25	39.23	54.00	-14.77	42.74	-3.51	Average	233	133																								
Note 1: Emission Level (dBUV/m) = SA Reading (dBUV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).																																	




Modulation	GFSK	Test Freq. (MHz)	2441																														
Polarization	Horizontal-Peak																																
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66																																	
Level (dBUV/m) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBUV/m</th><th>Limit dBUV/m</th><th>Margin dB</th><th>SA reading dBUV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>2364.50</td><td>52.32</td><td>74.00</td><td>-21.68</td><td>55.62</td><td>-3.30</td><td>Peak</td><td>186</td><td>178</td></tr><tr><td>2</td><td>2489.75</td><td>51.90</td><td>74.00</td><td>-22.10</td><td>55.38</td><td>-3.48</td><td>Peak</td><td>176</td><td>171</td></tr></table>					Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	2364.50	52.32	74.00	-21.68	55.62	-3.30	Peak	186	178	2	2489.75	51.90	74.00	-22.10	55.38	-3.48	Peak	176	171
	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg																								
1	2364.50	52.32	74.00	-21.68	55.62	-3.30	Peak	186	178																								
2	2489.75	51.90	74.00	-22.10	55.38	-3.48	Peak	176	171																								
Note 1: Emission Level (dBUV/m) = SA Reading (dBUV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).																																	



Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Horizontal-Average		
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66			
Level (dBUV/m)			



Modulation	GFSK	Test Freq. (MHz)	2441																														
Polarization	Vertical-Peak																																
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66																																	
Level (dBuV/m)  Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>2370.75</td><td>51.89</td><td>74.00</td><td>-22.11</td><td>55.25</td><td>-3.36</td><td>Peak</td><td>242</td><td>139</td></tr><tr><td>2</td><td>2490.00</td><td>51.22</td><td>74.00</td><td>-22.78</td><td>54.70</td><td>-3.48</td><td>Peak</td><td>321</td><td>230</td></tr></tbody></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	2370.75	51.89	74.00	-22.11	55.25	-3.36	Peak	242	139	2	2490.00	51.22	74.00	-22.78	54.70	-3.48	Peak	321	230
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg																								
1	2370.75	51.89	74.00	-22.11	55.25	-3.36	Peak	242	139																								
2	2490.00	51.22	74.00	-22.78	54.70	-3.48	Peak	321	230																								
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																	



Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Vertical-Average		
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66			
Level (dBUV/m) </			



Modulation	GFSK	Test Freq. (MHz)	2478
Polarization	Horizontal-Peak		
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66			
Level (dBUV/m) </			




Modulation	GFSK	Test Freq. (MHz)	2478
Polarization	Horizontal-Average		
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66			
Level (dBUV/m)			



Modulation	GFSK	Test Freq. (MHz)	2478
Polarization	Vertical-Peak		
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66			
Level (dBUV/m) </			




Modulation	GFSK		Test Freq. (MHz)	2478																															
Polarization	Vertical-Average																																		
Test By :Brad Wu_ Temperature(°C):25 Humidity(%):66																																			
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB/m</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>2317.50</td><td>39.18</td><td>54.00</td><td>-14.82</td><td>42.17</td><td>-2.99</td><td>Average</td><td>313</td><td>128</td></tr><tr><td>2</td><td>2483.50</td><td>41.51</td><td>54.00</td><td>-12.49</td><td>45.05</td><td>-3.54</td><td>Average</td><td>313</td><td>128</td></tr></table>							Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg	1	2317.50	39.18	54.00	-14.82	42.17	-2.99	Average	313	128	2	2483.50	41.51	54.00	-12.49	45.05	-3.54	Average	313	128
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg																										
1	2317.50	39.18	54.00	-14.82	42.17	-2.99	Average	313	128																										
2	2483.50	41.51	54.00	-12.49	45.05	-3.54	Average	313	128																										
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																			

2.4-2.4835GHz_SRD

CSEndB-DTS


2405MHz





2.4-2.4835GHz_SRD


CSEndB-DTS

2441MHz





Modulation Mode	Charging																																																																																																																																				
Power Phase	Line																																																																																																																																				
Test by : Akun Chung- Temperature: 23°C Humidity: 63%																																																																																																																																					
 <table><tr><th></th><th>Freq MHz</th><th>Level dBuV</th><th>Limit Line dBuV</th><th>Over Limit dB</th><th>Read Level dBuV</th><th>Factor dB</th><th>Cable loss dB</th><th>Aux dB</th><th>Remark</th></tr><tr><td>1</td><td>0.156</td><td>33.69</td><td>55.69</td><td>-22.00</td><td>24.01</td><td>9.65</td><td>0.03</td><td>0.00</td><td>Average</td></tr><tr><td>2</td><td>0.156</td><td>48.58</td><td>65.69</td><td>-17.11</td><td>38.90</td><td>9.65</td><td>0.03</td><td>0.00</td><td>QP</td></tr><tr><td>3</td><td>0.165</td><td>33.42</td><td>55.21</td><td>-21.79</td><td>23.74</td><td>9.65</td><td>0.03</td><td>0.00</td><td>Average</td></tr><tr><td>4</td><td>0.165</td><td>48.43</td><td>65.21</td><td>-16.78</td><td>38.75</td><td>9.65</td><td>0.03</td><td>0.00</td><td>QP</td></tr><tr><td>5</td><td>0.174</td><td>31.92</td><td>54.77</td><td>-22.85</td><td>22.24</td><td>9.64</td><td>0.04</td><td>0.00</td><td>Average</td></tr><tr><td>6</td><td>0.174</td><td>45.62</td><td>64.77</td><td>-19.15</td><td>35.94</td><td>9.64</td><td>0.04</td><td>0.00</td><td>QP</td></tr><tr><td>7</td><td>0.394</td><td>33.38</td><td>47.98</td><td>-14.60</td><td>23.70</td><td>9.64</td><td>0.04</td><td>0.00</td><td>Average</td></tr><tr><td>8</td><td>0.394</td><td>41.15</td><td>57.98</td><td>-16.83</td><td>31.47</td><td>9.64</td><td>0.04</td><td>0.00</td><td>QP</td></tr><tr><td>9*</td><td>0.405</td><td>35.32</td><td>47.75</td><td>-12.43</td><td>25.64</td><td>9.64</td><td>0.04</td><td>0.00</td><td>Average</td></tr><tr><td>10</td><td>0.405</td><td>42.66</td><td>57.75</td><td>-15.09</td><td>32.98</td><td>9.64</td><td>0.04</td><td>0.00</td><td>QP</td></tr><tr><td>11</td><td>25.456</td><td>18.78</td><td>50.00</td><td>-31.22</td><td>8.78</td><td>9.70</td><td>0.30</td><td>0.00</td><td>Average</td></tr><tr><td>12</td><td>25.456</td><td>23.77</td><td>60.00</td><td>-36.23</td><td>13.77</td><td>9.70</td><td>0.30</td><td>0.00</td><td>QP</td></tr></table>					Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Aux dB	Remark	1	0.156	33.69	55.69	-22.00	24.01	9.65	0.03	0.00	Average	2	0.156	48.58	65.69	-17.11	38.90	9.65	0.03	0.00	QP	3	0.165	33.42	55.21	-21.79	23.74	9.65	0.03	0.00	Average	4	0.165	48.43	65.21	-16.78	38.75	9.65	0.03	0.00	QP	5	0.174	31.92	54.77	-22.85	22.24	9.64	0.04	0.00	Average	6	0.174	45.62	64.77	-19.15	35.94	9.64	0.04	0.00	QP	7	0.394	33.38	47.98	-14.60	23.70	9.64	0.04	0.00	Average	8	0.394	41.15	57.98	-16.83	31.47	9.64	0.04	0.00	QP	9*	0.405	35.32	47.75	-12.43	25.64	9.64	0.04	0.00	Average	10	0.405	42.66	57.75	-15.09	32.98	9.64	0.04	0.00	QP	11	25.456	18.78	50.00	-31.22	8.78	9.70	0.30	0.00	Average	12	25.456	23.77	60.00	-36.23	13.77	9.70	0.30	0.00	QP
	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Aux dB	Remark																																																																																																																												
1	0.156	33.69	55.69	-22.00	24.01	9.65	0.03	0.00	Average																																																																																																																												
2	0.156	48.58	65.69	-17.11	38.90	9.65	0.03	0.00	QP																																																																																																																												
3	0.165	33.42	55.21	-21.79	23.74	9.65	0.03	0.00	Average																																																																																																																												
4	0.165	48.43	65.21	-16.78	38.75	9.65	0.03	0.00	QP																																																																																																																												
5	0.174	31.92	54.77	-22.85	22.24	9.64	0.04	0.00	Average																																																																																																																												
6	0.174	45.62	64.77	-19.15	35.94	9.64	0.04	0.00	QP																																																																																																																												
7	0.394	33.38	47.98	-14.60	23.70	9.64	0.04	0.00	Average																																																																																																																												
8	0.394	41.15	57.98	-16.83	31.47	9.64	0.04	0.00	QP																																																																																																																												
9*	0.405	35.32	47.75	-12.43	25.64	9.64	0.04	0.00	Average																																																																																																																												
10	0.405	42.66	57.75	-15.09	32.98	9.64	0.04	0.00	QP																																																																																																																												
11	25.456	18.78	50.00	-31.22	8.78	9.70	0.30	0.00	Average																																																																																																																												
12	25.456	23.77	60.00	-36.23	13.77	9.70	0.30	0.00	QP																																																																																																																												
Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB) + Aux (dB). 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).																																																																																																																																					

Modulation Mode	Charging																																																																																																																																																								
Power Phase	Neutral																																																																																																																																																								
Test by : Akun Chung- Temperature: 23°C Humidity: 63%																																																																																																																																																									
Level (dBUV)  Frequency (MHz) <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Over</th><th>Read</th><th>Factor</th><th>Cable</th><th>Aux</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV</th><th>Line</th><th>Limit</th><th>Level</th><th>dB</th><th>loss</th><th>dB</th><th></th></tr><tr><th></th><th></th><th></th><th>dBuV</th><th>dB</th><th>dBuV</th><th></th><th>dB</th><th></th><th></th></tr></thead><tbody><tr><td>1</td><td>0.150</td><td>34.06</td><td>56.00</td><td>-21.94</td><td>24.39</td><td>9.64</td><td>0.03</td><td>0.00</td><td>Average</td></tr><tr><td>2</td><td>0.150</td><td>48.09</td><td>66.00</td><td>-17.91</td><td>38.42</td><td>9.64</td><td>0.03</td><td>0.00</td><td>QP</td></tr><tr><td>3</td><td>0.159</td><td>33.05</td><td>55.52</td><td>-22.47</td><td>23.38</td><td>9.64</td><td>0.03</td><td>0.00</td><td>Average</td></tr><tr><td>4</td><td>0.159</td><td>46.49</td><td>65.52</td><td>-19.03</td><td>36.82</td><td>9.64</td><td>0.03</td><td>0.00</td><td>QP</td></tr><tr><td>5</td><td>0.177</td><td>33.08</td><td>54.64</td><td>-21.56</td><td>23.39</td><td>9.65</td><td>0.04</td><td>0.00</td><td>Average</td></tr><tr><td>6</td><td>0.177</td><td>46.12</td><td>64.64</td><td>-18.52</td><td>36.43</td><td>9.65</td><td>0.04</td><td>0.00</td><td>QP</td></tr><tr><td>7*</td><td>0.403</td><td>39.56</td><td>47.79</td><td>-8.23</td><td>29.88</td><td>9.64</td><td>0.04</td><td>0.00</td><td>Average</td></tr><tr><td>8</td><td>0.403</td><td>46.57</td><td>57.79</td><td>-11.22</td><td>36.89</td><td>9.64</td><td>0.04</td><td>0.00</td><td>QP</td></tr><tr><td>9</td><td>0.408</td><td>34.47</td><td>47.68</td><td>-13.21</td><td>24.79</td><td>9.64</td><td>0.04</td><td>0.00</td><td>Average</td></tr><tr><td>10</td><td>0.408</td><td>43.21</td><td>57.68</td><td>-14.47</td><td>33.53</td><td>9.64</td><td>0.04</td><td>0.00</td><td>QP</td></tr><tr><td>11</td><td>25.055</td><td>18.31</td><td>50.00</td><td>-31.69</td><td>8.19</td><td>9.82</td><td>0.30</td><td>0.00</td><td>Average</td></tr><tr><td>12</td><td>25.055</td><td>24.38</td><td>60.00</td><td>-35.62</td><td>14.26</td><td>9.82</td><td>0.30</td><td>0.00</td><td>QP</td></tr></tbody></table> Note 1: Level (dBUV) = Read Level (dBUV) + LISN Factor (dB) + Cable Loss (dB) + Aux (dB). 2: Over Limit (dB) = Level (dBUV) – Limit Line (dBUV).					Freq	Level	Limit	Over	Read	Factor	Cable	Aux	Remark		MHz	dBuV	Line	Limit	Level	dB	loss	dB					dBuV	dB	dBuV		dB			1	0.150	34.06	56.00	-21.94	24.39	9.64	0.03	0.00	Average	2	0.150	48.09	66.00	-17.91	38.42	9.64	0.03	0.00	QP	3	0.159	33.05	55.52	-22.47	23.38	9.64	0.03	0.00	Average	4	0.159	46.49	65.52	-19.03	36.82	9.64	0.03	0.00	QP	5	0.177	33.08	54.64	-21.56	23.39	9.65	0.04	0.00	Average	6	0.177	46.12	64.64	-18.52	36.43	9.65	0.04	0.00	QP	7*	0.403	39.56	47.79	-8.23	29.88	9.64	0.04	0.00	Average	8	0.403	46.57	57.79	-11.22	36.89	9.64	0.04	0.00	QP	9	0.408	34.47	47.68	-13.21	24.79	9.64	0.04	0.00	Average	10	0.408	43.21	57.68	-14.47	33.53	9.64	0.04	0.00	QP	11	25.055	18.31	50.00	-31.69	8.19	9.82	0.30	0.00	Average	12	25.055	24.38	60.00	-35.62	14.26	9.82	0.30	0.00	QP
	Freq	Level	Limit	Over	Read	Factor	Cable	Aux	Remark																																																																																																																																																
	MHz	dBuV	Line	Limit	Level	dB	loss	dB																																																																																																																																																	
			dBuV	dB	dBuV		dB																																																																																																																																																		
1	0.150	34.06	56.00	-21.94	24.39	9.64	0.03	0.00	Average																																																																																																																																																
2	0.150	48.09	66.00	-17.91	38.42	9.64	0.03	0.00	QP																																																																																																																																																
3	0.159	33.05	55.52	-22.47	23.38	9.64	0.03	0.00	Average																																																																																																																																																
4	0.159	46.49	65.52	-19.03	36.82	9.64	0.03	0.00	QP																																																																																																																																																
5	0.177	33.08	54.64	-21.56	23.39	9.65	0.04	0.00	Average																																																																																																																																																
6	0.177	46.12	64.64	-18.52	36.43	9.65	0.04	0.00	QP																																																																																																																																																
7*	0.403	39.56	47.79	-8.23	29.88	9.64	0.04	0.00	Average																																																																																																																																																
8	0.403	46.57	57.79	-11.22	36.89	9.64	0.04	0.00	QP																																																																																																																																																
9	0.408	34.47	47.68	-13.21	24.79	9.64	0.04	0.00	Average																																																																																																																																																
10	0.408	43.21	57.68	-14.47	33.53	9.64	0.04	0.00	QP																																																																																																																																																
11	25.055	18.31	50.00	-31.69	8.19	9.82	0.30	0.00	Average																																																																																																																																																
12	25.055	24.38	60.00	-35.62	14.26	9.82	0.30	0.00	QP																																																																																																																																																