

## SAR TEST REPORT

**Applicant Name:**

**JVC KENWOOD CORPORATION**  
1-16-2 Hakusan Midori-ku Yokohama-shi  
Kanagawa 226-8525 Japan

**Date of Issue:** 05. 10, 2017

**Test Report No.:** HCT-A-1704-F003-1

**Test Site:** HCT CO., LTD.

**FCC ID:**

**K44479000**

**Equipment Type:**  
**Model Name:**

**VHF DIGITAL TRANSCEIVER**  
**NX-3220-K, NX-3220-K2, NX-3220-K3**

**Testing has been carried out in accordance with:** 47CFR §2.1093  
ANSI/ IEEE C95.1 - 2005  
IEEE 1528-2013

**Date of Test:** 04/04/2017 ~ 04/06/2017

This device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in FCC KDB procedures and had been tested in accordance with the measurement procedures specified in FCC KDB procedures.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**Tested By**

**Reviewed By**



**In-Ho Park**  
**Test Engineer / SAR Team**  
**Certification Division**



**Dong-Seob Kim**  
**Technical Manager / SAR Team**  
**Certification Division**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

## **DOCUMENT HISTORY**

| Rev.              | DATE         | DESCRIPTION                               |
|-------------------|--------------|-------------------------------------------|
| HCT-A-1704-F003   | 04. 24, 2017 | First Approval Report                     |
| HCT-A-1704-F003-1 | 05. 10, 2017 | Revised a estimated BT SAR on the Report. |

# Table of Contents

|                                                         |     |
|---------------------------------------------------------|-----|
| 1. Attestation of Test Result of Device Under Test..... | 4   |
| 2. Test Methodology and Procedures .....                | 5   |
| 3. Output Power Specifications. ....                    | 6   |
| 4. Manufacturer's Accessory List.....                   | 9   |
| 5. INTRODUCTION .....                                   | 1 2 |
| 6. DESCRIPTION OF TEST EQUIPMENT .....                  | 1 3 |
| 7. SAR MEASUREMENT PROCEDURE .....                      | 1 6 |
| 8. DESCRIPTION OF TEST POSITION.....                    | 1 8 |
| 9. ANSI/ IEEE C95.1 - 2005 RF EXPOSURE LIMITS.....      | 1 9 |
| 10. SYSTEM VERIFICATION .....                           | 2 0 |
| 11. SAR TEST DATA SUMMARY .....                         | 2 2 |
| 12. Simultaneous SAR Analysis .....                     | 2 5 |
| 13. MEASUREMENT UNCERTAINTY .....                       | 2 6 |
| 13. SAR TEST EQUIPMENT .....                            | 2 7 |
| 14. CONCLUSION.....                                     | 2 8 |
| 15. REFERENCES .....                                    | 2 9 |
| Attachment 1. – SAR Test Plots.....                     | 3 1 |
| Attachment 2. – Dipole Verification Plots.....          | 3 9 |
| Attachment 3. – Probe Calibration Data .....            | 4 2 |
| Attachment 4. – Dipole Calibration Data .....           | 6 5 |
| Attachment 5. – SAR Tissue Characterization .....       | 7 4 |
| Attachment 6. – SAR SYSTEM VALIDATION .....             | 7 5 |

# 1. Attestation of Test Result of Device Under Test

| Test Laboratory |                                                                                          |
|-----------------|------------------------------------------------------------------------------------------|
| Company Name:   | HCT Co., LTD                                                                             |
| Address         | 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of Korea |
| Telephone       | +82 31 645 6300                                                                          |
| Fax.            | +82 31 645 6401                                                                          |

| Attestation of SAR test result |                                   |
|--------------------------------|-----------------------------------|
| Applicant Name:                | JVC KENWOOD CORPORATION           |
| FCC ID:                        | K44479000                         |
| Model:                         | NX-3220-K, NX-3220-K2, NX-3220-K3 |
| EUT Type:                      | VHF DIGITAL TRANSCEIVER           |
| Application Type:              | Certification                     |

| The Highest Reported SAR                  |                         |                 |                        |                     |                    |
|-------------------------------------------|-------------------------|-----------------|------------------------|---------------------|--------------------|
| Band                                      | Tx. Frequency           | Equipment Class | Reported 1g SAR (W/kg) |                     |                    |
|                                           | (MHz)                   |                 | Hand-held to Face      | Body-Worn Belt clip |                    |
| VHF (FCC)                                 | 150 ~ 174               | TNF             | 1.32                   | 5.46                | 50% PTT duty cycle |
| Bluetooth                                 | 2 402 ~ 2 480           | DSS/DTS         | N/A                    |                     |                    |
| Simultaneous SAR per KDB 690783 D01v01r03 |                         |                 | 5.59                   |                     |                    |
| Date(s) of Tests:                         | 04/04/2017 ~ 04/06/2017 |                 |                        |                     |                    |

## 2. Test Methodology and Procedures

The tests documented in this report were performed in accordance with IEEE Standard 1528-2013 & IEEE 1528-2005 and the following published KDB procedures.

- FCC KDB Publication 447498 D01 General SAR Guidance v06
- FCC KDB Publication 648474 D04 Handset SAR v01r03
- FCC KDB Publication 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04
- FCC KDB Publication 865664 D02 SAR Reporting v01r02
- FCC KDB Publication 643646 D01 SAR Test for PTT Radios v01r03

### \* DUT Description



### 3. Output Power Specifications.

#### 3.1 Nominal and Maximum Output Power Specifications

This device operates using the following maximum output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB publication 447498 D01v06.

#### 3.2 Maximum Output Power

| Band      | Frequency             | Power  |
|-----------|-----------------------|--------|
| VHF       | 150 MHz ~ 174 MHz     | 5.2 W  |
| Bluetooth | 2 402 MHz ~ 2 480 MHz | 2.5 mW |

#### 3.3 Output Average Conducted Power

| VHF                                     |                                              |                 |         |             |
|-----------------------------------------|----------------------------------------------|-----------------|---------|-------------|
| Model                                   | Antenna                                      | Frequency (MHz) | Channel | Power (dBm) |
| NX-3220-K,<br>NX-3220-K2,<br>NX-3220-K3 | KRA-22M, KRA-26M , KRA-41M, KRA-25, KRA-28   | 1               | 150.05  | 36.85       |
|                                         |                                              | 7               | 158.05  | 36.82       |
|                                         | KRA-22M2, KRA-26M2, KRA-41M2, KRA-25, KRA-28 | 8               | 166.00  | 36.92       |
|                                         |                                              | 3               | 173.95  | 36.98       |

For FCC Band:

Per KDB 447498 D01v06 Page 7 section 6) pages 7-8, the number of channels required to be tested is as follows.

$F_{high}$  = 174 MHz

$F_c$  = 162 MHz

$F_{Low}$  = 150 MHz

$N_c = \text{Round} \{ [100(f_{high} - f_{low}) / f_c]^{0.5} \times (f_c / 100)^{0.2} \} = \text{Round} \{ [100(174-150) / 162]^{0.5} \times (162/100)^{0.2} \} = 4$

Therefore, for the frequency band from 150 MHz to 174, 4channels are required for testing.

### 3.4 SAR Summation Scenario

According to FCC KDB 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the EUT are shown below paths and are mode in same rectangle to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.



Simultaneous transmission paths

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB 447498 D01v06.

| Simultaneous Transmission Scenarios |           |
|-------------------------------------|-----------|
| Applicable Combination              | Body-Worn |
| VHF + 2.4 GHz Bluetooth             | Yes       |

### 3.5 SAR Test Exclusions Applied

#### (A) Bluetooth

Per FCC KDB 447498 D01v06, The SAR exclusion threshold for distance < 50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel(mW)}}{\text{Test Separation Distance (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0 \text{ for } 1 - \text{g SAR}$$

| Mode      | Frequency<br>[MHz] | Maximum<br>Allowed Power<br>[mW] | Separation<br>Distance<br>[mm] | ≤ 3.0 for 1g SAR |
|-----------|--------------------|----------------------------------|--------------------------------|------------------|
| Bluetooth | 2 480              | 3                                | 5                              | 0.9              |

Based on the maximum conducted power of Bluetooth and antenna to use separation distance, Bluetooth SAR was not required  $[(3/5)*\sqrt{2.480}] = 0.9 < 3.0$ .

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v06 IV.C.1iii, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is ≤ 1.6W/kg. When standalone SAR is not required to be measured per FCC KDB 447498 D01v06 4.3.22, the following equation must be used to estimate the standalone 1-g SAR and 10g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHZ})}}{7.5} * \frac{(\text{Max Power of channel mW})}{\text{Min Separation Distance}}$$

Estimated 1-g SAR

| Mode      | Frequency<br>[MHz] | Maximum<br>Allowed Power<br>[mW] | Separation Distance<br>(Body)<br>[mm] | Estimated 1g SAR<br>(Body)<br>[W/kg] |
|-----------|--------------------|----------------------------------|---------------------------------------|--------------------------------------|
| Bluetooth | 2 480              | 3                                | 5                                     | 0.126                                |

**Note:**

Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission. The Estimated SAR results were determined according to FCC KDB447498 D01v06.

## 4. Manufacturer's Accessory List

| Part No.  | Description                                   | Accessory Type              | Accessory |
|-----------|-----------------------------------------------|-----------------------------|-----------|
| KRA-22M   | VHF Low Profile Helical Antenna (146-162 MHz) | Antennas                    | 1         |
| KRA-22M2  | VHF Low Profile Helical Antenna (162-174 MHz) |                             | 2         |
| KRA-26M   | VHF Helical Antenna (146-162 MHz)             |                             | 3         |
| KRA-26M2  | VHF Helical Antenna (162-174 MHz)             |                             | 4         |
| KRA-25    | VHF whip antenna (148-162 MHz)                |                             | 5         |
| KRA-28    | VHF whip antenna (140-170 MHz)                |                             | 6         |
| KRA-41M   | VHF Stubby antenna (146-162 MHz)              |                             | 7         |
| KRA-41M2  | VHF Stubby antenna (162-174 MHz)              |                             | 8         |
| KNB-55L   | Li-Ion Battery Pack (1480mA)                  | Battery                     | 1         |
| KNB-56N   | Ni-MH Battery Pack (1400mA)                   |                             | 2         |
| KNB-57L   | Li-Ion Battery Pack (2000mA)                  |                             | 3         |
| KNB-68LC  | Li-Ion Battery Pack (2000mA)                  |                             | 4         |
| KBP-5     | AA Alkaline Battery Pack                      |                             | 5         |
| KWR-1     | Water Resistance Bag                          | Body-worn                   | 1         |
| KBH-11    | Belt Clip                                     |                             | 2         |
| KLH-207K  | Nylon Case (non Display)                      |                             | 3         |
| KLH-207K2 | Nylon Case (Std Keypad)                       |                             | 4         |
| KLH-207K3 | Nylon Case (Full Keypad)                      |                             | 5         |
| KLH-206K  | Leather Case (non Display)                    |                             | 6         |
| KLH-206K2 | Leather Case (Std Keypad)                     |                             | 7         |
| KLH-206K3 | Leather Case (Full Keypad)                    |                             | 8         |
| KBH-13DS  | Leather swivel belt loop                      |                             | 9         |
| KLH-140SW | Swivel Belt Loop With D Ring                  |                             | 10        |
| KLH-37BT  | Leather Belt                                  |                             | 11        |
| KLH-38ST  | Shoulder Strap                                |                             | 12        |
| KMC-45D   | Speaker Microphone                            | Microphones Audio Accessory | 1         |
| KMC-45    | Speaker Microphone                            |                             | 2         |
| KMC-21    | Compact Speaker Microphone                    |                             | 3         |
| KMC-21S   | Compact Speaker Microphone                    |                             | 4         |
| KEP-2     | 25mm Earphone kit for KMC-45                  |                             | 5         |
| KHS-10-BH | Heavy-duty headset                            |                             | 6         |
| KHS-10-OH | Heavy-duty headset                            |                             | 7         |
| KHS-7     | Single Muff Headset                           |                             | 8         |
| KHS-7A    | Single Muff Headset w/in-line PTT             |                             | 9         |
| KHS-8BL   | 2-Wire Palm Mic w/ Earphone                   |                             | 10        |
| KHS-8BE   | 2-Wire Palm Mic w/ Earphone                   |                             | 11        |
| KHS-8NC   | 2-Wire Palm Mic w/ Earphone, NC               |                             | 12        |
| KHS-9BL   | 3-Wire Lapel Mic w/ Earphone                  |                             | 13        |
| KHS-9BE   | 3-Wire Lapel Mic w/ Earphone                  |                             | 14        |
| KHS-22    | Behind-the-head Headset w/PTT                 |                             | 15        |
| KHS-23    | 2-Wire Palm Mic                               |                             | 16        |
| KHS-25    | D-Ring Ear Headset                            |                             | 17        |
| KHS-26    | Ear bund In-line PTT Headset                  |                             | 18        |
| KHS-27    | D-Ring In-line PTT Headset                    |                             | 19        |
| KHS-27A   | D-Ring In-line PTT Headset                    |                             | 20        |
| KHS-31    | C-Ring Headset                                |                             | 21        |
| KHS-31C   | C-Ring Headset                                |                             | 22        |
| KHS-1     | Headset with PTT/VOX                          |                             | 23        |
| KHS-21    | Headset                                       |                             | 24        |
| KHS-29F   | Headset                                       |                             | 25        |
| EMC-11    | Clip Microphone with Earphone                 |                             | 26        |
| KHS-35F   | Headset                                       |                             | 27        |
| EMC-12    | Clip Microphone with Earphone                 |                             | 28        |

\* **Note:** Battery Dimensions

| No. | Battery Model | description                  | Size (mm)               |
|-----|---------------|------------------------------|-------------------------|
| 1   | KNB-55L       | Li-Ion Battery Pack (1480mA) | WHD 56.0 x 100.5 x 15.5 |
| 2   | KNB-56N       | Ni-MH Battery Pack (1400mA)  | WHD 56.0 x 100.5 x 20.2 |
| 3   | KNB-57L       | Li-Ion Battery Pack (2000mA) | WHD 56.0 x 100.5 x 20.2 |
| 4   | KNB-68LC      | Li-Ion Battery Pack (2000mA) | WHD 56.0 x 100.5 x 16.6 |
| 5   | KBP-5         | AA Alkaline Battery Pack     | WHD 56.0 x 100.5 x 21.5 |

### Radio Face Test (Hand-held to Face)

| Battery 1 |        |        |        |        |        |        |        |
|-----------|--------|--------|--------|--------|--------|--------|--------|
| Ant. 1    | Ant. 2 | Ant. 3 | Ant. 4 | Ant. 5 | Ant. 6 | Ant. 7 | Ant. 8 |
| Yes       | Yes    | Yes    | Yes    | Yes    | Yes    | Yes    | Yes    |
| Battery 2 |        |        |        |        |        |        |        |
| Ant. 1    | Ant. 2 | Ant. 3 | Ant. 4 | Ant. 5 | Ant. 6 | Ant. 7 | Ant. 8 |
| Yes       | Yes    | Yes    | Yes    | Yes    | Yes    | Yes    | Yes    |
| Battery 3 |        |        |        |        |        |        |        |
| Ant. 1    | Ant. 2 | Ant. 3 | Ant. 4 | Ant. 5 | Ant. 6 | Ant. 7 | Ant. 8 |
| Yes       | Yes    | Yes    | Yes    | Yes    | Yes    | Yes    | Yes    |
| Battery 4 |        |        |        |        |        |        |        |
| Ant. 1    | Ant. 2 | Ant. 3 | Ant. 4 | Ant. 5 | Ant. 6 | Ant. 7 | Ant. 8 |
| Yes       | Yes    | Yes    | Yes    | Yes    | Yes    | Yes    | Yes    |
| Battery 5 |        |        |        |        |        |        |        |
| Ant. 1    | Ant. 2 | Ant. 3 | Ant. 4 | Ant. 5 | Ant. 6 | Ant. 7 | Ant. 8 |
| Yes       | Yes    | Yes    | Yes    | Yes    | Yes    | Yes    | Yes    |

**Radio Body Test (Body-Worn)**

| Audio Accessory | Battery |     |     |     |     |
|-----------------|---------|-----|-----|-----|-----|
|                 | 1       | 2   | 3   | 4   | 5   |
| 1               | No      | No  | No  | No  | No  |
| 2               | No      | No  | No  | No  | No  |
| 3               | Yes     | Yes | Yes | Yes | Yes |
| 4               | No      | No  | No  | No  | No  |
| 5               | No      | No  | No  | No  | No  |
| 6               | No      | No  | No  | No  | No  |
| 7               | No      | No  | No  | No  | No  |
| 8               | No      | No  | No  | No  | No  |
| 9               | No      | No  | No  | No  | No  |
| 10              | No      | No  | No  | No  | No  |
| 11              | No      | No  | No  | No  | No  |
| 12              | No      | No  | No  | No  | No  |
| 13              | No      | No  | No  | No  | No  |
| 14              | No      | No  | No  | No  | No  |
| 15              | No      | No  | No  | No  | No  |
| 16              | No      | No  | No  | No  | No  |
| 17              | No      | No  | No  | No  | No  |
| 18              | No      | No  | No  | No  | No  |
| 19              | No      | No  | No  | No  | No  |
| 20              | No      | No  | No  | No  | No  |
| 21              | No      | No  | No  | No  | No  |
| 22              | No      | No  | No  | No  | No  |
| 23              | No      | No  | No  | No  | No  |
| 24              | No      | No  | No  | No  | No  |
| 25              | No      | No  | No  | No  | No  |
| 26              | No      | No  | No  | No  | No  |
| 27              | No      | No  | No  | No  | No  |
| 28              | No      | No  | No  | No  | No  |

\* Manufacture's disclosed accessory listing information provided by Kenwood corporation.

\* Note:

Audio Accessory KMC-21 was chosen for the testing body worn radio configuration.

## 5. INTRODUCTION

The FCC has adopted the guidelines for evaluating the environmental effects of radio frequency radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices.

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-2005 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz. 1992 by the Institute of Electrical and Electronics Engineers, Inc., New York 10017. The measurement procedure described in IEEE/ANSI C95.3-1992 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave is used for guidance in measuring SAR due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields," NCRP Report No. 86 NCRP, 1986, Bethesda, MD 20814. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

### SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative of the incremental electromagnetic energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density ( $\rho$ ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body.

$$SAR = \frac{d}{dt} \left( \frac{dU}{dm} \right)$$

Figure 1. SAR Mathematical Equation

*SAR is expressed in units of Watts per Kilogram (W/kg)*

$$SAR = \sigma E^2 / \rho$$

Where:

$\sigma$  = conductivity of the tissue-simulant material (S/m)  
 $\rho$  = mass density of the tissue-simulant material (kg/m<sup>3</sup>)  
 $E$  = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relations to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.

## 6. DESCRIPTION OF TEST EQUIPMENT

### 6.1 SAR MEASUREMENT SETUP

These measurements are performed using the DASY4 automated dosimetric assessment system. It is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland. It consists of high precision robotics system (Staubli), robot controller, Pentium III computer, near-field probe, probe alignment sensor, and the generic twin phantom containing the brain equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Figure.2).

A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The PC with Windows XP or Windows 7 is working with SAR Measurement system DASY4 & DASY5, A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.




Figure 2. HCT SAR Lab. Test Measurement Set-up

The DAE consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer. The system is described in detail in.

## 6.2 Phantom

### • ELI Phantom

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG diametric probes and dipoles.



Figure 6.1 ELI Phantom

|                 |                                        |
|-----------------|----------------------------------------|
| Shell Thickness | $2.0 \pm 0.2\text{mm}$                 |
| Filling Volume  | approx. 30 liters                      |
| Dimensions      | Major axis: 600 mm, Minor axis: 400 mm |

## 6.3 Device Holder for Transmitters

### Device Holder – Mounting Device

In combination with the SAM Phantom, the Mounting Device enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeatably positioned according to the EN 50360:2001/A:2001 and FCC KDB specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

Note: A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produced infinite number of configurations. To produce the Worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.



## 6.4 Validation Dipole

The reference dipole should have a return loss better than -20 dB (measured in the setup) at the resonant frequency to reduce the uncertainty in the power measurement.

### CLA Dipole

| System Validation Dipole |                                                                                                                                                                                                                                 |                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Description              | Narrowband antenna is used to simulate the 30-220 MHz range and calculates the SAR antenna system calibration value. A resonant loop antenna is integrated in a metal structure from the environment of the resonant structure. |  |
| Frequency                | 150 MHz                                                                                                                                                                                                                         |                                                                                     |
| Return Loss              | > 10 dB at specified validation position                                                                                                                                                                                        |                                                                                     |
| Power Capability         | >10 W continuous                                                                                                                                                                                                                |                                                                                     |
| Dimension                | CLA150: dipole length : 222.0 mm; overall height : 95.0 mm                                                                                                                                                                      |                                                                                     |

## 6.5 Brain & Muscle Tissue Simulating Mixture Characterization

The brain and muscle mixtures consist of a viscous gel using hydrox-ethyl cellulose (HEC) gelling agent and saline solution (see Table 1). Preservation with a bactericide is added and visual inspection is made to make sure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. The mixture characterizations used for the brain and muscle tissue simulating liquids are according to the data by C. Gabriel and G. Hartsgrove.

| Frequency (MHz)                              | 30    | 50    |       | 144   |       | 450   |      | 835   | 900   |      |
|----------------------------------------------|-------|-------|-------|-------|-------|-------|------|-------|-------|------|
| Recipe source number                         | 3     | 3     | 2     | 2     | 3     | 2     | 4    | 2     | 2     | 4    |
| Ingredients (% by weight)                    |       |       |       |       |       |       |      |       |       |      |
| Deionised water                              | 48,30 | 48,30 | 53,53 | 55,12 | 48,30 | 48,53 | 56   | 50,36 | 50,31 | 56   |
| Tween                                        |       |       | 44,70 | 43,31 |       | 49,51 |      | 48,39 | 48,34 |      |
| Oxidised mineral oil                         |       |       |       |       |       |       | 44   |       |       | 44   |
| Diethyleneglycol monohexylether              |       |       |       |       |       |       |      |       |       |      |
| Triton X-100                                 |       |       |       |       |       |       |      |       |       |      |
| Diacetin                                     | 50,00 | 50,00 |       |       | 50,00 |       |      |       |       |      |
| DGBE                                         |       |       |       |       |       |       |      |       |       |      |
| NaCl                                         | 1,60  | 1,60  | 1,77  | 1,57  | 1,60  | 1,96  |      | 1,25  | 1,35  |      |
| Additives and salt                           | 0,10  | 0,10  |       |       | 0,10  |       |      |       |       |      |
| Measured dielectric parameters               |       |       |       |       |       |       |      |       |       |      |
| $\epsilon_r'$                                | 54,2  | 53,1  | 54,54 | 52,81 | 51,0  | 43,29 | 42,3 | 41,6  | 41,0  | 40,6 |
| $\sigma$ (S/m)                               | 0,75  | 0,75  | 0,76  | 0,76  | 0,77  | 0,88  | 0,84 | 0,90  | 0,98  | 0,98 |
| Temp. (°C)                                   |       |       | 21    | 21    |       | 21    | 20   | 21    | 21    | 20   |
| $\epsilon_{r\_temp\_liquid}$ uncertainty (%) | 0,8   | 0,1   |       |       | 0,1   | 0,1   |      | 0,04  | 0,04  |      |
| $\sigma_{temp\_liquid}$ uncertainty (%)      | 2,8   | 2,8   |       |       | 2,6   | 4,2   |      | 1,6   | 1,6   |      |
| Target values (from Table 1)                 |       |       |       |       |       |       |      |       |       |      |
| $\epsilon_r'$                                | 55,0  | 54,5  |       | 52,4  |       | 43,5  |      | 41,5  | 41,5  |      |
| $\sigma$ (S/m)                               | 0,75  | 0,75  |       | 0,76  |       | 0,87  |      | 0,90  | 0,97  |      |

Fig 4. Composition of the Tissue Equivalent Matter

## 7. SAR MEASUREMENT PROCEDURE

The evaluation was performed with the following procedure:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no more than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the DUT's head and body area and the horizontal grid resolution was depending on the FCC KDB 865664 D01v01r04 table 4-1 & IEEE 1528-2013.
2. Based on step, the area of the maximum absorption was determined by sophisticated interpolations routines implemented in DASY software. When an Area Scan has measured all reachable point. DASY system computes the field maximal found in the scanned are, within a range of the maximum. SAR at this fixed point was measured and used as a reference value.
3. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB 865664 D01v01r04 table 4-1 and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (reference from the DASY manual.)
  - a. The data at the surface were extrapolated, since the center of the dipoles is no more than 2.7 mm away from the tip of the probe (it is different from the probe type) and the distance between the surface and the lowest measuring point is 1.2 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
  - b. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions. The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.
  - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan. If the value changed by more than 5 %, the SAR evaluation and drift measurements were repeated.

Area scan and zoom scan resolution setting follow KDB 865664 D01v01r04 quoted below.

|                                                                                                                                                                                                                                                                                               |                                    |                                                                                      | $\leq 3$ GHz                                                                                                                                                                                                                                                           | $> 3$ GHz                                                               |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|--------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|
| Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface                                                                                                                                                                                        |                                    |                                                                                      | $5\pm 1$ mm                                                                                                                                                                                                                                                            | $\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm                      |
| Maximum probe angle from probe axis to phantom surface normal at the measurement location                                                                                                                                                                                                     |                                    |                                                                                      | $30^{\circ} \pm 1^{\circ}$                                                                                                                                                                                                                                             | $20^{\circ} \pm 1^{\circ}$                                              |
| Maximum area scan Spatial resolution: $\Delta x_{Area}, \Delta y_{Area}$                                                                                                                                                                                                                      |                                    |                                                                                      | $\leq 2$ GHz: $\leq 15$ mm<br>2-3 GHz: $\leq 12$ mm                                                                                                                                                                                                                    | 3-4 GHz: $\leq 12$ mm<br>4-6 GHz: $\leq 10$ mm                          |
|                                                                                                                                                                                                                                                                                               |                                    |                                                                                      | When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device. |                                                                         |
| Maximum zoom scan Spatial resolution: $\Delta x_{zoom}, \Delta y_{zoom}$                                                                                                                                                                                                                      |                                    |                                                                                      | $\leq 2$ GHz: $\leq 8$ mm<br>2-3 GHz: $\leq 5$ mm*                                                                                                                                                                                                                     | 3-4 GHz: $\leq 5$ mm*<br>4-6 GHz: $\leq 4$ mm*                          |
| Maximum zoom scan Spatial resolution normal to phantom surface                                                                                                                                                                                                                                | uniform grid: $\Delta z_{zoom}(n)$ |                                                                                      | $\leq 5$ mm                                                                                                                                                                                                                                                            | 3-4 GHz: $\leq 4$ mm<br>4-5 GHz: $\leq 3$ mm<br>5-6 GHz: $\leq 2$ mm    |
|                                                                                                                                                                                                                                                                                               | graded grid                        | $\Delta z_{zoom}(1)$ : between 1 <sup>st</sup> two Points closest to phantom surface | $\leq 4$ mm                                                                                                                                                                                                                                                            | 3-4 GHz: $\leq 3$ mm<br>4-5 GHz: $\leq 2.5$ mm<br>5-6 GHz: $\leq 2$ mm  |
|                                                                                                                                                                                                                                                                                               |                                    | $\Delta z_{zoom}(n>1)$ : between subsequent Points                                   | $\leq 1.5 \cdot \Delta z_{zoom}(n-1)$                                                                                                                                                                                                                                  |                                                                         |
| Minimum zoom scan volume                                                                                                                                                                                                                                                                      | x, y, z                            |                                                                                      | $\geq 30$ mm                                                                                                                                                                                                                                                           | 3-4 GHz: $\geq 28$ mm<br>4-5 GHz: $\geq 25$ mm<br>5-6 GHz: $\geq 22$ mm |
| Note: $\delta$ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.                                                                                                                                             |                                    |                                                                                      |                                                                                                                                                                                                                                                                        |                                                                         |
| * When zoom scan is required and the reported SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is $\leq 1.4$ W/kg, $\leq 8$ mm, $\leq 7$ mm and $\leq 5$ mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz. |                                    |                                                                                      |                                                                                                                                                                                                                                                                        |                                                                         |

## 8. DESCRIPTION OF TEST POSITION

### 8.1 Body Holster/Belt Clip Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration. A device with a headset output is tested with a headset connected to the device. Body dielectric parameters are used.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with each accessory. If multiple accessory share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some Devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used.

Since this EUT does not supply any body worn accessory to the end user a distance of 0 cm from the EUT back surface to the liquid interface is configured for the generic test.


"See the Test SET-UP Photo"

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessory(ies), Including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

In all cases SAR measurements are performed to investigate the worst-case positioning. Worst case positioning is then documented and used to perform Body SAR testing.

### 8.2 Hand-held to Face device

A typical example of a front-of-face device is a two-way radio that is held at a distance from the face of the user when transmitting. In these cases the device under test shall be positioned at the distance to the phantom surface that corresponds to the intended use as specified by the manufacturer in the user instructions. If the intended use is not specified, a separation distance of 25 mm<sup>5</sup> between the phantom surface and the device shall be used.



## 9. ANSI/ IEEE C95.1 - 2005 RF EXPOSURE LIMITS

| HUMAN EXPOSURE                                         | UNCONTROLLED ENVIRONMENT<br>General Population | CONTROLLED ENVIRONMENT<br>Occupational |
|--------------------------------------------------------|------------------------------------------------|----------------------------------------|
|                                                        | (W/kg) or (mW/g)                               | (W/kg) or (mW/g)                       |
| SPATIAL PEAK SAR *<br>(Brain)                          | 1.60                                           | 8.00                                   |
| SPATIAL AVERAGE SAR **<br>(Whole Body)                 | 0.08                                           | 0.40                                   |
| SPATIAL PEAK SAR ***<br>(Hands / Feet / Ankle / Wrist) | 4.00                                           | 20.00                                  |

**Table 8.1 Safety Limits for Partial Body Exposure**

### NOTES:

\* The Spatial Peak value of the SAR averaged over any 1 g of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

\*\* The Spatial Average value of the SAR averaged over the whole-body.

\*\*\* The Spatial Peak value of the SAR averaged over any 10 g of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

**Uncontrolled Environments** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

**Controlled Environments** are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

## 10. SYSTEM VERIFICATION

### 10.1 Tissue Verification

The Head/ body simulating material is calibrated by HCT using the DAKS 3.5 to determine the conductivity and permittivity.

**Table for Head Tissue Verification**

| Date of Tests | Tissue Temp. (°C) | Tissue Type | Freq. (MHz) | Measured Conductivity $\sigma$ (S/m) | Measured Dielectric Constant, $\epsilon$ | Target Conductivity $\sigma$ (S/m) | Target Dielectric Constant, $\epsilon$ | % dev $\sigma$ | % dev $\epsilon$ |
|---------------|-------------------|-------------|-------------|--------------------------------------|------------------------------------------|------------------------------------|----------------------------------------|----------------|------------------|
| 04/06/2017    | 21.8              | 150H        | 100         | 0.721                                | 55.298                                   | 0.756                              | 54.630                                 | -4.63%         | 1.22%            |
|               |                   |             | 150         | 0.748                                | 50.332                                   | 0.760                              | 52.300                                 | -1.58%         | -3.76%           |
|               |                   |             | 200         | 0.801                                | 47.543                                   | 0.797                              | 49.970                                 | 0.50%          | -4.86%           |

**Table for Body Tissue Verification**

| Date of Tests | Tissue Temp. (°C) | Tissue Type | Freq. (MHz) | Measured Conductivity $\sigma$ (S/m) | Measured Dielectric Constant, $\epsilon$ | Target Conductivity $\sigma$ (S/m) | Target Dielectric Constant, $\epsilon$ | % dev $\sigma$ | % dev $\epsilon$ |
|---------------|-------------------|-------------|-------------|--------------------------------------|------------------------------------------|------------------------------------|----------------------------------------|----------------|------------------|
| 04/04/2017    | 21.7              | 150B        | 100         | 0.735                                | 64.148                                   | 0.760                              | 63.130                                 | -3.29%         | 1.61%            |
|               |                   |             | 150         | 0.783                                | 62.358                                   | 0.800                              | 61.900                                 | -2.13%         | 0.74%            |
|               |                   |             | 200         | 0.808                                | 60.262                                   | 0.840                              | 60.670                                 | -3.81%         | -0.67%           |

### 10.2 System Verification

Prior to assessment, the system is verified to the  $\pm 10\%$  of the specifications at 150 MHz by using the system Verification kit. (Graphic Plots Attached)

#### System Verification Results

| Freq. | Date       | Probe (S/N) | Dipole (S/N) | Liquid | Amb. Temp. | Liquid Temp. | 1 W Target SAR <sub>1g</sub> (SPEAG) | Measured SAR <sub>1g</sub> | 1 W Normalized SAR <sub>1g</sub> | Deviation | Limit [%] |
|-------|------------|-------------|--------------|--------|------------|--------------|--------------------------------------|----------------------------|----------------------------------|-----------|-----------|
| [MHz] |            |             |              |        | [°C]       | [°C]         | [W/kg]                               | [W/kg]                     | [W/kg]                           | [%]       | [%]       |
| 150   | 04/06/2017 | 3968        | 4014         | Head   | 21.9       | 21.8         | 3.68                                 | 0.373                      | 3.73                             | + 1.36    | $\pm 10$  |
| 150   | 04/04/2017 | 3903        | 4014         | Body   | 21.9       | 21.7         | 3.68                                 | 0.354                      | 3.54                             | - 3.80    | $\pm 10$  |

### 10.3 System Verification Procedure

SAR measurement was prior to assessment, the system is verified to the  $\pm 10\%$  of the specifications at each frequency band by using the system Verification kit. (Graphic Plots Attached)

- Cabling the system, using the Verification kit equipments.
- Generate about 100 mW Input Level from the Signal generator to the Dipole Antenna.
- Dipole Antenna was placed below the Flat phantom.
- The measured one-gram SAR at the surface of the phantom above the dipole feed-point should be within 10 % of the target reference value.
- The results are normalized to 1 W input power.

NOTE;

SAR Verification was performed according to the FCC KDB 865664 D01v01r04.

## 11. SAR TEST DATA SUMMARY

### 11.1 Measurement Results (Hand-held to Face SAR)

| Antenna                                                                                     | Frequency<br>(MHz) | Tune-Up Limit<br>(dBm) | Conducted Power<br>(dBm) | Power Drift<br>(dB) | Battery  | Separation Distance<br>(mm)                   | Measured SAR<br>(mW/g) | SAR 50% Duty<br>(mW/g) | Reported SAR<br>(mW/g) | Plot No. |
|---------------------------------------------------------------------------------------------|--------------------|------------------------|--------------------------|---------------------|----------|-----------------------------------------------|------------------------|------------------------|------------------------|----------|
| KRA-22M2                                                                                    | 173.95             | 37.16                  | 36.98                    | -1.56               | KNB-57L  | 25                                            | 1.01                   | 0.51                   | 0.75                   | -        |
| KRA-22M                                                                                     | 150.05             | 37.16                  | 36.85                    | -0.02               | KNB-57L  | 25                                            | 0.877                  | 0.439                  | 0.473                  | -        |
| KRA-26M2                                                                                    | 173.95             | 37.16                  | 36.98                    | -1.52               | KNB-57L  | 25                                            | 1.79                   | 0.90                   | <b>1.32</b>            | 1        |
| KRA-26M2                                                                                    | 173.95             | 37.16                  | 36.98                    | -0.95               | KNB-55L  | 25                                            | 1.92                   | 0.96                   | 1.25                   | 2        |
| KRA-26M2                                                                                    | 173.95             | 37.16                  | 36.98                    | -0.90               | KNB-56N  | 25                                            | 1.75                   | 0.88                   | 1.12                   | -        |
| KRA-26M2                                                                                    | 173.95             | 37.16                  | 36.98                    | -0.93               | KNB-68LC | 25                                            | 1.73                   | 0.87                   | 1.12                   | -        |
| KRA-26M2                                                                                    | 173.95             | 37.16                  | 36.98                    | -2.48               | KBP-5    | 25                                            | 1.17                   | 0.59                   | 1.08                   | -        |
| KRA-26M                                                                                     | 150.05             | 37.16                  | 36.85                    | -0.35               | KNB-57L  | 25                                            | 0.643                  | 0.322                  | 0.374                  | -        |
| KRA-41M2                                                                                    | 173.95             | 37.16                  | 36.98                    | -0.71               | KNB-57L  | 25                                            | 0.406                  | 0.203                  | 0.249                  | -        |
| KRA-41M                                                                                     | 150.05             | 37.16                  | 36.85                    | -0.50               | KNB-57L  | 25                                            | 0.538                  | 0.269                  | 0.324                  | -        |
| KRA-25                                                                                      | 150.05             | 37.16                  | 36.85                    | -0.60               | KNB-57L  | 25                                            | 0.951                  | 0.476                  | 0.587                  | -        |
| KRA-28                                                                                      | 166.00             | 37.16                  | 36.92                    | 0.48                | KNB-57L  | 25                                            | 0.553                  | 0.277                  | 0.261                  | -        |
| KRA-26M2                                                                                    | 173.95             | 37.16                  | 36.98                    | -0.53               | KNB-57L  | 25                                            | 2.21                   | 1.11                   | 1.30 *                 | 3        |
| KRA-26M2                                                                                    | 173.95             | 37.16                  | 36.98                    | -0.61               | KNB-57L  | 25                                            | 2.09                   | 1.05                   | 1.25 **                | 4        |
| ANSI/ IEEE C95.1 - 2005 – Safety Limit<br>Spatial Peak<br>Controlled Exposure/ Occupational |                    |                        |                          |                     |          | Head<br>8 W/kg (mW/g)<br>Averaged over 1 gram |                        |                        |                        |          |

\* Basic

\*\* Standard

Note : Battery KNB-57L was selected as the default battery for assessments at the Face because it has the highest capacity (refer to Sec.4 Manufacturer's battery list).

## 11.2 Measurement Results (Body-worn Belt clip SAR)

| Antenna                                                                                     | Frequency | Tune-Up Limit | Conducted Power | Power Drift | Battery  | Measured SAR                                  | SAR 50% Duty | Reported SAR   | Plot No. |
|---------------------------------------------------------------------------------------------|-----------|---------------|-----------------|-------------|----------|-----------------------------------------------|--------------|----------------|----------|
|                                                                                             | (MHz)     | (dBm)         | (dBm)           | (dB)        |          | (mW/g)                                        | (mW/g)       | (mW/g)         |          |
| KRA-22M2                                                                                    | 173.95    | 37.16         | 36.98           | -0.28       | KNB-55L  | 1.79                                          | 0.90         | 0.95           | -        |
| KRA-22M                                                                                     | 150.05    | 37.16         | 36.85           | -0.32       | KNB-55L  | 5.88                                          | 2.94         | 3.40           | -        |
| KRA-26M2                                                                                    | 173.95    | 37.16         | 36.98           | -1.01       | KNB-55L  | 1.83                                          | 0.92         | 1.20           | -        |
| KRA-26M                                                                                     | 150.05    | 37.16         | 36.85           | -0.71       | KNB-55L  | 5.07                                          | 2.54         | 3.21           | -        |
| KRA-41M2                                                                                    | 173.95    | 37.16         | 36.98           | -0.28       | KNB-55L  | 1.25                                          | 0.63         | 0.69           | -        |
| KRA-41M                                                                                     | 150.05    | 37.16         | 36.85           | -0.86       | KNB-55L  | 4.18                                          | 2.09         | 2.74           | -        |
| KRA-25                                                                                      | 150.05    | 37.16         | 36.85           | -0.65       | KNB-55L  | 6.31                                          | 3.16         | 3.94           | -        |
| KRA-25                                                                                      | 158.05    | 37.16         | 36.82           | -1.31       | KBP-5    | 4.82                                          | 2.41         | 3.52           | -        |
| KRA-25                                                                                      | 158.05    | 37.16         | 36.82           | -0.54       | KNB-56N  | 6.56                                          | 3.28         | 4.02           | -        |
| KRA-25                                                                                      | 158.05    | 37.16         | 36.82           | -0.51       | KNB-57L  | 8.24                                          | 4.12         | 5.01           | 5        |
| KRA-25                                                                                      | 158.05    | 37.16         | 36.82           | -0.74       | KNB-68LC | 6.78                                          | 3.39         | 4.35           | -        |
| KRA-25                                                                                      | 158.05    | 37.16         | 36.82           | -0.61       | KNB-55L  | 6.88                                          | 3.44         | 4.28           | -        |
| KRA-28                                                                                      | 166.00    | 37.16         | 36.92           | 0.27        | KNB-55L  | 1.19                                          | 0.60         | 0.59           | -        |
| KRA-25                                                                                      | 158.05    | 37.16         | 36.82           | -0.11       | KNB-57L  | 9.84                                          | 4.92         | <b>5.46 *</b>  | 6        |
| KRA-25                                                                                      | 158.05    | 37.16         | 36.82           | -0.28       | KNB-57L  | 9.05                                          | 4.53         | <b>5.22 **</b> | 7        |
| ANSI/ IEEE C95.1 - 2005 – Safety Limit<br>Spatial Peak<br>Controlled Exposure/ Occupational |           |               |                 |             |          | Body<br>8 W/kg (mW/g)<br>Averaged over 1 gram |              |                |          |

\* Basic

\*\* Standard

Note : Battery KNB-55L was selected as the default battery for assessments at the Body because it is the thinnest battery (refer to Sec.4 Manufacturer's battery list).

## 11.3 SAR Test Notes

### General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, FCC KDB Procedure.
2. Batteries are fully charged at the beginning of the SAR measurements. A standard battery was used for all SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB 447498 D01v06.
6. Test signal call mode is Manual test cord.
7. The EUT was tested for face-held SAR with a 2.5 cm separation distance between the front of the EUT and the outer surface of the planar phantom.
8. The Body-worn SAR evaluation was performed with the Balt-clip body-worn accessory attached to the DUT and touching the outer surface of the planar phantom.
9. The adjusted SAR value was calculated by first scaling the SAR value up by the drift. This value was then scaled up based on the difference of the upper end the tolerance (37.16 dBm) and the measured conducted power. The resultant value is then multiplied by 0.5 to give the SAR value at 50% duty cycle.
10. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB 447498 D01v06. Test Procedures applied in accordance with FCC KDB 643646 D01v01r03.
11. Measurement was reduced per KDB 643646 D01v01r03.
12. When the SAR for all antennas tested using the default battery is  $\leq 3.5$  W/kg, testing of all other required channels is not necessary.
13. When the SAR of an antenna tested on the highest output power using the default battery is  $> 3.5$  W/Kg and  $\leq 4.0$  W/Kg, testing of the immediately adjacent channel(s) is not necessary, but testing of other required channels may still be required.
14. When the SAR for all antennas tested using the default battery  $\leq 4.0$  W/kg, test additional batteries using the antenna and channel configuration that resulted in the highest SAR.
15. When the SAR of an antenna tested on the highest output power channel using the default battery is  $> 4.0$  W/kg and  $\leq 6.0$  W/kg, testing of the required immediately adjacent channel(s) is necessary. For the remaining channels that cannot be excluded, this rule may be applied recursively with respect to the highest output power channel among the remaining channels.
16. Based on the SAR measured in the body-worn test sequence with default audio accessory, if the SAR for the antenna, body-worn accessory and battery combination(s) applicable to an audio accessory is/are  $> 4.0$  W/kg and  $< 6.0$  W/kg, test that audio accessory using the highest body-worn SAR combination (antenna, battery and body-worn accessory) and channel configuration previously identified that is applicable to the audio accessory.
17. When the SAR of an antenna tested is  $> 6.0$  W/kg, test that battery and antenna combination with the default body-worn and audio accessory on the required immediately adjacent channels.
18. If the SAR measured  $> 7.0$  W/kg, test that battery, antenna, body-worn and audio accessory combination on all required channels.

## 12. Simultaneous SAR Analysis

### 12.1 Simultaneous Transmission Summation for Body-Worn

| Simultaneous Transmission Summation Scenario with Bluetooth |          |                     |         |               |                  |
|-------------------------------------------------------------|----------|---------------------|---------|---------------|------------------|
| Exposure condition                                          | Distance | Band                | VHF SAR | Bluetooth SAR | $\Sigma$ 1-g SAR |
|                                                             | (mm)     |                     | (W/kg)  | (W/kg)        | (W/kg)           |
| Body-worn                                                   | 5        | Body-worn Belt clip | 5.46    | 0.126         | 5.586            |

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498 D01v06. Estimated SAR results were used for SAR summation for body-worn back side at 5 mm to determine simultaneous transmission SAR test exclusion.

The simultaneous transmission summation is applied only for body-worn case according to user condition. Bluetooth transmission is using for Bluetooth headset when DUT is on the body-worn case.

### 12.2 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit. And therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013.

## 13. MEASUREMENT UNCERTAINTY

| Uncertainty (450 MHz)         |       |       |      |                |                      |                  |
|-------------------------------|-------|-------|------|----------------|----------------------|------------------|
| Error Description             | Tol   | Prob. | Div. | c <sub>i</sub> | Standard Uncertainty | v <sub>eff</sub> |
|                               | (± %) | dist. |      |                | (± %)                |                  |
| 1.Measurement System          |       |       |      |                |                      |                  |
| Probe Calibration             | 6.65  | N     | 1    | 1              | 6.65                 | ∞                |
| Axial Isotropy                | 4.70  | R     | 1.73 | 0.70           | 1.90                 | ∞                |
| Hemispherical Isotropy        | 9.60  | R     | 1.73 | 0.70           | 3.88                 | ∞                |
| Boundary Effects              | 1.00  | R     | 1.73 | 1              | 0.58                 | ∞                |
| Linearity                     | 4.70  | R     | 1.73 | 1              | 2.71                 | ∞                |
| System Detection Limits       | 0.25  | R     | 1.73 | 1              | 0.14                 | ∞                |
| Readout Electronics           | 0.30  | N     | 1.00 | 1              | 0.30                 | ∞                |
| Response Time                 | 0.80  | R     | 1.73 | 1              | 0.46                 | ∞                |
| Integration Time              | 2.60  | R     | 1.73 | 1              | 1.50                 | ∞                |
| RF Ambient Noise              | 3.00  | R     | 1.73 | 1              | 1.73                 | ∞                |
| RF Ambient Conditions         | 3.00  | R     | 1.73 | 1              | 1.73                 | ∞                |
| Probe Positioner              | 0.40  | R     | 1.73 | 1              | 0.23                 | ∞                |
| Probe Positioning             | 2.90  | R     | 1.73 | 1              | 1.67                 | ∞                |
| Max SAR Eval                  | 2.00  | R     | 1.73 | 1              | 1.15                 | ∞                |
| 2.Test Sample Related         |       |       |      |                |                      |                  |
| Device Positioning            | 2.11  | N     | 1.00 | 1              | 2.11                 | 9                |
| Device Holder                 | 3.60  | N     | 1.00 | 1              | 3.60                 | 5                |
| Power Drift                   | 5.00  | R     | 1.73 | 1              | 2.89                 | ∞                |
| Power Scaling                 | 0.00  | R     | 1.73 | 1              | 0.00                 | ∞                |
| 3.Phantom and Setup           |       |       |      |                |                      |                  |
| Phantom Uncertainty           | 7.50  | R     | 1.73 | 1              | 3.53                 | ∞                |
| Liquid Conductivity(target)   | 5.00  | R     | 1.73 | 0.64           | 1.85                 | ∞                |
| Liquid Conductivity(meas.)    | 1.35  | N     | 1    | 0.78           | 1.05                 | ∞                |
| Liquid Permittivity (target)  | 5.00  | R     | 1.73 | 0.60           | 1.73                 | ∞                |
| Liquid Permittivity(meas.)    | 0.90  | N     | 1    | 0.23           | 0.21                 | ∞                |
| Combined Standard Uncertainty |       |       |      |                | 11.36                |                  |
| Coverage Factor for 95 %      |       |       |      |                | k=2                  |                  |
| Expanded STD Uncertainty      |       |       |      |                | 22.73                |                  |

## 14. SAR TEST EQUIPMENT

| Manufacturer | Type / Model                    | S/N                | Calib. Date | Calib.Interval | Calib.Due  |
|--------------|---------------------------------|--------------------|-------------|----------------|------------|
| SPEAG        | ELI Phantom                     | -                  | N/A         | N/A            | N/A        |
| HP           | SAR System Control PC           | -                  | N/A         | N/A            | N/A        |
| Staubli      | Robot ControllerCS7MB           | F01/ 5K08A1/ C/ 01 | N/A         | N/A            | N/A        |
| Staubli      | CS8Cspeag-TX60                  | F10/ 5D1CA1/ C/ 01 | N/A         | N/A            | N/A        |
| Staubli      | RX90B L                         | F01/ 5K08A1/ A/ 01 | N/A         | N/A            | N/A        |
| Staubli      | TX60 Xlspeag                    | F10/ 5D1CA1/ A/ 01 | N/A         | N/A            | N/A        |
| Staubli      | Teach Pendant (Joystick)        | D22134001 1        | N/A         | N/A            | N/A        |
| Staubli      | Teach Pendant (Joystick)        | D21142106          | N/A         | N/A            | N/A        |
| SPEAG        | DAE3                            | 504                | 07/26/2016  | Annual         | 07/26/2017 |
| SPEAG        | DAE4                            | 869                | 09/27/2016  | Annual         | 09/27/2017 |
| SPEAG        | E-Field Probe EX3DV4            | 3968               | 05/31/2016  | Annual         | 05/31/2017 |
| SPEAG        | E-Field Probe EX3DV4            | 3903               | 09/28/2016  | Annual         | 09/28/2017 |
| SPEAG        | Dipole CLA150                   | 4014               | 09/15/2016  | Annual         | 09/15/2017 |
| Agilent      | Power Meter N1911A              | MY45101406         | 09/28/2016  | Annual         | 09/28/2017 |
| HP           | Power Sensor 8481A              | 2702A72055         | 05/27/2016  | Annual         | 05/27/2017 |
| SPEAG        | DAKS-12                         | 1026               | 04/26/2016  | Annual         | 04/26/2017 |
| HP           | Directional Bridge              | 86205A             | 05/18/2016  | Annual         | 05/18/2017 |
| HP           | Signal Generator N5182A         | MY47070230         | 05/13/2016  | Annual         | 05/13/2017 |
| HP           | 11636B/Power Divider            | 58698              | 03/05/2017  | Annual         | 03/05/2018 |
| TESTO        | 175-H1/Thermometer              | 40331939309        | 02/10/2017  | Annual         | 02/10/2018 |
| HP           | 8447F amplifier                 | 3113A05981         | 01/09/2017  | Annual         | 01/09/2018 |
| Agilent      | Attenuator(3dB)                 | 52744              | 10/16/2016  | Annual         | 10/16/2017 |
| Agilent      | Attenuator(20dB)                | 52664              | 10/16/2016  | Annual         | 10/16/2017 |
| HP           | Notebook(DAKS)                  | -                  | N/A         | N/A            | N/A        |
| HP           | Dual Directional Coupler        | 16072              | 10/20/2015  | Annual         | 10/20/2016 |
| HP           | Network Analyzer 8753ES         | JP39240221         | 02/27/2017  | Annual         | 02/27/2018 |
| Agilent      | Power Sensor N1921A             | MY55220026         | 08/24/2016  | Annual         | 08/24/2017 |
| Aeroflex     | Fixed Coaxial Attenuator (30dB) | CE6106             | 11/23/2016  | Annual         | 11/23/2017 |

**NOTE:**

1. The E-field probe was calibrated by SPEAG, by the waveguide technique procedure. Dipole Verification measurement is performed by HCT Lab. before each test. The brain/body simulating material is calibrated by HCT using the DAKS-12 to determine the conductivity and permittivity (dielectric constant) of the brain/body-equivalent material.

## 15. CONCLUSION

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the ANSI/IEEE C95.1- 2005.

These measurements are taken to simulate the RF effects exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests.

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

## 16. REFERENCES

- [1] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice or Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices.
- [2] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radio frequency Radiation, Aug. 1996.
- [3] ANSI/IEEE C95.1 - 1991, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300 kHz to 100 GHz, New York: IEEE, Aug. 1992
- [4] ANSI/IEEE C 95.1 - 2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3 kHz to 300 GHz, New York: IEEE, 2006.
- [5] ANSI/IEEE C95.3 - 1991, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, 1992.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for Radio Frequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 120-124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300 MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectro magnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computer mathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10 kHz-300 GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, EidgenØssische Technische Hoschs Schule ZØrich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation and procedures – Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.

- [21] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures – Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz) Mar. 2010.
- [22] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radio communication Apparatus (All Frequency Band) Issue 5, March 2015.
- [23] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [24] FCC SAR Test procedures for 2G-3G Devices, Mobile Hotspot and UMPC Device KDB 941225 D01.
- [25] SAR Measurement Guidance for IEEE 802.11 transmitters, KDB 248227 D01v02r02
- [26] SAR Evaluation of Handsets with Multiple Transmitters and Antennas KDB 648474 D03, D04.
- [27] SAR Evaluation for Laptop, Notebook, Netbook and Tablet computers KDB 616217 D04.
- [28] SAR Measurement and Reporting Requirements for 100 MHz – 6 GHz, KDB 865664 D01, D02.
- [29] FCC General RF Exposure Guidance and SAR procedures for Dongles, KDB 447498 D01,D02.

## Attachment 1. – SAR Test Plots

Test Laboratory: HCT CO., LTD  
EUT Type: VHF DIGITAL TRANSCEIVER  
Liquid Temperature: 21.8 °C  
Ambient Temperature: 21.9 °C  
Test Date: 04/06/2017  
Plot No.: 1

**DUT: K3220; Type: bar**


Communication System: UID 0, 150MHz(FCC); Frequency: 173.95 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 173.95$  MHz;  $\sigma = 0.796$  S/m;  $\epsilon_r = 47.825$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

## DASY Configuration:

- Probe: EX3DV4 - SN3968; ConvF(13.17, 13.17, 13.17); Calibrated: 2016-05-31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn504; Calibrated: 2016-07-26
- Phantom: ELI4.0
- Measurement SW: DASY4, Version 4.7 (80);

**Head front 3ch 26M2/Area Scan (6x22x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 2.23 W/kg

**Head front 3ch 26M2/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 54.89 V/m; Power Drift = -1.52 dB  
Peak SAR (extrapolated) = 2.32 W/kg  
**SAR(1 g) = 1.79 W/kg; SAR(10 g) = 1.4 W/kg**  
Maximum value of SAR (measured) = 2.07 W/kg



0 dB = 2.23 W/kg = 3.49 dBW/kg

Test Laboratory: HCT CO., LTD  
EUT Type: VHF DIGITAL TRANSCEIVER  
Liquid Temperature: 21.8 °C  
Ambient Temperature: 21.9 °C  
Test Date: 04/06/2017  
Plot No.: 2

**DUT: K3220; Type: bar**


Communication System: UID 0, 150MHz(FCC); Frequency: 173.95 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 173.95$  MHz;  $\sigma = 0.796$  S/m;  $\epsilon_r = 47.825$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

## DASY Configuration:

- Probe: EX3DV4 - SN3968; ConvF(13.17, 13.17, 13.17); Calibrated: 2016-05-31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn504; Calibrated: 2016-07-26
- Phantom: ELI4.0
- Measurement SW: DASY4, Version 4.7 (80);

**Head front 3ch 26M2/Area Scan (6x22x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 2.29 W/kg

**Head front 3ch 26M2/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 53.24 V/m; Power Drift = -0.95 dB  
Peak SAR (extrapolated) = 2.44 W/kg  
**SAR(1 g) = 1.92 W/kg; SAR(10 g) = 1.49 W/kg**  
Maximum value of SAR (measured) = 2.20 W/kg



0 dB = 2.29 W/kg = 3.60 dBW/kg

Test Laboratory: HCT CO., LTD  
EUT Type: VHF DIGITAL TRANSCEIVER  
Liquid Temperature: 21.8 °C  
Ambient Temperature: 21.9 °C  
Test Date: 04/06/2017  
Plot No.: 3

**DUT: K3220; Type: bar**


Communication System: UID 0, 150MHz(FCC); Frequency: 173.95 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 173.95$  MHz;  $\sigma = 0.796$  S/m;  $\epsilon_r = 47.825$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

## DASY Configuration:

- Probe: EX3DV4 - SN3968; ConvF(13.17, 13.17, 13.17); Calibrated: 2016-05-31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn504; Calibrated: 2016-07-26
- Phantom: ELI4.0
- Measurement SW: DASY4, Version 4.7 (80);

**Head front 3ch 26M2/Area Scan (5x21x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 2.56 W/kg

**Head front 3ch 26M2/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 55.92 V/m; Power Drift = -0.53 dB  
Peak SAR (extrapolated) = 2.79 W/kg  
**SAR(1 g) = 2.21 W/kg; SAR(10 g) = 1.76 W/kg**  
Maximum value of SAR (measured) = 2.52 W/kg



0 dB = 2.56 W/kg = 4.09 dBW/kg

Test Laboratory: HCT CO., LTD  
EUT Type: VHF DIGITAL TRANSCEIVER  
Liquid Temperature: 21.8 °C  
Ambient Temperature: 21.9 °C  
Test Date: 04/06/2017  
Plot No.: 4

**DUT: K3220; Type: bar**


Communication System: UID 0, 150MHz(FCC); Frequency: 173.95 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 173.95$  MHz;  $\sigma = 0.796$  S/m;  $\epsilon_r = 47.825$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

## DASY Configuration:

- Probe: EX3DV4 - SN3968; ConvF(13.17, 13.17, 13.17); Calibrated: 2016-05-31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn504; Calibrated: 2016-07-26
- Phantom: ELI4.0
- Measurement SW: DASY4, Version 4.7 (80);

**Head front 3ch 26M2/Area Scan (5x21x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 2.50 W/kg

**Head front 3ch 26M2/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 54.62 V/m; Power Drift = -0.61 dB  
Peak SAR (extrapolated) = 2.71 W/kg  
**SAR(1 g) = 2.09 W/kg; SAR(10 g) = 1.64 W/kg**  
Maximum value of SAR (measured) = 2.41 W/kg



0 dB = 2.50 W/kg = 3.98 dBW/kg

Test Laboratory: HCT CO., LTD  
EUT Type: VHF DIGITAL TRANSCEIVER  
Liquid Temperature: 21.7 °C  
Ambient Temperature: 21.9 °C  
Test Date: 04/04/2017  
Plot No.: 5

**DUT: NX-3220; Type: bar**

Communication System: UID 0, 150MHz (0); Frequency: 158.05 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 158.05$  MHz;  $\sigma = 0.789$  S/m;  $\epsilon_r = 61.971$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3903; ConvF(13.33, 13.33, 13.33); Calibrated: 2016-09-28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2016-09-27
- Phantom: ELI v4.0
- Measurement SW: DASY52, Version 52.10 (0);

**Body Belt Clip KBH-11 7ch KNB-57L\_KRA-25/Area Scan (7x26x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 9.17 W/kg

**Body Belt Clip KBH-11 7ch KNB-57L\_KRA-25/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 97.87 V/m; Power Drift = -0.51 dB

Peak SAR (extrapolated) = 21.7 W/kg

**SAR(1 g) = 8.24 W/kg; SAR(10 g) = 4.67 W/kg**

Maximum value of SAR (measured) = 13.6 W/kg



**Body Belt Clip KBH-11 7ch KNB-57L\_KRA-25/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 97.87 V/m; Power Drift = -0.51 dB

Peak SAR (extrapolated) = 6.82 W/kg

**SAR(1 g) = 5.01 W/kg; SAR(10 g) = 3.87 W/kg**

Maximum value of SAR (measured) = 5.91 W/kg



Test Laboratory: HCT CO., LTD  
EUT Type: VHF DIGITAL TRANSCEIVER  
Liquid Temperature: 21.7 °C  
Ambient Temperature: 21.9 °C  
Test Date: 04/04/2017  
Plot No.: 6

**DUT: NX-3220; Type: bar**

Communication System: UID 0, 150MHz (0); Frequency: 158.05 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 158.05$  MHz;  $\sigma = 0.789$  S/m;  $\epsilon_r = 61.971$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3903; ConvF(13.33, 13.33, 13.33); Calibrated: 2016-09-28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2016-09-27
- Phantom: ELI v4.0
- Measurement SW: DASY52, Version 52.10 (0);

**Body Belt Clip KBH-11 7ch KNB-57L\_KRA-25 std/Area Scan (7x26x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 10.9 W/kg



**Body Belt Clip KBH-11 7ch KNB-57L\_KRA-25 std/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 96.08 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 27.7 W/kg

**SAR(1 g) = 9.84 W/kg; SAR(10 g) = 5.16 W/kg**

Maximum value of SAR (measured) = 17.3 W/kg



Test Laboratory: HCT CO., LTD  
EUT Type: VHF DIGITAL TRANSCEIVER  
Liquid Temperature: 21.7 °C  
Ambient Temperature: 21.9 °C  
Test Date: 04/04/2017  
Plot No.: 7

**DUT: NX-3220; Type: bar**

Communication System: UID 0, 150MHz (0); Frequency: 158.05 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 158.05$  MHz;  $\sigma = 0.789$  S/m;  $\epsilon_r = 61.971$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

## DASY5 Configuration:

- Probe: EX3DV4 - SN3903; ConvF(13.33, 13.33, 13.33); Calibrated: 2016-09-28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2016-09-27
- Phantom: ELI v4.0
- Measurement SW: DASY52, Version 52.10 (0);

**Body Belt Clip KBH-11 7ch KNB-57L\_KRA-25 basic/Area Scan (7x26x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 11.1 W/kg


**Body Belt Clip KBH-11 7ch KNB-57L\_KRA-25 basic/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 85.01 V/m; Power Drift = -0.28 dB

Peak SAR (extrapolated) = 25.3 W/kg

**SAR(1 g) = 9.05 W/kg; SAR(10 g) = 4.75 W/kg**

Maximum value of SAR (measured) = 15.9 W/kg



## Attachment 2. – Dipole Verification Plots

## ■ Verification Data (150 MHz Head)

Test Laboratory: HCT CO., LTD  
Input Power: 100 mW (20 dBm)  
Liquid Temp: 21.8 °C  
Test Date: 04/06/2017

### DUT: CLA-150; Type: CLA-150


Communication System: UID 0, CW; Frequency: 150 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 150 \text{ MHz}$ ;  $\sigma = 0.748 \text{ S/m}$ ;  $\epsilon_r = 50.332$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3968; ConvF(13.17, 13.17, 13.17); Calibrated: 2016-05-31;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn504; Calibrated: 2016-07-26
- Phantom: ELI4.0
- Measurement SW: DASY4, Version 4.7 (80);

**150MHz Head Verification/Area Scan (11x11x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (measured) = 0.441 W/kg

**150MHz Head Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 24.47 V/m; Power Drift = -0.23 dB  
Peak SAR (extrapolated) = 0.559 W/kg  
**SAR(1 g) = 0.373 W/kg; SAR(10 g) = 0.253 W/kg**  
Maximum value of SAR (measured) = 0.468 W/kg



0 dB = 0.441 W/kg = -3.55 dBW/kg

## ■ Verification Data (150 MHz Body)

Test Laboratory: HCT CO., LTD  
Input Power 100 mW (20 dBm)  
Liquid Temp: 21.7 °C  
Test Date: 04/04/2017

### DUT: CLA-150; Type: CLA-150


Communication System: UID 0, CW (0); Frequency: 150 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 150 \text{ MHz}$ ;  $\sigma = 0.783 \text{ S/m}$ ;  $\epsilon_r = 62.358$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section

#### DASY Configuration:

- Probe: EX3DV4 - SN3903; ConvF(13.33, 13.33, 13.33); Calibrated: 2016-09-28;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2016-09-27
- Phantom: ELI v4.0
- Measurement SW: DASY52, Version 52.8 (8);

**150MHz Body Verification/Area Scan (9x9x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (measured) = 0.335 W/kg

**150MHz Body Verification/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 19.95 V/m; Power Drift = -0.00 dB  
Peak SAR (extrapolated) = 0.520 W/kg  
**SAR(1 g) = 0.354 W/kg; SAR(10 g) = 0.241 W/kg**  
Maximum value of SAR (measured) = 0.380 W/kg



0 dB = 0.335 W/kg = -4.75 dBW/kg

## Attachment 3. – Probe Calibration Data

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**S** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client: **HCT (Dymstec)**

Certificate No: **EX3-3903\_Sep16**

## CALIBRATION CERTIFICATE

Object: **EX3DV4 - SN:3903**

Calibration procedure(s): **QA CAL-01.v9, QA CAL-12.v9, QA CAL-14.v4, QA CAL-23.v5,  
QA CAL-25.v6  
Calibration procedure for dosimetric E-field probes**

Calibration date: **September 28, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility, environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|------------------|-----------------------------------|------------------------|
| Power meter NRP            | SN: 104778       | 06-Apr-16 (No. 217-02288/02289)   | Apr-17                 |
| Power sensor NRP-Z91       | SN: 103244       | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Power sensor NRP-Z91       | SN: 103245       | 06-Apr-16 (No. 217-02289)         | Apr-17                 |
| Reference 20 dB Attenuator | SN: S5277 (20x)  | 05-Apr-16 (No. 217-02293)         | Apr-17                 |
| Reference Probe ES3DV2     | SN: 3013         | 31-Dec-15 (No. ES3-3013_Dec15)    | Dec-16                 |
| DAE4                       | SN: 660          | 23-Dec-15 (No. DAE4-660_Dec15)    | Dec-16                 |
| Secondary Standards        | ID               | Check Date (in house)             | Scheduled Check        |
| Power meter E4419B         | SN: GB41293874   | 06-Apr-16 (in house check Jun-16) | In house check: Jun-16 |
| Power sensor E4412A        | SN: MY41498087   | 06-Apr-16 (in house check Jun-16) | In house check: Jun-16 |
| Power sensor E4412A        | SN: 000110210    | 06-Apr-16 (in house check Jun-16) | In house check: Jun-16 |
| RF generator HP 6648C      | SN: US3642U01700 | 04-Aug-99 (in house check Jun-16) | In house check: Jun-16 |
| Network Analyzer HP 8753E  | SN: US37390585   | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

|                                                                                                                 | Name          | Function              | Signature |
|-----------------------------------------------------------------------------------------------------------------|---------------|-----------------------|-----------|
| Calibrated by:                                                                                                  | Michael Weber | Laboratory Technician |           |
| Approved by:                                                                                                    | Katja Pokovic | Technical Manager     |           |
| Issued: September 29, 2016                                                                                      |               |                       |           |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |               |                       |           |

Certificate No: EX3-3903\_Sep16

Page 1 of 11

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

#### Glossary:

|                       |                                                                                                                                                   |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                   | tissue simulating liquid                                                                                                                          |
| NORM <sub>x,y,z</sub> | sensitivity in free space                                                                                                                         |
| ConvF                 | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                        |
| DCP                   | diode compression point                                                                                                                           |
| CF                    | crest factor (1/duty_cycle) of the RF signal                                                                                                      |
| A, B, C, D            | modulation dependent linearization parameters                                                                                                     |
| Polarization $\phi$   | $\phi$ rotation around probe axis                                                                                                                 |
| Polarization $\theta$ | $\theta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\theta = 0$ is normal to probe axis |
| Connector Angle       | information used in DASY system to align probe sensor X to the robot coordinate system                                                            |

#### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

#### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\theta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the  $E^2$ -field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).

EX3DV4 – SN:3903

September 28, 2016

# Probe EX3DV4

## SN:3903

Manufactured: September 4, 2012  
Calibrated: September 28, 2016

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)

EX3DV4-- SN:3903

September 28, 2016

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3903

### Basic Calibration Parameters

|                                                    | Sensor X | Sensor Y | Sensor Z | Unc (k=2)    |
|----------------------------------------------------|----------|----------|----------|--------------|
| Norm ( $\mu\text{V}/(\text{V/m})^2$ ) <sup>A</sup> | 0.39     | 0.36     | 0.53     | $\pm 10.1\%$ |
| DCP (mV) <sup>B</sup>                              | 102.5    | 106.2    | 103.1    |              |

### Modulation Calibration Parameters

| UID | Communication System Name |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C   | D<br>dB | VR<br>mV | Unc <sup>C</sup><br>(k=2) |
|-----|---------------------------|---|---------|------------------------------|-----|---------|----------|---------------------------|
| 0   | CW                        | X | 0.0     | 0.0                          | 1.0 | 0.00    | 174.0    | $\pm 3.5\%$               |
|     |                           | Y | 0.0     | 0.0                          | 1.0 |         | 184.6    |                           |
|     |                           | Z | 0.0     | 0.0                          | 1.0 |         | 194.4    |                           |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter; uncertainty not required.

<sup>C</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4- SN:3903

September 28, 2016

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3903

### Calibration Parameter Determined in Head Tissue Simulating Media

| f (MHz) <sup>c</sup> | Relative Permittivity <sup>e</sup> | Conductivity (S/m) <sup>f</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>g</sup> | Depth <sup>g</sup> (mm) | Unc (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-----------|
| 150                  | 52.3                               | 0.76                            | 13.42   | 13.42   | 13.42   | 0.00               | 1.00                    | ± 13.3 %  |
| 300                  | 45.3                               | 0.87                            | 12.68   | 12.68   | 12.68   | 0.10               | 1.10                    | ± 13.3 %  |
| 450                  | 43.5                               | 0.87                            | 11.00   | 11.00   | 11.00   | 0.20               | 1.25                    | ± 13.3 %  |
| 750                  | 41.9                               | 0.89                            | 11.35   | 11.35   | 11.35   | 0.33               | 1.14                    | ± 12.0 %  |
| 835                  | 41.5                               | 0.90                            | 10.72   | 10.72   | 10.72   | 0.51               | 0.80                    | ± 12.0 %  |
| 900                  | 41.5                               | 0.97                            | 10.30   | 10.30   | 10.30   | 0.35               | 1.01                    | ± 12.0 %  |
| 1450                 | 40.5                               | 1.20                            | 8.76    | 8.76    | 8.76    | 0.39               | 0.80                    | ± 12.0 %  |
| 1750                 | 40.1                               | 1.37                            | 8.75    | 8.75    | 8.75    | 0.28               | 0.85                    | ± 12.0 %  |
| 1900                 | 40.0                               | 1.40                            | 8.41    | 8.41    | 8.41    | 0.28               | 0.84                    | ± 12.0 %  |
| 1950                 | 40.0                               | 1.40                            | 8.22    | 8.22    | 8.22    | 0.32               | 0.80                    | ± 12.0 %  |
| 2300                 | 39.5                               | 1.67                            | 8.01    | 8.01    | 8.01    | 0.32               | 0.80                    | ± 12.0 %  |
| 2450                 | 39.2                               | 1.80                            | 7.54    | 7.54    | 7.54    | 0.31               | 0.84                    | ± 12.0 %  |
| 2600                 | 39.0                               | 1.96                            | 7.42    | 7.42    | 7.42    | 0.31               | 0.86                    | ± 12.0 %  |
| 5250                 | 35.9                               | 4.71                            | 5.51    | 5.51    | 5.51    | 0.35               | 1.80                    | ± 13.1 %  |
| 5600                 | 35.5                               | 5.07                            | 4.78    | 4.78    | 4.78    | 0.45               | 1.80                    | ± 13.1 %  |
| 5750                 | 35.4                               | 5.22                            | 5.04    | 5.04    | 5.04    | 0.45               | 1.80                    | ± 13.1 %  |

<sup>c</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>e</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>g</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:3903

September 28, 2016

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3903

### Calibration Parameter Determined in Body Tissue Simulating Media

| f (MHz) <sup>c</sup> | Relative Permittivity <sup>e</sup> | Conductivity (S/m) <sup>f</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>g</sup> | Depth <sup>h</sup> (mm) | Unc (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-----------|
| 150                  | 61.9                               | 0.80                            | 13.33   | 13.33   | 13.33   | 0.00               | 1.00                    | ± 13.3 %  |
| 300                  | 58.2                               | 0.92                            | 12.07   | 12.07   | 12.07   | 0.08               | 1.10                    | ± 13.3 %  |
| 450                  | 56.7                               | 0.94                            | 11.95   | 11.95   | 11.95   | 0.10               | 1.20                    | ± 13.3 %  |
| 750                  | 55.5                               | 0.96                            | 10.50   | 10.50   | 10.50   | 0.29               | 1.13                    | ± 12.0 %  |
| 835                  | 55.2                               | 0.97                            | 10.42   | 10.42   | 10.42   | 0.55               | 0.80                    | ± 12.0 %  |
| 1750                 | 53.4                               | 1.49                            | 8.37    | 8.37    | 8.37    | 0.35               | 0.91                    | ± 12.0 %  |
| 1900                 | 53.3                               | 1.52                            | 8.10    | 8.10    | 8.10    | 0.37               | 0.80                    | ± 12.0 %  |
| 2450                 | 52.7                               | 1.95                            | 7.69    | 7.69    | 7.69    | 0.33               | 0.85                    | ± 12.0 %  |
| 2600                 | 52.5                               | 2.16                            | 7.45    | 7.45    | 7.45    | 0.33               | 0.90                    | ± 12.0 %  |
| 5250                 | 48.9                               | 5.36                            | 4.63    | 4.63    | 4.63    | 0.50               | 1.90                    | ± 13.1 %  |
| 5600                 | 48.5                               | 5.77                            | 3.85    | 3.85    | 3.85    | 0.60               | 1.90                    | ± 13.1 %  |
| 5750                 | 48.3                               | 5.94                            | 4.13    | 4.13    | 4.13    | 0.60               | 1.90                    | ± 13.1 %  |

<sup>c</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.


<sup>e</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>g</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:3903

September 28, 2016

### Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )

EX3DV4- SN:3903

September 28, 2016

### Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$





Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )

EX3DV4-SN:3903

September 28, 2016

### Dynamic Range f(SAR<sub>head</sub>) (TEM cell, f<sub>eval</sub> = 1900 MHz)




Uncertainty of Linearity Assessment:  $\pm 0.6\%$  (k=2)


EX3DV4- SN:3903

September 28, 2016

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid Error ( $\phi$ , $\theta$ ), $f = 900 \text{ MHz}$



EX3DV4- SN:3903

September 28, 2016

**DASY/EASY - Parameters of Probe: EX3DV4 - SN:3903****Other Probe Parameters**

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle (°)                           | -33.3      |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 9 mm       |
| Tip Diameter                                  | 2.5 mm     |
| Probe Tip to Sensor X Calibration Point       | 1 mm       |
| Probe Tip to Sensor Y Calibration Point       | 1 mm       |
| Probe Tip to Sensor Z Calibration Point       | 1 mm       |
| Recommended Measurement Distance from Surface | 1.4 mm     |

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client: **HCT (Dymstec)**

Certificate No: **EX3-3968\_May16**

## CALIBRATION CERTIFICATE

Object: **EX3DV4 - SN:3968**

Calibration procedure(s): **QA CAL-01.v9, QA CAL-12.v9, QA CAL-14.v4, QA CAL-23.v5,  
QA CAL-25.v6  
Calibration procedure for dosimetric E-field probes**

Calibration date: **May 31, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|------------------|-----------------------------------|------------------------|
| Power meter NRP            | SN: 104778       | 08-Apr-16 (No. 217-02288/02289)   | Apr-17                 |
| Power sensor NRP-Z91       | SN: 103244       | 08-Apr-16 (No. 217-02288)         | Apr-17                 |
| Power sensor NRP-Z91       | SN: 103245       | 08-Apr-16 (No. 217-02289)         | Apr-17                 |
| Reference 20 dB Attenuator | SN: S5277 (20x)  | 05-Apr-16 (No. 217-02293)         | Apr-17                 |
| Reference Probe ES3DV2     | SN: 3013         | 31-Dec-15 (No. ES3-3013_Dec15)    | Dec-16                 |
| DAE4                       | SN: 660          | 23-Dec-15 (No. DAE4-660_Dec15)    | Dec-16                 |
| Secondary Standards        | ID               | Check Date (in house)             | Scheduled Check        |
| Power meter E4419B         | SN: GB41293874   | 06-Apr-16 (No. 217-02285/02284)   | In house check: Jun-16 |
| Power sensor E4412A        | SN: MY41498087   | 08-Apr-16 (No. 217-02285)         | In house check: Jun-16 |
| Power sensor E4412A        | SN: 000110210    | 06-Apr-16 (No. 217-02284)         | In house check: Jun-16 |
| RF generator HP 8648C      | SN: US3642U01700 | 04-Aug-99 (in house check Apr-13) | In house check: Jun-16 |
| Network Analyzer HP 8753E  | SN: US37390585   | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

|                                                                                                                 | Name           | Function              | Signature |
|-----------------------------------------------------------------------------------------------------------------|----------------|-----------------------|-----------|
| Calibrated by:                                                                                                  | Jeton Kasirali | Laboratory Technician |           |
| Approved by:                                                                                                    | Katja Pokovic  | Technical Manager     |           |
| Issued: June 1, 2016                                                                                            |                |                       |           |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |                |                       |           |

Certificate No: EX3-3968\_May16

Page 1 of 11

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

**Glossary:**

|                        |                                                                                                                                                   |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                    | tissue simulating liquid                                                                                                                          |
| NORM <sub>x,y,z</sub>  | sensitivity in free space                                                                                                                         |
| ConvF                  | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                        |
| DCP                    | diode compression point                                                                                                                           |
| CF                     | crest factor (1/duty_cycle) of the RF signal                                                                                                      |
| A, B, C, D             | modulation dependent linearization parameters                                                                                                     |
| Polarization $\varphi$ | $\varphi$ rotation around probe axis                                                                                                              |
| Polarization $\theta$  | $\theta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\theta = 0$ is normal to probe axis |
| Connector Angle        | information used in DASY system to align probe sensor X to the robot coordinate system                                                            |

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Methods Applied and Interpretation of Parameters:**

- NORM<sub>x,y,z</sub>:** Assessed for E-field polarization  $\theta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub> = NORM<sub>x,y,z</sub> \* frequency\_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>:** DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR:** PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>:** A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters:** Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy):** in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset:** The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle:** The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).

EX3DV4 – SN:3968

May 31, 2016

# Probe EX3DV4

## SN:3968

Manufactured: September 30, 2013  
Calibrated: May 31, 2016

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)

EX3DV4- SN:3968

May 31, 2016

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3968

### Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k=2)     |
|-----------------------------------------------------------|----------|----------|----------|---------------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 0.36     | 0.35     | 0.42     | $\pm 10.1 \%$ |
| DCP (mV) <sup>B</sup>                                     | 101.7    | 102.0    | 97.4     |               |

### Modulation Calibration Parameters

| UID | Communication System Name |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C   | D<br>dB | VR<br>mV | Unc <sup>F</sup><br>(k=2) |
|-----|---------------------------|---|---------|------------------------------|-----|---------|----------|---------------------------|
| 0   | CW                        | X | 0.0     | 0.0                          | 1.0 | 0.00    | 134.4    | $\pm 2.5 \%$              |
|     |                           | Y | 0.0     | 0.0                          | 1.0 |         | 131.5    |                           |
|     |                           | Z | 0.0     | 0.0                          | 1.0 |         | 146.5    |                           |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X,Y,Z do not affect the  $E^2$  field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>F</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4- SN:3968

May 31, 2016

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3968

### Calibration Parameter Determined in Head Tissue Simulating Media

| f (MHz) <sup>c</sup> | Relative Permittivity <sup>e</sup> | Conductivity (S/m) <sup>f</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>g</sup> | Depth <sup>h</sup> (mm) | Unc (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-----------|
| 150                  | 52.3                               | 0.76                            | 13.17   | 13.17   | 13.17   | 0.00               | 1.00                    | ± 13.3 %  |
| 300                  | 45.3                               | 0.87                            | 12.10   | 12.10   | 12.10   | 0.09               | 1.10                    | ± 13.3 %  |
| 450                  | 43.5                               | 0.87                            | 10.73   | 10.73   | 10.73   | 0.16               | 1.20                    | ± 13.3 %  |
| 750                  | 41.9                               | 0.89                            | 10.27   | 10.27   | 10.27   | 0.51               | 0.80                    | ± 12.0 %  |
| 835                  | 41.5                               | 0.90                            | 9.97    | 9.97    | 9.97    | 0.42               | 0.87                    | ± 12.0 %  |
| 900                  | 41.5                               | 0.97                            | 9.62    | 9.62    | 9.62    | 0.25               | 1.20                    | ± 12.0 %  |
| 1450                 | 40.5                               | 1.20                            | 8.55    | 8.55    | 8.55    | 0.34               | 0.80                    | ± 12.0 %  |
| 1750                 | 40.1                               | 1.37                            | 8.45    | 8.45    | 8.45    | 0.33               | 0.80                    | ± 12.0 %  |
| 1900                 | 40.0                               | 1.40                            | 8.14    | 8.14    | 8.14    | 0.31               | 0.80                    | ± 12.0 %  |
| 1950                 | 40.0                               | 1.40                            | 7.89    | 7.89    | 7.89    | 0.37               | 0.80                    | ± 12.0 %  |
| 2300                 | 39.5                               | 1.67                            | 7.72    | 7.72    | 7.72    | 0.30               | 0.89                    | ± 12.0 %  |
| 2450                 | 39.2                               | 1.80                            | 7.30    | 7.30    | 7.30    | 0.35               | 0.80                    | ± 12.0 %  |
| 2600                 | 39.0                               | 1.96                            | 7.24    | 7.24    | 7.24    | 0.37               | 0.80                    | ± 12.0 %  |
| 5250                 | 35.9                               | 4.71                            | 5.35    | 5.35    | 5.35    | 0.30               | 1.80                    | ± 13.1 %  |
| 5600                 | 35.5                               | 5.07                            | 4.66    | 4.66    | 4.66    | 0.40               | 1.80                    | ± 13.1 %  |
| 5750                 | 35.4                               | 5.22                            | 4.78    | 4.78    | 4.78    | 0.40               | 1.80                    | ± 13.1 %  |

<sup>c</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>e</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>g</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:3968

May 31, 2016

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3968

### Calibration Parameter Determined in Body Tissue Simulating Media

| f (MHz) <sup>c</sup> | Relative Permittivity <sup>e</sup> | Conductivity (S/m) <sup>f</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>g</sup> | Depth <sup>h</sup> (mm) | Unc (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-----------|
| 150                  | 61.9                               | 0.80                            | 12.46   | 12.46   | 12.46   | 0.00               | 1.00                    | ± 13.3 %  |
| 300                  | 58.2                               | 0.92                            | 11.57   | 11.57   | 11.57   | 0.08               | 1.11                    | ± 13.3 %  |
| 450                  | 56.7                               | 0.94                            | 11.24   | 11.24   | 11.24   | 0.10               | 1.20                    | ± 13.3 %  |
| 750                  | 55.5                               | 0.96                            | 9.65    | 9.65    | 9.65    | 0.40               | 0.92                    | ± 12.0 %  |
| 835                  | 55.2                               | 0.97                            | 9.66    | 9.66    | 9.66    | 0.49               | 0.80                    | ± 12.0 %  |
| 1750                 | 53.4                               | 1.49                            | 8.16    | 8.16    | 8.16    | 0.34               | 0.80                    | ± 12.0 %  |
| 1900                 | 53.3                               | 1.52                            | 7.89    | 7.89    | 7.89    | 0.40               | 0.80                    | ± 12.0 %  |
| 2450                 | 52.7                               | 1.95                            | 7.31    | 7.31    | 7.31    | 0.41               | 0.80                    | ± 12.0 %  |
| 2600                 | 52.5                               | 2.16                            | 7.11    | 7.11    | 7.11    | 0.34               | 0.80                    | ± 12.0 %  |
| 5250                 | 48.9                               | 5.36                            | 4.37    | 4.37    | 4.37    | 0.50               | 1.90                    | ± 13.1 %  |
| 5600                 | 48.5                               | 5.77                            | 3.78    | 3.78    | 3.78    | 0.55               | 1.90                    | ± 13.1 %  |
| 5750                 | 48.3                               | 5.94                            | 3.92    | 3.92    | 3.92    | 0.60               | 1.90                    | ± 13.1 %  |

<sup>c</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.


<sup>e</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>g</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:3968

May 31, 2016

### Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )

EX3DV4- SN:3968

May 31, 2016

### Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$





Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  (k=2)

EX3DV4- SN:3968

May 31, 2016

### Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell, $f_{\text{eval}} = 1900 \text{ MHz}$ )




Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

EX3DV4- SN:3968


May 31, 2016

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error ( $\phi$ ,  $\theta$ ), f = 900 MHz



EX3DV4- SN:3968

May 31, 2016

**DASY/EASY - Parameters of Probe: EX3DV4 - SN:3968****Other Probe Parameters**

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle (°)                           | 63.4       |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 9 mm       |
| Tip Diameter                                  | 2.5 mm     |
| Probe Tip to Sensor X Calibration Point       | 1 mm       |
| Probe Tip to Sensor Y Calibration Point       | 1 mm       |
| Probe Tip to Sensor Z Calibration Point       | 1 mm       |
| Recommended Measurement Distance from Surface | 1.4 mm     |

## Attachment 4. – Dipole Calibration Data

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **HCT (Dymstec)**

Certificate No: **CLA150-4014\_Sep16**

## CALIBRATION CERTIFICATE

Object **CLA150 - SN: 4014**

Calibration procedure(s) **QA CAL-15.v8  
Calibration procedure for system validation sources below 700 MHz**

Calibration date: **September 15, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility; environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter NRP             | SN: 104778         | 06-Apr-16 (No. 217-02288/02289)   | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103244         | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Power sensor NRP-Z91        | SN: 103245         | 06-Apr-16 (No. 217-02289)         | Apr-17                 |
| Reference 30 dB Attenuator  | SN: 5129 (30b)     | 05-Apr-16 (No. 217-02294)         | Apr-17                 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 06-Apr-16 (No. 217-02295)         | Apr-17                 |
| Reference Probe EX3DV4      | SN: 3877           | 31-Dec-15 (No. EX3-3877_Dec15)    | Dec-16                 |
| DAE4                        | SN: 654            | 12-Aug-16 (No. DAE4-654_Aug16)    | Aug-17                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power meter E4419B          | SN: GB41293874     | 06-Apr-16 (No. 217-02285/02284)   | In house check: Jun-16 |
| Power sensor E4412A         | SN: MY41489067     | 06-Apr-16 (No. 217-02285)         | In house check: Jun-16 |
| Power sensor E4412A         | SN: 000110210      | 06-Apr-16 (No. 217-02284)         | In house check: Jun-16 |
| RF generator HP 8648C       | SN: US3642U01700   | 04-Aug-99 (in house check Jun-16) | In house check: Jun-16 |
| Network Analyzer HP 8753E   | SN: US37390585     | 18-Oct-01 (in house check Oct-15) | In house check: Oct-16 |

Calibrated by: **Jeton Kastrati** **Function: Laboratory Technician** **Signature: [Signature]**

Approved by: **Katja Pokovic** **Technical Manager** **Signature: [Signature]**

Issued: September 16, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

**Glossary:**

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The source is mounted in a touch configuration below the center marking of the flat phantom.
- Return Loss:** This parameter is measured with the source positioned under the liquid filled phantom (as described in the measurement condition clause). The Return Loss ensures low reflected power. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

### Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                      |                                  |                                  |
|----------------------|----------------------------------|----------------------------------|
| DASY Version         | DASY5                            | V52.8.8                          |
| Extrapolation        | Advanced Extrapolation           |                                  |
| Phantom              | ELI4 Flat Phantom                | Shell thickness: $2 \pm 0.2$ mm  |
| EUT Positioning      | Touch Position                   |                                  |
| Zoom Scan Resolution | $dx, dy = 4.0$ mm, $dz = 1.4$ mm | Graded Ratio = 1.4 (Z direction) |
| Frequency            | $150$ MHz $\pm 1$ MHz            |                                  |

### Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity           |
|-----------------------------------------|---------------------|----------------|------------------------|
| Nominal Head TSL parameters             | $22.0$ °C           | 52.3           | $0.76$ mho/m           |
| Measured Head TSL parameters            | $(22.0 \pm 0.2)$ °C | $50.2 \pm 6$ % | $0.76$ mho/m $\pm 6$ % |
| Head TSL temperature change during test | $< 0.5$ °C          | ----           | ----                   |

### SAR result with Head TSL

|                                                         |                  |                                |
|---------------------------------------------------------|------------------|--------------------------------|
| SAR averaged over $1$ cm <sup>3</sup> (1 g) of Head TSL | Condition        |                                |
| SAR measured                                            | 1 W input power  | $3.71$ W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W | $3.68$ W/kg $\pm 18.4$ % (k=2) |

|                                                           |                  |                                |
|-----------------------------------------------------------|------------------|--------------------------------|
| SAR averaged over $10$ cm <sup>3</sup> (10 g) of Head TSL | condition        |                                |
| SAR measured                                              | 1 W input power  | $2.47$ W/kg                    |
| SAR for nominal Head TSL parameters                       | normalized to 1W | $2.45$ W/kg $\pm 18.0$ % (k=2) |

### Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity           |
|-----------------------------------------|---------------------|----------------|------------------------|
| Nominal Body TSL parameters             | $22.0$ °C           | 61.9           | $0.80$ mho/m           |
| Measured Body TSL parameters            | $(22.0 \pm 0.2)$ °C | $60.6 \pm 6$ % | $0.84$ mho/m $\pm 6$ % |
| Body TSL temperature change during test | $< 0.5$ °C          | ----           | ----                   |

### SAR result with Body TSL

|                                                         |                  |                                |
|---------------------------------------------------------|------------------|--------------------------------|
| SAR averaged over $1$ cm <sup>3</sup> (1 g) of Body TSL | Condition        |                                |
| SAR measured                                            | 1 W input power  | $3.84$ W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W | $3.68$ W/kg $\pm 18.4$ % (k=2) |

|                                                           |                  |                                |
|-----------------------------------------------------------|------------------|--------------------------------|
| SAR averaged over $10$ cm <sup>3</sup> (10 g) of Body TSL | condition        |                                |
| SAR measured                                              | 1 W input power  | $2.55$ W/kg                    |
| SAR for nominal Body TSL parameters                       | normalized to 1W | $2.45$ W/kg $\pm 18.0$ % (k=2) |

**Appendix (Additional assessments outside the scope of SCS 0108)**

**Antenna Parameters with Head TSL**

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $47.0 \Omega + 6.9 j\Omega$ |
| Return Loss                          | -22.2 dB                    |

**Antenna Parameters with Body TSL**

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $49.0 \Omega + 6.5 j\Omega$ |
| Return Loss                          | -23.6 dB                    |

**Additional EUT Data**

|                 |               |
|-----------------|---------------|
| Manufactured by | SPEAG         |
| Manufactured on | June 30, 2014 |

## DASY5 Validation Report for Head TSL

Date: 15.09.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: CLA-150; Type: CLA-150; Serial: 4014**

Communication System: UID 0 - CW; Frequency: 150 MHz

Medium parameters used:  $f = 150$  MHz;  $\sigma = 0.76$  S/m;  $\epsilon_r = 50.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3877; ConvF(12.02, 12.02, 12.02); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn654; Calibrated: 12.08.2016
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP-1003
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### CLA Calibration for HSL-LF Tissue/CLA150, touch configuration, Pin=1W/Area Scan

(81x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 5.22 W/kg

### CLA Calibration for HSL-LF Tissue/CLA150, touch configuration, Pin=1W/Zoom Scan,


dist=1.4mm (8x10x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 82.90 V/m; Power Drift = -0.10 dB


Peak SAR (extrapolated) = 6.97 W/kg

SAR(1 g) = 3.71 W/kg; SAR(10 g) = 2.47 W/kg

Maximum value of SAR (measured) = 5.18 W/kg



# Impedance Measurement Plot for Head TSL



**DASY5 Validation Report for Body TSL**

Date: 15.09.2016

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: CLA-150; Type: CLA-150; Serial: 4014**

Communication System: UID 0 - CW; Frequency: 150 MHz

Medium parameters used:  $f = 150$  MHz;  $\sigma = 0.84$  S/m;  $\epsilon_r = 60.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

**DASY52 Configuration:**

- Probe: EX3DV4 - SN3877; ConvF(11.44, 11.44, 11.44); Calibrated: 31.12.2015;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn654; Calibrated: 12.08.2016
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:1003
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

**CLA Calibration for MSL-LF Tissue/CLA150, touch configuration, Pin=1W/Area Scan**

(81x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 5.42 W/kg


**CLA Calibration for MSL-LF Tissue/CLA150, touch configuration, Pin=1W/Zoom Scan,****dist=1.4mm (8x10x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 79.46 V/m; Power Drift = -0.06 dB


Peak SAR (extrapolated) = 7.21 W/kg

SAR(1 g) = 3.84 W/kg; SAR(10 g) = 2.55 W/kg

Maximum value of SAR (measured) = 5.37 W/kg



### Impedance Measurement Plot for Body TSL



## Attachment 5. – SAR Tissue Characterization

The brain and muscle mixtures consist of a viscous gel using hydrox-ethyl cellulose (HEC) gelling agent and saline solution (see Table 3.1). Preservation with a bactericide is added and visual inspection is made to make sure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. The mixture characterizations used for the brain and muscle tissue simulating liquids are according to the data by C. Gabriel and G. Hartsgrove.

| Ingredients<br>(% by weight)  | Frequency (MHz) |        |
|-------------------------------|-----------------|--------|
|                               | 150             |        |
| Tissue Type                   | Head            | Body   |
| Water                         | 38.35 %         | 46.6 % |
| Salt (NaCl)                   | 5.15 %          | 2.6 %  |
| Sugar                         | 55.5 %          | 49.7 % |
| HEC                           | 0.9 %           | 1.0 %  |
| Bactericide                   | 0.1 %           | 0.1 %  |
| Triton X-100                  | -               | -      |
| DGBE                          | -               | -      |
| Diethylene glycol hexyl ether | -               | -      |

|                           |                                                                    |        |                        |
|---------------------------|--------------------------------------------------------------------|--------|------------------------|
| Salt:                     | 99 % Pure Sodium Chloride                                          | Sugar: | 98 % Pure Sucrose      |
| Water:                    | De-ionized, 16M resistivity                                        | HEC:   | Hydroxyethyl Cellulose |
| DGBE:                     | 99 % Di(ethylene glycol) butyl ether,[2-(2-butoxyethoxy) ethanol]  |        |                        |
| Triton X-100(ultra pure): | Polyethylene glycol mono[4-(1,1,3,3-tetramethylbutyl)phenyl] ether |        |                        |

### Composition of the Tissue Equivalent Matter

## Attachment 6. – SAR SYSTEM VALIDATION

Per FCC KCB 865664 D02v01r02, SAR system validation status should be document to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in IEEE 1528-2003 and FCC KDB 865664 D01v01r04. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

| SAR System No. | Probe | Probe Type | Probe Calibration Point |     | Dipole | Date       | Dielectric Parameters |                       | CW Validation |                 |                | Modulation Validation |             |     |
|----------------|-------|------------|-------------------------|-----|--------|------------|-----------------------|-----------------------|---------------|-----------------|----------------|-----------------------|-------------|-----|
|                |       |            |                         |     |        |            | Measured Permittivity | Measured Conductivity | Sensitivity   | Probe Linearity | Probe Isotropy | MOD. Type             | Duty Factor | PAR |
| 9              | 3968  | EX3DV4     | Head                    | 150 | 4014   | 2016.09.23 | 51.4                  | 3.78                  | PASS          | PASS            | PASS           | N/A                   | N/A         | N/A |
| 5              | 3903  | EX3DV4     | Body                    | 150 | 4014   | 2016.09.23 | 62.2                  | 3.77                  | PASS          | PASS            | PASS           | N/A                   | N/A         | N/A |

**SAR System Validation Summary**

**Note;**

All measurement were performed using probes calibrated for CW signal only. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01r04. SAR system were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to KDB 865664 D01v01r04.