



Prüfbericht-Nr.: <i>Test report no.:</i>	CN26WR6N 001	Auftrags-Nr.: <i>Order no.:</i>	48301158	Seite 1 von 47 Page 1 of 47
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2026-01-30	
Auftraggeber: <i>Client:</i>	JVCKENWOOD Corporation 3-12, Moriyacho, Kanagawa-ku, Yokohama-shi, Kanagawa, Japan			
Prüfgegenstand: <i>Test item:</i>	BODY-WORN CAMERA			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	KWC-B51			
Auftrags-Inhalt: <i>Order content:</i>	Test Report for FCC SAR			
Prüfgrundlage: <i>Test specification:</i>	FCC 47 CFR §2.1093 IEEE Std 1528-2013 IEC/IEEE 62209-1528:2020 Published RF exposure KDB procedures			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2026-01-28			
Prüfmuster-Nr.: <i>Test sample no.:</i>	A004197665-001			
Prüfzeitraum: <i>Testing period:</i>	2026-08-31 - 2026-09-21			
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland Taiwan Ltd. New Taipei Branch			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland Taiwan Ltd. Taipei Testing Laboratories			
Prüfergebnis*: <i>Test result*:</i>	Pass			
überprüft von: <i>compiled by:</i>	genehmigt von: <i>authorized by:</i>			
Datum: <i>Date:</i>	2026-09-29	Ausstellungsdatum: <i>Issue date:</i>	2026-09-29	
Stellung / Position:	Senior Project Manager	Stellung / Position:	Project Engineer	
Sonstiges / Other:				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>				
Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>				
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet * Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.:
Test report no.:

CN26WR6N 001

Seite 2 von 47
Page 2 of 47

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TÜV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TÜV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

CONTENTS

HISTORY OF THIS TEST REPORT	5
1. GENERAL INFORMATION	6
1.1 STATEMENT OF COMPLIANCE	6
1.2 EQUIPMENT UNDER TEST (EUT) INFORMATION	7
1.2.1 GENERAL INFORMATION	7
1.2.2 WIRELESS TECHNOLOGIES	7
1.3 MAXIMUM CONDUCTED POWER	8
2. TEST SITES	9
2.1 TEST LABORATORY	9
2.2 TEST FACILITIES	9
2.3 LIST OF TEST AND MEASUREMENT INSTRUMENTS	10
3. MEASUREMENT UNCERTAINTY	11
4. TEST SPECIFICATION, METHODS AND PROCEDURES	13
5. RF EXPOSURE LIMITS	14
5.1 UNCONTROLLED ENVIRONMENT	14
5.2 CONTROLLED ENVIRONMENT	14
6. SAR MEASUREMENT SYSTEM	15
6.1 DEFINITION OF SPECIFIC ABSORPTION RATE (SAR)	15
6.2 SPEAG DASY SYSTEM	15
6.2.1 ROBOT	16
6.2.2 PROBES	17
6.2.3 DATA ACQUISITION ELECTRONICS (DAE)	17
6.2.4 PHANTOMS	18
6.2.5 DEVICE HOLDER	19
6.2.6 SYSTEM VALIDATION DIPOLES	19
6.2.7 TISSUE SIMULATING LIQUIDS	20
7. SAR MEASUREMENT PROCEDURE	22
7.1 AREA & ZOOM SCAN PROCEDURE	22
7.2 VOLUME SCAN PROCEDURE	22
7.3 POWER DRIFT MONITORING	23
7.4 SPATIAL PEAK SAR EVALUATION	23
7.5 SAR AVERAGED METHODS	23
8. SAR MEASUREMENT EVALUATION	24
8.1 TECHNICAL SPECIFICATION	24
9. TEST SET-UP AND OPERATION MODES	26
9.1 EUT CONFIGURATION AND SETTING	26
9.2 EUT TESTING POSITION	27

Prüfbericht - Nr.: CN26WR6N 001
Test Report No.Seite 4 von 47
Page 4 of 47

9.2.1	BODY EXPOSURE CONDITIONS	27
9.3	ANTENNA LOCATION	27
9.3.1	SAR TEST EXCLUSION EVALUATIONS	28
9.4	SIMULTANEOUS TRANSMISSION POSSIBILITIES	28
9.5	TISSUE VERIFICATION	29
9.6	SYSTEM VALIDATION.....	30
9.6.1	SYSTEM CHECK PROCEDURE.....	30
9.6.2	SYSTEM VERIFICATION	31
9.7	MAXIMUM OUTPUT POWER.....	32
9.7.1	MEASURED CONDUCTED POWER RESULT	32
9.8	SAR TESTING RESULTS.....	41
9.8.1	SAR TEST REDUCTION CONSIDERATIONS	41
9.8.2	SAR RESULTS FOR BODY EXPOSURE CONDITION (SEPARATION DISTANCE IS 0.5CM GAP).....	43
9.8.3	SAR MEASUREMENT VARIABILITY	45
9.8.4	MULTI-BAND TRANSMISSION EVALUATION	46
10.	APPENDIXES	47

APPENDIX A – SAR PLOTS OF SYSTEM VERIFICATION**APPENDIX B – SAR PLOTS OF SAR MEASUREMENT****APPENDIX C – CALIBRATION CERTIFICATE FOR PROBE AND DIPOLE****APPENDIX D – PHOTOGRAPHS OF THE TEST SET-UP**

Prüfbericht - Nr.: CN26WR6N 001
Test Report No.

Seite 5 von 47
Page 5 of 47

HISTORY OF THIS TEST REPORT

Revision	Description	Date Issued
R01	Original Release	2026-09-29

1. General Information

1.1 Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for the EUT are as follows:

Equipment Class	Operating Mode	Highest Reported Body SAR _{1g} (0 cm Gap) (W/kg)
PCB	LTE 2	0.940
	LTE 5	0.431
	LTE 7	0.196
	LTE 12	0.639
	LTE 13	0.629
	LTE 66	1.195
DTS	2.4G WLAN	0.626
NII	5G WLAN	0.628
Highest Simultaneous Transmission SAR		1.20

Note:

1. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6W/kg as averaged over any 1 gram of tissue; 10-gram SAR for Product Specific 10g SAR, limit: 4.0W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.
2. This device supports both LTE band 4 and band 66. The frequency span of LTE band 66 can completely cover LTE band 4, and they have the same tune-up power. SAR was tested for LTE band 66 only.

Prüfbericht - Nr.: CN26WR6N 001
Test Report No.

Seite 7 von 47
 Page 7 of 47

1.2 Equipment Under Test (EUT) Information

1.2.1 General Information

EUT Type	BODY-WORN CAMERA
Model Name	KWC-B51
FCC ID	K44529701
Antenna Type	Fixed Internal Antenna

1.2.2 Wireless Technologies

Tx Frequency Bands (Unit: MHz)	LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 66: 1710.7 MHz ~ 1780 MHz WLAN 2.4GHz Band: 2400 MHz ~ 2483.5 MHz WLAN U-NII 1: 5150 MHz ~ 5250 MHz WLAN U-NII 2: 5250 MHz ~ 5320 MHz WLAN U-NII 3: 5470 MHz ~ 5725 MHz WLAN U-NII 4: 5725 MHz ~ 5825 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz NFC : 13.56 MHz
Uplink Modulations	LTE: QPSK, 16QAM 802.11b: DSSS 802.11a/g/n/ac: OFDM Bluetooth: GFSK, $\pi/4$ -DQPSK, 8-DPSK Bluetooth LE: GFSK

1.3 Maximum Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Mode	LTE 2	LTE 4	LTE 5	LTE 7
QPSK/16QAM	21.5	22.0	23.5	21.5

Mode	LTE 12	LTE 13	LTE 66
QPSK/16QAM	23.5	23.5	22.0

Mode	2.4G WLAN	5.2G WLAN	5.3G WLAN	5.6G WLAN	5.8G WLAN
802.11a	N/A	12.5	12.0	13.5	11.0
802.11b	18.0	N/A	N/A	N/A	N/A
802.11g	16.0	N/A	N/A	N/A	N/A
802.11n HT20	16.5	12.0	11.5	13.0	10.5
802.11n HT40	17.0	12.0	12.0	13.5	10.5
802.11ac VHT80	N/A	10.5	11.5	13.5	10.5

Mode	2.4G Bluetooth
GFSK	2.0
8DPSK	1.0
LE	2.5

2. Test Sites

2.1 Test Laboratory

TÜV Rheinland Taiwan Ltd. Taipei Testing Laboratories

11F., No. 758, Sec. 4, Bade Rd., Songshan Dist., Taipei City 105 Taiwan (R.O.C.)

2.2 Test Facilities

TÜV Rheinland Taiwan Ltd. Taipei Testing Laboratories

No. 458-18, 458-19, Sec. 2, Fenliao Rd., Linkou Dist., New Taipei City 244 Taiwan (R.O.C.)

The tests at the test sites have been conducted under the supervision of a TÜV engineer.

FCC Registration No.: 180491 (TW3567)

ISED Registration No.: 25563 (TW3567)

2.3 List of Test and Measurement Instruments

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
E-field probes	SPEAG	EX3DV4	7400	2026/4/23	1 Year
Data Acquisition Electronics	SPEAG	DAE4	855	2026/4/20	1 Year
System Validation Dipole	SPEAG	D750V3	1199	2026/3/16	1 Year
System Validation Dipole	SPEAG	D835V2	4d058	2026/3/16	1 Year
System Validation Dipole	SPEAG	D1800V2	2d156	2026/3/12	1 Year
System Validation Dipole	SPEAG	D1900V2	5d090	2026/3/12	1 Year
System Validation Dipole	SPEAG	D2450V2	804	2026/3/10	1 Year
System Validation Dipole	SPEAG	D2600V2	1171	2026/3/10	1 Year
System Validation Dipole	SPEAG	D5GHzV2	1235	2026/3/18	1 Year
System Validation Dipole	SPEAG	D6.5GHzV2	1044	2026/4/22	1 Year
Dielectric Assessment Kit	SPEAG	DAK-3.5	1292	2026/4/21	1 Year
ENA	Agilent	E5080A	MY55200677	2026/1/15	1 Year
Power Meter	Anritsu	ML2495A	1901008	2026/2/24	1 Year
Power Sensor	Anritsu	MA2411B	1725269	2026/2/24	1 Year
Power Sensor	R&S	NRP33S	101622	2026/3/18	1 Year
Power Sensor	R&S	NRP33S	101623	2026/3/11	1 Year
Signal Analyzer	R&S	FSV40	101512	2026/2/24	1 Year
Signal Generator	R&S	SMB100A03	181334	2026/2/3	1 Year
Wireless Tester	Anritsu	MT8821C	6262044753	2026/7/2	1 Year
Digital Thermometer	Testo	608-H1	45207434	2025/11/21	1 Year
Directional coupler	Fairview Microwave	FMCP1025-20	A000553136-001	N/A	N/A
Power Amplifier	EMCI	EMC2830P	980352	N/A	N/A
Power Amplifier	mini-circuits	ZHL-42W	SN002101809	N/A	N/A
ELI Phantom	SPEAG	QDOVA002AA	TP-1153	N/A	N/A

3. Measurement Uncertainty

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in table below.

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor(a)	1/k(b)	$1/\sqrt{3}$	$1/\sqrt{6}$	$1/\sqrt{2}$

- (a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity
- (b) κ is the coverage factor

Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

SAR Uncertainty Budget According to IEC/IEEE 62209-1528 (Frequency band: 4MHz - 10GHz range)								
Symbol	Input quantity X_i (source of uncertainty)	Unc. Value	Prob. Dist.	Div.	ci (1g)	ci (10g)	Std.Unc. (1g) (±%)	Std.Unc. (10g) (±%)
Measurement system errors								
CF	Probe calibration (±%)	9.3	N	2	1	1	4.65	4.65
CF_{drift}	Probe calibration drift (±%)	1.0	N	1	1	1	1.0	1.0
LIN	Probe linearity and detection limit (±%)	4.7	R	1.732	1	1	2.7	2.7
BBS	Broadband signal (±%)	3.0	N	1	1	1	3.0	3.0
ISO	Probe isotropy (±%)	7.6	R	2	1	1	3.8	3.8
DAE	Other probe and data acquisition errors (±%)	0.3	N	1.732	1	1	0.17	0.17
AMB	RF ambient and noise (±%)	1.8	N	1	1	1	1.8	1.8
Δ_{xyz}	Probe positioning errors (± mm)	0.20	N	1	0.33	0.33	0.07	0.07
DAT	Data processing errors (±%)	3.5	N	1	1	1	3.5	3.5
Phantom and device (DUT or validation antenna) errors								
$LIQ(\sigma)$	Conductivity (meas.) DAK (±%)	3.5	N	1	0.78	0.71	2.73	2.49
$LIQ(T_c)$	Conductivity (temp.)(±%)	3	R	1	0.78	0.71	1.35	1.23
EPS	Phantom Permittivity (±%)	14	R	1.732	0.5	0.5	4.0	4.0
DIS	Distance DUT – TSL (±%)	2	N	1	2	2	4.0	4.0
D_{xyz}	Device Positioning (±%)	2	N	1	1	1	2.2	2.2
H	Device Holder (±%)	3.4	N	1	1	1	3.2	3.2
MOD	DUT Modulation (±%)	2.4	R	1.732	1	1	1.39	1.39
TAS	Time-average SAR (±%)	2.4	R	1.732	1	1	1.39	1.39
RF_{drift}	DUT drift (±%)	5	N	1	1	1	5.0	5.0
VAL	Val Antenna Unc. (±%)	0	N	1	1	1	0.0	0.0
Pin	Unc. Input Power (±%)	0	N	1	1	1	0.0	0.0
Corrections to the SAR result								
$C(\varepsilon, \sigma)$	Deviation to Target (±%)	1.9	N	1	1	0.84	1.9	1.6
$C(R)$	SAR scaling (±%)	0	R	$\sqrt{3}$	1	1	0.0	0.0
$u(\Delta SAR)$	Combined uncertainty						12.57	12.47
	Coverage Factor for 95%						K=2	K=2
U	Expanded uncertainty					U =	±25.14	±24.94

Uncertainty budget for frequency range 4 MHz to 10 GHz

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

4. Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR §2.1093, IEEE STD 1528-2013, the following FCC Published RF exposure KDB procedures & manufacturer KDB inquiries:

- KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- KDB 865664 D02 RF Exposure Reporting v01r02
- KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- KDB 447498 D04 Interim General RF Exposure Guidance v01
- KDB 941225 D05 SAR for LTE Devices v02r05

In addition to the above, the following information was used:

- [TCB workshop](#) October, 2014; Page 36, RF Exposure Procedures Update (Overlapping LTE Bands)

5. RF Exposure Limits

5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is average over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

6. SAR Measurement System

6.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)


SAR measurement can be related to the electrical field in the tissue by

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

6.2 SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY6 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.



DASY System Setup

6.2.1 Robot

The DASY system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



DASY6

6.2.2 Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.


Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	4 MHz to 10 GHz Linearity: ± 0.2 dB	
Directivity	± 0.1 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

6.2.3 Data Acquisition Electronics (DAE)

Model	DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	< 5 μ V (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	


6.2.4 Phantoms

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEC/IEEE 62209-1528. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	

Model	ELI	
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 4 MHz to 10 GHz. ELI is fully compatible with the IEC/IEEE 62209-1528 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	

6.2.5 Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	


Model	Laptop Extensions Kit	
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC/IEEE 62209-1528 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
Material	POM, Acrylic glass, Foam	

6.2.6 System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	300 MHz to 10 GHz	
Return Loss	> 20 dB	
Power Capability	> 100 W (f < 1GHz), > 40 W (f > 1GHz)	

6.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528 Appendix A.

The workshop effective February 19, 2019, FCC has permitted the use of single head tissue simulating liquid specified in IEC 62209 1 for all SAR tests.

The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

Targets of Tissue Simulating Liquid

Frequency (MHz)	Target Permittivity	Range of ±5%	Target Conductivity	Range of ±5%
For Head				
4	55	52.3 ~ 57.8	0.75	0.71 ~ 0.79
13	55	52.3 ~ 57.8	0.75	0.71 ~ 0.79
30	55	52.3 ~ 57.8	0.75	0.71 ~ 0.79
150	52.3	49.7 ~ 54.9	0.76	0.72 ~ 0.80
300	45.3	43.0 ~ 47.6	0.87	0.83 ~ 0.91
450	43.5	41.3 ~ 45.7	0.87	0.83 ~ 0.91
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1950	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2100	39.8	37.5 ~ 41.5	1.49	1.42 ~ 1.56
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06
3000	38.5	36.6 ~ 40.4	2.40	2.28 ~ 2.52
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06
4000	37.4	35.5 ~ 39.3	3.43	3.26 ~ 3.60
4500	36.8	35.0 ~ 38.6	3.94	3.74 ~ 4.14
5000	36.2	34.4 ~ 38.0	4.45	4.23 ~ 4.67
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89
5400	35.8	34.0 ~ 37.6	4.86	4.62 ~ 5.10
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53
6000	35.1	33.3 ~ 36.9	5.48	5.21 ~ 5.75
6500	34.5	32.8 ~ 36.2	6.07	5.77 ~ 6.37
7000	33.9	32.2 ~ 35.6	6.65	6.32 ~ 6.98
7500	33.3	31.6 ~ 35	7.24	6.88 ~ 7.6
8000	32.7	31.1 ~ 34.3	7.84	7.45 ~ 8.23
8500	32.1	30.5 ~ 33.7	8.46	8.04 ~ 8.88
9000	31.6	30 ~ 33.2	9.08	8.63 ~ 9.53
9500	31.0	29.5 ~ 32.6	9.71	9.22 ~ 10.2
10000	30.4	28.9 ~ 31.9	10.40	9.88 ~ 10.92

7. SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- (a) Make EUT to transmit maximum output power
- (b) Measure conducted output power through RF cable
- (c) Place the EUT in the specific position of phantom
- (d) Perform SAR testing steps on the DASY system
- (e) Record the SAR value

7.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

Items	≤ 2GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan ($\Delta x, \Delta y$)	≤ 15mm	≤ 12 mm	≤ 12 mm	≤ 10 mm	≤ 10 mm
Zoom Scan ($\Delta x, \Delta y$)	≤ 8 mm	≤ 5 mm	≤ 5 mm	≤ 4 mm	≤ 4 mm
Zoom Scan (Δz)	≤ 5 mm	≤ 5 mm	≤ 4 mm	≤ 3 mm	≤ 2 mm
Zoom Scan Volume	≥ 30 mm	≥ 30 mm	≥ 28 mm	≥ 25 mm	≥ 22 mm

Note:

When zoom scan is required and report SAR is ≤ 1.4 W/kg, the zoom scan resolution of $\Delta x / \Delta y$ (2-3 GHz): ≤ 8 mm, 3-4 GHz: ≤ 7 mm, 4-6 GHz: ≤ 5 mm) may be applied.

7.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

7.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

7.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

7.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

8. SAR Measurement Evaluation

8.1 Technical Specification

<Considerations Related to LTE for Setup and Testing>

This device contains LTE transmitter which follows 3GPP standards, is category 3, supports both QPSK and 16QAM, 64QAM, 256QAM modulations, and supported LTE band and channel bandwidth is listed in below. The output power was tested per 3GPP TS 36.521-1 maximum transmit procedures for both QPSK and 16QAM modulation. The results please refer to section 4.6 of this report.

EUT Supported LTE Band and Channel Bandwidth						
LTE Band	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz
2	V	V	V	V	V	V
4	V	V	V	V	V	V
5	V	V	V	V		
7			V	V	V	V
12	V	V	V	V		
13			V	V		
66	V	V	V	V	V	V

The LTE maximum power reduction (MPR) in accordance with 3GPP TS 36.101 is active all times during LTE operation. The allowed MPR for the maximum output power is specified in below.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2, and 3

Modulation	Channel bandwidth / Transmission bandwidth (NRB)						MPR (dB)
	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3
256 QAM	≥ 1						≤ 5

In addition, the device is compliant with additional maximum power reduction (A-MPR) requirements defined in 3GPP TS 36.101 section 6.2.4 that was disabled for all FCC compliance testing.

During LTE SAR testing, the related parameters of operating band, channel bandwidth, uplink channel number, modulation type, and RB was set in base station simulator. When the EUT has registered and communicated to base station simulator, the simulator set to make EUT transmitting the maximum radiated power.

<Considerations Related to WLAN for Setup and Testing>**Initial Test Configuration**

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

Subsequent Test Configuration

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.

SAR Test Configuration and Channel Selection

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

- 1) The channel closest to mid-band frequency is selected for SAR measurement.
- 2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

Test Reduction for U-NII-1 (5.2 GHz) and U-NII-2A (5.3 GHz) Bands

For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following.

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition).
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration.

9. Test Set-up and Operation Modes

9.1 EUT Configuration and Setting

<Connections between EUT and System Simulator>

For WWAN SAR testing, the EUT was linked and controlled by base station emulator Anritsu MT8821C is used for LTE. Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

<Considerations Related to WLAN for Setup and Testing>

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.



9.2 EUT Testing Position

According to technical standards, the EUT is tested for SAR compliance in the use configurations described in the following subsections.

9.2.1 Body Exposure Conditions

The EUT was tested for six surfaces of the EUT as front surface, back surface, left side, right side, top side, and bottom side. The separation distance between the EUT and phantom is 0mm.

9.3 Antenna Location



9.3.1 SAR Test Exclusion Evaluations

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

One way of determining the threshold power level for the secondary transmitter ($P_{\text{available}}$) is to calculate it from the measured psSAR of the primary transmitter (psSAR_1) according to Formula (18):

$$P_{\text{available}} = P_{\text{max},m} \left[(SAR_{\text{lim}} - SAR_1) / SAR_{\text{lim}} \right] \quad (18)$$

where $P_{\text{max},m}$ is the maximum threshold exclusion power level, which is calculated by $SAR_{\text{lim}} \times m$, and m is an averaging mass.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Max. Primary Transmitter					Secondary Transmitter	
Max. Primary Transmitter (dBm)	Max. Primary Transmitter (mW)	P_{max} (mW)	psSAR ₁ (W/kg)	SAR _{lim} (W/kg)	$P_{\text{available}}$ (mW)	Require SAR Testing?
2.14	1.64	7.3	1.23	1.6	1.69	Not Required

9.4 Simultaneous Transmission Possibilities

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous TX Combination	Capable Transmit Configurations	Body Exposure Condition
1	WWAN + WLAN 2.4GHz	Yes
2	WWAN + WLAN 5GHz	Yes

Note :

1. The 2.4G WLAN and 5G WLAN cannot transmit simultaneously.

9.5 Tissue Verification

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.

The measuring results for tissue simulating liquid are shown as below.

Tissue Type	Frequency (MHz)	Ambient Temp. (°C)	Liquid Temp. (°C)	Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Target Conductivity (σ)	Target Permittivity (ϵ_r)	Conductivity Deviation (%)	Permittivity Deviation (%)	Test Date
Head	750	23.4	22.3	0.913	43.217	0.89	41.9	2.58	3.14	2026/9/16
Head	835	23.2	22.1	0.945	43.137	0.9	41.5	5.00	3.94	2026/9/17
Head	1800	23.1	22.5	1.406	40.926	1.4	40	0.43	2.32	2026/9/16
Head	1900	23.4	22.2	1.465	40.843	1.4	40	4.64	2.11	2026/8/31
Head	2450	23.6	22.2	1.811	39.933	1.8	39.2	0.61	1.87	2026/9/18
Head	2600	23.2	22.1	1.929	39.674	1.96	39	-1.58	1.73	2026/8/31
Head	5250	23.5	22.4	4.535	35.312	4.71	35.9	-3.72	-1.64	2026/9/21
Head	5600	23.5	22.4	4.925	34.697	5.07	35.5	-2.86	-2.26	2026/9/21
Head	5750	23.5	22.4	5.096	34.429	5.22	35.4	-2.38	-2.74	2026/9/21


Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within $\pm 5\%$ of the target values. Liquid temperature during the SAR testing must be within $\pm 2^\circ\text{C}$.

9.6 System Validation

9.6.1 System check Procedure

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (1W is used for 13MHz, 250 mW is used for 450 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

9.6.2 System Verification

The measuring results for system check are shown as below.

Frequency (MHz)	Measured SAR 1g(W/kg)	normalized SAR 1g(W/kg)	Targeted SAR 1g(W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
750	2.06	8.24	8.76	-5.94	1199	7400	855
835	2.44	9.76	9.51	2.63	4d058	7400	855
1800	9.51	38.04	38.7	-1.71	2d156	7400	855
1900	9.37	37.48	40.2	-6.77	5d090	7400	855
2450	12.30	49.2	52.6	-6.46	804	7400	855
2600	13.00	52	55.3	-5.97	1171	7400	855
5250	7.34	73.4	79.8	-8.02	1235	7400	855
5600	7.83	78.3	80.6	-2.85	1235	7400	855
5750	7.50	75	77.9	-3.72	1235	7400	855

Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

9.7 Maximum Output Power

9.7.1 Measured Conducted Power Result

All Rate have been tested, the Worst average power (Unit: dBm) is shown as below.

LTE B2/BW=1.4M			Average Conducted Power(dBm)			LTE B2/BW=3M			Average Conducted Power(dBm)		
Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)			Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)		
			18607 / 1850.7	18900 / 1880	19193 / 1909.3				18615 / 1851.5	18900 / 1880	19185 / 1908.5
QPSK	1/0	21.00	20.64	20.81	20.53	QPSK	1/0	21.00	20.79	20.95	20.54
	1/3	21.00	20.70	20.99	20.79		1/7	21.50	20.79	21.01	20.78
	1/5	21.00	20.51	20.88	20.39		1/14	21.00	20.34	20.98	20.75
	3/0	21.00	20.64	20.61	20.32		8/0	21.00	20.61	20.61	20.24
	3/1	21.00	20.55	20.88	20.41		8/3	21.00	20.33	20.59	20.34
	3/3	21.00	20.46	20.67	20.22		8/7	21.00	20.19	20.52	20.33
	6/0	20.00	19.55	19.86	19.48		15/0	20.00	19.74	19.93	19.75
16QAM	1/0	20.00	19.61	19.89	19.86	16QAM	1/0	20.00	19.79	19.77	19.47
	1/3	20.00	19.65	19.97	19.95		1/7	20.50	20.22	20.17	19.96
	1/5	20.50	19.72	20.18	19.79		1/14	20.50	19.86	20.07	19.79
	3/0	20.00	19.69	19.92	19.67		8/0	19.50	19.01	18.82	18.51
	3/1	20.50	19.77	20.04	19.73		8/3	19.00	18.82	18.96	18.56
	3/3	20.50	19.56	20.01	19.57		8/7	19.50	18.49	19.02	18.65
	6/0	19.00	18.80	18.84	18.54		15/0	19.00	18.76	18.96	18.73
LTE B2/BW=5M			Average Conducted Power (dBm)			LTE B2/BW=10M			Average Conducted Power (dBm)		
Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)			Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)		
			18625 / 1852.5	18900 / 1880	19175 / 1907.5				18650 / 1855	18900 / 1880	19150 / 1905
QPSK	1/0	21.00	20.81	20.68	20.35	QPSK	1/0	21.00	20.65	20.78	20.47
	1/12	21.00	20.38	20.82	20.99		1/24	21.00	20.61	20.73	20.37
	1/24	21.00	20.32	20.84	20.43		1/49	21.00	20.37	20.59	20.49
	12/0	21.00	20.28	20.56	20.14		25/0	21.00	20.33	20.62	20.18
	12/6	21.00	20.25	20.56	20.19		25/12	21.00	20.17	20.56	20.63
	12/13	21.00	20.37	20.68	20.25		25/25	21.00	20.29	20.61	20.13
	25/0	20.00	19.45	19.99	19.58		50/0	20.00	19.62	19.92	19.52
16QAM	1/0	20.00	19.63	19.58	18.84	16QAM	1/0	20.00	19.69	19.18	19.37
	1/12	20.50	19.33	20.22	19.71		1/24	20.00	19.68	19.99	19.63
	1/24	20.00	19.09	19.93	19.63		1/49	20.00	18.56	19.74	19.56
	12/0	19.00	18.62	18.69	18.36		25/0	19.00	18.61	18.93	18.59
	12/6	19.00	18.46	18.87	18.87		25/12	19.50	18.49	19.05	18.75
	12/13	19.00	18.29	18.76	18.45		25/25	19.00	18.57	18.82	18.66
	25/0	19.00	18.62	18.92	18.54		50/0	19.00	18.59	18.74	18.48
LTE B2/BW=15M			Average Conducted Power (dBm)			LTE B2/BW=20M			Average Conducted Power (dBm)		
Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)			Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)		
			18675 / 1857.5	18900 / 1880	19125 / 1902.5				18700 / 1860	18900 / 1880	19100 / 1900
QPSK	1/0	21.00	20.69	20.75	20.54	QPSK	1/0	21.50	20.33	21.16	20.48
	1/37	21.00	20.71	20.99	20.68		1/49	21.00	20.52	20.84	20.46
	1/74	21.00	20.53	20.77	20.44		1/99	21.00	20.56	20.44	20.66
	36/0	21.00	20.25	20.52	20.25		50/0	21.50	20.45	21.06	20.25
	36/19	21.00	20.29	20.57	20.12		50/24	21.00	20.41	20.61	20.25
	36/39	21.00	20.22	20.62	20.25		50/50	21.00	20.37	20.53	20.23
	75/0	20.00	19.58	19.84	19.44		100/0	20.00	19.65	19.82	19.35
16QAM	1/0	20.00	19.79	19.56	19.41	16QAM	1/0	19.50	19.19	18.93	18.83
	1/37	20.00	19.65	19.69	19.91		1/49	20.50	19.21	20.04	19.58
	1/74	20.00	19.47	19.43	19.53		1/99	19.50	18.79	18.94	19.23
	36/0	19.00	18.63	18.72	18.51		50/0	19.00	18.43	18.58	18.45
	36/19	19.00	18.46	18.95	18.91		50/24	19.00	18.42	18.84	18.36
	36/39	19.00	18.52	18.79	18.42		50/50	19.00	18.49	18.69	18.62
	75/0	19.00	18.56	18.72	18.52		100/0	19.00	18.45	18.84	18.43

LTE B4/BW=1.4M		Average Conducted Power(dBm)				LTE B4/BW=3M		Average Conducted Power(dBm)			
Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)			Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)		
			19957 / 1710.7	20175 / 1732.5	20393 / 1754.3				19965 / 1711.5	20175 / 1732.5	20385 / 1753.5
QPSK	1/0	21.50	20.73	21.12	20.88	QPSK	1/0	21.50	21.17	20.76	21.29
	1/2	21.50	21.25	21.22	20.93		1/7	21.50	21.16	21.31	21.14
	1/5	21.50	20.96	21.07	20.88		1/14	21.00	20.84	20.98	20.84
	3/0	21.50	21.15	21.18	21.09		8/0	20.50	20.19	20.23	20.15
	3/1	21.50	21.22	21.22	21.32		8/3	20.50	20.08	20.21	19.99
	3/3	21.50	21.09	21.13	21.09		8/7	20.50	20.09	20.09	20.04
	6/0	20.50	20.12	20.08	20.11		15/0	20.50	20.13	20.12	20.03
16QAM	1/0	20.50	20.45	20.38	19.56	16QAM	1/0	20.50	20.06	20.17	20.04
	1/2	21.00	20.49	20.55	19.54		1/7	21.00	20.56	20.44	20.02
	1/5	20.50	20.32	20.23	20.12		1/14	20.50	20.27	20.27	20.12
	3/0	20.50	20.33	20.22	20.12		8/0	19.50	19.26	19.47	19.03
	3/1	21.00	20.56	20.35	20.18		8/3	19.50	19.29	19.36	19.07
	3/3	21.00	20.25	20.59	20.27		8/7	19.50	19.04	19.26	19.03
	6/0	19.50	19.18	19.35	19.08		15/0	19.50	19.18	19.32	19.18
LTE B4/BW=5M		Average Conducted Power (dBm)				LTE B4/BW=10M		Average Conducted Power (dBm)			
Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)			Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)		
			19975/ 1712.5	20175/ 1732.5	20375/ 1752.5				20000/ 1715	20175/ 1732.5	20350/ 1750
QPSK	1/0	21.50	20.97	21.03	21.15	QPSK	1/0	21.00	20.75	20.65	20.90
	1/12	21.00	20.90	20.85	20.89		1/24	21.00	20.97	20.93	21.08
	1/24	21.00	20.78	20.95	20.79		1/49	21.00	20.99	20.77	20.91
	12/0	20.50	20.09	20.01	20.01		25/0	21.00	20.55	20.45	20.71
	12/6	20.50	20.04	20.07	20.13		25/12	21.00	20.54	20.55	20.71
	12/13	20.50	20.01	20.01	20.31		25/25	21.00	20.39	20.56	20.69
	25/0	20.50	20.02	20.17	20.48		50/0	20.00	19.88	19.88	19.93
16QAM	1/0	20.50	20.26	20.24	20.08	16QAM	1/0	21.00	20.36	20.09	20.61
	1/12	20.50	19.99	20.28	20.29		1/24	20.50	19.86	20.01	20.29
	1/24	20.00	19.66	19.82	19.21		1/49	20.00	19.65	19.64	19.92
	12/0	19.50	19.12	19.23	19.09		25/0	19.50	19.04	19.06	19.05
	12/6	19.50	19.03	19.23	19.17		25/12	19.50	19.03	19.12	19.04
	12/13	19.50	18.84	19.19	19.11		25/25	19.50	19.14	19.11	19.22
	25/0	19.50	19.01	19.11	19.16		50/0	19.50	19.15	19.22	19.35
LTE B4/BW=15M		Average Conducted Power (dBm)				LTE B4/BW=20M		Average Conducted Power (dBm)			
Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)			Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)		
			20025 / 1717.5	20175 / 1732.5	20325 / 1747.5				20050 / 1720	20175 / 1732.5	20300 / 1745
QPSK	1/0	21.50	21.15	21.02	21.09	QPSK	1/0	22.00	20.94	21.59	21.21
	1/37	21.50	20.87	21.02	21.12		1/49	21.50	20.88	21.38	21.09
	1/74	21.00	20.69	20.66	20.81		1/99	21.50	20.96	21.08	21.38
	36/0	21.00	20.36	20.55	20.57		50/0	21.50	20.98	21.39	21.22
	36/19	21.00	20.33	20.51	20.63		50/24	21.50	21.11	21.09	21.12
	36/39	21.00	20.53	20.53	20.71		50/50	21.50	20.94	21.12	21.15
	75/0	20.50	19.82	19.91	20.08		100/0	20.50	20.11	20.11	20.23
16QAM	1/0	20.00	19.96	19.84	19.84	16QAM	1/0	20.50	19.81	19.76	20.01
	1/37	21.00	19.82	20.29	20.65		1/49	20.50	19.81	20.01	20.21
	1/74	20.50	19.69	20.05	19.77		1/99	20.50	20.14	20.31	19.97
	36/0	19.50	19.36	18.89	19.26		50/0	19.50	19.05	19.15	19.42
	36/19	19.50	18.92	19.05	18.99		50/24	19.50	19.22	19.07	19.14
	36/39	19.50	18.81	18.98	19.21		50/50	19.50	19.07	19.23	19.23
	75/0	19.50	18.87	18.84	19.02		100/0	19.50	19.07	19.00	19.24

LTE B5/BW=1.4M		Average Conducted Power (dBm)				LTE B5/BW=3M		Average Conducted Power (dBm)			
Modula- -tion	RB Size/ Offset	Max. Tune-up	Channel/Frequency(MHz)			Modula- -tion	RB Size/ Offset	Max. Tune-up	Channel/Frequency(MHz)		
			20407 / 824.7	20525 / 836.5	20643 / 848.3				20415 / 825.5	20525 / 836.5	20635 / 847.5
QPSK	1/0	23.00	22.75	22.79	22.78	QPSK	1/0	23.50	22.47	22.82	23.03
	1/3	23.50	22.93	23.02	23.04		1/7	23.50	23.01	22.72	22.86
	1/5	23.50	23.06	22.88	23.02		1/14	23.00	22.58	22.85	22.59
	3/0	23.50	22.95	23.04	23.05		8/0	22.50	21.97	22.11	22.04
	3/1	23.50	22.98	23.01	23.07		8/3	22.50	21.97	22.10	22.09
	3/3	23.50	22.97	23.09	23.01		8/7	22.50	21.95	22.08	21.95
	6/0	22.50	21.98	22.15	22.01		15/0	22.50	21.95	22.01	21.98
16QAM	1/0	22.00	21.56	21.36	21.85	16QAM	1/0	22.50	22.04	21.51	21.72
	1/3	22.50	22.07	21.56	21.65		1/7	22.50	22.36	22.16	22.07
	1/5	22.00	21.94	21.88	21.53		1/14	22.50	22.19	22.07	21.79
	3/0	22.50	21.96	22.11	22.18		8/0	21.00	20.85	20.78	20.82
	3/1	22.50	22.19	22.42	22.22		8/3	21.50	21.05	20.86	20.98
	3/3	22.50	22.15	22.39	21.49		8/7	21.50	21.01	20.84	20.81
	6/0	21.50	21.18	20.97	20.86		15/0	21.50	20.85	20.97	21.06
LTE B5/BW=5M		Average Conducted Power(dBm)				LTE B5/BW=10M		Average Conducted Power(dBm)			
Modula- -tion	RB Size/ Offset	Max. Tune-up	Channel/Frequency(MHz)			Modula- -tion	RB Size/ Offset	Max. Tune-up	Channel/Frequency(MHz)		
			20425 / 826.5	20525 / 836.5	20625 / 846.5				20450 / 829	20525 / 836.5	20600 / 844
QPSK	1/0	23.00	22.68	22.57	22.89	QPSK	1/0	23.50	22.74	23.18	22.69
	1/12	23.50	23.01	22.88	22.78		1/24	23.00	22.95	22.82	22.74
	1/24	23.00	22.78	22.66	22.66		1/49	23.50	22.93	23.03	21.66
	12/0	23.00	22.63	22.66	22.71		25/0	23.50	22.95	23.14	23.01
	12/6	23.00	22.72	22.65	22.66		25/12	23.50	23.03	22.95	23.10
	12/13	23.00	22.58	22.51	22.64		25/25	23.00	22.95	22.93	22.93
	25/0	22.00	21.85	21.98	21.93		50/0	22.00	21.99	21.93	21.95
16QAM	1/0	22.00	21.29	21.35	21.86	16QAM	1/0	22.00	21.68	21.67	21.58
	1/12	22.00	21.53	21.77	21.59		1/24	22.00	21.67	21.37	21.88
	1/24	21.50	21.46	21.34	21.12		1/49	22.00	21.64	21.21	21.44
	12/0	21.00	20.83	20.98	20.79		25/0	21.50	21.02	20.92	21.04
	12/6	21.00	20.84	20.67	20.79		25/12	21.50	21.06	20.93	21.01
	12/13	21.00	20.71	20.66	20.72		25/25	21.50	21.03	21.03	20.86
	25/0	21.00	20.98	20.85	20.87		50/0	21.50	21.06	20.86	20.85

LTE B7/BW=5M		Average Conducted Power (dBm)				LTE B7/BW=10M		Average Conducted Power (dBm)			
Modulation	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)		
			20775 / 2502.5	21100 / 2535	21425 / 2567.5				20800 / 2505	21100 / 2535	21400 / 2565
QPSK	1/0	21.00	20.51	20.62	20.32	QPSK	1/0	21.00	20.56	20.55	20.32
	1/12	21.00	20.57	20.68	20.53		1/24	21.00	20.54	20.81	20.28
	1/24	21.00	20.37	20.53	20.34		1/49	21.00	20.55	20.45	20.37
	12/0	20.50	20.26	20.44	20.22		25/0	20.50	20.38	20.36	20.17
	12/6	20.50	20.36	20.35	20.27		25/12	20.50	20.32	20.42	20.36
	12/13	20.50	20.19	20.36	20.26		25/25	20.50	20.32	20.39	20.21
	25/0	20.00	19.58	19.73	19.51		50/0	20.00	19.82	19.85	19.72
16QAM	1/0	19.50	19.22	19.18	18.63	16QAM	1/0	20.00	19.65	18.94	19.15
	1/12	20.00	19.06	19.63	19.25		1/24	19.50	19.03	19.26	19.03
	1/24	19.50	19.22	19.44	18.82		1/49	19.50	19.44	19.22	19.14
	12/0	19.00	18.49	18.47	18.44		25/0	19.00	18.68	18.67	18.34
	12/6	19.00	18.53	18.65	18.33		25/12	19.00	18.75	18.81	18.62
	12/13	19.00	18.42	18.53	18.32		25/25	19.00	18.67	18.83	18.54
	25/0	19.00	18.59	18.81	18.36		50/0	19.00	18.69	18.71	18.59
LTE B7/BW=15M		Average Conducted Power (dBm)				LTE B7/BW=20M		Average Conducted Power (dBm)			
Modulation	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)		
			20825 / 2507.5	21100 / 2535	21375 / 2562.5				20850 / 2510	21100 / 2535	21350 / 2560
QPSK	1/0	20.50	20.26	20.36	20.17	QPSK	1/0	21.50	20.24	21.09	20.21
	1/37	21.00	20.52	20.57	20.45		1/49	21.00	20.49	20.41	20.58
	1/74	21.00	20.38	20.59	20.31		1/99	20.50	20.24	20.24	20.21
	36/0	20.50	20.18	20.12	20.16		50/0	21.00	20.39	20.91	20.44
	36/19	20.50	20.27	20.26	20.47		50/24	20.50	20.49	20.45	20.34
	36/39	20.50	20.14	20.26	20.04		50/50	20.50	20.39	20.49	20.44
	75/0	19.50	19.47	19.52	19.39		100/0	19.50	19.39	19.47	19.31
16QAM	1/0	19.50	19.21	19.17	19.45	16QAM	1/0	19.00	18.69	18.48	18.77
	1/37	20.00	19.24	19.41	19.55		1/49	20.00	19.34	19.84	19.16
	1/74	19.50	19.39	19.43	19.35		1/99	19.50	18.96	19.11	18.97
	36/0	19.00	18.48	18.59	18.37		50/0	18.50	18.34	18.39	18.41
	36/19	19.50	18.48	19.31	18.34		50/24	19.00	18.34	18.41	18.52
	36/39	19.00	18.45	18.57	18.34		50/50	18.50	18.33	18.36	18.23
	75/0	18.50	18.48	18.48	18.41		100/0	19.00	18.57	18.46	18.26

LTE B12/BW=1.4M		Average Conducted Power (dBm)				LTE B12/BW=3M		Average Conducted Power (dBm)			
Modulation	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)		
			23017 / 699.7	23095 / 707.5	23173 / 715.3				23025 / 700.5	23095 / 707.5	23165 / 714.5
QPSK	1/0	23.00	22.54	22.84	22.93	QPSK	1/0	23.50	22.98	22.89	23.07
	1/2	23.00	22.83	22.85	22.79		1/7	23.50	22.99	23.04	23.03
	1/5	23.00	22.61	22.54	22.72		1/14	23.50	22.78	22.75	23.19
	3/0	23.00	22.75	22.96	22.79		8/0	22.50	21.98	22.08	21.93
	3/1	23.00	22.81	22.95	22.88		8/3	22.50	21.96	22.03	21.95
	3/3	23.00	22.79	22.88	22.77		8/7	22.50	21.85	22.02	21.89
	6/0	22.00	21.76	21.84	21.81		15/0	22.50	21.98	22.01	22.08
16QAM	1/0	22.00	21.64	21.74	21.69	16QAM	1/0	22.50	22.07	21.68	21.84
	1/2	22.00	21.23	21.21	21.62		1/7	22.50	22.12	21.95	22.26
	1/5	22.00	21.34	21.22	21.53		1/14	22.50	22.10	21.79	21.82
	3/0	22.50	21.95	22.11	21.88		8/0	21.00	20.76	20.75	20.98
	3/1	22.50	22.01	22.15	22.05		8/3	21.00	20.78	20.77	20.84
	3/3	22.50	22.03	22.07	21.89		8/7	21.00	20.71	20.63	20.95
	6/0	21.00	20.93	20.84	20.81		15/0	21.50	21.02	20.97	21.09
LTE B12/BW=5M		Average Conducted Power (dBm)				LTE B12/BW=10M		Average Conducted Power (dBm)			
Modulation	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)		
			23035 / 701.5	23095 / 707.5	23155 / 713.5				23060 / 704	23095 / 707.5	23130 / 711
QPSK	1/0	23.00	22.86	22.89	22.63	QPSK	1/0	23.50	22.69	23.28	22.79
	1/12	23.50	22.94	23.28	23.12		1/24	23.00	22.81	22.75	22.58
	1/24	23.50	23.14	22.62	22.88		1/49	23.00	22.82	22.62	22.71
	12/0	22.50	22.03	21.91	21.84		25/0	23.00	22.82	23.22	22.96
	12/6	22.50	22.02	21.98	21.96		25/12	23.00	22.87	22.88	22.89
	12/13	22.50	22.06	22.08	21.97		25/25	23.00	22.92	22.78	22.92
	25/0	22.00	21.97	21.94	21.88		50/0	22.00	21.96	21.89	21.95
16QAM	1/0	22.00	21.78	21.21	21.19	16QAM	1/0	22.00	21.54	21.17	21.95
	1/12	22.00	21.63	21.43	21.71		1/24	22.50	22.04	21.84	21.64
	1/24	22.00	21.84	21.32	21.63		1/49	22.00	21.69	21.69	21.59
	12/0	21.00	20.80	20.82	20.81		25/0	21.50	21.12	21.03	21.01
	12/6	21.00	20.88	20.73	20.91		25/12	21.50	21.06	21.04	21.15
	12/13	21.00	20.97	20.85	20.82		25/25	21.50	20.96	21.05	20.86
	25/0	21.00	20.92	20.99	20.79		50/0	21.50	20.98	20.91	21.05

LTE B66/BW=1.4M			Average Conducted Power(dBm)			LTE B66/BW=3M			Average Conducted Power(dBm)		
Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)			Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)		
			131979 / 1710.7	132322 / 1745	132665 / 1779.3				131987 / 1711.5	132322 / 1745	132657 / 1778.5
QPSK	1/0	21.00	20.86	21.03	20.85	QPSK	1/0	21.00	20.73	20.74	20.76
	1/3	21.50	21.08	21.05	21.01		1/7	21.00	20.81	20.56	20.54
	1/5	21.50	21.01	21.01	20.68		1/14	21.00	20.72	20.72	20.57
	3/0	21.00	20.91	20.75	20.76		8/0	20.50	20.37	20.36	20.35
	3/1	21.00	20.85	20.78	20.65		8/3	20.50	20.38	20.39	20.34
	3/3	21.00	20.83	20.81	20.58		8/7	20.50	20.33	20.38	20.33
	6/0	20.00	19.85	19.85	19.78		15/0	20.00	19.98	19.88	19.74
16QAM	1/0	21.00	20.13	20.28	20.83	16QAM	1/0	21.00	20.62	20.42	20.36
	1/3	21.00	20.19	20.33	20.95		1/7	21.00	20.21	20.53	20.44
	1/5	21.00	19.72	20.14	20.83		1/14	20.50	20.18	20.36	20.48
	3/0	20.00	19.88	19.81	19.64		8/0	19.50	18.97	19.23	19.03
	3/1	20.00	19.84	19.85	19.58		8/3	19.50	18.95	19.12	19.05
	3/3	20.00	19.94	19.92	19.54		8/7	19.50	19.01	19.08	19.11
	6/0	19.00	18.92	18.92	18.71		15/0	19.00	18.85	18.81	18.76
LTE B66/BW=5M			Average Conducted Power (dBm)			LTE B66/BW=10M			Average Conducted Power (dBm)		
Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)			Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)		
			131997 / 1712.5	132322 / 1745	132647 / 1777.5				132022 / 1715	132322 / 1745	132622 / 1775
QPSK	1/0	21.00	20.69	20.92	20.79	QPSK	1/0	21.00	20.79	20.74	20.78
	1/12	21.50	21.31	20.82	20.83		1/24	21.50	21.15	20.91	20.96
	1/24	21.00	20.71	20.72	20.55		1/49	21.00	20.72	20.75	20.63
	12/0	20.50	20.44	20.32	20.25		25/0	20.50	20.48	20.45	20.49
	12/6	20.50	20.41	20.30	20.24		25/12	20.50	20.49	20.48	20.47
	12/13	20.50	20.39	20.33	20.11		25/25	20.50	20.45	20.50	20.44
	25/0	20.00	19.91	19.76	19.81		50/0	20.00	19.89	19.88	19.83
16QAM	1/0	20.00	19.62	19.75	19.86	16QAM	1/0	20.50	20.29	19.76	20.35
	1/12	20.00	19.72	19.82	19.57		1/24	21.50	20.45	19.75	20.55
	1/24	20.00	19.48	19.73	19.11		1/49	20.50	20.44	19.68	19.73
	12/0	19.50	19.06	18.75	18.92		25/0	19.50	19.03	18.72	19.03
	12/6	19.50	19.01	18.80	18.91		25/12	19.50	19.04	18.79	18.92
	12/13	19.50	19.04	18.74	18.77		25/25	19.50	19.06	18.86	18.89
	25/0	19.50	19.01	18.89	18.79		50/0	19.00	18.89	18.95	18.73
LTE B66/BW=15M			Average Conducted Power (dBm)			LTE B66/BW=20M			Average Conducted Power (dBm)		
Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)			Modula-tion	RB Size/Offset	Max. Tune-up	Channel/Frequency(MHz)		
			132047 / 1717.5	132322 / 1745	132597 / 1772.5				132072 / 1720	132322 / 1745	132572 / 1770
QPSK	1/0	21.00	20.67	20.66	20.74	QPSK	1/0	22.00	21.53	21.78	21.68
	1/37	21.00	20.70	20.73	20.86		1/49	22.00	21.23	21.44	21.58
	1/74	21.00	20.58	20.61	20.49		1/99	22.00	21.67	21.43	21.21
	36/0	21.00	20.44	20.46	20.52		50/0	22.00	20.64	21.73	20.55
	36/19	20.50	20.45	20.44	20.48		50/24	21.00	20.65	20.59	20.59
	36/39	20.50	20.41	20.45	20.35		50/50	21.00	20.68	20.51	20.58
	75/0	20.00	19.84	19.78	19.79		100/0	20.00	19.85	19.75	19.74
16QAM	1/0	21.00	20.56	20.34	20.07	16QAM	1/0	20.00	19.25	19.96	20.07
	1/37	20.50	20.23	20.05	19.98		1/49	20.00	19.79	19.87	20.54
	1/74	20.50	20.17	20.33	20.04		1/99	20.00	19.89	19.55	20.08
	36/0	19.00	18.81	18.99	18.92		50/0	19.00	18.58	18.74	18.81
	36/19	19.00	18.85	18.94	18.89		50/24	19.00	18.76	18.77	18.79
	36/39	19.00	18.83	18.93	18.81		50/50	19.00	18.80	18.69	18.81
	75/0	19.00	18.87	18.82	18.79		100/0	19.00	18.78	18.73	18.78

<Bluetooth>

Channel	Frequency	Average Conducted Power (dBm)	
		DH5	3DH5
CH 00	2402	1.53	0.67
CH 39	2441	1.69	0.95
CH 78	2480	1.63	0.79
Max. Tune-up		2.00	1.00

<Bluetooth LE>

Channel	Frequency	Average Conducted Power (dBm)	
		1Mbps	2Mbps
CH 00	2402	1.64	1.72
CH 19	2440	1.79	2.14
CH 39	2480	1.70	1.85
Max. Tune-up		2.00	2.50

<WLAN 2.4G>

2.4G WIFI 1TX					
Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Average Power (dBm)	Max. Tune up
802.11b	1	2412	1	17.50	18.00
	7	2442		17.54	18.00
	13	2472		17.48	18.00
802.11g	1	2412	6	15.87	16.00
	7	2442		15.89	16.00
	13	2472		15.88	16.00
802.11n HT20	1	2412	MCS0	16.36	16.50
	7	2442		16.32	16.50
	13	2472		16.32	16.50
802.11n HT40	3	2422	MCS0	16.72	17.00
	7	2442		16.85	17.00
	11	2462		16.34	17.00

<WLAN 5G>

5.2G WIFI_1TX						
Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Average Power (dBm)	Max. Tune up
5.2G	802.11a	36	5180	6	11.42	12.00
		40	5200		11.40	12.00
		44	5220		11.81	12.00
		48	5240		12.13	12.50
	802.11n HT20	36	5180	MCS0	10.90	12.00
		40	5200		11.25	12.00
		44	5220		11.40	12.00
		48	5240		11.57	12.00
	802.11n HT40	38	5190	MCS0	11.50	12.00
		46	5230		11.86	12.00
	802.11ac VHT80	42	5210	NSS1 MCS0	10.13	10.50

5.3G WIFI_1TX						
Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Average Power (dBm)	Max. Tune up
5.3G	802.11a	52	5260	6	11.59	12.00
		56	5280		11.48	11.50
		60	5300		11.65	12.00
		64	5320		11.72	12.00
	802.11n HT20	52	5260	MCS0	10.99	11.00
		56	5280		10.85	11.00
		60	5300		11.25	11.50
		64	5320		11.09	11.50
	802.11n HT40	54	5270	MCS0	11.58	12.00
		62	5310		11.29	11.50
	802.11ac VHT80	58	5290	NSS1 MCS0	11.14	11.50

5.6G WIFI_1TX						
Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Average Power (dBm)	Max. Tune up
5.6G	802.11a	100	5500	6	13.08	13.50
		120	5600		11.62	12.00
		124	5620		11.33	11.50
		132	5660		10.54	11.00
		140	5700		10.62	11.00
	802.11n HT20	100	5500	MCS0	12.53	13.00
		120	5600		11.18	11.50
		124	5620		11.05	11.50
		132	5660		10.21	10.50
		140	5700		10.30	10.50
	802.11n HT40	102	5510	MCS0	13.04	13.50
		116	5590		12.00	12.00
		126	5630		11.21	11.50
		134	5670		11.39	11.50
	802.11ac VHT80	106	5530	NSS1 MCS0	13.01	13.50
		122	5610		11.71	12.00

5.8G WIFI_1TX						
Band	Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Average Power (dBm)	Max. Tune up
5.8G	802.11a	149	5745	6	9.76	11.00
		157	5785		9.97	11.00
		165	5825		10.86	11.00
	802.11n HT20	149	5745	MCS0	9.31	10.50
		157	5785		9.58	10.50
		165	5825		10.35	10.50
	802.11n HT40	151	5755	MCS0	9.70	10.50
		159	5795		10.11	10.50
	802.11ac VHT80	155	5775	NSS1 MCS0	10.33	10.50

9.8 SAR Testing Results

9.8.1 SAR Test Reduction Considerations

<KDB 447498 D01, General RF Exposure Guidance>

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1) ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- (2) ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3) ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

<KDB 941225 D05, SAR Evaluation Considerations for LTE Devices>

- (1) QPSK with 1 RB and 50% RB allocation

Start with the largest channel bandwidth and measure SAR, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

- (2) QPSK with 100% RB allocation

SAR is not required when the highest maximum output power for 100% RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

- (3) Higher order modulations

SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> 1/2$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

- (4) Other channel bandwidth

SAR is required when the highest maximum output power of the smaller channel bandwidth is $> 1/2$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

<KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>

- (1) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is ≤ 0.4 W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
- (2) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is ≤ 0.8 W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is ≤ 1.2 W/kg.
- (3) For WLAN 5 GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is > 0.8 W/kg, SAR is required for the subsequent highest measured output power channel until the reported SAR result is ≤ 1.2 W/kg or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is ≤ 1.2 W/kg.

9.8.2 SAR Results for Body Exposure Condition (Separation Distance is 0.5cm Gap)

Plot No.	Band	BW (MHz)	Modulation	RB#	RB Offset	Test Position	Ch.	Freq. (MHz)	Measured Conducted Power (dBm)	Max. Tune-up Power (dBm)	Tune-up Scaling Factor	Duty Cycle Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Reported SAR-1g (W/kg)
	LTE Band 2	20M	QPSK	1	0	Front	18900	1880	21.16	21.50	1.081	1.000	0.04	0.030	0.032
	LTE Band 2	20M	QPSK	50	0	Front	18900	1880	21.16	21.50	1.081	1.000	-0.02	0.033	0.036
	LTE Band 2	20M	QPSK	1	0	Back	18900	1880	21.16	21.50	1.081	1.000	-0.09	0.111	0.120
	LTE Band 2	20M	QPSK	50	0	Back	18900	1880	21.16	21.50	1.081	1.000	-0.15	0.137	0.148
	LTE Band 2	20M	QPSK	1	0	Left Side	18900	1880	21.16	21.50	1.081	1.000	0	<0.001	<0.001
	LTE Band 2	20M	QPSK	50	0	Left Side	18900	1880	21.16	21.50	1.081	1.000	0	<0.001	<0.001
	LTE Band 2	20M	QPSK	1	0	Right Side	18900	1880	21.16	21.50	1.081	1.000	0.09	0.689	0.745
	LTE Band 2	20M	QPSK	50	0	Right Side	18900	1880	21.16	21.50	1.081	1.000	0.04	0.697	0.754
	LTE Band 2	20M	QPSK	1	0	Top Side	18900	1880	21.16	21.50	1.081	1.000	0	<0.001	<0.001
	LTE Band 2	20M	QPSK	50	0	Top Side	18900	1880	21.16	21.50	1.081	1.000	0	<0.001	<0.001
	LTE Band 2	20M	QPSK	1	0	Bottom Side	18900	1880	21.16	21.50	1.081	1.000	0.03	0.017	0.018
	LTE Band 2	20M	QPSK	50	0	Bottom Side	18900	1880	21.16	21.50	1.081	1.000	-0.07	0.016	0.017
	LTE Band 2	20M	QPSK	50	0	Right Side	18700	1860	20.33	21.50	1.309	1.000	0.05	0.570	0.746
14	LTE Band 2	20M	QPSK	50	0	Right Side	19100	1900	20.48	21.50	1.265	1.000	-0.04	0.743	0.940
	LTE Band 5	10M	QPSK	1	0	Front	20525	836.5	23.18	23.50	1.076	1.000	0.11	0.349	0.376
	LTE Band 5	10M	QPSK	25	0	Front	20525	836.5	23.18	23.50	1.076	1.000	0.12	0.321	0.346
	LTE Band 5	10M	QPSK	1	0	Back	20525	836.5	23.18	23.50	1.076	1.000	0.09	0.232	0.250
	LTE Band 5	10M	QPSK	25	0	Back	20525	836.5	23.18	23.50	1.076	1.000	0.03	0.222	0.239
	LTE Band 5	10M	QPSK	1	0	Left Side	20525	836.5	23.18	23.50	1.076	1.000	-0.09	0.00191	0.002
	LTE Band 5	10M	QPSK	25	0	Left Side	20525	836.5	23.18	23.50	1.076	1.000	-0.16	0.00164	0.002
	LTE Band 5	10M	QPSK	1	0	Right Side	20525	836.5	23.18	23.50	1.076	1.000	0.06	0.278	0.299
	LTE Band 5	10M	QPSK	25	0	Right Side	20525	836.5	23.18	23.50	1.076	1.000	-0.08	0.207	0.223
	LTE Band 5	10M	QPSK	1	0	Top Side	20525	836.5	23.18	23.50	1.076	1.000	0.17	0.019	0.020
	LTE Band 5	10M	QPSK	25	0	Top Side	20525	836.5	23.18	23.50	1.076	1.000	-0.07	0.022	0.024
	LTE Band 5	10M	QPSK	1	0	Bottom Side	20525	836.5	23.18	23.50	1.076	1.000	0.05	0.370	0.398
181	LTE Band 5	10M	QPSK	25	0	Bottom Side	20525	836.5	23.18	23.50	1.076	1.000	-0.08	0.400	0.431
	LTE Band 7	20M	QPSK	1	0	Front	21100	2535	21.09	21.50	1.099	1.000	-0.05	0.025	0.027
	LTE Band 7	20M	QPSK	50	0	Front	21100	2535	21.09	21.50	1.099	1.000	-0.06	0.014	0.015
	LTE Band 7	20M	QPSK	1	0	Back	21100	2535	21.09	21.50	1.099	1.000	0.07	0.040	0.044
	LTE Band 7	20M	QPSK	50	0	Back	21100	2535	21.09	21.50	1.099	1.000	0.09	0.029	0.032
	LTE Band 7	20M	QPSK	1	0	Left Side	21100	2535	21.09	21.50	1.099	1.000	0	<0.001	<0.001
	LTE Band 7	20M	QPSK	50	0	Left Side	21100	2535	21.09	21.50	1.099	1.000	0	<0.001	<0.001
	LTE Band 7	20M	QPSK	1	0	Right Side	21100	2535	21.09	21.50	1.099	1.000	0.15	0.152	0.167
	LTE Band 7	20M	QPSK	50	0	Right Side	21100	2535	21.09	21.50	1.099	1.000	-0.04	0.127	0.140
	LTE Band 7	20M	QPSK	1	0	Top Side	21100	2535	21.09	21.50	1.099	1.000	-0.08	0.027	0.030
	LTE Band 7	20M	QPSK	50	0	Top Side	21100	2535	21.09	21.50	1.099	1.000	0.06	0.018	0.020
	LTE Band 7	20M	QPSK	1	0	Bottom Side	21100	2535	21.09	21.50	1.099	1.000	0.05	0.016	0.018
	LTE Band 7	20M	QPSK	50	0	Bottom Side	21100	2535	21.09	21.50	1.099	1.000	0.01	0.018	0.020
	LTE Band 7	20M	QPSK	1	0	Right Side	20850	2510	20.24	21.50	1.337	1.000	0.08	0.123	0.164
30	LTE Band 7	20M	QPSK	1	0	Right Side	21350	2560	20.21	21.50	1.346	1.000	-0.05	0.146	0.196
	LTE Band 12	10M	QPSK	1	0	Front	23095	707.5	23.28	23.50	1.052	1.000	0.02	0.108	0.114
	LTE Band 12	10M	QPSK	25	0	Front	23095	707.5	23.28	23.50	1.052	1.000	-0.05	0.097	0.102
	LTE Band 12	10M	QPSK	1	0	Back	23095	707.5	23.28	23.50	1.052	1.000	-0.07	0.219	0.230
	LTE Band 12	10M	QPSK	25	0	Back	23095	707.5	23.28	23.50	1.052	1.000	0.12	0.198	0.208
	LTE Band 12	10M	QPSK	1	0	Left Side	23095	707.5	23.28	23.50	1.052	1.000	-0.07	0.00828	0.009
	LTE Band 12	10M	QPSK	25	0	Left Side	23095	707.5	23.28	23.50	1.052	1.000	-0.09	0.00818	0.009
37	LTE Band 12	10M	QPSK	1	0	Right Side	23095	707.5	23.28	23.50	1.052	1.000	-0.19	0.607	0.639
	LTE Band 12	10M	QPSK	25	0	Right Side	23095	707.5	23.28	23.50	1.052	1.000	0.04	0.539	0.567
	LTE Band 12	10M	QPSK	1	0	Top Side	23095	707.5	23.28	23.50	1.052	1.000	-0.08	0.0062	0.007
	LTE Band 12	10M	QPSK	25	0	Top Side	23095	707.5	23.28	23.50	1.052	1.000	-0.15	0.0056	0.006
	LTE Band 12	10M	QPSK	1	0	Bottom Side	23095	707.5	23.28	23.50	1.052	1.000	0.02	0.117	0.123
	LTE Band 12	10M	QPSK	25	0	Bottom Side	23095	707.5	23.28	23.50	1.052	1.000	0.03	0.108	0.114

Plot No.	Band	BW (MHz)	Modulation	RB#	RB Offset	Test Position	Ch.	Freq. (MHz)	Measured Conducted Power (dBm)	Max. Tune-up Power (dBm)	Tune-up Scaling Factor	Duty Cycle Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Reported SAR-1g (W/kg)
	LTE Band 13	10M	QPSK	1	0	Front	23230	782	23.41	23.50	1.021	1.000	-0.06	0.277	0.283
	LTE Band 13	10M	QPSK	25	0	Front	23230	782	23.41	23.50	1.021	1.000	-0.03	0.212	0.216
	LTE Band 13	10M	QPSK	1	0	Back	23230	782	23.41	23.50	1.021	1.000	0.02	0.570	0.582
	LTE Band 13	10M	QPSK	25	0	Back	23230	782	23.41	23.50	1.021	1.000	0.06	0.509	0.520
	LTE Band 13	10M	QPSK	1	0	Left Side	23230	782	23.41	23.50	1.021	1.000	-0.15	0.014	0.014
	LTE Band 13	10M	QPSK	25	0	Left Side	23230	782	23.41	23.50	1.021	1.000	-0.11	0.012	0.012
50	LTE Band 13	10M	QPSK	1	0	Right Side	23230	782	23.41	23.50	1.021	1.000	-0.13	0.616	0.629
	LTE Band 13	10M	QPSK	25	0	Right Side	23230	782	23.41	23.50	1.021	1.000	0.07	0.501	0.511
	LTE Band 13	10M	QPSK	1	0	Top Side	23230	782	23.41	23.50	1.021	1.000	-0.02	0.020	0.020
	LTE Band 13	10M	QPSK	25	0	Top Side	23230	782	23.41	23.50	1.021	1.000	0.04	0.018	0.018
	LTE Band 13	10M	QPSK	1	0	Bottom Side	23230	782	23.41	23.50	1.021	1.000	0.01	0.423	0.432
	LTE Band 13	10M	QPSK	25	0	Bottom Side	23230	782	23.41	23.50	1.021	1.000	-0.05	0.353	0.360
	LTE Band 66	20M	QPSK	1	0	Front	132322	1745	21.78	22.00	1.052	1.000	0.02	0.197	0.207
	LTE Band 66	20M	QPSK	50	0	Front	132322	1745	21.78	22.00	1.052	1.000	-0.06	0.185	0.195
	LTE Band 66	20M	QPSK	1	0	Back	132322	1745	21.78	22.00	1.052	1.000	0.08	0.226	0.238
	LTE Band 66	20M	QPSK	50	0	Back	132322	1745	21.78	22.00	1.052	1.000	-0.11	0.299	0.315
	LTE Band 66	20M	QPSK	1	0	Left Side	132322	1745	21.78	22.00	1.052	1.000	0.03	0.059	0.062
	LTE Band 66	20M	QPSK	50	0	Left Side	132322	1745	21.78	22.00	1.052	1.000	0.07	0.052	0.055
	LTE Band 66	20M	QPSK	1	0	Right Side	132322	1745	21.78	22.00	1.052	1.000	0.16	1.060	1.115
	LTE Band 66	20M	QPSK	1	0	Right Side	132322	1745	21.78	22.00	1.052	1.000	0.11	0.778	0.818
	LTE Band 66	20M	QPSK	1	0	Top Side	132322	1745	21.78	22.00	1.052	1.000	0	<0.001	<0.001
	LTE Band 66	20M	QPSK	50	0	Top Side	132322	1745	21.78	22.00	1.052	1.000	0	<0.001	<0.001
	LTE Band 66	20M	QPSK	1	0	Bottom Side	132322	1745	21.78	22.00	1.052	1.000	0.02	0.154	0.162
	LTE Band 66	20M	QPSK	50	0	Bottom Side	132322	1745	21.78	22.00	1.052	1.000	-0.04	0.152	0.160
	LTE Band 66	20M	QPSK	1	0	Right Side	132072	1720	21.53	22.00	1.114	1.000	-0.09	0.743	0.828
86	LTE Band 66	20M	QPSK	1	0	Right Side	132572	1770	21.68	22.00	1.076	1.000	0.08	1.110	1.195

Plot No.	Band	Mode	Test Position	Ch.	Frequency (MHz)	Measured Conducted Power (dBm)	Max. Tune-up Power (dBm)	Tune-up Scaling Factor	Duty Cycle Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Reported SAR-1g (W/kg)
	WLAN2.4G	802.11b 1Mbps	Front	6	2437	17.54	18.00	1.112	1.000	-0.09	0.057	0.063
	WLAN2.4G	802.11b 1Mbps	Back	6	2437	17.54	18.00	1.112	1.000	0.04	0.143	0.159
109	WLAN2.4G	802.11b 1Mbps	Left Side	6	2437	17.54	18.00	1.112	1.000	-0.15	0.563	0.626
	WLAN2.4G	802.11b 1Mbps	Right Side	6	2437	17.54	18.00	1.112	1.000	-0.08	0.00481	0.005
	WLAN2.4G	802.11b 1Mbps	Top Side	6	2437	17.54	18.00	1.112	1.000	0.03	0.022	0.024
	WLAN2.4G	802.11b 1Mbps	Bottom Side	6	2437	17.54	18.00	1.112	1.000	-0.04	0.00307	0.003
	WLAN5G	802.11a 6Mbps	Front	48	5240	12.13	12.50	1.089	1.004	-0.14	0.024	0.026
	WLAN5G	802.11a 6Mbps	Back	48	5240	12.13	12.50	1.089	1.004	0	<0.001	<0.001
121	WLAN5G	802.11a 6Mbps	Left Side	48	5240	12.13	12.50	1.089	1.004	0.08	0.549	0.600
	WLAN5G	802.11a 6Mbps	Right Side	48	5240	12.13	12.50	1.089	1.004	0	<0.001	<0.001
	WLAN5G	802.11a 6Mbps	Top Side	48	5240	12.13	12.50	1.089	1.004	-0.08	0.012	0.013
	WLAN5G	802.11a 6Mbps	Bottom Side	48	5240	12.13	12.50	1.089	1.004	0	<0.001	<0.001
	WLAN5G	802.11a 6Mbps	Front	64	5320	11.72	12.00	1.067	1.000	-0.09	0.036	0.038
	WLAN5G	802.11a 6Mbps	Back	64	5320	11.72	12.00	1.067	1.000	0	<0.001	<0.001
129	WLAN5G	802.11a 6Mbps	Left Side	64	5320	11.72	12.00	1.067	1.000	0.16	0.560	0.597
	WLAN5G	802.11a 6Mbps	Right Side	64	5320	11.72	12.00	1.067	1.000	0	<0.001	<0.001
	WLAN5G	802.11a 6Mbps	Top Side	64	5320	11.72	12.00	1.067	1.000	0	<0.001	<0.001
	WLAN5G	802.11a 6Mbps	Bottom Side	64	5320	11.72	12.00	1.067	1.000	0	<0.001	<0.001
	WLAN5G	802.11a 6Mbps	Front	100	5500	13.08	13.50	1.102	1.000	-0.06	0.066	0.073
	WLAN5G	802.11a 6Mbps	Back	100	5500	13.08	13.50	1.102	1.000	0	<0.001	<0.001
137	WLAN5G	802.11a 6Mbps	Left Side	100	5500	13.08	13.50	1.102	1.000	0.11	0.493	0.543
	WLAN5G	802.11a 6Mbps	Right Side	100	5500	13.08	13.50	1.102	1.000	0	<0.001	<0.001
	WLAN5G	802.11a 6Mbps	Top Side	100	5500	13.08	13.50	1.102	1.000	-0.11	0.039	0.043
	WLAN5G	802.11a 6Mbps	Bottom Side	100	5500	13.08	13.50	1.102	1.000	0	<0.001	<0.001

Plot No.	Band	Mode	Test Position	Ch.	Frequency (MHz)	Measured Conducted Power (dBm)	Max. Tune-up Power (dBm)	Tune-up Scaling Factor	Duty Cycle Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Reported SAR-1g (W/kg)
	WLAN5G	802.11a 6Mbps	Front	165	5825	10.86	11.00	1.033	1.000	0.05	0.065	0.067
	WLAN5G	802.11a 6Mbps	Back	165	5825	10.86	11.00	1.033	1.000	-0.09	0.038	0.039
145	WLAN5G	802.11a 6Mbps	Left Side	165	5825	10.86	11.00	1.033	1.000	0.04	0.608	0.628
	WLAN5G	802.11a 6Mbps	Right Side	165	5825	10.86	11.00	1.033	1.000	0	<0.001	<0.001
	WLAN5G	802.11a 6Mbps	Top Side	165	5825	10.86	11.00	1.033	1.000	-0.09	0.080	0.083
	WLAN5G	802.11a 6Mbps	Bottom Side	165	5825	10.86	11.00	1.033	1.000	0	<0.001	<0.001

Note: "<0.01" means the SAR value is too low to be measured.

Test Engineer: Morrison Huang

9.8.3 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Band	Test Position	Ch.	Original Measured SAR-1g (W/kg)	1st Repeated SAR-1g (W/kg)	L/S Ratio (%)
LTE Band 2	Right Side	19100	0.743	0.739	-0.5
LTE Band 66	Right Side	132572	1.110	1.095	-0.014

9.8.4 Multi-band Transmission Evaluation

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR_{1g} of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR_{1g} 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR_{1g} is greater than the SAR limit (SAR_{1g} 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

Hotspot		Reported SAR (W/kg)			Summed 1g SAR (W/kg)	
WWAN Band	Exposure Position	1	2	3	1+2	1+3
		WWAN	2.4GHz WLAN	5GHz WLAN		
LTE Band 2	Front	0.036	0.063	0.073	0.099	0.109
	Back	0.148	0.159	0.039	0.307	0.187
	Left side	-	0.626	0.628	0.626	0.628
	Right side	0.940	0.005	-	0.945	0.940
	Top side	-	0.024	0.083	0.024	0.083
	Bottom side	0.018	0.003	-	0.021	0.018
LTE Band 5	Front	0.376	0.063	0.073	0.439	0.449
	Back	0.250	0.159	0.039	0.409	0.289
	Left side	0.002	0.626	0.628	0.628	0.630
	Right side	0.299	0.005	-	0.304	0.299
	Top side	0.024	0.024	0.083	0.048	0.107
	Bottom side	0.431	0.003	-	0.434	0.431
LTE Band 7	Front	0.027	0.063	0.073	0.090	0.100
	Back	0.044	0.159	0.039	0.203	0.083
	Left side	-	0.626	0.628	0.626	0.628
	Right side	0.196	0.005	-	0.201	0.196
	Top side	0.030	0.024	0.083	0.054	0.113
	Bottom side	0.020	0.003	-	0.023	0.020
LTE Band 12	Front	0.114	0.063	0.073	0.177	0.187
	Back	0.230	0.159	0.039	0.389	0.269
	Left side	0.009	0.626	0.628	0.635	0.637
	Right side	0.639	0.005	-	0.644	0.639
	Top side	0.007	0.024	0.083	0.031	0.090
	Bottom side	0.123	0.003	-	0.126	0.123
LTE Band 13	Front	0.283	0.063	0.073	0.346	0.356
	Back	0.582	0.159	0.039	0.741	0.621
	Left side	0.014	0.626	0.628	0.640	0.642
	Right side	0.616	0.005	-	0.621	0.616
	Top side	0.020	0.024	0.083	0.044	0.103
	Bottom side	0.432	0.003	-	0.435	0.432
LTE Band 66	Front	0.207	0.063	0.073	0.270	0.280
	Back	0.315	0.159	0.039	0.474	0.354
	Left side	0.062	0.626	0.628	0.688	0.690
	Right side	1.195	0.005	-	1.200	1.195
	Top side	-	0.024	0.083	0.024	0.083
	Bottom side	0.162	0.003	-	0.165	0.162

Prüfbericht - Nr.: CN26WR6N 001
Test Report No.

Seite 47 von 47
Page 47 of 47

10. Appendixes

Appendix A – SAR Plots of System Verification

Appendix B – SAR Plots of SAR Measurement

Appendix C – Calibration Certificate for Probe and Dipole

Appendix D – Photographs of the Test Set-Up

---END---