

RF exposure information

Product description

Applicant	:	YAESU MUSEN CO., LTD.
Address	:	Tennozu Parkside Building, 2-5-8, Higashi-Shinagawa, Shinagawa-ku, Tokyo 140-0002 Japan
FCC ID	:	K6620715X40
Model	:	FTM-300DR
Test item	:	144/430MHz DUAL BAND TRANSCEIVER (Bluetooth)
Operating frequency range	:	2402 - 2480 MHz
Measured conducted output power	:	-1.6 dBm@2402 MHz, -0.4 dBm@2440 MHz, +0.2 dBm@ 2480 MHz (result is referred from test report WE190401BC1-51 issued by SGS Japan Inc.)
Maximum antenna gain	:	+2.14 dBi
Specification of maximum output power	:	+2.0 dBm
Specification of output power tolerance	:	(tolerance is included in specification of maximum output power)
Separation distance	:	No declaration by the applicant (≤ 5 mm)

Analysis for portable use

Standalone SAR test exclusion considerations are defined in the KDB 447498 v06 chapter 4.3.1.

- a) For 100 MHz to 6 GHz and *test separation distances* ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{(\text{min. test separation distance, mm})} \right] \cdot \left[\sqrt{f_{\text{GHz}}} \right] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR,}^{30} \text{ where}$$

- f_{GHz} is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation³¹
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as *numeric thresholds* in step b) below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

The measured maximum conducted output power is +0.2 dBm (1.05 mW).

The specification of maximum output power +2.0 dBm (1.58 mW), this value is highest, so we use this value to calculation.

Applying above formula for this device, $(1.58 \text{ mW} / 5 \text{ mm}) \cdot \sqrt{2.480 \text{ GHz}} = 0.498$, rounded to one decimal = 0.5

Result is less than 3.0, so YAESU MUSEN CO., LTD. 144/430MHz DUAL BAND TRANSCEIVER (Bluetooth) (FTM-300DR) meets the SAR exclusion.

For reference, other frequency results are shown below.

General RF exposure = $(1.58 \text{ mW} / 5 \text{ mm}) \cdot \sqrt{2.402 \text{ GHz}} = 0.490$, rounded to one decimal = 0.5

General RF exposure = $(1.58 \text{ mW} / 5 \text{ mm}) \cdot \sqrt{2.440 \text{ GHz}} = 0.494$, rounded to one decimal = 0.5

This Test Report is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at <http://www.sgs.com>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Unless otherwise stated the results shown in this Test Report refer only to the sample(s) tested. This Test Report cannot be reproduced, in full, without prior approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this test report is unlawful and offenders may be prosecuted to the fullest extent of the law.

この試験報告書は裏面に記載された、もしくは <http://www.sgs.com> で入手が可能なサービスに関する一般的条件に則して発行されます。そちらに明記されている弊社の負うべき債務・補償の範囲及び司法管轄の項目をご確認ください。他に特に明記のない限り、この試験報告書に記載された結果は、試験サンプルのみに属します。この書面全体の複製以外には、弊社からの事前の許可を得ること無く複製することを禁じます。この試験報告書を無断で変更、偽造、改ざんすることは違法であり、違反者に対しては法的手段を講じることとなります。