

TEST REPORT

Applicant	Belkin International, Inc.
Address	555 S. Aviation Blvd., Suite 180, El Segundo, CA 90245, USA

Manufacturer or Supplier	Belkin International, Inc.
Address	555 S. Aviation Blvd., Suite 180, El Segundo, CA 90245, USA
Product	SoundForm™ Dot ANC Earbuds
Additional Product	SoundForm™ Dot Earbuds
Brand Name	belkin
Model	AUC018
Additional Models & Model Difference	AUC019, See section 3.1
Date of tests	Apr. 20, 2026 ~ Apr. 30, 2026

the tests have been carried out according to the requirements of the following standards:

☒ **FCC Part 15, Subpart C, Section 15.247**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Eric Fang Project Engineer / EMC Department	Approved by Glyn He Assistant Manager / EMC Department
	 Date: Jun. 03, 2026

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents

TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS.....	5
2 MEASUREMENT UNCERTAINTY	5
3 GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF EUT	6
3.2 DESCRIPTION OF TEST MODES.....	7
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST	8
3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	8
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	10
3.4 DESCRIPTION OF SUPPORT UNITS.....	10
3.5 CONFIGURATION OF SYSTEM UNDER TEST	10
3.6 DUTY CYCLE OF TESET SIGNAL	11
4 TEST TYPES AND RESULTS.....	12
4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT	12
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	12
4.1.2 TEST INSTRUMENTS.....	13
4.1.3 TEST PROCEDURES	14
4.1.4 DEVIATION FROM TEST STANDARD	15
4.1.5 TEST SETUP	15
4.1.6 EUT OPERATING CONDITIONS	16
4.1.7 TEST RESULTS.....	17
4.2 NUMBER OF HOPPING FREQUENCY USED	57
4.2.1 LIMIT OF HOPPING FREQUENCY USED	57
4.2.2 TEST SETUP	57
4.2.3 TEST INSTRUMENTS.....	57
4.2.4 TEST PROCEDURES	58
4.2.5 DEVIATION FROM TEST STANDARD	58
4.2.6 TEST RESULTS.....	58
4.3 DWELL TIME ON EACH CHANNEL	63
4.3.1 LIMIT OF DWELL TIME USED	63
4.3.2 TEST SETUP	63
4.3.3 TEST INSTRUMENTS.....	63

4.3.4	TEST PROCEDURES	63
4.3.5	DEVIATION FROM TEST STANDARD	64
4.3.6	TEST RESULTS.....	64
4.4	CHANNEL BANDWIDTH.....	70
4.4.1	LIMITS OF CHANNEL BANDWIDTH	70
4.4.2	TEST SETUP	70
4.4.3	TEST INSTRUMENTS.....	70
4.4.4	TEST PROCEDURE	70
4.5.5	DEVIATION FROM TEST STANDARD	70
4.4.6	EUT OPERATING CONDITION.....	70
4.4.7	TEST RESULTS.....	71
4.5	HOPPING CHANNEL SEPARATION	79
4.5.1	LIMIT OF HOPPING CHANNEL SEPARATION	79
4.5.2	TEST SETUP	79
4.5.3	TEST INSTRUMENTS.....	79
4.5.4	TEST PROCEDURES	79
4.5.5	DEVIATION FROM TEST STANDARD	79
4.5.6	TEST RESULTS.....	80
4.6	CONDUCTED OUTPUT POWER	88
4.6.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT.....	88
4.6.2	TEST SETUP	88
4.6.3	TEST INSTRUMENTS.....	88
4.6.4	TEST PROCEDURES	88
4.6.5	DEVIATION FROM TEST STANDARD	88
4.6.6	EUT OPERATING CONDITION.....	89
4.6.7	TEST RESULTS.....	90
4.7	OUT OF BAND EMISSION MEASUREMENT	92
4.7.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	92
4.7.2	TEST INSTRUMENTS.....	92
4.7.3	TEST PROCEDURE	92
4.7.4	DEVIATION FROM TEST STANDARD	92
4.7.5	EUT OPERATING CONDITION.....	92
4.7.6	TEST RESULTS.....	92
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	101
6	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	102



Test Report No.: RF2603WDG0421-1

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF2603WDG0421-1	Original release	May 08, 2026

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	N/A	Powered From Battery.
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output Power	PASS	Meet the requirement of limit.
15.247(d)&15.209	Transmitter Radiated Emission	PASS	Meet the requirement of limit.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	3.36dB
Radiated emissions	9KHz ~ 30MHz	2.66dB
	30MHz ~ 1GMHz	4.06dB
	1GHz ~ 18GHz	4.90dB
	18GHz ~ 40GHz	4.58dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	SoundForm™ Dot ANC Earbuds
ADDITIONAL PRODUCT	SoundForm™ Dot Earbuds
MODEL NO.	AUC018
ADDITIONAL MODELS	AUC019
FCC ID	K7SAUC018
POWER SUPPLY	Earbuds: DC 3.85V From Li-ion Battery or DC 5V From Charging Case
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, $\pi/4$ DQPSK, 8DPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
PEAK OUTPUT POWER	2.992mW (Max. Measured)
ANTENNA TYPE	FPC Antenna, Left:-1.14dBi Gain; Right: 1.27dBi Gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	See section 3.4
ACCESSORY	N/A

NOTES:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 2603WDG0421-2, 2603WDG0421-3, 2603WDG0421-4, 2603WDG0421-5) for detailed product photo.
4. In charging mode , BT Function not working.
5. The circuits of the earbuds on both ears are different, so they were tested separately.
6. Additional model AUC019 is identical with test model AUC018 except the difference as follows:

Product Name	Model No.	Difference
SoundForm™ Dot ANC Earbuds	AUC018	Front cavity vent hole, with ANC function
SoundForm™ Dot Earbuds	AUC019	No front cavity vent hole, without ANC function

Remark: Based on the difference of above, picked up the AUC018 for all test.

3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, power supply voltage range and antenna ports. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	-	√	DC 3.85V with BT link

Where **RE<1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission

RE≥1G: Radiated Emission above 1GHz
APCM: Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, X axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
A	0 to 78	39	FHSS	GFSK	DH5

For the test results, only the worst case was shown in test report.

RADIATED EMISSION TEST (ABOVE 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, X axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
A	0 to 78	0, 39, 78	FHSS	GFSK	DH5
	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
A	0 to 78	0, 39, 78	FHSS	GFSK	DH5
	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	26deg. C, 53%RH	DC 3.85V From Battery	Ludius
RE≥1G	26deg. C, 56%RH	DC 3.85V From Battery	Ludius
PLC	-	-	-
APCM	25deg. C, 54%RH	DC 3.85V From Battery	Jeffrey

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. Section 15.247

KDB 558074 D01 15.247 Meas Guidance v05r02

ANSI C63.10-2020

All test items have been performed and recorded as per the above standards.


3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	iPhone 17 Pro Max 1#	Apple	A3527 (MG054CH/A)	CD4WV14FYY	BCG-E8962A
2	Notebook	DELL	Inspiron 13-7378	GMSJZD2	N/A

Description	Length (m)	Shielding (Y/N)	Remark
USB-A to USB-C cable(optional)	0.3	N	-
USB-A to USB-C cable(optional)	0.3	N	SHENZHEN TAI LIFENG ELECTRONIC TECHNOLOGY CO., LTD. / 116.14.02090

3.5 CONFIGURATION OF SYSTEM UNDER TEST






3.6 DUTY CYCLE OF TESET SIGNAL


Left Earbud:

Test Mode	Packet Type	On Time (ms)	Period (ms)	Duty Cycle (%)	1/T Min. VBW (KHz)	VBW Setting
BDR(GFSK)	DH5	2.885	3.752	76.89	0.346	500Hz
EDR(8DPSK)	3DH5	2.878	3.748	76.79	0.347	500Hz



Right Earbud:

Test Mode	Packet Type	On Time (ms)	Period (ms)	Duty Cycle (%)	1/T Min. VBW (KHz)	VBW Setting
BDR(GFSK)	DH5	2.877	3.752	76.68	0.347	500Hz
EDR(8DPSK)	3DH5	2.890	3.750	77.07	0.346	500Hz



4 TEST TYPES AND RESULTS

4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTES:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU40	100449	Oct. 09, 26
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	Apr. 08, 27
Active Loop Antenna (9KHz -30MHz)	SCHWARZBECK	FMZB 1519B	1519B-045	Apr. 12, 27
Amplifier (9KHz -1GHz)	Burgeon	BPA-530	100210	Feb. 12, 27
Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-554	Dec. 14, 26
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	0085519	Oct. 11, 26
Horn Antenna (18GHz -40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170147	Apr. 18, 27
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	May 17, 26
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A
Broadband Preamplifier (1GHz~18GHz)	SCHWARZBECK	BBV9718	305	Feb. 12, 27
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Oct. 10, 26

NOTES:

1. The test was performed in 966 Chamber .
2. Equipment are calibrated by calibration laboratory accredited to ISO/IEC 17025 by a mutually recognized Accreditation and all tests are conducted within a valid calibration cycle.
4. Test Firm Registration Number: 749762.
5. Designation Number: CN1174

4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 1.5 meters(above 1GHz) and 0.8 meters(below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. For below 1GHz was used bilog antenna, and above 1GHz was used horn antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1.3m above the ground.
- g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTES:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.

4.1.4 DEVIATION FROM TEST STANDARD


No deviation.

4.1.5 TEST SETUP

Below 30MHz test setup




Below 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

Above 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.

4.1.7 TEST RESULTS

Left Earbud:

BELOW 1GHz WORST-CASE DATA:


GFSK DH5

CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTIO N FACTOR (dB/m)
1	36.22	13.1 QP	40.0	-26.9	1.06 H	20	30.7	-17.6
2	152.80	12.2 QP	43.5	-31.3	1.18 H	33	28.7	-16.5
3	361.11	13.5 QP	46.0	-32.5	1.30 H	45	27.5	-14.1
4	591.17	20.8 QP	46.0	-25.2	1.55 H	69	29.1	-8.3
5	860.10	24.2 QP	46.0	-21.8	1.84 H	98	28.4	-4.2
6	933.16	25.2 QP	46.0	-20.8	1.88 H	133	28.5	-3.3

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value




CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTIO N FACTOR (dB/m)
1	36.22	14.7 QP	40.0	-25.3	1.00 V	179	32.3	-17.6
2	146.59	12.0 QP	43.5	-31.5	1.00 V	198	28.7	-16.6
3	560.08	19.7 QP	46.0	-26.3	1.00 V	216	29.2	-9.5
4	639.36	21.6 QP	46.0	-24.4	1.00 V	234	29.3	-7.7
5	844.55	24.3 QP	46.0	-21.7	1.18 V	268	28.7	-4.4
6	892.74	24.5 QP	46.0	-21.5	1.02 V	247	28.5	-4.0

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value





**BUREAU
VERITAS**

Test Report No.: RF2603WDG0421-1

Right Earbud:

BELOW 1GHz WORST-CASE DATA:


GFSK DH5

CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTIO N FACTOR (dB/m)
1	36.22	14.2 QP	40.0	-25.8	1.87 H	258	31.8	-17.6
2	137.26	12.3 QP	43.5	-31.2	1.74 H	272	29.4	-17.1
3	373.54	14.9 QP	46.0	-31.1	1.49 H	296	28.6	-13.7
4	612.93	20.2 QP	46.0	-25.9	1.37 H	308	28.1	-7.9
5	799.47	23.6 QP	46.0	-22.4	2.01 H	244	29.5	-5.9
6	923.83	25.1 QP	46.0	-20.9	1.25 H	320	28.6	-3.5

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value



**Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch**

No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942. People's Republic of China.


Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com

CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTIO N FACTOR (dB/m)
1	36.22	14.5 QP	40.0	-25.5	1.42 V	176	32.2	-17.6
2	68.86	11.9 QP	40.0	-28.2	1.21 V	197	30.4	-18.5
3	138.81	12.6 QP	43.5	-31.0	1.55 V	164	29.5	-17.0
4	488.57	17.9 QP	46.0	-28.1	1.68 V	150	28.8	-10.9
5	710.87	23.4 QP	46.0	-22.7	1.80 V	139	29.9	-6.5
6	930.05	27.2 QP	46.0	-18.8	1.03 V	216	30.6	-3.4

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value



Left Earbud:

ABOVE 1GHz DATA

BT_GFSK


CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.2 PK	74.0	-29.8	3.25 H	15	42.0	2.3
2	2390.00	31.8 AV	54.0	-22.2	3.25 H	15	29.6	2.3
3	*2402.00	92.0 PK			4.00 H	156	89.8	2.3
4	*2402.00	90.2 AV			4.00 H	156	87.9	2.3
5	4804.00	51.2 PK	74.0	-22.8	2.35 H	87	45.4	5.9
6	4804.00	35.2 AV	54.0	-18.8	2.35 H	87	29.3	5.9
7	#7206.00	52.8 PK	74.0	-21.2	2.35 H	45	44.1	8.8
8	#7206.00	37.6 AV	54.0	-16.4	2.35 H	45	28.9	8.8
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.4 PK	74.0	-29.6	3.25 V	15	42.1	2.3
2	2390.00	31.9 AV	54.0	-22.1	3.25 V	15	29.6	2.3
3	*2402.00	93.9 PK			1.56 V	45	91.6	2.3
4	*2402.00	92.8 AV			1.56 V	45	90.5	2.3
5	4804.00	50.2 PK	74.0	-23.8	1.56 V	45	44.3	5.9
6	4804.00	34.3 AV	54.0	-19.7	1.56 V	45	28.4	5.9
7	#7206.00	51.1 PK	74.0	-22.9	1.65 V	58	42.4	8.8
8	#7206.00	38.7 AV	54.0	-15.3	1.65 V	58	29.9	8.8


REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.


BT GFSK 2402MHz Horizontal




BT-GFSK 2402MHz Vertical



BT-GFSK 2402MHz Horizontal



BT-GFSK 2402MHz Vertical




CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	96.9 PK			1.56 H	156	94.6	2.3
2	*2441.00	96.2 AV			1.56 H	156	93.9	2.3
3	4882.00	50.2 PK	74.0	-23.8	1.65 H	58	44.4	5.7
4	4882.00	34.3 AV	54.0	-19.7	1.65 H	58	28.5	5.7
5	7323.00	53.5 PK	74.0	-20.5	4.00 H	84	44.6	8.9
6	7323.00	38.3 AV	54.0	-15.8	4.00 H	84	29.4	8.9
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	92.1 PK			1.65 V	360	89.8	2.3
2	*2441.00	91.4 AV			1.65 V	360	89.1	2.3
3	4882.00	50.1 PK	74.0	-23.9	1.65 V	45	44.4	5.7
4	4882.00	34.2 AV	54.0	-19.9	1.65 V	45	28.4	5.7
5	7323.00	51.4 PK	74.0	-22.6	1.56 V	45	42.5	8.9
6	7323.00	38.5 AV	54.0	-15.5	1.56 V	45	29.6	8.9


REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.


BT GFSK 2441MHz Horizontal




BT-GFSK 2441MHz Vertical



BT-GFSK 2441MHz Horizontal



BT-GFSK 2441MHz Vertical




CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	98.2 PK			1.56 H	45	95.8	2.4
2	*2480.00	97.6 AV			1.56 H	45	95.2	2.4
3	2483.50	56.2 PK	74.0	-17.8	2.35 H	15	53.8	2.4
4	2483.50	49.3 AV	54.0	-4.7	2.35 H	15	47.0	2.4
5	4960.00	52.2 PK	74.0	-21.8	1.56 H	45	46.6	5.6
6	4960.00	34.8 AV	54.0	-19.2	1.56 H	45	29.2	5.6
7	7440.00	52.3 PK	74.0	-21.7	2.35 H	5	43.4	8.9
8	7440.00	40.3 AV	54.0	-13.7	2.35 H	5	31.4	8.9
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	91.2 PK			1.56 V	45	88.8	2.4
2	*2480.00	90.2 AV			1.56 V	45	87.8	2.4
3	2483.50	49.4 PK	74.0	-24.6	2.35 V	45	47.0	2.4
4	2483.50	45.3 AV	54.0	-8.7	2.35 V	45	42.9	2.4
5	4960.00	49.2 PK	74.0	-24.8	1.56 V	45	43.7	5.6
6	4960.00	35.5 AV	54.0	-18.5	1.56 V	45	29.9	5.6
7	7440.00	52.4 PK	74.0	-21.6	1.56 V	45	43.5	8.9
8	7440.00	38.2 AV	54.0	-15.8	1.56 V	45	29.2	8.9


REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.


BT GFSK 2480MHz Horizontal




BT-GFSK 2480MHz Vertical



BT-GFSK 2480MHz Horizontal



BT-GFSK 2480MHz Vertical





BT_8DPSK


CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.1 PK	74.0	-29.9	2.35 H	5	41.8	2.3
2	2390.00	32.0 AV	54.0	-22.0	2.35 H	5	29.7	2.3
3	*2402.00	96.5 PK			1.65 H	56	94.3	2.3
4	*2402.00	92.4 AV			1.65 H	56	90.2	2.3
5	4804.00	48.2 PK	74.0	-25.8	1.56 H	45	42.3	5.9
6	4804.00	35.8 AV	54.0	-18.2	1.56 H	45	29.9	5.9
7	#7206.00	51.4 PK	74.0	-22.6	2.35 H	5	42.6	8.8
8	#7206.00	41.3 AV	54.0	-12.7	2.35 H	5	32.5	8.8
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.9 PK	74.0	-29.1	2.35 V	15	42.6	2.3
2	2390.00	31.9 AV	54.0	-22.1	2.35 V	15	29.7	2.3
3	*2402.00	93.6 PK			1.65 V	45	91.3	2.3
4	*2402.00	89.5 AV			1.65 V	45	87.2	2.3
5	4804.00	49.2 PK	74.0	-24.8	4.00 V	156	43.3	5.9
6	4804.00	32.8 AV	54.0	-21.2	4.00 V	156	27.0	5.9
7	#7206.00	50.4 PK	74.0	-23.6	1.65 V	58	41.6	8.8
8	#7206.00	40.3 AV	54.0	-13.7	1.65 V	58	31.5	8.8


REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.


BT-8DPSK 2402MHz Horizontal




BT-8DPSK 2402MHz Vertical



BT-8DPSK 2402MHz Horizontal



BT-8DPSK 2402MHz Vertical




CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	97.2 PK			3.25 H	56	94.9	2.3
2	*2441.00	95.2 AV			3.25 H	56	92.9	2.3
3	4882.00	48.2 PK	74.0	-25.8	1.56 H	156	42.4	5.7
4	4882.00	34.8 AV	54.0	-19.2	1.56 H	156	29.1	5.7
5	7323.00	51.3 PK	74.0	-22.7	3.25 H	15	42.4	8.9
6	7323.00	41.4 AV	54.0	-12.6	3.25 H	15	32.5	8.9
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	94.2 PK			1.65 V	360	91.9	2.3
2	*2441.00	89.2 AV			1.65 V	360	86.9	2.3
3	4882.00	49.2 PK	74.0	-24.8	3.25 V	45	43.4	5.7
4	4882.00	38.2 AV	54.0	-15.8	3.25 V	45	32.4	5.7
5	7323.00	52.2 PK	74.0	-21.8	1.65 V	148	43.3	8.9
6	7323.00	41.6 AV	54.0	-12.4	1.65 V	148	32.7	8.9


REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.


BT-8DPSK 2441MHz Horizontal




BT-8DPSK 2441MHz Vertical



BT-8DPSK 2441MHz Horizontal



BT-8DPSK 2441MHz Vertical




CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	95.2 PK			4.00 H	45	92.8	2.4
2	*2480.00	94.7 AV			4.00 H	45	92.3	2.4
3	2483.50	58.8 PK	74.0	-15.2	4.00 H	156	56.5	2.4
4	2483.50	47.3 AV	54.0	-6.7	4.00 H	156	45.0	2.4
5	4960.00	49.2 PK	74.0	-24.8	1.65 H	45	43.6	5.6
6	4960.00	35.8 AV	54.0	-18.2	1.65 H	45	30.2	5.6
7	7440.00	52.1 PK	74.0	-21.9	2.35 H	360	43.2	8.9
8	7440.00	41.3 AV	54.0	-12.7	2.35 H	360	32.3	8.9
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	95.2 PK			1.56 V	45	92.8	2.4
2	*2480.00	87.4 AV			1.56 V	45	85.0	2.4
3	2483.50	50.9 PK	74.0	-23.1	1.65 V	45	48.5	2.4
4	2483.50	44.9 AV	54.0	-9.1	1.65 V	45	42.5	2.4
5	4960.00	49.5 PK	74.0	-24.5	1.65 V	45	43.9	5.6
6	4960.00	35.8 AV	54.0	-18.2	1.65 V	45	30.2	5.6
7	7440.00	51.4 PK	74.0	-22.6	2.35 V	87	42.4	8.9
8	7440.00	41.3 AV	54.0	-12.7	2.35 V	87	32.4	8.9


REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.


BT-8DPSK 2480MHz Horizontal




BT-8DPSK 2480MHz Vertical



BT-GFSK 2480MHz Horizontal



BT-GFSK 2480MHz Vertical



Right Earbud:

ABOVE 1GHz DATA

BT_GFSK


CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	45.0 PK	74.0	-29.0	1.56 H	56	42.8	2.3
2	2390.00	32.6 AV	54.0	-21.4	1.56 H	56	30.4	2.3
3	*2402.00	91.7 PK			1.56 H	56	89.4	2.3
4	*2402.00	90.3 AV			1.56 H	56	88.0	2.3
5	4804.00	50.2 PK	74.0	-23.8	3.25 H	45	44.3	5.9
6	4804.00	44.4 AV	54.0	-9.6	3.25 H	45	38.5	5.9
7	#7206.00	54.4 PK	74.0	-19.7	2.35 H	145	45.6	8.8
8	#7206.00	44.3 AV	54.0	-9.7	2.35 H	145	35.5	8.8
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.4 PK	74.0	-29.6	1.65 V	56	42.2	2.3
2	2390.00	34.6 AV	54.0	-19.4	1.65 V	56	32.3	2.3
3	*2402.00	91.4 PK			1.56 V	56	89.2	2.3
4	*2402.00	90.6 AV			1.56 V	56	88.3	2.3
5	4804.00	51.3 PK	74.0	-22.7	1.56 V	58	45.4	5.9
6	4804.00	46.6 AV	54.0	-7.4	1.56 V	58	40.8	5.9
7	#7206.00	54.4 PK	74.0	-19.6	1.56 V	56	45.6	8.8
8	#7206.00	43.6 AV	54.0	-10.4	1.56 V	56	34.8	8.8


REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.


BT GFSK 2402MHz Horizontal




BT-GFSK 2402MHz Vertical



BT-GFSK 2402MHz Horizontal



BT-GFSK 2402MHz Vertical




CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	92.0 PK			1.56 H	56	89.7	2.3
2	*2441.00	91.5 AV			1.56 H	56	89.2	2.3
3	4882.00	50.1 PK	74.0	-23.9	1.56 H	360	44.4	5.7
4	4882.00	45.1 AV	54.0	-8.9	1.56 H	360	39.4	5.7
5	7323.00	53.2 PK	74.0	-20.8	1.56 H	45	44.4	8.9
6	7323.00	42.5 AV	54.0	-11.5	1.56 H	45	33.6	8.9
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	92.2 PK			1.00 V	360	89.9	2.3
2	*2441.00	90.4 AV			1.00 V	360	88.1	2.3
3	4882.00	51.2 PK	74.0	-22.8	1.56 V	58	45.4	5.7
4	4882.00	45.1 AV	54.0	-8.9	1.56 V	58	39.3	5.7
5	7323.00	50.2 PK	74.0	-23.8	1.56 V	45	41.4	8.9
6	7323.00	44.4 AV	54.0	-9.6	1.56 V	45	35.5	8.9


REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.


BT GFSK 2441MHz Horizontal




BT-GFSK 2441MHz Vertical



BT-GFSK 2441MHz Horizontal



BT-GFSK 2441MHz Vertical




CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	90.7 PK			1.56 H	56	88.3	2.4
2	*2480.00	90.0 AV			1.56 H	56	87.7	2.4
3	2483.50	48.5 PK	74.0	-25.5	1.56 H	56	46.2	2.4
4	2483.50	43.3 AV	54.0	-10.7	1.56 H	56	40.9	2.4
5	4960.00	51.2 PK	74.0	-22.8	1.56 H	58	45.6	5.6
6	4960.00	47.2 AV	54.0	-6.8	1.56 H	58	41.6	5.6
7	7440.00	50.3 PK	74.0	-23.7	1.56 H	58	41.4	8.9
8	7440.00	41.4 AV	54.0	-12.6	1.56 H	58	32.5	8.9
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	93.3 PK			1.56 V	56	90.9	2.4
2	*2480.00	91.8 AV			1.56 V	56	89.5	2.4
3	2483.50	54.4 PK	74.0	-19.6	1.56 V	56	52.1	2.4
4	2483.50	46.6 AV	54.0	-7.4	1.56 V	56	44.2	2.4
5	4960.00	51.2 PK	74.0	-22.8	4.00 V	56	45.6	5.6
6	4960.00	44.4 AV	54.0	-9.6	4.00 V	56	38.8	5.6
7	7440.00	50.2 PK	74.0	-23.8	1.56 V	58	41.2	8.9
8	7440.00	42.1 AV	54.0	-11.9	1.56 V	58	33.2	8.9


REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.


BT GFSK 2480MHz Horizontal




BT-GFSK 2480MHz Vertical



BT-GFSK 2480MHz Horizontal



BT-GFSK 2480MHz Vertical



BT_8DPSK


CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.0 PK	74.0	-30.0	1.55 H	56	41.8	2.3
2	2390.00	31.8 AV	54.0	-22.2	1.55 H	56	29.5	2.3
3	*2402.00	92.3 PK			1.00 H	360	90.0	2.3
4	*2402.00	87.7 AV			1.00 H	360	85.4	2.3
5	4804.00	50.1 PK	74.0	-23.9	2.35 H	15	44.2	5.9
6	4804.00	42.8 AV	54.0	-11.2	2.35 H	15	36.9	5.9
7	#7206.00	52.2 PK	74.0	-21.8	1.56 H	58	43.4	8.8
8	#7206.00	41.4 AV	54.0	-12.6	1.56 H	58	32.6	8.8
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.9 PK	74.0	-29.1	2.35 V	15	42.7	2.3
2	2390.00	32.3 AV	54.0	-21.7	2.35 V	15	30.0	2.3
3	*2402.00	97.4 PK			1.56 V	56	95.1	2.3
4	*2402.00	93.5 AV			1.56 V	56	91.2	2.3
5	4804.00	51.4 PK	74.0	-22.6	3.25 V	87	45.5	5.9
6	4804.00	44.2 AV	54.0	-9.8	3.25 V	87	38.3	5.9
7	#7206.00	53.4 PK	74.0	-20.6	1.00 V	15	44.6	8.8
8	#7206.00	43.3 AV	54.0	-10.7	1.00 V	15	34.5	8.8


REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.


BT-8DPSK 2402MHz Horizontal




BT-8DPSK 2402MHz Vertical



BT-8DPSK 2402MHz Horizontal



BT-8DPSK 2402MHz Vertical




CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	93.7 PK			1.56 H	56	91.4	2.3
2	*2441.00	90.0 AV			1.56 H	56	87.6	2.3
3	4882.00	49.5 PK	74.0	-24.5	1.56 H	5	43.8	5.7
4	4882.00	40.2 AV	54.0	-13.8	1.56 H	5	34.5	5.7
5	7323.00	52.4 PK	74.0	-21.6	1.65 H	58	43.5	8.9
6	7323.00	41.3 AV	54.0	-12.7	1.65 H	58	32.4	8.9
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	94.1 PK			1.56 V	46	91.8	2.3
2	*2441.00	93.0 AV			1.56 V	46	90.7	2.3
3	4882.00	49.2 PK	74.0	-24.9	4.00 V	235	43.4	5.7
4	4882.00	42.3 AV	54.0	-11.7	4.00 V	235	36.6	5.7
5	7323.00	51.4 PK	74.0	-22.6	1.56 V	56	42.5	8.9
6	7323.00	41.3 AV	54.0	-12.7	1.56 V	56	32.4	8.9


REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.


BT-8DPSK 2441MHz Horizontal




BT-8DPSK 2441MHz Vertical



BT-8DPSK 2441MHz Horizontal



BT-8DPSK 2441MHz Vertical




CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	89.5 PK			1.00 H	56	87.1	2.4
2	*2480.00	85.0 AV			1.00 H	56	82.6	2.4
3	2483.50	49.4 PK	74.0	-24.6	2.35 H	15	47.0	2.4
4	2483.50	42.2 AV	54.0	-11.8	2.35 H	15	39.8	2.4
5	4960.00	49.7 PK	74.0	-24.4	2.35 H	15	44.1	5.6
6	4960.00	43.6 AV	54.0	-10.5	2.35 H	15	38.0	5.6
7	7440.00	52.4 PK	74.0	-21.6	3.25 H	45	43.5	8.9
8	7440.00	41.2 AV	54.0	-12.8	3.25 H	45	32.2	8.9
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	92.7 PK			1.56 V	56	90.4	2.4
2	*2480.00	88.7 AV			1.56 V	56	86.4	2.4
3	2483.50	48.0 PK	74.0	-26.0	2.35 V	56	45.6	2.4
4	2483.50	45.2 AV	54.0	-8.8	2.35 V	56	42.8	2.4
5	4960.00	49.2 PK	74.0	-24.8	1.56 V	56	43.6	5.6
6	4960.00	44.3 AV	54.0	-9.7	1.56 V	56	38.7	5.6
7	7440.00	51.4 PK	74.0	-22.6	1.56 V	5	42.5	8.9
8	7440.00	42.4 AV	54.0	-11.6	1.56 V	5	33.5	8.9


REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.


BT-8DPSK 2480MHz Horizontal




BT-8DPSK 2480MHz Vertical



BT-8DPSK 2480MHz Horizontal



BT-8DPSK 2480MHz Vertical




4.2 NUMBER OF HOPPING FREQUENCY USED

4.2.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.2.2 TEST SETUP



4.2.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
Power Sensor	Keysight	U2021XA	MY57320002	Apr. 06, 27
Digital Multimeter	FLUKE	15B	12151063	Jun. 03, 26
Humid & Temp Programmable Tester	Haida	HD-225T	110807201	Oct. 10, 26
Oscilloscope	Agilent	DSO9254A	MY51260160	Jul. 06, 26
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101003	Oct. 09, 26
Signal Generator	Agilent	N5183A	MY50140980	Jul. 06, 26
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Jul. 06, 26
Attenuator	MINI	BW-S10W2+	S130129FGE2	N/A
DC Source	Rohde&Schwarz	HMP2020	101295	Jun. 03, 26
Test software	ADT	ADT_RF Test Software V6.6.5.3	N/A	N/A

NOTE:

1. The test was performed in RF Oven room.
2. Equipment are calibrated by calibration laboratory accredited to ISO/IEC 17025 by a mutually recognized Accreditation and all tests are conducted within a valid calibration cycle.

4.2.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were completed.

4.2.5 DEVIATION FROM TEST STANDARD



No deviation.

4.2.6 TEST RESULTS



There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

Left Earbud:

GFSK





8DPSK





Right Earbud:

GFSK



8DPSK




4.3 DWELL TIME ON EACH CHANNEL

4.3.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.3.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 TEST RESULTS

Left Earbud:

GFSK


Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	51	322.32	0.444	143.11	400	PASS
DH3	79	31.6	5	27	170.64	1.68	286.68	400	PASS
DH5	79	31.6	5	17	107.44	2.96	318.02	400	PASS

8DPSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
3DH1	79	31.6	5	50	316	0.432	136.51	400	PASS
3DH3	79	31.6	5	26	164.32	1.73	284.27	400	PASS
3DH5	79	31.6	5	17	107.44	2.944	316.3	400	PASS

NOTE: Test plots of the transmitting time slot are shown on next page.

GFSK






BUREAU
VERITAS

Test Report No.: RF2603WDG0421-1

8DPSK



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dq@bureauveritas.com

Right Earbud:

GFSK


Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	49	309.68	0.444	137.5	400	PASS
DH3	79	31.6	5	25	158.00	1.720	271.76	400	PASS
DH5	79	31.6	5	17	107.44	3.014	323.82	400	PASS

8DPSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
3DH1	79	31.6	5	49	309.68	0.456	141.21	400	PASS
3DH3	79	31.6	5	27	170.64	1.740	296.91	400	PASS
3DH5	79	31.6	5	16	101.12	2.976	300.93	400	PASS

NOTE: Test plots of the transmitting time slot are shown on next page.

GFSK






BUREAU
VERITAS

Test Report No.: RF2603WDG0421-1

8DPSK



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942. People's Republic of China.


Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com

4.4 CHANNEL BANDWIDTH

4.4.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.4.4 TEST PROCEDURE

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- Repeat above procedures until all frequencies measured were complete.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


4.4.7 TEST RESULTS

Left Earbud:


GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.95376
39	2441	0.95377
78	2480	0.95226


CH 0



CH 39




CH 78




8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.28
39	2441	1.28
78	2480	1.29


CH 0



CH 39




CH 78




Right Earbud:
GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.95192
39	2441	0.95347
78	2480	0.95334


CH 0



CH 39




CH 78




8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.29
39	2441	1.29
78	2480	1.29


CH 0



CH 39



CH 78




4.5 HOPPING CHANNEL SEPARATION

4.5.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.5.4 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 TEST RESULTS


Left Earbud:

GFSK


CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	0.95376	0.64	PASS
39	2441	1.00	0.95377	0.64	PASS
78	2480	1.00	0.95226	0.63	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.


CH 0



CH 39



CH 78




8DPSK


CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	1.28	0.85	PASS
39	2441	1.00	1.28	0.85	PASS
78	2480	1.00	1.29	0.86	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.


CH 0



CH 39



CH 78






GFSK


CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	0.95192	0.63	PASS
39	2441	1.00	0.95347	0.64	PASS
78	2480	1.00	0.95334	0.64	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.


CH 0



CH 39



CH 78




8DPSK


CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	1.29	0.86	PASS
39	2441	1.00	1.29	0.86	PASS
78	2480	1.00	1.29	0.86	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.


CH 0



CH 39



CH 78




4.6 CONDUCTED OUTPUT POWER

4.6.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.6.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor and set the detector to PEAK. Record the power level.

An average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor and set the detector to AVERAGE. Record the power level.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.6.7 TEST RESULTS

MAXIMUM PEAK OUTPUT POWER

Left Earbud:

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	3.59	2.286	125	PASS
39	2441	3.90	2.455	125	PASS
78	2480	3.73	2.36	125	PASS

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	4.31	2.698	125	PASS
39	2441	4.76	2.992	125	PASS
78	2480	4.62	2.897	125	PASS

Right Earbud:

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	3.26	2.118	125	PASS
39	2441	3.71	2.35	125	PASS
78	2480	3.52	2.249	125	PASS

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	3.26	2.118	125	PASS
39	2441	3.80	2.399	125	PASS
78	2480	3.71	2.35	125	PASS

AVERAGE OUTPUT POWER(FOR REFERENCE)

Left Earbud:

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	2.06	1.607
39	2441	2.58	1.811
78	2480	2.41	1.742

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	1.83	1.524
39	2441	2.33	1.71
78	2480	2.19	1.656

Right Earbud:

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	2.02	1.592
39	2441	2.45	1.758
78	2480	2.31	1.702

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	1.75	1.496
39	2441	2.22	1.667
78	2480	2.31	1.702

4.7 OUT OF BAND EMISSION MEASUREMENT

4.7.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz RBW).

4.7.2 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.7.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. of Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation.

4.7.5 EUT OPERATING CONDITION


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.7.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.

Left Earbud:

GFSK






BUREAU
VERITAS


Test Report No.: RF2603WDG0421-1

8DPSK

Low Channel



High Channel



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch


No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com


Right Earbud:

GFSK

Low Channel



High Channel






BUREAU
VERITAS


Test Report No.: RF2603WDG0421-1

8DPSK

Low Channel



High Channel



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch


No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com


Left Earbud:

GFSK

Hopping on Low Channel



Hopping on High Channel






BUREAU
VERITAS


Test Report No.: RF2603WDG0421-1

8DPSK

Hopping on Low Channel



Hopping on High Channel



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch


No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942, People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com


Right Earbud:

GFSK

Hopping on Low Channel



Hopping on High Channel






BUREAU
VERITAS


Test Report No.: RF2603WDG0421-1

8DPSK

Hopping on Low Channel



Hopping on High Channel



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---