

RF EXPOSURE TEST REPORT

Applicant	Belkin International, Inc
Address	555 S. Aviation Blvd., Suite 180, El Segundo, CA 90245-4852, USA

Manufacturer or Supplier	Belkin International, Inc.
Address	555 S. Aviation Blvd., Suite 180, El Segundo, CA 90245-4852, USA
Product	Magnetic Wireless Power Bank 5K + Stand
Brand Name	belkin
Model	BPD004
Additional Model & Model Difference	N/A
Date of tests	May 23, 2022

The submitted sample of the above equipment has been tested according to the requirements of the following standard:

- ☒ 47 CFR PART 1, Subpart I, Section 1.1310
- ☒ KDB 680106 D01

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Lucas Chen Project Engineer / EMC Department	Approved by Glyn He Assistant Manager / EMC Department
	 Date: May 25, 2022

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <https://www.cps.bureauveritas.com/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD.....	3
1. GENERAL INFORMATION.....	4
1.1. GENERAL DESCRIPTION OF EUT	4
2. RF EXPOSURE MEASUREMENT	5
2.1 LIMITS	5
2.2 DESCRIPTION OF SUPPORT UNITS.....	5
2.3 CONFIGURATION OF SYSTEM UNDER TEST	6
2.4 TEST SETUP FOR WPC.....	6
2.5 MEASUREMENT UNCERTAINTY.....	7
2.1 EQUIPMENTS USED DURING TEST.....	7
2.2 TEST POINT DESCRIPTION	8
2.3 TEST RESULTS	9
3. PHOTOGRAPHS OF THE TEST CONFIGURATION.....	21



Test Report No.: FM2204WDG0403

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM2204WDG0403	Original release	May 11, 2022

1. GENERAL INFORMATION

1.1. GENERAL DESCRIPTION OF EUT

FCC ID	K7SBPD004
PRODUCT	Magnetic Wireless Power Bank 5K + Stand
MODEL NO.	BPD004
ADDITIONAL MODEL	N/A
POWER SUPPLY	Input: 5.0V $\Rightarrow$ 2.0A ,9.0V $\Rightarrow$ 2.0A USB-C Output:5.0V $\Rightarrow$ 2.0A Wireless Output:5.0V 5.0W/7.5W Total Output (USB-C + Wireless):10.0W
MODULATION TECHNOLOGY	FSK
OPERATING FREQUENCY RANGE	111KHz ~ 148KHz
ANTENNA TYPE	Coil Antenna
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	Refer to user's manual

NOTES:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions, but only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 2204WDG0403) for detailed product photo.

2. RF EXPOSURE MEASUREMENT

2.1 LIMITS

§ 1.1310 The criteria listed in table 1 shall be used to evaluate the environmental impact of human exposure to radiofrequency(RF) radiation as specified in § 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of § 2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

Reference KDB 680106 D01 RF Exposure Wireless Charging App v03




The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

2.2 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	iPhone 13 Pro	Apple	A2639	N/A	N/A
2	Adapter	N/A	N/A	N/A	N/A

2.3 CONFIGURATION OF SYSTEM UNDER TEST

Standby (Adapter input)	Charging Mode with iPhone 13 Pro (Adapter input)
	
Charging Mode with iPhone 13 Pro (Battery Full)	
	

Note: The worst condition is when the phone is charged at 10%, so the test is performed when the phone is charged at 10%.

2.4 TEST SETUP FOR WPC



Note: Measurements should be made from all sides, with the 0 cm to 20 cm, in 2 cm minimum increment measured from the edge of the device, measured from the center of the probe(s) to the edge of the device.

2.5 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

Tabulated list of the error components and uncertainty values contributing to the total measurement uncertainty

Combined standard uncertainty and expanded uncertainty (for $k \geq 2$) of each measurement


PARAMETER	UNCERTAINTY
E-Field Measurement	± 0.003 V/m
H-Field Measurement	± 0.001 μ T

2.1 EQUIPMENTS USED DURING TEST

Item	Test Equipment	Manufacturer	Model No.	S/No	Due date.
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	8m*4m*4m	NSEMC003	2023-03-19
2	Electric and Magnetic Field Probe-Analyzer	Narda	EHP-200A	180ZX10216	Mar. 17, 23
3	Test Software	Narda	EHP200-TS	V1.94	N/A

- NOTE:**
1. The test was performed in RS chamber. (Chenwu)
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 3. The diameter of the probe is 8 cm.

2.2 TEST POINT DESCRIPTION



Notes:

1. Z-axis 1, It means the load surface.
2. Z-axis 2, It means the back of the load surface.

2.3 TEST RESULTS

Type-C IN Mode

Standby Mode 1: EUT USB-C port input + Standby (distance 0 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	9.25	6.38	7.99	6.32	5.1	5.32
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-604.75	-607.62	-606.01	-607.68	-608.9	-608.68
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-297.75	-300.62	-299.01	-300.68	-301.9	-301.68

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.235	0.256	0.234	0.234	0.241	0.246
Max H-Field(A/m)	0.187	0.204	0.186	0.186	0.192	0.196
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.443	-1.426	-1.444	-1.444	-1.438	-1.434
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.628	-0.611	-0.629	-0.629	-0.623	-0.619

Measurements was made from all sides and the top of the primary/client pair, with the 0 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 2: EUT USB-C port input + iPhone 13 Pro operating (10% electric quantity) (distance 0/2/4 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	8.95	5.98	6.93	6.66	4.99	5.36
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-605.05	-608.02	-607.07	-607.34	-609.01	-608.64
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-298.05	-301.02	-300.07	-300.34	-302.01	-301.64

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.257	0.249	0.235	0.237	0.238	0.245
Max H-Field(A/m)	0.205	0.198	0.187	0.189	0.189	0.195
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.425	-1.432	-1.443	-1.441	-1.441	-1.435
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.610	-0.617	-0.628	-0.626	-0.626	-0.620

Measurements was made from all sides and the top of the primary/client pair, with the 0/2/4 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 3: EUT USB-C port input + iPhone 13 Pro operating (10% electric quantity) (distance 6 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	7.26	5.12	5.85	4.89	4.36	5.45
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-606.74	-608.88	-608.15	-609.11	-609.64	-608.55
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-299.74	-301.88	-301.15	-302.11	-302.64	-301.55

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.251	0.242	0.236	0.241	0.235	0.245
Max H-Field(A/m)	0.200	0.193	0.188	0.192	0.187	0.195
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.430	-1.437	-1.442	-1.438	-1.443	-1.435
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.615	-0.622	-0.627	-0.623	-0.628	-0.620

Measurements was made from all sides and the top of the primary/client pair, with the 6 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 4: EUT USB-C port input + iPhone 13 Pro operating (10% electric quantity) (distance 8 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	7.15	4.98	5.99	5.32	5.12	5.36
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-606.85	-609.02	-608.01	-608.68	-608.88	-608.64
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-299.85	-302.02	-301.01	-301.68	-301.88	-301.64

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.246	0.242	0.254	0.26	0.239	0.241
Max H-Field(A/m)	0.196	0.193	0.202	0.207	0.190	0.192
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.434	-1.437	-1.428	-1.423	-1.440	-1.438
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.619	-0.622	-0.613	-0.608	-0.625	-0.623

Measurements was made from all sides and the top of the primary/client pair, with the 8 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 5: EUT USB-C port input + iPhone 13 Pro operating (10% electric quantity) (distance 10 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	6.32	4.65	4.19	4.22	4.89	5.12
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-607.68	-609.35	-609.81	-609.78	-609.11	-608.88
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-300.68	-302.35	-302.81	-302.78	-302.11	-301.88

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.237	0.238	0.238	0.232	0.234	0.239
Max H-Field(A/m)	0.189	0.189	0.189	0.185	0.186	0.190
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.441	-1.441	-1.441	-1.445	-1.444	-1.440
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.626	-0.626	-0.626	-0.630	-0.629	-0.625

Measurements was made from all sides and the top of the primary/client pair, with the 10 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 6: EUT USB-C port input + iPhone 13 Pro operating (10% electric quantity) (distance 12 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	6.01	4.21	3.89	4.17	4.29	4.87
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-607.99	-609.79	-610.11	-609.83	-609.71	-609.13
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-300.99	-302.79	-303.11	-302.83	-302.71	-302.13

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.231	0.232	0.23	0.231	0.234	0.238
Max H-Field(A/m)	0.184	0.185	0.183	0.184	0.186	0.189
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.446	-1.445	-1.447	-1.446	-1.444	-1.441
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.631	-0.630	-0.632	-0.631	-0.629	-0.626

Measurements was made from all sides and the top of the primary/client pair, with the 12 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 7: EUT USB-C port input + iPhone 13 Pro operating (10% electric quantity) (distance 14 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	5.21	4.36	3.25	4.62	3.66	4.23
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-608.79	-609.64	-610.75	-609.38	-610.34	-609.77
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-301.79	-302.64	-303.75	-302.38	-303.34	-302.77

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.232	0.23	0.23	0.231	0.232	0.235
Max H-Field(A/m)	0.185	0.183	0.183	0.184	0.185	0.187
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.445	-1.447	-1.447	-1.446	-1.445	-1.443
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.630	-0.632	-0.632	-0.631	-0.630	-0.628

Measurements was made from all sides and the top of the primary/client pair, with the 14 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Standby Mode 8: EUT USB-C port input + iPhone 13 Pro operating (10% electric quantity) (distance 16 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	4.89	4.06	4.02	4.33	3.89	4.35
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-609.11	-609.94	-609.98	-609.67	-610.11	-609.65
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-302.11	-302.94	-302.98	-302.67	-303.11	-302.65

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.229	0.228	0.228	0.229	0.228	0.231
Max H-Field(A/m)	0.182	0.182	0.182	0.182	0.182	0.184
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.448	-1.448	-1.448	-1.448	-1.448	-1.446
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.633	-0.633	-0.633	-0.633	-0.633	-0.631

Measurements was made from all sides and the top of the primary/client pair, with the 16 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 9: EUT USB-C port input + iPhone 13 Pro operating (10% electric quantity) (distance 18 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	3.86	3.69	3.68	4.02	4.02	3.99
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-610.14	-610.31	-610.32	-609.98	-609.98	-610.01
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-303.14	-303.31	-303.32	-302.98	-302.98	-303.01

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.228	0.229	0.23	0.228	0.227	0.229
Max H-Field(A/m)	0.182	0.182	0.183	0.182	0.181	0.182
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.448	-1.448	-1.447	-1.448	-1.449	-1.448
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.633	-0.633	-0.632	-0.633	-0.634	-0.633

Measurements was made from all sides and the top of the primary/client pair, with the 18 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 10: EUT USB-C port input + iPhone 13 Pro operating (10% electric quantity) (distance 20 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	2.89	2.96	2.56	3.06	3.29	3.32
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-611.11	-611.04	-611.44	-610.94	-610.71	-610.68
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-304.11	-304.04	-304.44	-303.94	-303.71	-303.68

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.229	0.228	0.231	0.231	0.229	0.228
Max H-Field(A/m)	0.182	0.182	0.184	0.184	0.182	0.182
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.448	-1.448	-1.446	-1.446	-1.448	-1.448
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.633	-0.633	-0.631	-0.631	-0.633	-0.633

Measurements was made from all sides and the top of the primary/client pair, with the 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 11: EUT USB-C port input + iPhone 13 Pro operating (50% electric quantity) (distance 0 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	8.35	6.03	6.33	6.45	5.02	5.39
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-605.65	-607.97	-607.67	-607.55	-608.98	-608.61
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-298.65	-300.97	-300.67	-300.55	-301.98	-301.61

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.249	0.241	0.231	0.238	0.236	0.239
Max H-Field(A/m)	0.198	0.192	0.184	0.189	0.188	0.190
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.432	-1.438	-1.446	-1.441	-1.442	-1.440
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.617	-0.623	-0.631	-0.626	-0.627	-0.625

Measurements was made from all sides and the top of the primary/client pair, with the 0 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 12: EUT USB-C port input + iPhone 13 Pro operating (90% electric quantity) (distance 0 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	8.03	6.05	6.34	6.46	4.93	5.37
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-605.97	-607.95	-607.66	-607.54	-609.07	-608.63
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-298.97	-300.95	-300.66	-300.54	-302.07	-301.63

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.243	0.242	0.23	0.232	0.234	0.236
Max H-Field(A/m)	0.193	0.193	0.183	0.185	0.186	0.188
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.437	-1.437	-1.447	-1.445	-1.444	-1.442
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.622	-0.622	-0.632	-0.630	-0.629	-0.627

Measurements was made from all sides and the top of the primary/client pair, with the 0 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Battery Mode

Charging Mode 1: EUT(Full Battery) + Standby (distance 0 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	8.82	6.35	7.65	6.3	4.69	5.06
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-605.18	-607.65	-606.35	-607.7	-609.31	-608.94
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-298.18	-300.65	-299.35	-300.7	-302.31	-301.94

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.238	0.25	0.241	0.231	0.242	0.241
Max H-Field(A/m)	0.189	0.199	0.192	0.184	0.193	0.192
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.441	-1.431	-1.438	-1.446	-1.437	-1.438
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.626	-0.616	-0.623	-0.631	-0.622	-0.623

Measurements was made from all sides and the top of the primary/client pair, with the 0/2/4 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 2: EUT(Full Battery) + iPhone 13 Pro operating (10% electric quantity) (distance 0/2/4 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	8.67	5.85	6.87	6.52	5.03	5.46
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-605.33	-608.15	-607.13	-607.48	-608.97	-608.54
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-298.33	-301.15	-300.13	-300.48	-301.97	-301.54

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.251	0.254	0.236	0.234	0.233	0.243
Max H-Field(A/m)	0.200	0.202	0.188	0.186	0.186	0.193
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.430	-1.428	-1.442	-1.444	-1.444	-1.437
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.615	-0.613	-0.627	-0.629	-0.629	-0.622

Measurements was made from all sides and the top of the primary/client pair, with the 0/2/4 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 3: EUT(Full Battery) + iPhone 13 Pro operating (10% electric quantity) (distance 6 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	7.25	6.12	5.96	5.03	4.63	5.86
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-606.75	-607.88	-608.04	-608.97	-609.37	-608.14
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	7.25	6.12	5.96	5.03	4.63	5.86

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.248	0.246	0.243	0.242	0.236	0.248
Max H-Field(A/m)	0.197	0.196	0.193	0.193	0.188	0.197
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.433	-1.434	-1.437	-1.437	-1.442	-1.433
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.618	-0.619	-0.622	-0.622	-0.627	-0.618

Measurements was made from all sides and the top of the primary/client pair, with the 6 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 4: EUT(Full Battery) + iPhone 13 Pro operating (10% electric quantity) (distance 8 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	6.85	5.06	5.86	5.42	5.31	5.44
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-607.15	-608.94	-608.14	-608.58	-608.69	-608.56
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-300.15	-301.94	-301.14	-301.58	-301.69	-301.56

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.248	0.246	0.251	0.251	0.24	0.243
Max H-Field(A/m)	0.197	0.196	0.200	0.200	0.191	0.193
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.433	-1.434	-1.430	-1.430	-1.439	-1.437
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.618	-0.619	-0.615	-0.615	-0.624	-0.622

Measurements was made from all sides and the top of the primary/client pair, with the 8 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 5: EUT(Full Battery) + iPhone 13 Pro operating (10% electric quantity) (distance 10 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	6.03	5.02	4.32	4.21	4.67	5.01
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-607.97	-608.98	-609.68	-609.79	-609.33	-608.99
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-300.97	-301.98	-302.68	-302.79	-302.33	-301.99

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.235	0.234	0.236	0.231	0.234	0.238
Max H-Field(A/m)	0.187	0.186	0.188	0.184	0.186	0.189
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.443	-1.444	-1.442	-1.446	-1.444	-1.441
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.628	-0.629	-0.627	-0.631	-0.629	-0.626

Measurements was made from all sides and the top of the primary/client pair, with the 10 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 6: EUT(Full Battery) + iPhone 13 Pro operating (10% electric quantity) (distance 12 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	6.02	4.32	3.96	4.02	4.03	4.25
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-607.98	-609.68	-610.04	-609.98	-609.97	-609.75
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-300.98	-302.68	-303.04	-302.98	-302.97	-302.75

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.231	0.231	0.23	0.229	0.232	0.235
Max H-Field(A/m)	0.184	0.184	0.183	0.182	0.185	0.187
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.446	-1.446	-1.447	-1.448	-1.445	-1.443
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.631	-0.631	-0.632	-0.633	-0.630	-0.628

Measurements was made from all sides and the top of the primary/client pair, with the 12 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 7: EUT(Full Battery) + iPhone 13 Pro operating (10% electric quantity) (distance 14 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	4.89	4.66	3.65	4.52	3.57	4.03
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-609.11	-609.34	-610.35	-609.48	-610.43	-609.97
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-302.11	-302.34	-303.35	-302.48	-303.43	-302.97

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.231	0.231	0.231	0.229	0.234	0.235
Max H-Field(A/m)	0.184	0.184	0.184	0.182	0.186	0.187
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.446	-1.446	-1.446	-1.448	-1.444	-1.443
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.631	-0.631	-0.631	-0.633	-0.629	-0.628

Measurements was made from all sides and the top of the primary/client pair, with the 14 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 8: EUT(Full Battery) + iPhone 13 Pro operating (10% electric quantity) (distance 16 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	4.55	3.63	3.87	4.09	4.36	4.42
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-609.45	-610.37	-610.13	-609.91	-609.64	-609.58
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-302.45	-303.37	-303.13	-302.91	-302.64	-302.58

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.229	0.228	0.228	0.229	0.231	0.234
Max H-Field(A/m)	0.182	0.182	0.182	0.182	0.184	0.186
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.448	-1.448	-1.448	-1.448	-1.446	-1.444
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.633	-0.633	-0.633	-0.633	-0.631	-0.629

Measurements was made from all sides and the top of the primary/client pair, with the 16 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 9: EUT(Full Battery) + iPhone 13 Pro operating (10% electric quantity) (distance 18 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	3.56	3.25	3.45	3.36	3.87	3.97
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-610.44	-610.75	-610.55	-610.64	-610.13	-610.03
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-303.44	-303.75	-303.55	-303.64	-303.13	-303.03

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.229	0.228	0.229	0.228	0.228	0.229
Max H-Field(A/m)	0.182	0.182	0.182	0.182	0.182	0.182
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.448	-1.448	-1.448	-1.448	-1.448	-1.448
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.633	-0.633	-0.633	-0.633	-0.633	-0.633

Measurements was made from all sides and the top of the primary/client pair, with the 18 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 10: EUT(Full Battery) + iPhone 13 Pro operating (10% electric quantity) (distance 20 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	2.56	2.36	2.51	2.38	2.69	2.38
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-611.44	-611.64	-611.49	-611.62	-611.31	-611.62
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-304.44	-304.64	-304.49	-304.62	-304.31	-304.62

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.228	0.229	0.229	0.228	0.228	0.231
Max H-Field(A/m)	0.182	0.182	0.182	0.182	0.182	0.184
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.448	-1.448	-1.448	-1.448	-1.448	-1.446
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.633	-0.633	-0.633	-0.633	-0.633	-0.631

Measurements was made from all sides and the top of the primary/client pair, with the 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 11: EUT(Full Battery) + iPhone 13 Pro operating (50% electric quantity) (distance 0 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	7.56	6.23	6.05	6.03	5.12	5.65
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-606.44	-607.77	-607.95	-607.97	-608.88	-608.35
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-299.44	-300.77	-300.95	-300.97	-301.88	-301.35

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.247	0.247	0.232	0.241	0.245	0.243
Max H-Field(A/m)	0.197	0.197	0.185	0.192	0.195	0.193
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.433	-1.433	-1.445	-1.438	-1.435	-1.437
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.618	-0.618	-0.630	-0.623	-0.620	-0.622

Measurements was made from all sides and the top of the primary/client pair, with the 0 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 12: EUT(Full Battery) + iPhone 13 Pro operating (90% electric quantity) (distance 0 cm)

E-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max E-Field(V/m)	7.36	6.2	6.01	6.02	4.29	5.04
Limit(V/m)	614	614	614	614	614	614
Margin (V/m)	-606.64	-607.8	-607.99	-607.98	-609.71	-608.96
50% Limit (V/m)	307	307	307	307	307	307
50% Margin (V/m)	-299.64	-300.8	-300.99	-300.98	-302.71	-301.96

H-Field Measurement						
EUT Side	Left	Right	Top	Down	Z-axis 1	Z-axis 2
Max H-Field(uT)	0.239	0.242	0.234	0.239	0.238	0.242
Max H-Field(A/m)	0.190	0.193	0.186	0.190	0.189	0.193
Limit(A/m)	1.63	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.440	-1.437	-1.444	-1.440	-1.441	-1.437
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.625	-0.622	-0.629	-0.625	-0.626	-0.622

Measurements was made from all sides and the top of the primary/client pair, with the 0 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

3. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (FCC MPE Test Photos, Reference No.: 2204WDG0403-1)

--- END ---