

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.209)

Report No.: RFBCBS-WTW-P26010027

FCC ID: K7SBPD016

Product: BoostCharge Slim Magnetic Power Bank 10K with Stand, BoostCharge Slim Magnetic Power Bank 10K (refer to item 3.1 for more details)

Brand: belkin

Model No.: BPD016, BBA018 (refer to item 3.1 for more details)

Received Date: 2026/1/5

Test Date: 2026/1/21 ~ 2026/1/23

Issued Date: 2026/3/12

Applicant: Belkin International, Inc.

Address: 555 S. Aviation Blvd., Suite 180, El Segundo, CA 90245, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan

FCC Registration / 788550 / TW0003

Designation Number:

Approved by: _____

Jeremy Lin

Jeremy Lin / Project Engineer

, Date: _____

2026/3/12

This test report consists of 39 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Vera Huang / Specialist



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate.....	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	5
2.2 Supplementary Information	5
3 General Information	6
3.1 General Description.....	6
3.2 Antenna Description of EUT.....	7
3.3 Channel List.....	7
3.4 Test Mode Applicability and Tested Channel Detail.....	8
3.5 Test Program Used and Operation Descriptions	9
3.6 Connection Diagram of EUT and Peripheral Devices	9
3.7 Configuration of Peripheral Devices and Cable Connections	10
4 Test Instruments	11
4.1 AC Power Conducted Emissions	11
4.2 Radiated Emissions below 30 MHz.....	11
4.3 Radiated Emissions above 30 MHz	12
5 Limits of Test Items.....	13
5.1 AC Power Conducted Emissions	13
5.2 Radiated Emissions below 30 MHz.....	13
5.3 Radiated Emissions above 30 MHz	13
6 Test Arrangements.....	14
6.1 AC Power Conducted Emissions	14
6.1.1 Test Setup	14
6.1.2 Test Procedure	14
6.2 Radiated Emissions below 30 MHz.....	15
6.2.1 Test Setup	15
6.2.2 Test Procedure	15
6.3 Radiated Emissions above 30 MHz	16
6.3.1 Test Setup	16
6.3.2 Test Procedure	16
7 Test Results of Test Item	17
7.1 AC Power Conducted Emissions	17
7.2 Radiated Emissions below 30 MHz.....	23
7.3 Radiated Emissions above 30 MHz	32
8 Pictures of Test Arrangements	38
9 Information of the Testing Laboratories	39

Release Control Record

Issue No.	Description	Date Issued
RFBCBS-WTW-P26010027	Original Release	2026/3/12

1 Certificate

Product: BoostCharge Slim Magnetic Power Bank 10K with Stand, BoostCharge Slim Magnetic Power Bank 10K (refer to item 3.1 for more details)

Brand: belkin

Test Model: BPD016, BBA018 (refer to item 3.1 for more details)

Sample Status: Engineering sample

Applicant: Belkin International, Inc.

Test Date: 2026/1/21 ~ 2026/1/23

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.209)

Measurement procedure: ANSI C63.10-2020

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.209)			
Standard / Clause	Test Item	Result	Remark
15.207	AC Power Conducted Emissions	Pass	Minimum passing margin is -13.22 dB at 0.69800 MHz
15.209	Radiated Emissions below 30 MHz	Pass	Minimum passing margin is -21.3 dB at 13.7149 MHz
15.209	Radiated Emissions above 30 MHz	Pass	Minimum passing margin is -2.6 dB at 440.31 MHz

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)
AC Power Conducted Emissions	9 kHz ~ 30 MHz	2.90 dB
Radiated Emissions below 30 MHz	9 kHz ~ 30 MHz	2.44 dB
Radiated Emissions above 30 MHz	9 kHz ~ 30 MHz	2.44 dB
	30 MHz ~ 1 GHz	2.95 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description

Product	BoostCharge Slim Magnetic Power Bank 10K with Stand, BoostCharge Slim Magnetic Power Bank 10K
Brand	belkin
Test Model	BPD016, BBA018
Status of EUT	Engineering sample
Power Supply Rating	5V=3A, 9V=3A, 12V=2.5A, 15V=2A
Modulation Type	FSK
Operating Frequency	360kHz (PTx), for iPhone 111-148kHz (PTx): 127.7kHz, for iPhone 111-148kHz (PTx): 144kHz, for Android phone
Number of Channel	2
Output Power (Field Strength)	360kHz: -28.9dBuV/m (PK) (300m) -35.3dBuV/m (AV) (300m) 127.7kHz: -8.0dBuV/m (PK) (300m) -10.3dBuV/m (AV) (300m)

Note:

1. All models are listed as below.

Product Name	Model	Difference
BoostCharge Slim Magnetic Power Bank 10K with Stand	BPD016	With kickstand, no rear magnetic ring
BoostCharge Slim Magnetic Power Bank 10K	BBA018	No kickstand, with rear magnetic ring

2. The EUT uses following accessories.

Item	Brand	Model	Specification
Battery	Lishen	SP526578SR	Power Rating: 3.87V, 19.35Wh
Type C USB Cable (optional)	belkin	ALN-CMCM2-0710-001 (Black) ALN-CMCM2-0710-002 (White)	0.6m cable

3. The EUT uses following support unit.

Item	Brand	Model	Specification
USB-C Power Adapter	belkin	WCA013dq	AC Input power: 100~240V, 1.0A, 50-60Hz DC Output power: (PDO) 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=2.25A (PPS) 5V-16V=2.8A

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 Antenna Description of EUT

Antenna	Frequency range	Antenna Type	Connector Type
Phone Charging Coil	111-148kHz, 360kHz	Coil	None (soldered)

* Due to radiated measurements are made and the antenna gain is already accounted for this device, so provide an antenna datasheet and/or antenna measurement report is not required. The antenna dimensions and pictures (include antenna wire length if have) are stated in EUT photo exhibit.

3.3 Channel List

2 channels are provided to this EUT:

Channel	Frequency
1	360kHz
2	111~148kHz @127.7kHz

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. EUT has 2 models and difference is as listed: BPD016: With kickstand, no rear magnetic ring / BBA018: No kickstand, with rear magnetic ring. Pre-scan these models and find the worst case as a representative test condition. 2. EUT can be used in the following ways: X-axis / Y-axis / Z-axis / Kickstand for BPD016. Pre-scan these ways and find the worst case as a representative test condition. 3. Coil can be operated in one of the frequencies, where the frequency range is 111kHz ~ 148kHz for iPhone_127.7kHz and Android phone_144kHz. Pre-scan these frequencies and find the worst case as a representative test condition. 4. EUT can be operated 2 modes: Power Bank Mode / Pass Thru Mode. Pre-scan these ways and find the worst case as a representative test condition.
Worst Case:	1. The Worst Model: BPD018 2. X-axis / Y-axis / Z-axis / Kickstand. The Worst Condition: X-axis 3. 111kHz ~ 148kHz Worst Frequency: for iPhone_127.7 kHz 4. The Worst Operating Mode: Pass Thru Mode

Following channel(s) was (were) selected for the final test as listed below:

Test Item	EUT Configure Mode	Tested Frequency	Modulation
AC Power Conducted Emissions	A	360kHz	FSK
	B	127.7kHz	FSK
	C	Standby	-
Radiated Emissions below 30 MHz	A	360kHz	FSK
	B	127.7kHz	FSK
	C	Standby	-
Radiated Emissions above 30 MHz	A	360kHz	FSK
	B	127.7kHz	FSK
	C	Standby	-
EUT Configure Mode:	A	Charging Mode - 360kHz (iPhone 17 Pro Max)	
	B	Charging Mode - 127.7kHz (iPhone 11 Pro Max)	
	C	Standby Mode	

Note.


- 1.) For detailed configuration of system under test, please refer to Test Set Up Photos.
- 2.) Power Bank Mode:
 - One device charging: 15W Qi2 wireless charging iPhone, or 1 x USB-C 30W max output
 - 1 x USB-C 12W + Wireless charging 7.5W
- Pass-Thru Mode:
 - 15W Qi2 wireless output for iPhone (Provided a 20W or larger PSU is connected)

3.5 Test Program Used and Operation Descriptions


No test software is required during testing. The EUT can be under transmission condition for testing after powering on.

3.6 Connection Diagram of EUT and Peripheral Devices


Mode A



Mode B



Mode C



3.7 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	USB-C Power Adapter	belkin	WCA013dq	N/A	N/A	Supplied by applicant
B	iPhone 17 Pro Max	APPLE	A3526	N/A	N/A	Supplied by applicant
C	Cellphone	Motorola	XT2201-1	N/A	N/A	Supplied by applicant
D	iPhone 11 Pro Max	APPLE	A2218	N/A	N/A	Supplied by applicant

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	Type C USB Cable	1	0.6	Yes	0	Accessory of EUT
2	Type C USB Cable	1	1	Yes	0	Provided by Lab

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance HUBER+SUHNER	E1-011276	01	2025/2/11	2026/2/10
	E1-011277	02	2025/10/31	2026/10/30
	E1-011313	11	2025/2/11	2026/2/10
DC LISN Schwarzbeck	NNBM 8126G	8126G-069	2025/11/3	2026/11/2
Diode Pulse Limiter Schwarzbeck	VTSD 9561 F-N	01617	2025/8/23	2026/8/22
EMI Test Receiver R&S	ESR3	102783	2025/12/15	2026/12/14
LISN R&S	ESH2-Z5	100100	2025/3/5	2026/3/4
	ESH3-Z5	100312	2025/8/29	2026/8/28
RF Coaxial Cable Woken	5D-FB	Cable-cond2-01	2025/8/23	2026/8/22
Software BVADT	BVADT_Conf_ V7.4.1.0	N/A	N/A	N/A
V-LISN Schwarzbeck	NNBL 8226-2	8226-142	2025/8/27	2026/8/26

Notes:

1. The test was performed in HY - Conduction 2.
2. Tested Date: 2026/1/23

4.2 Radiated Emissions below 30 MHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn Max-Full	MFA-440H	AT93021705	N/A	N/A
Loop Antenna TESEQ	HLA 6121	45745	2025/9/1	2026/8/31
MXE EMI Receiver Agilent	N9038A	MY51210203	2025/8/27	2026/8/26
Preamplifier EMCI	EMC001340	980201	2025/9/21	2026/9/20
RF Coaxial Cable Woken	8D-FB	Cable-Ch10-01	2025/9/21	2026/9/20
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table Max-Full	MFT-201SS	N/A	N/A	N/A
Turn Table Controller Max-Full	MG-7802	N/A	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 5.
2. Tested Date: 2026/1/21 ~ 2026/1/22

4.3 Radiated Emissions above 30 MHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn Max-Full	MFA-440H	AT93021705	N/A	N/A
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-472	2025/9/16	2026/9/15
Loop Antenna TESEQ	HLA 6121	45745	2025/9/1	2026/8/31
MXE EMI Receiver Agilent	N9038A	MY51210203	2025/8/27	2026/8/26
Preamplifier EMCI	EMC 330H	980112	2025/9/21	2026/9/20
	EMC001340	980201	2025/9/21	2026/9/20
RF Coaxial Cable Woken	8D-FB	Cable-Ch10-01	2025/9/21	2026/9/20
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table Max-Full	MFT-201SS	N/A	N/A	N/A
Turn Table Controller Max-Full	MG-7802	N/A	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 5.
2. Tested Date: 2026/1/23

5 Limits of Test Items

5.1 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.2 Radiated Emissions below 30 MHz

Frequency (MHz)	Field Strength (dBuV/m)		Measurement Distance (meters)
	uV/m	dBuV/m	
0.009 – 0.490	2400 / F (kHz)	48.52-13.80	300
0.490 – 1.705	24000 / F (kHz)	33.80-22.97	30
1.705 – 30.0	30	29.54	30

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, and the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

5.3 Radiated Emissions above 30 MHz

Frequency (MHz)	Measurement Distance (at 3m)	
	uV/m	dBuV/m
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
Above 960	500	54.0


Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

6 Test Arrangements

6.1 AC Power Conducted Emissions

6.1.1 Test Setup



Note: 1. Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.1.2 Test Procedure


- Exploratory ac power-line conducted emission measurements: The EUT shall be operated on the mid channel and in the mode with highest output power unless the fundamental operates in the AC power-line emission test range then the EUT shall be operated in the range of typical modes of operation.
- The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.

6.2 Radiated Emissions below 30 MHz

6.2.1 Test Setup

For Radiated emission below 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.2.2 Test Procedure

For Radiated emission below 30 MHz

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode (however, peak detector measurements may be used to determine compliance with QP requirements), except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.


Notes:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
- All modes of operation were investigated and the worst-case emissions are reported.
- KDB 414788 OATS and Chamber Correlation Justification.
 - Based on FCC 15.31(f)(2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.
 - OATs and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

6.3 Radiated Emissions above 30 MHz

6.3.1 Test Setup

For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.3.2 Test Procedure

For Radiated emission above 30 MHz

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz (however, peak detector measurements may be used to determine compliance with QP requirements).

Notes:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequencies less than or equal to 1 GHz (however, peak detector measurements may be used to determine compliance with QP requirements).
- All modes of operation were investigated and the worst-case emissions are reported.

7 Test Results of Test Item

7.1 AC Power Conducted Emissions


Mode A

RF Mode	WPT	Channel	CH 1 : 360 kHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 69% RH
Tested By	Thomas Cheng		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.23351	10.30	25.82	9.19	36.12	19.49	62.32	52.32	-26.20	-32.83
2	0.34600	10.37	23.22	5.86	33.59	16.23	59.06	49.06	-25.47	-32.83
3	0.70600	10.46	24.67	9.93	35.13	20.39	56.00	46.00	-20.87	-25.61
4	1.23800	10.53	19.81	2.65	30.34	13.18	56.00	46.00	-25.66	-32.82
5	1.66600	10.55	19.76	5.80	30.31	16.35	56.00	46.00	-25.69	-29.65
6	3.01800	10.67	14.98	1.88	25.65	12.55	56.00	46.00	-30.35	-33.45

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	WPT	Channel	CH 1 : 360 kHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 69% RH
Tested By	Thomas Cheng		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.21800	10.32	33.35	10.22	43.67	20.54	62.89	52.89	-19.22	-32.35
2	0.47000	10.46	29.16	8.62	39.62	19.08	56.51	46.51	-16.89	-27.43
3	0.61000	10.49	31.00	8.47	41.49	18.96	56.00	46.00	-14.51	-27.04
4	1.27000	10.58	29.57	6.28	40.15	16.86	56.00	46.00	-15.85	-29.14
5	2.15400	10.63	28.06	7.64	38.69	18.27	56.00	46.00	-17.31	-27.73
6	6.98600	10.89	20.83	6.98	31.72	17.87	60.00	50.00	-28.28	-32.13

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Mode B

RF Mode	WPT	Channel	CH 2 : 127.7 kHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 69% RH
Tested By	Thomas Cheng		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.24200	10.31	25.81	8.68	36.12	18.99	62.03	52.03	-25.91	-33.04
2	0.73800	10.47	25.62	13.20	36.09	23.67	56.00	46.00	-19.91	-22.33
3	1.16600	10.53	18.86	2.08	29.39	12.61	56.00	46.00	-26.61	-33.39
4	1.64200	10.55	23.24	6.70	33.79	17.25	56.00	46.00	-22.21	-28.75
5	12.59400	10.92	14.13	2.83	25.05	13.75	60.00	50.00	-34.95	-36.25
6	27.72200	10.90	8.39	1.51	19.29	12.41	60.00	50.00	-40.71	-37.59

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	WPT	Channel	CH 2 : 127.7 kHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 69% RH
Tested By	Thomas Cheng		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.26200	10.35	25.47	7.32	35.82	17.67	61.37	51.37	-25.55	-33.70
2	0.47000	10.46	24.83	8.61	35.29	19.07	56.51	46.51	-21.22	-27.44
3	0.79000	10.52	25.33	10.64	35.85	21.16	56.00	46.00	-20.15	-24.84
4	1.93000	10.62	24.74	9.45	35.36	20.07	56.00	46.00	-20.64	-25.93
5	6.26600	10.87	18.65	3.49	29.52	14.36	60.00	50.00	-30.48	-35.64
6	13.27400	11.07	17.57	5.21	28.64	16.28	60.00	50.00	-31.36	-33.72

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Mode C

RF Mode	Standby		
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 69% RH
Tested By	Thomas Cheng		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18200	10.27	20.18	2.88	30.45	13.15	64.39	54.39	-33.94	-41.24
2	0.29400	10.34	19.79	3.95	30.13	14.29	60.41	50.41	-30.28	-36.12
3	0.69504	10.46	23.76	16.10	34.22	26.56	56.00	46.00	-21.78	-19.44
4	1.28200	10.53	16.80	4.25	27.33	14.78	56.00	46.00	-28.67	-31.22
5	1.85000	10.56	13.69	2.74	24.25	13.30	56.00	46.00	-31.75	-32.70
6	3.12200	10.68	11.30	1.10	21.98	11.78	56.00	46.00	-34.02	-34.22

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	Standby		
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 69% RH
Tested By	Thomas Cheng		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.26200	10.35	24.14	7.87	34.49	18.22	61.37	51.37	-26.88	-33.15
2	0.43000	10.45	20.66	7.80	31.11	18.25	57.25	47.25	-26.14	-29.00
3	0.69800	10.50	30.95	22.28	41.45	32.78	56.00	46.00	-14.55	-13.22
4	1.01800	10.57	20.30	8.42	30.87	18.99	56.00	46.00	-25.13	-27.01
5	1.66200	10.60	18.29	5.98	28.89	16.58	56.00	46.00	-27.11	-29.42
6	4.98600	10.84	13.16	1.14	24.00	11.98	56.00	46.00	-32.00	-34.02

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



7.2 Radiated Emissions below 30 MHz


Mode A

RF Mode	WPT	Channel	CH 1 : 360 kHz
Frequency Range	9 kHz ~ 150 kHz; 150 kHz ~ 30 MHz	Detector Function & Bandwidth	Peak (PK) / Average (AV), 200 Hz; Peak (PK) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	18 °C, 63% RH
Tested By	Thomas Cheng		

Antenna Polarity : Parallel								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*0.3600	-28.9 PK	36.5	-65.4	1.00	152	31.3	-60.2
2	*0.3600	-35.3 AV	16.5	-51.8	1.00	152	24.9	-60.2
3	0.7200	1.3 PK	30.5	-29.2	1.00	338	21.6	-20.3
4	0.7200	-9.1 AV	30.5	-39.6	1.00	338	11.2	-20.3
5	4.3577	-7.6 PK	29.5	-37.1	1.00	2	12.5	-20.1
6	9.3962	-5.1 PK	29.5	-34.6	1.00	147	14.0	-19.1
7	11.8255	4.1 PK	29.5	-25.4	1.00	216	22.5	-18.4
8	15.9042	-5.5 PK	29.5	-35.0	1.00	50	13.1	-18.6
9	21.7825	-5.4 PK	29.5	-34.9	1.00	161	13.0	-18.4
10	27.8706	-6.0 PK	29.5	-35.5	1.00	331	11.8	-17.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The test distance for below 0.49 MHz is 3 m, extrapolate the measured field strength to a distance of 300 meters.
Distance factor@3 m = $40 \cdot \log(3/300) = -80$ dB
7. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.
Distance factor@3 m = $40 \cdot \log(3/30) = -40$ dB




RF Mode	WPT	Channel	CH 1 : 360 kHz
Frequency Range	9 kHz ~ 150 kHz; 150 kHz ~ 30 MHz	Detector Function & Bandwidth	Peak (PK) / Average (AV), 200 Hz; Peak (PK) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	18 °C, 63% RH
Tested By	Thomas Cheng		

Antenna Polarity : Perpendicular								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*0.3600	-32.6 PK	36.5	-69.1	1.00	296	27.6	-60.2
2	*0.3600	-40.1 AV	16.5	-56.6	1.00	296	20.1	-60.2
3	0.7200	-1.8 PK	30.5	-32.3	1.00	220	18.5	-20.3
4	0.7200	-15.4 AV	30.5	-45.9	1.00	220	4.9	-20.3
5	2.2883	-2.6 PK	29.5	-32.1	1.00	164	17.8	-20.4
6	7.9566	-6.3 PK	29.5	-35.8	1.00	37	12.9	-19.2
7	11.8255	1.1 PK	29.5	-28.4	1.00	208	19.5	-18.4
8	13.7149	-0.5 PK	29.5	-30.0	1.00	19	18.2	-18.7
9	18.5734	-3.5 PK	29.5	-33.0	1.00	2	14.3	-17.8
10	27.2408	-6.3 PK	29.5	-35.8	1.00	2	11.7	-18.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. The test distance for below 0.49 MHz is 3 m, extrapolate the measured field strength to a distance of 300 meters.
Distance factor@3 m = $40 \cdot \log(3/300) = -80$ dB
7. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.
Distance factor@3 m = $40 \cdot \log(3/30) = -40$ dB




RF Mode	WPT	Channel	CH 1 : 360 kHz
Frequency Range	9 kHz ~ 150 kHz; 150 kHz ~ 30 MHz	Detector Function & Bandwidth	Peak (PK) / Average (AV), 200 Hz; Peak (PK) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	18 °C, 63% RH
Tested By	Thomas Cheng		

Antenna Polarity : Ground-parallel								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*0.3600	-31.1 PK	36.5	-67.6	1.00	41	29.1	-60.2
2	*0.3600	-38.4 AV	16.5	-54.9	1.00	41	21.8	-60.2
3	0.7200	-4.0 PK	30.5	-34.5	1.00	193	16.3	-20.3
4	0.7200	-15.6 AV	30.5	-46.1	1.00	193	4.7	-20.3
5	3.6379	-7.4 PK	29.5	-36.9	1.00	289	12.9	-20.3
6	8.7364	-6.7 PK	29.5	-36.2	1.00	198	12.6	-19.3
7	13.7149	8.2 PK	29.5	-21.3	1.00	19	26.9	-18.7
8	15.3344	-0.6 PK	29.5	-30.1	1.00	324	18.2	-18.8
9	21.7825	-4.6 PK	29.5	-34.1	1.00	26	13.8	-18.4
10	27.5407	-6.7 PK	29.5	-36.2	1.00	281	11.2	-17.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The test distance for below 0.49 MHz is 3 m, extrapolate the measured field strength to a distance of 300 meters.
Distance factor@3 m = $40 \cdot \log(3/300) = -80$ dB
7. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.
Distance factor@3 m = $40 \cdot \log(3/30) = -40$ dB




Mode B

RF Mode	WPT	Channel	CH 2 : 127.7 kHz
Frequency Range	9 kHz ~ 150 kHz; 150 kHz ~ 30 MHz	Detector Function & Bandwidth	Peak (PK) / Average (AV), 200 Hz; Peak (PK) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	18 °C, 63% RH
Tested By	Thomas Cheng		

Antenna Polarity : Parallel								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*0.1277	-8.0 PK	45.5	-53.5	1.00	245	52.6	-60.6
2	*0.1277	-10.3 AV	25.5	-35.8	1.00	245	50.3	-60.6
3	0.2554	-24.9 PK	39.5	-64.4	1.00	335	35.3	-60.2
4	0.2554	-31.1 AV	19.5	-50.6	1.00	335	29.1	-60.2
5	0.6388	4.9 PK	31.5	-26.6	1.00	285	25.2	-20.2
6	3.7879	-7.4 PK	29.5	-36.9	1.00	167	12.9	-20.3
7	9.0063	-6.4 PK	29.5	-36.0	1.00	327	12.9	-19.3
8	14.5246	-5.4 PK	29.5	-34.9	1.00	240	13.5	-18.9
9	19.0233	-5.1 PK	29.5	-34.6	1.00	63	12.6	-17.7
10	26.4911	-6.6 PK	29.5	-36.2	1.00	55	11.6	-18.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The test distance for below 0.49 MHz is 3 m, extrapolate the measured field strength to a distance of 300 meters.
Distance factor@3 m = $40 \cdot \log(3/300) = -80$ dB
7. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.
Distance factor@3 m = $40 \cdot \log(3/30) = -40$ dB




RF Mode	WPT	Channel	CH 2 : 127.7 kHz
Frequency Range	9 kHz ~ 150 kHz; 150 kHz ~ 30 MHz	Detector Function & Bandwidth	Peak (PK) / Average (AV), 200 Hz; Peak (PK) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	18 °C, 63% RH
Tested By	Thomas Cheng		

Antenna Polarity : Perpendicular								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*0.1277	-12.8 PK	45.5	-58.3	1.00	253	47.8	-60.6
2	*0.1277	-16.3 AV	25.5	-41.8	1.00	253	44.3	-60.6
3	0.2554	-27.7 PK	39.5	-67.2	1.00	38	32.5	-60.2
4	0.2554	-35.3 AV	19.5	-54.8	1.00	38	24.9	-60.2
5	0.5188	1.4 PK	33.3	-31.9	1.00	65	21.6	-20.2
6	2.2583	-2.6 PK	29.5	-32.1	1.00	343	17.8	-20.4
7	7.2668	-7.3 PK	29.5	-36.8	1.00	173	11.8	-19.1
8	13.5649	-1.3 PK	29.5	-30.8	1.00	102	17.4	-18.7
9	15.3344	-1.9 PK	29.5	-31.4	1.00	18	16.9	-18.8
10	25.2014	-4.7 PK	29.5	-34.2	1.00	18	13.4	-18.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The test distance for below 0.49 MHz is 3 m, extrapolate the measured field strength to a distance of 300 meters.
Distance factor@3 m = $40 \cdot \log(3/300) = -80$ dB
7. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.
Distance factor@3 m = $40 \cdot \log(3/30) = -40$ dB




RF Mode	WPT	Channel	CH 2 : 127.7 kHz
Frequency Range	9 kHz ~ 150 kHz; 150 kHz ~ 30 MHz	Detector Function & Bandwidth	Peak (PK) / Average (AV), 200 Hz; Peak (PK) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	18 °C, 63% RH
Tested By	Thomas Cheng		

Antenna Polarity : Ground-parallel								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*0.1277	-17.5 PK	45.5	-63.0	1.00	139	43.1	-60.6
2	*0.1277	-30.4 AV	25.5	-55.9	1.00	139	30.2	-60.6
3	0.2554	-31.4 PK	39.5	-70.9	1.00	170	28.8	-60.2
4	0.2554	-42.5 AV	19.5	-62.0	1.00	170	17.7	-60.2
5	0.5488	2.1 PK	32.8	-30.7	1.00	144	22.3	-20.2
6	6.1272	-6.3 PK	29.5	-35.8	1.00	103	12.6	-18.9
7	13.5649	4.4 PK	29.5	-25.1	1.00	141	23.1	-18.7
8	15.3344	5.6 PK	29.5	-23.9	1.00	180	24.4	-18.8
9	16.9539	3.6 PK	29.5	-25.9	1.00	110	21.9	-18.3
10	24.6316	-5.5 PK	29.5	-35.0	1.00	8	12.8	-18.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The test distance for below 0.49 MHz is 3 m, extrapolate the measured field strength to a distance of 300 meters.
Distance factor@3 m = $40 \cdot \log(3/300) = -80$ dB
7. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.
Distance factor@3 m = $40 \cdot \log(3/30) = -40$ dB




Mode C

RF Mode	Standby		
Frequency Range	9 kHz ~ 150 kHz; 150 kHz ~ 30 MHz	Detector Function & Bandwidth	Quasi-Peak (QP), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	18 °C, 63% RH
Tested By	Thomas Cheng		

Antenna Polarity : Parallel								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2.6482	-6.2 QP	29.5	-35.7	1.00	217	14.3	-20.5
2	7.2368	-5.7 QP	29.5	-35.2	1.00	30	13.4	-19.1
3	11.4956	-5.4 QP	29.5	-34.9	1.00	159	13.1	-18.5
4	17.0139	-5.9 QP	29.5	-35.4	1.00	290	12.4	-18.3
5	22.4723	-6.1 QP	29.5	-35.6	1.00	2	12.4	-18.5
6	27.8706	-6.4 QP	29.5	-35.9	1.00	65	11.4	-17.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.
Distance factor@3 m = $40 \cdot \log(3/30) = -40$ dB




RF Mode	Standby		
Frequency Range	9 kHz ~ 150 kHz; 150 kHz ~ 30 MHz	Detector Function & Bandwidth	Quasi-Peak (QP), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	18 °C, 63% RH
Tested By	Thomas Cheng		

Antenna Polarity : Perpendicular								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2.2583	-4.1 QP	29.5	-33.6	1.00	318	16.3	-20.4
2	6.1871	-6.0 QP	29.5	-35.5	1.00	137	12.9	-18.9
3	11.5855	-5.3 QP	29.5	-34.8	1.00	286	13.1	-18.4
4	15.3344	-2.1 QP	29.5	-31.6	1.00	174	16.7	-18.8
5	20.7328	-5.7 QP	29.5	-35.2	1.00	263	12.4	-18.1
6	27.3308	-6.7 QP	29.5	-36.2	1.00	171	11.3	-18.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.
Distance factor@3 m = $40 \cdot \log(3/30) = -40$ dB




RF Mode	Standby		
Frequency Range	9 kHz ~ 150 kHz; 150 kHz ~ 30 MHz	Detector Function & Bandwidth	Peak (PK), 200 Hz; Peak (PK), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	18 °C, 63% RH
Tested By	Thomas Cheng		

Antenna Polarity : Ground-parallel								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1.5086	-3.0 PK	24.0	-27.0	1.00	185	17.4	-20.4
2	7.9266	-5.7 PK	29.5	-35.2	1.00	78	13.5	-19.2
3	13.5649	3.0 PK	29.5	-26.5	1.00	348	21.7	-18.7
4	15.3344	5.2 PK	29.5	-24.3	1.00	132	24.0	-18.8
5	16.9539	3.6 PK	29.5	-25.9	1.00	180	21.9	-18.3
6	25.0215	-2.9 PK	29.5	-32.4	1.00	45	15.1	-18.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.
Distance factor@3 m = $40 \cdot \log(3/30) = -40$ dB



7.3 Radiated Emissions above 30 MHz


Mode A

RF Mode	WPT	Channel	CH 1 : 360 kHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	78.50	31.4 QP	40.0	-8.6	1.00 H	252	48.2	-16.8
2	192.96	32.5 QP	43.5	-11.0	1.00 H	231	47.8	-15.3
3	269.59	34.1 QP	46.0	-11.9	1.00 H	265	46.7	-12.6
4	359.80	40.6 QP	46.0	-5.4	1.00 H	247	50.9	-10.3
5	440.31	43.4 QP	46.0	-2.6	1.00 H	303	51.2	-7.8
6	920.46	38.3 QP	46.0	-7.7	1.00 H	180	37.7	0.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.




RF Mode	WPT	Channel	CH 1 : 360 kHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	18 °C, 63% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	53.28	32.1 QP	40.0	-7.9	1.00 V	263	44.2	-12.1
2	86.26	33.5 QP	40.0	-6.5	1.00 V	188	51.8	-18.3
3	192.96	29.4 QP	43.5	-14.1	1.00 V	76	44.7	-15.3
4	440.31	38.5 QP	46.0	-7.5	1.00 V	159	46.3	-7.8
5	519.85	37.0 QP	46.0	-9.0	1.00 V	142	42.7	-5.7
6	920.46	39.2 QP	46.0	-6.8	1.00 V	202	38.6	0.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.




Mode B

RF Mode	WPT	Channel	CH 2 : 127.7 kHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	18 °C, 63% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	77.53	31.2 QP	40.0	-8.8	1.00 H	285	47.7	-16.5
2	192.96	31.9 QP	43.5	-11.6	1.00 H	252	47.2	-15.3
3	296.75	31.5 QP	46.0	-14.5	1.00 H	242	43.3	-11.8
4	359.80	39.4 QP	46.0	-6.6	1.00 H	249	49.7	-10.3
5	440.31	43.3 QP	46.0	-2.7	1.00 H	300	51.1	-7.8
6	920.46	39.7 QP	46.0	-6.3	1.00 H	2	39.1	0.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.




RF Mode	WPT	Channel	CH 2 : 127.7 kHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	18 °C, 63% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	53.28	32.1 QP	40.0	-7.9	1.00 V	263	44.2	-12.1
2	86.26	33.5 QP	40.0	-6.5	1.00 V	188	51.8	-18.3
3	192.96	29.4 QP	43.5	-14.1	1.00 V	76	44.7	-15.3
4	440.31	38.5 QP	46.0	-7.5	1.00 V	159	46.3	-7.8
5	519.85	37.0 QP	46.0	-9.0	1.00 V	142	42.7	-5.7
6	920.46	39.2 QP	46.0	-6.8	1.00 V	202	38.6	0.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.




Mode C

RF Mode	Standby		
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	18 °C, 63% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	77.53	30.7 QP	40.0	-9.3	1.00 H	325	47.2	-16.5
2	125.06	28.8 QP	43.5	-14.7	1.00 H	58	42.6	-13.8
3	192.96	33.0 QP	43.5	-10.5	1.00 H	223	48.3	-15.3
4	359.80	35.8 QP	46.0	-10.2	2.00 H	236	46.1	-10.3
5	440.31	41.5 QP	46.0	-4.5	1.00 H	299	49.3	-7.8
6	925.31	38.9 QP	46.0	-7.1	2.00 H	257	38.3	0.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.




RF Mode	Standby		
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	18 °C, 63% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	52.31	33.4 QP	40.0	-6.6	1.00 V	1	45.4	-12.0
2	120.21	30.5 QP	43.5	-13.0	1.00 V	88	44.8	-14.3
3	440.31	36.7 QP	46.0	-9.3	1.50 V	161	44.5	-7.8
4	519.85	35.5 QP	46.0	-10.5	1.00 V	150	41.2	-5.7
5	746.83	39.3 QP	46.0	-6.7	2.00 V	18	40.0	-0.7
6	925.31	37.4 QP	46.0	-8.6	1.50 V	166	36.8	0.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.



8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---