




CH1




CH6



CH11



CH6 (Turbo)







EUT	Wireless PCI Adapter	MODEL	F5D7001
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 67% RH, 991 hPa
PA	2	TESTED BY	Leo Hung

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-11.70	8	PASS
6	2437	-11.46	8	PASS
11	2462	-11.92	8	PASS
6 (Turbo)	2437	-14.87	8	PASS


CH1




CH6



CH11



CH6 (Turbo)



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 100MHz bandwidth from band edge. The band edges were measured and recorded.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation.

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6.



4.6.6 TEST RESULTS


The spectrum plots are attached on the following 12 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).


4.6.7 TEST RESULTS(A)


PA 1:


The band edge emission plot of CCK technique on the following 1~2 pages show 60.31dB delta between carrier maximum power and local maximum emission in restrict band (2.3888GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.8 is 107.42dBuV/m, so the maximum field strength in restrict band is $107.42 - 60.31 = 47.11$ dBuV/m which is under 54dBuV/m limit.

The band edge emission plot of CCK technique on the following 3~4 pages show 57.57dB delta between carrier maximum power and local maximum emission in restrict band (2.4839GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.8 is 106.33dBuV/m, so the maximum field strength in restrict band is $106.33 - 57.57 = 48.76$ dBuV/m which is under 54dBuV/m limit.














PA 2:


The band edge emission plot of CCK technique on the following 1~2 pages show 60.31dB delta between carrier maximum power and local maximum emission in restrict band (2.3888GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.8 is 105.52dBuV/m, so the maximum field strength in restrict band is $105.52 - 60.31 = 45.21$ dBuV/m which is under 54dBuV/m limit.

The band edge emission plot of CCK technique on the following 3~4 pages show 57.57dB delta between carrier maximum power and local maximum emission in restrict band (2.4839GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.8 is 104.54dBuV/m, so the maximum field strength in restrict band is $104.54 - 57.57 = 46.97$ dBuV/m which is under 54dBuV/m limit.









4.6.8 TEST RESULTS(B)

PA 1:

Normal mode


The band edge emission plot of OFDM technique on the following 1~2 pages show 54.90dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.9 is 105.34dBuV/m, so the maximum field strength in restrict band is $105.34 - 54.90 = 50.44$ dBuV/m which is under 54dBuV/m limit.


The band edge emission plot of OFDM technique on the following 3~4 pages show 54.10dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.9 is 107.07dBuV/m, so the maximum field strength in restrict band is $107.07 - 54.10 = 52.97$ dBuV/m which is under 54dBuV/m limit.


Turbo mode


The band edge emission plot of OFDM technique on the following 5~6 pages show 58.76dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.9 is 102.08dBuV/m, so the maximum field strength in restrict band is $102.08 - 58.76 = 43.32$ dBuV/m which is under 54dBuV/m limit.


The band edge emission plot of OFDM technique on the following 7~8 pages show 59.25dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.9 is 102.08dBuV/m, so the maximum field strength in restrict band is $102.08 - 59.25 = 42.83$ dBuV/m which is under 54dBuV/m limit.




















PA 2:

Normal mode


The band edge emission plot of OFDM technique on the following 1~2 pages show 54.90dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.9 is 105.66dBuV/m, so the maximum field strength in restrict band is $105.66 - 54.90 = 50.76$ dBuV/m which is under 54dBuV/m limit.


The band edge emission plot of OFDM technique on the following 3~4 pages show 54.10dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.9 is 105.43dBuV/m, so the maximum field strength in restrict band is $105.43 - 54.10 = 51.33$ dBuV/m which is under 54dBuV/m limit.


Turbo mode


The band edge emission plot of OFDM technique on the following 5~6 pages show 58.76dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.9 is 100.83dBuV/m, so the maximum field strength in restrict band is $100.83 - 58.76 = 42.07$ dBuV/m which is under 54dBuV/m limit.


The band edge emission plot of OFDM technique on the following 7~8 pages show 59.25dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.9 is 100.83dBuV/m, so the maximum field strength in restrict band is $100.83 - 59.25 = 41.58$ dBuV/m which is under 54dBuV/m limit.






















4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is dipole antenna with Reverse SMA connector. And the maximum Gain of this antenna is 1.8dBi.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST



RADIATED EMISSION TEST



6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC/RF Lab

Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab

Tel: 886-3-3183232
Fax: 886-3-3185050

Linko RF Lab

Tel: 886-3-3270910
Fax: 886-3-3270892

Email: service@mail.adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

Report Format Version 1.5