

Date: 2003-11-07

TEST REPORT

Page 1 of 26

No.: HM111637

FCC PART 15 SUBPART C CERTIFICATION REPORT

FOR LOW POWER TRANSMITTER

TEST REPORT No.: HM111637

Equipment Under Test [EUT]:

Model Number:

Applicant:

FCC ID :

FM Audio Transmitter

F8V367

Belkin Corporation

K7SF8V367

Date: 2003-11-07

TEST REPORT

Page 2 of 26

No.: HM111637

CONTENT:

Cover	Page 1 of 1	
Content	Page 2-3 of 1	
Conclusion	Page 4 of 1	
<u>1.0</u>	<u>General Details</u>	
1.1	Test Laboratory	Page 5 of 1
1.2	Applicant Details	Page 5 of 1
	Applicant	
	HKSTC Code Number for Applicant	
	Manufacturer	
1.3	Equipment Under Test [EUT]	Page 6 of 1
	Description of EUT operation	
1.4	Date of Order	Page 6 of 1
1.5	Submitted Sample	Page 6 of 1
1.6	Test Duration	Page 6 of 1
1.7	Country of Origin	Page 6 of 1
1.8	Additional Information of EUT	Page 7 of 1
<u>2.0</u>	<u>Technical Details</u>	
2.1	Investigations Requested	Page 8 of 1
2.2	Test Standards and Results Summary	Page 8 of 1
<u>3.0</u>	<u>Test Results</u>	
3.1	Emission	Page 9-18 of 1
3.2	Bandwidth Measurement	Page 19-23 of 1

Date: 2003-11-07

No.: HM111637

TEST REPORT

Page 3 of 26

Appendix A

List of Measurement Equipment

Page 24 of 1

Appendix B

Photographs

Page 25-1 of 1

Date: 2003-11-07

TEST REPORT

Page 4 of 26

No.: HM111637

CONCLUSION

The submitted product was deemed to have COMPLIED with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

Verified by
Ivan Toa

K C Lee
for Chief Executive

Date: 2003-11-07

TEST REPORT

Page 5 of 26

No.: HM111637

1.0 General Details

1.1 Test Laboratory

The Hong Kong Standards and Testing Centre Ltd.
EMC Laboratory
10 Dai Wang Street, Taipo Industrial Estate
New Territories, Hong Kong

Telephone: 852 2666 1888
Fax: 852 2664 4353

1.2 Applicant Details Applicant

BELKIN CORPORATION
501 West Walnut Street, Compton CA 90220-5221

HKSTC Code Number for Applicant

SHT009

Manufacturer

N/A

Date: 2003-11-07

TEST REPORT

Page 6 of 26

No.: HM111637

1.3 Equipment Under Test [EUT]

Description of Sample

Product: FM Audio Transmitter
Manufacturer: N/A
Brand Name: BELKIN
Model Number: F8V367
Input Voltage: 3Vd.c ("AAA" size battery x 2)

1.3.1 Description of EUT Operation

The Equipment Under Test (EUT) is an Belkin Corporation., FM Audio Transmitter. The transmitter is a 2 button transmitter. The EUT continues to transmit while button is being pressed., Modulation by IC. and tape is pulse modulation.

1.4 Date of Order

2003-09-05

1.5 Submitted Sample(s):

6 Samples per model

1.6 Test Duration

2003-10-23

1.7 Country of Origin

China

Date: 2003-11-07

TEST REPORT

Page 7 of 26

No.: HM111637

1.8 Additional Information of EUT

	Submitted	Not Available
User Manual	☒	☐
Part List	☒	☐
Circuit Diagram	☒	☐
Printed Circuit Board [PCB] Layout	☒	☐
Block diagram	☒	☐
FCC ID Label	☒	☐

Date: 2003-11-07

TEST REPORT

Page 8 of 26

No.: HM111637

2.0 Technical Details

2.1 Investigations Requested

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15 and ANSI C63.4: 2000 for FCC Certification.

2.2 Test Standards and Results Summary Tables

EMISSION Results Summary						
Test Condition	Test Requirement	Test Method	Class / Severity	Test Result		
				Pass	Failed	N/A
Field Strength of Fundamental Emissions & Spurious Emissions	FCC 47CFR 15.239	ANSI C63.4:2000	N/A	☒	☐	☐
Radiated Emissions, 30MHz to 1GHz	FCC 47CFR 15.209	ANSI C63.4:2000	Class B	☒	☐	☐
Conducted Emissions on AC, 0.15MHz to 30MHz	FCC 47CFR 15.207	ANSI C63.4:2000	Class B	☐	☐	☒

Note: N/A - Not Applicable


3.0 Test Results**3.1 Emission****3.1.1 Radiated Emissions (30 – 1000MHz)**

Test Requirement:	FCC 47CFR 15.109 Class A
Test Method:	ANSI C63.4:2000
Test Date:	2003-10-23
Mode of Operation:	On mode

Test Method:

The sample was placed 0.8m above the ground plane on the OATS *. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

*: OATS [Open Area Test Site] located at HKSTC with a metal ground plane filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 90657.

Test Setup:

Date: 2003-11-07

TEST REPORT

Page 10 of 26

No.: HM111637

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.239]:

Frequency Range of Fundamental [MHz]	Peak Limits [μV/m]	Average Limits [μV/m]
88-108	2,500	250

Results:

Field Strength of Fundamental Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
88.10	30.4	10.4	40.8	109.6	2,500	Horizontal

Field Strength of Fundamental Emissions						
Average Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
88.10	30.1	10.4	40.5	105.9	250	Horizontal

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz ±5.7dB

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

For effective averaging, the bandwidth of the video filter must be smaller than the resolution bandwidth. The higher the ratio of resolution bandwidth to video bandwidth, the greater the averaging will be. Below setting for HP8572A EMI Receiver.

Resolution Bandwidth : 3MHz

Video Bandwidth 1Hz

Date: 2003-11-07

TEST REPORT

Page 11 of 26

No.: HM111637

Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [μV/m]
30-88	100
88-216	150
216-960	200
Above 960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Results :

Radiated Emissions Quasi-Peak						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
176.20	< 1.0	13.2	< 14.2	< 5.1	150	Vertical
264.30	< 1.0	9.8	< 10.8	< 3.5	150	Vertical
352.40	< 1.0	11.5	< 12.5	< 4.2	150	Vertical
440.50	< 1.0	15.9	< 16.9	< 7.0	200	Vertical
528.60	< 1.0	17.4	< 18.4	< 8.3	200	Vertical
616.70	< 1.0	17.2	< 18.2	< 8.1	200	Vertical
704.80	< 1.0	18.8	< 19.8	< 9.8	200	Vertical
792.90	< 1.0	19.7	< 20.7	< 10.8	200	Vertical
881.00	< 1.0	20.6	< 21.6	< 12.0	200	Vertical

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz ±5.7dB

Date: 2003-11-07

TEST REPORT

Page 12 of 26

No.: HM111637

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.239]:

Frequency Range of Fundamental [MHz]	Peak Limits [μV/m]	Average Limits [μV/m]
88-108	2,500	250

Results:

Field Strength of Fundamental Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
88.30	30.3	10.4	40.7	108.4	2,500	Horizontal

Field Strength of Fundamental Emissions						
Average Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
88.30	30.1	10.4	40.5	105.9	250	Horizontal

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz ±5.7dB

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

For effective averaging, the bandwidth of the video filter must be smaller than the resolution bandwidth. The higher the ratio of resolution bandwidth to video bandwidth, the greater the averaging will be. Below setting for HP8572A EMI Receiver.

Resolution Bandwidth : 3MHz
Video Bandwidth 1Hz

Date: 2003-11-07

TEST REPORT

Page 13 of 26

No.: HM111637

Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [μV/m]
30-88	100
88-216	150
216-960	200
Above 960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Results :

Radiated Emissions Quasi-Peak						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
176.60	< 1.0	13.2	< 14.2	< 5.1	150	Vertical
264.90	< 1.0	9.8	< 10.8	< 3.5	150	Vertical
353.20	< 1.0	11.5	< 12.5	< 4.2	150	Vertical
441.50	< 1.0	15.9	< 16.9	< 7.0	200	Vertical
529.80	< 1.0	17.4	< 18.4	< 8.3	200	Vertical
618.10	< 1.0	17.2	< 18.2	< 8.1	200	Vertical
706.40	< 1.0	18.8	< 19.8	< 9.8	200	Vertical
794.70	< 1.0	19.7	< 20.7	< 10.8	200	Vertical
883.00	< 1.0	20.6	< 21.6	< 12.0	200	Vertical

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz ±5.7dB

Date: 2003-11-07

TEST REPORT

Page 14 of 26

No.: HM111637

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.239]:

Frequency Range of Fundamental [MHz]	Peak Limits [μV/m]	Average Limits [μV/m]
88-108	2,500	250

Results:

Field Strength of Fundamental Emissions Peak Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
88.50	31.2	10.4	41.6	120.2	2,500	Horizontal

Field Strength of Fundamental Emissions Average Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	Field Polarity
88.50	31.1	10.4	41.5	118.9	250	Horizontal

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz ±5.7dB

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

For effective averaging, the bandwidth of the video filter must be smaller than the resolution bandwidth. The higher the ratio of resolution bandwidth to video bandwidth, the greater the averaging will be. Below setting for HP8572A EMI Receiver.

Resolution Bandwidth : 3MHz
Video Bandwidth 1Hz

Date: 2003-11-07

TEST REPORT

Page 15 of 26

No.: HM111637

Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [μV/m]
30-88	100
88-216	150
216-960	200
Above 960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Results :

Radiated Emissions Quasi-Peak						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
177.00	< 1.0	13.2	< 14.2	< 5.1	150	Vertical
265.50	< 1.0	9.8	< 10.8	< 3.5	150	Vertical
354.00	< 1.0	11.5	< 12.5	< 4.2	150	Vertical
442.50	< 1.0	15.9	< 16.9	< 7.0	200	Vertical
531.00	< 1.0	17.4	< 18.4	< 8.3	200	Vertical
619.50	< 1.0	17.2	< 18.2	< 8.1	200	Vertical
708.00	< 1.0	18.8	< 19.8	< 9.8	200	Vertical
796.50	< 1.0	19.7	< 20.7	< 10.8	200	Vertical
885.00	< 1.0	20.6	< 21.6	< 12.0	200	Vertical

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz ±5.7dB

Date: 2003-11-07

TEST REPORT

Page 16 of 26

No.: HM111637

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.239]:

Frequency Range of Fundamental [MHz]	Peak Limits [μV/m]	Average Limits [μV/m]
88-108	2,500	250

Results:

Field Strength of Fundamental Emissions Peak Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
88.70	31.8	10.4	42.2	128.8	2,500	Horizontal

Field Strength of Fundamental Emissions Average Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	Field Polarity
88.70	31.5	10.4	41.9	124.5	250	Horizontal

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz ±5.7dB

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

For effective averaging, the bandwidth of the video filter must be smaller than the resolution bandwidth. The higher the ratio of resolution bandwidth to video bandwidth, the greater the averaging will be. Below setting for HP8572A EMI Receiver.

Resolution Bandwidth : 3MHz
Video Bandwidth 1Hz

Date: 2003-11-07

TEST REPORT

Page 17 of 26

No.: HM111637

Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [μV/m]
30-88	100
88-216	150
216-960	200
Above 960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Results :

Radiated Emissions Quasi-Peak						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	E-Field Polarity
177.40	< 1.0	13.2	< 14.2	< 5.1	150	Vertical
266.10	< 1.0	9.8	< 10.8	< 3.5	150	Vertical
354.80	< 1.0	11.5	< 12.5	< 4.2	150	Vertical
443.50	< 1.0	15.9	< 16.9	< 7.0	200	Vertical
532.20	< 1.0	17.4	< 18.4	< 8.3	200	Vertical
620.90	< 1.0	17.2	< 18.2	< 8.1	200	Vertical
709.60	< 1.0	18.8	< 19.8	< 9.8	200	Vertical
798.30	< 1.0	19.7	< 20.7	< 10.8	200	Vertical
887.00	< 1.0	20.6	< 21.6	< 12.0	200	Vertical

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz ±5.7dB

Date: 2003-11-07

TEST REPORT

Page 18 of 26

No.: HM111637

3.1.1 Conducted Emissions (0.15MHz to 30MHz)

Test Requirement:	FCC 47CFR 15.107
Test Method:	ANSI C63.4:2000
Test Date:	2003-10-23
Mode of Operation:	N/A

Results: N/A

The EUT is operated by a single source of internal battery power [located in the battery compartment], therefore power line conducted emission was deemed unnecessary.

Date: 2003-11-07

TEST REPORT

Page 19 of 26

No.: HM111637

3.2 20B Bandwidth of Fundamental Emission

Test Requirement:	FCC 47 CFR 15.227
Test Method:	ANSI C63.4:2000 (Section 13.1.7)
Test Date:	2003-10-23
Mode of Operation:	On mode

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Test Setup:

As Test Setup of clause 3.1.1 in this test report.

Date: 2003-11-07

TEST REPORT

Page 20 of 26

No.: HM111637


Limits for 20dB Bandwidth of Fundamental Emission:

Frequency Range [MHz]	26dB Bandwidth [KHz]	FCC Limits [MHz]
88.1	79.5	200

Result:

The following figure is the measured bandwidth of Fundamental Emission.

20 Bandwidth of Fundamental Emission



Date: 2003-11-07

TEST REPORT

Page 21 of 26

No.: HM111637


Limits for 20dB Bandwidth of Fundamental Emission:

Frequency Range [MHz]	26dB Bandwidth [KHz]	FCC Limits [KHz]
88.3	75	200

Result:

The following figure is the measured bandwidth of Fundamental Emission.

20B Bandwidth of Fundamental Emission



Date: 2003-11-07

TEST REPORT

Page 22 of 26

No.: HM111637


Limits for 20dB Bandwidth of Fundamental Emission:

Frequency Range [MHz]	20B Bandwidth [KHz]	FCC Limits [KHz]
88.5	76.5	200

Result:

The following figure is the measured bandwidth of Fundamental Emission.

20B Bandwidth of Fundamental Emission



Date: 2003-11-07

TEST REPORT

Page 23 of 26

No.: HM111637


Limits for 20dB Bandwidth of Fundamental Emission:

Frequency Range [MHz]	20B Bandwidth [KHz]	FCC Limits [KHz]
88.7	74	200

Result:

The following figure is the measured bandwidth of Fundamental Emission.

20B Bandwidth of Fundamental Emission



Date: 2003-11-07

TEST REPORT

Page 24 of 26

No.: HM111637

Appendix A

Test Equipment Audit

Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM007	SPECTRUM ANALYZER	HEWLETT PACKARD	HP85660B	3144A21192	14/03/03
EM008	SPECTRUM ANALYZER DISPLAY	HEWLETT PACKARD	HP85662A	3144A20514	14/03/03
EM009	QUASI PEAK ADAPTOR	HEWLETT PACKARD	HP85650A	3303A01702	14/03/03
EM010	RF PRESELECTOR	HEWLETT PACKARD	HP85685A	3221A01410	14/03/03
EM011	ATTENUATOR/SWITCH	HEWLETT PACKARD	HP11713A	2508A10595	14/03/03
EM012	PRE-AMPLIFIER	HEWLETT PACKARD	HP8449B	3008A00262	14/03/03
EM013	CONTROLLER (COMPUTER), COLOR MONITOR, KEYBOARD & MOUSE FLOPPY DRIVE	HEWLETT PACKARD HEWLETT PACKARD HEWLETT PACKARD	HP9000 HP A1097C HP9133L	6226A60314 3151J39517 2623A02468	CM
EM020	HORN ANTENNA	EMCO	3115	4032	19/07/00
EM022	LOOP ANTENNA	EMCO	6502	1189-2424	04/08/00
EM072	SIGNAL GENERATOR	HEWLETT PACKARD	8640B	1948A11892	N/A
EM083	HKSTC OPEN AREA TEST SITE	HKSTC	N/A	N/A	08/11/02
EM131	PORTABLE SPECTRUM ANALYSER	HEWLETT PACKARD	8595EM	3710A00155	18/12/01
EM145	EMI TEST RECEIVER	R & S	ESCS 30	830245/021	02/08/03
EM194	BICONILOG ANTENNA	EMCO	3142B	1795	14/05/02
EM195	ANTENNA POSITIONING MAST	EMCO	2075	2368	N/A
EM196	MULTI-DEVICE CONTROLLER	EMCO	2090	1662	N/A

Conducted Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM078	VARIAC	SHANGHAI VOLTAGE	TDGC-3/0.5	N/A	CM
EM081	SMALL SCREENED ROOM	MIKO INST HK	N/A	N/A	18/10/02
EM119	LISN	R & S	ESH3-Z5	0831.5518.5 2	01/10/02
EM127	ISOLATION TRANSFORMER 220 TO 300	WING SUN	N/A	N/A	CM
EM142	PULSES LIMITER	R & S	ESH3Z2	357.8810.52	03/07/02
EM181	EMI TEST RECEIVER	R & S	ESIB7	100072	28/11/01
EM154	SHIELDING ROOM	SIEMENA MATSUSHITA COMPONENTS	N/A	803-740-057- 99A	18/10/02
EM197	LISN	EMCO	4825/2	1193	08/04/03

Remarks:

CM Corrective Maintenance
N/A Not Applicable or Not Available
TBD To Be Determined

Date: 2003-11-07

TEST REPORT

Page 25 of 26

No.: HM111637

Appendix B

Photographs of EUT

Front View of the product




Rear View of the product



Inner Circuit Top View



Inner Circuit Bottom View



Date: 2003-11-07

TEST REPORT

Page 26 of 26

No.: HM111637

Photographs of EUT

Measurement of Radiated Emission Test Set Up



End of Document