

FCC RADIO TEST REPORT

Applicant's company	Belkin International, Inc.
Applicant Address	12045 East Waterfront Drive, Playa Vista, CA 90094
FCC ID	K7SF9K1103V1

Product Name	N750 DB Wireless N+ Router
Brand Name	Belkin
Model Name	F9K1103v1
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Received Date	Mar. 28, 2011
Final Test Date	Apr. 30, 2011
Submission Type	Original Equipment



Statement

Test result included is only for the IEEE 802.11n, IEEE 802.11b/g part and IEEE 802.11a (5725 ~ 5850MHz) of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2009** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.

Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna.....	6
3.4. Table for Carrier Frequencies	8
3.5. Table for Test Modes	9
3.6. Table for Testing Locations.....	10
3.7. Table for Supporting Units	11
3.8. Table for Parameters of Test Software Setting	12
3.9. Test Configurations	14
4. TEST RESULT	16
4.1. AC Power Line Conducted Emissions Measurement.....	16
4.2. Peak Output Power Measurement	22
4.3. Power Spectral Density Measurement	28
4.4. 6dB Spectrum Bandwidth Measurement	38
4.5. Radiated Emissions Measurement	45
4.6. Band Edge Emissions Measurement	73
4.7. Antenna Requirements	85
5. LIST OF MEASURING EQUIPMENTS	86
6. TEST LOCATION.....	88
7. TAF CERTIFICATE OF ACCREDITATION	89
APPENDIX A. TEST PHOTOS	A1 ~ A6
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE	B1 ~B3
APPENDIX D. CO-LOCATION REPORT.....	C1 ~ C3

History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR132801AB	Rev. 01	Initial issue of report	May 02, 2011

1. CERTIFICATE OF COMPLIANCE

Product Name : N750 DB Wireless N+ Router
Brand Name : Belkin
Model Name : F9K1103v1
Applicant : Belkin International, Inc.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Mar. 28, 2011 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Jordan Hsiao 2011.5.3

Jordan Hsiao
SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	6.55 dB
4.2	15.247(b)(3)	Peak Output Power	Complies	0.00 dB
4.3	15.247(e)	Power Spectral Density	Complies	7.30 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	3.25 dB
4.6	15.247(d)	Band Edge Emissions	Complies	1.06 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n

Items	Description
Product Type	IEEE 802.11n (2.4GHz Band): WLAN (2TX, 2RX) IEEE 802.11n (5GHz Band): WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	For 2.4GHz Band: 11 for 20MHz bandwidth ; 7 for 40MHz bandwidth For 5GHz Band: 5 for 20MHz bandwidth ; 2 for 40MHz bandwidth
Channel Band Width (99%)	For 2.4GHz Band: MCS0 (20MHz): 17.48 MHz ; MCS0 (40MHz): 35.84 MHz For 5GHz Band: MCS0 (20MHz): 17.32 MHz ; MCS0 (40MHz): 35.60 MHz
Peak Output Power	For 2.4GHz Band: MCS0 (20MHz): 30.00 dBm ; MCS0 (40MHz): 30.00 dBm For 5GHz Band: MCS0 (20MHz): 29.84 dBm ; MCS0 (40MHz): 29.79 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

802.11a/b/g

Items	Description
Product Type	IEEE 802.11b/g: WLAN (1TX, 2RX) IEEE 802.11a: WLAN (1TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11a/g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11b/g: 11 ; 11a: 5
Channel Band Width (99%)	11b: 14.96 MHz ; 11g: 16.36 MHz ; 11a: 16.28 MHz
Peak Output Power	11b: 27.93 dBm ; 11g: 28.56 dBm ; 11a: 27.58 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna & Band width

Antenna	Single (TX)		Two (TX)		Three (TX)	
Band width Mode	20 MHz	40 MHz	20 MHz	40 MHz	20 MHz	40 MHz
IEEE 802.11a	V	X	X	X	X	X
IEEE 802.11b	V	X	X	X	X	X
IEEE 802.11g	V	X	X	X	X	X
IEEE 802.11n (2.4GHz Band)	X	X	V	V	X	X
IEEE 802.11n (5GHz Band)	X	X	X	X	V	V

IEEE 802.11n spec

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Datarate(Mbps)			
									800nsGI		400nsGI	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5	7.200	15
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0	14.400	30
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5	21.700	45
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0	28.900	60
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0	43.300	90
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0	57.800	120
6	1	64-QAM	3/4	6	312	648	234	486	58.5	121.5	65.000	135
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0	72.200	150
8	2	BPSK	1/2	1	104	216	52	108	13.0	27.0	14.444	30
9	2	QPSK	1/2	2	208	432	104	216	26.0	54.0	28.889	60
10	2	QPSK	3/4	2	208	432	156	324	39.0	81.0	43.333	90
11	2	16-QAM	1/2	4	416	864	208	432	52.0	108.0	57.778	120
12	2	16-QAM	3/4	4	416	864	312	648	78.0	162.0	86.667	180
13	2	64-QAM	2/3	6	624	1296	416	864	104.0	216.0	115.556	240
14	2	64-QAM	3/4	6	624	1296	468	972	117.0	243.0	130.000	270
15	2	64-QAM	5/6	6	624	1296	520	1080	130.0	270.0	144.444	300

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

3.2. Accessories

Power	Brand	Model	Rating
Adapter 1	LEADER	MU24-B120200-A1	Input: 100-240VAC, 50/60Hz, 1.0A Output: 12VDC, 2A
Adapter 2	DVE	DSA-24CA-12 120200	Input: 100-240VAC, 50/60Hz, 0.8A Output: 12VDC, 2A

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	
1	-	-	PCB Printed Antenna	N/A	5GHz Band	4.8
2	-	-	PCB Printed Antenna	N/A	5GHz Band	4.8
3	-	-	PCB Printed Antenna	N/A	5GHz Band	4.8
4	-	-	PCB Printed Antenna	N/A	2.4GHz Band	4.5
5	-	-	PCB Printed Antenna	N/A	2.4GHz Band	4.5

Note:

For 2.4GHz Band:

There are two antennas of EUT for 2.4GHz Band.

For IEEE 802.11b/g:

Both Ant. 4 and Ant. 5 can be used as transmitting/receiving antennas, but only one of them is used as transmitting antenna.

The EUT supports the antenna with TX diversity function.

Due to Ant. 4 generated higher output power, so all tests were base on this setting and recorded in this report.

For IEEE 802.11n (2.4GHz Band):

Ant. 4 and Ant. 5 can be used as transmitting/receiving antennas.

Ant. 4 and Ant. 5 could transmit/receive simultaneously.

For 5GHz Band:

There are three antennas of EUT for 5GHz Band.

For IEEE 802.11a:

Ant. 1, Ant. 2 and Ant. 3 can be used as transmitting/receiving antennas, but only one of them is used as transmitting antenna.


The EUT supports the antenna with TX diversity function.

Due to Ant. 1 generated higher output power, so all tests were base on this setting and recorded in this report.

For IEEE 802.11n (5GHz Band):

Ant. 1, Ant. 2 and Ant. 3 can be used as transmitting/receiving antennas.

Ant. 1, Ant. 2 and Ant. 3 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

For 2.4GHz Band

Frequency Allocation for IEEE 802.11b/g

For IEEE 802.11b/g, use Channel 1~Channel 11.

There are two bandwidth systems for IEEE 802.11n.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

For 5GHz Band

Frequency Allocation for IEEE 802.11a

For IEEE 802.11a, use Channel 149, 153, 157, 161, 165.

There are two bandwidth systems for IEEE 802.11n.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 151, 159.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz Band 4	149	5745 MHz	159	5795 MHz
	151	5755 MHz	161	5805 MHz
	153	5765 MHz	165	5825 MHz
	157	5785 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

For 2.4GHz Band

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	CTX	Auto	-	-
Peak Output Power	MCS0/20MHz	7.2 Mbps	1/6/11	4/5
	MCS0/40MHz	15 Mbps	3/6/9	4/5
	11b/CCK	1 Mbps	1/6/11	4
	11g/BPSK	6 Mbps	1/6/11	4
Power Spectral Density 6dB Spectrum Bandwidth	MCS0/20MHz	7.2 Mbps	1/6/11	4/5
	MCS0/40MHz	15 Mbps	3/6/9	4/5
	11b/CCK	1 Mbps	1/6/11	4
	11g/BPSK	6 Mbps	1/6/11	4
Radiated Emissions Below 1GHz	CTX	Auto	-	-
Radiated Emissions Above 1GHz	MCS0/20MHz	7.2 Mbps	1/6/11	4/5
	MCS0/40MHz	15 Mbps	3/6/9	4/5
	11b/CCK	1 Mbps	1/6/11	4
	11g/BPSK	6 Mbps	1/6/11	4
Band Edge Emissions	MCS0/20MHz	7.2 Mbps	1/11	4/5
	MCS0/40MHz	15 Mbps	3/9	4/5
	11b/CCK	1 Mbps	1/11	4
	11g/BPSK	6 Mbps	1/11	4

For 5GHz Band

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	CTX	Auto	-	-
Peak Output Power	MCS0/20MHz	7.2 Mbps	149/157/165	1/2/3
	MCS0/40MHz	15 Mbps	151/159	1/2/3
	11a/BPSK	6 Mbps	149/157/165	1
Power Spectral Density 6dB Spectrum Bandwidth	MCS0/20MHz	7.2 Mbps	149/157/165	1/2/3
	MCS0/40MHz	15 Mbps	151/159	1/2/3
	11a/BPSK	6 Mbps	149/157/165	1
Radiated Emissions Below 1GHz	CTX	Auto	-	-
Radiated Emissions Above 1GHz	MCS0/20MHz	7.2 Mbps	149/157/165	1/2/3
	MCS0/40MHz	15 Mbps	151/159	1/2/3
	11a/BPSK	6 Mbps	149/157/165	1
Band Edge Emissions	MCS0/20MHz	7.2 Mbps	149/157/165	1/2/3
	MCS0/40MHz	15 Mbps	151/159	1/2/3
	11a/BPSK	6 Mbps	149/157/165	1

All the test modes were listed as below.

Mode 1. EUT + Adapter 1

Mode 2. EUT + Adapter 2

<For MPE and Co-location Test>:

The EUT could be applied with WLAN 2.4GHz and WLAN 5GHz function; therefore Maximum Permissible Exposure (Please refer to Appendix B) and Co-location (please refer to Appendix C) tests are added for simultaneously transmit between WLAN 2.4GHz and WLAN 5GHz function.

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH01-CB	SAC	Hsin Chu	187376	IC 4086D	-
CO01-CB	Conduction	Hsin Chu	187376	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Flash Disk	Silicon	I-Series	DoC
Flash Disk	Silicon	I-Series	DoC
Notebook	DELL	D400	QDS-BRCM1005-D
Notebook	DELL	D400	QDS-BRCM1005-D
Notebook	DELL	D420	E2KWM3945ABG
Notebook	DELL	D420	E2KWM3945ABG
Notebook	DELL	PP25L	E2K4965AGNM

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

For 2.4GHz Band

Power Parameters of IEEE 802.11n Ant. 4

Test Software Version	RT3092 Release Version: 1.5.7.6		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 20MHz	13	13	14
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS0 40MHz	13	13	14

Power Parameters of IEEE 802.11b/g Ant. 4

Test Software Version	RT3092 Release Version: 1.5.7.6		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	11	1B	1C
IEEE 802.11g	16	17	1B

Power Parameters of IEEE 802.11n Ant. 5

Test Software Version	RT3092 Release Version: 1.5.7.6		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 20MHz	19	18	19
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS0 40MHz	19	18	19

For 5GHz Band

Power Parameters of IEEE 802.11n Ant. 1

Test Software Version	RT3883 QA UI Release Version: 1.0.4.8		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS0 20MHz	0F/02	10/00	10/04
Frequency	5755 MHz	5795 MHz	-
MCS0 40MHz	0D/00	0F/04	-

Power Parameters of IEEE 802.11a Ant. 1

Test Software Version	RT3883 QA UI Release Version: 1.0.4.8		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	1F	1F	1F

Power Parameters of IEEE 802.11n Ant. 2

Test Software Version	RT3883 QA UI Release Version: 1.0.4.8		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS0 20MHz	0D/00	0E/00	0F/04
Frequency	5755 MHz	5795 MHz	-
MCS0 40MHz	0B/00	0D/00	-

Power Parameters of IEEE 802.11n Ant. 3

Test Software Version	RT3883 QA UI Release Version: 1.0.4.8		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS0 20MHz	16/00	18/00	1A/00
Frequency	5755 MHz	5795 MHz	-
MCS0 40MHz	12/00	14/00	-

For 2.4GHz Band:

During the test, "RT3092 Release Version: 1.5.7.6" under WIN XP was executed to control the EUT continuously transmit RF signal.

For 5GHz Band:


During the test, "RT3883 QA UI Release Version: 1.0.4.8" under WIN XP was executed to control the EUT continuously transmit RF signal.

3.9. Test Configurations

3.9.1. Radiation Emissions Test Configuration


Test Configuration: 9kHz~1GHz

Test Mode: Mode 1 / Mode 2



Test Configuration: above 1GHz

Test Mode: Mode 1 / Mode 2





Test Mode: Mode 1 / Mode 2



4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	23°C	Humidity	61%
Test Engineer	Sin Chang	Phase	Line
Configuration	CTX	Test Mode	Mode 1



	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.16155	58.84	-6.55	65.38	58.57	0.07	0.20	QP
2	0.16155	38.88	-16.51	55.38	38.61	0.07	0.20	AVERAGE
3	0.19654	48.73	-15.02	63.76	48.48	0.05	0.20	QP
4	0.19654	25.11	-28.64	53.76	24.86	0.05	0.20	AVERAGE
5	0.21620	50.13	-12.84	62.96	49.88	0.05	0.20	QP
6	0.21620	33.49	-19.48	52.96	33.24	0.05	0.20	AVERAGE
7	0.40187	37.24	-10.57	47.81	37.01	0.03	0.20	AVERAGE
8	0.40187	44.42	-13.39	57.81	44.19	0.03	0.20	QP
9	2.088	31.66	-24.34	56.00	31.41	0.05	0.20	QP
10	2.088	22.52	-23.48	46.00	22.27	0.05	0.20	AVERAGE
11	17.661	31.38	-28.62	60.00	30.17	0.71	0.50	QP
12	17.661	24.40	-25.60	50.00	23.19	0.71	0.50	AVERAGE

Temperature	23°C	Humidity	61%
Test Engineer	Sin Chang	Phase	Neutral
Configuration	CTX	Test Mode	Mode 1




	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.16677	58.02	-7.10	65.12	57.72	0.10	0.20	QP
2	0.16677	44.54	-10.58	55.12	44.24	0.10	0.20	AVERAGE
3	0.21279	48.58	-14.52	63.10	48.30	0.08	0.20	QP
4	0.21279	31.37	-21.73	53.10	31.09	0.08	0.20	AVERAGE
5	0.25480	41.42	-20.18	61.60	41.14	0.08	0.20	QP
6	0.25480	22.40	-29.20	51.60	22.12	0.08	0.20	AVERAGE
7	0.39763	44.67	-13.23	57.90	44.40	0.07	0.20	QP
8	0.39763	36.42	-11.48	47.90	36.15	0.07	0.20	AVERAGE
9	1.111	33.46	-22.54	56.00	33.21	0.07	0.17	QP
10	1.111	20.27	-25.73	46.00	20.02	0.07	0.17	AVERAGE
11	3.820	29.08	-26.92	56.00	28.64	0.14	0.30	QP
12	3.820	18.03	-27.97	46.00	17.59	0.14	0.30	AVERAGE

Note:


Level = Read Level + LISN Factor + Cable Loss.

Temperature	23°C	Humidity	61%
Test Engineer	Sin Chang	Phase	Line
Configuration	CTX	Test Mode	Mode 2



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15567	41.45	-24.24	65.69	41.18	0.07	0.20	QP
2	0.15567	22.54	-33.15	55.69	22.27	0.07	0.20	AVERAGE
3	0.24682	34.60	-27.26	61.86	34.36	0.04	0.20	QP
4	0.24682	29.86	-22.00	51.86	29.62	0.04	0.20	AVERAGE
5	0.73131	25.52	-30.48	56.00	25.29	0.03	0.20	QP
6	0.73131	8.22	-37.78	46.00	7.99	0.03	0.20	AVERAGE
7	1.552	19.66	-26.34	46.00	19.51	0.04	0.11	AVERAGE
8	1.552	29.35	-26.65	56.00	29.20	0.04	0.11	QP
9	7.646	38.29	-21.71	60.00	37.62	0.28	0.40	QP
10	7.646	31.40	-18.60	50.00	30.73	0.28	0.40	AVERAGE
11	12.060	25.35	-34.65	60.00	24.51	0.44	0.40	QP
12	12.060	19.69	-30.31	50.00	18.85	0.44	0.40	AVERAGE

Temperature	23°C	Humidity	61%
Test Engineer	Sin Chang	Phase	Neutral
Configuration	CTX	Test Mode	Mode 2



	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15160	43.72	-22.19	65.91	43.42	0.10	0.20	QP
2	0.15160	30.12	-25.79	55.91	29.82	0.10	0.20	AVERAGE
3	0.22319	40.48	-22.22	62.70	40.20	0.08	0.20	QP
4	0.22319	35.51	-17.19	52.70	35.23	0.08	0.20	AVERAGE
5	0.37117	26.96	-31.51	58.47	26.69	0.07	0.20	QP
6	0.37117	22.40	-26.07	48.47	22.13	0.07	0.20	AVERAGE
7	1.552	26.45	-29.55	56.00	26.26	0.08	0.11	QP
8	1.552	16.42	-29.58	46.00	16.23	0.08	0.11	AVERAGE
9	3.025	26.30	-29.70	56.00	25.97	0.12	0.21	QP
10	3.025	18.71	-27.29	46.00	18.38	0.12	0.21	AVERAGE
11	7.728	40.99	-19.01	60.00	40.27	0.32	0.40	QP
12	7.728	31.33	-18.67	50.00	30.61	0.32	0.40	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Peak Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

4.2.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the peak power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Peak

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Test was performed in accordance with Measurement of Digital Transmission Systems Operating under Section 15.247 March 23, 2005.
3. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.2.4. Test Setup Layout

Spectrum Parameter	Setting
RF Output Power Method	☒ ANSI C63.10 clause 6.10.2.1 (a) power meter method
RF Output Power Method	☐ ANSI C63.10 clause 6.10.2.1 (b) channel integration method
RF Output Power Method	☐ ANSI C63.10 clause 6.10.3.1 Method 1 - spectral trace averaging
RF Output Power Method	☐ ANSI C63.10 clause 6.10.3.2 Method 2 - zero-span mode with trace averaging

4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Peak Output Power

Temperature	21°C	Humidity	63%
Test Engineer	Jacky Ho	Configurations	IEEE 802.11n
Test Date	Apr. 07, 2011		

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz Ant. 4

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	26.65	30.00	Complies
6	2437 MHz	26.54	30.00	Complies
11	2462 MHz	27.03	30.00	Complies

Configuration IEEE 802.11n MCS0 20MHz Ant. 5

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	26.75	30.00	Complies
6	2437 MHz	26.60	30.00	Complies
11	2462 MHz	26.95	30.00	Complies

Configuration IEEE 802.11n MCS0 20MHz Ant. 4 + Ant. 5

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	29.71	30.00	Complies
6	2437 MHz	29.58	30.00	Complies
11	2462 MHz	30.00	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. 4

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	26.56	30.00	Complies
6	2437 MHz	26.54	30.00	Complies
9	2452 MHz	27.02	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. 5

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	26.62	30.00	Complies
6	2437 MHz	26.47	30.00	Complies
9	2452 MHz	26.95	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. 4 + Ant. 5

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	29.60	30.00	Complies
6	2437 MHz	29.52	30.00	Complies
9	2452 MHz	30.00	30.00	Complies

For 5GHz Band

Configuration IEEE 802.11n MCS0 20MHz Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	25.06	30.00	Complies
157	5785 MHz	25.39	30.00	Complies
165	5825 MHz	24.73	30.00	Complies

Configuration IEEE 802.11n MCS0 20MHz Ant. 2

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	25.03	30.00	Complies
157	5785 MHz	24.53	30.00	Complies
165	5825 MHz	24.52	30.00	Complies

Configuration IEEE 802.11n MCS0 20MHz Ant. 3

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	24.92	30.00	Complies
157	5785 MHz	25.23	30.00	Complies
165	5825 MHz	25.13	30.00	Complies

Configuration IEEE 802.11n MCS0 20MHz Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	29.77	30.00	Complies
157	5785 MHz	29.84	30.00	Complies
165	5825 MHz	29.57	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	24.99	30.00	Complies
159	5795 MHz	24.96	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. 2

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	25.01	30.00	Complies
159	5795 MHz	25.02	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. 3

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	25.05	30.00	Complies
159	5795 MHz	24.95	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	29.79	30.00	Complies
159	5795 MHz	29.75	30.00	Complies

Temperature	21°C	Humidity	63%
Test Engineer	Jacky Ho	Configurations	IEEE 802.11a/b/g
Test Date	May 02, 2011		

Configuration IEEE 802.11b Ant. 4

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	23.15	30.00	Complies
6	2437 MHz	27.60	30.00	Complies
11	2462 MHz	27.93	30.00	Complies

Configuration IEEE 802.11g Ant. 4

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	28.03	30.00	Complies
6	2437 MHz	28.23	30.00	Complies
11	2462 MHz	28.56	30.00	Complies

Configuration IEEE 802.11a Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	27.58	30.00	Complies
157	5785 MHz	27.27	30.00	Complies
165	5825 MHz	27.22	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	30 kHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	10s

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 30kHz and the sweep time to 10s and record the maximum peak value.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	21°C	Humidity	63%
Test Engineer	Jacky Ho	Configurations	IEEE 802.11n

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz Ant. 4 + Ant. 5

Channel	Frequency	Power Density (dBm/3kHz)		Total Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2			
1	2412 MHz	-10.96	-12.81	-8.78	8.00	Complies
6	2437 MHz	-13.96	-13.47	-10.70	8.00	Complies
11	2462 MHz	-10.01	-13.61	-8.44	8.00	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. 4 + Ant. 5

Channel	Frequency	Power Density (dBm/3kHz)		Total Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2			
3	2422 MHz	-13.60	-13.49	-10.53	8.00	Complies
6	2437 MHz	-16.47	-12.90	-11.32	8.00	Complies
9	2452 MHz	-14.22	-14.65	-11.42	8.00	Complies

For 5GHz Band

Configuration 11a IEEE 802.11n MCS0 20MHz Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)			Total Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3			
149	5745 MHz	-14.83	-15.50	-13.46	-9.74	8.00	Complies
157	5785 MHz	-16.45	-15.76	-13.06	-10.06	8.00	Complies
165	5825 MHz	-15.72	-16.50	-13.84	-10.43	8.00	Complies

Configuration 11a IEEE 802.11n MCS0 40MHz Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)			Total Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3			
151	5755 MHz	-20.08	-17.70	-16.79	-13.21	8.00	Complies
159	5795 MHz	-20.33	-18.15	-16.56	-13.31	8.00	Complies

Temperature	21°C	Humidity	63%
Test Engineer	Jacky Ho	Configurations	IEEE 802.11a/b/g

Configuration IEEE 802.11b Ant. 4

Channel	Frequency	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	-3.46	8.00	Complies
6	2437 MHz	0.36	8.00	Complies
11	2462 MHz	0.70	8.00	Complies

Configuration IEEE 802.11g Ant. 4

Channel	Frequency	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	-7.56	8.00	Complies
6	2437 MHz	-6.20	8.00	Complies
11	2462 MHz	-7.41	8.00	Complies


Configuration IEEE 802.11a Ant. 1

Channel	Frequency	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
149	5745 MHz	-7.07	8.00	Complies
157	5785 MHz	-8.54	8.00	Complies
165	5825 MHz	-6.60	8.00	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. 4 / 2437 MHz




Date: 28.APR.2011 18:22:49

Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. 5 / 2437 MHz




Date: 28.APR.2011 18:21:12

Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. 4 / 2422 MHz




Date: 28.APR.2011 18:31:55

Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. 5 / 2422 MHz




Date: 28.APR.2011 18:33:40

Power Density Plot on Configuration 11a IEEE 802.11n MCS0 20MHz Ant. 1 / 5745 MHz




Date: 29.APR.2011 06:14:29

Power Density Plot on Configuration 11a IEEE 802.11n MCS0 20MHz Ant. 2 / 5745 MHz




Date: 29.APR.2011 06:16:31

Power Density Plot on Configuration 11a IEEE 802.11n MCS0 20MHz Ant. 3 / 5745 MHz




Date: 29.APR.2011 06:17:35

Power Density Plot on Configuration 11a IEEE 802.11n MCS0 40MHz Ant. 1 / 5755 MHz




Date: 29.APR.2011 06:27:45

Power Density Plot on Configuration 11a IEEE 802.11n MCS0 40MHz Ant. 2 / 5755 MHz




Date: 29.APR.2011 06:26:49

Power Density Plot on Configuration 11a IEEE 802.11n MCS0 40MHz Ant. 3 / 5755 MHz




Date: 29.APR.2011 06:25:55

Power Density Plot on Configuration IEEE 802.11b Ant. 4 / 2462 MHz




Date: 29.APR.2011 04:40:41

Power Density Plot on Configuration IEEE 802.11g Ant. 4 / 2437 MHz



Date: 29.APR.2011 04:45:59

Power Density Plot on Configuration IEEE 802.11a Ant. 1 / 5825 MHz



Date: 29.APR.2011 05:08:57

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	21°C	Humidity	63%
Test Engineer	Jacky Ho	Configurations	IEEE 802.11n

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz Ant. 4 + Ant. 5

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	15.76	17.44	500	Complies
6	2437 MHz	15.84	17.48	500	Complies
11	2462 MHz	15.80	17.48	500	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. 4 + Ant. 5

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	35.12	35.76	500	Complies
6	2437 MHz	35.20	35.84	500	Complies
9	2452 MHz	35.04	35.84	500	Complies

For 5GHz Band

Configuration 11a IEEE 802.11n MCS0 20MHz Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	15.08	17.32	500	Complies
157	5785 MHz	15.00	17.28	500	Complies
165	5825 MHz	15.08	17.28	500	Complies

Configuration 11a IEEE 802.11n MCS0 40MHz Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	32.80	35.44	500	Complies
159	5795 MHz	32.64	35.60	500	Complies

Temperature	21°C	Humidity	63%
Test Engineer	Jacky Ho	Configurations	IEEE 802.11a/b/g

Configuration IEEE 802.11b Ant. 4

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	12.08	14.96	500	Complies
6	2437 MHz	10.16	14.40	500	Complies
11	2462 MHz	10.16	14.36	500	Complies

Configuration IEEE 802.11g Ant. 4

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	15.36	16.32	500	Complies
6	2437 MHz	15.80	16.36	500	Complies
11	2462 MHz	15.76	16.36	500	Complies


Configuration IEEE 802.11a Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	15.16	16.28	500	Complies
157	5785 MHz	15.12	16.28	500	Complies
165	5825 MHz	15.08	16.28	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. 4 + Ant. 5 / 2412 MHz




Date: 7.APR.2011 22:09:18

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. 4 + Ant. 5 / 2452 MHz




Date: 7.APR.2011 22:08:03

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. 1 + Ant. 2 + Ant. 3 / 5785MHz




Date: 9.APR.2011 09:21:38

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. 1 + Ant. 2 + Ant. 3 / 5795 MHz




Date: 9.APR.2011 09:34:48

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. 4 / 2437 MHz




Date: 29.APR.2011 04:13:27

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. 4 / 2412 MHz



Date: 29.APR.2011 04:42:07

6 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. 1 / 5825 MHz



Date: 29.APR.2011 05:07:28

4.5. Radiated Emissions Measurement

4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	CTX
Test Date	Apr. 22, 2011		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	CTX
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	125.06	31.91	43.50	-11.59	45.93	1.25	27.48	12.21	0	100	Peak	HORIZONTAL
2	143.49	29.76	43.50	-13.74	43.55	1.42	27.38	12.17	0	100	Peak	HORIZONTAL
3	375.32	35.30	46.00	-10.70	45.08	2.25	27.43	15.40	0	100	Peak	HORIZONTAL
4	625.58	40.10	46.00	-5.90	46.27	3.05	28.07	18.85	0	100	Peak	HORIZONTAL
5	750.71	37.94	46.00	-8.06	42.81	3.50	27.80	19.43	0	100	Peak	HORIZONTAL
6 p	875.84	42.75	46.00	-3.25	46.35	3.50	27.45	20.35	0	100	Peak	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	56.43	33.80	40.00	-6.20	53.30	0.80	27.77	7.47	0	100	QP	VERTICAL
2	125.06	31.69	43.50	-11.81	45.71	1.25	27.48	12.21	0	400	Peak	VERTICAL
3	375.32	39.56	46.00	-6.44	49.34	2.25	27.43	15.40	0	400	Peak	VERTICAL
4	625.58	41.58	46.00	-4.42	47.75	3.05	28.07	18.85	0	400	Peak	VERTICAL
5	750.71	37.66	46.00	-8.34	42.53	3.50	27.80	19.43	0	400	Peak	VERTICAL
6	875.84	41.38	46.00	-4.62	44.98	3.50	27.45	20.35	0	400	Peak	VERTICAL

Note:


The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	CTX
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	125.06	29.93	43.50	-13.57	43.95	1.25	27.48	12.21	0	100	Peak	HORIZONTAL
2	148.34	29.74	43.50	-13.76	43.71	1.45	27.36	11.94	0	100	Peak	HORIZONTAL
3	375.32	37.75	46.00	-8.25	47.53	2.25	27.43	15.40	0	100	Peak	HORIZONTAL
4	625.58	40.56	46.00	-5.44	46.73	3.05	28.07	18.85	0	100	Peak	HORIZONTAL
5	750.71	37.59	46.00	-8.41	42.46	3.50	27.80	19.43	0	100	Peak	HORIZONTAL
6	875.84	42.73	46.00	-3.27	46.33	3.50	27.45	20.35	0	100	Peak	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	59.10	30.52	40.00	-9.48	50.53	0.80	27.76	6.95	0	400	Peak	VERTICAL
2	125.06	31.71	43.50	-11.79	45.73	1.25	27.48	12.21	0	400	Peak	VERTICAL
3	375.32	39.57	46.00	-6.43	49.35	2.25	27.43	15.40	0	400	Peak	VERTICAL
4	625.58	41.04	46.00	-4.96	47.21	3.05	28.07	18.85	0	400	Peak	VERTICAL
5	750.71	36.87	46.00	-9.13	41.74	3.50	27.80	19.43	0	400	Peak	VERTICAL
6	875.84	41.45	46.00	-4.55	45.05	3.50	27.45	20.35	0	400	Peak	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11n MCS0 20MHz Ch 1 / Ant. 4 + Ant. 5
Test Date	Apr. 06, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	4824.07	30.61	54.00	-23.39	29.27	3.31	33.06	35.03	150	100 Average	HORIZONTAL
2	4824.35	42.24	74.00	-31.76	40.90	3.31	33.06	35.03	150	100 Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	4824.02	42.38	74.00	-31.62	41.04	3.31	33.06	35.03	242	100 Peak	VERTICAL
2	4824.11	29.98	54.00	-24.02	28.64	3.31	33.06	35.03	242	100 Average	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11n MCS0 20MHz Ch 6 / Ant. 4 + Ant. 5
Test Date	Apr. 06, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4873.76	43.02	74.00	-30.98	41.56	3.33	33.16	35.03	206	100	Peak	HORIZONTAL
2	4874.05	30.50	54.00	-23.50	29.04	3.33	33.16	35.03	206	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4874.05	29.59	54.00	-24.41	28.13	3.33	33.16	35.03	154	100	Average	VERTICAL
2	4874.22	42.01	74.00	-31.99	40.55	3.33	33.16	35.03	154	100	Peak	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11n MCS0 20MHz Ch11 / Ant. 4 + Ant. 5
Test Date	Apr. 06, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4923.85	30.66	54.00	-23.34	29.06	3.35	33.26	35.01	160	100	Average	HORIZONTAL
2	4924.21	42.67	74.00	-31.33	41.07	3.35	33.26	35.01	160	100	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4923.68	29.90	54.00	-24.10	28.30	3.35	33.26	35.01	222	100	Average	VERTICAL
2	4924.39	43.11	74.00	-30.89	41.51	3.35	33.26	35.01	222	100	Peak	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11n MCS0 40MHz Ch 3 / Ant. 4 + Ant. 5
Test Date	Apr. 06, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4843.92	30.24	54.00	-23.76	28.86	3.32	33.09	35.03	135	100	Average	HORIZONTAL
2	4844.07	42.32	74.00	-31.68	40.94	3.32	33.09	35.03	135	100	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4843.96	30.07	54.00	-23.93	28.69	3.32	33.09	35.03	212	100	Average	VERTICAL
2	4844.50	42.34	74.00	-31.66	40.96	3.32	33.09	35.03	212	100	Peak	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11n MCS0 40MHz Ch 6 / Ant. 4 + Ant. 5
Test Date	Apr. 06, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4873.97	42.54	74.00	-31.46	41.08	3.33	33.16	35.03	161	100	Peak	HORIZONTAL
2	4873.98	29.97	54.00	-24.03	28.51	3.33	33.16	35.03	161	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4873.89	42.21	74.00	-31.79	40.75	3.33	33.16	35.03	244	100	Peak	VERTICAL
2	4874.04	29.63	54.00	-24.37	28.17	3.33	33.16	35.03	244	100	Average	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11n MCS0 40MHz Ch 9 / Ant. 4 + Ant. 5
Test Date	Apr. 06, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4903.51	42.63	74.00	-31.37	41.12	3.34	33.19	35.02	235	100	Peak	HORIZONTAL
2	4904.04	30.41	54.00	-23.59	28.90	3.34	33.19	35.02	235	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4904.05	41.93	74.00	-32.07	40.42	3.34	33.19	35.02	177	100	Peak	VERTICAL
2	4904.29	29.75	54.00	-24.25	28.24	3.34	33.19	35.02	177	100	Average	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	11a IEEE 802.11n MCS0 20MHz CH 149 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 31, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	11490.00	43.90	60.00	-16.10	32.15	7.33	35.08	39.50	266	100	Average	HORIZONTAL
2 p	11490.90	57.55	80.00	-22.45	45.80	7.33	35.08	39.50	266	100	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	11492.70	42.84	60.00	-17.16	31.09	7.33	35.08	39.50	288	100	Average	VERTICAL
2 p	11493.10	55.42	80.00	-24.58	43.67	7.33	35.08	39.50	288	100	Peak	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	11a IEEE 802.11n MCS0 20MHz CH 157 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 31, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	11571.10	55.01	80.00	-24.99	43.34	7.29	35.09	39.47	162	100	Peak	HORIZONTAL
2 a	11573.10	41.59	60.00	-18.41	29.91	7.29	35.08	39.47	162	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	11571.90	54.02	80.00	-25.98	42.34	7.29	35.08	39.47	290	100	Peak	VERTICAL
2 a	11573.00	41.42	60.00	-18.58	29.74	7.29	35.08	39.47	290	100	Average	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	11a IEEE 802.11n MCS0 20MHz CH 165 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 31, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	11653.80	41.68	60.00	-18.32	30.09	7.22	35.07	39.44	149	100	Average	HORIZONTAL
2 p	11654.70	54.64	80.00	-25.36	43.05	7.22	35.07	39.44	149	100	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	11643.20	52.00	80.00	-28.00	40.39	7.24	35.07	39.44	312	100	Peak	VERTICAL
2 a	11647.00	41.14	60.00	-18.86	29.55	7.22	35.07	39.44	312	100	Average	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	11a IEEE 802.11n MCS0 40MHz CH 151 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 31, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	11510.30	41.73	60.00	-18.27	29.98	7.35	35.10	39.50	266	100	Average	HORIZONTAL
2 p	11511.00	54.64	80.00	-25.36	42.89	7.35	35.10	39.50	266	100	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	11510.40	53.11	80.00	-26.89	41.36	7.35	35.10	39.50	0	100	Peak	VERTICAL
2 a	11510.40	40.70	60.00	-19.30	28.95	7.35	35.10	39.50	0	100	Average	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	11a IEEE 802.11n MCS0 40MHz CH 159 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 31, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	11589.86	40.14	60.00	-19.86	28.46	7.29	35.08	39.47	9	100	Average	HORIZONTAL
2 p	11590.14	51.22	80.00	-28.78	39.54	7.29	35.08	39.47	9	100	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	11589.04	51.08	80.00	-28.92	39.40	7.29	35.08	39.47	240	100	Peak	VERTICAL
2 a	11589.95	39.63	60.00	-20.37	27.95	7.29	35.08	39.47	240	100	Average	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11b CH 1 / Ant. 4
Test Date	Apr. 29, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	4823.87	46.36	74.00	-27.64	43.91	4.26	35.20	33.39	97	104	Peak	HORIZONTAL
2 a	4823.97	35.66	54.00	-18.34	33.21	4.26	35.20	33.39	97	104	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	4823.92	32.85	54.00	-21.15	30.40	4.26	35.20	33.39	317	100	Average	VERTICAL
2 p	4824.15	45.31	74.00	-28.69	42.86	4.26	35.20	33.39	317	100	Peak	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11b CH 6 / Ant. 4
Test Date	Apr. 29, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	4873.96	42.06	54.00	-11.94	39.45	4.33	35.20	33.48	263	100	Average	HORIZONTAL
2	4874.01	47.76	74.00	-26.24	45.15	4.33	35.20	33.48	263	100	Peak	HORIZONTAL
3 p	7310.00	54.08	74.00	-19.92	47.64	5.36	35.43	36.51	219	100	Peak	HORIZONTAL
4 a	7310.20	47.14	54.00	-6.86	40.70	5.36	35.43	36.51	219	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	4873.79	45.69	74.00	-28.31	43.08	4.33	35.20	33.48	319	100	Peak	VERTICAL
2	4874.03	36.81	54.00	-17.19	34.20	4.33	35.20	33.48	319	100	Average	VERTICAL
3 a	7310.20	44.98	54.00	-9.02	38.54	5.36	35.43	36.51	280	100	Average	VERTICAL
4 p	7311.97	52.49	74.00	-21.51	46.04	5.37	35.43	36.51	280	100	Peak	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11b CH 11 / Ant. 4
Test Date	Apr. 29, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	4923.99	46.41	74.00	-27.59	43.64	4.39	35.20	33.58	322	110	Peak	HORIZONTAL
2	4923.99	38.07	54.00	-15.93	35.30	4.39	35.20	33.58	322	110	Average	HORIZONTAL
3 p	7384.99	54.79	74.00	-19.21	48.25	5.39	35.46	36.61	240	140	Peak	HORIZONTAL
4 a	7385.24	47.52	54.00	-6.48	40.98	5.39	35.46	36.61	240	140	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	4923.84	47.20	74.00	-26.80	44.43	4.39	35.20	33.58	316	100	Peak	VERTICAL
2	4923.97	36.66	54.00	-17.34	33.89	4.39	35.20	33.58	316	100	Average	VERTICAL
3 p	7384.85	53.10	74.00	-20.90	46.56	5.39	35.46	36.61	242	142	Peak	VERTICAL
4 a	7385.19	44.25	54.00	-9.75	37.71	5.39	35.46	36.61	242	142	Average	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11g CH 1 / Ant. 4
Test Date	Apr. 29, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	4824.13	44.76	74.00	-29.24	42.31	4.26	35.20	33.39	240	100	Peak	HORIZONTAL
2 a	4824.32	31.94	54.00	-22.06	29.49	4.26	35.20	33.39	240	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	4823.52	31.84	54.00	-22.16	29.39	4.26	35.20	33.39	185	100	Average	VERTICAL
2 p	4824.46	44.46	74.00	-29.54	42.01	4.26	35.20	33.39	185	100	Peak	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11g CH 6 / Ant. 4
Test Date	Apr. 29, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	4873.67	45.74	74.00	-28.26	43.13	4.33	35.20	33.48	145	100	Peak	HORIZONTAL
2 a	4874.41	33.20	54.00	-20.80	30.59	4.33	35.20	33.48	145	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	4874.35	33.32	54.00	-20.68	30.71	4.33	35.20	33.48	210	100	Average	VERTICAL
2 p	4874.40	45.52	74.00	-28.48	42.91	4.33	35.20	33.48	210	100	Peak	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11g CH 11 / Ant. 5
Test Date	Apr. 29, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	4924.00	45.11	74.00	-28.89	42.34	4.39	35.20	33.58	220	100	Peak	HORIZONTAL
2 a	4924.46	31.99	54.00	-22.01	29.22	4.39	35.20	33.58	220	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	4923.78	44.29	74.00	-29.71	41.52	4.39	35.20	33.58	289	100	Peak	VERTICAL
2 a	4924.05	31.84	54.00	-22.16	29.07	4.39	35.20	33.58	289	100	Average	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11a CH 149 / Ant. 1
Test Date	Apr. 30, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	11486.20	73.09	80.00	-6.91	64.48	5.11	38.78	35.28	104	100	Peak	HORIZONTAL
2	11487.90	56.17	60.00	-3.83	47.56	5.11	38.78	35.28	104	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	11486.30	72.14	80.00	-7.86	63.53	5.11	38.78	35.28	293	111	Peak	VERTICAL
2	11487.80	54.77	60.00	-5.23	46.16	5.11	38.78	35.28	293	111	Average	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11a CH 157 / Ant. 1
Test Date	Apr. 30, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	11566.40	72.29	80.00	-7.71	63.64	5.13	38.82	35.30	110	100	Peak	HORIZONTAL
2	11571.30	54.51	60.00	-5.49	45.84	5.14	38.83	35.30	110	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	11571.90	62.62	80.00	-17.38	53.95	5.14	38.83	35.30	2	100	Peak	VERTICAL
2	11572.00	49.21	60.00	-10.79	40.54	5.14	38.83	35.30	2	100	Average	VERTICAL

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11a CH 165 / Ant. 1
Test Date	Apr. 29, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	11647.96	53.23	60.00	-6.77	41.64	7.22	35.07	39.44	106	104	Average	HORIZONTAL
2 p	11648.35	69.67	80.00	-10.33	58.08	7.22	35.07	39.44	106	104	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	11647.93	48.15	60.00	-11.85	36.56	7.22	35.07	39.44	150	111	Average	VERTICAL
2 p	11648.25	61.60	80.00	-18.40	50.01	7.22	35.07	39.44	150	111	Peak	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

4.6.3. Test Procedures

- The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
- In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11n MCS0 20MHz Ch 1, 6, 11 / Ant. 4 + Ant. 5
Test date	Apr. 06, 2011		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2360.00	50.32	54.00	-3.68	20.03	2.19	28.10	0.00	249	158	Average	HORIZONTAL
2	2360.40	61.98	74.00	-12.02	31.69	2.19	28.10	0.00	249	158	Peak	HORIZONTAL
3	2409.60	92.65	54.00			2.22	28.21	0.00	249	158	Average	HORIZONTAL
4	2411.20	111.30	74.00			2.22	28.21	0.00	249	158	Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2384.40	63.73	74.00	-10.27	33.35	2.21	28.17	0.00	272	132	Peak	HORIZONTAL
2	2384.80	52.03	54.00	-1.97	21.65	2.21	28.17	0.00	272	132	Average	HORIZONTAL
3	2433.80	111.82	74.00			2.23	28.25	0.00	272	132	Peak	HORIZONTAL
4	2434.20	94.39	54.00			2.23	28.29	0.00	272	132	Average	HORIZONTAL
5	2489.10	52.38	54.00	-1.62	21.70	2.26	28.42	0.00	272	132	Average	HORIZONTAL
6	2489.10	63.91	74.00	-10.09	33.23	2.26	28.42	0.00	272	132	Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2457.60	112.38	74.00			2.24	28.33	0.00	272	132	Peak	HORIZONTAL
2	2458.80	94.81	54.00			2.24	28.33	0.00	272	132	Average	HORIZONTAL
3	2483.50	47.90	54.00	-6.10	17.26	2.26	28.38	0.00	272	132	Average	HORIZONTAL
4	2486.30	63.96	74.00	-10.04	33.28	2.26	28.42	0.00	272	132	Peak	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11n MCS0 40MHz Ch 3, 6, 9 / Ant. 4 + Ant. 5
Test date	Apr. 06, 2011		

Channel 3

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2387.60	71.81	74.00	-2.19	41.43	2.21	28.17	0.00	284	103	Peak	VERTICAL
2	2390.00	52.51	54.00	-1.49	22.12	2.22	28.17	0.00	284	103	Average	VERTICAL
3	2420.40	106.05	74.00			2.23	28.25	0.00	284	103	Peak	VERTICAL
4	2433.20	83.78	54.00			2.23	28.25	0.00	284	103	Average	VERTICAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2389.20	66.85	74.00	-7.15	36.47	2.21	28.17	0.00	271	136	Peak	HORIZONTAL
2	2390.00	46.66	54.00	-7.34	16.27	2.22	28.17	0.00	271	136	Average	HORIZONTAL
3	2445.80	86.86	54.00			2.24	28.29	0.00	271	136	Average	HORIZONTAL
4	2446.20	109.80	74.00			2.24	28.29	0.00	271	136	Peak	HORIZONTAL
5	2483.50	46.00	54.00	-8.00	15.36	2.26	28.38	0.00	271	136	Average	HORIZONTAL
6	2483.50	63.47	74.00	-10.53	32.83	2.26	28.38	0.00	271	136	Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 9

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2440.00	110.42	74.00			2.23	28.29	0.00	271	133	Peak	HORIZONTAL
2	2457.20	87.26	54.00			2.24	28.33	0.00	271	133	Average	HORIZONTAL
3	2483.50	49.77	54.00	-4.23	19.13	2.26	28.38	0.00	271	133	Average	HORIZONTAL
4	2485.10	68.08	74.00	-5.92	37.40	2.26	28.42	0.00	271	133	Peak	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11b CH 1, 6, 11 / Ant. 4
Test Date	Apr. 29, 2011		

Channel 1

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	2389.00	61.30	74.00	-12.70	30.39	2.86	0.00	28.05	85	145	Peak	HORIZONTAL
2 !	2390.00	52.91	54.00	-1.09	21.98	2.88	0.00	28.05	85	145	Average	HORIZONTAL
3 p	2413.00	113.31	74.00			2.88	0.00	28.09	85	145	Peak	HORIZONTAL
4 a	2413.60	108.47	54.00			2.88	0.00	28.09	85	145	Average	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 !	2389.00	51.98	54.00	-2.02	21.07	2.86	0.00	28.05	81	144	Average	HORIZONTAL
2	2389.40	64.33	74.00	-9.67	33.42	2.86	0.00	28.05	81	144	Peak	HORIZONTAL
3 a	2435.20	115.27	54.00			2.89	0.00	28.18	81	144	Average	HORIZONTAL
4 p	2435.40	120.40	74.00			2.89	0.00	28.18	81	144	Peak	HORIZONTAL
5	2484.50	62.32	74.00	-11.68	31.13	2.93	0.00	28.26	81	144	Peak	HORIZONTAL
6 !	2484.90	49.57	54.00	-4.43	18.38	2.93	0.00	28.26	81	144	Average	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	2463.00	115.88	74.00			2.91	0.00	28.22	282	140	Peak	HORIZONTAL
2 a	2463.80	111.06	54.00			2.91	0.00	28.22	282	140	Average	HORIZONTAL
3 !	2484.10	51.22	54.00	-2.78	20.03	2.93	0.00	28.26	282	140	Average	HORIZONTAL
4	2484.70	60.20	74.00	-13.80	29.01	2.93	0.00	28.26	282	140	Peak	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	50%
Test Engineer	Magic Li	Configurations	IEEE 802.11g CH 1, 6, 11 / Ant. 4
Test Date	Apr. 29, 2011		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	2359.20	63.81	74.00	-10.19	32.99	2.85	0.00	27.97	87	144	Peak	HORIZONTAL
2 !	2359.60	52.76	54.00	-1.24	21.94	2.85	0.00	27.97	87	144	Average	HORIZONTAL
3 a	2413.20	96.73	54.00			2.88	0.00	28.09	87	144	Average	HORIZONTAL
4 p	2413.60	114.20	74.00			2.88	0.00	28.09	87	144	Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	2384.40	64.79	74.00	-9.21	33.88	2.86	0.00	28.05	85	152	Peak	HORIZONTAL
2 !	2384.40	52.91	54.00	-1.09	22.00	2.86	0.00	28.05	85	152	Average	HORIZONTAL
3 p	2432.20	113.03	74.00			2.89	0.00	28.13	85	152	Peak	HORIZONTAL
4 a	2435.80	95.44	54.00			2.89	0.00	28.18	85	152	Average	HORIZONTAL
5	2489.90	62.28	74.00	-11.72	31.05	2.93	0.00	28.30	85	152	Peak	HORIZONTAL
6 !	2489.90	51.25	54.00	-2.75	20.02	2.93	0.00	28.30	85	152	Average	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	2457.20	115.39	74.00			2.91	0.00	28.22	278	144	Peak	HORIZONTAL
2 a	2461.00	98.45	54.00			2.91	0.00	28.22	278	144	Average	HORIZONTAL
3 !	2483.50	52.94	54.00	-1.06	21.75	2.93	0.00	28.26	278	144	Average	HORIZONTAL
4 !	2484.10	71.54	74.00	-2.46	40.35	2.93	0.00	28.26	278	144	Peak	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. 4 + Ant. 5 / 2412 MHz




Date: 7.APR.2011 22:02:22

High Band Edge Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. 4 + Ant. 5 / 2462 MHz




Date: 7.APR.2011 22:02:48

Low Band Edge Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. 4 + Ant. 5 / 2422 MHz




Date: 7.APR.2011 22:05:14

High Band Edge Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. 4 + Ant. 5 / 2452 MHz




Date: 7.APR.2011 22:04:18

Low Band Edge Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. 1 + Ant. 2 + Ant. 3 / 5745 MHz




Date: 9.APR.2011 09:20:47

High Band Edge Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. 1 + Ant. 2 + Ant. 3 / 5825 MHz




Date: 9.APR.2011 09:25:26

Low Band Edge Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. 1 + Ant. 2 + Ant. 3 / 5755 MHz




Date: 9.APR.2011 09:34:15

High Band Edge Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. 1 + Ant. 2 + Ant. 3 / 5795 MHz




Date: 9.APR.2011 09:36:28

Low Band Edge Plot on Configuration IEEE 802.11b Ant. 4 / 2412 MHz




Date: 29.APR.2011 04:09:57

High Band Edge Plot on Configuration IEEE 802.11b Ant. 4 / 2462 MHz




Date: 29.APR.2011 04:40:51

Low Band Edge Plot on Configuration IEEE 802.11g Ant. 4 / 2412 MHz




Date: 29.APR.2011 04:43:48

High Band Edge Plot on Configuration IEEE 802.11g Ant. 4 / 2462 MHz




Date: 29.APR.2011 04:49:44

Low Band Edge Plot on Configuration IEEE 802.11a Ant. 1 / 5745 MHz



Date: 29.APR.2011 04:59:34

High Band Edge Plot on Configuration IEEE 802.11a Ant. 1 / 5825 MHz



Date: 29.APR.2011 05:09:08

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Sep. 01, 2010	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Oct. 28, 2010	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9K ~ 30MHz	Nov. 16, 2010	Conduction (CO01-CB)
PULSE LIMITER	R&S	ESH3-Z2	100430	9K~30MHz	Jan. 04, 2011	Conduction (CO01-CB)
COND Cable	-	Cable	-	0.15MHz~30MHz	Dec. 04, 2010	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Oct. 17, 2010	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 22, 2010	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Oct. 08, 2010	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 17, 2010	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2010	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Nov. 17, 2010	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP	100304	9kHz ~ 40GHz	Nov. 22, 2010	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 22, 2011	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Sep. 09, 2010*	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N/A	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N/A	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz - 26.5 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz - 26.5 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP30	100023	9KHz~30GHz	Mar. 15, 2011	Conducted (TH01-CB)
Spectrum analyzer	R&S	FSV30	101026	9KHz~30GHz	Jul. 23, 2010	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	May 21, 2010	Conducted (TH01-CB)
Thermo-Hygro Meter	N/A	HC 520	#1	15~70 degree	Nov. 02, 2010	Conducted (TH01-CB)
Signal Generator	R&S	SMR40	100302	10MHz-40GHz	Nov. 19, 2010	Conducted (TH01-CB)
RF Power Divider	HP	11636A	00306	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Splitter	Anaren	44100	1839	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Splitter	Anaren	42100	17930	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
Signal generator	R&S	SMU200A	102782	10MHz-40GHz	Mar. 09, 2011	Conducted (TH01-CB)
Horn Antenna	COM-POWER	AH-118	071187	1GHz - 18GHz	Mar. 18, 2011	Conducted (TH01-CB)
Horn Antenna	COM-POWER	AH-118	071042	1GHz - 18GHz	Oct. 14, 2010	Radiation (05CH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-12	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-13	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Sep. 13, 2010	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Sep. 08, 2010	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

* Calibration Interval of instruments listed above is two year.

NCR means Non-Calibration required.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihsu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-091230

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2010 to January 09, 2013
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities



Jay-San Chen
President, Taiwan Accreditation Foundation
Date : December 30, 2009

P1, total 22 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix