

5401 _____	ROSEMOUNT GÖTEBORG, SWEDEN RADAR LEVEL TRANSMITTER MAY BE PROTECTED BY US AND FOREIGN PATENTS AND PATENTS PENDING	IS CL I, II, III, DIV. 1, GP A,B,C,D,E,F & G
TAG _____		CL I, ZONE 0, AEx ia IIC T4
MFG _____		WHEN INSTALLED PER CONTROL DWG 9150077-XXX
S/N _____		NI CL I, DIV 2, GP A,B,C & D; SUITABLE FOR CL II, III
HART® 4-20mA		DI V 2, GP F & G; NI MAX 42,5 V, 25mA
SUPPLY: 10,5 – 30VDC (I.S.)		APPROVED FM WARNING: SUBSTITUTION OF COMPONENTS MAY IMPAIR SUITABILITY FOR DIV 1 & WARNING: EXPLOSION HAZARD – DO NOT DISCONNECT EQUIPMENT UNLESS AREA IS KNOWN TO BE NON-HAZARDOUS IS/HART
FCC ID: K8C5401		
ENCL. TYPE 4X, IP66, IP67		
		

All text except, FCC information, Model name, Rosemount logo and manufacturing country/city is example text.
The label above is placed as in the “External Photos” document.