

RF EXPOSURE REPORT

REPORT NO.: SA141201E10

MODEL NO.: DAP-2553B1

FCC ID: KA2AP2553B1

RECEIVED: Dec. 01, 2014

TESTED: Dec. 18 to 22, 2014

ISSUED: Dec. 30, 2014

APPLICANT: D-Link Corporation

ADDRESS: No.289, Sinhu 3rd Rd., Neihu District, Taipei City
114, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd.,
Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS : No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung
Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

TEST LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung
Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

TEST LOCATION (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung
Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

This report should not be used by the client to claim
product certification, approval, or endorsement by any
government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION.....	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	7



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA141201E10	Original release	Dec. 30, 2014



A D T

1. CERTIFICATION

PRODUCT: D-Link AirPremier N Dual Band PoE Access Point,
D-Link Wireless N Dual Band PoE Access Point

BRAND NAME: D-Link

MODEL NO.: DAP-2553B1


TEST SAMPLE: R&D SAMPLE

APPLICANT: D-Link Corporation

TESTED: Dec. 18 to 22, 2014

STANDARDS: FCC Part 2 (Section 2.1091)
KDB 447498 D03
IEEE C95.1

The above equipment (Model: DAP-2553B1) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :  , **Date:** Dec. 30, 2014
(Lori Chung, Specialist)

Approved by :  , **Date:** Dec. 30, 2014
(May Chen, Manager)

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Brand	Model	Gain (dBi) Without cable loss	Cable loss (dB)	Net Gain (dBi)	Frequency range (MHz to MHz)	Cable Length (mm)	Antenna Type	Connector Type
Chain (0)	WHA YU GROUP	C037-510912-A (SSR-82286)	3.08	0.6	3.02	2400~2483.5	120	Dipole	SMA Plug Reverse
			5.96	1.1	4.86	5150~5250			
			6.23	1.1	5.13	5250~5350			
			6.17	1.1	5.07	5470~5725			
Chain (1)	WHA YU GROUP	C037-510912-A (SSR-82286)	3.08	0.7	2.38	2400~2483.5	140	Dipole	SMA Plug Reverse
			5.96	1.2	4.76	5150~5250			
			6.23	1.2	5.03	5250~5350			
			6.17	1.2	4.97	5470~5725			
Chain (2)	WHA YU GROUP	C037-510912-A (SSR-82286)	3.08	0.7	2.38	2400~2483.5	170	Dipole	SMA Plug Reverse
			5.96	1.2	4.76	5150~5250			
			6.23	1.2	5.03	5250~5350			
			6.17	1.2	4.97	5470~5725			

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

For 15.247:

802.11b:

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412 ~ 2462	191.102	7.18	20	0.19861	1

$$\text{Directional gain} = 10 \log[(10^{G_{1/20}} + 10^{G_{2/20}} + 10^{G_{3/20} \cdot 2}) / 3] = 7.18 \text{ dBi}$$

802.11g:

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412 ~ 2462	156.814	7.18	20	0.16297	1

$$\text{Directional gain} = 10 \log[(10^{G_{1/20}} + 10^{G_{2/20}} + 10^{G_{3/20} \cdot 2}) / 3] = 7.18 \text{ dBi}$$

802.11n (HT20):

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412 ~ 2462	157.691	7.18	20	0.16388	1

$$\text{Directional gain} = 10 \log[(10^{G_{1/20}} + 10^{G_{2/20}} + 10^{G_{3/20} \cdot 2}) / 3] = 7.18 \text{ dBi}$$

802.11n (HT40):

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2422 ~ 2452	60.288	7.18	20	0.06266	1

$$\text{Directional gain} = 10 \log[(10^{G_{1/20}} + 10^{G_{2/20}} + 10^{G_{3/20} \cdot 2}) / 3] = 7.18 \text{ dBi}$$

For 15.407:

802.11a:

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5180 – 5240	315.189	9.56	20	0.56663	1
5745 - 5825	319.714	9.77	20	0.60324	1

For 5150-5250MHz: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 9.56\text{dBi}$

For 5725-5850MHz: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 9.77\text{dBi}$

802.11n (HT20)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5180 – 5240	311.734	9.56	20	0.56042	1
5745 - 5825	353.51	9.77	20	0.66701	1

For 5150-5250MHz: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 9.56\text{dBi}$

For 5725-5850MHz: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 9.77\text{dBi}$

802.11n (HT40)

FREQUENCY (MHz)	CONDUCTED POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
5190 – 5230	227.548	9.56	20	0.40907	1
5755 - 5795	140.871	9.77	20	0.26580	1

For 5150-5250MHz: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 9.56\text{dBi}$

For 5725-5850MHz: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3] = 9.77\text{dBi}$

--- END ---