

RF Exposure Report

Report No.: SA190726C11A

FCC ID: KA2BA2520PA1

Model: DBA-2520P

Received Date: Jul. 26, 2019

Test Date: Nov. 11 ~ Dec. 25, 2019

Issued Date: Dec. 25, 2019

Applicant: D-Link Corporation

Address: 17595 Mt. Herrmann, Fountain Valley, California, United States, 92708

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

FCC Registration / 788550 / TW0003
Designation Number:



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specifically mentioned, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA190726C11A	Original release	Dec. 25, 2019

1 Certificate of Conformity

Product: Nuclias Cloud-Managed AC1900 Wave 2 Access Point

Brand: D-Link Corporation

Model: DBA-2520P

Sample Status: Engineering sample

Applicant: D-Link Corporation

Test Date: Nov. 11 ~ Dec. 25, 2019

Standards: FCC Part 2 (Section 2.1091)

References Test KDB 447498 D01 General RF Exposure Guidance v06

Guidance: IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Polly Chen , **Date:** Dec. 25, 2019
Polly Chen / Specialist

Approved by : Bruce Chen , **Date:** Dec. 25, 2019
Bruce Chen / Senior Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 30cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
CDD Mode					
2412-2462	27.69	7.77	30	0.311	1
5180-5240	27.68	8.77	30	0.390	1
5260-5320	23.47	8.77	30	0.148	1
5500-5720	23.84	8.77	30	0.161	1
5745-5825	29.98	8.77	30	0.663	1
Beamforming Mode					
2412-2462	22.86	7.77	30	0.102	1
5180-5240	22.91	8.77	30	0.130	1
5260-5320	18.70	8.77	30	0.049	1
5500-5720	19.07	8.77	30	0.054	1
5745-5825	25.21	8.77	30	0.221	1

*Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Note:

1. Directional gain:

2.4GHz Band: Directional gain = 3dBi + 10log(3) = 7.77dBi

5GHz Band: Directional gain = 4dBi + 10log (3) = 8.77dBi

2. The above Max Power is Tune-up Power which client declared.

Conclusion:

2.4GHz & 5GHz can transmit at same time.

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

1. WLAN 2.4GHz + WLAN 5GHz Band 1 = $0.311 / 1 + 0.390 / 1 = 0.701$

2. WLAN 2.4GHz + WLAN 5GHz Band 3 = $0.311 / 1 + 0.161 / 1 = 0.472$

3. WLAN 2.4GHz + WLAN 5GHz Band 4 = $0.311 / 1 + 0.663 / 1 = 0.974$

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---