FCC Radio Test Report

FCC ID: KA2CHS162A1

This report concerns: Original Grant

Project No.	:	2009H044
Equipment	:	DCH-S162 A1
Brand Name	:	D-Link
Test Model	:	DCH-S162 A1
Series Model	:	N/A
Applicant	:	D-Link Corporation
Address	:	17595 Mt. Herrmann，Fountain Valley,California United State 92708
Manufacturer	:	D-Link Corporation
Address	:	17595 Mt. Herrmann，Fountain Valley,California United State 92708
Factory	:	LEEDARSON LIGHTING CO., LTD.
Address	:	Xingtai Industrial Zone,Economic Development Zone, Changtai County,Zhangzhou City, Fujian Province, P.R.China
Date of Receipt	:	Oct. 23, 2020
Date of Test	:	Oct. 23, 2020~Dec. 02, 2020
Issued Date	:	Dec. 14, 2020
Report Version	:	R00
Test Sample	:	Engineering Sample No.: SH2020111669/SH2020111670
Standard(s)	:	FCC Part15, Subpart C (15.247) ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Maker Qi

Prepared by : Maker Qi

Ryan. Wang

Approved by : Ryan Wang

Certificate # 5123. 03

Add: No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210,China
TEL: +86-021-61765666
Web: www.newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, A2LA, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.
Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

Table of Contents Page

REPORT ISSUED HISTORY 6

1 . SUMMARY OF TEST RESULTS 7

1.1 TEST FACILITY 8

1.2 MEASUREMENT UNCERTAINTY 8

1.3 TEST ENVIRONMENT CONDITIONS 8

2 . GENERAL INFORMATION 9

2.1 GENERAL DESCRIPTION OF EUT 9

2.2 DESCRIPTION OF TEST MODES 10

2.3 PARAMETERS OF TEST SOFTWARE 11

2.4 DUTY CYCLE 12

2.5 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 13

2.6 SUPPORT UNITS 13

3 . AC POWER LINE CONDUCTED EMISSIONS TEST 14

3.1 LIMIT 14

3.2 TEST PROCEDURE 14

3.3 DEVIATION FROM TEST STANDARD 14

3.4 TEST SETUP 15

3.5 EUT OPERATION CONDITIONS 15

3.6 TEST RESULTS 15

4 . RADIATED EMISSIONS TEST 16

4.1 LIMIT 16

4.2 TEST PROCEDURE 17

4.3 DEVIATION FROM TEST STANDARD 17

4.4 TEST SETUP 18

4.5 EUT OPERATION CONDITIONS 19

4.6 TEST RESULTS - 9 KHZ TO 30 MHZ 19

4.7 TEST RESULTS - 30 MHZ TO 1000 MHZ 19

4.8 TEST RESULTS - ABOVE 1000 MHZ 19

5 . BANDWIDTH TEST 20

5.1 LIMIT 20

5.2 TEST PROCEDURE 20

5.3 DEVIATION FROM STANDARD 20

5.4 TEST SETUP 20

Table of Contents Page

5.5 EUT OPERATION CONDITIONS 20
5.6 TEST RESULTS 20
6 . MAXIMUM OUTPUT POWER TEST 21
6.1 LIMIT 21
6.2 TEST PROCEDURE 21
6.3 DEVIATION FROM STANDARD 21
6.4 TEST SETUP 21
6.5 EUT OPERATION CONDITIONS 21
6.6 TEST RESULTS 21
7 . CONDUCTED SPURIOUS EMISSIONS 22
7.1 LIMIT 22
7.2 TEST PROCEDURE 22
7.3 DEVIATION FROM STANDARD 22
7.4 TEST SETUP 22
7.5 EUT OPERATION CONDITIONS 22
7.6 TEST RESULTS 22
8 . POWER SPECTRAL DENSITY TEST 23
8.1 LIMIT 23
8.2 TEST PROCEDURE 23
8.3 DEVIATION FROM STANDARD 23
8.4 TEST SETUP 23
8.5 EUT OPERATION CONDITIONS 23
8.6 TEST RESULTS 23
9 . MEASUREMENT INSTRUMENTS LIST 24
10 . EUT TEST PHOTO 26
APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS 29
APPENDIX B - RADIATED EMISSION - 9 KHZ TO 30 MHZ 32
APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ 33
APPENDIX D - RADIATED EMISSION- ABOVE 1000 MHZ 36
APPENDIX E - BANDWIDTH 73
APPENDIX F - MAXIMUM OUTPUT POWER 77
APPENDIX G - CONDUCTED SPURIOUS EMISSIONS 79

Table of Contents **Page**

APPENDIX H - POWER SPECTRAL DENSITY **83**

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	Dec. 14, 2020

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC Part15, Subpart C (15.247)				
Standard(s) Section	**Test Item**	**Test Result**	**Judgment**	**Remark**
15.207	AC Power Line Conducted Emissions	APPENDIX A	PASS	------
15.247(d) 15.205(a) 15.209(a)	Radiated Emissions	APPENDIX B APPENDIX C APPENDIX D	PASS	------
15.247(a)(2)	Bandwidth	APPENDIX E	PASS	------
15.247(b)(3)	Maximum Output Power	APPENDIX F	PASS	------
15.247(d)	Conducted Spurious Emissions	APPENDIX G	PASS	------
15.247(e)	Power Spectral Density	APPENDIX H	PASS	------
15.203	Antenna Requirement	------	PASS	Note(2)

Note:

(1) “N/A” denotes test is not applicable in this test report.

(2) The device what use a permanently attached antenna were considered sufficient to comply with the provisions of 15.203.

1.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210,China
BTL's Test Firm Registration Number for FCC: 476765
BTL's Designation Number for FCC: CN1241

1.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))
The BTL measurement uncertainty as below table:

A. Radiated emissions test:

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)
SH-CB01	CISPR	9 KHz~30 MHz	V	3.79
		9 KHz~30 MHz	H	3.57
		30 MHz~200 MHz	V	4.04
		30 MHz~200 MHz	H	3.76
		200 MHz~1,000 MHz	V	4.24
		200 MHz~1,000 MHz	H	3.84
		1 GHz~18 GHz	V	4.46
		1 GHz~18 GHz	H	4.40
		18 GHz~40 GHz	V	3.95
		18 GHz~40 GHz	H	3.95

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By
AC Power Line Conducted Emissions	25°C	54%	AC 120V/60Hz	Joven Xiong
Radiated Emissions-9K-30MHz	24°C	58%	AC 120V/60Hz	Forest Li
Radiated Emissions-30 MHz to 1GHz	24°C	58%	AC 120V/60Hz	Forest Li
Radiated Emissions-Above 1000 MHz	24°C	58%	AC 120V/60Hz	Forest Li
Bandwidth	23°C	62%	AC 120V/60Hz	Danny Dang
Maximum output power & e.i.r.p.	23°C	62%	AC 120V/60Hz	Danny Dang
Conducted Spurious Emissions	23°C	62%	AC 120V/60Hz	Danny Dang
Power Spectral Density	23°C	62%	AC 120V/60Hz	Danny Dang

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	DCH-S162 A1
Brand Name	D-Link
Test Model	DCH-S162 A1
Series Model	N/A
Model Difference(s)	N/A
Software Version	V1.00.07
Hardware Version	V2.0
Power Source	AC Power supplied.
Power Rating	AC100~240V 50/60Hz
Operation Frequency	2412 MHz ~ 2462 MHz
Modulation Type	IEEE 802.11b: DSSS IEEE 802.11g: OFDM IEEE 802.11n: OFDM
Bit Rate of Transmitter	IEEE 802.11b: 11/5.5/2/1 Mbps IEEE 802.11g: 54/48/36/24/18/12/9/6 Mbps IEEE 802.11n: up to 150 Mbps
Maximum Output Power Non-Beamforming	IEEE 802.11b: 19.68 dBm (0.0929 W) IEEE 802.11g: 23.84 dBm (0.2421 W) IEEE 802.11n (HT20): 22.71 dBm (0.1866 W)

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. Channel List:

CH01 - CH11 for IEEE 802.11b, IEEE 802.11g, IEEE 802.11n (HT20)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

3. Antenna Specification:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Note
1	N/A	N/A	Loop	N/A	1.86	N/A

Note:

The antenna gain is provided by the manufacturer.

2.2 DESCRIPTION OF TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode.

Pretest Mode	Description
Mode 1	TX B Mode Channel 01/06/11
Mode 2	TX G Mode Channel 01/06/11
Mode 3	TX N-20 MHz Mode Channel 01/06/11
Mode 4	TX G Mode Channel 01

Following mode(s) as (were) found to be the worst case(s) and selected for the final test.

AC power line conducted emissions test	
Final Test Mode:	Description
Mode 4	TX G Mode Channel 01

Radiated emissions test - Below 1GHz	
Final Test Mode:	Description
Mode 5	TX G Mode Channel 01

Radiated emissions test- Above 1GHz	
Final Test Mode:	Description
Mode 1	TX B Mode Channel 01/06/11
Mode 2	TX G Mode Channel 01/06/11
Mode 3	TX N-20 MHz Mode Channel 01/06/11

Conducted test	
Final Test Mode:	Description
Mode 1	TX B Mode Channel 01/06/11
Mode 2	TX G Mode Channel 01/06/11
Mode 3	TX N-20 MHz Mode Channel 01/06/11

NOTE:

(1) The measurements are performed at the high, middle, low available channels.

(3) For radiated emission below 1 GHz test, the IEEE 802.11g Channel 01 is found to be the worst case and recorded.

2.3 PARAMETERS OF TEST SOFTWARE

Test Software	UI_mptoolv1.0.0.1		
Frequency (MHz)	2412	2437	2462
IEEE 802.11b	88.00	88.00	87.00
IEEE 802.11g	92.00	90.00	90.00
IEEE 802.11n (HT20)	86.00	84.00	84.00

2.4 DUTY CYCLE

If duty cycle is ≥ 98 %, duty factor is not required.
If duty cycle is < 98 %, duty factor shall be considered.
The output power = measured power + duty factor.

IEEE 802.11b



Date: 20.NOV.2020 15:12:27

Duty cycle = 12.448 ms / 12.576 ms = 98.98%
Duty Factor = 10 log(1/Duty cycle) = 0.04

IEEE 802.11g



Date: 20.NOV.2020 15:12:56

Duty cycle = 2.068 ms / 2.200 ms = 94.00%
Duty Factor = 10 log(1/Duty cycle) = 0.27

IEEE 802.11n (HT20)



Date: 20.NOV.2020 15:13:30

Duty cycle = 1.928 ms / 2.064 ms = 93.41%
Duty Factor = 10 log(1/Duty cycle) = 0.30,

NOTE:
For IEEE 802.11b:
For radiated emissions frequency above 1 GHz, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 kHz (Duty cycle >98%).

For IEEE 802.11g and IEEE 802.11n (HT20):
For radiated emissions frequency above 1 GHz, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 1 kHz (Duty cycle < 98%).

2.5 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.6 SUPPORT UNITS

Item	Equipment	Brand	Model No.	Series No.
-	-	-	-	-

Item	Cable Type	Shielded Type	Ferrite Core	Length
-	-	-	-	-

3. AC POWER LINE CONDUCTED EMISSIONS TEST

3.1 LIMIT

Frequency of Emission (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56*	56 to 46*
0.50 - 5.0	56	46
5.0 - 30.0	60	50

NOTE:

(1) The tighter limit applies at the band edges.
(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item -EUT Test Photos.

3.3 DEVIATION FROM TEST STANDARD

No deviation

3.4 TEST SETUP



3.5 EUT OPERATION CONDITIONS

EUT was programmed to be in continuously transmitting mode.

3.6 TEST RESULTS

Please refer to the APPENDIX A.

4. RADIATED EMISSIONS TEST

4.1 LIMIT

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-1000 MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000 MHz)

Frequency (MHz)	(dBuV/m at 3 m)	
	Peak	Average
Above 1000	74	54

NOTE:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

(4) The test result calculated as following:
Measurement Value = Reading Level + Correct Factor
Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)
Margin Level = Measurement Value - Limit Value

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1 MHz / 3 MHz for Peak, 1 MHz / 1/T for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9 kHz~90 kHz for PK/AVG detector
Start ~ Stop Frequency	90 kHz~110 kHz for QP detector
Start ~ Stop Frequency	110 kHz~490 kHz for PK/AVG detector
Start ~ Stop Frequency	490 kHz~30 MHz for QP detector
Start ~ Stop Frequency	30 MHz~1000 MHz for QP detector

4.2 TEST PROCEDURE

a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1 GHz)
b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1 GHz)
c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn‘t perform. (below 1 GHz)
h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn‘t perform. (above 1 GHz)
i. For the actual test configuration, please refer to the related Item -EUT Test Photos.

4.3 DEVIATION FROM TEST STANDARD

No deviation

4.4 TEST SETUP

9 kHz-30 MHz



30 MHz to 1 GHz



Above 1 GHz



4.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.6 TEST RESULTS - 9 KHZ TO 30 MHZ

Please refer to the APPENDIX B

Remark:

(1) Distance extrapolation factor = 40 log (specific distance / test distance) (dB).
(2) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.7 TEST RESULTS - 30 MHZ TO 1000 MHZ

Please refer to the APPENDIX C.

4.8 TEST RESULTS - ABOVE 1000 MHZ

Please refer to the APPENDIX D.

Remark:

(1) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

5. BANDWIDTH TEST

5.1 LIMIT

FCC Part15, Subpart C (15.247)		
Section	Test Item	Limit
15.247(a)(2)	6 dB Bandwidth	Minimum 500 kHz
	99% Emission Bandwidth	-

5.2 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.

b. Spectrum Setting:
For 6 dB Bandwidth : RBW= 100 kHz, VBW=300 kHz, Sweep time = auto.
For 99% Emission Bandwidth B/G/N-20 Mode: RBW= 300 KHz, VBW=1 MHz, Sweep time = 2.5 ms.
For 99% Emission Bandwidth N-40 Mode: RBW= 1 MHz, VBW=3 MHz, Sweep time = 2.5 ms.

c. The bandwidth was performed in accordance with method 11.8.1 of ANSI C63.10-2013.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

5.6 TEST RESULTS

Please refer to the APPENDIX E.

6. MAXIMUM OUTPUT POWER TEST

6.1 LIMIT

FCC Part15, Subpart C (15.247)		
Section	Test Item	Limit
15.247(b)(3)	Maximum Output Power	1 Watt or 30dBm

6.2 TEST PROCEDURE

a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below.

b. The maximum conducted output power was performed in accordance with method 11.9.1.3 (for peak power) or 11.9.2.3.1 (for AVG power) of ANSI C63.10-2013.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

6.6 TEST RESULTS

Please refer to the APPENDIX F.

7. CONDUCTED SPURIOUS EMISSIONS

7.1 LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

7.2 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. Spectrum Setting: RBW= 100 kHz, VBW=300 kHz, Sweep time = Auto.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP

7.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

7.6 TEST RESULTS

Please refer to the APPENDIX G.

8. POWER SPECTRAL DENSITY TEST

8.1 LIMIT

FCC Part15, Subpart C (15.247)		
Section	Test Item	Limit
15.247(e)	Power Spectral Density	8 dBm (in any 3 kHz)

8.2 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. Spectrum Setting: RBW=3 kHz, VBW=10 kHz, Sweep time = Auto.
c. The Power Spectral Density was performed in accordance with method 11.10.2 of ANSI C63.10-2013.

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP

8.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

8.6 TEST RESULTS

Please refer to the APPENDIX H.

9. MEASUREMENT INSTRUMENTS LIST

AC Power Line Conducted Emissions					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Line Impedance Stabilisation Network	Schwarzbeck	NNLK 8121	8121-822	Mar. 21, 2021
2	TWO-LINE V-NETWORK	R&S	ENV216	101340	Aug. 23, 2021
3	Test Cable	emci	EMCRG400-BM-NM-10000	170628	Jul. 15, 2021
4	EMI Test Receiver	R&S	ESCI	100082	Mar. 21, 2021
5	50Ω Terminator	SHX	TF2-1G-A	17051602	Mar. 21, 2021
6	50Ω coaxial switch	Anritsu	MP59B	6201750902	Mar. 21, 2021
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

Radiated Emissions - 30 MHz to 1 GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	719	Apr. 02, 2021
2	Pre-Amplifier	emci	EMC9135	980400	Mar. 21, 2021
3	MXE EMI Receiver	Keysight	N9038A	MY57150106	Mar. 21, 2021
4	Test Cable	emci	EMC104-SM-SM-7000	170330	Apr. 13, 2021
5	Test Cable	emci	EMC104-SM-SM-1000	170331	Apr. 13, 2021
6	Test Cable	emci	EMC104-SM-NM-3500	170621	Apr. 13, 2021
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

Radiated Emissions - Above 1 GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Double-Ridged Waveguide Horn Antenna	ETS-Lindgren	9120D	00206960	Apr. 02, 2021
2	Pre-Amplifier	emci	EMC012645SE	980421	May. 11, 2021
3	EXA Spectrum Analyzer	Keysight	N9010A	MY56480545	Mar. 21, 2021
4	Test Cable	emci	EMC104-SM-SM-7000	170330	Apr. 13, 2021
5	Test Cable	emci	EMC104-SM-SM-1000	170331	Apr. 13, 2021
6	Test Cable	emci	EMC104-SM-NM-3500	170621	Apr. 13, 2021
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
8	MXE EMI Receiver	Keysight	N9038A	MY57150106	May. 06, 2021
9	Double-Ridged Waveguide Horn Antenna	ETS-Lindgren	3116C	00203919	Jul. 20, 2021
10	Pre-Amplifier	emci	EMC184045SE	980409	Mar. 21, 2021
11	EXA Spectrum Analyzer	Keysight	N9010A	MY56480579	Mar. 21, 2021
12	Test Cable	emci	EMC102-KM-KM-800	170654	Apr. 13, 2021
13	Test Cable	emci	Super Reliable-40G-SS11-7000	W0030860001	Apr. 13, 2021
14	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

Bandwidth					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100626	May. 06, 2021

Maximum Output Power					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Peak Power Analyze	Keysight	8990B	MY51000507	Mar. 21, 2021
2	Wideband Power Sensor	Keysight	N9123A	MY58310003	Mar. 21, 2021

Antenna Conducted Spurious Emissions					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100626	May. 06, 2021

Power Spectral Density					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100626	May. 06, 2021

Remark: ”N/A” denotes no model name, serial no. or calibration specified.
All calibration period of equipment list is one year.

10. EUT TEST PHOTO

Conducted Emissions Test Photos



Radiated Emissions Test Photos

30 MHz to 1 GHz





Radiated Emissions Test Photos

Above 1 GHz





APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS

Test Mode:	TX G Mode Channel 01



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.3480	32.94	9.76	42.70	59.01	-16.31	peak	
2	*	0.5415	34.99	9.80	44.79	56.00	-11.21	peak	
3		0.5820	34.12	9.81	43.93	56.00	-12.07	peak	
4		1.1625	32.11	9.85	41.96	56.00	-14.04	peak	
5		1.9770	31.90	9.90	41.80	56.00	-14.20	peak	
6		3.4440	30.50	9.98	40.48	56.00	-15.52	peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX G Mode Channel 01

Neutral



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1590	35.71	9.69	45.40	65.52	-20.12	peak	
2		0.3885	30.79	9.76	40.55	58.10	-17.55	peak	
3	*	0.5415	35.01	9.78	44.79	56.00	-11.21	peak	
4		0.5775	32.00	9.79	41.79	56.00	-14.21	peak	
5		1.1220	30.05	9.83	39.88	56.00	-16.12	peak	
6		1.9005	28.97	9.87	38.84	56.00	-17.16	peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX B - RADIATED EMISSION - 9 KHZ TO 30 MHZ

Note: The measured value have enough margin over 20dB than the limit, therefore they are not reported.

APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ

Test Mode:	TX G Mode Channel 01

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	67.3450	51.97	-18.15	33.82	40.00	-6.18	Peak	
2	142.5200	46.16	-16.67	29.49	43.50	-14.01	Peak	
3	305.4800	54.69	-15.48	39.21	46.00	-6.79	Peak	
4	436.4300	48.63	-12.33	36.30	46.00	-9.70	Peak	
5	712.3950	42.07	-7.82	34.25	46.00	-11.75	Peak	
6 *	804.5450	46.45	-6.51	39.94	46.00	-6.06	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX G Mode Channel 01

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	85.2900	57.26	-21.91	35.35	40.00	-4.65	Peak	
2	211.8750	55.77	-19.36	36.41	43.50	-7.09	Peak	
3	383.0799	40.13	-13.68	26.45	46.00	-19.55	Peak	
4	457.2850	41.58	-11.77	29.81	46.00	-16.19	Peak	
5	800.1800	38.04	-6.53	31.51	46.00	-14.49	Peak	
6	913.1850	37.94	-5.69	32.25	46.00	-13.75	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX D - RADIATED EMISSION- ABOVE 1000 MHZ

Test Mode:	TX B Mode 2412 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2389.1350	23.28	31.74	55.02	74.00	-18.98	Peak	
2	2389.1350	2.75	31.74	34.49	54.00	-19.51	AVG	
3	2411.1750	68.97	31.72	100.69	74.00	26.69	Peak	
4 *	2411.1750	66.35	31.72	98.07	54.00	44.07	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX B Mode 2412 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4823.7250	53.06	-10.91	42.15	74.00	-31.85	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX B Mode 2412 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2385.2400	22.01	31.75	53.76	74.00	-20.24	Peak	
2	2385.2400	2.51	31.75	34.26	54.00	-19.74	AVG	
3	2411.1750	69.29	31.72	101.01	74.00	27.01	Peak	
4 *	2411.1750	67.04	31.72	98.76	54.00	44.76	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX B Mode 2412 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4823.7250	54.47	-10.91	43.56	74.00	-30.44	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX B Mode 2437 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	22.12	31.74	53.86	74.00	-20.14	Peak	
2	2390.0000	1.45	31.74	33.19	54.00	-20.81	AVG	
3	2436.1600	70.28	31.72	102.00	74.00	28.00	Peak	
4 *	2436.1600	67.67	31.72	99.39	54.00	45.39	AVG	
5	2483.5000	22.44	31.71	54.15	74.00	-19.85	Peak	
6	2483.5000	1.36	31.71	33.07	54.00	-20.93	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX B Mode 2437 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4874.0000	53.89	-10.79	43.10	74.00	-30.90	Peak	
2 *	7312.5250	51.09	-4.07	47.02	74.00	-26.98	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX B Mode 2437 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	23.49	31.74	55.23	74.00	-18.77	Peak	
2	2390.0000	1.38	31.74	33.12	54.00	-20.88	AVG	
3	2437.7750	66.37	31.72	98.09	74.00	24.09	Peak	
4 *	2437.7750	67.21	31.72	98.93	54.00	44.93	AVG	
5	2483.5000	22.24	31.71	53.95	74.00	-20.05	Peak	
6	2483.5000	1.06	31.71	32.77	54.00	-21.23	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX B Mode 2437 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	4873.4500	54.50	-10.79	43.71	74.00	-30.29	Peak	
2 *	7311.2500	51.69	-4.07	47.62	74.00	-26.38	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX B Mode 2462 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2461.2400	70.07	31.71	101.78	74.00	27.78	Peak	
2 *	2461.2400	67.83	31.71	99.54	54.00	45.54	AVG	
3	2483.5000	22.24	31.71	53.95	74.00	-20.05	Peak	
4	2483.5000	2.59	31.71	34.30	54.00	-19.70	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX B Mode 2462 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4923.1750	53.25	-10.63	42.62	74.00	-31.38	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX B Mode 2462 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2461.2400	69.15	31.71	100.86	74.00	26.86	Peak	
2 *	2461.2400	66.66	31.71	98.37	54.00	44.37	AVG	
3	2483.5000	22.46	31.71	54.17	74.00	-19.83	Peak	
4	2483.5000	2.08	31.71	33.79	54.00	-20.21	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX B Mode 2462 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4924.4500	56.20	-10.62	45.58	74.00	-28.42	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX G Mode 2412 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	25.26	31.74	57.00	74.00	-17.00	Peak	
2	2390.0000	6.54	31.74	38.28	54.00	-15.72	AVG	
3	2410.7950	68.59	31.72	100.31	74.00	26.31	Peak	
4 *	2410.7950	60.35	31.72	92.07	54.00	38.07	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX G Mode 2412 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4824.0000	48.81	-10.91	37.90	74.00	-36.10	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX G Mode 2412 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	22.58	31.74	54.32	74.00	-19.68	Peak	
2	2390.0000	5.60	31.74	37.34	54.00	-16.66	AVG	
3	2409.7500	69.05	31.72	100.77	74.00	26.77	Peak	
4 *	2409.7500	60.58	31.72	92.30	54.00	38.30	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX G Mode 2412 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4824.0000	50.67	-10.91	39.76	74.00	-34.24	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX G Mode 2437 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	22.96	31.74	54.70	74.00	-19.30	Peak	
2	2390.0000	3.03	31.74	34.77	54.00	-19.23	AVG	
3	2439.0100	69.00	31.72	100.72	74.00	26.72	Peak	
4 *	2439.0100	61.35	31.72	93.07	54.00	39.07	AVG	
5	2483.5000	22.93	31.71	54.64	74.00	-19.36	Peak	
6	2483.5000	3.43	31.71	35.14	54.00	-18.86	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX G Mode 2437 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4874.0000	49.00	-10.79	38.21	74.00	-35.79	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX G Mode 2437 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	22.70	31.74	54.44	74.00	-19.56	Peak	
2	2390.0000	3.04	31.74	34.78	54.00	-19.22	AVG	
3	2439.2000	67.04	31.72	98.76	74.00	24.76	Peak	
4 *	2439.2000	59.12	31.72	90.84	54.00	36.84	AVG	
5	2483.5000	22.39	31.71	54.10	74.00	-19.90	Peak	
6	2483.5000	2.63	31.71	34.34	54.00	-19.66	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX G Mode 2437 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4874.0000	51.40	-10.79	40.61	74.00	-33.39	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX G Mode 2462 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2460.4800	68.21	31.71	99.92	74.00	25.92	Peak	
2 *	2460.4800	60.77	31.71	92.48	54.00	38.48	AVG	
3	2483.5000	27.90	31.71	59.61	74.00	-14.39	Peak	
4	2483.5000	10.09	31.71	41.80	54.00	-12.20	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX G Mode 2462 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4924.0000	49.24	-10.63	38.61	74.00	-35.39	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX G Mode 2462 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2460.3850	67.19	31.71	98.90	74.00	24.90	Peak	
2 *	2460.3850	59.59	31.71	91.30	54.00	37.30	AVG	
3	2483.5000	27.27	31.71	58.98	74.00	-15.02	Peak	
4	2483.5000	7.69	31.71	39.40	54.00	-14.60	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX G Mode 2462 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4928.2750	52.55	-10.61	41.94	74.00	-32.06	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX N-20M Mode 2412 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	22.46	31.74	54.20	74.00	-19.80	Peak	
2	2390.0000	3.33	31.74	35.07	54.00	-18.93	AVG	
3	2410.1299	66.27	31.72	97.99	74.00	23.99	Peak	
4 *	2410.1299	55.79	31.72	87.51	54.00	33.51	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX N-20M Mode 2412 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4824.0000	48.57	-10.91	37.66	74.00	-36.34	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX N-20M Mode 2412 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	22.36	31.74	54.10	74.00	-19.90	Peak	
2	2390.0000	4.02	31.74	35.76	54.00	-18.24	AVG	
3	2409.8450	66.89	31.72	98.61	74.00	24.61	Peak	
4 *	2409.8450	58.73	31.72	90.45	54.00	36.45	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX N-20M Mode 2412 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4824.0000	50.24	-10.91	39.33	74.00	-34.67	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX N-20M Mode 2437 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	22.17	31.74	53.91	74.00	-20.09	Peak	
2	2390.0000	2.71	31.74	34.45	54.00	-19.55	AVG	
3	2438.6299	66.35	31.72	98.07	74.00	24.07	Peak	
4 *	2438.6299	58.02	31.72	89.74	54.00	35.74	AVG	
5	2483.5000	22.61	31.71	54.32	74.00	-19.68	Peak	
6	2483.5000	2.46	31.71	34.17	54.00	-19.83	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX N-20M Mode 2437 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4874.0000	49.24	-10.79	38.45	74.00	-35.55	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX N-20M Mode 2437 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2390.0000	23.11	31.74	54.85	74.00	-19.15	Peak	
2	2390.0000	2.82	31.74	34.56	54.00	-19.44	AVG	
3	2438.0600	68.06	31.72	99.78	74.00	25.78	Peak	
4 *	2438.0600	59.87	31.72	91.59	54.00	37.59	AVG	
5	2483.5000	22.23	31.71	53.94	74.00	-20.06	Peak	
6	2483.5000	2.63	31.71	34.34	54.00	-19.66	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX N-20M Mode 2437 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4874.0000	52.02	-10.79	41.23	74.00	-32.77	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX N-20M Mode 2462 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2460.1950	67.13	31.71	98.84	74.00	24.84	Peak	
2 *	2460.1950	58.69	31.71	90.40	54.00	36.40	AVG	
3	2483.5000	24.54	31.71	56.25	74.00	-17.75	Peak	
4	2483.5000	6.81	31.71	38.52	54.00	-15.48	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX N-20M Mode 2462 MHz

Vertical



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4924.0000	48.69	-10.63	38.06	74.00	-35.94	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX N-20M Mode 2462 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	2460.4800	67.59	31.71	99.30	74.00	25.30	Peak	
2 *	2460.4800	60.00	31.71	91.71	54.00	37.71	AVG	
3	2483.5000	24.91	31.71	56.62	74.00	-17.38	Peak	
4	2483.5000	7.44	31.71	39.15	54.00	-14.85	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode:	TX N-20M Mode 2462 MHz

Horizontal



No.	Freq.	Reading Level	Correct Factor	Measure ment	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1 *	4924.0000	50.67	-10.63	40.04	74.00	-33.96	Peak	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX E - BANDWIDTH

Test Mode	TX B Mode

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	6 dB Bandwidth Min. Limit (kHz)	Result
01	2412	8.08	500	Complies
06	2437	9.58	500	Complies
11	2462	9.58	500	Complies

CH01



Date: 13.MAY.2020 16:34:09

CH06



Date: 27.NOV.2020 11:35:55

CH11



Date: 27.NOV.2020 11:41:01

Channel	Frequency (MHz)	99 % Emission Bandwidth (MHz)	Result
01	2412	14.00	Complies
06	2437	14.00	Complies
11	2462	14.16	Complies

CH01



Date: 27.NOV.2020 11:33:42

CH06



Date: 27.NOV.2020 11:36:02

CH11



Date: 27.NOV.2020 11:41:07

Test Mode	TX G Mode

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	6 dB Bandwidth Min. Limit (kHz)	Result
01	2412	16.39	500	Complies
06	2437	16.35	500	Complies
11	2462	16.35	500	Complies

CH01



Date: 27.NOV.2020 11:44:22

CH06



Date: 27.NOV.2020 11:54:52

CH11



Date: 27.NOV.2020 11:57:54

Channel	Frequency (MHz)	99 % Emission Bandwidth (MHz)	Result
01	2412	17.04	Complies
06	2437	17.12	Complies
11	2462	17.04	Complies

CH01



Date: 27.NOV.2020 11:44:28

CH06



Date: 27.NOV.2020 11:54:59

CH11



Date: 27.NOV.2020 11:58:01

Test Mode	TX N-20M Mode

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	6 dB Bandwidth Min. Limit (kHz)	Result
01	2412	16.40	500	Complies
06	2437	16.43	500	Complies
11	2462	16.42	500	Complies

CH01



CH06



CH11



Channel	Frequency (MHz)	99 % Emission Bandwidth (MHz)	Result
01	2412	17.12	Complies
06	2437	17.12	Complies
11	2462	16.96	Complies

CH01



CH06



CH11



APPENDIX F - MAXIMUM OUTPUT POWER

Test Mode	TX B Mode

Channel	Frequency (MHz)	Peak Output Power (dBm)	Max. Limit (W)	Result
01	2412	19.45	1.0000	Complies
06	2437	19.68	1.0000	Complies
11	2462	19.46	1.0000	Complies

Test Mode	TX G Mode

Channel	Frequency (MHz)	Peak Output Power (dBm)	Max. Limit (W)	Result
01	2412	23.84	1.0000	Complies
06	2437	23.54	1.0000	Complies
11	2462	23.42	1.0000	Complies

Test Mode	TX N-20M Mode

Channel	Frequency (MHz)	Peak Output Power (dBm)	Max. Limit (W)	Result
01	2412	22.71	1.0000	Complies
06	2437	22.65	1.0000	Complies
11	2462	22.70	1.0000	Complies

APPENDIX G - CONDUCTED SPURIOUS EMISSIONS

Test Mode	TX B Mode

Bandedge-CH01



Date: 27.NOV.2020 11:33:49

Bandedge-CH11



Date: 27.NOV.2020 11:41:15

CH01 – 10th Harmonic of the fundamental frequency



Date: 27.NOV.2020 11:34:02



Date: 27.NOV.2020 11:34:10



Date: 27.NOV.2020 11:34:17

CH06 – 10th Harmonic of the fundamental frequency



Date: 27.NOV.2020 11:36:22



Date: 27.NOV.2020 11:36:30



Date: 27.NOV.2020 11:36:37

CH11 – 10th Harmonic of the fundamental frequency



Date: 27.NOV.2020 11:41:28



Date: 27.NOV.2020 11:41:35



Date: 27.NOV.2020 11:41:43

Test Mode	TX G Mode

Bandedge-CH01



Date: 27.NOV.2020 11:44:36

Bandedge-CH11



Date: 27.NOV.2020 11:58:08

CH01 – 10th Harmonic of the fundamental frequency



Date: 27.NOV.2020 11:44:49



Date: 27.NOV.2020 11:44:56



Date: 27.NOV.2020 11:45:03

CH06 – 10th Harmonic of the fundamental frequency



Date: 27.NOV.2020 11:55:20



Date: 27.NOV.2020 11:55:27



Date: 27.NOV.2020 11:55:34

CH11 – 10th Harmonic of the fundamental frequency



Date: 27.NOV.2020 11:58:21



Date: 27.NOV.2020 11:58:28



Date: 27.NOV.2020 11:58:36

Test Mode	TX N-20M Mode

Bandedge-CH01



Date: 27.NOV.2020 12:00:36

Bandedge-CH11



Date: 27.NOV.2020 12:06:57

CH01 – 10th Harmonic of the fundamental frequency



Date: 27.NOV.2020 12:00:49



Date: 27.NOV.2020 12:00:56



Date: 27.NOV.2020 12:01:04

CH06 – 10th Harmonic of the fundamental frequency



Date: 27.NOV.2020 12:04:43



Date: 27.NOV.2020 12:04:50



Date: 27.NOV.2020 12:04:58

CH11 – 10th Harmonic of the fundamental frequency



Date: 27.NOV.2020 12:07:10



Date: 27.NOV.2020 12:07:17



Date: 27.NOV.2020 12:07:24

APPENDIX H - POWER SPECTRAL DENSITY

Test Mode	TX B Mode

Channel	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
01	2412	-5.52	8	Complies
06	2437	-4.61	8	Complies
11	2462	-6.00	8	Complies

CH01



Date: 27.NOV.2020 11:34:25

CH06



Date: 27.NOV.2020 11:36:45

CH11



Date: 27.NOV.2020 11:41:51

Test Mode	TX G Mode

Channel	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
01	2412	-8.62	8	Complies
06	2437	-10.44	8	Complies
11	2462	-10.24	8	Complies

CH01



Date: 27.NOV.2020 11:50:03

CH06



Date: 27.NOV.2020 11:55:43

CH11



Date: 27.NOV.2020 11:58:44

Test Mode	TX N-20M Mode

Channel	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
01	2412	-11.22	8	Complies
06	2437	-11.62	8	Complies
11	2462	-11.23	8	Complies

CH01



CH06



CH11



End of Test Report