

FCC TEST REPORT

REPORT NO.: RF931018L03

MODEL NO.: DI-524

RECEIVED: Oct. 07, 2004

TESTED: Oct. 07, 2004 ~ Jan. 03, 2005

ISSUED: Jan. 05, 2005

APPLICANT: D-Link Corporation

ADDRESS: No.8,Li-Hsin VII Road Science Based
Industrial Park Hsin-Chu,Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan,
R.O.C.

This test report consists of 60 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.



Table of Contents

1	CERTIFICATION	4
2	SUMMARY OF TEST RESULTS	5
2.1	GENERAL DESCRIPTION OF EUT	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	7
3.4	DESCRIPTION OF SUPPORT UNITS	8
3.5	CONFIGURATION OF SYSTEM UNDER TEST	8
4	TEST TYPES AND RESULTS	9
4.1	CONDUCTED EMISSION MEASUREMENT	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	9
4.1.2	TEST INSTRUMENTS	9
4.1.3	TEST PROCEDURES	10
4.1.4	DEVIATION FROM TEST STANDARD	10
4.1.5	TEST SETUP	11
4.1.6	EUT OPERATING CONDITIONS	11
4.1.7	TEST RESULTS	11
4.2	RADIATED EMISSION MEASUREMENT	18
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	18
4.2.2	TEST INSTRUMENTS	19
4.2.3	TEST PROCEDURES	20
4.2.4	DEVIATION FROM TEST STANDARD	20
4.2.5	TEST SETUP	21
4.2.6	EUT OPERATING CONDITIONS	21
4.2.7	TEST RESULTS	22
4.2.8	TEST RESULTS (A)	23
4.2.9	TEST RESULTS (B)	26
4.3	6dB BANDWIDTH MEASUREMENT	29
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	29
4.3.2	TEST INSTRUMENTS	29
4.3.3	TEST PROCEDURE	30
4.3.4	DEVIATION FROM TEST STANDARD	30
4.3.5	TEST SETUP	30
4.3.6	EUT OPERATING CONDITIONS	30
4.3.7	TEST RESULTS (A)	31
4.3.8	TEST RESULTS (B)	34
4.4	MAXIMUM PEAK OUTPUT POWER	37
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	37
4.4.2	TEST INSTRUMENTS	37
4.4.3	TEST PROCEDURES	38
4.4.4	DEVIATION FROM TEST STANDARD	38
4.4.5	TEST SETUP	38
4.4.6	EUT OPERATING CONDITIONS	38

4.4.7	TEST RESULTS (A)	39
4.4.8	TEST RESULTS (B)	39
4.5	POWER SPECTRAL DENSITY MEASUREMENT	40
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	40
4.5.2	TEST INSTRUMENTS.....	40
4.5.3	TEST PROCEDURE.....	41
4.5.4	DEVIATION FROM TEST STANDARD	41
4.5.5	TEST SETUP.....	41
4.5.6	EUT OPERATING CONDITIONS	41
4.5.7	TEST RESULTS (A)	42
4.5.8	TEST RESULTS (B)	45
4.6	BAND EDGES MEASUREMENT	48
4.6.1	LIMITS OF BAND EDGES MEASUREMENT.....	48
4.6.2	TEST INSTRUMENTS.....	48
4.6.3	TEST PROCEDURE.....	48
4.6.4	DEVIATION FROM TEST STANDARD	48
4.6.5	EUT OPERATING CONDITION	48
4.6.6	TEST RESULTS	49
4.6.7	TEST RESULTS(A)	49
4.6.8	TEST RESULTS(B)	50
4.7	ANTENNA REQUIREMENT	57
4.7.1	STANDARD APPLICABLE	57
4.7.2	ANTENNA CONNECTED CONSTRUCTION	57
5	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	58
6	INFORMATION ON THE TESTING LABORATORIES	60



1 CERTIFICATION

PRODUCT : Wireless G Router
MODEL NO. : DI-524
BRAND NAME : D-Link
APPLICANT : D-Link Corporation
TESTED : Oct. 07, 2004 ~ Jan. 03, 2005
TEST SAMPLE : ENGINEERING SAMPLE
STANDARDS : FCC Part 15, Subpart C (Section 15.247),
ANSI C63.4-2003

The above equipment has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Andrea Hsia , **DATE:** Jan. 05, 2005
(Andrea Hsia)

TECHNICAL

ACCEPTANCE : Gary Chang , **DATE:** Jan. 05, 2005
Responsible for RF (Gary Chang)

APPROVED BY : Cody Chang , **DATE:** Jan. 05, 2005
(Cody Chang, Deputy Manager)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -13.51dB at 2.547MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -1.28dB at 2390.00MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

2.1 GENERAL DESCRIPTION OF EUT

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.73 dB
	200MHz ~1000MHz	3.74 dB
	1GHz ~ 18GHz	2.20 dB
	18GHz ~ 40GHz	1.88 dB

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless G Router
MODEL NO.	DI-524
POWER SUPPLY	5.0Vdc from AC adapter
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
RADIO TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	56.49mW
ANTENNA TYPE	Dipole antenna with 2dBi gain (Printed antenna for Receiver use)
DATA CABLE	NA
I/O PORTS	4 LAN and 1 WAN ports
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT was tested with the following adapter:

BRAND:	D-Link
MODEL :	JTA0302B
INPUT :	100-120Vac, 50-60Hz, 0.5A
OUTPUT :	5.0Vdc, 2.5A
POWER LINE:	DC 1.8m non-shielded cable without core

2. The EUT operates in the 2.4GHz frequency spectrum with throughput of up to 54Mbps.
3. The EUT complies with IEEE 802.11g standards and backwards compatible with IEEE 802.11b products.
4. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

NOTE:

1. Below 1GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11 with OFDM technique, the worst case was chosen for final test.
2. Above 1GHz, the channel 1, 6, and 11 were tested individually.
3. After pre-testing all data rates, the worst cases were 11Mbps with DSSS technique and 6Mbps with OFDM technique.
4. For conducted emission test, we have chosen 6Mbps with OFDM technique as the worst case after pre-testing in conducted emission test site.
5. Two test results were presented in the following sections. The test result A was for DSSS technique and the test result B was for OFDM technique.

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a Wireless G Router. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4- 2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP05L	20838027664	E2K24CLNS
2	NOTEBOOK COMPUTER	DELL	PP05L	12130898320	E2K24CLNS
3	PRINTER	EPSON	LQ-300+	DCGY047265	FCC DoC Approved
4	MODEM	ACEEX	1414V/3	0401008248	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA
3	1.2m shielded cable without core.
4	1.2m shielded cable without core.

NOTE:

1. All power cords of the above support units are non shielded (1.8m).
2. Item 2 act as a communication partner to transfer data.

3.5 CONFIGURATION OF SYSTEM UNDER TEST



4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100291	Nov. 16, 2005
RF signal cable Woken	5D-FB	Cable-HYC01-01	Mar. 02, 2005
LISN ROHDE & SCHWARZ	ESH3-Z5	100312	Mar. 03, 2005
LISN ROHDE & SCHWARZ	ESH2-Z5	100104	Mar. 02, 2005
Software ADT	ADT_Cond_V3	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 1.
 3. The VCCI Site Registration No. is C-2040.




4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels (Limit -20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS


- a. Placed the EUT on the testing table.
- b. Prepared another Notebook system to act as communication partner and placed it outside of testing area.
- c. The communication partner run a test program (provided by manufacturer) to enable EUT under transmission/receiving condition continuously at specific channel frequency via an RJ45 cable.
- d. The notebook system sent "H" messages to its screen.
- e. The notebook system sent "H" messages to modem.
- f. The notebook system sent "H" messages to printer, and the printer printed them on paper.
- g. Steps d ~ f were repeated.

4.1.7 TEST RESULTS

EUT	Wireless G Router	MODEL	DI-524
CHANNEL	1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	21 deg. C, 61% RH, 991 hPa	TESTED BY	Long Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.11	47.58	-	47.69	-	64.65	54.65	-16.96	-
2	0.237	0.12	41.38	-	41.50	-	62.19	52.19	-20.69	-
3	0.472	0.13	32.97	-	33.10	-	56.49	46.49	-23.39	-
4	2.589	0.17	41.90	-	42.07	-	56.00	46.00	-13.93	-
5	2.826	0.18	37.95	-	38.13	-	56.00	46.00	-17.87	-
6	22.144	1.08	30.19	-	31.27	-	60.00	50.00	-28.73	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless G Router	MODEL	DI-524
CHANNEL	1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	21 deg. C, 61% RH, 991 hPa	TESTED BY	Long Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.11	45.25	-	45.36	-	64.64	54.64	-19.29	-
2	0.236	0.11	38.43	-	38.54	-	62.24	52.24	-23.70	-
3	1.711	0.16	32.83	-	32.99	-	56.00	46.00	-23.01	-
4	2.535	0.17	41.54	-	41.71	-	56.00	46.00	-14.29	-
5	5.305	0.23	20.66	-	20.89	-	60.00	50.00	-39.11	-
6	22.156	0.69	20.74	-	21.43	-	60.00	50.00	-38.57	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless G Router	MODEL	DI-524
CHANNEL	6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	21 deg. C, 61% RH, 991 hPa	TESTED BY	Long Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.11	47.60	-	47.71	-	64.61	54.61	-16.90	-
2	0.237	0.12	40.82	-	40.94	-	62.21	52.21	-21.27	-
3	0.473	0.13	32.89	-	33.02	-	56.47	46.47	-23.45	-
4	1.953	0.16	34.74	-	34.90	-	56.00	46.00	-21.10	-
5	2.545	0.17	42.04	-	42.21	-	56.00	46.00	-13.79	-
6	22.456	1.09	29.70	-	30.79	-	60.00	50.00	-29.21	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless G Router	MODEL	DI-524
CHANNEL	6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	21 deg. C, 61% RH, 991 hPa	TESTED BY	Long Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.179	0.11	45.27	-	45.38	-	64.55	54.55	-19.18	-
2	0.474	0.12	30.04	-	30.16	-	56.44	46.44	-26.28	-
3	1.898	0.16	33.57	-	33.73	-	56.00	46.00	-22.27	-
4	2.547	0.17	42.32	-	42.49	-	56.00	46.00	-13.51	-
5	6.874	0.27	24.39	-	24.66	-	60.00	50.00	-35.34	-
6	21.926	0.69	32.67	-	33.36	-	60.00	50.00	-26.64	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless G Router	MODEL	DI-524
CHANNEL	11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	21 deg. C, 61% RH, 991 hPa	TESTED BY	Long Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.179	0.11	47.24	-	47.35	-	64.55	54.55	-17.20	-
2	0.356	0.13	36.11	-	36.24	-	58.81	48.81	-22.58	-
3	1.721	0.16	34.12	-	34.28	-	56.00	46.00	-21.72	-
4	2.613	0.17	41.05	-	41.22	-	56.00	46.00	-14.78	-
5	14.030	0.69	16.41	-	17.10	-	60.00	50.00	-42.90	-
6	23.573	1.12	31.09	-	32.21	-	60.00	50.00	-27.79	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless G Router	MODEL	DI-524
CHANNEL	11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	PHASE	Netural (N)
ENVIRONMENTAL CONDITIONS	21 deg. C, 61% RH, 991 hPa	TESTED BY	Long Chen

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.11	44.27	-	44.38	-	64.61	54.61	-20.23	-
2	0.357	0.12	29.12	-	29.24	-	58.80	48.80	-29.56	-
3	1.723	0.16	33.58	-	33.74	-	56.00	46.00	-22.26	-
4	2.555	0.17	42.22	-	42.39	-	56.00	46.00	-13.61	-
5	18.306	0.69	27.40	-	28.09	-	60.00	50.00	-31.91	-
6	24.534	0.67	29.98	-	30.65	-	60.00	50.00	-29.35	-

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESIB7	100188	Dec. 19, 2005
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Nov. 21, 2005
BILOG Antenna SCHWARZBECK	VULB9168	9168-157	Feb. 03, 2005
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-407	Feb. 03, 2005
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA 9170241	Feb. 23, 2005
Preamplifier Agilent	8449B	3008A01961	Nov. 09, 2005
Preamplifier Agilent	8447D	2944A10629	Nov. 09, 2005
RF signal cable HUBER+SUHNER	SUCOFLEX 104	218182/4	Mar. 04, 2005
RF signal cable HUBER+SUHNER	SUCOFLEX 104	218194/4	Mar. 04, 2005
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower ADT.	AT100	AT93021702	NA
Turn Table ADT.	TT100.	TT93021702	NA
Controller ADT.	SC100.	SC93021702	NA

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 1.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The IC Site Registration No. is IC4924-2.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

EUT	Wireless G Router	MODEL	DI-524
CHANNEL	11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120 Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25 deg. C, 61% RH, 991 hPa	TESTED BY	Long Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	249.66	42.74 QP	46.00	-3.26	1.00 H	331	29.32	13.41
2	300.20	34.58 QP	46.00	-11.42	1.00 H	262	19.77	14.81
3	319.64	34.37 QP	46.00	-11.63	1.00 H	232	19.15	15.22
4	374.07	34.63 QP	46.00	-11.37	1.00 H	229	18.24	16.39
5	500.42	35.26 QP	46.00	-10.74	1.50 H	67	16.54	18.72
6	640.38	34.69 QP	46.00	-11.31	2.50 H	214	12.89	21.81
7	799.78	37.21 QP	46.00	-8.79	2.00 H	214	13.44	23.77
8	961.12	38.34 QP	54.00	-15.66	1.50 H	163	12.47	25.87

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	199.12	31.48 QP	43.50	-12.02	1.00 V	310	19.95	11.53
2	249.66	37.77 QP	46.00	-8.23	1.00 V	1	24.36	13.41
3	319.64	32.67 QP	46.00	-13.33	1.50 V	343	17.45	15.22
4	348.80	31.37 QP	46.00	-14.63	1.50 V	352	15.54	15.83
5	449.88	30.86 QP	46.00	-15.14	1.00 V	349	12.75	18.11
6	479.04	35.16 QP	46.00	-10.84	1.00 V	310	16.70	18.46
7	640.38	33.31 QP	46.00	-12.69	1.50 V	307	11.51	21.81
8	799.78	37.18 QP	46.00	-8.82	1.00 V	7	13.41	23.77

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

4.2.8 TEST RESULTS (A)

EUT	Wireless G Router	MODEL	DI-524
CHANNEL	1	FREQUENCY RANGE	1~25 GHz
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1120.00	50.01 PK	74.00	-23.99	1.19 H	313	23.25	26.76
1	1120.00	48.09 AV	54.00	-5.91	1.19 H	313	21.33	26.76
2	2360.00	51.60 PK	74.00	-22.40	1.00 H	305	19.89	31.71
2	2360.00	43.34 AV	54.00	-10.66	1.00 H	305	11.63	31.71
3	2390.00	52.39 PK	74.00	-21.61	1.00 H	314	20.59	31.80
3	2390.00	44.65 AV	54.00	-9.35	1.00 H	314	12.85	31.80
4	*2412.00	108.15 PK			1.00 H	314	76.28	31.87
4	*2412.00	100.04 AV			1.00 H	314	68.17	31.87
5	4824.00	60.59 PK	74.00	-13.41	1.00 H	149	22.48	38.11
5	4824.00	48.91 AV	54.00	-5.09	1.00 H	149	10.80	38.11

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1600.00	50.06 PK	74.00	-23.94	1.11 V	340	21.43	28.63
1	1600.00	47.55 AV	54.00	-6.45	1.11 V	340	18.92	28.63
2	1920.00	49.90 PK	74.00	-24.10	1.22 V	336	19.75	30.15
2	1920.00	46.97 AV	54.00	-7.03	1.22 V	336	16.82	30.15
3	2360.00	53.02 PK	74.00	-20.98	1.08 V	250	21.31	31.71
3	2360.00	44.82 AV	54.00	-9.18	1.08 V	250	13.11	31.71
4	2390.00	55.71 PK	74.00	-18.29	1.08 V	193	23.91	31.80
4	2390.00	46.00 AV	54.00	-8.00	1.08 V	193	14.20	31.80
5	*2412.00	111.10 PK			1.08 V	193	79.23	31.87
5	*2412.00	103.43 AV			1.08 V	193	71.56	31.87
6	4824.00	63.21 PK	74.00	-10.79	1.06 V	309	25.10	38.11
6	4824.00	51.34 AV	54.00	-2.66	1.06 V	309	13.23	38.11

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	Wireless G Router	MODEL	DI-524
CHANNEL	6	FREQUENCY RANGE	1~25 GHz
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1120.00	48.62 PK	74.00	-25.38	1.18 H	25	21.86	26.76
1	1120.00	46.75 AV	54.00	-7.25	1.18 H	25	19.99	26.76
2	2360.00	52.97 PK	74.00	-21.03	1.00 H	299	21.26	31.71
2	2360.00	43.93 AV	54.00	-10.07	1.00 H	299	12.22	31.71
3	*2437.00	107.80 PK			1.04 H	185	75.85	31.95
3	*2437.00	99.80 AV			1.04 H	185	67.85	31.95
4	4874.00	60.64 PK	74.00	-13.36	1.00 H	160	22.36	38.28
4	4874.00	48.56 AV	54.00	-5.44	1.00 H	160	10.28	38.28

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1120.00	48.54 PK	74.00	-25.46	1.25 V	334	21.78	26.76
1	1120.00	46.32 AV	54.00	-7.68	1.25 V	334	19.56	26.76
2	1920.00	48.64 PK	74.00	-25.36	1.16 V	7	18.49	30.15
2	1920.00	45.64 AV	54.00	-8.36	1.16 V	7	15.49	30.15
3	2360.00	53.53 PK	74.00	-20.47	1.05 V	277	21.82	31.71
3	2360.00	45.15 AV	54.00	-8.85	1.05 V	277	13.44	31.71
4	*2437.00	112.70 PK			1.08 V	249	80.75	31.95
4	*2437.00	104.80 AV			1.08 V	249	72.85	31.95
5	4874.00	64.17 PK	74.00	-9.83	1.28 V	360	25.89	38.28
5	4874.00	52.43 AV	54.00	-1.57	1.28 V	360	14.15	38.28

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	Wireless G Router	MODEL	DI-524
CHANNEL	11	FREQUENCY RANGE	1~25 GHz
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1120.00	49.88 PK	74.00	-24.12	1.21 H	314	23.12	26.76
1	1120.00	48.28 AV	54.00	-5.72	1.21 H	314	21.52	26.76
2	2360.00	53.07 PK	74.00	-20.93	1.00 H	304	21.36	31.71
2	2360.00	43.77 AV	54.00	-10.23	1.00 H	304	12.06	31.71
3	*2462.00	107.10 PK			1.28 H	58	75.08	32.02
3	*2462.00	99.40 AV			1.28 H	58	67.38	32.02
4	2483.50	50.77 PK	74.00	-23.23	1.28 H	58	18.68	32.09
4	2483.50	43.07 AV	54.00	-10.93	1.28 H	58	10.98	32.09
5	4924.00	56.41 PK	74.00	-17.59	1.08 H	61	17.92	38.49
5	4924.00	43.87 AV	54.00	-10.13	1.08 H	61	5.38	38.49

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1600.00	49.90 PK	74.00	-24.10	1.07 V	313	21.27	28.63
1	1600.00	47.34 AV	54.00	-6.66	1.07 V	313	18.71	28.63
2	1920.00	49.48 PK	74.00	-24.52	1.22 V	8	19.33	30.15
2	1920.00	46.83 AV	54.00	-7.17	1.22 V	8	16.68	30.15
3	2360.00	52.63 PK	74.00	-21.37	1.24 V	360	20.92	31.71
3	2360.00	44.36 AV	54.00	-9.64	1.24 V	360	12.65	31.71
4	*2462.00	112.46 PK			1.04 V	47	80.44	32.02
4	*2462.00	104.62 AV			1.04 V	47	72.60	32.02
5	2483.50	56.13 PK	74.00	-17.87	1.04 V	47	24.04	32.09
5	2483.50	46.49 AV	54.00	-7.51	1.04 V	47	14.40	32.09
6	4924.00	59.86 PK	74.00	-14.14	1.13 V	262	21.37	38.49
6	4924.00	48.34 AV	54.00	-5.66	1.13 V	262	9.85	38.49

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

4.2.9 TEST RESULTS (B)

EUT	Wireless G Router	MODEL	DI-524
CHANNEL	1	FREQUENCY RANGE	1~25 GHz
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1120.00	50.25 PK	74.00	-23.75	1.08 H	250	23.49	26.76
1	1120.00	48.20 AV	54.00	-5.80	1.08 H	250	21.44	26.76
2	2360.00	54.21 PK	74.00	-19.79	1.00 H	305	22.50	31.71
2	2360.00	45.16 AV	54.00	-8.84	1.00 H	305	13.45	31.71
3	2390.00	58.09 PK	74.00	-15.91	1.00 H	315	26.29	31.80
3	2390.00	48.74 AV	54.00	-5.26	1.00 H	315	16.94	31.80
4	*2412.00	104.71 PK			1.00 H	315	72.84	31.87
4	*2412.00	95.36 AV			1.00 H	315	63.49	31.87
5	4824.00	58.84 PK	74.00	-15.16	1.08 H	250	20.73	38.11
5	4824.00	44.19 AV	54.00	-9.81	1.08 H	250	6.08	38.11

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1600.00	50.75 PK	74.00	-23.25	1.00 V	13	22.12	28.63
1	1600.00	48.66 AV	54.00	-5.34	1.00 V	13	20.03	28.63
2	1920.00	48.86 PK	74.00	-25.14	1.21 V	335	18.71	30.15
1	1920.00	45.75 AV	54.00	-8.25	1.21 V	335	15.60	30.15
3	2360.00	54.85 PK	74.00	-19.15	1.13 V	178	23.14	31.71
3	2360.00	47.03 AV	54.00	-6.97	1.13 V	178	15.32	31.71
4	2390.00	62.02 PK	74.00	-11.98	1.16 V	344	30.22	31.80
4	2390.00	52.72 AV	54.00	-1.28	1.16 V	344	20.92	31.80
5	*2412.00	108.64 PK			1.16 V	344	76.77	31.87
5	*2412.00	99.34 AV			1.16 V	344	67.47	31.87
6	4824.00	61.37 PK	74.00	-12.63	1.06 V	43	23.26	38.11
6	4824.00	49.14 AV	54.00	-4.86	1.06 V	43	11.03	38.11

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	Wireless G Router	MODEL	DI-524
CHANNEL	6	FREQUENCY RANGE	1~25 GHz
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1120.00	49.45 PK	74.00	-24.55	1.18 H	24	22.69	26.76
1	1120.00	47.45 AV	54.00	-6.55	1.18 H	24	20.69	26.76
2	2360.00	53.43 PK	74.00	-20.57	1.00 H	296	21.72	31.71
2	2360.00	45.21 AV	54.00	-8.79	1.00 H	296	13.50	31.71
3	*2437.00	104.55 PK			1.25 H	298	72.60	31.95
3	*2437.00	95.12 AV			1.25 H	298	63.17	31.95
4	4874.00	58.99 PK	74.00	-15.01	1.24 H	157	20.71	38.28
4	4874.00	45.94 AV	54.00	-8.06	1.24 H	157	7.66	38.28

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1600.00	50.37 PK	74.00	-23.63	1.08 V	357	21.74	28.63
1	1600.00	48.12 AV	54.00	-5.88	1.08 V	357	19.49	28.63
2	1920.00	48.65 PK	74.00	-25.35	1.15 V	6	18.50	30.15
2	1920.00	45.56 AV	54.00	-8.44	1.15 V	6	15.41	30.15
3	2360.00	54.25 PK	74.00	-19.75	1.06 V	276	22.54	31.71
3	2360.00	46.59 AV	54.00	-7.41	1.06 V	276	14.88	31.71
4	*2437.00	109.72 PK			1.06 V	248	77.77	31.95
4	*2437.00	99.82 AV			1.06 V	248	67.87	31.95
5	2520.00	55.83 PK	74.00	-18.17	1.00 V	246	23.62	32.21
5	2520.00	50.66 AV	54.00	-3.34	1.00 V	246	18.45	32.21
6	4874.00	61.76 PK	74.00	-12.24	1.03 V	37	23.48	38.28
6	4874.00	48.91 AV	54.00	-5.09	1.03 V	37	10.63	38.28

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT	Wireless G Router	MODEL	DI-524
CHANNEL	11	FREQUENCY RANGE	1~25 GHz
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 60% RH, 991 hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1120.00	50.07 PK	74.00	-23.93	1.18 H	313	23.31	26.76
1	1120.00	48.03 AV	54.00	-5.97	1.18 H	313	21.27	26.76
2	2360.00	52.83 PK	74.00	-21.17	1.00 H	306	21.12	31.71
2	2360.00	44.72 AV	54.00	-9.28	1.00 H	306	13.01	31.71
3	*2462.00	103.09 PK			1.01 H	21	71.07	32.02
3	*2462.00	93.75 AV			1.01 H	21	61.73	32.02
4	2483.50	55.39 PK	74.00	-18.61	1.01 H	21	23.30	32.09
4	2483.50	46.05 AV	54.00	-7.95	1.01 H	21	13.96	32.09
5	4924.00	55.04 PK	74.00	-18.96	1.06 H	68	16.55	38.49
5	4924.00	41.62 AV	54.00	-12.38	1.06 H	68	3.13	38.49

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1600.00	51.11 PK	74.00	-22.89	1.01 V	11	22.48	28.63
1	1600.00	48.87 AV	54.00	-5.13	1.01 V	11	20.24	28.63
2	1920.00	49.33 PK	74.00	-24.67	1.21 V	346	19.18	30.15
2	1920.00	46.14 AV	54.00	-7.86	1.21 V	346	15.99	30.15
3	2360.00	53.90 PK	74.00	-20.10	1.28 V	348	22.19	31.71
3	2360.00	45.63 AV	54.00	-8.37	1.28 V	348	13.92	31.71
4	*2462.00	109.77 PK			1.06 V	202	77.75	32.02
4	*2462.00	100.33 AV			1.06 V	202	68.31	32.02
5	2483.50	62.07 PK	74.00	-11.93	1.06 V	202	29.98	32.09
5	2483.50	52.63 AV	54.00	-1.37	1.06 V	202	20.54	32.09
6	4924.00	56.76 PK	74.00	-17.24	1.04 V	334	18.27	38.49
6	4924.00	43.79 AV	54.00	-10.21	1.04 V	334	5.30	38.49

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS (A)


EUT	Wireless G Router	MODEL	DI-524
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 67% RH, 991 hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	9.58	0.5	PASS
6	2437	9.93	0.5	PASS
11	2462	9.86	0.5	PASS


CH1



CH6



CH11




4.3.8 TEST RESULTS (B)


EUT	Wireless G Router	MODEL	DI-524
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 67% RH, 991 hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.59	0.5	PASS
6	2437	16.55	0.5	PASS
11	2462	16.59	0.5	PASS


CH1



CH6



CH11



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005
AGILENT SIGNAL GENERATOR	E8257C	MY43320668	Dec. 06, 2005
TEKTRONIX OSCILLOSCOPE	TDS 1012	C019167	Feb. 01, 2005
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G. was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same reading on oscilloscope. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS (A)

EUT	Wireless G Router	MODEL	DI-524
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 67% RH, 991 hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	56.234	17.50	30	PASS
6	2437	56.494	17.52	30	PASS
11	2462	56.364	17.51	30	PASS

4.4.8 TEST RESULTS (B)

EUT	Wireless G Router	MODEL	DI-524
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 67% RH, 991 hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	40.738	16.10	30	PASS
6	2437	39.811	16.00	30	PASS
11	2462	35.481	15.50	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITIONS


Same as 4.3.6

4.5.7 TEST RESULTS (A)


EUT	Wireless G Router	MODEL	DI-524
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 67% RH, 991 hPa
TESTED BY	Leo Hung		

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-9.01	8	PASS
6	2437	-9.18	8	PASS
11	2462	-9.01	8	PASS


CH1



CH6



CH11




4.5.8 TEST RESULTS (B)


EUT	Wireless G Router	MODEL	DI-524
INPUT POWER (SYSTEM)	120 Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23 deg. C, 67% RH, 991 hPa
TESTED BY	Leo Hung		

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-16.96	8	PASS
6	2437	-16.72	8	PASS
11	2462	-17.11	8	PASS


CH1



CH6



CH11



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges were measured and recorded.

The spectrum plots (Peak RBW=VBW=100kHz ; Average RBW=1MHz, VBW=10Hz) are attached on the following pages.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.6 TEST RESULTS

The spectrum plots are attached on the following 12 images. D2 line indicates the highest level, and D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(d).

4.6.7 TEST RESULTS (A)

NOTE:

The band edge emission plot of DSSS technique on page 51 shows 56.03dB between carrier maximum power and local maximum emission in restrict band (2.3600GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.8 is 111.10dBuV/m (Peak), so the maximum field strength in restrict band is $111.10 - 56.03 = 55.07$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of DSSS technique on page 51 shows 57.86dB between carrier maximum power and local maximum emission in restrict band (2.3601GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.8 is 103.43dBuV/m (Average), so the maximum field strength in restrict band is $103.43 - 57.86 = 45.57$ dBuV/m which is under 54dBuV/m limit.

The band edge emission plot of DSSS technique on page 52 shows 56.22dB between carrier maximum power and local maximum emission in restrict band (2.4875GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.8 is 112.46dBuV/m (Peak), so the maximum field strength in restrict band is $112.46 - 56.22 = 56.24$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of DSSS technique on page 53 shows 58.56dB between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.8 is 104.62dBuV/m (Average), so the maximum field strength in restrict band is $104.62 - 58.56 = 46.06$ dBuV/m which is under 54dBuV/m limit.

4.6.8 TEST RESULTS(B)



NOTE:



The band edge emission plot of OFDM technique on page 54 shows 41.90dB between carrier maximum power and local maximum emission in restrict band (2.3890GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.9 is 108.64dBuV/m (Peak), so the maximum field strength in restrict band is $108.64 - 41.90 = 66.74$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot of OFDM technique on page 54 shows 49.05dB between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.9 is 99.34dBuV/m (Average), so the maximum field strength in restrict band is $99.34 - 49.05 = 50.29$ dBuV/m which is under 54dBuV/m limit.



The band edge emission plot of OFDM technique on page 55 shows 43.03dB between carrier maximum power and local maximum emission in restrict band (2.4837GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.9 is 109.77dBuV/m (Peak), so the maximum field strength in restrict band is $109.77 - 43.03 = 66.74$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot of OFDM technique on page 56 shows 48.99dB between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.9 is 100.33dBuV/m (Average), so the maximum field strength in restrict band is $100.33 - 48.99 = 51.34$ dBuV/m which is under 54dBuV/m limit.



DSSS mode:





OFDM mode:







4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION



The antenna used in this product is Dipole antenna with RSMA connector. And the maximum Gain of this antenna is 2dBi.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST



RADIATED EMISSION TEST



6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025:

USA	FCC, NVLAP, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Linko RF Lab.

Tel: 886-3-3270910

Fax: 886-3-3270892

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.