FCC TEST REPORT

REPORT NO.: RF940705L11
MODEL NO.: DI-524
RECEIVED: Jul. 05, 2005
TESTED: Jul. 05 ~ 13, 2005
ISSUED: Jul. 20, 2005

APPLICANT: D-Link Corporation

ADDRESS: No.8, Li-Hsin VII Road Science Based Industrial Park Hsin-Chu,Taiwan

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 62 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.

0528
ILAC MRA

No. 2177-01

TABLE OF CONTENTS

1. CERTIFICATION....4
2. SUMMARY OF TEST RESULTS....5
2.1 MEASUREMENT UNCERTAINTY....5
3. GENERAL INFORMATION....6
3.1 GENERAL DESCRIPTION OF EUT....6
3.2 DESCRIPTION OF TEST MODES....7
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST....7
3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL....8
3.2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS....10
3.2.4 DESCRIPTION OF SUPPORT UNITS....10
4. TEST TYPES AND RESULTS....11
4.1 CONDUCTED EMISSION MEASUREMENT....11
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT....11
4.1.2 TEST INSTRUMENTS....11
4.1.3 TEST PROCEDURES....12
4.1.4 DEVIATION FROM TEST STANDARD....12
4.1.5 TEST SETUP....13
4.1.6 EUT OPERATING CONDITIONS....13
4.1.7 TEST RESULTS....13
4.2 RADIATED EMISSION MEASUREMENT....20
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT....20
4.2.2 TEST INSTRUMENTS....21
4.2.3 TEST PROCEDURES....22
4.2.4 DEVIATION FROM TEST STANDARD....23
4.2.5 TEST SETUP....23
4.2.6 EUT OPERATING CONDITIONS....23
4.2.7 TEST RESULTS....24
4.3 6dB BANDWIDTH MEASUREMENT....31
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT....31
4.3.2 TEST INSTRUMENTS....31
4.3.3 TEST PROCEDURE....32
4.3.4 DEVIATION FROM TEST STANDARD....32
4.3.5 TEST SETUP....32
4.3.6 EUT OPERATING CONDITIONS....32
4.3.7 TEST RESULTS....33
4.4 MAXIMUM PEAK OUTPUT POWER....39
4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT....39

4.4.2 INSTRUMENTS 39
4.4.3 TEST PROCEDURES 40
4.4.4 DEVIATION FROM TEST STANDARD 40
4.4.5 TEST SETUP 40
4.4.6 EUT OPERATING CONDITIONS 40
4.4.7 TEST RESULTS 41
4.5 POWER SPECTRAL DENSITY MEASUREMENT 42
4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT 42
4.5.2 TEST INSTRUMENTS 42
4.5.3 TEST PROCEDURE 43
4.5.4 DEVIATION FROM TEST STANDARD 43
4.5.5 TEST SETUP 43
4.5.6 EUT OPERATING CONDITION 43
4.5.7 TEST RESULTS 44
4.6 BAND EDGES MEASUREMENT 50
4.6.1 LIMITS OF BAND EDGES MEASUREMENT 50
4.6.2 TEST INSTRUMENTS 50
4.6.3 TEST PROCEDURE 50
4.6.4 DEVIATION FROM TEST STANDARD 50
4.6.5 EUT OPERATING CONDITION 50
4.6.6 TEST RESULTS 51
4.7 ANTENNA REQUIREMENT 59
4.7.1 STANDARD APPLICABLE 59
4.7.2 ANTENNA CONNECTED CONSTRUCTION 59
5. PHOTOGRAPHS OF THE TEST CONFIGURATION 60
6. INFORMATION ON THE TESTING LABORATORIES 62

1. CERTIFICATION

PRODUCT: AirPlus G™ 802.11g/2.4GHz Wirless Router
MODEL: DI-524
BRAND: D-Link
APPLICANT: D-Link Corporation
TESTED: Jul. 05 ~ 13, 2005
TEST SAMPLE: ENGINEERING SAMPLE
STANDARDS: FCC Part 15, Subpart C (Section 15.247), ANSI C63.4-2003

The above equipment have been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Wendy Liao , **DATE:** Jul. 20, 2005
Wendy Liao

TECHNICAL ACCEPTANCE : Gary Chang , **DATE:** Jul. 20, 2005
Responsible for RF
Gary Chang

APPROVED BY : Gary Chang for , **DATE:** Jul. 20, 2005
Cody Chang / Deputy Manager

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**REMARK**
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is –16.57dB at 0.177MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is –2.02dB at 76.65MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz ~ 30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.73 dB
	200MHz ~1000MHz	3.74 dB
	1GHz ~ 18GHz	2.20 dB
	18GHz ~ 40GHz	1.88 dB

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	AirPlus G™ 802.11g/2.4GHz Wirless Router
MODEL NO.	DI-524
POWER SUPPLY	5Vdc from AC adapter
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
RADIO TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	51.523mW
ANTENNA TYPE	Dipole antenna with 2.0dBi gain Printed antenna with 0dBi gain
DATA CABLE	NA
I/O PORTS	RJ45
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT was tested with the following adapter:

BRAND:	D-Link
MODEL:	JTA0302B
INPUT:	100 ~ 120Vac, 0.5A, 50 ~ 60Hz
OUTPUT:	5Vdc, 2.5A
POWER LINE:	1.8m non-shielded cable without core

2. The EUT, operates in the 2.4GHz frequency range, lets you connect IEEE 802.11g or IEEE 802.11b devices to the network. With its high-speed data transmissions of up to 54Mbps.
3. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	PLC	RE<1G	RE≥1G	APCM	
-	√	√	√	√	NA

Where **PLC:** Power Line Conducted Emission **RE<1G:** Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz **APCM:** Antenna Port Conducted Measurement

POWER LINE CONDUCTED EMISSION TEST:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

RADIATED EMISSION TEST (BELOW 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	11	OFDM	BPSK	6

RADIATED EMISSION TEST (ABOVE 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

BANDEDGE MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 11	DSSS	CCK	11
802.11g	1 to 11	1, 11	OFDM	BPSK	6

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

3.2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a AirPlus GTM 802.11g/2.4GHz Wirless Router. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4- 2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP05L	12130898320	E2K24CLNS
2	PRINTER	EPSON	LQ-300+	DCGY047265	FCC DoC Approved
3	MODEM	ACEEX	1414V/3	0401008248	IFAXDM1414
4	NOTEBOOK COMPUTER	DELL	PP05L	20838027664	E2K24CLNS

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m Shielded cable.
3.	1.2m Shielded cable.
4.	NA

NOTE: 1. All power cords of the above support units are non shielded (1.8m).

2. Item 4 act as a communication partner to transfer data.

4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

NOTE:
1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100291	Nov. 16, 2005
RF signal cable Woken	5D-FB	Cable-HYC01-01	Jan. 09, 2006
LISN SCHWARZBECK	NNBL 8226-2	8226-142	May. 02, 2006
LISN ROHDE & SCHWARZ	ESH2-Z5	100104	Feb. 15, 2006
Software ADT	ADT_Cond_V3	NA	NA

NOTE:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Shielded Room 1.
3. The VCCI Site Registration No. is C-2040.

4.1.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

a. Connected the EUT to a notebook system via RJ45 cable and placed on a testing table.
b. The notebook system ran a test program (provided by manufacturer) to enable EUT under transmission/receiving condition continuously at specific channel frequency.
c. The notebook system sent "H" messages to its screen.
d. The notebook system sent “H” messages to modem.
e. The notebook system sent "H" messages to printer, and the printer printed them on paper.
f. Steps c ~ e were repeated.

4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA

EUT	AirPlus G™ 802.11g/2.4GHz Wirless Router	MEASUREMENT DETAIL	
MODEL	DI-524	PHASE	Line 1
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	William Chien		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.11	45.51	-	45.62	-	64.61	54.61	-18.99	-
2	0.357	0.11	31.06	-	31.17	-	58.80	48.80	-27.63	-
3	2.063	0.26	36.17	-	36.43	-	56.00	46.00	-19.57	-
4	2.941	0.32	34.80	-	35.12	-	56.00	46.00	-20.88	-
5	16.230	0.67	35.05	-	35.72	-	60.00	50.00	-24.28	-
6	21.910	1.15	38.36	-	39.51	-	60.00	50.00	-20.49	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	AirPlus G^{TM} 802.11g/2.4GHz Wirless Router	MEASUREMENT DETAIL	
MODEL	DI-524	PHASE	Line 2
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	William Chien		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	**0.177**	**0.11**	**47.93**	**-**	**48.04**	**-**	**64.61**	**54.61**	**-16.57**	**-**
2	0.236	0.11	41.57	-	41.68	-	62.24	52.24	-20.56	-
3	0.470	0.13	38.97	-	39.10	-	56.51	46.51	-17.41	-
4	2.293	0.28	36.40	-	36.68	-	56.00	46.00	-19.32	-
5	2.941	0.32	37.18	-	37.50	-	56.00	46.00	-18.50	-
6	21.664	0.77	40.85	-	41.62	-	60.00	50.00	-18.38	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	AirPlus G^{TM} 802.11g/2.4GHz Wirless Router	MEASUREMENT DETAIL	
MODEL	DI-524	PHASE	Line 1
CHANNEL	Channel 6	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	William Chien		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.11	45.43	-	45.54	-	64.61	54.61	-19.07	-
2	0.236	0.11	38.27	-	38.38	-	62.24	52.24	-23.86	-
3	0.474	0.13	34.63	-	34.76	-	56.44	46.44	-21.68	-
4	2.063	0.26	36.13	-	36.39	-	56.00	46.00	-19.61	-
5	2.949	0.32	36.86	-	37.18	-	56.00	46.00	-18.82	-
6	21.664	1.14	40.34	-	41.48	-	60.00	50.00	-18.52	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	AirPlus G™ 802.11g/2.4GHz Wirless Router	MEASUREMENT DETAIL	
MODEL	DI-524	PHASE	Line 2
CHANNEL	Channel 6	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	William Chien		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.11	45.16	-	45.27	-	64.79	54.79	-19.53	-
2	0.470	0.13	38.25	-	38.38	-	56.51	46.51	-18.13	-
3	2.066	0.26	36.89	-	37.15	-	56.00	46.00	-18.85	-
4	2.895	0.32	37.70	-	38.02	-	56.00	46.00	-17.98	-
5	16.230	0.52	35.62	-	36.14	-	60.00	50.00	-23.86	-
6	21.668	0.77	38.95	-	39.72	-	60.00	50.00	-20.28	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	AirPlus G^{TM} 802.11g/2.4GHz Wirless Router	MEASUREMENT DETAIL	
MODEL	DI-524	PHASE	Line 1
CHANNEL	Channel 11	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	William Chien		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.11	45.41	-	45.52	-	64.61	54.61	-19.09	-
2	0.236	0.11	38.41	-	38.52	-	62.24	52.24	-23.72	-
3	0.470	0.13	35.31	-	35.44	-	56.51	46.51	-21.07	-
4	2.125	0.27	36.46	-	36.73	-	56.00	46.00	-19.27	-
5	10.793	0.54	33.29	-	33.83	-	60.00	50.00	-26.17	-
6	21.664	1.14	40.52	-	41.66	-	60.00	50.00	-18.34	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	AirPlus G™ 802.11g/2.4GHz Wirless Router	MEASUREMENT DETAIL	
MODEL	DI-524	PHASE	Line 2
CHANNEL	Channel 11	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	William Chien		

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.11	47.91	-	48.02	-	64.61	54.61	-16.59	-
2	0.353	0.11	36.51	-	36.62	-	58.89	48.89	-22.27	-
3	0.470	0.13	38.65	-	38.78	-	56.51	46.51	-17.73	-
4	2.125	0.27	37.20	-	37.47	-	56.00	46.00	-18.53	-
5	2.949	0.32	37.24	-	37.56	-	56.00	46.00	-18.44	-
6	21.664	0.77	40.57	-	41.34	-	60.00	50.00	-18.66	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESI7	838496/016	Jan. 07, 2006
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100041	Nov. 29, 2005
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Jan. 22, 2006
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-404	Jan. 05, 2006
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA 9170242	Jan. 23, 2006
Preamplifier Agilent	8447D	2944A10631	Nov. 17, 2005
Preamplifier Agilent	8449B	3008A01960	Nov. 14, 2005
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	219272/4	Jan. 26, 2006
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	219275/4	Jan. 26, 2006
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA
Antenna Tower Controller inn-co GmbH	CO2000	019303	NA
Turn Table ADT.	TT100.	TT93021704	NA
Turn Table Controller ADT.	SC100.	SC93021704	NA

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 3.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The IC Site Registration No. is IC4924-4.

4.2.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak method or average method as specified and then reported in data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

RADIATED WORST-CASE DATA: BELOW 1GHz

EUT	AirPlus G^{TM} 802.11g/2.4GHz Wirless Router	**MEASUREMENT DETAIL**	
MODEL	DI-524	**FREQUENCY RANGE**	Below 1000MHz
CHANNEL	Channel 11	**DETECTOR FUNCTION**	Quasi-Peak
MODULATION TYPE	BPSK	**ENVIRONMENTAL CONDITIONS**	25deg. C, 64%RH, 991hPa
TRANSFER RATE	6Mbps	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Match Tsui		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	84.43	29.12 QP	40.00	-10.88	2.00 H	235	19.15	9.97
2	185.51	34.71 QP	43.50	-8.79	1.00 H	61	22.26	12.45
3	218.56	38.65 QP	46.00	-7.35	1.00 H	61	26.97	11.69
4	249.66	37.32 QP	46.00	-8.68	2.00 H	163	24.22	13.11
5	274.93	33.64 QP	46.00	-12.36	1.00 H	298	19.76	13.88
6	300.20	31.93 QP	46.00	-14.07	1.00 H	127	17.51	14.41
7	348.80	31.39 QP	46.00	-14.61	1.00 H	274	15.89	15.49

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	37.78	37.58 QP	40.00	-2.42	1.00 V	196	22.62	14.96
2	**76.65**	**37.98 QP**	**40.00**	**-2.02**	**1.00 V**	**349**	**27.24**	**10.74**
3	107.76	34.96 QP	43.50	-8.54	1.25 V	181	23.30	11.67
4	166.07	33.66 QP	43.50	-9.84	1.25 V	217	19.34	14.32
5	232.16	32.31 QP	46.00	-13.69	1.00 V	205	19.84	12.48
6	249.66	42.12 QP	46.00	-3.88	1.00 V	199	29.02	13.11
7	274.93	31.18 QP	46.00	-14.82	1.50 V	181	17.30	13.88
8	300.20	32.92 QP	46.00	-13.08	1.00 V	91	18.50	14.41
9	368.24	29.38 QP	46.00	-16.62	1.25 V	139	13.41	15.96
10	698.70	28.96 QP	46.00	-17.04	1.75 V	73	6.97	22.00

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

802.11b DSSS MODULATION

EUT	AirPlus G™ 802.11g/2.4GHz Wirless Router	MEASUREMENT DETAIL	
MODEL	DI-524	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 1	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	CCK	ENVIRONMENTAL CONDITIONS	24deg. C, 63%RH, 991hPa
TRANSFER RATE	11Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	44.07 PK	74.00	-29.93	1.03 H	247	14.71	29.36
2	2390.00	43.71 PK	74.00	-30.29	1.46 H	50	11.84	31.87
3	*2412.00	104.05 PK			1.46 H	50	72.09	31.96
3	*2412.00	96.52 AV			1.46 H	50	64.56	31.96
4	3216.00	47.69 PK	74.00	-26.31	1.11 H	134	13.73	33.96
5	4824.00	51.27 PK	74.00	-22.73	1.03 H	245	13.44	37.83
5	4824.00	44.32 AV	54.00	-9.68	1.03 H	245	6.49	37.83

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	43.12 PK	74.00	-30.88	1.25 V	212	13.76	29.36
1	1608.00	35.56 AV	54.00	-18.44	1.25 V	212	6.20	29.36
2	2390.00	52.84 PK	74.00	-21.16	1.01 V	212	20.97	31.87
2	2390.00	45.53 AV	54.00	-8.47	1.01 V	212	13.66	31.87
3	*2412.00	113.18 PK			1.01 V	212	81.22	31.96
3	*2412.00	105.87 AV			1.01 V	212	73.91	31.96
4	3216.00	48.78 PK	74.00	-25.22	1.00 V	218	14.81	33.96
4	3216.00	39.04 AV	54.00	-14.96	1.00 V	218	5.07	33.96
5	4824.00	53.49 PK	74.00	-20.51	1.11 V	159	15.66	37.83
5	4824.00	46.66 AV	54.00	-7.34	1.11 V	159	8.83	37.83

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

EUT	AirPlus G™ 802.11g/2.4GHz Wirless Router	**MEASUREMENT DETAIL**	
MODEL	DI-524	**FREQUENCY RANGE**	1 ~ 25GHz
CHANNEL	Channel 6	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
MODULATION TYPE	CCK	**ENVIRONMENTAL CONDITIONS**	24deg. C, 63%RH, 991hPa
TRANSFER RATE	11Mbps	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	44.27 PK	74.00	-29.73	1.01 H	249	14.87	29.40
2	*2437.00	103.09 PK			1.46 H	49	71.03	32.06
2	*2437.00	95.39 AV			1.46 H	49	63.33	32.06
3	3248.00	47.93 PK	74.00	-26.07	1.09 H	213	13.94	33.99
4	4874.00	51.37 PK	74.00	-22.63	1.02 H	241	13.39	37.98
4	4874.00	44.50 AV	54.00	-9.50	1.02 H	241	6.52	37.98

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	44.27 PK	74.00	-29.73	1.21 V	235	14.87	29.40
2	*2437.00	113.14 PK			1.03 V	214	81.08	32.06
2	*2437.00	105.67 AV			1.03 V	214	73.61	32.06
3	3248.00	48.61 PK	74.00	-25.39	1.02 V	176	14.62	33.99
4	4874.00	53.31 PK	74.00	-20.69	1.05 V	103	15.33	37.98
4	4874.00	46.27 AV	54.00	-7.73	1.05 V	103	8.29	37.98

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

EUT	AirPlus G™ 802.11g/2.4GHz Wirless Router	**MEASUREMENT DETAIL**	
MODEL	DI-524	**FREQUENCY RANGE**	1 ~ 25GHz
CHANNEL	Channel 11	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
MODULATION TYPE	CCK	**ENVIRONMENTAL CONDITIONS**	24deg. C, 63%RH, 991hPa
TRANSFER RATE	11Mbps	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	44.71 PK	74.00	-29.29	1.05 H	214	15.26	29.45
2	*2462.00	102.40 PK			1.45 H	51	70.24	32.16
2	*2462.00	95.28 AV			1.45 H	51	63.12	32.16
3	2483.50	44.78 PK	74.00	-29.22	1.45 H	51	12.54	32.24
4	3282.00	47.61 PK	74.00	-26.39	1.14 H	77	13.59	34.02
5	4924.00	52.71 PK	74.00	-21.29	1.04 H	253	14.57	38.14
5	4924.00	45.86 AV	54.00	-8.14	1.04 H	253	7.72	38.14

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	44.26 PK	74.00	-29.74	1.07 V	153	14.81	29.45
2	*2462.00	113.82 PK			1.01 V	212	81.66	32.16
2	*2462.00	106.62 AV			1.01 V	212	74.46	32.16
3	2483.50	55.20 PK	74.00	-18.80	1.01 V	212	22.96	32.24
3	2483.50	48.00 AV	54.00	-6.00	1.01 V	212	15.76	32.24
4	3282.00	48.67 PK	74.00	-25.33	1.01 V	258	14.65	34.02
5	4924.00	53.81 PK	74.00	-20.19	1.09 V	72	15.67	38.14
5	4924.00	46.95 AV	54.00	-7.05	1.09 V	72	8.81	38.14

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

802.11g OFDM MODULATION

EUT	AirPlus G™ 802.11g/2.4GHz Wirless Router	MEASUREMENT DETAIL	
MODEL	DI-524	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 1	DETECTOR FUNCTION	Peak (PK) Average (AV)
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	24deg. C, 63%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	41.27 PK	74.00	-32.73	1.22 H	27	11.91	29.36
2	2390.00	49.11 PK	74.00	-24.89	1.40 H	264	17.24	31.87
3	*2412.00	100.08 PK			1.40 H	264	68.12	31.96
3	*2412.00	90.52 AV			1.40 H	264	58.56	31.96
4	3216.00	45.96 PK	74.00	-28.04	1.07 H	253	12.00	33.96
5	4824.00	49.65 PK	74.00	-24.35	1.17 H	235	11.82	37.83

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	43.65 PK	74.00	-30.35	1.24 V	19	14.29	29.36
1	1608.00	34.98 AV	54.00	-19.02	1.24 V	19	5.62	29.36
2	2390.00	58.24 PK	74.00	-15.76	1.30 V	216	26.37	31.87
2	2390.00	49.15 AV	54.00	-4.85	1.30 V	216	17.28	31.87
3	*2412.00	109.21 PK			1.30 V	216	77.25	31.96
3	*2412.00	100.12 AV			1.30 V	216	68.16	31.96
4	3216.00	46.71 PK	74.00	-27.29	1.02 V	325	12.75	33.96
4	3216.00	37.13 AV	54.00	-16.87	1.02 V	325	3.17	33.96
5	4824.00	51.35 PK	74.00	-22.65	1.09 V	155	13.52	37.83
5	4824.00	38.68 AV	54.00	-15.32	1.09 V	155	0.85	37.83

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

EUT	AirPlus G^{TM} 802.11g/2.4GHz Wirless Router	**MEASUREMENT DETAIL**	
MODEL	DI-524	**FREQUENCY RANGE**	1 ~ 25GHz
CHANNEL	Channel 6	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
MODULATION TYPE	BPSK	**ENVIRONMENTAL CONDITIONS**	24deg. C, 63%RH, 991hPa
TRANSFER RATE	6Mbps	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	42.21 PK	74.00	-31.79	1.24 H	167	12.81	29.40
2	*2437.00	100.48 PK			1.36 H	263	68.42	32.06
2	*2437.00	90.29 AV			1.36 H	263	58.23	32.06
3	3248.00	46.61 PK	74.00	-27.39	1.10 H	195	12.62	33.99
4	4874.00	49.92 PK	74.00	-24.08	1.12 H	217	11.94	37.98

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	43.87 PK	74.00	-30.13	1.21 V	259	14.47	29.40
2	*2437.00	109.57 PK			1.26 V	212	77.51	32.06
2	*2437.00	99.61 AV			1.26 V	212	67.55	32.06
3	3248.00	46.29 PK	74.00	-27.71	1.03 V	295	12.30	33.99
4	4874.00	51.76 PK	74.00	-22.24	1.21 V	210	13.78	37.98
4	4874.00	38.84 AV	54.00	-15.16	1.21 V	210	0.86	37.98

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

EUT	AirPlus G™ 802.11g/2.4GHz Wirless Router	**MEASUREMENT DETAIL**	
MODEL	DI-524	**FREQUENCY RANGE**	1 ~ 25GHz
CHANNEL	Channel 11	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
MODULATION TYPE	BPSK	**ENVIRONMENTAL CONDITIONS**	24deg. C, 63%RH, 991hPa
TRANSFER RATE	6Mbps	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Brad Wu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	42.17 PK	74.00	-31.83	1.09 H	225	12.72	29.45
2	*2462.00	99.51 PK			1.36 H	264	67.35	32.16
2	*2462.00	89.53 AV			1.36 H	264	57.37	32.16
3	2483.50	51.12 PK	74.00	-22.88	1.36 H	264	18.88	32.24
3	2483.50	41.14 AV	54.00	-12.86	1.36 H	264	8.90	32.24
4	3282.00	46.89 PK	74.00	-27.11	1.21 H	350	12.87	34.02
5	4924.00	49.78 PK	74.00	-24.22	1.20 H	317	11.64	38.14

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	44.21 PK	74.00	-29.79	1.06 V	253	14.76	29.45
2	*2462.00	110.02 PK			1.23 V	202	77.86	32.16
2	*2462.00	100.20 AV			1.23 V	202	68.04	32.16
3	2483.50	61.63 PK	74.00	-12.37	1.23 V	202	29.39	32.24
3	2483.50	51.81 AV	54.00	-2.19	1.23 V	202	19.57	32.24
4	3282.00	47.68 PK	74.00	-26.32	1.10 V	67	13.66	34.02
5	4924.00	51.67 PK	74.00	-22.33	1.09 V	154	13.53	38.14
5	4924.00	38.72 AV	54.00	-15.28	1.09 V	154	0.58	38.14

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK 30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP

4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b DSSS MODULATION

EUT	AirPlus G™ 802.11g/2.4GHz Wirless Router	**MODEL**	DI-524
MODULATION TYPE	CCK	**TRANSFER RATE**	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	24deg. C, 64%RH, 991hPa
TESTED BY	Brad Wu		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	11.80	0.5	PASS
6	2437	12.12	0.5	PASS
11	2462	12.00	0.5	PASS

CH1


*RBW 100 kHz
*VBW 100 kHz
SWT 5 ms
Delta 2 [T1]
2.24 dB
11.800000000 MHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 1 [T1]
-0.53 dBm
2.406080000 GHz
1 PK
VIEW
D1 5.71 dBm
D2
LVL
F1
F2
Center 2.412 GHz
2 MHz/
Span 20 MHz

CH6


*RBW 100 kHz
*VBW 100 kHz
SWT 5 ms
Delta 2 [T1]
-1.98 dB
12.120000000 MHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 1 [T1]
0.80 dBm
2.431200000 GHz
1 PK
VIEW
D1 5.77 dBm
D2
LVL
F1
F2
Center 2.437 GHz
2 MHz/
Span 20 MHz

CH11


*RBW 100 kHz
*VBW 100 kHz
SWT 5 ms
Delta 2 [T1]
1.80 dB
12.000000000 MHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 1 [T1]
-2.01 dBm
2.456200000 GHz
D1 5.81 dBm
D2
1 PK VIEW
A
LVL
F1
F2
Center 2.462 GHz
2 MHz/
Span 20 MHz

802.11g OFDM MODULATION

EUT	AirPlus G™ 802.11g/2.4GHz Wirless Router	**MODEL**	DI-524
MODULATION TYPE	BPSK	**TRANSFER RATE**	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	24deg. C, 64%RH, 991hPa
TESTED BY	Brad Wu		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.36	0.5	PASS
6	2437	16.40	0.5	PASS
11	2462	16.40	0.5	PASS

CH1


*RBW 100 kHz
*VBW 100 kHz
SWT 5 ms
Delta 2 [T1]
0.91 dB
16.360000000 MHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 1 [T1]
-3.69 dBm
2.403840000 GHz
1 PK
VIEW
D1 1.73 dBm
D2 -4.27 dBm
LVL
F1
F2
Center 2.412 GHz
2 MHz/
Span 20 MHz

CH6


*RBW 100 kHz
*VBW 100 kHz
SWT 5 ms
Delta 2 [T1]
0.15 dB
16.400000000 MHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 1 [T1]
-4.00 dBm
2.428840000 GHz
1 PK
VIEW
D1 2.22 dBm
LVL
F1
F2
Center 2.437 GHz
2 MHz/
Span 20 MHz

CH11


*RBW 100 kHz
*VBW 100 kHz
SWT 5 ms
Delta 2 [T1]
2.24 dB
16.400000000 MHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 1 [T1]
-4.65 dBm
2.453800000 GHz
1 PK
VIEW
A
LVL
D1 1.7 dBm
D2 -4.3 dBm
F1
F2
Center 2.462 GHz
2 MHz/
Span 20 MHz

4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005
AGILENT SIGNAL GENERATOR	E8257C	MY43320668	Dec. 06, 2005
DIGITAL RT OSCILLOSCOPE	TDS1012	C037299	Dec. 07, 2005
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.

2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.

3. Adjusted the power to have the same reading on oscilloscope. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP

4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS

802.11b DSSS MODULATION

EUT	AirPlus G™ 802.11g/2.4GHz Wirless Router	**MODEL**	DI-524
MODULATION TYPE	CCK	**TRANSFER RATE**	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	24deg. C, 64%RH, 991hPa
TESTED BY	Brad Wu		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	51.050	17.08	30	PASS
6	2437	51.286	17.10	30	PASS
11	2462	51.523	17.12	30	PASS

802.11g OFDM MODULATION

EUT	AirPlus G™ 802.11g/2.4GHz Wirless Router	**MODEL**	DI-524
MODULATION TYPE	BPSK	**TRANSFER RATE**	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	24deg. C, 64%RH, 991hPa
TESTED BY	Brad Wu		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	40.272	16.05	30	PASS
6	2437	40.087	16.03	30	PASS
11	2462	40.179	16.04	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP

4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.5.7 TEST RESULTS

802.11b DSSS MODULATION

EUT	AirPlus G™ 802.11g/2.4GHz Wirless Router	**MODEL**	DI-524
MODULATION TYPE	CCK	**TRANSFER RATE**	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	24deg. C, 64%RH, 991hPa
TESTED BY	Brad Wu		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-7.26	8	PASS
6	2437	-7.58	8	PASS
11	2462	-7.35	8	PASS

CH1


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-7.26 dBm
2.412720000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
1 PK VIEW
A
LVL
Center 2.412 GHz
150 kHz/
Span 1.5 MHz

CH6


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-7.58 dBm
2.437720000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
1 PK VIEW
A
LVL
Center 2.437 GHz
150 kHz/
Span 1.5 MHz

CH11


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-7.35 dBm
2.462720000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
1 PK
VIEW
A
LVL
1
10
0
-10
-20
-30
-40
-50
-60
-70
Center 2.462 GHz
150 kHz/
Span 1.5 MHz

802.11g OFDM MODULATION

EUT	AirPlus G™ 802.11g/2.4GHz Wirless Router	**MODEL**	DI-524
MODULATION TYPE	BPSK	**TRANSFER RATE**	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	24deg. C, 64%RH, 991hPa
TESTED BY	Brad Wu		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-10.50	8	PASS
6	2437	-10.61	8	PASS
11	2462	-10.24	8	PASS

CH1


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-10.50 dBm
2.412630000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
1 PK VIEW
A
LVL
Center 2.412 GHz
150 kHz/
Span 1.5 MHz

CH6


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-10.61 dBm
2.437630000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
1 PK VIEW
A
LVL
Center 2.437 GHz
150 kHz/
Span 1.5 MHz

CH11


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-10.24 dBm
2.462015000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
1 PK
VIEW
A
LVL
10
0
-10
-20
-30
-40
-50
-60
-70
1
Center 2.462 GHz
150 kHz/
Span 1.5 MHz

4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW=VBW=100kHz; Average RBW=1MHz, VBW=10Hz) are attached on the following pages.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.6 TEST RESULTS

The spectrum plots are attached on the following 12 images. D2 line indicates the highest level, and D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(d).

802.11b DSSS MODULATION

NOTE 1: The band edge emission plot on page 52 show 50.68dBc delta between carrier maximum power and local maximum emission in restrict band (2.3200GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 113.18dBuV/m (Peak), so the maximum field strength in restrict band is 113.18 – 50.68 = 62.50dBuV/m, which is under 74dBuV/m limit.

The band edge emission plot on page 52 show 58.67dBc delta between carrier maximum power and local maximum emission in restrict band (2.3200GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 105.87dBuV/m (Average), so the maximum field strength in restrict band is 105.87 – 58.67 = 47.20dBuV/m, which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on the page 53 show 52.18dBc delta between carrier maximum power and local maximum emission in restrict band (2.4970GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 113.82dBuV/m (Peak), so the maximum field strength in restrict band is 113.82 – 52.18 = 61.64dBuV/m, which is under 74dBuV/m limit.

The band edge emission plot on the page 54 show 59.48dBc delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 106.62dBuV/m (Average), so the maximum field strength in restrict band is 106.62 – 59.48 = 47.14dBuV/m, which is under 54dBuV/m limit.


*RBW 100 kHz
*VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
5.67 dBm
2.414400000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 2 [T1]
-33.10 dBm
2.397200000 GHz
Marker 3 [T1]
-48.62 dBm
2.390000000 GHz
Marker 4 [T1]
-45.01 dBm
2.320000000 GHz
D1 5.67 dBm
D2 -14.33 dBm
1 PK VIEW
A
LVL
F2
F1
Center 2.3674 GHz
10 MHz/
Span 100 MHz


*RBW 1 MHz
*VBW 10 Hz
SWT 25 s
Marker 1 [T1]
5.43 dBm
2.413400000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 2 [T1]
-33.30 dBm
2.397800000 GHz
Marker 3 [T1]
-55.62 dBm
2.390000000 GHz
Marker 4 [T1]
-53.24 dBm
2.320000000 GHz
D1 5.43 dBm
D2 -14.57 dBm
1 PK VIEW
A
LVL
F2
F1
Center 2.3674 GHz
10 MHz/
Span 100 MHz


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
4.84 dBm
2.377180000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
1 PK
VIEW
D1 5.67 dBm
D2 -14.33 dBm
A
LVL
Start 30 MHz
2.497 GHz/
Stop 25 GHz


*RBW 100 kHz
*VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
5.71 dBm
2.461600000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
1 PK
VIEW
D1 5.71 dBm
D2 -14.29 dBm
Marker 2 [T1]
-50.09 dBm
2.483500000 GHz
Marker 3 [T1]
-46.47 dBm
2.497000000 GHz
Marker 4 [T1]
-50.32 dBm
2.500000000 GHz
A
LVL
F1
F2
Center 2.503 GHz
10 MHz/
Span 100 MHz


*RBW 1 MHz
*VBW 10 Hz
SWT 25 s
Marker 1 [T1]
5.61 dBm
2.463200000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 2 [T1]
-53.87 dBm
2.483500000 GHz
Marker 3 [T1]
-53.87 dBm
2.483500000 GHz
Marker 4 [T1]
-54.34 dBm
2.500000000 GHz
1 PK
VIEW
D1 5.61 dBm
D2 -14.39 dBm
A
LVL
F1
F2
Center 2.5012 GHz
10 MHz/
Span 100 MHz


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
5.16 dBm
2.427120000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
1 PK
VIEW
D1 5.71 dBm
D2 -14.29 dBm
A
LVL
Start 30 MHz
2.497 GHz/
Stop 25 GHz

802.11g OFDM MODULATION

NOTE 1: The band edge emission plot on page 56 show 46.96dBc delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 109.21dBuV/m (Peak), so the maximum field strength in restrict band is 109.21 – 46.96 = 62.25dBuV/m, which is under 74dBuV/m limit.

The band edge emission plot on page 56 show 50.79dBc delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 100.12dBuV/m (Average), so the maximum field strength in restrict band is 100.12 – 50.79 = 49.33dBuV/m, which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on the page 57 show 44.72dBc delta between carrier maximum power and local maximum emission in restrict band (2.4844GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 110.02dBuV/m (Peak), so the maximum field strength in restrict band is 110.02 – 44.72 = 65.30dBuV/m, which is under 74dBuV/m limit.

The band edge emission plot on the page 58 show 48.81dBc delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 100.20dBuV/m (Average), so the maximum field strength in restrict band is 100.20 – 48.81 = 51.39dBuV/m, which is under 54dBuV/m limit.


*RBW 100 kHz
*VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
1.44 dBm
2.410800000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 2 [T1]
-28.46 dBm
2.399000000 GHz
Marker 3 [T1]
-45.52 dBm
2.390000000 GHz
Marker 4 [T1]
-45.52 dBm
2.390000000 GHz
1 PK
VIEW
D1 1.44 dBm
D2 -18.56 dBm
A
LVL
F2
F1
Center 2.371 GHz
10 MHz/
Span 100 MHz


*RBW 1 MHz
*VBW 10 Hz
SWT 25 s
Marker 1 [T1]
0.08 dBm
2.414200000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 2 [T1]
-36.79 dBm
2.400000000 GHz
Marker 3 [T1]
-50.71 dBm
2.390000000 GHz
Marker 4 [T1]
-50.71 dBm
2.390000000 GHz
1 PK
VIEW
D1 0.08 dBm
D2 -19.92 dBm
A
LVL
F2
F1
Center 2.371 GHz
10 MHz/
Span 100 MHz


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
-0.89 dBm
2.377180000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 2 [T1]
-42.52 dBm
20.405520000 GHz
1 PK
VIEW
D1 1.44 dBm
D2 -18.56 dBm
LVL
Start 30 MHz
2.497 GHz/
Stop 25 GHz


*RBW 100 kHz
*VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
1.99 dBm
2.467000000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 2 [T1]
-42.85 dBm
2.483500000 GHz
Marker 3 [T1]
-42.73 dBm
2.484400000 GHz
Marker 4 [T1]
-47.61 dBm
2.500000000 GHz
1 PK
VIEW
D1 1.99 dBm
D2 -18.01 dBm
LVL
F1
F2
Center 2.504 GHz
10 MHz/
Span 100 MHz


*RBW 1 MHz
*VBW 10 Hz
SWT 25 s
Marker 1 [T1]
0.50 dBm
2.464000000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 2 [T1]
-48.31 dBm
2.483500000 GHz
Marker 3 [T1]
-48.31 dBm
2.483500000 GHz
Marker 4 [T1]
-55.15 dBm
2.500000000 GHz
1 PK
VIEW
D1 0.5 dBm
D2 -19.5 dBm
LVL
F1
F2
Center 2.506 GHz
10 MHz/
Span 100 MHz


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
0.80 dBm
2.427120000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 2 [T1]
-42.17 dBm
24.800240000 GHz
1 PK
VIEW
D1 1.99 dBm
D2 -18.01 dBm
LVL
Start 30 MHz
2.497 GHz/
Stop 25 GHz

4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product are Printed antenna and Dipole antenna with Reverse SMA antenna connector. The maximum Gain of the antenna is 2.00dBi.

5. PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST

RADIATED EMISSION TEST





6. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, NVLAP, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3185050

Linko RF Lab.
Tel: 886-3-3270910
Fax: 886-3-3270892

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also