FCC TEST REPORT

REPORT NO.: RF950215L11B
MODEL NO.: DIR-450 (refer to item 3.1 for other models)
RECEIVED: Feb. 16, 2006
TESTED: Feb. 18 ~ Jun. 29, 2006 (for normal mode)
Aug. 31, 2006 (for turbo mode)
ISSUED: Dec. 08, 2006

APPLICANT: D-Link Corporation

ADDRESS: 17595 Mt. Herrmann, Fountain Valley, CA 92708, U.S.A.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No.47, 14th Ling, Chia Pau Tsuen, Linko Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 72 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.

No. 2177-01

0528

Table of Contents

1 CERTIFICATION 4
2 SUMMARY OF TEST RESULTS 5
2.1 MEASUREMENT UNCERTAINTY 5
3 GENERAL INFORMATION 6
3.1 GENERAL DESCRIPTION OF EUT 6
3.2 DESCRIPTION OF TEST MODES 7
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST 7
3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL 8
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS 10
3.4 DESCRIPTION OF SUPPORT UNITS 10
4 TEST TYPES AND RESULTS 11
4.1 CONDUCTED EMISSION MEASUREMENT 11
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 11
4.1.2 TEST INSTRUMENTS 11
4.1.3 TEST PROCEDURES 12
4.1.4 DEVIATION FROM TEST STANDARD 12
4.1.5 TEST SETUP 13
4.1.6 EUT OPERATING CONDITIONS 13
4.1.7 TEST RESULTS 14
4.2 RADIATED EMISSION MEASUREMENT 22
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT 22
4.2.2 TEST INSTRUMENTS 23
4.2.3 TEST PROCEDURES 24
4.2.4 DEVIATION FROM TEST STANDARD 24
4.2.5 TEST SETUP 25
4.2.6 EUT OPERATING CONDITIONS 25
4.2.7 TEST RESULTS 26
4.3 6dB BANDWIDTH MEASUREMENT 35
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT 35
4.3.2 TEST INSTRUMENTS 35
4.3.3 TEST PROCEDURE 36
4.3.4 DEVIATION FROM TEST STANDARD 36
4.3.5 TEST SETUP 36
4.3.6 EUT OPERATING CONDITIONS 36

4.3.7 TEST RESULTS 37
4.4 MAXIMUM PEAK OUTPUT POWER 44
4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT 44
4.4.2 TEST INSTRUMENTS 44
4.4.3 TEST PROCEDURES 45
4.4.4 DEVIATION FROM TEST STANDARD 45
4.4.5 TEST SETUP 45
4.4.6 EUT OPERATING CONDITIONS 45
4.4.7 TEST RESULTS 46
4.5 POWER SPECTRAL DENSITY MEASUREMENT 48
4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT 48
4.5.2 TEST INSTRUMENTS 48
4.5.3 TEST PROCEDURE 49
4.5.4 DEVIATION FROM TEST STANDARD 49
4.5.5 TEST SETUP 49
4.5.6 EUT OPERATING CONDITIONS 49
4.5.7 TEST RESULTS 50
4.6 BAND EDGES MEASUREMENT 57
4.6.1 LIMITS OF BAND EDGES MEASUREMENT 57
4.6.2 TEST INSTRUMENTS 57
4.6.3 TEST PROCEDURE 57
4.6.4 DEVIATION FROM TEST STANDARD 57
4.6.5 EUT OPERATING CONDITION 57
4.6.6 TEST RESULTS 58
4.7 ANTENNA REQUIREMENT 70
4.7.1 STANDARD APPLICABLE 70
4.7.2 ANTENNA CONNECTED CONSTRUCTION 70
5 INFORMATION ON THE TESTING LABORATORIES 71
APPENDIX-A A-1

1 CERTIFICATION

PRODUCT:	802.11g Mini PCI Card
BRAND:	D-Link
MODEL NO.:	DIR-450 (refer to item 3.1 for other models)
APPLICANT:	D-Link Corporation
TESTED:	Feb. 18 ~ Jun. 29, 2006 (for normal mode) Aug. 31, 2006 (for turbo mode)
TEST SAMPLE:	ENGINEERING SAMPLE
STANDARDS:	FCC Part 15, Subpart C (Section 15.247), ANSI C63.4-2003

The above equipment have been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Windy Chou , **DATE:** Dec. 08, 2006
(Windy Chou)

TECHNICAL ACCEPTANCE : Long Chen , **DATE:** Dec. 08, 2006
Responsible for RF
(Long Chen)

APPROVED BY : Gary Chang , **DATE:** Dec. 08, 2006
(Gary Chang / Supervisor)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	**Test Type and Limit**	**Result**	**REMARK**
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is –17.22dB at 0.209MHz.
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit : min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is –1.51dB at 2483.5MHz.
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.64 dB
	200MHz ~1000MHz	3.65 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	802.11g Mini PCI Card
MODEL NO.	DIR-450 (refer to note below for other models)
FCC ID	KA2DIR450A1
POWER SUPPLY	3.3Vdc from host equipment
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps (up to 108Mbps for turbo mode)
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11 for Normal mode / 1 for Turbo mode
MAXIMUM OUTPUT POWER	60.117mW
ANTENNA TYPE	Monopole antenna with 2dBi gain PIFA antenna (receive only)
DATA CABLE	NA
I/O PORTS	NA
ASSOCIATED DEVICES	NA

NOTE:

1. This report combined two reports together, and changing the applicant, model, brand and product name. The two reports no. are RF950215L11 and RF950215L11A.
2. The following models are identical to each other except for their model no. due to marketing requirement.

Brand	Model
D-Link	WLG-1302
	DIR-450
	DIR-451
	DIR-452

3. The EUT complies with IEEE 802.11g standards and backwards compatible with IEEE 802.11b products.
4. The EUT operates in the 2.4GHz frequency spectrum with throughput of up to 108Mbps.
5. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

For 802.11g: One channel is provided to this EUT for turbo mode.

CHANNEL	FREQUENCY
6	2437 MHz

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
-	√	√	√	√	-

Where **PLC:** Power Line Conducted Emission **RE<1G:** Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz **APCM:** Antenna Port Conducted Measurement

Power Line Conducted Emission Test:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11g Turbo	6	6	OFDM	QPSK	12

Radiated Emission Test (Below 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11g Turbo	6	6	OFDM	QPSK	12

Radiated Emission Test (Above 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11g Turbo	6	6	OFDM	QPSK	12

Bandedge Measurement:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 11	DSSS	CCK	11
802.11g	1 to 11	1, 11	OFDM	BPSK	6
802.11g Turbo	6	6	OFDM	QPSK	12

Antenna Port Conducted Measurement:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11g Turbo	6	6	OFDM	QPSK	12

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)
ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	Compaq	N800C	470048-515	FCC DoC Approved

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA

NOTE: All power cords of the above support units are non shielded (1.8m).

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

NOTE:
1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100291	Nov. 11, 2006
RF signal cable Woken	5D-FB	Cable-HYC01-01	Jan. 06, 2007
LISN ROHDE & SCHWARZ	ESH3-Z5	100312	Feb. 15, 2007
LISN ROHDE & SCHWARZ	ESH2-Z5	100104	Feb. 07, 2007
Software ADT	ADT_Cond_V3	NA	NA

NOTE:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Shielded Room 1.
3. The VCCI Site Registration No. is C-2040.

4.1.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under Limit - 20dB was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

a. Connected the EUT into the notebook system and placed on a testing table.
b. The computer system ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
c. The notebook system displayed “H” messages on its screen.
d. Repeated item c.

4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA_NORMAL MODE

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	**PHASE**	Line 1
MODULATION TYPE	BPSK	**6dB BANDWIDTH**	9 kHz
TRANSFER RATE	6Mbps	**ENVIRONMENTAL CONDITIONS**	20deg. C, 60%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**TESTED BY**	Lori Chiu

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.213	0.10	44.06	-	44.16	-	63.11	-	-18.95	-
2	0.388	0.10	32.02	-	32.12	-	58.10	-	-25.98	-
3	0.502	0.12	32.64	-	32.76	-	56.00	-	-23.24	-
4	4.422	0.48	24.19	-	24.67	-	56.00	-	-31.33	-
5	10.250	0.57	29.23	-	29.80	-	60.00	-	-30.20	-
6	15.410	0.76	30.40	-	31.16	-	60.00	-	-28.84	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-":N/A.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	PHASE	Line 2
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	20deg. C, 60%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Lori Chiu

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.216	0.10	43.94	-	44.04	-	62.96	-	-18.92	-
2	0.377	0.10	32.93	-	33.03	-	58.35	-	-25.32	-
3	0.498	0.12	33.24	-	33.36	-	56.04	-	-22.68	-
4	5.371	0.47	24.22	-	24.69	-	60.00	-	-35.31	-
5	10.164	0.47	29.62	-	30.09	-	60.00	-	-29.91	-
6	15.332	0.64	29.59	-	30.23	-	60.00	-	-29.77	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	PHASE	Line 1
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	20deg. C, 60%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Lori Chiu

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.209	0.10	44.08	-	44.18	-	63.26	-	-19.08	-
2	0.392	0.10	31.94	-	32.04	-	58.02	-	-25.98	-
3	0.502	0.12	32.36	-	32.48	-	56.00	-	-23.52	-
4	4.398	0.48	23.17	-	23.65	-	56.00	-	-32.35	-
5	10.563	0.58	29.57	-	30.15	-	60.00	-	-29.85	-
6	15.770	0.79	30.23	-	31.02	-	60.00	-	-28.98	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	PHASE	Line 2
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	20deg. C, 60%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Lori Chiu

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.209	0.10	45.92	-	46.02	-	63.26	53.26	-17.24	-
2	0.388	0.10	34.82	-	34.92	-	58.10	48.10	-23.18	-
3	0.505	0.12	33.69	-	33.81	-	56.00	46.00	-22.19	-
4	5.336	0.47	23.29	-	23.76	-	60.00	50.00	-36.24	-
5	8.855	0.46	28.86	-	29.32	-	60.00	50.00	-30.68	-
6	15.582	0.65	28.91	-	29.56	-	60.00	50.00	-30.44	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	PHASE	Line 1
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	20deg. C, 60%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Lori Chiu

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.205	0.10	41.48	-	41.58	-	63.42	53.42	-21.84	-
2	0.306	0.10	31.64	-	31.74	-	60.07	50.07	-28.33	-
3	0.506	0.12	31.67	-	31.79	-	56.00	46.00	-24.21	-
4	4.141	0.47	24.55	-	25.02	-	56.00	46.00	-30.98	-
5	10.402	0.57	28.84	-	29.41	-	60.00	50.00	-30.59	-
6	16.012	0.81	29.23	-	30.04	-	60.00	50.00	-29.96	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	PHASE	Line 2
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	20deg. C, 60%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Lori Chiu

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	**0.209**	**0.10**	**45.94**	**-**	**46.04**	**-**	**63.26**	**53.26**	**-17.22**	**-**
2	0.306	0.10	33.88	-	33.98	-	60.07	50.07	-26.09	-
3	0.505	0.12	32.48	-	32.60	-	56.00	46.00	-23.40	-
4	5.594	0.47	24.44	-	24.91	-	60.00	50.00	-35.09	-
5	8.785	0.46	28.72	-	29.18	-	60.00	50.00	-30.82	-
6	14.785	0.62	29.34	-	29.96	-	60.00	50.00	-30.04	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



CONDUCTED WORST-CASE DATA_TURBO MODE

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	PHASE	Line 1
MODULATION TYPE	QPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	12Mbps	ENVIRONMENTAL CONDITIONS	20deg. C, 60%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Match Tsui

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.229	0.10	43.41	-	43.51	-	62.50	52.50	-18.99	-
2	0.347	0.10	27.28	-	27.38	-	59.02	49.02	-31.64	-
3	0.473	0.11	22.85	-	22.96	-	56.47	46.47	-33.51	-
4	4.219	0.47	23.00	-	23.47	-	56.00	46.00	-32.53	-
5	10.995	0.59	27.92	-	28.51	-	60.00	50.00	-31.49	-
6	15.631	0.78	30.30	-	31.08	-	60.00	50.00	-28.92	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	PHASE	Line 2
MODULATION TYPE	QPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	12Mbps	ENVIRONMENTAL CONDITIONS	20deg. C, 60%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Match Tsui

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.226	0.10	44.59	-	44.69	-	62.58	52.58	-17.89	-
2	0.397	0.10	34.93	-	35.03	-	57.93	47.93	-22.90	-
3	0.512	0.12	33.24	-	33.36	-	56.00	46.00	-22.64	-
4	5.386	0.47	25.72	-	26.19	-	60.00	50.00	-33.81	-
5	10.175	0.47	30.62	-	31.09	-	60.00	50.00	-28.91	-
6	15.356	0.64	30.24	-	30.88	-	60.00	50.00	-29.12	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESIB7	100188	Dec. 20, 2006
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Nov. 27, 2006
BILOG Antenna SCHWARZBECK	VULB9168	9168-157	Jan. 15, 2007
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-407	Jan. 22, 2007
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170147	Jan. 26, 2007
Preamplifier Agilent	8449B	3008A01961	Oct. 23, 2006
Preamplifier Agilent	8447D	2944A10629	Oct. 27, 2006
RF signal cable HUBER+SUHNER	SUCOFLEX 104	214380/4	Jan. 16, 2007
RF signal cable HUBER+SUHNER	SUCOFLEX 104	219266/4	Jan. 16, 2007
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower ADT.	AT100	AT93021702	NA
Turn Table ADT.	TT100.	TT93021702	NA
Controller ADT.	SC100.	SC93021702	NA

NOTE:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 2.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The IC Site Registration No. is IC4924-2.

4.2.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

RADIATED WORST-CASE DATA: BELOW 1GHz_NORMAL MODE

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	**FREQUENCY RANGE**	Below 1000MHz
MODULATION TYPE	BPSK	**DETECTOR FUNCTION**	Quasi-Peak
TRANSFER RATE	6Mbps	**ENVIRONMENTAL CONDITIONS**	22deg. C, 65%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**TESTED BY**	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	99.98	35.49 QP	43.50	-8.01	1.00 H	247	26.49	8.99
2	131.08	33.11 QP	43.50	-10.39	3.00 H	31	20.84	12.27
3	166.07	39.98 QP	43.50	-3.52	1.00 H	247	26.95	13.03
4	220.50	34.91 QP	46.00	-11.09	1.00 H	70	23.41	11.50
5	232.16	39.70 QP	46.00	-6.30	1.00 H	247	27.82	11.88
6	300.20	34.13 QP	46.00	-11.87	1.00 H	103	18.51	15.62
7	350.74	41.72 QP	46.00	-4.28	1.50 H	70	25.42	16.31
8	366.29	37.26 QP	46.00	-8.74	1.00 H	103	20.44	16.82
9	399.34	33.40 QP	46.00	-12.60	1.00 H	103	15.49	17.92
10	702.59	33.59 QP	46.00	-12.41	2.00 H	196	9.36	24.22

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	99.98	28.58 QP	43.50	-14.92	1.00 V	85	19.58	8.99
2	164.13	30.38 QP	43.50	-13.12	1.00 V	25	17.23	13.15
3	350.74	33.99 QP	46.00	-12.01	1.00 V	343	17.69	16.31
4	397.39	30.82 QP	46.00	-15.18	1.00 V	85	12.97	17.85
5	584.01	32.36 QP	46.00	-13.64	1.00 V	1	10.30	22.06
6	597.62	30.34 QP	46.00	-15.66	1.00 V	136	7.91	22.42
7	663.71	32.57 QP	46.00	-13.43	1.00 V	136	9.23	23.33
8	702.59	33.75 QP	46.00	-12.25	1.00 V	172	9.53	24.22
9	945.57	30.66 QP	46.00	-15.34	1.00 V	136	1.45	29.21

REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

RADIATED WORST-CASE DATA: BELOW 1GHz_TURBO MODE

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	QPSK	DETECTOR FUNCTION	Quasi-Peak
TRANSFER RATE	12Mbps	ENVIRONMENTAL CONDITIONS	27deg. C, 67%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Lori Chiu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	98.04	41.33 QP	43.50	-2.17	1.00 H	178	32.31	9.02
2	133.03	40.57 QP	43.50	-2.93	1.00 H	25	28.04	12.53
3	166.07	41.56 QP	43.50	-1.94	1.00 H	25	28.53	13.03
4	199.12	40.73 QP	43.50	-2.77	1.00 H	25	29.84	10.89
5	232.16	43.50 QP	46.00	-2.50	1.00 H	25	31.61	11.88
6	267.15	44.22 QP	46.00	-1.78	1.00 H	49	30.54	13.68
7	298.26	42.06 QP	46.00	-3.94	1.00 H	25	26.53	15.53
8	331.30	43.47 QP	46.00	-2.53	1.00 H	25	27.44	16.03
9	395.45	35.92 QP	46.00	-10.08	1.00 H	178	18.14	17.79

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	72.77	28.91 QP	40.00	-11.09	1.00 V	220	17.46	11.46
2	99.98	32.29 QP	43.50	-11.21	1.00 V	202	23.30	8.99
3	133.03	34.96 QP	43.50	-8.54	1.00 V	202	22.44	12.53
4	164.13	34.52 QP	43.50	-8.98	1.00 V	94	21.37	13.15
5	199.12	37.08 QP	43.50	-6.42	1.00 V	202	26.19	10.89
6	265.21	33.05 QP	46.00	-12.95	1.00 V	202	19.71	13.34
7	331.30	36.68 QP	46.00	-9.32	1.00 V	202	20.64	16.03

REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

802.11b DSSS MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	DETECTOR FUNCTION	Peak(PK) Average (AV)
TRANSFER RATE	11Mbps	ENVIRONMENTAL CONDITIONS	25deg. C, 70%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2386.00	54.35 PK	74.00	-19.65	1.13 H	7	23.15	31.20
1	2386.00	46.03 AV	54.00	-7.97	1.13 H	7	14.83	31.20
2	*2412.00	101.13 PK			1.13 H	7	69.82	31.31
2	*2412.00	93.49 AV			1.13 H	7	62.18	31.31
3	3216.00	47.99 PK	74.00	-26.01	1.02 H	303	15.04	32.95
3	3216.00	43.80 AV	54.00	-10.20	1.02 H	303	10.85	32.95
4	4824.00	45.19 PK	74.00	-28.81	1.22 H	248	8.19	37.00
4	4824.00	33.85 AV	54.00	-20.15	1.22 H	248	-3.15	37.00

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2386.00	60.59 PK	74.00	-13.41	1.22 V	75	29.39	31.20
1	2386.00	51.63 AV	54.00	-2.37	1.22 V	75	20.43	31.20
2	*2412.00	113.73 PK			1.19 V	134	82.42	31.31
2	*2412.00	105.98 AV			1.19 V	134	74.67	31.31
3	3216.00	47.54 PK	74.00	-26.46	1.28 V	214	14.59	32.95
3	3216.00	43.08 AV	54.00	-10.92	1.28 V	214	10.13	32.95
4	4824.00	46.34 PK	74.00	-27.66	1.03 V	318	9.34	37.00
4	4824.00	36.63 AV	54.00	-17.37	1.03 V	318	-0.37	37.00

REMARKS: 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	**FREQUENCY RANGE**	1 ~ 25GHz
MODULATION TYPE	CCK	**DETECTOR FUNCTION**	Peak(PK) Average (AV)
TRANSFER RATE	11Mbps	**ENVIRONMENTAL CONDITIONS**	22deg. C, 65%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**TESTED BY**	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	100.82 PK			1.11 H	7	69.42	31.40
1	*2437.00	93.15 AV			1.11 H	7	61.75	31.40
2	3249.00	46.51 PK	74.00	-27.49	1.16 H	232	13.52	32.99
2	3249.00	40.61 AV	54.00	-13.39	1.16 H	232	7.62	32.99
3	4874.00	44.87 PK	74.00	-29.13	1.16 H	360	7.73	37.14
3	4874.00	33.70 AV	54.00	-20.30	1.16 H	360	-3.44	37.14

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	113.04 PK			1.17 V	330	81.64	31.40
1	*2437.00	105.12 AV			1.17 V	330	73.72	31.40
2	3249.00	46.44 PK	74.00	-27.56	1.48 V	281	13.45	32.99
2	3249.00	40.71 AV	54.00	-13.29	1.48 V	281	7.72	32.99
3	4874.00	44.98 PK	74.00	-29.02	1.06 V	104	7.84	37.14
3	4874.00	34.64 AV	54.00	-19.36	1.06 V	104	-2.50	37.14

REMARKS: 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	**FREQUENCY RANGE**	1 ~ 25GHz
MODULATION TYPE	CCK	**DETECTOR FUNCTION**	Peak(PK) Average (AV)
TRANSFER RATE	11Mbps	**ENVIRONMENTAL CONDITIONS**	22deg. C, 65%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**TESTED BY**	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	101.71 PK			1.07 H	360	70.21	31.50
1	*2462.00	94.14 AV			1.07 H	360	62.64	31.50
2	2488.00	53.16 PK	74.00	-20.84	1.07 H	360	21.56	31.60
2	2488.00	45.01 AV	54.00	-8.99	1.07 H	360	13.41	31.60
3	3282.00	46.54 PK	74.00	-27.46	1.18 H	16	13.51	33.03
3	3282.00	39.91 AV	54.00	-14.09	1.18 H	16	6.88	33.03
4	4924.00	46.16 PK	74.00	-27.84	1.11 H	136	8.89	37.27
4	4924.00	33.06 AV	54.00	-20.94	1.11 H	136	-4.21	37.27

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	113.10 PK			1.16 V	133	81.60	31.50
1	*2462.00	105.60 AV			1.16 V	133	74.10	31.50
2	2487.00	60.13 PK	74.00	-13.87	1.16 V	132	28.53	31.60
2	2487.00	51.50 AV	54.00	-2.50	1.16 V	132	19.90	31.60
3	3282.00	47.30 PK	74.00	-26.70	1.01 V	277	14.27	33.03
3	3282.00	42.33 AV	54.00	-11.67	1.01 V	277	9.30	33.03
4	4924.00	46.90 PK	74.00	-27.10	1.02 V	10	9.63	37.27
4	4924.00	36.09 AV	54.00	-17.91	1.02 V	10	-1.18	37.27

REMARKS: 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. T other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency.

802.11g OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	DETECTOR FUNCTION	Peak(PK) Average (AV)
TRANSFER RATE	6Mbps	ENVIRONMENTAL CONDITIONS	22deg. C, 65%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.67 PK	74.00	-14.33	1.42 H	312	28.45	31.22
1	2390.00	46.14 AV	54.00	-7.86	1.42 H	312	14.92	31.22
2	*2412.00	100.09 PK			1.42 H	312	68.78	31.31
2	*2412.00	90.74 AV			1.42 H	312	59.43	31.31
3	3216.00	48.42 PK	74.00	-25.58	1.00 H	304	15.47	32.95
3	3216.00	43.90 AV	54.00	-10.10	1.00 H	304	10.95	32.95
4	4824.00	46.49 PK	74.00	-27.51	1.00 H	0	9.49	37.00
4	4824.00	32.53 AV	54.00	-21.47	1.00 H	0	-4.47	37.00

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	69.01 PK	74.00	-4.99	1.14 V	237	37.79	31.22
1	2390.00	52.09 AV	54.00	-1.91	1.14 V	237	20.87	31.22
2	*2412.00	110.04 PK			1.36 V	277	78.73	31.31
2	*2412.00	101.07 AV			1.36 V	277	69.76	31.31
3	3216.00	47.73 PK	74.00	-26.27	1.25 V	208	14.78	32.95
3	3216.00	42.23 AV	54.00	-11.77	1.25 V	208	9.28	32.95
4	4824.00	44.69 PK	74.00	-29.31	1.14 V	0	7.69	37.00
4	4824.00	33.60 AV	54.00	-20.40	1.14 V	0	-3.40	37.00

REMARKS: 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. rgin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	**FREQUENCY RANGE**	1 ~ 25GHz
MODULATION TYPE	BPSK	**DETECTOR FUNCTION**	Peak(PK) Average (AV)
TRANSFER RATE	6Mbps	**ENVIRONMENTAL CONDITIONS**	22deg. C, 65%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**TESTED BY**	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	100.47 PK			1.10 H	360	69.07	31.40
1	*2437.00	90.74 AV			1.10 H	360	59.34	31.40
2	3249.00	45.75 PK	74.00	-28.25	1.39 H	18	12.76	32.99
2	3249.00	39.97 AV	54.00	-14.03	1.39 H	18	6.98	32.99

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	110.51 PK			1.17 V	180	79.11	31.40
1	*2437.00	101.35 AV			1.17 V	180	69.95	31.40
2	3249.00	46.02 PK	74.00	-27.98	1.26 V	315	13.03	32.99
2	3249.00	39.90 AV	54.00	-14.10	1.26 V	315	6.91	32.99

REMARKS: 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	**FREQUENCY RANGE**	1 ~ 25GHz
MODULATION TYPE	BPSK	**DETECTOR FUNCTION**	Peak(PK) Average (AV)
TRANSFER RATE	6Mbps	**ENVIRONMENTAL CONDITIONS**	22deg. C, 65%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**TESTED BY**	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	100.07 PK			1.03 H	360	68.57	31.50
1	*2462.00	90.51 AV			1.03 H	360	59.01	31.50
2	2483.50	58.03 PK	74.00	-15.97	1.06 H	360	26.44	31.59
2	2483.50	45.89 AV	54.00	-8.11	1.06 H	360	14.30	31.59
3	3282.00	45.43 PK	74.00	-28.57	1.16 H	17	12.40	33.03
3	3282.00	39.86 AV	54.00	-14.14	1.16 H	17	6.83	33.03

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	110.03 PK			1.14 V	28	78.53	31.50
1	*2462.00	100.09 AV			1.14 V	28	68.59	31.50
2	2483.50	70.83 PK	74.00	-3.17	1.16 V	30	39.24	31.59
2	**2483.50**	**52.49 AV**	**54.00**	**-1.51**	**1.16 V**	**30**	**20.90**	**31.59**
3	3282.00	46.23 PK	74.00	-27.77	1.06 V	278	13.20	33.03
3	3282.00	41.66 AV	54.00	-12.34	1.06 V	278	8.63	33.03

REMARKS: 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.

802.11g OFDM TURBO MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	QPSK	DETECTOR FUNCTION	Peak(PK) Average (AV)
TRANSFER RATE	12Mbps	ENVIRONMENTAL CONDITIONS	20deg. C, 60%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	55.01 PK	74.00	-18.99	1.15 H	203	23.62	31.39
1	2390.00	44.87 AV	54.00	-9.13	1.15 H	203	13.48	31.39
2	*2437.00	96.00 PK			1.15 H	203	64.46	31.54
2	*2437.00	86.68 AV			1.15 H	203	55.14	31.54
3	2483.50	56.00 PK	74.00	-18.00	1.15 H	215	24.30	31.70
3	2483.50	45.44 AV	54.00	-8.56	1.15 H	215	13.74	31.70
4	4874.00	45.59 PK	74.00	-28.41	1.22 H	218	8.30	37.29
4	4874.00	33.50 AV	54.00	-20.50	1.22 H	218	-3.79	37.29

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	44.27 PK	74.00	-29.73	1.19 V	252	15.48	28.79
1	1624.00	40.79 AV	54.00	-13.21	1.19 V	252	12.00	28.79
2	2320.00	59.43 PK	74.00	-14.57	1.19 V	123	28.28	31.15
2	2320.00	50.93 AV	54.00	-3.07	1.19 V	123	19.78	31.15
3	2390.00	62.40 PK	74.00	-11.60	1.16 V	195	31.01	31.39
3	2390.00	49.35 AV	54.00	-4.65	1.16 V	195	17.96	31.39
4	*2437.00	110.06 PK			1.15 V	196	78.52	31.54
4	*2437.00	99.71 AV			1.15 V	196	68.17	31.54
5	2483.50	65.22 PK	74.00	-8.78	1.18 V	189	33.52	31.70
5	2483.50	50.93 AV	54.00	-3.07	1.18 V	189	19.23	31.70
6	4874.00	45.90 PK	74.00	-28.10	1.15 V	295	8.61	37.29
6	4874.00	33.60 AV	54.00	-20.40	1.15 V	295	-3.69	37.29

REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b DSSS MODULATION

MODULATION TYPE	CCK	**TRANSFER RATE**	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	26deg.C, 66%RH, 991hPa
TESTED BY	Morgan Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	12.48	0.5	PASS
6	2437	12.12	0.5	PASS
11	2462	12.64	0.5	PASS

CH1


*RBW 100 kHz
*VBW 100 kHz
Delta 2 [T1]
0.47 dB
12.480000000 MHz
Ref 20 dBm
*Att 30 dB
SWT 5 ms
Marker 1 [T1]
-2.04 dBm
2.405880000 GHz
1 PK
VIEW
A
D1 4.4 dBm
D2 3.96 dBm
F1
F2
Center 2.412 GHz
2 MHz/
Span 20 MHz

CH6


*RBW 100 kHz
*VBW 100 kHz
Delta 2 [T1]
0.71 dB
12.120000000 MHz
Ref 20 dBm
*Att 30 dB
SWT 5 ms
Marker 1 [T1]
-1.49 dBm
2.430880000 GHz
1 PK
VIEW
A
D1 4.96 dBm
D2 4.24 dBm
F1
F2
Center 2.437 GHz
2 MHz/
Span 20 MHz

CH11


*RBW 100 kHz
*VBW 100 kHz
SWT 5 ms
Delta 2 [T1]
0.46 dB
12.640000000 MHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
-1.76 dBm
2.455680000 GHz
1 PK
VIEW
A
D1 4.35 dBm
D2 0.65 dBm
F1
F2
Center 2.462 GHz
2 MHz/
Span 20 MHz

802.11g OFDM MODULATION_NORMAL MODE

MODULATION TYPE	BPSK	**TRANSFER RATE**	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	26deg.C, 66%RH, 991hPa
TESTED BY	Morgan Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.40	0.5	PASS
6	2437	16.48	0.5	PASS
11	2462	16.44	0.5	PASS

CH1


*RBW 100 kHz
*VBW 100 kHz
SWT 5 ms
Delta 2 [T1]
0.11 dB
16.400000000 MHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
-4.89 dBm
2.403800000 GHz
1 PK
VIEW
D1 0.58 dBm
D2 -5.42 dBm
F1
F2
Center 2.412 GHz
2 MHz/
Span 20 MHz

CH6


*RBW 100 kHz
*VBW 100 kHz
SWT 5 ms
Delta 2 [T1]
-0.31 dB
16.480000000 MHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
-5.54 dBm
2.428720000 GHz
1 PK
VIEW
D1 0.48 dBm
D2 -5.52 dBm
F1
F2
Center 2.437 GHz
2 MHz/
Span 20 MHz

CH11


*RBW 100 kHz
*VBW 100 kHz
SWT 5 ms
Delta 2 [T1]
0.56 dB
16.440000000 MHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
-5.68 dBm
2.453760000 GHz
1 PK
VIEW
A
D1 0.66 dBm
D2 -5.34 dBm
F1
F2
Center 2.462 GHz
2 MHz/
Span 20 MHz

802.11g OFDM MODULATION_TURBO MODE

MODULATION TYPE	QPSK	TRANSFER RATE	12Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26deg.C, 66%RH, 991hPa
TESTED BY	Morgan Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
6	2437	32.64	0.5	PASS

CH6



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm. .

4.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007
AGILENT SIGNAL GENERATOR	E8257C	MY43320668	Dec. 07, 2006
DIGITAL RT OSCILLOSCOPE	TDS1012	C037299	Nov. 28, 2006
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE:
The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to peak the response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same peak reading on oscilloscope. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP

4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS

802.11b DSSS MODULATION

MODULATION TYPE	CCK	**TRANSFER RATE**	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	26deg.C, 66%RH, 991hPa
TESTED BY	Morgan Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	60.117	17.79	30	PASS
6	2437	59.566	17.75	30	PASS
11	2462	59.704	17.76	30	PASS

802.11g OFDM MODULATION_NORMAL MODE

MODULATION TYPE	BPSK	**TRANSFER RATE**	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	26deg.C, 66%RH, 991hPa
TESTED BY	Morgan Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	36.224	15.59	30	PASS
6	2437	35.975	15.56	30	PASS
11	2462	36.151	15.58	30	PASS

802.11g OFDM MODULATION_TURBO MODE

MODULATION TYPE	QPSK	**TRANSFER RATE**	12Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	26deg.C, 66%RH, 991hPa
TESTED BY	Morgan Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
6	2437	35.727	15.53	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded.
The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITIONS

Same as 4.3.6

4.5.7 TEST RESULTS

802.11b DSSS MODULATION

MODULATION TYPE	CCK	**TRANSFER RATE**	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	26deg.C, 66%RH, 991hPa
TESTED BY	Morgan Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-8.52	8	PASS
6	2437	-8.78	8	PASS
11	2462	-8.85	8	PASS

CH1


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-8.52 dBm
2.412741000 GHz
Ref 20 dBm
*Att 30 dB
1 PK
VIEW
A
Center 2.413365 GHz
150 kHz/
Span 1.5 MHz

CH6


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-8.78 dBm
2.437741000 GHz
Ref 20 dBm
*Att 30 dB
1 PK
VIEW
A
Center 2.438245 GHz
150 kHz/
Span 1.5 MHz

CH11


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-8.85 dBm
2.462744000 GHz
Ref 20 dBm
*Att 30 dB
1 PK
VIEW
A
20
-10
0
-10
-20
-30
-40
-50
-60
-70
-80
1
Center 2.46281 GHz
150 kHz/
Span 1.5 MHz

802.11g OFDM MODULATION_NORMAL MODE

MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26deg.C, 66%RH, 991hPa
TESTED BY	Morgan Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-11.78	8	PASS
6	2437	-11.95	8	PASS
11	2462	-11.62	8	PASS

CH1


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-11.78 dBm
2.412891000 GHz
Ref 20 dBm
*Att 30 dB
1 PK
VIEW
A
Center 2.412855 GHz
150 kHz/
Span 1.5 MHz

CH6


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-11.95 dBm
2.437618000 GHz
Ref 20 dBm
*Att 30 dB
1 PK
VIEW
A
Center 2.43799 GHz
150 kHz/
Span 1.5 MHz

CH11


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-11.62 dBm
2.463257000 GHz
Ref 20 dBm
*Att 30 dB
1 PK
VIEW
A
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
1
Center 2.46308 GHz
150 kHz/
Span 1.5 MHz

802.11g OFDM MODULATION_TURBO MODE

MODULATION TYPE	BPSK	**TRANSFER RATE**	12Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	26deg.C, 66%RH, 991hPa
TESTED BY	Morgan Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
6	2437	-13.63	8	PASS

CH6



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 100MHz bandwidth from band edge. The band edges was measured and recorded. The spectrum plots (Peak RBW=VBW=100kHz; Average RBW=1MHz, VBW=10Hz) are attached on the following pages.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.6 TEST RESULTS

The spectrum plots are attached on the following 18 images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

802.11b DSSS MODULATION

NOTE 1: The band edge emission plot of DSSS technique on the next page shows 52.08dBc between carrier maximum power and local maximum emission in restrict band (2.3861GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 113.73dBuV/m (Peak), so the maximum field strength in restrict band is 113.73-52.08=61.65dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of DSSS technique on the next page shows 53.30dBc between carrier maximum power and local maximum emission in restrict band (2.3868GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 105.98dBuV/m (Average), so the maximum field strength in restrict band is 105.98-53.30=52.68dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot of DSSS technique on the next second shows 51.07dBc between carrier maximum power and local maximum emission in restrict band (2.4874GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 113.10dBuV/m (Peak), so the maximum field strength in restrict band is 113.10-51.07=62.03dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of DSSS technique on the next third page shows 53.84dBc between carrier maximum power and local maximum emission in restrict band (2.4880GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 105.60dBuV/m (Average), so the maximum field strength in restrict band is 105.60-53.84=51.76dBuV/m which is under 54dBuV/m limit.

802.11b DSSS MODULATION






*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
3.22 dBm
2.377180000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-42.92 dBm
23.551740000 GHz
1 PK
VIEW
D1 4.9 dBm
D2 -15.1 dBm
Start 30 MHz
2.497 GHz/
Stop 25 GHz


*RBW 100 kHz
*VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
4.47 dBm
2.463400000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-49.44 dBm
2.483500000 GHz
Marker 3 [T1]
-46.60 dBm
2.487400000 GHz
Marker 4 [T1]
-51.79 dBm
2.500000000 GHz
1 PK
VIEW
D1 4.47 dBm
D2 -15.53 dBm
F1
F2
Center 2.504 GHz
10 MHz/
Span 100 MHz


*RBW 1 MHz
*VBW 10 Hz
SWT 25 s
Marker 1 [T1]
3.87 dBm
2.461400000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-54.46 dBm
2.483500000 GHz
Marker 3 [T1]
-49.97 dBm
2.488000000 GHz
Marker 4 [T1]
-58.26 dBm
2.500000000 GHz
1 PK
VIEW
D1 3.87 dBm
D2 -16.13 dBm
F1
F2
Center 2.504 GHz
10 MHz/
Span 100 MHz


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
2.67 dBm
2.427120000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-43.29 dBm
21.953660000 GHz
Marker 3 [T1]
-44.49 dBm
679.220000000 MHz
1 PK
VIEW
D1 4.47 dBm
D2 -15.53 dBm
Start 30 MHz
2.497 GHz/
Stop 25 GHz

802.11g OFDM MODULATION_NORMAL MODE

NOTE 1: The band edge emission plot of OFDM technique on the next page shows 47.57dBc between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 110.04dBuV/m (Peak), so the maximum field strength in restrict band is 110.04-47.57=62.47dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of OFDM technique on the next page shows 50.33dBc between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 101.07dBuV/m (Average), so the maximum field strength in restrict band is 101.07-50.33=50.74dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot of OFDM technique on the second page shows 46.05dBc between carrier maximum power and local maximum emission in restrict band (2.4852GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 110.03dBuV/m (Peak), so the maximum field strength in restrict band is 110.03-46.05=63.98dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of OFDM technique on the third page shows 48.73dBc between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 100.09dBuV/m (Average), so the maximum field strength in restrict band is 100.09-48.73=51.36dBuV/m which is under 54dBuV/m limit.

802.11g OFDM MODULATION






*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
-1.00 dBm
2.377180000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-42.75 dBm
22.053540000 GHz
1 PK
VIEW
D1 0.7 dBm
D2 -19.3 dBm
Start 30 MHz
2.497 GHz/
Stop 25 GHz


*RBW 100 kHz
*VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
0.61 dBm
2.460680000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-45.84 dBm
2.483500000 GHz
Marker 3 [T1]
-45.44 dBm
2.485200000 GHz
Marker 4 [T1]
-50.08 dBm
2.500000000 GHz
1 PK
VIEW
D1 0.61 dBm
D2 -19.39 dBm
F1
F2
Center 2.50308 GHz
10 MHz/
Span 100 MHz


*RBW 1 MHz
*VBW 10 Hz
SWT 25 s
Marker 1 [T1]
-0.94 dBm
2.460200000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-49.67 dBm
2.483500000 GHz
Marker 3 [T1]
-49.67 dBm
2.483500000 GHz
Marker 4 [T1]
-59.12 dBm
2.500000000 GHz
1 PK
VIEW
A
D1 -0.94 dBm
D2 -20.94 dBm
F1
F2
Center 2.503 GHz
10 MHz/
Span 100 MHz


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
-2.11 dBm
2.427120000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-44.04 dBm
15.361580000 GHz
1 PK
VIEW
A
D1 0.61 dBm
D2 -19.39 dBm
Start 30 MHz
2.497 GHz/
Stop 25 GHz

802.11g OFDM MODULATION_TURBO MODE

NOTE 1: The band edge emission plot of OFDM technique on the next page shows 47.94dBc between carrier maximum power and local maximum emission in restrict band (2.320GHz). The emission of carrier strength list in the test result of channel 6 at the item 4.2.7 is 110.06dBuV/m (Peak), so the maximum field strength in restrict band is 110.06-47.94=62.12dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of OFDM technique on the next page shows 49.32dBc between carrier maximum power and local maximum emission in restrict band (2.3198GHz). The emission of carrier strength list in the test result of channel 6 at the item 4.2.7 is 99.71dBuV/m (Average), so the maximum field strength in restrict band is 99.71-49.32=50.39dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot of OFDM technique on the next second page shows 47.70dBc between carrier maximum power and local maximum emission in restrict band (2.4899GHz). The emission of carrier strength list in the test result of channel 6 at the item 4.2.7 is 110.06dBuV/m (Peak), so the maximum field strength in restrict band is 110.06-47.70=62.36dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of OFDM technique on the next third page shows 47.80dBc between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 6 at the item 4.2.7 is 99.71dBuV/m (Average), so the maximum field strength in restrict band is 99.71-47.80=51.91dBuV/m which is under 54dBuV/m limit.

802.11g OFDM TURBO MODULATION






*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
-0.52 dBm
2.427120000 GHz
Ref 10.5 dBm
*Att 20 dB
10 Offset 0.5 dB
D1 1.14 dBm
D2 -18.86 dBm
Marker 2 [T1]
-44.05 dBm
1.628080000 GHz
Marker 3 [T1]
-53.33 dBm
329.640000000 MHz
Marker 4 [T1]
-51.73 dBm
22.802640000 GHz
1 PK
VIEW
A
LVL
Start 30 MHz
2.497 GHz/
Stop 25 GHz


*RBW 100 kHz
*VBW 100 kHz
SWT 20 ms
Marker 1 [T1]
1.64 dBm
2.439400000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
D1 1.64 dBm
D2 -18.36 dBm
Marker 2 [T1]
-46.55 dBm
2.483500000 GHz
Marker 3 [T1]
-46.06 dBm
2.489900000 GHz
Marker 4 [T1]
-48.97 dBm
2.500000000 GHz
1 PK
VIEW
A
LVL
F1
F2
Center 2.5186 GHz
20 MHz/
Span 200 MHz


*RBW 1 MHz
*VBW 10 Hz
SWT 50 s
Marker 1 [T1]
-2.06 dBm
2.445200000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 2 [T1]
-49.86 dBm
2.483500000 GHz
Marker 3 [T1]
-49.86 dBm
2.483500000 GHz
Marker 4 [T1]
-53.53 dBm
2.500000000 GHz
1 PK
VIEW
A
LVL
D1 -2.06 dBm
D2 -22.06 dBm
F1
F2
Center 2.5172 GHz
20 MHz/
Span 200 MHz


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
0.72 dBm
2.427120000 GHz
Ref 20.5 dBm
*Att 30 dB
20 Offset 0.5 dB
Marker 2 [T1]
-44.76 dBm
1.628080000 GHz
Marker 3 [T1]
-42.24 dBm
22.153420000 GHz
1 PK
VIEW
A
LVL
D1 1.64 dBm
D2 -18.36 dBm
Start 30 MHz
2.497 GHz/
Stop 25 GHz

4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Monopole antenna with UFL-R-SMT connector. The maximum Gain of the antenna is 2dBi.

5 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025

USA	FCC, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, NCC
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3185050

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

APPENDIX-A

MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.