

D-Link *AirPlus*™ G **DWL-G730AP**

802.11g/2.4GHz
Wireless Pocket Router/AP

Manual

Contents

- Package Contents 3
- Introduction..... 4
- Wireless Basics 6
- Hardware Overview 8
- Getting Started in AP Mode 9
- Getting Started in Client Mode 10
- Getting Started in Router Mode 11
- Using the Configuration Utility in AP Mode 12
- Using the Configuration Utility in AP Client Mode 24
- Using the Configuration Utility in Router Mode 35
- Networking Basics 60
- Technical Specifications 73
- Contacting Technical Support 76
- Warranty and Registration 77

Package Contents



Contents of Package:

- **D-Link AirPlus™ G DWL-G730AP**
802.11g/2.4GHz Wireless Pocket Router/AP
- Power Supply - 5V DC, 1.2A
- Manual on CD
- Quick Installation Guide
- Ethernet Cable
- USB Power Cable
- Travel Case

If any of the above items are missing, please contact your reseller.

Note: Using a power supply with a different voltage rating than the one included with the DWL-G730AP will cause damage and void the warranty for this product.

System Requirements:

Computer with Windows XP/2000/Me operating system with an installed Ethernet adapter

Internet Explorer version 6.0 or Netscape Navigator version 7.0, with JavaScript enabled

Introduction

The pocket-sized DWL-G730AP gives you all the features of a full-size router/access point with pocket-size convenience and portability. Carry it along with you on business trips and vacations, and experience the convenience of wireless networking with your colleagues and family almost anywhere you travel.

With 3 different operating modes, the versatile DWL-G730AP can be used as a portable access point, AP client or router.

At up to five times the speed of previous wireless devices (maximum wireless signal rate up to 54Mbps*), you can work faster and more efficiently, increasing productivity. With the DWL-G730AP, bandwidth-intensive applications like graphics or multimedia will benefit significantly because large files are able to move across the network quickly.

The D-Link *AirPlus™* G DWL-G730AP Wireless Pocket Router/AP is an 802.11g high-performance, wireless device that is also compatible with 802.11b devices. It is an ideal way to extend the reach and number of computers connected to your wireless network.

The DWL-G730AP is capable of data transfer rates up to 54Mbps*, when used with other D-Link *AirPlus* G products, and can be integrated into a large network.

*Maximum wireless signal rate based on IEEE Standard 802.11g specifications. Actual data throughput will vary. Network conditions and environmental factors lower actual data throughput rate.

Features and Benefits

- **Up to 5X Faster with AirPlus G Products** - maximum wireless signal rate up to 54Mbps.* With increased data rate and capacity, the DWL-G730AP delivers media rich content such as digital images, videos, and MP3 files much faster than standard 802.11b networks.
- **Fully 802.11b Compatible** – Fully compatible with the IEEE 802.11b standard and interoperable with all existing 802.11b compliant devices.
- **Network Security with up to 128-bit WEP Encryption** – Supports 64/128-bit WEP encryption for a level of security for your data and wireless communication.
- **Built-in DHCP Server** – If enabled, it will automatically assign IP addresses to wireless clients on the local network.
- **Web-based interface for Managing and Configuring** – Easy-to-use interface independent of the operating system.

*Maximum wireless signal rate based on IEEE Standard 802.11g specifications. Actual data throughput will vary. Network conditions and environmental factors lower actual data throughput rate.

Wireless Basics

D-Link wireless products are based on industry standards to provide easy-to-use and compatible high-speed wireless connectivity within your home, business or public access wireless networks. D-Link wireless products will allow you access to the data you want, when and where you want it. You will be able to enjoy the freedom that wireless networking brings.

A Wireless Local Area Network (WLAN) is a computer network that transmits and receives data with radio signals instead of wires. WLANs are used increasingly in both home and office environments, and public areas such as airports, coffee shops and universities. Innovative ways to utilize WLAN technology are helping people to work and communicate more efficiently. Increased mobility and the absence of cabling and other fixed infrastructure have proven to be beneficial for many users.

Wireless users can use the same applications they use on a wired network. Wireless adapter cards used on laptop and desktop systems support the same protocols as Ethernet adapter cards.

People use WLAN technology for many different purposes:

Mobility - Productivity increases when people have access to data in any location within the operating range of the WLAN. Management decisions based on real-time information can significantly improve worker efficiency.

Low Implementation Costs – WLANs are easy to set up, manage, change and relocate. Networks that frequently change can benefit from WLANs ease of implementation. WLANs can operate in locations where installation of wiring may be impractical.

Installation and Network Expansion - Installing a WLAN system can be fast and easy and can eliminate the need to pull cable through walls and ceilings. Wireless technology allows the network to go where wires cannot go - even outside the home or office.

Scalability – WLANs can be configured in a variety of ways to meet the needs of specific applications and installations. Configurations are easily changed and range from peer-to-peer networks suitable for a small number of users to larger infrastructure networks to accommodate hundreds or thousands of users, depending on the number of wireless devices deployed.

Inexpensive Solution - Wireless network devices are as competitively priced as conventional Ethernet network devices.

Wireless Basics (*continued*)

Installation Considerations

Keep in mind, that the number, thickness and location of walls, ceilings, or other objects that the wireless signals must pass through, may limit the range. Typical ranges vary depending on the types of materials and background RF (radio frequency) noise in your home or business. The key to maximizing wireless range is to follow these basic guidelines:

- 1** Keep the number of walls and ceilings between the DWL-G730AP and other network devices to a minimum - each wall or ceiling can reduce your DWL-G730AP's range from 3-90 feet (1-30 meters.) Position your devices so that the number of walls or ceilings is minimized.
- 2** Be aware of the direct line between network devices. A wall that is 1.5 feet thick (.5 meters), at a 45-degree angle appears to be almost 3 feet (1 meter) thick. At a 2-degree angle it looks over 42 feet (14 meters) thick! Position devices so that the signal will travel straight through a wall or ceiling (instead of at an angle) for better reception.
- 3** Building materials can impede the wireless signal - a solid metal door or aluminum studs may have a negative effect on range. Try to position wireless devices and computers with wireless adapters so that the signal passes through drywall or open doorways and not other materials.
- 4** Keep your product away (at least 3-6 feet or 1-2 meters) from electrical devices or appliances that generate RF noise.

Hardware Overview


Top Panel



Power LED: Solid indicates a connection to a good power source.


LAN LED: Solid indicates an Ethernet connection. Blinking indicates activity on the Ethernet network.

WLAN LED: A solid light indicates that the wireless segment is ready. This LED blinks during wireless data transmission.



Mode Selection Switch: Used to select AP, client, or router mode.

Rear Panel




Reset Button: Used to restore default settings.

Receptor for Power Adapter

LAN Port
This is the connection for Ethernet cables to your Ethernet-enabled device. When in Router mode, this port functions as a WAN port.

Getting Started - in AP mode

An Example of a Wireless Infrastructure Network




Please remember that D-Link AirPlus G wireless devices are pre-configured to connect together, right out of the box, with their default settings.

For a typical wireless setup at home (as shown above), please do the following:

- 1** You will need broadband Internet access (a Cable or DSL-subscriber line into your home or office)
- 2** Consult with your Cable or DSL provider for proper installation of the modem
- 3** Connect the Cable or DSL modem to your broadband router (see the **Quick Installation Guide** included with your router.)
- 4** Connect the router to the D-Link AirPlus G DWL-G730AP (in access point mode). (See the **Quick Installation Guide** included with the DWL-G730AP.)
- 5** If you are connecting a desktop computer in your network, you can install the D-Link AirPlus G DWL-G510 wireless PCI adapter into an available PCI slot on your desktop computer. (See the **Quick Installation Guide** included with the DWL-G510.)
- 6** Install the drivers for the wireless Cardbus adapter into a laptop computer. (e.g, the DWL-G630; See the **Quick Installation Guide** included with the DWL-G630.)

Getting Started - in Client mode

An Example of a Wireless Infrastructure Network




Please remember that D-Link AirPlus G wireless devices are pre-configured to connect together, right out of the box, with their default settings.

For a typical wireless setup at home (as shown above), please do the following:

- 1** You will need broadband Internet access (a Cable or DSL-subscriber line into your home or office)
- 2** Consult with your Cable or DSL provider for proper installation of the modem
- 3** Connect the Cable or DSL modem to your broadband router (see the **Quick Installation Guide** included with your router.)
- 4** Connect the D-Link AirPlus G DWL-G730AP (in client mode) to your laptop. (See the **Quick Installation Guide** included with the DWL-G730AP.)

Getting Started - in Router mode

An Example of a Wireless Infrastructure Network



Please remember that D-Link AirPlus G wireless devices are pre-configured to connect together, right out of the box, with their default settings.

For a typical wireless setup at home (as shown above), please do the following:

- 1** You will need broadband Internet access (a Cable or DSL-subscriber line into your home or office)
- 2** Consult with your Cable or DSL provider for proper installation of the modem.
- 3** Connect the modem to the D-Link AirPlus G DWL-G730AP (in router mode). (See the **Quick Installation Guide** included with the DWL-G730AP.)
- 4** If you are connecting a desktop computer in your network, you can install the D-Link AirPlus G DWL-G510 wireless PCI adapter into an available PCI slot on your desktop computer. (See the **Quick Installation Guide** included with the DWL-G510.)
- 5** Install the drivers for the wireless Cardbus adapter into a laptop computer. (e.g, the DWL-G630; See the **Quick Installation Guide** included with the DWL-G630.)

Using the Configuration Utility in **AP Mode**

After you have completed the initial installation and the Setup Wizard (as illustrated in the Quick Installation Guide that is included with the DWL-G730AP), and you have selected AP Mode, you can access the configuration menu, at any time, by opening the web-browser and typing in the IP address of the DWL-G730AP.


The DWL-G730AP's default IP address is shown below:

- Open the web browser
- Type in the **IP address** of the DWL-G730AP. (192.168.0.30).




Note: If you have changed the default IP address assigned to the DWL-G730AP, make sure to enter the correct IP address.

- Type **admin** in the **User Name** field
- Leave the **Password** blank
- Click **OK**



The **Home>Wizard** screen will appear. Please refer to the *Quick Installation Guide* for more information regarding the Setup Wizard.



Using the Configuration Utility in **AP Mode** (continued)

Home > Wireless

Hexadecimal digits consist of the numbers 0-9 and the letters A-F

ASCII (American Standard Code for Information Interchange) is a code for representing English letters as numbers from 0-127

D-Link
Building Networks for People

AirPlus G

802.11g/2.4GHz Wireless Pocket Access Point

DWL-G730AP

Wizard
Wireless
LAN
DHCP

Home Advanced Tools Status Help

Wireless Settings

The DWL-G730AP is running in the AP mode.

These are the wireless settings for the AP (Access Point) Portion.

SSID : default

Channel : 6

Authentication : ☒ Open System ☐ Shared Key ☐ WPA ☐ WPA-PSK

WEP : ☒ Enabled ☐ Disabled

WEP Encryption : 64Bit

Key Type : HEX

Key1 :

Key2 :

Key3 :

Key4 :

☒ ☐ ☐ ☐

Apply Cancel Help

SSID: (Service Set Identifier) default is the default setting. The SSID is a unique name that identifies a network. All devices on a network must share the same SSID name in order to communicate on the network. If you choose to change the SSID from the default setting, input your new SSID name in this field.

Channel: Channel **6** is the default channel. Input a new number if you want to change the default setting. All devices on the network must be set to the same channel to communicate on the network.

Authentication:

Select **Open System** to communicate the key across the network.

Select **Shared Key** to limit communication only to those devices that share the same WEP settings.

Select **WPA** to select *Wi-Fi Protected Access* in conjunction with a RADIUS server in your network

Select **WPA-PSK** to select *Wi-Fi Protected Access* without a RADIUS server.

WEP: Select **Enabled** or **Disabled**.

WEP Encryption: Select **64-bit** or **128-bit** WEP encryption.

Key Type: Select **Hexadecimal** or **ASCII** key type

Keys 1-4: Input up to four encryption keys. You will select one of these to be the active key.

Apply: Click **Apply** to apply the changes.

Using the Configuration Utility in **AP Mode** (continued)

Home > Wireless > WPA

SSID: (Service Set Identifier) Default is the default setting. The SSID is a unique name that identifies a network. All devices on a network must share the same SSID name in order to communicate on the network. If you choose to change the SSID from the default setting, input your new SSID name in this field.

Channel: Channel **6** is the default channel. Input a new number if you want to change the default setting. All devices on the network must be set to the same channel to communicate on the network.

Authentication:

Select **WPA** to select *Wi-Fi Protected Access* in conjunction with a RADIUS server in your network.

When **WPA** is selected fill in the following fields:

RADIUS Server 1 IP: Enter the IP address of the RADIUS server.

Port: Enter the Port number here.

Shared Secret: Enter the shared secret here.

RADIUS Server 2 IP: Enter the IP address of the RADIUS server.

Port: Enter the Port number here.

Shared Secret: Enter the shared secret here.

Apply: Click **Apply** to apply the changes.

D-Link Building Networks for People

AirPlus G

802.11g/2.4GHz Wireless Pocket Access Point

DWL-G730AP

Wizard Wireless LAN DHCP

Home Advanced Tools Status Help

Wireless Settings

The DWL-G730AP is running in the AP mode.

These are the wireless settings for the AP(Access Point)Portion.

SSID: default

Channel: 6

Authentication: ☐ Open System ☐ Shared Key ☒ WPA ☐ WPA-PSK

002.1X

RADIUS Server 1 IP: 0.0.0.0

Port: 1812

Shared Secret:

RADIUS Server 2 IP (Optional): 0.0.0.0

Port: 0

Shared Secret:

Apply Cancel Help

Using the Configuration Utility in **AP Mode** (continued)

Home > Wireless > WPA-PSK

SSID: (Service Set Identifier) Default is the default setting. The SSID is a unique name that identifies a network. All devices on a network must share the same SSID name in order to communicate on the network. If you choose to change the SSID from the default setting, input your new SSID name in this field.

Channel: Channel **6** is the default channel.

Input a new number if you want to change the default setting. All devices on the network must be set to the same channel to communicate on the network.

Authentication:

When **WPA-PSK** is selected fill in the following fields:

Passphrase: Enter the Passphrase here.

Confirmed Passphrase: Confirm the Passphrase here.

Apply: Click **Apply** to apply the changes.

The screenshot shows the D-Link configuration utility interface. At the top, it says 'D-Link Building Networks for People' and 'AirPlus G'. Below that, it identifies the device as '802.11g/2.4GHz Wireless Pocket Access Point'. The left sidebar has buttons for 'Wizard', 'Wireless' (which is highlighted), 'LAN', and 'DHCP'. The main content area has tabs for 'Home', 'Advanced', 'Tools', 'Status', and 'Help'. Under the 'Home' tab, it says 'Wireless Settings' and 'The DWL-G730AP is running in the AP mode.' It then displays the wireless settings: 'SSID : default', 'Channel : 6' (with a dropdown arrow), and 'Authentication : ☐ Open System ☐ Shared Key ☐ WPA ☒ WPA-PSK'. There are input fields for 'Passphrase :' and 'Confirmed Passphrase :'. At the bottom right, there are three buttons: 'Apply' (with a green checkmark), 'Cancel' (with a red X), and 'Help' (with a red plus sign).

Using the Configuration Utility in AP Mode (continued)

Home > LAN

D-Link
Building Networks for People

AirPlus G

802.11g/2.4GHz Wireless Pocket Access Point

DWL-G730AP

Home Advanced Tools Status Help

LAN Settings

LAN IP ☐ Dynamic IP Address
☒ Static IP Address

IP Address

Subnet Mask

Gateway

DNS Server

Dynamic IP Address: Select this option if you would like to have an IP Address automatically assigned to the DWL-G730AP by a DHCP server in your network.

DHCP stands for Dynamic Host Configuration Protocol. It is a protocol for assigning dynamic IP addresses “automatically.” With a DHCP Server there is no need to manually assign an IP Address.

Static IP Address: Select this option if you are manually assigning an IP address.

IP Address: 192.168.0.30 is the default IP address of the access point.

Subnet Mask: 255.255.255.0 is the default Subnet Mask. All devices on the network must have the same subnet mask to communicate on the network.

Gateway: Enter the IP address of the router in your network.

DNS Server: Enter the IP address of the DNS server. The DNS server translates domain names such as www.dlink.com into IP addresses.

IP Address

If you need to assign static IP addresses to the devices in your network, please remember that the IP address for each computer or device must be in the same IP address range as all the devices in the network. Each device must also have the same subnet mask. *For example: Assign the first computer an IP address of 192.168.0.2 and a subnet mask of 255.255.255.0, the second device an IP address of 192.168.0.3 and a subnet mask of 255.255.255.0, and so on.* **Note: Devices that are assigned the same IP address may not be visible on the network.**

Using the Configuration Utility in AP Mode (continued)

Home > DHCP

D-Link
Building Networks for People

DWL-G730AP

Wizard

Wireless

LAN

DHCP

AirPlus G

802.11g/2.4GHz Wireless Pocket Access Point

HomeAdvancedToolsStatusHelp

DHCP Server

The DWL-G730AP can be setup as a DHCP server to distribute IP addresses to the LAN network.

DHCP Server

☐ Enabled ☒ Disabled

Starting IP Address

192 . 168 . 0 .

Ending IP Address

192 . 168 . 0 .

Lease Time

Apply Cancel Help

DHCP Client Table

Host Name	IP Address	MAC Address	Expired Time
-----------	------------	-------------	--------------

DHCP Server: Select **Enabled** or **Disabled**. Disabled is the default setting. If you want to use the DWL-G730AP as a DHCP server, to automatically assign dynamic IP addresses on the network, you will select Enabled.

Starting IP Address: If you have enabled the DHCP server function, enter the starting point of the IP address range for your network.

Ending IP Address: Enter the ending IP address of your IP address range, if you have enabled the DHCP function of the DWL-G730AP.

Lease Time: Choose the length of time during which the DHCP function of the DWL-G730AP automatically regenerates the IP addresses to the devices in your network.

DHCP Client Table: Lists the devices on your network that are receiving dynamic IP addresses from the DWL-G730AP.

17

Using the Configuration Utility in **AP Mode** (continued)

Advanced > Performance

Beacon Interval: Beacons are packets sent by an access point to synchronize a wireless network. Specify a beacon interval value. Default (100) is recommended.

RTS Threshold: This value should remain at its default setting of 2432. If you encounter inconsistent data flow, only minor modifications to the value range between 256 and 2432 are recommended.

Fragmentation: This value should remain at its default setting of 2346. If you experience a high packet error rate, you may slightly increase your fragmentation threshold within the value range of 256 to 2346. Setting the fragmentation threshold too low may result in poor performance.

DTIM Interval (Beacon Rate): (Delivery Traffic Indication Message) Enter a value between 1 and 255 (default is 3) for the Delivery Traffic Indication Message (DTIM.) A DTIM is a countdown informing clients of the next window for listening to broadcast and multicast messages.


TX Rates: Select the transmission rate for the network. The default setting is Auto.

Mode Setting: For utmost speed, select **G Mode** to include only 802.11g devices in your network. Select **Mix Mode** to include 802.11g and 802.11b devices in your network.

Preamble: Short Preamble is the default setting. (High traffic networks should use the shorter preamble type.) The preamble defines the length of the CRC block (Cyclic Redundancy Check is a common technique for detecting data transmission errors) used in communication between the access point and the wireless network adapters.

SSID Broadcast: (Service Set Identifier) Enable or Disable (default) the broadcast of the SSID name across the network. SSID is a name that identifies a wireless network. All devices on a network must use the same SSID to establish communication.

Antenna Transmit Power: Select the transmission power of the antenna. Limiting antenna power can be useful for security purposes.



Using the Configuration Utility in AP Mode (continued)

Advanced > Filters

The screenshot shows the D-Link configuration utility interface for the DWL-G730AP. The left sidebar contains the D-Link logo, the model number DWL-G730AP, and three buttons: Performance, Filters (highlighted), and a third unlabeled button. The main content area has a title bar with 'Home', 'Advanced' (selected), 'Tools', 'Status', and 'Help'. Below the title bar, the section is titled 'MAC Filters'. A text box explains: 'Filters are used to allow or deny Wireless Clients users from accessing the DWL-G730AP.' There are three radio button options: 'Disabled MAC Filters' (selected), 'Only allow MAC address(es) listed below to connect to DWL-G730AP', and 'Only deny MAC address(es) listed below to connect to DWL-G730AP'. Below these are input fields for 'MAC Address' (a series of six boxes separated by hyphens) and a 'Clear' button. There is also a 'Connected PCs' dropdown menu and a 'Clone' button. At the bottom right of the main area are three buttons: a green checkmark (Apply), an orange X (Cancel), and a red plus sign (Help). Below the main area is a section titled 'MAC Filter List' with a sub-header 'MAC Address' and a large empty table area.

Use **MAC Filters** to allow or deny wireless clients (identified by their MAC addresses) access to the DWL-G730AP.

You can manually add a MAC address or select the MAC address from the list of clients that are currently connected to the router (**Connected PCs**).

The default setting is **Disabled MAC Filters**.

MAC Filter List: This list will display the MAC addresses that are in the selected filter.

Using the Configuration Utility in **AP Mode** (continued)

Tools > Admin

New Password: Enter the new password.

Confirm Password:
Re-enter the password to confirm it.

The screenshot shows the D-Link AirPlus G configuration utility interface. The top navigation bar includes 'Home', 'Advanced', 'Tools' (selected), 'Status', and 'Help'. The left sidebar shows 'Admin' (selected), 'System', and 'Firmware'. The main content area is titled 'Administrator Settings' and contains two password input fields: 'New Password' and 'Confirm Password'. At the bottom right, there are three buttons: 'Apply' (with a green checkmark), 'Cancel' (with a yellow X), and 'Help' (with a red plus sign).

Tools > System

Save Settings: The current system settings can be saved as a file onto the local hard drive.

Load Settings: The saved file or any other saved setting file can be loaded back on the access point. To reload a system settings file, click on **Browse** to browse the local hard drive and locate the system file to be used. Click **Load** when you have selected the file to be loaded back onto the access point.


Restore: You may also reset the DWL-G730AP back to factory settings by clicking on **Restore**. Make sure to save the unit's settings before clicking on **Restore**. You will lose your current settings when you click **Restore**.

The screenshot shows the D-Link AirPlus G configuration utility interface. The top navigation bar includes 'Home', 'Advanced', 'Tools' (selected), 'Status', and 'Help'. The left sidebar shows 'Admin', 'System' (selected), and 'Firmware'. The main content area is titled 'System Settings' and contains three sections: 'Save Settings to Local Hard Drive' with a 'Save' button; 'Load Settings From Local Hard Drive' with a 'Browse' button and a 'Load' button; and 'Restore to Factory Default Settings' with a 'Restore' button. A 'Help' button (with a red plus sign) is located at the bottom right.

Using the Configuration Utility in AP Mode (continued)


Tools > Firmware

You can upgrade the firmware of the DWL-G730AP on this page. When you click [Click here to check...](#) in this window you will be connected to D-Link's website, where you can download the latest firmware update. After you have completed the firmware download to your hard drive, click **Browse** to browse your local hard drive and locate the firmware to be used for the update. Click **Apply**.



Status > Device Info

This screen displays the current firmware version, and the current wireless and Ethernet settings of the DWL-G730AP.



Using the Configuration Utility in AP Mode (continued)

Status > Log



View Log

The DWL-G730AP keeps a running log of events and activities occurring on the AP. If the device is rebooted, the logs are automatically cleared. You may save the log files under Log Setting.

First Page - The first page of the log.

Last Page - The last page of the log.

Previous - Moves back one log page.

Next - Moves forward one log page.

Clear - Clears the logs completely.

Log Settings - Brings up the page to configure the logs.

Log Settings


Not only does the DWL-G730AP display the logs of activities and events, it can be setup to send these logs to another location. The logs can be sent via email to an email account.

Using the Configuration Utility in AP Mode (continued)

Traffic Statistics

The DWL-G730AP keeps statistics of traffic that passes through it. You are able to view the amount of packets that pass through the Ethernet and wireless portions of the network. The traffic counter will reset if the device is rebooted.

Status> Stats



Connected Wireless PCs List

This list displays the MAC addresses of connected PCs and the length of time that they have been connected.

Status > Wireless



Menu

Select from this menu for extra help.


Help



Using the Configuration Utility in **AP Client Mode**

Whenever you want to configure your network or the DWL-G730AP, you can access the Configuration Menu by opening the Web browser and typing in the IP address of the DWL-G730AP. The DWL-G730AP default IP address is shown at right.

- Open the Web browser
- Type in the **IP address** of the AP Client (http://192.168.0.30)




Note: if you have changed the default IP address assigned to the DWL-G730AP, make sure to enter the correct IP address.

- Type **admin** in the **User Name** field
- Leave the **Password** blank
- Click **OK**



Home > Wizard

The Home>Wizard screen will appear. Please refer to the *Quick Installation Guide* for more information regarding the Setup Wizard.



Using the Configuration Utility in AP Client Mode (continued)


Home > Wireless

SSID-

Service Set Identifier (SSID) is the name designated for a specific wireless local area network (WLAN). The SSID's factory default setting is **default**. The SSID can be easily changed to connect to an existing wireless network or to establish a new wireless network.

Channel-

6 is the default channel. All devices on the network must share the same channel. (Note: The wireless adapters will automatically scan and match the wireless setting.)



Wireless Mode-

Select **Infrastructure** or **Ad-Hoc** mode.

Authentication-

Select **Open System** to communicate the key across the network.

Select **Shared Key** to limit communication only to those devices that share the same WEP settings.

Select **WPA-PSK** to select *Wi-Fi Protected Access* without a RADIUS server.

WEP-

Wired Equivalent Privacy (WEP) is a wireless security protocol for Wireless Local Area Networks (WLAN). WEP provides security by encrypting the data that is sent over the WLAN. Select **Enabled** or **Disabled**. **Disabled** is the default setting.

WEP Encryption-

Select the level of encryption desired: 64-bit, or 128-bit

Key Type-

Select **HEX** or **ASCII**

Keys 1-4-

Input up to 4 WEP keys; select the one you wish to use

Using the Configuration Utility in AP Client Mode (continued)

Home > Wireless > WPA-PSK

SSID-

Service Set Identifier (SSID) is the name designated for a specific wireless local area network (WLAN). The SSID's factory default setting is **default**. The SSID can be easily changed to connect to an existing wireless network or to establish a new wireless network. Click **Site Survey** to view the available networks.

Channel-

6 is the default channel. All devices on the network must share the same channel. *(Note: The wireless adapters will automatically scan and match the wireless setting.)*

The screenshot shows the D-Link configuration utility for the DWL-G730AP. The interface has a blue header with the D-Link logo and 'AirPlus G' branding. Below the header, it says '802.11g/2.4GHz Wireless Pocket Access Point'. The main menu has tabs for 'Home', 'Advanced', 'Tools', 'Status', and 'Help'. The 'Home' tab is selected, and the 'Wireless Settings' section is active. A message states 'The DWL-G730AP is running in the AP Client mode.' Below this, it says 'These are the wireless settings for the AP(Access Point)Portion.' The settings include: SSID: 'default' with a 'Site Survey' button; Channel: '6' with a dropdown arrow; Wireless Mode: 'Infrastructure' selected (radio buttons for Infrastructure, Ad-hoc); Authentication: 'WPA-PSK' selected (radio buttons for Open System, Shared Key, WPA-PSK); Passphrase: an empty text field; and Confirmed Passphrase: an empty text field. At the bottom right, there are three icons: a green checkmark, a red X, and a red plus sign, with the labels 'Apply', 'Cancel', and 'Help' respectively.

Wireless Mode- Select Infrastructure or Ad-Hoc mode.

Authentication- Select **Open System**, Shared Key or WPA-PSK

When **WPA-PSK** is selected fill in the following fields:


Passphrase: Enter the Passphrase here.

Confirmed Passphrase: Confirm the Passphrase here.

Apply: Click **Apply** to apply the changes.

Using the Configuration Utility in AP Client Mode (continued)

Home > LAN



LAN is short for Local Area Network. This is considered your internal network. These are the IP settings of the LAN interface for the DWL-G730AP. These settings may be referred to as private settings. You may change the LAN IP address if needed. The LAN IP address is private to your internal network and cannot be seen on the Internet.

IP Address- The IP address of the LAN interface. The default IP address is: **192.168.0.30**

Subnet Mask- The subnet mask of the LAN interface.
The default subnet mask is **255.255.255.0**

Gateway- The IP address of the router.

DNS Server- The IP address of the Domain Name Server.

Using the Configuration Utility in AP Client Mode (continued)

Advanced > Performance

Beacon Interval:

Beacons are packets sent by an access point to synchronize a wireless network. Specify a beacon interval value. Default (100) is recommended.

RTS Threshold: This value should remain at its default setting of 2432. If you encounter inconsistent data flow, only minor modifications to the value range between 256 and 2432 are recommended.

Fragmentation: This value should remain at its default setting of 2346. If you experience a high packet error rate, you may slightly increase your fragmentation threshold within the value range of 256 to 2346. Setting the fragmentation threshold too low may result in poor performance.


DTIM Interval: (Delivery Traffic Indication Message) Enter a value between 1 and 255 (default is 3) for the Delivery Traffic Indication Message (DTIM.) A DTIM is a countdown informing clients of the next window for listening to broadcast and multicast messages.

TX Rates: Select the transmission rate for the network. The default setting is Auto.

Preamble Type: **Short Preamble** is the default setting. (High traffic networks should use the shorter preamble type.) The preamble defines the length of the CRC block (Cyclic Redundancy Check is a common technique for detecting data transmission errors) used in communication between the access point and the wireless network adapters.

SSID Broadcast: (Service Set Identifier) Enable or Disable (default) the broadcast of the SSID name across the network. SSID is a name that identifies a wireless network. All devices on a network must use the same SSID to establish communication.

Antenna Transmit Power: Select the transmission power of the antenna. Limiting antenna power can be useful for security purposes.



Using the Configuration Utility in AP Client Mode (continued)

Tools > Admin

D-Link
Building Networks for People

DWL-G730AP



Admin

System

Firmware

AirPlus™ G

802.11g/2.4GHz Wireless Pocket Access Point

HomeAdvanced**Tools**StatusHelp

Administrator Settings

New Password

Confirm Password

ApplyCancelHelp

Administrator Settings-

New Password- Enter the password.

Confirm Password- Enter the password again.

Using the Configuration Utility in AP Client Mode (continued)

Tools > System



The current system settings can be saved as a file onto the local hard drive. To reload a system settings file, click on **Browse** to browse the local hard drive and locate the system file to be used.


Save Settings to Local Hard Drive- Click **Save** to save the current settings to the local hard drive

Load Settings from Local Hard Drive- Click **Browse** to find the settings, then click **Load**

Restore to Factory Default Settings- Click **Restore** to restore the factory default settings

Using the Configuration Utility in AP Client Mode (continued)

Tools > Firmware




You can upgrade the firmware of the router here. Make sure the firmware you want to use is on the local hard drive of the computer. Check the D-Link support site for firmware updates at <http://support.dlink.com> and download firmware upgrades to your hard drive. After you have downloaded the firmware upgrade to your hard drive, click **Browse** to browse the local hard drive and locate the firmware to be used for the update.

Firmware Upgrade- Click on the link in this screen to find out if there is updated firmware; if so, download the new firmware to your hard drive.

Browse- After you have downloaded the new firmware, click **Browse** in this window to locate the firmware update on your hard drive. Click **Apply** to complete the firmware upgrade.

Using the Configuration Utility in AP Client Mode (continued)

Status > Device Info



This screen displays the current firmware version, and the current wireless and Ethernet settings of the DWL-G730AP.

Using the Configuration Utility in AP Client Mode (continued)

Status > Stats


Building Networks for People



Device Info

Stats

HomeAdvancedToolsStatusHelp

Traffic Statistics

Traffic Statistics display Receive and Transmit Packets Passing through the DWL-G730AP

Ethernet

Send Good Packets1460

Recv Good Packets0

Wireless

Send Good Packets1460

Recv Good Packets0



Help

This screen displays the Traffic Statistics. Here you can view the amount of packets that pass through the DWL-G730AP on both the Ethernet and the wireless networks. The traffic counter will reset if the device is rebooted.

33

Using the Configuration Utility in AP Client Mode (continued)

Help



The Help menu is displayed here. Click on a topic to learn more about it.

Using the Configuration Utility in Router Mode



To configure the DWL-G730AP in Router mode, you must be connected to the router via a wireless network adapter. The LAN Port on the unit functions as a WAN port when the DWL-G730AP is operating in Router mode. To run the setup wizard, establish a wireless connection with the DWL-G730AP and follow the steps below.

To use the DWL-G730AP as a router, toggle the switch on the back of the unit.

- Open the Web browser
- Type in the **IP address** of the router (http://192.168.0.30)


Note: if you have changed the default IP address assigned to the DWL-G730AP, make sure to enter the correct IP address.

- Type **admin** in the **User Name** field
- Leave the **Password** blank
- Click **OK**



Home > Wizard

The Home>Wizard screen will appear. Please refer to the *Quick Installation Guide* for more information regarding the Setup Wizard.



Using the Configuration Utility in Router Mode (continued)

Home > Wireless

SSID-

Service Set Identifier (SSID) is the name designated for a specific wireless local area network (WLAN). The SSID's factory default setting is **default**. The SSID can be easily changed to connect to an existing wireless network or to establish a new wireless network.

The screenshot shows the D-Link configuration utility for a DWL-G730AP router. The 'Wireless' tab is selected in the left sidebar. The main content area is titled 'Wireless Settings' and contains the following fields and options:

- SSID: default
- Channel: 6
- Authentication: ☒ Open System, ☐ Shared Key, ☐ WPA-PSK
- WEP: ☐ Enabled, ☒ Disabled
- WEP Encryption: 64Bit
- Key Type: HEX
- Key1:
- Key2:
- Key3:
- Key4:

At the bottom right, there are three icons: a green checkmark, a red X, and a red plus sign, with the labels 'Apply', 'Cancel', and 'Help' respectively.

Channel-

6 is the default channel. All devices on the network must share the same channel.

Authentication-

Select **Open System** to communicate the key across the network.

Select **Shared Key** to limit communication only to those devices that share the same WEP settings.

Select **WPA-PSK** to select *Wi-Fi Protected Access* without a RADIUS server.

WEP-

Wired Equivalent Privacy (WEP) is a wireless security protocol for Wireless Local Area Networks (WLAN). WEP provides security by encrypting the data that is sent over the WLAN. Select **Enabled** or **Disabled**. **Disabled** is the default setting.

WEP Encryption-

Select the level of encryption desired: 64-bit, or 128-bit.

Key Type-

Select **HEX** or **ASCII**.

Keys 1-4-

Input up to 4 WEP keys; select the one you wish to use.

Using the Configuration Utility in Router Mode (continued)

Home > Wireless > WPA-PSK

SSID: (Service Set Identifier) default is the default setting. The SSID is a unique name that identifies a network. All devices on a network must share the same SSID name in order to communicate on the network. If you choose to change the SSID from the default setting, input your new SSID name in this field.

Channel: Channel **6** is the default channel. Input a

new number if you want to change the default setting. All devices on the network must be set to the same channel to communicate on the network.

Authentication:

When **WPA-PSK** is selected fill in the following fields:

Passphrase: Enter the Passphrase here.

Confirmed Passphrase: Confirm the Passphrase here.

Apply: Click **Apply** to apply the changes.

The screenshot shows the D-Link configuration utility for a DWL-G730AP router. The 'Wireless Settings' tab is active. The SSID is set to 'default'. The Channel is set to '6'. The Authentication is set to 'WPA-PSK'. There are fields for 'Passphrase' and 'Confirmed Passphrase'. The 'Apply' button is highlighted with a green checkmark, indicating it is the next step.

Using the Configuration Utility in **Router Mode** (continued)

Home > WAN > Dynamic IP Address

Dynamic IP Address is selected here.

Other options include:
Static IP Address
(if your ISP provides you with a static IP address), **PPPoE** (for most DSL users), **PPTP** (for Europe) and **BigPond Cable** (for Australia).

The screenshot shows the D-Link AirPlus G 802.11g/2.4GHz Wireless Router configuration utility. On the left is a sidebar with buttons for Wizard, Wireless, WAN (highlighted), LAN, and DHCP. The main area is titled 'WAN Settings' and asks the user to select an option to connect to their ISP. The 'Dynamic IP Address' option is selected. Below this, the 'Dynamic IP' section contains fields for Host Name (DWL-G730AP), MAC Address (00-2C-5E-98-70-B4), Primary DNS Address (0.0.0.0), Secondary DNS Address (0.0.0.0), and MTU (1500). A 'Clone MAC Address' button is located between the MAC Address and Primary DNS Address fields. At the bottom right are 'Apply', 'Cancel', and 'Help' buttons.

Dynamic IP Address-

Choose **Dynamic IP Address** to obtain an IP address automatically.

Host Name-

The Host Name is optional but may be required by some ISPs. The default host name is the device name of the router and may be changed.

MAC Address-

The default MAC address is set to the WAN's physical interface MAC address on the router. It is not recommended that you change the default MAC address unless required by your ISP.

Clone MAC Address-

The default MAC address is set to the WAN's physical interface MAC address on the router. You can use the "Clone MAC Address" button to copy the MAC address of the Ethernet Card installed by your ISP and replace the WAN MAC address with the MAC address of the router. It is not recommended that you change the default MAC address unless required by your ISP.

Primary/Secondary DNS Address-

Enter a DNS address if you do not wish to use the one provided by your ISP.

MTU-

Maximum Transmission Unit-1500 is the default setting- Enter an MTU value only if required by your ISP. Otherwise, leave it at the default setting.

Using the Configuration Utility in Router Mode (continued)

Home > LAN


Building Networks for People



Wizard

Wireless

WAN

LAN

DHCP

AirPlus G™
802.11g/2.4GHz Wireless Router

Home

Advanced

Tools

Status

Help

LAN Settings

The IP address of the DWL-G730AP.

IP Address

192.168.0.30

Subnet Mask

255.255.255.0

Local Domain Name

(optional)







Apply Cancel Help

LAN is short for Local Area Network. This is considered your internal network. These are the IP settings of the LAN interface for the DWL-G730AP. These settings may be referred to as Private settings. You may change the LAN IP address if needed. The LAN IP address is private to your internal network and cannot be seen on the Internet.

IP Address-

The IP address of the LAN interface. The default IP address is:
192.168.0.30

Subnet Mask-

The subnet mask of the LAN interface.
The default subnet mask is **255.255.255.0**

Local Domain-

This field is optional. Enter in the local domain name.


39

Using the Configuration Utility in Router Mode (continued)

Home > DHCP

DHCP stands for *Dynamic Host Control Protocol*.

The DWL-G730AP has a built-in DHCP server. The DHCP Server will automatically assign an IP address to the computers on the LAN/private network. Be sure to set your computers to be DHCP clients by setting their TCP/IP settings to “Obtain an IP Address Automatically.” When you turn your computers on, they will automatically load the proper TCP/IP settings provided by the DWL-G730AP. The DHCP server will automatically allocate an unused IP address from the IP address pool to the requesting computer. You must specify the starting and ending address of the IP address pool.



DHCP Server- Select **Enabled** or **Disabled**. The **default** setting is **Enabled**.

Starting IP Address- The starting IP address for the DHCP server’s IP assignment.

Ending IP Address- The ending IP address for the DHCP server’s IP assignment.

Lease Time- The length of time for the IP lease. Enter the Lease time. The default setting is one hour.

Static DHCP is used to allow the DHCP server to assign some Static IP addresses via specific MAC addresses.

Static DHCP- Select **Enabled** or **Disabled**.

Name- Enter a name here.

IP- Enter the last digits of the IP address here.

MAC Address- Enter the MAC address of the computer that will be assigned the Static DHCP IP address.

DHCP Client- Use this pull-down list to list DHCP clients on your network. To copy the MAC address into the MAC address section above, simply select the client from the pull-down list and click the **Clone** button.