

FCC RF Test Report

APPLICANT : D-Link Co.
EQUIPMENT : Wireless N300 Mini Router
BRAND NAME : D-Link
MODEL NAME : DIR-513A
FCC ID : KA2IR513AA1
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Aug. 05, 2014 and testing was completed on Oct. 15, 2014. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification subjective to this standard	6
1.5 Modification of EUT	6
1.6 Testing Location	7
1.7 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency and Channel	8
2.2 Pre-Scanned RF Power.....	9
2.3 Test Mode.....	11
2.4 Connection Diagram of Test System.....	12
2.5 Support Unit used in test configuration and system	13
2.6 EUT Operation Test Setup	13
2.7 Measurement Results Explanation Example.....	13
3 TEST RESULT	14
3.1 6dB Bandwidth Measurement	14
3.2 Peak Output Power Measurement	17
3.3 Power Spectral Density Measurement	20
3.4 Conducted Band Edges and Spurious Emission Measurement	23
3.5 Radiated Band Edges and Spurious Emission Measurement	48
3.6 AC Conducted Emission Measurement.....	52
3.7 Antenna Requirements.....	58
4 LIST OF MEASURING EQUIPMENT	60
5 UNCERTAINTY OF EVALUATION	61
APPENDIX A. TEST RESULT OF RADIATED TEST RESULTS	
APPENDIX B. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR480567	Rev. 01	Initial issue of report	Oct. 20, 2014



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	RSS-210 A8.2(a)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	RSS-210 A8.4	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	RSS-210 A8.2(b)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	RSS-210 A8.5	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
			Conducted Spurious Emission		Pass	-
3.5	15.247(d)	RSS-210 A8.5	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 0.15 dB at 2388.660 MHz
3.6	15.207	RSS-Gen 7.2.4	AC Conducted Emission	15.207(a)	Pass	Under limit 7.90 dB at 0.566 MHz
3.7	15.203 & 15.247(b)	RSS-210 A8.4	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

D-Link Co.

No. 289, Sinhu 3rd Rd., Neihu District Taipei City 114 Taiwan

1.2 Manufacturer

SHENZHEN MTN ELECTRONIC CO., LTD.

MTN Industrial Park, No. 9, Futai Road, Pingxi community, Pingdi Street, Longgang District, Shenzhen, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Wireless N300 Mini Router
Brand Name	D-Link
Model Name	DIR-513A
FCC ID	KA2IR513AA1
EUT supports Radios application	WLAN 11b/g/n (HT20/HT40)
HW Version	A1
SW Version	1.00
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard			
Tx/Rx Channel Frequency Range	802.11b/g/n : 2412 MHz ~ 2462 MHz		
Maximum Output Power to antenna	SISO <Ant 1> 802.11b : 15.82 dBm (0.0382 W) 802.11g : 24.93 dBm (0.3112 W) 802.11n HT20 : 24.89 dBm (0.3083 W) 802.11n HT40 : 23.66 dBm (0.2323 W) SISO <Ant 2> 802.11b : 15.32 dBm (0.0340 W) 802.11g : 24.51 dBm (0.2825 W) 802.11n HT20 : 25.17 dBm (0.3289 W) 802.11n HT40 : 23.51 dBm (0.2244 W) MIMO <Ant 1+2> 802.11b : 18.98 dBm (0.0791 W) 802.11g : 28.02 dBm (0.6339 W) 802.11n HT20 : 28.31 dBm (0.6776 W) 802.11n HT40 : 26.82 dBm (0.4808 W)		
Antenna Type	<Ant 1> 802.11b/g/n : FPC Antenna with gain 0.68 dBi <Ant 2> 802.11b/g/n : FPC Antenna with gain 1.53 dBi		
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)		
Antenna Function for Transmitter		Chain Port 0 Ant. 1	Chain Port 1 Ant. 2
	802.11 b/g/n SISO	V	V
	802.11 b/g/n MIMO	V	V

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		
	TH02-HY	CO05-HY	03CH05HY

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.4-2003

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

SISO <Ant. 1>

802.11b				
Data Rate (MHz)	1M bps	2M bps	5.5M bps	11M bps
Peak Power (dBm)	15.82	15.80	15.79	15.77

802.11g								
Data Rate (MHz)	6M bps	9M bps	12M bps	18M bps	24M bps	36M bps	48M bps	54M bps
Peak Power (dBm)	24.93	24.59	24.42	24.45	24.90	24.41	24.80	21.70

2.4GHz 802.11n HT20								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	24.89	24.87	24.82	24.35	24.31	24.50	24.81	24.87

2.4GHz 802.11n HT40								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	23.66	23.56	23.34	23.30	23.51	23.64	23.11	22.67

SISO <Ant. 2>

802.11b				
Data Rate (MHz)	1M bps	2M bps	5.5M bps	11M bps
Peak Power (dBm)	15.32	15.31	15.29	15.25

802.11g								
Data Rate (MHz)	6M bps	9M bps	12M bps	18M bps	24M bps	36M bps	48M bps	54M bps
Peak Power (dBm)	24.51	24.08	23.72	23.85	24.31	23.66	24.15	24.01

2.4GHz 802.11n HT20								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	25.17	24.96	25.16	24.53	24.41	24.50	24.87	25.01

2.4GHz 802.11n HT40								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	23.51	23.48	23.36	23.26	23.35	23.24	22.90	22.65

**MIMO <Ant. 1+2>**

802.11b								
Data Rate (MHz)	1M bps	2M bps	5.5M bps	11M bps				
Peak Power (dBm)	18.98	18.77	18.74	18.94				

802.11g								
Data Rate (MHz)	6M bps	9M bps	12M bps	18M bps	24M bps	36M bps	48M bps	54M bps
Peak Power (dBm)	28.02	27.84	27.51	27.70	28.01	27.93	27.89	27.94

2.4GHz 802.11n HT20								
Data Rate (MHz)	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
Peak Power (dBm)	28.31	28.19	28.13	28.07	27.92	28.09	28.19	28.20

2.4GHz 802.11n HT40								
Data Rate (MHz)	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
Peak Power (dBm)	26.82	26.65	26.30	26.71	26.80	26.71	26.57	26.53

Note: MIMO Ant. 1+2 is a calculated result from sum of the power MIMO Ant. 1 and MIMO Ant. 2.


2.3 Test Mode

Final results of test modes, data rates and test channels are shown as following table.


Test Cases				
Conducted TCs	Test Items	Mode	Data Rate	Test Channel
	6dB and 99% BW Power Spectral Density	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
	Output Power	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
	Conducted Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	MCS0	1/11
		802.11n HT40	MCS0	3/9
	Conducted Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
Radiated TCs	Radiated Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	MCS0	1/11
		802.11n HT40	MCS0	3/9
	Radiated Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
Test Cases				
AC Conducted Emission	Mode 1 : EUT with Adapter + WLAN Link + RJ-45 Link + iPod			

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
2.	Notebook	DELL	P20G	FCC DoC/ Contains FCC ID:QDS-BRCM1051	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Notebook	DELL	N4110	FCC DoC/ Contains FCC ID: QDS-BRCM1051	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m

2.6 EUT Operation Test Setup

For WLAN function, programmed RF utility, "Test Tool" installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Test Band :	2.4GHz	Temperature :	21~26°C
Test Engineer :	Alex Lee and Derreck Chen	Relative Humidity :	45~54%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	99% Bandwidth (MHz)		6dB Bandwidth (MHz)		6dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant. 1	Ant. 2	Ant. 1	Ant. 2		
11b	1Mbps	2	1	2412			9.58	10.04	0.5	Pass
11b	1Mbps	2	6	2437			10.00	9.30	0.5	Pass
11b	1Mbps	2	11	2462			10.06	9.76	0.5	Pass
11g	6Mbps	2	1	2412			16.34	16.34	0.5	Pass
11g	6Mbps	2	6	2437			16.30	16.32	0.5	Pass
11g	6Mbps	2	11	2462			16.32	16.34	0.5	Pass
HT20	MCS0	2	1	2412			17.08	17.08	0.5	Pass
HT20	MCS0	2	6	2437			17.02	17.30	0.5	Pass
HT20	MCS0	2	11	2462			17.06	17.30	0.5	Pass
HT40	MCS0	2	3	2422			36.28	36.24	0.5	Pass
HT40	MCS0	2	6	2437			36.28	35.68	0.5	Pass
HT40	MCS0	2	9	2452			36.00	35.92	0.5	Pass



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Peak Output Power Measurement

3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup





3.2.5 Test Result of Peak Output Power

Test Band :	2.4GHz	Temperature :	21~26℃
Test Engineer :	Alex Lee and Derreck Chen	Relative Humidity :	45~54%

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Max. Limit (dBm)		DG (dBi)		Pass/Fail
					Ant. 1	Ant. 2	SUM	Ant. 1	Ant. 2	Ant. 1	Ant. 2	
11b	1Mbps	1	1	2412	14.70	15.02	-	30.00	30.00	0.68	1.53	Pass
11b	1Mbps	1	6	2437	14.19	14.29		30.00	30.00	0.68	1.53	Pass
11b	1Mbps	1	11	2462	15.82	15.32		30.00	30.00	0.68	1.53	Pass
11g	6Mbps	1	1	2412	23.16	23.29		30.00	30.00	0.68	1.53	Pass
11g	6Mbps	1	6	2437	24.93	24.51		30.00	30.00	0.68	1.53	Pass
11g	6Mbps	1	11	2462	23.95	23.83		30.00	30.00	0.68	1.53	Pass
HT20	MCS0	1	1	2412	22.59	22.47		30.00	30.00	0.68	1.53	Pass
HT20	MCS0	1	6	2437	24.89	25.17		30.00	30.00	0.68	1.53	Pass
HT20	MCS0	1	11	2462	22.08	21.48		30.00	30.00	0.68	1.53	Pass
HT40	MCS0	1	3	2422	21.03	20.84		30.00	30.00	0.68	1.53	Pass
HT40	MCS0	1	6	2437	23.66	23.51		30.00	30.00	0.68	1.53	Pass
HT40	MCS0	1	9	2452	19.95	20.14		30.00	30.00	0.68	1.53	Pass
11b	1Mbps	2	1	2412	15.14	15.45	18.31	30.00		4.13		Pass
11b	1Mbps	2	6	2437	14.35	14.32	17.35	30.00		4.13		Pass
11b	1Mbps	2	11	2462	16.12	15.81	18.98	30.00		4.13		Pass
11g	6Mbps	2	1	2412	23.57	23.68	26.64	30.00		4.13		Pass
11g	6Mbps	2	6	2437	25.05	24.96	28.02	30.00		4.13		Pass
11g	6Mbps	2	11	2462	24.29	24.04	27.18	30.00		4.13		Pass
HT20	MCS0	2	1	2412	22.62	22.65	25.64	30.00		4.13		Pass
HT20	MCS0	2	6	2437	25.24	25.35	28.31	30.00		4.13		Pass
HT20	MCS0	2	11	2462	22.21	21.88	25.06	30.00		4.13		Pass
HT40	MCS0	2	3	2422	21.11	21.19	24.16	30.00		4.13		Pass
HT40	MCS0	2	6	2437	23.76	23.85	26.82	30.00		4.13		Pass
HT40	MCS0	2	9	2452	20.06	20.26	23.17	30.00		4.13		Pass

Note: Measured power (dBm) has offset with cable loss.



3.2.6 Test Result of Average output Power (Reporting Only)

Test Band :	2.4GHz	Temperature :	21~26℃
Test Engineer :	Alex Lee and Derreck Chen	Relative Humidity :	45~54%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)		
					Ant. 1	Ant. 2	Ant. 1	Ant. 2	Sum Power
11b	1Mbps	1	1	2412	0.10	0.10	11.25	11.61	-
11b	1Mbps	1	6	2437	0.10	0.10	10.80	10.95	
11b	1Mbps	1	11	2462	0.10	0.10	12.47	11.97	
11g	6Mbps	1	1	2412	0.57	0.57	13.05	13.40	
11g	6Mbps	1	6	2437	0.57	0.57	16.05	15.19	
11g	6Mbps	1	11	2462	0.57	0.57	14.25	14.02	
HT20	MCS0	1	1	2412	0.60	0.60	12.97	12.80	
HT20	MCS0	1	6	2437	0.60	0.60	16.35	16.35	
HT20	MCS0	1	11	2462	0.60	0.60	12.58	11.85	
HT40	MCS0	1	3	2422	1.13	1.13	7.94	11.03	
HT40	MCS0	1	6	2437	1.13	1.13	14.35	14.45	
HT40	MCS0	1	9	2452	1.13	1.13	10.11	10.35	
11b	1Mbps	2	1	2412	0.10	0.10	11.62	11.97	14.81
11b	1Mbps	2	6	2437	0.10	0.10	10.62	10.70	13.67
11b	1Mbps	2	11	2462	0.10	0.10	12.50	12.10	15.31
11g	6Mbps	2	1	2412	0.62	0.57	14.00	14.08	17.05
11g	6Mbps	2	6	2437	0.62	0.57	16.72	16.57	19.65
11g	6Mbps	2	11	2462	0.62	0.57	14.93	14.67	17.81
HT20	MCS0	2	1	2412	0.66	0.66	13.16	13.22	16.20
HT20	MCS0	2	6	2437	0.66	0.66	17.72	17.93	20.84
HT20	MCS0	2	11	2462	0.66	0.66	12.68	12.34	15.52
HT40	MCS0	2	3	2422	1.13	1.18	11.08	11.30	14.21
HT40	MCS0	2	6	2437	1.13	1.18	14.44	14.63	17.55
HT40	MCS0	2	9	2452	1.13	1.18	10.28	10.17	13.24

Note: Measured power (dBm) has offset with cable loss and duty factor.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.


If measurements performed using method (2) plus $10 \log(N)$ exceeds the emission limit, the test should choose method (1) before declaring that the device fails the emission limit.

Method (1): Measure and sum the spectra across the outputs.

The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.

Method (2): Measure and add $10 \log(N)$ dB, where N is the number of outputs. (N=2)

3.3.4 Test Setup




3.3.5 Test Result of Power Spectral Density

Test Band :	2.4GHz	Temperature :	21~26°C
Test Engineer :	Alex Lee and Derreck Chen	Relative Humidity :	45~54%

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak Power Density (dBm/3kHz)			Max. Limit (dBm/3kHz)		DG (dBi)		Pass/Fail
					Ant. 1	Ant. 2	Worst +10log(2)	Ant. 1	Ant. 2	Ant. 1	Ant. 2	
11b	1Mbps	2	1	2412	-15.28	-15.10	-12.09	4.13		8.00		Pass
11b	1Mbps	2	6	2437	-15.16	-15.52	-12.15	4.13		8.00		Pass
11b	1Mbps	2	11	2462	-13.33	-14.83	-10.32	4.13		8.00		Pass
11g	6Mbps	2	1	2412	-14.78	-14.11	-11.10	4.13		8.00		Pass
11g	6Mbps	2	6	2437	-10.84	-11.47	-7.83	4.13		8.00		Pass
11g	6Mbps	2	11	2462	-13.45	-13.53	-10.44	4.13		8.00		Pass
HT20	MCS0	2	1	2412	-14.80	-13.56	-10.55	4.13		8.00		Pass
HT20	MCS0	2	6	2437	-10.42	-10.32	-7.31	4.13		8.00		Pass
HT20	MCS0	2	11	2462	-15.29	-14.86	-11.85	4.13		8.00		Pass
HT40	MCS0	2	3	2422	-19.71	-18.58	-15.57	4.13		8.00		Pass
HT40	MCS0	2	6	2437	-17.14	-16.20	-13.19	4.13		8.00		Pass
HT40	MCS0	2	9	2452	-19.88	-20.73	-16.87	4.13		8.00		Pass

Note: Measured power density (dBm) has offset with cable loss.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission




Number of TX = 2, Ant. 1 (Measured)

Number of TX :	2	Ant. :	1
Test Mode :	802.11b	Temperature :	21~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~54%
Test Channel :	01	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11b Channel 01


100kHz PSD reference Level



4

Date: 8.OCT.2014 10:26:50


Low Channel Plot



4

Date: 8.OCT.2014 10:27:11


Spurious Emission 30MHz~3GHz



4

Date: 8.OCT.2014 10:27:34

Spurious Emission 2GHz~25GHz



4


Date: 8.OCT.2014 10:27:52



Number of TX :	2	Ant. :	1
Test Mode :	802.11b	Temperature :	21~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11b Channel 06


100kHz PSD reference Level



4

Date: 8.OCT.2014 12:24:27


Spurious Emission 30MHz~3GHz



4

Date: 8.OCT.2014 12:25:06

Spurious Emission 2GHz~25GHz



4


Date: 8.OCT.2014 12:25:24



Number of TX :	2	Ant. :	1
Test Mode :	802.11b	Temperature :	21~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~54%
Test Channel :	11	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11b Channel 11


100kHz PSD reference Level



4

Date: 8.OCT.2014 12:50:21


High Channel Plot



4

Date: 8.OCT.2014 12:50:40


Spurious Emission 30MHz~3GHz



4

Date: 8.OCT.2014 12:51:09

Spurious Emission 2GHz~25GHz



4


Date: 8.OCT.2014 12:51:27



Number of TX :	2	Ant. :	1
Test Mode :	802.11g	Temperature :	21~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~54%
Test Channel :	01	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11g Channel 01


100kHz PSD reference Level



4

Date: 8.OCT.2014 13:15:18


Low Channel Plot



4

Date: 8.OCT.2014 13:15:38


Spurious Emission 30MHz~3GHz



4

Date: 8.OCT.2014 13:16:04

Spurious Emission 2GHz~25GHz



4


Date: 8.OCT.2014 13:16:22



Number of TX :	2	Ant. :	1
Test Mode :	802.11g	Temperature :	21~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11g Channel 06


100kHz PSD reference Level



4

Date: 8.OCT.2014 13:29:28


Spurious Emission 30MHz~3GHz



4

Date: 8.OCT.2014 13:30:30

Spurious Emission 2GHz~25GHz



4


Date: 8.OCT.2014 13:30:48



Number of TX :	2	Ant. :	1
Test Mode :	802.11g	Temperature :	21~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~54%
Test Channel :	11	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11g Channel 11


100kHz PSD reference Level



4

Date: 8.OCT.2014 13:44:32


High Channel Plot



4

Date: 8.OCT.2014 13:44:52


Spurious Emission 30MHz~3GHz



4

Date: 8.OCT.2014 13:45:20

Spurious Emission 2GHz~25GHz







4

Date: 8.OCT.2014 13:45:38



Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT20	Temperature :	21~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~54%
Test Channel :	01	Test Engineer :	Alex Lee and Derreck Chen


WLAN 802.11n HT20 Channel 01**100kHz PSD reference Level****Low Channel Plot****Spurious Emission 30MHz~3GHz****Spurious Emission 2GHz~25GHz**



Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT20	Temperature :	21~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11n HT20 Channel 06


100kHz PSD reference Level



4

Date: 8.OCT.2014 14:34:52


Spurious Emission 30MHz~3GHz



4

Date: 8.OCT.2014 14:35:16

Spurious Emission 2GHz~25GHz



4


Date: 8.OCT.2014 14:35:33



Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT20	Temperature :	21~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~54%
Test Channel :	11	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11n HT20 Channel 11


100kHz PSD reference Level



4

Date: 8.OCT.2014 14:45:33


High Channel Plot



4

Date: 8.OCT.2014 14:45:52


Spurious Emission 30MHz~3GHz



4

Date: 8.OCT.2014 14:46:17

Spurious Emission 2GHz~25GHz




4


Date: 8.OCT.2014 14:46:35




Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT40	Temperature :	21~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~54%
Test Channel :	03	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11n HT40 Channel 03**100kHz PSD reference Level**


Date: 13.OCT.2014 17:39:54

Low Channel Plot

Date: 13.OCT.2014 17:40:10

Spurious Emission 30MHz~3GHz

Date: 15.OCT.2014 18:00:30

Spurious Emission 2GHz~25GHz


Date: 15.OCT.2014 17:57:50



Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT40	Temperature :	21~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Alex Lee and Derreck Chen


WLAN 802.11n HT40 Channel 06

100kHz PSD reference Level




Date: 13.OCT.2014 16:36:07

Spurious Emission 30MHz~3GHz



Date: 13.OCT.2014 18:20:11

Spurious Emission 2GHz~25GHz




Date: 13.OCT.2014 18:25:29



Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT40	Temperature :	21~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~54%
Test Channel :	09	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11n HT40 Channel 09


100kHz PSD reference Level



4

Date: 8.OCT.2014 15:55:03


High Channel Plot



4

Date: 8.OCT.2014 15:55:24


Spurious Emission 30MHz~3GHz



4

Date: 8.OCT.2014 15:57:00

Spurious Emission 2GHz~25GHz




4

Date: 8.OCT.2014 15:56:06


**Number of TX = 2, Ant. 2 (Measured)**

Number of TX :	2	Ant. :	2
Test Mode :	802.11b	Temperature :	21~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~54%
Test Channel :	01	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11b Channel 01**100kHz PSD reference Level**


4

Date: 8.OCT.2014 10:38:10

Low Channel Plot


4

Date: 8.OCT.2014 10:38:29

Spurious Emission 30MHz~3GHz

4

Date: 8.OCT.2014 10:38:56


Spurious Emission 2GHz~25GHz

4

Date: 8.OCT.2014 10:39:14




Number of TX :	2	Ant. :	2
Test Mode :	802.11b	Temperature :	21~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11b Channel 06**100kHz PSD reference Level**


4

Date: 8.OCT.2014 12:35:30

Spurious Emission 30MHz~3GHz

4

Date: 8.OCT.2014 12:35:52

Spurious Emission 2GHz~25GHz

4


Date: 8.OCT.2014 12:36:09



Number of TX :	2	Ant. :	2
Test Mode :	802.11b	Temperature :	21~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~54%
Test Channel :	11	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11b Channel 11


100kHz PSD reference Level



4

Date: 8.OCT.2014 13:02:41


High Channel Plot



4

Date: 8.OCT.2014 13:02:59


Spurious Emission 30MHz~3GHz



4

Date: 8.OCT.2014 13:03:27

Spurious Emission 2GHz~25GHz




4

Date: 8.OCT.2014 13:03:45




Number of TX :	2	Ant. :	2
Test Mode :	802.11g	Temperature :	21~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~54%
Test Channel :	01	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11g Channel 01**100kHz PSD reference Level**


4

Date: 8.OCT.2014 13:19:55

Low Channel Plot


4

Date: 8.OCT.2014 13:20:14

Spurious Emission 30MHz~3GHz

4

Date: 8.OCT.2014 13:20:49

Spurious Emission 2GHz~25GHz

4


Date: 8.OCT.2014 13:21:07



Number of TX :	2	Ant. :	2
Test Mode :	802.11g	Temperature :	21~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11g Channel 06


100kHz PSD reference Level



4

Date: 8.OCT.2014 13:37:11


Spurious Emission 30MHz~3GHz



4

Date: 8.OCT.2014 13:37:57

Spurious Emission 2GHz~25GHz




4

Date: 8.OCT.2014 13:38:15




Number of TX :	2	Ant. :	2
Test Mode :	802.11g	Temperature :	21~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~54%
Test Channel :	11	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11g Channel 11**100kHz PSD reference Level**


4

Date: 8.OCT.2014 13:54:11

High Channel Plot


4

Date: 8.OCT.2014 13:54:29

Spurious Emission 30MHz~3GHz

4

Date: 8.OCT.2014 13:55:02

Spurious Emission 2GHz~25GHz

4


Date: 8.OCT.2014 13:55:20



Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT20	Temperature :	21~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~54%
Test Channel :	01	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11n HT20 Channel 01


100kHz PSD reference Level



4

Date: 8.OCT.2014 14:27:12


Low Channel Plot



4

Date: 8.OCT.2014 14:27:32


Spurious Emission 30MHz~3GHz



4

Date: 8.OCT.2014 14:29:06

Spurious Emission 2GHz~25GHz



4


Date: 8.OCT.2014 14:29:24



Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT20	Temperature :	21~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11n HT20 Channel 06


100kHz PSD reference Level



4

Date: 8.OCT.2014 14:38:32


Spurious Emission 30MHz~3GHz



4

Date: 8.OCT.2014 14:38:55

Spurious Emission 2GHz~25GHz



4


Date: 8.OCT.2014 14:39:13



Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT20	Temperature :	21~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~54%
Test Channel :	11	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11n HT20 Channel 11


100kHz PSD reference Level



4

Date: 8.OCT.2014 14:54:08


High Channel Plot



4

Date: 8.OCT.2014 14:54:39


Spurious Emission 30MHz~3GHz



4

Date: 8.OCT.2014 14:55:02

Spurious Emission 2GHz~25GHz



4


Date: 8.OCT.2014 14:55:20



Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT40	Temperature :	21~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~54%
Test Channel :	03	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11n HT40 Channel 03


100kHz PSD reference Level



4

Date: 8.OCT.2014 15:28:22


Low Channel Plot



4

Date: 8.OCT.2014 15:28:40


Spurious Emission 30MHz~3GHz



4

Date: 8.OCT.2014 15:34:21

Spurious Emission 2GHz~25GHz



4


Date: 8.OCT.2014 15:29:30



Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT40	Temperature :	21~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Alex Lee and Derreck Chen


WLAN 802.11n HT40 Channel 06

100kHz PSD reference Level




Date: 13.OCT.2014 17:20:34

Spurious Emission 30MHz~3GHz



Date: 13.OCT.2014 18:31:54


Spurious Emission 2GHz~25GHz




Date: 13.OCT.2014 17:27:13




Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT40	Temperature :	21~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~54%
Test Channel :	09	Test Engineer :	Alex Lee and Derreck Chen

WLAN 802.11n HT40 Channel 09**100kHz PSD reference Level**


Date: 13.OCT.2014 17:52:13

High Channel Plot

Date: 13.OCT.2014 17:52:43

Spurious Emission 30MHz~3GHz

Date: 13.OCT.2014 17:57:29

Spurious Emission 2GHz~25GHz

Date: 13.OCT.2014 18:36:44

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.


For average measurement:

 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
1+2	802.11b for Ant 1	97.76	8720	0.11	300Hz
1+2	802.11b for Ant 2	97.75	8680	0.12	
1+2	802.11g for Ant 1	86.75	1440	0.69	1kHz
1+2	802.11g for Ant 2	87.80	1440	0.69	
1+2	2.4GHz 802.11n HT20 for Ant 1	85.90	1340	0.75	
1+2	2.4GHz 802.11n HT20 for Ant 2	85.90	1340	0.75	
1+2	2.4GHz 802.11n HT40 for Ant 1	77.01	670	1.49	3kHz
1+2	2.4GHz 802.11n HT40 for Ant 2	76.14	670	1.49	

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result

Please refer to Sporton report number appendix A as below.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission


Test Mode :	Mode 1	Temperature :	20~22℃
Test Engineer :	Kai-Chun Chu	Relative Humidity :	46~48%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	EUT with Adapter + WLAN Link + RJ-45 Link + iPod		



Final Result : QuasiPeak


Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.566000	45.0	Off	L1	19.4	11.0	56.0
0.982000	40.4	Off	L1	19.5	15.6	56.0
1.070000	39.9	Off	L1	19.5	16.1	56.0
1.230000	39.2	Off	L1	19.5	16.8	56.0
1.350000	40.6	Off	L1	19.5	15.4	56.0
1.446000	39.8	Off	L1	19.5	16.2	56.0
1.598000	39.1	Off	L1	19.5	16.9	56.0
1.726000	40.1	Off	L1	19.5	15.9	56.0
1.886000	38.3	Off	L1	19.5	17.7	56.0
2.014000	39.3	Off	L1	19.5	16.7	56.0
2.214000	40.4	Off	L1	19.6	15.6	56.0
2.542000	40.8	Off	L1	19.5	15.2	56.0
2.806000	39.5	Off	L1	19.6	16.5	56.0
3.118000	38.2	Off	L1	19.6	17.8	56.0
3.334000	40.8	Off	L1	19.6	15.2	56.0
3.486000	39.8	Off	L1	19.6	16.2	56.0
3.702000	41.0	Off	L1	19.5	15.0	56.0
3.862000	39.1	Off	L1	19.6	16.9	56.0
4.094000	39.9	Off	L1	19.6	16.1	56.0
4.262000	36.9	Off	L1	19.6	19.1	56.0
4.550000	36.6	Off	L1	19.6	19.4	56.0
4.702000	37.2	Off	L1	19.6	18.8	56.0

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	46~48%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	EUT with Adapter + WLAN Link + RJ-45 Link + iPod		


Final Result : Average


Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.566000	38.1	Off	L1	19.4	7.9	46.0
0.982000	32.7	Off	L1	19.5	13.3	46.0
1.070000	31.1	Off	L1	19.5	14.9	46.0
1.230000	29.0	Off	L1	19.5	17.0	46.0
1.350000	32.5	Off	L1	19.5	13.5	46.0
1.446000	31.1	Off	L1	19.5	14.9	46.0
1.598000	27.4	Off	L1	19.5	18.6	46.0
1.726000	31.5	Off	L1	19.5	14.5	46.0
1.886000	29.3	Off	L1	19.5	16.7	46.0
2.014000	28.2	Off	L1	19.5	17.8	46.0
2.214000	32.4	Off	L1	19.6	13.6	46.0
2.542000	31.9	Off	L1	19.5	14.1	46.0
2.806000	28.5	Off	L1	19.6	17.5	46.0
3.118000	27.2	Off	L1	19.6	18.8	46.0
3.334000	32.2	Off	L1	19.6	13.8	46.0
3.486000	29.6	Off	L1	19.6	16.4	46.0
3.702000	31.7	Off	L1	19.5	14.3	46.0
3.862000	29.1	Off	L1	19.6	16.9	46.0
4.094000	30.4	Off	L1	19.6	15.6	46.0
4.262000	27.7	Off	L1	19.6	18.3	46.0
4.550000	29.0	Off	L1	19.6	17.0	46.0
4.702000	26.5	Off	L1	19.6	19.5	46.0

Test Mode :	Mode 1	Temperature :	20~22℃
Test Engineer :	Kai-Chun Chu	Relative Humidity :	46~48%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	EUT with Adapter + WLAN Link + RJ-45 Link + iPod		


Final Result : QuasiPeak

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.494000	37.7	Off	N	19.4	18.4	56.1
0.582000	40.0	Off	N	19.4	16.0	56.0
0.790000	33.7	Off	N	19.5	22.3	56.0
0.998000	38.4	Off	N	19.5	17.6	56.0
1.326000	38.3	Off	N	19.5	17.7	56.0
1.414000	37.9	Off	N	19.5	18.1	56.0
1.598000	35.4	Off	N	19.5	20.6	56.0
1.686000	37.1	Off	N	19.6	18.9	56.0
1.966000	35.0	Off	N	19.6	21.0	56.0
2.190000	39.4	Off	N	19.6	16.6	56.0
2.662000	37.4	Off	N	19.5	18.6	56.0
2.918000	38.4	Off	N	19.5	17.6	56.0
3.222000	37.4	Off	N	19.6	18.6	56.0
3.382000	39.8	Off	N	19.6	16.2	56.0
3.718000	40.1	Off	N	19.6	15.9	56.0
4.006000	38.0	Off	N	19.6	18.0	56.0
4.134000	38.0	Off	N	19.6	18.0	56.0
4.702000	35.0	Off	N	19.6	21.0	56.0

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	46~48%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	EUT with Adapter + WLAN Link + RJ-45 Link + iPod		


Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.494000	22.1	Off	N	19.4	24.0	46.1
0.582000	24.9	Off	N	19.4	21.1	46.0
0.790000	20.7	Off	N	19.5	25.3	46.0
0.998000	24.0	Off	N	19.5	22.0	46.0
1.326000	23.1	Off	N	19.5	22.9	46.0
1.414000	23.6	Off	N	19.5	22.4	46.0
1.598000	20.5	Off	N	19.5	25.5	46.0
1.686000	22.6	Off	N	19.6	23.4	46.0
1.966000	21.0	Off	N	19.6	25.0	46.0
2.190000	24.8	Off	N	19.6	21.2	46.0
2.662000	22.5	Off	N	19.5	23.5	46.0
2.918000	22.6	Off	N	19.5	23.4	46.0
3.222000	22.3	Off	N	19.6	23.7	46.0
3.382000	24.0	Off	N	19.6	22.0	46.0
3.718000	24.6	Off	N	19.6	21.4	46.0
4.006000	22.2	Off	N	19.6	23.8	46.0
4.134000	22.4	Off	N	19.6	23.6	46.0
4.702000	22.0	Off	N	19.6	24.0	46.0



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the Antenna exceeds 6 dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

For CDD transmissions, directional gain is calculated as

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k / 20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

The EUT supports CDD mode.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant. 1	Ant. 2	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
2.4 GHz	0.68	1.53	4.13	4.13	0.00	0.00

Power Limit Reduction = DG(Power) – 6dBi, (min = 0)

PSD Limit Reduction = DG(PSD) – 6dBi, (min = 0)



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 09, 2014	Aug. 13, 2014~ Oct. 15, 2014	Jun. 08, 2015	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	1036004	300MHz~40GHz	Aug. 09, 2014	Aug. 13, 2014~ Oct. 15, 2014	Aug. 08, 2015	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	1027253	300MHz~40GHz	Aug. 09, 2014	Aug. 13, 2014~ Oct. 15, 2014	Aug. 08, 2015	Conducted (TH02-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz ~ 2.75GHz	Nov. 15, 2013	Aug. 15, 2014	Nov. 14, 2014	Conduction (CO05-HY)
LISN (for auxiliary equipment)	Rohde & Schwarz	ENV216	100081	9kHz ~ 30MHz	Dec. 12, 2013	Aug. 15, 2014	Dec. 11, 2014	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz ~ 30MHz	Dec. 04, 2013	Aug. 15, 2014	Dec. 03, 2014	Conduction (CO05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Aug. 15, 2014	N/A	Conduction (CO05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 09, 2014	Sep. 08, 2014~ Sep. 26, 2014	Jun. 08, 2015	Radiation (03CH05-HY)
Bilog Antenna	Schaffner	CBL6111C	2725	30MHz~1GHz	Oct. 10, 2013	Sep. 08, 2014~ Sep. 26, 2014	Oct. 09, 2014	Radiation (03CH05-HY)
Double Ridged Guide Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1241	1GHz~18GHz	Apr. 16, 2014	Sep. 08, 2014~ Sep. 26, 2014	Apr. 15, 2015	Radiation (03CH05-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	18GHz~40GHz	Oct. 02, 2014	Sep. 08, 2014~ Sep. 26, 2014	Oct. 01, 2015	Radiation (03CH05-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590074	100kHz~18GHz	Jul. 07, 2014	Sep. 08, 2014~ Sep. 26, 2014	Jul. 06, 2015	Radiation (03CH05-HY)
Preamplifier	EMCI	EMC011830	980148	DC~18GHz	Jun. 23, 2014	Sep. 08, 2014~ Sep. 26, 2014	Jun. 22, 2015	Radiation (03CH05-HY)
Preamplifier	COM-POWER	PA-103	161075	9kHz~30MHz	Apr. 15, 2014	Sep. 08, 2014~ Sep. 26, 2014	Apr. 14, 2015	Radiation (03CH05-HY)
Preamplifier	Miteq	TTA0204	1872107	18GHz~40GHz	May 23, 2014	Sep. 08, 2014~ Sep. 26, 2014	May 22, 2015	Radiation (03CH05-HY)
Turn Table	HD	HD100	420/611	0 - 360 degree	N/A	Sep. 08, 2014~ Sep. 26, 2014	N/A	Radiation (03CH05-HY)
Antenna Mast	HD	HD100	240/666	1 m - 4 m	N/A	Sep. 08, 2014~ Sep. 26, 2014	N/A	Radiation (03CH05-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.10
---	------