Test Mode	IEEE 802.11n HT40 / 5270 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10540.00	Peak	35.22	11.41	46.63	68.20	-21.57
15810.00	Peak	39.00	14.04	53.04	74.00	-20.96
15810.00	Average	30.02	14.04	44.06	54.00	-9.94
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5270 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10540.00	Peak	31.54	11.41	42.95	68.20	-25.25
15810.00	Peak	39.67	14.04	53.71	74.00	-20.29
15810.00	Average	30.10	14.04	44.14	54.00	-9.86
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5310 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10620.00	Peak	39.64	11.52	51.16	74.00	-22.84
10620.00	Average	30.02	11.52	41.54	54.00	-12.46
15930.00	Peak	28.11	14.81	42.92	74.00	-31.08
15930.00	Average	21.22	14.81	36.03	54.00	-17.97

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5310 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10620.00	Peak	33.33	11.52	44.84	74.00	-29.16
10620.00	Average	25.75	11.52	37.27	54.00	-16.73
15930.00	Peak	28.84	14.81	43.65	74.00	-30.35
15930.00	Average	21.17	14.81	35.98	54.00	-18.02

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5290 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10580.00	Peak	32.95	11.48	44.43	68.20	-23.77
15870.00	Peak	29.81	14.34	44.15	74.00	-29.85
15870.00	Average	20.37	14.34	34.71	54.00	-19.29
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5290 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10580.00	Peak	31.94	11.48	43.42	68.20	-24.78
15870.00	Peak	29.81	14.34	44.15	74.00	-29.85
15870.00	Average	20.32	14.34	34.66	54.00	-19.34
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT160 / 5250 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10500.00	Peak	31.60	11.41	43.01	68.20	-25.19
15750.00	Peak	29.13	14.22	43.35	74.00	-30.65
15750.00	Average	21.13	14.22	35.35	54.00	-18.65
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT160 / 5250 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10500.00	Peak	31.34	11.41	42.75	68.20	-25.45
15750.00	Peak	29.74	14.22	43.96	74.00	-30.04
15750.00	Average	20.50	14.22	34.72	54.00	-19.28
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5260 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10520.00	Peak	33.66	11.41	45.07	68.20	-23.13
15780.00	Peak	43.80	14.08	57.88	74.00	-16.12
15780.00	Average	35.57	14.08	49.65	54.00	-4.35
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5260 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10520.00	Peak	34.67	11.41	46.08	68.20	-22.12
15780.00	Peak	43.21	14.08	57.29	74.00	-16.71
15780.00	Average	34.85	14.08	48.93	54.00	-5.07
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5300 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10600.00	Peak	44.33	11.53	55.86	68.20	-12.34
10600.00	Average	35.57	11.53	47.10	54.00	-6.90
15900.00	Peak	37.46	14.45	51.91	74.00	-22.09
15900.00	Average	32.23	14.45	46.68	54.00	-7.32

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5300 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10600.00	Peak	42.61	11.53	54.14	68.20	-14.06
10600.00	Average	33.85	11.53	45.38	54.00	-8.62
15900.00	Peak	43.60	14.45	58.05	74.00	-15.95
15900.00	Average	34.35	14.45	48.80	54.00	-5.20

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5320 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10640.00	Peak	43.74	11.50	55.24	74.00	-18.76
10640.00	Average	34.62	11.50	46.12	54.00	-7.88
15960.00	Peak	34.15	15.09	49.24	74.00	-24.76
15960.00	Average	25.99	15.09	41.08	54.00	-12.92

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5320 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10640.00	Peak	39.86	11.50	51.36	74.00	-22.64
10640.00	Average	31.44	11.50	42.94	54.00	-11.06
15960.00	Peak	28.21	15.09	43.29	74.00	-30.71
15960.00	Average	20.90	15.09	35.99	54.00	-18.01

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5270 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10540.00	Peak	36.27	11.41	47.68	68.20	-20.52
15810.00	Peak	34.25	14.04	48.29	74.00	-25.71
15810.00	Average	34.37	14.04	48.40	54.00	-5.60
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5270 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10540.00	Peak	34.70	11.41	46.11	68.20	-22.09
15810.00	Peak	34.33	14.04	48.36	74.00	-25.64
15810.00	Average	34.76	14.04	48.80	54.00	-5.20
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5310 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10620.00	Peak	35.92	11.52	47.44	74.00	-26.56
10620.00	Average	29.46	11.52	40.98	54.00	-13.02
15930.00	Peak	28.90	14.81	43.72	74.00	-30.28
15930.00	Average	24.47	14.81	39.29	54.00	-14.71

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5310 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10620.00	Peak	33.28	11.52	44.79	74.00	-29.21
10620.00	Average	26.50	11.52	38.02	54.00	-15.98
15930.00	Peak	29.73	14.81	44.54	74.00	-29.46
15930.00	Average	25.03	14.81	39.84	54.00	-14.16

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5290 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10580.00	Peak	32.90	11.48	44.38	68.20	-23.82
15870.00	Peak	29.12	14.34	43.46	74.00	-30.54
15870.00	Average	23.27	14.34	37.61	54.00	-16.39
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5290 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10580.00	Peak	32.38	11.48	43.86	68.20	-24.34
15870.00	Peak	28.54	14.34	42.88	74.00	-31.12
15870.00	Average	23.36	14.34	37.70	54.00	-16.30
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE160 / 5250 MHz	Temp/Hum	24.1℃)/ 58%RH
Test Item	Harmonic	Test Date	March 31, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10500.00	Peak	31.33	11.41	42.74	68.20	-25.46
15750.00	Peak	28.42	14.22	42.64	74.00	-31.36
15750.00	Average	23.28	14.22	37.50	54.00	-16.50
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE160 / 5250 MHz	Temp/Hum	24.1℃)/ 58%RH
Test Item	Harmonic	Test Date	March 31, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10500.00	Peak	31.18	11.41	42.59	68.20	-25.61
15750.00	Peak	29.91	14.22	44.13	74.00	-29.87
15750.00	Average	23.55	14.22	37.77	54.00	-16.23
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data for UNII-2c

(1) Chain 0:

Test Mode	IEEE 802.11a / 5500 MHz	Temp/Hum	21.8(℃)/ 53%RH
Test Item	Harmonic	Test Date	April 3, 2023
Polarize	Vertical	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11000.00	Peak	36.53	12.42	48.95	74.00	-25.05
11000.00	Average	29.62	12.42	42.04	54.00	-11.96
16500.00	Peak	28.73	18.70	47.43	68.20	-20.77
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5500 MHz	Temp/Hum	21.8(℃)/ 53%RH
Test Item	Harmonic	Test Date	April 3, 2023
Polarize	Horizontal	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11000.00	Peak	34.87	12.42	47.29	74.00	-26.71
11000.00	Average	27.43	12.42	39.85	54.00	-14.15
16500.00	Peak	29.07	18.70	47.77	68.20	-20.43
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5580 MHz	Temp/Hum	22.0(℃)/ 58%RH
Test Item	Harmonics	Test Date	April 6, 2023
Polarize	Vertical	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11160.00	Peak	41.36	12.48	53.84	74.00	-20.16
11160.00	Average	31.30	12.48	43.78	54.00	-10.22
16740.00	Peak	29.41	20.88	50.29	68.20	-17.91
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5580 MHz	Temp/Hum	22.0(℃)/ 58%RH
Test Item	Harmonic	Test Date	April 6, 2023
Polarize	Horizontal	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11160.00	Peak	39.58	12.48	52.06	74.00	-21.94
11160.00	Average	28.59	12.48	41.07	54.00	-12.93
16740.00	Peak	29.14	20.88	50.02	68.20	-18.18
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5700 MHz	Temp/Hum	22.0(℃)/ 58%RH
Test Item	Harmonic	Test Date	April 6, 2023
Polarize	Vertical	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11400.00	Peak	41.83	12.39	54.22	74.00	-19.78
11400.00	Average	31.83	12.39	44.22	54.00	-9.78
17100.00	Peak	28.27	25.62	53.89	68.20	-14.31
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5700 MHz	Temp/Hum	22.0(℃)/ 58%RH
Test Item	Harmonic	Test Date	April 6, 2023
Polarize	Horizontal	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11400.00	Peak	39.33	12.39	51.72	74.00	-22.28
11400.00	Average	29.66	12.39	42.05	54.00	-11.95
17100.00	Peak	28.71	25.62	54.33	68.20	-13.87
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data for UNII-2c

(2) Chain 1:

Test Mode	IEEE 802.11a / 5500 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11000.00	Peak	40.88	12.42	53.30	74.00	-20.70
11000.00	Average	32.02	12.42	44.44	54.00	-9.56
16500.00	Peak	28.71	18.70	47.41	68.20	-20.79
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5500 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11000.00	Peak	38.57	12.42	50.99	74.00	-23.01
11000.00	Average	30.36	12.42	42.78	54.00	-11.22
16500.00	Peak	29.21	18.70	47.91	68.20	-20.29
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5580 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonics	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11160.00	Peak	41.19	12.48	53.67	74.00	-20.33
11160.00	Average	33.46	12.48	45.94	54.00	-8.06
16740.00	Peak	30.09	20.88	50.96	68.20	-17.24
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5580 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11160.00	Peak	38.96	12.48	51.43	74.00	-22.57
11160.00	Average	29.46	12.48	41.94	54.00	-12.06
16740.00	Peak	29.26	20.88	50.14	68.20	-18.06
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5700 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11400.00	Peak	42.78	12.39	55.17	74.00	-18.83
11400.00	Average	33.27	12.39	45.66	54.00	-8.34
17100.00	Peak	29.18	25.62	54.80	68.20	-13.40
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5700 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Czerny Lin
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11400.00	Peak	41.73	12.39	54.12	74.00	-19.89
11400.00	Average	29.77	12.39	42.16	54.00	-11.84
17100.00	Peak	28.70	25.62	54.32	68.20	-13.88
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data for UNII-2c
(3) MIMO:

Test Mode	IEEE 802.11n HT20 / 5500 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11000.00	Peak	37.56	12.42	49.98	74.00	-24.02
11000.00	Average	33.96	12.42	46.38	54.00	-7.62
16500.00	Peak	27.83	18.70	46.53	68.20	-21.67
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5500 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11000.00	Peak	34.53	12.42	46.95	74.00	-27.05
11000.00	Average	30.70	12.42	43.12	54.00	-10.88
16500.00	Peak	27.75	18.70	46.45	68.20	-21.75
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5580 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11160.00	Peak	38.33	12.48	50.80	74.00	-23.20
11160.00	Average	34.35	12.48	46.83	54.00	-7.17
16740.00	Peak	28.72	20.88	49.60	68.20	-18.60
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5580 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11160.00	Peak	37.35	12.48	49.82	74.00	-24.18
11160.00	Average	31.66	12.48	44.14	54.00	-9.86
16740.00	Peak	27.35	20.88	48.22	68.20	-19.98
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5700 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11400.00	Peak	37.95	12.39	50.34	74.00	-23.66
11400.00	Average	33.23	12.39	45.62	54.00	-8.38
17100.00	Peak	29.00	25.62	54.62	68.20	-13.58
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5700 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11400.00	Peak	35.66	12.39	48.05	74.00	-25.95
11400.00	Average	30.09	12.39	42.48	54.00	-11.52
17100.00	Peak	28.21	25.62	53.83	68.20	-14.37
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5510 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11020.00	Peak	35.38	12.39	47.77	74.00	-26.23
11020.00	Average	29.92	12.39	42.31	54.00	-11.69
16530.00	Peak	27.91	18.66	46.58	68.20	-21.62
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5510 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11020.00	Peak	33.48	12.39	45.87	74.00	-28.13
11020.00	Average	27.47	12.39	39.86	54.00	-14.14
16530.00	Peak	29.03	18.66	47.69	68.20	-20.51
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5550 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11100.00	Peak	34.06	12.60	46.66	74.00	-27.34
11100.00	Average	29.50	12.60	42.10	54.00	-11.90
16650.00	Peak	28.63	19.99	48.61	68.20	-19.59
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5550 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11100.00	Peak	31.88	12.60	44.48	74.00	-29.52
11100.00	Average	27.16	12.60	39.76	54.00	-14.24
16650.00	Peak	28.86	19.99	48.84	68.20	-19.36
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5670 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11340.00	Peak	36.85	12.55	49.41	74.00	-24.59
11340.00	Average	31.11	12.55	43.66	54.00	-10.34
17010.00	Peak	27.37	25.32	52.69	68.20	-15.51
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5670 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11340.00	Peak	32.17	12.55	44.72	74.00	-29.28
11340.00	Average	28.17	12.55	40.73	54.00	-13.27
17010.00	Peak	27.84	25.32	53.16	68.20	-15.04
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5530 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11060.00	Peak	32.64	12.40	45.04	74.00	-28.96
11060.00	Average	26.58	12.40	38.98	54.00	-15.02
16590.00	Peak	27.71	19.22	46.93	68.20	-21.27
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5530 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11060.00	Peak	31.98	12.40	44.37	74.00	-29.63
11060.00	Average	25.67	12.40	38.07	54.00	-15.93
16590.00	Peak	28.52	19.22	47.75	68.20	-20.45
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5610 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11220.00	Peak	30.66	12.60	43.27	74.00	-30.73
11220.00	Average	28.64	12.60	41.24	54.00	-12.76
16830.00	Peak	28.34	22.01	50.35	68.20	-17.85
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5610 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11220.00	Peak	34.32	12.60	46.92	74.00	-27.08
11220.00	Average	27.25	12.60	39.86	54.00	-14.14
16830.00	Peak	28.64	22.01	50.65	68.20	-17.55
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT160 / 5570 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11140.00	Peak	30.08	12.49	42.57	74.00	-31.43
11140.00	Average	24.86	12.49	37.34	54.00	-16.66
16710.00	Peak	28.53	20.67	49.19	68.20	-19.01
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT160 / 5570 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11140.00	Peak	31.78	12.49	44.27	74.00	-29.73
11140.00	Average	24.57	12.49	37.06	54.00	-16.94
16710.00	Peak	29.23	20.67	49.90	68.20	-18.30
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5500 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11000.00	Peak	35.61	12.42	48.03	74.00	-25.97
11000.00	Average	31.54	12.42	43.96	54.00	-10.04
16500.00	Peak	28.56	18.70	47.26	68.20	-20.94
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5500 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11000.00	Peak	32.83	12.42	45.25	74.00	-28.75
11000.00	Average	29.26	12.42	41.68	54.00	-12.32
16500.00	Peak	28.69	18.70	47.39	68.20	-20.81
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5580 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11160.00	Peak	36.77	12.48	49.24	74.00	-24.76
11160.00	Average	32.90	12.48	45.38	54.00	-8.62
16740.00	Peak	27.89	20.88	48.77	68.20	-19.43
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5580 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11160.00	Peak	31.77	12.48	44.24	74.00	-29.76
11160.00	Average	29.09	12.48	41.56	54.00	-12.44
16740.00	Peak	28.26	20.88	49.13	68.20	-19.07
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5700 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11400.00	Peak	39.14	12.39	51.53	74.00	-22.47
11400.00	Average	34.03	12.39	46.42	54.00	-7.58
17100.00	Peak	28.49	25.62	54.11	68.20	-14.09
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5700 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11400.00	Peak	34.83	12.39	47.22	74.00	-26.78
11400.00	Average	28.47	12.39	40.86	54.00	-13.14
17100.00	Peak	28.82	25.62	54.44	68.20	-13.76
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5510 MHz_	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11020.00	Peak	35.12	12.39	47.51	74.00	-26.49
11020.00	Average	31.44	12.39	43.83	54.00	-10.17
16530.00	Peak	27.23	18.66	45.89	68.20	-22.31
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5510 MHz_	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11020.00	Peak	31.72	12.39	44.11	74.00	-29.89
11020.00	Average	33.33	12.39	45.72	54.00	-8.28
16530.00	Peak	28.81	18.66	47.47	68.20	-20.73
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5550 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11100.00	Peak	37.89	12.60	50.49	74.00	-23.51
11100.00	Average	30.44	12.60	43.04	54.00	-10.96
16650.00	Peak	27.67	19.99	47.66	68.20	-20.54
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5550 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11100.00	Peak	34.04	12.60	46.64	74.00	-27.36
11100.00	Average	28.90	12.60	41.50	54.00	-12.50
16650.00	Peak	28.62	19.99	48.60	68.20	-19.60
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5670 MHz_	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11340.00	Peak	37.14	12.55	49.70	74.00	-24.30
11340.00	Average	32.08	12.55	44.63	54.00	-9.37
17010.00	Peak	27.57	25.32	52.89	68.20	-15.31
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5670 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11340.00	Peak	34.11	12.55	46.66	74.00	-27.34
11340.00	Average	29.92	12.55	42.47	54.00	-11.53
17010.00	Peak	27.16	25.32	52.48	68.20	-15.72
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5530 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11060.00	Peak	32.70	12.40	45.10	74.00	-28.90
11060.00	Average	26.72	12.40	39.12	54.00	-14.88
16590.00	Peak	27.94	19.22	47.16	68.20	-21.04
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5530 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11060.00	Peak	32.08	12.40	44.48	74.00	-29.52
11060.00	Average	25.67	12.40	38.07	54.00	-15.93
16590.00	Peak	28.78	19.22	48.00	68.20	-20.20
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5610 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11220.00	Peak	36.38	12.60	48.98	74.00	-25.02
11220.00	Average	32.69	12.60	45.29	54.00	-8.71
16830.00	Peak	28.06	22.01	50.07	68.20	-18.13
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5610 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11220.00	Peak	33.04	12.60	45.64	74.00	-28.36
11220.00	Average	28.92	12.60	41.52	54.00	-12.48
16830.00	Peak	29.37	22.01	51.37	68.20	-16.83
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE160 / 5570 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11140.00	Peak	30.94	12.49	43.43	74.00	-30.57
11140.00	Average	24.40	12.49	36.89	54.00	-17.11
16710.00	Peak	28.49	20.67	49.16	68.20	-19.04
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE160 / 5570 MHz	Temp/Hum	21.8(℃)/ 61%RH
Test Item	Harmonic	Test Date	April 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11140.00	Peak	30.29	12.49	42.78	74.00	-31.22
11140.00	Average	24.26	12.49	36.75	54.00	-17.25
16710.00	Peak	28.07	20.67	48.74	68.20	-19.46
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data for UNII-3

(1) Chain 0:

Test Mode	IEEE 802.11a / 5745 MHz	Temp/Hum	23.5(℃)/ 60%RH
Test Item	Harmonic	Test Date	March 29, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11490.00	Peak	38.25	12.39	50.64	74.00	-23.36
11490.00	Average	32.97	12.39	45.36	54.00	-8.64
17235.00	Peak	28.19	26.10	54.30	68.20	-13.90
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5500 MHz	Temp/Hum	23.5(℃)/ 60%RH
Test Item	Harmonic	Test Date	March 29, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11490.00	Peak	32.58	12.39	44.97	74.00	-29.03
11490.00	Average	28.07	12.39	40.46	54.00	-13.54
17235.00	Peak	27.96	26.10	54.06	68.20	-14.14
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5785 MHz	Temp/Hum	23.5(℃)/ 60%RH
Test Item	Harmonics	Test Date	March 29, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11570.00	Peak	37.08	12.49	49.57	74.00	-24.43
11570.00	Average	32.57	12.49	45.06	54.00	-8.94
17355.00	Peak	28.63	25.47	54.10	68.20	-14.10
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5785 MHz	Temp/Hum	23.5(℃)/ 60%RH
Test Item	Harmonic	Test Date	March 29, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11570.00	Peak	33.23	12.49	45.72	74.00	-28.28
11570.00	Average	28.49	12.49	40.98	54.00	-13.02
17355.00	Peak	28.92	25.47	54.39	68.20	-13.81
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5825 MHz	Temp/Hum	23.5(℃)/ 60%RH
Test Item	Harmonic	Test Date	March 29, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11650.00	Peak	35.75	12.43	48.17	74.00	-25.83
11650.00	Average	30.73	12.43	43.15	54.00	-10.85
17475.00	Peak	29.28	25.06	54.34	68.20	-13.86
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5825 MHz	Temp/Hum	23.5(℃)/ 60%RH
Test Item	Harmonic	Test Date	March 29, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11650.00	Peak	34.16	12.43	46.58	74.00	-27.42
11650.00	Average	29.60	12.43	42.03	54.00	-11.97
17475.00	Peak	28.81	25.06	53.87	68.20	-14.33
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data for UNII-3

(2) Chain 1:

Test Mode	IEEE 802.11a / 5745 MHz	Temp/Hum	23.5(℃)/ 60%RH
Test Item	Harmonic	Test Date	March 29, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11490.00	Peak	38.26	12.39	50.65	74.00	-23.35
11490.00	Average	33.53	12.39	45.92	54.00	-8.08
17235.00	Peak	28.64	26.10	54.74	68.20	-13.46
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5745 MHz	Temp/Hum	23.5(℃)/ 60%RH
Test Item	Harmonic	Test Date	March 29, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11490.00	Peak	32.77	12.39	45.16	74.00	-28.84
11490.00	Average	29.53	12.39	41.92	54.00	-12.08
17235.00	Peak	28.19	26.10	54.29	68.20	-13.91
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5785 MHz	Temp/Hum	23.5(℃)/ 60%RH
Test Item	Harmonics	Test Date	March 29, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11570.00	Peak	33.56	12.49	46.05	74.00	-27.95
11570.00	Average	33.14	12.49	45.63	54.00	-8.37
17355.00	Peak	28.70	25.47	54.17	68.20	-14.03
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5785 MHz	Temp/Hum	23.5(℃)/ 60%RH
Test Item	Harmonic	Test Date	March 29, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)	
11570.00	Peak	34.51	12.49	47.00	74.00	-27.00	H
11570.00	Average	29.41	12.49	41.90	54.00	-12.10	H
17355.00	Peak	28.45	25.47	53.92	68.20	-14.28	H
N/A							

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5825 MHz	Temp/Hum	23.5(℃)/ 60%RH
Test Item	Harmonic	Test Date	March 29, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11650.00	Peak	33.49	12.43	45.92	74.00	-28.08
11650.00	Average	32.00	12.43	44.42	54.00	-9.58
17475.00	Peak	28.32	25.06	53.38	68.20	-14.82
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11a / 5825 MHz	Temp/Hum	23.5(℃)/ 60%RH
Test Item	Harmonic	Test Date	March 29, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11650.00	Peak	32.82	12.43	45.24	74.00	-28.76
11650.00	Average	30.16	12.43	42.58	54.00	-11.42
17475.00	Peak	28.65	25.06	53.71	68.20	-14.49
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data for UNII-3
(3) MIMO:

Test Mode	IEEE 802.11n HT20 / 5745 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11490.00	Peak	42.71	12.39	55.10	74.00	-18.90
11490.00	Average	33.83	12.39	46.22	54.00	-7.78
17235.00	Peak	29.20	26.10	55.30	68.20	-12.90
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5745 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11490.00	Peak	35.88	12.39	48.27	74.00	-25.73
11490.00	Average	30.33	12.39	42.72	54.00	-11.28
17235.00	Peak	29.26	26.10	55.36	68.20	-12.84
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5785 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11570.00	Peak	40.07	12.49	52.56	74.00	-21.44
11570.00	Average	33.26	12.49	45.75	54.00	-8.25
17355.00	Peak	29.69	25.47	55.16	68.20	-13.04
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5785 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11570.00	Peak	36.32	12.49	48.81	74.00	-25.19
11570.00	Average	30.02	12.49	42.51	54.00	-11.49
17355.00	Peak	29.22	25.47	54.69	68.20	-13.51
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5825 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11650.00	Peak	40.37	12.43	52.80	74.00	-21.21
11650.00	Average	33.93	12.43	46.36	54.00	-7.65
17475.00	Peak	28.34	25.06	53.40	68.20	-14.80
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5825 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11650.00	Peak	39.03	12.43	51.45	74.00	-22.55
11650.00	Average	31.54	12.43	43.97	54.00	-10.04
17475.00	Peak	30.34	25.06	55.40	68.20	-12.80
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5755 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11510.00	Peak	37.33	12.43	49.76	74.00	-24.24
11510.00	Average	31.32	12.43	43.75	54.00	-10.25
17265.00	Peak	29.29	26.14	55.43	68.20	-12.77
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5755 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11510.00	Peak	33.93	12.43	46.36	74.00	-27.64
11510.00	Average	27.69	12.43	40.12	54.00	-13.88
17265.00	Peak	28.72	26.14	54.86	68.20	-13.34
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5795 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11590.00	Peak	36.15	12.48	48.63	74.00	-25.37
11590.00	Average	28.69	12.48	41.17	54.00	-12.83
17385.00	Peak	29.12	25.27	54.38	68.20	-13.82
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5795 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11590.00	Peak	34.18	12.48	46.65	74.00	-27.35
11590.00	Average	27.06	12.48	39.54	54.00	-14.46
17385.00	Peak	29.61	25.27	54.88	68.20	-13.32
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5775 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11550.00	Peak	35.63	12.51	48.13	74.00	-25.87
11550.00	Average	27.24	12.51	39.75	54.00	-14.26
17325.00	Peak	29.16	25.79	54.95	68.20	-13.25
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5775 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11550.00	Peak	33.38	12.51	45.89	74.00	-28.11
11550.00	Average	25.99	12.51	38.50	54.00	-15.51
17325.00	Peak	29.42	25.79	55.21	68.20	-12.99
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5745 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11490.00	Peak	38.46	12.39	50.85	74.00	-23.15
11490.00	Average	33.28	12.39	45.67	54.00	-8.33
17235.00	Peak	29.11	26.10	55.22	68.20	-12.98
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5745 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11490.00	Peak	37.01	12.39	49.40	74.00	-24.60
11490.00	Average	30.65	12.39	43.04	54.00	-10.96
17235.00	Peak	29.13	26.10	55.24	68.20	-12.96
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5785 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11570.00	Peak	38.73	12.49	51.22	74.00	-22.78
11570.00	Average	33.49	12.49	45.98	54.00	-8.02
17355.00	Peak	30.43	25.47	55.90	68.20	-12.30
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5785 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11570.00	Peak	33.60	12.49	46.10	74.00	-27.90
11570.00	Average	28.33	12.49	40.82	54.00	-13.18
17355.00	Peak	30.37	25.47	55.84	68.20	-12.36
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5825 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11650.00	Peak	39.99	12.43	52.42	74.00	-21.58
11650.00	Average	33.57	12.43	46.00	54.00	-8.01
17475.00	Peak	29.90	25.06	54.96	68.20	-13.24
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5825 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11650.00	Peak	36.82	12.43	49.24	74.00	-24.76
11650.00	Average	30.30	12.43	42.72	54.00	-11.28
17475.00	Peak	29.82	25.06	54.88	68.20	-13.32
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5755 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11510.00	Peak	36.39	12.43	48.82	74.00	-25.18
11510.00	Average	29.82	12.43	42.25	54.00	-11.75
17265.00	Peak	28.16	26.14	54.30	68.20	-13.90
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5755 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11510.00	Peak	33.98	12.43	46.41	74.00	-27.59
11510.00	Average	27.06	12.43	39.49	54.00	-14.51
17265.00	Peak	28.61	26.14	54.75	68.20	-13.45
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5795 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11590.00	Peak	35.31	12.48	47.79	74.00	-26.21
11590.00	Average	29.71	12.48	42.19	54.00	-11.81
17385.00	Peak	29.51	25.27	54.78	68.20	-13.42
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5795 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11590.00	Peak	34.54	12.48	47.01	74.00	-26.99
11590.00	Average	27.99	12.48	40.47	54.00	-13.53
17385.00	Peak	28.66	25.27	53.93	68.20	-14.27
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5775 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11550.00	Peak	34.43	12.51	46.93	74.00	-27.07
11550.00	Average	27.71	12.51	40.22	54.00	-13.79
17325.00	Peak	28.41	25.79	54.20	68.20	-14.00
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5775 MHz	Temp/Hum	23.2(℃)/ 61%RH
Test Item	Harmonic	Test Date	March 30, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11550.00	Peak	33.34	12.51	45.85	74.00	-28.15
11550.00	Average	25.21	12.51	37.72	54.00	-16.29
17325.00	Peak	28.80	25.79	54.59	68.20	-13.61
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data for UNII-3

(4) Co-Location:

Test Mode	IEEE 802.11ax HE40 Mode (2452MHz)+ IEEE 802.11ax HE20(Band 1-5180MHz)	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	April 13, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4904.00	Peak	36.81	1.81	38.62	74.00	-35.38
4904.00	Average	28.41	1.81	30.22	54.00	-23.78
7356.00	Peak	38.42	7.65	46.07	74.00	-27.93
7356.00	Average	35.50	7.65	43.15	54.00	-10.85
10360.00	Peak	37.61	11.26	48.87	74.00	-25.13
15540.00	Peak	35.14	12.38	47.52	74.00	-26.48
15540.00	Average	30.73	12.38	43.11	54.00	-10.89

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 Mode (2452MHz)+ IEEE 802.11ax HE20(Band 1-5180MHz)	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	April 13, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4904.00	Peak	36.42	1.81	38.23	74.00	-35.77
4904.00	Average	27.97	1.81	29.78	54.00	-24.22
7356.00	Peak	36.16	7.65	43.81	74.00	-30.19
7356.00	Average	33.44	7.65	41.09	54.00	-12.91
10360.00	Peak	34.87	11.26	46.13	74.00	-27.87
15540.00	Peak	33.08	12.38	45.45	74.00	-28.55
15540.00	Average	28.39	12.38	40.77	54.00	-13.23

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 Mode (Band 1-5180MHz)+ IEEE 802.11ax HE40(2452MHz)	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	April 13, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4904.00	Peak	36.81	1.81	38.62	74.00	-35.38
4904.00	Average	28.41	1.81	30.22	54.00	-23.78
7356.00	Peak	38.42	7.65	46.07	74.00	-27.93
7356.00	Average	35.50	7.65	43.15	54.00	-10.85
10360.00	Peak	37.61	11.26	48.87	68.20	-19.33
15540.00	Peak	35.14	12.38	47.52	74.00	-26.48
15540.00	Average	30.73	12.38	43.11	54.00	-10.89

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 Mode (Band 1-5180MHz)+ IEEE 802.11ax HE40(2452MHz)	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	April 13, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4904.00	Peak	36.42	1.81	38.23	74.00	-35.77
4904.00	Average	27.97	1.81	29.78	54.00	-24.22
7356.00	Peak	36.16	7.65	43.81	74.00	-30.19
7356.00	Average	33.44	7.65	41.09	54.00	-12.91
10360.00	Peak	34.87	11.26	46.13	68.20	-22.07
15540.00	Peak	33.08	12.38	45.45	74.00	-28.55
15540.00	Average	28.39	12.38	40.77	54.00	-13.23

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Above 1G Test Data: Beamforming

Test Data for UNII-1

Test Mode	IEEE 802.11n HT20 / 5180 MHz	Temp/Hum	23.2(℃)/ 60%RH
Test Item	Harmonic	Test Date	May 15, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10360.00	Peak	32.58	11.26	43.84	68.20	-24.36
15540.00	Peak	30.54	12.38	42.92	74.00	-31.08
15540.00	Average	22.02	12.38	34.40	54.00	-19.60
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5180 MHz	Temp/Hum	23.2(℃)/ 60%RH
Test Item	Harmonic	Test Date	May 15, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10360.00	Peak	31.54	11.26	42.80	68.20	-25.40
15540.00	Peak	29.94	12.38	42.32	74.00	-31.68
15540.00	Average	21.89	12.38	34.27	54.00	-19.73
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5220 MHz	Temp/Hum	23.2(℃)/ 60%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10440.00	Peak	36.93	11.25	48.18	68.20	-20.02
15660.00	Peak	28.80	13.53	42.33	74.00	-31.67
15660.00	Average	23.43	13.53	36.96	54.00	-17.04
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5220 MHz	Temp/Hum	23.2(℃)/ 60%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10440.00	Peak	31.65	11.25	42.90	68.20	-25.30
15660.00	Peak	28.41	13.53	41.94	74.00	-32.06
15660.00	Average	23.49	13.53	37.01	54.00	-16.99
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5240 MHz	Temp/Hum	23.2(℃)/ 60%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10480.00	Peak	31.28	11.35	42.63	68.20	-25.57
15720.00	Peak	28.36	14.11	42.47	74.00	-31.53
15720.00	Average	23.20	14.11	37.30	54.00	-16.70
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5240 MHz	Temp/Hum	23.2(℃)/ 60%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10480.00	Peak	32.36	11.35	43.71	68.20	-24.49
15720.00	Peak	28.83	14.11	42.94	74.00	-31.06
15720.00	Average	23.07	14.11	37.18	54.00	-16.82
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5190 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10380.00	Peak	32.57	11.22	43.78	68.20	-24.42
15570.00	Peak	29.76	12.41	42.18	74.00	-31.82
15570.00	Average	23.49	12.41	35.90	54.00	-18.10
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5190 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10380.00	Peak	32.32	11.22	43.54	68.20	-24.66
15570.00	Peak	30.04	12.41	42.46	74.00	-31.54
15570.00	Average	22.84	12.41	35.25	54.00	-18.75
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5230 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10460.00	Peak	31.70	11.30	42.99	68.20	-25.21
15690.00	Peak	29.94	13.90	43.84	74.00	-30.16
15690.00	Average	22.45	13.90	36.35	54.00	-17.65
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5230 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10460.00	Peak	32.00	11.30	43.30	68.20	-24.90
15690.00	Peak	29.90	13.90	43.80	74.00	-30.20
15690.00	Average	22.41	13.90	36.31	54.00	-17.69
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5210 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10420.00	Peak	31.75	11.21	42.96	68.20	-25.24
15630.00	Peak	29.06	13.06	42.12	74.00	-31.88
15630.00	Average	23.58	13.06	36.64	54.00	-17.36
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5210 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10420.00	Peak	31.99	11.21	43.20	68.20	-25.00
15630.00	Peak	28.48	13.06	41.54	74.00	-32.46
15630.00	Average	23.57	13.06	36.62	54.00	-17.38
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5180 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10360.00	Peak	32.03	11.26	43.29	68.20	-24.91
15540.00	Peak	30.34	12.38	42.72	74.00	-31.28
15540.00	Average	22.46	12.38	34.84	54.00	-19.16
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5180 MHz_	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10360.00	Peak	32.16	11.26	43.42	68.20	-24.78
15540.00	Peak	30.05	12.38	42.43	74.00	-31.57
15540.00	Average	22.01	12.38	34.39	54.00	-19.61
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5220 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10440.00	Peak	33.05	11.25	44.30	68.20	-23.90
15660.00	Peak	28.42	13.53	41.95	74.00	-32.05
15660.00	Average	22.74	13.53	36.27	54.00	-17.73
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5220 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10440.00	Peak	32.23	11.25	43.48	68.20	-24.72
15660.00	Peak	29.86	13.53	43.39	74.00	-30.61
15660.00	Average	22.81	13.53	36.34	54.00	-17.66
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5240 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10480.00	Peak	31.61	11.35	42.96	68.20	-25.24
15720.00	Peak	28.82	14.11	42.93	74.00	-31.07
15720.00	Average	22.58	14.11	36.69	54.00	-17.31
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5240 MHz_	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10480.00	Peak	30.63	11.35	41.98	68.20	-26.22
15720.00	Peak	29.16	14.11	43.27	74.00	-30.73
15720.00	Average	23.01	14.11	37.12	54.00	-16.88
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5190 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	March 30, 2022
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10380.00	Peak	31.56	11.22	42.77	68.20	-25.43
15570.00	Peak	29.75	12.41	42.16	74.00	-31.84
15570.00	Average	25.00	12.41	37.41	54.00	-16.59
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5190 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	March 30, 2022
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10380.00	Peak	32.07	11.22	43.29	68.20	-24.91
15570.00	Peak	31.79	12.41	44.21	74.00	-29.79
15570.00	Average	23.85	12.41	36.26	54.00	-17.74
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5230 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10460.00	Peak	31.91	11.30	43.20	68.20	-25.00
15690.00	Peak	30.64	13.90	44.55	74.00	-29.45
15690.00	Average	23.50	13.90	37.41	54.00	-16.59
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5230 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10460.00	Peak	32.12	11.30	43.42	68.20	-24.78
15690.00	Peak	30.51	13.90	44.42	74.00	-29.58
15690.00	Average	24.13	13.90	38.03	54.00	-15.97
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5210 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10420.00	Peak	31.15	11.21	42.36	68.20	-25.84
15630.00	Peak	29.84	13.06	42.90	74.00	-31.10
15630.00	Average	23.81	13.06	36.87	54.00	-17.13
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5210 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10420.00	Peak	32.19	11.21	43.40	68.20	-24.80
15630.00	Peak	29.85	13.06	42.90	74.00	-31.10
15630.00	Average	23.93	13.06	36.98	54.00	-17.02
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data for UNII-2a

Test Mode	IEEE 802.11n HT20 / 5260 MHz	Temp/Hum	23.2(℃)/ 60%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10520.00	Peak	31.67	11.41	43.08	68.20	-25.12
15780.00	Peak	29.26	14.08	43.33	74.00	-30.67
15780.00	Average	23.19	14.08	37.26	54.00	-16.74
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5260 MHz	Temp/Hum	23.2(℃)/ 60%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10520.00	Peak	30.44	11.41	41.85	68.20	-26.35
15780.00	Peak	28.67	14.08	42.75	74.00	-31.25
15780.00	Average	23.38	14.08	37.45	54.00	-16.55
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5300 MHz	Temp/Hum	23.2(℃)/ 60%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10600.00	Peak	31.97	11.53	43.50	68.20	-24.70
15900.00	Peak	28.44	14.45	42.89	74.00	-31.11
15900.00	Average	23.53	14.45	37.98	54.00	-16.02
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5300 MHz	Temp/Hum	23.2(℃)/ 60%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10600.00	Peak	31.90	11.53	43.43	68.20	-24.77
15900.00	Peak	28.35	14.45	42.80	74.00	-31.20
15900.00	Average	23.54	14.45	37.99	54.00	-16.01
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5320 MHz	Temp/Hum	23.2(℃)/ 60%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10640.00	Peak	30.77	11.50	42.27	74.00	-31.73
10640.00	Average	26.69	11.50	38.20	54.00	-15.80
15960.00	Peak	28.22	15.09	43.31	74.00	-30.69
15960.00	Average	23.52	15.09	38.61	54.00	-15.39

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5320 MHz	Temp/Hum	23.2(℃)/ 60%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10640.00	Peak	31.35	11.50	42.85	74.00	-31.15
10640.00	Average	25.40	11.50	36.90	54.00	-17.10
15960.00	Peak	28.23	15.09	43.32	74.00	-30.68
15960.00	Average	23.04	15.09	38.13	54.00	-15.87

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5270 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10540.00	Peak	32.31	11.41	43.72	68.20	-24.48
15810.00	Peak	29.68	14.04	43.72	74.00	-30.28
15810.00	Average	22.61	14.04	36.65	54.00	-17.35
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5270 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10540.00	Peak	30.80	11.41	42.21	68.20	-25.99
15810.00	Peak	29.60	14.04	43.64	74.00	-30.36
15810.00	Average	22.11	14.04	36.15	54.00	-17.85
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5310 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10620.00	Peak	32.51	11.52	44.02	74.00	-29.98
10620.00	Average	24.66	11.52	36.18	54.00	-17.82
15930.00	Peak	29.14	14.81	43.96	74.00	-30.04
15930.00	Average	22.79	14.81	37.61	54.00	-16.39

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5310 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10620.00	Peak	31.87	11.52	43.39	74.00	-30.61
10620.00	Average	23.74	11.52	35.26	54.00	-18.74
15930.00	Peak	29.01	14.81	43.82	74.00	-30.18
15930.00	Average	22.63	14.81	37.44	54.00	-16.56

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5290 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10580.00	Peak	31.66	11.48	43.14	68.20	-25.06
15870.00	Peak	28.84	14.34	43.18	74.00	-30.82
15870.00	Average	23.38	14.34	37.72	54.00	-16.28
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5290 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10580.00	Peak	31.23	11.48	42.71	68.20	-25.49
15870.00	Peak	29.46	14.34	43.80	74.00	-30.20
15870.00	Average	23.26	14.34	37.60	54.00	-16.40
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT160 / 5250 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10500.00	Peak	31.06	11.41	42.47	68.20	-25.73
15750.00	Peak	28.60	14.22	42.82	74.00	-31.18
15750.00	Average	22.98	14.22	37.20	54.00	-16.80
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT160 / 5250 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10500.00	Peak	30.69	11.41	42.10	68.20	-26.10
15750.00	Peak	29.37	14.22	43.59	74.00	-30.41
15750.00	Average	22.68	14.22	36.90	54.00	-17.10
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5260 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10520.00	Peak	32.57	11.41	43.98	68.20	-24.22
15780.00	Peak	29.83	14.08	43.90	74.00	-30.10
15780.00	Average	23.60	14.08	37.68	54.00	-16.32
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5260 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10520.00	Peak	31.77	11.41	43.18	68.20	-25.02
15780.00	Peak	29.55	14.08	43.63	74.00	-30.37
15780.00	Average	23.57	14.08	37.64	54.00	-16.36
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5300 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10600.00	Peak	32.76	11.53	44.29	68.20	-23.91
15900.00	Peak	30.16	14.45	44.61	74.00	-29.39
15900.00	Average	24.03	14.45	38.48	54.00	-15.52
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5300 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10600.00	Peak	31.96	11.53	43.49	68.20	-24.71
15900.00	Peak	29.68	14.45	44.13	74.00	-29.87
15900.00	Average	24.09	14.45	38.54	54.00	-15.46
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5320 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10640.00	Peak	31.96	11.50	43.46	74.00	-30.54
10640.00	Average	26.60	11.50	38.10	54.00	-15.90
15960.00	Peak	30.28	15.09	45.37	74.00	-28.63
15960.00	Average	23.59	15.09	38.68	54.00	-15.32

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5320 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10640.00	Peak	31.50	11.50	43.00	74.00	-31.00
10640.00	Average	25.50	11.50	37.01	54.00	-16.99
15960.00	Peak	29.64	15.09	44.73	74.00	-29.27
15960.00	Average	23.51	15.09	38.60	54.00	-15.40

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5270 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10540.00	Peak	31.71	11.41	43.12	68.20	-25.08
15810.00	Peak	30.67	14.04	44.71	74.00	-29.29
15810.00	Average	23.54	14.04	37.58	54.00	-16.42
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5270 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10540.00	Peak	32.14	11.41	43.55	68.20	-24.65
15810.00	Peak	29.63	14.04	43.67	74.00	-30.33
15810.00	Average	23.43	14.04	37.47	54.00	-16.53
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5310 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10620.00	Peak	31.60	11.52	43.12	74.00	-30.88
10620.00	Average	24.48	11.52	35.99	54.00	-18.01
15930.00	Peak	30.23	14.81	45.04	74.00	-28.96
15930.00	Average	23.64	14.81	38.46	54.00	-15.54

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5310 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10620.00	Peak	32.21	11.52	43.72	74.00	-30.28
10620.00	Average	24.18	11.52	35.70	54.00	-18.30
15930.00	Peak	29.63	14.81	44.44	74.00	-29.56
15930.00	Average	23.69	14.81	38.50	54.00	-15.50

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5290 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 18, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
10580.00	Peak	32.96	11.48	44.44	68.20	-23.76
15870.00	Peak	29.25	14.34	43.59	74.00	-30.41
15870.00	Average	23.90	14.34	38.25	54.00	-15.75
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5290 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 18, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10580.00	Peak	31.23	11.48	42.71	68.20	-25.49
15870.00	Peak	29.82	14.34	44.16	74.00	-29.84
15870.00	Average	24.00	14.34	38.34	54.00	-15.66
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE160 / 5250 MHz	Temp/Hum	24.3(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 18, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10500.00	Peak	30.95	11.41	42.36	68.20	-25.84
15750.00	Peak	29.02	14.22	43.24	74.00	-30.76
15750.00	Average	20.96	14.22	35.18	54.00	-18.82
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE160 / 5250 MHz	Temp/Hum	24.3(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 18, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
10500.00	Peak	31.39	11.41	42.80	68.20	-25.40
15750.00	Peak	28.66	14.22	42.88	74.00	-31.12
15750.00	Average	20.99	14.22	35.21	54.00	-18.79
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data for UNII-2c

Test Mode	IEEE 802.11n HT20 / 5500 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11000.00	Peak	31.00	12.42	43.42	74.00	-30.58
11000.00	Average	29.92	12.42	42.34	54.00	-11.66
16500.00	Peak	27.59	18.70	46.29	68.20	-21.91
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5500 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11000.00	Peak	30.87	12.42	43.29	74.00	-30.71
11000.00	Average	23.66	12.42	36.08	54.00	-17.92
16500.00	Peak	28.59	18.70	47.29	68.20	-20.91
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5580 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11160.00	Peak	31.32	12.48	43.79	74.00	-30.21
11160.00	Average	24.88	12.48	37.36	54.00	-16.64
16740.00	Peak	29.07	20.88	49.95	68.20	-18.25
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5580 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11160.00	Peak	31.86	12.48	44.34	74.00	-29.66
11160.00	Average	23.34	12.48	35.82	54.00	-18.18
16740.00	Peak	28.24	20.88	49.11	68.20	-19.09
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5700 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11400.00	Peak	30.03	12.39	42.42	74.00	-31.58
11400.00	Average	24.37	12.39	36.76	54.00	-17.24
17100.00	Peak	27.49	25.62	53.11	68.20	-15.09
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5700 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11400.00	Peak	31.79	12.39	44.18	74.00	-29.82
11400.00	Average	23.02	12.39	35.41	54.00	-18.59
17100.00	Peak	29.56	25.62	55.18	68.20	-13.02
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5510 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11020.00	Peak	30.72	12.39	43.11	74.00	-30.89
11020.00	Average	23.20	12.39	35.59	54.00	-18.41
16530.00	Peak	28.99	18.66	47.66	68.20	-20.54
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5510 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11020.00	Peak	30.27	12.39	42.66	74.00	-31.34
11020.00	Average	23.28	12.39	35.67	54.00	-18.33
16530.00	Peak	28.02	18.66	46.68	68.20	-21.52
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5550 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11100.00	Peak	30.70	12.60	43.30	74.00	-30.70
11100.00	Average	23.13	12.60	35.73	54.00	-18.27
16650.00	Peak	29.03	19.99	49.02	68.20	-19.18
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5550 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11100.00	Peak	31.21	12.60	43.81	74.00	-30.19
11100.00	Average	22.99	12.60	35.59	54.00	-18.41
16650.00	Peak	28.21	19.99	48.20	68.20	-20.00
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5670 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11340.00	Peak	29.89	12.55	42.44	74.00	-31.56
11340.00	Average	23.29	12.55	35.84	54.00	-18.16
17010.00	Peak	26.70	25.32	52.02	68.20	-16.18
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5670 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11340.00	Peak	30.40	12.55	42.95	74.00	-31.05
11340.00	Average	23.03	12.55	35.58	54.00	-18.42
17010.00	Peak	28.02	25.32	53.34	68.20	-14.86
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5530 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11060.00	Peak	30.25	12.40	42.65	74.00	-31.35
11060.00	Average	23.59	12.40	35.98	54.00	-18.02
16590.00	Peak	28.57	19.22	47.79	68.20	-20.41
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5530 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11060.00	Peak	31.53	12.40	43.93	74.00	-30.07
11060.00	Average	23.92	12.40	36.32	54.00	-17.68
16590.00	Peak	29.02	19.22	48.24	68.20	-19.96
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5610 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11220.00	Peak	30.09	12.60	42.69	74.00	-31.31
11220.00	Average	24.03	12.60	36.64	54.00	-17.36
16830.00	Peak	27.66	22.01	49.67	68.20	-18.53
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5610 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11220.00	Peak	30.49	12.60	43.10	74.00	-30.90
11220.00	Average	24.15	12.60	36.76	54.00	-17.24
16830.00	Peak	29.76	22.01	51.76	68.20	-16.44
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT160 / 5570 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11140.00	Peak	30.88	12.49	43.37	74.00	-30.63
11140.00	Average	23.86	12.49	36.34	54.00	-17.66
16710.00	Peak	27.81	20.67	48.48	68.20	-19.72
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT160 / 5570 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11140.00	Peak	30.13	12.49	42.62	74.00	-31.38
11140.00	Average	24.13	12.49	36.62	54.00	-17.38
16710.00	Peak	28.12	20.67	48.79	68.20	-19.41
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5500 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11000.00	Peak	31.55	12.42	43.97	74.00	-30.03
11000.00	Average	24.07	12.42	36.49	54.00	-17.51
16500.00	Peak	28.68	18.70	47.38	68.20	-20.82
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5500 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11000.00	Peak	30.67	12.42	43.09	74.00	-30.91
11000.00	Average	23.88	12.42	36.30	54.00	-17.70
16500.00	Peak	27.64	18.70	46.34	68.20	-21.86
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5580 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11160.00	Peak	33.82	12.48	46.29	74.00	-27.71
11160.00	Average	25.18	12.48	37.65	54.00	-16.35
16740.00	Peak	28.69	20.88	49.57	68.20	-18.63
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5580 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11160.00	Peak	30.94	12.48	43.42	74.00	-30.58
11160.00	Average	24.41	12.48	36.88	54.00	-17.12
16740.00	Peak	28.11	20.88	48.98	68.20	-19.22
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5700 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11400.00	Peak	31.41	12.39	43.80	74.00	-30.20
11400.00	Average	24.07	12.39	36.46	54.00	-17.54
17100.00	Peak	28.65	25.62	54.27	68.20	-13.93
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5700 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11400.00	Peak	31.26	12.39	43.65	74.00	-30.35
11400.00	Average	23.74	12.39	36.13	54.00	-17.87
17100.00	Peak	28.92	25.62	54.54	68.20	-13.66
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5510 MHz_	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11020.00	Peak	31.28	12.39	43.67	74.00	-30.33
11020.00	Average	23.73	12.39	36.12	54.00	-17.88
16530.00	Peak	29.17	18.66	47.83	68.20	-20.37
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5510 MHz_	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11020.00	Peak	30.65	12.39	43.04	74.00	-30.96
11020.00	Average	23.74	12.39	36.13	54.00	-17.87
16530.00	Peak	28.60	18.66	47.26	68.20	-20.94
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5550 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11100.00	Peak	30.28	12.60	42.88	74.00	-31.12
11100.00	Average	23.74	12.60	36.34	54.00	-17.66
16650.00	Peak	30.71	19.99	50.69	68.20	-17.51
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5550 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11100.00	Peak	30.91	12.60	43.51	74.00	-30.49
11100.00	Average	23.75	12.60	36.35	54.00	-17.65
16650.00	Peak	28.64	19.99	48.63	68.20	-19.57
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5670 MHz_	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11340.00	Peak	30.84	12.55	43.39	74.00	-30.61
11340.00	Average	23.61	12.55	36.16	54.00	-17.84
17010.00	Peak	27.58	25.32	52.90	68.20	-15.30
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5670 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11340.00	Peak	30.58	12.55	43.14	74.00	-30.86
11340.00	Average	23.59	12.55	36.15	54.00	-17.85
17010.00	Peak	28.04	25.32	53.36	68.20	-14.84
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5530 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 18, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11060.00	Peak	30.24	12.40	42.64	74.00	-31.36
11060.00	Average	23.80	12.40	36.19	54.00	-17.81
16590.00	Peak	29.53	19.22	48.76	68.20	-19.44
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5530 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 18, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11060.00	Peak	30.79	12.40	43.19	74.00	-30.81
11060.00	Average	23.78	12.40	36.17	54.00	-17.83
16590.00	Peak	30.17	19.22	49.39	68.20	-18.81
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5610 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 18, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11220.00	Peak	31.38	12.60	43.99	74.00	-30.01
11220.00	Average	23.75	12.60	36.35	54.00	-17.65
16830.00	Peak	29.42	22.01	51.42	68.20	-16.78
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5610 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 18, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11220.00	Peak	30.98	12.60	43.58	74.00	-30.42
11220.00	Average	23.85	12.60	36.45	54.00	-17.55
16830.00	Peak	28.96	22.01	50.97	68.20	-17.23
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE160 / 5570 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 18, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11400.00	Peak	32.19	12.39	44.58	74.00	-29.42
11400.00	Average	23.02	12.39	35.41	54.00	-18.59
17100.00	Peak	28.83	25.62	54.45	68.20	-13.75
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE160 / 5570 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 18, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11400.00	Peak	31.56	12.39	43.95	74.00	-30.05
11400.00	Average	22.92	12.39	35.31	54.00	-18.69
17100.00	Peak	28.71	25.62	54.33	68.20	-13.87
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data for UNII-3

Test Mode	IEEE 802.11n HT20 / 5745 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11490.00	Peak	32.91	12.39	45.30	74.00	-28.70
11490.00	Average	25.32	12.39	37.71	54.00	-16.29
17235.00	Peak	29.23	26.10	55.33	68.20	-12.87
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5745 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11490.00	Peak	33.31	12.39	45.70	74.00	-28.30
11490.00	Average	24.12	12.39	36.51	54.00	-17.49
17235.00	Peak	28.93	26.10	55.03	68.20	-13.17
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5785 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11570.00	Peak	32.82	12.49	45.31	74.00	-28.69
11570.00	Average	25.11	12.49	37.60	54.00	-16.40
17355.00	Peak	28.44	25.47	53.91	68.20	-14.29
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5785 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11570.00	Peak	31.39	12.49	43.88	74.00	-30.12
11570.00	Average	23.67	12.49	36.16	54.00	-17.84
17355.00	Peak	28.35	25.47	53.82	68.20	-14.38
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5825 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11650.00	Peak	31.80	12.43	44.23	74.00	-29.77
11650.00	Average	25.51	12.43	37.94	54.00	-16.07
17475.00	Peak	27.71	25.06	52.77	68.20	-15.43
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT20 / 5825 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Tony Chao
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11650.00	Peak	31.90	12.43	44.33	74.00	-29.67
11650.00	Average	24.41	12.43	36.84	54.00	-17.17
17475.00	Peak	29.84	25.06	54.90	68.20	-13.30
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5755 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11510.00	Peak	30.61	12.43	43.04	74.00	-30.96
11510.00	Average	23.46	12.43	35.89	54.00	-18.11
17265.00	Peak	28.91	26.14	55.05	68.20	-13.15
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5755 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11510.00	Peak	32.42	12.43	44.85	74.00	-29.15
11510.00	Average	23.57	12.43	35.99	54.00	-18.01
17265.00	Peak	29.30	26.14	55.44	68.20	-12.76
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5795 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11590.00	Peak	30.09	12.48	42.56	74.00	-31.44
11590.00	Average	23.47	12.48	35.95	54.00	-18.05
17385.00	Peak	28.81	25.27	54.08	68.20	-14.12
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11n HT40 / 5795 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11590.00	Peak	29.78	12.48	42.26	74.00	-31.74
11590.00	Average	23.39	12.48	35.87	54.00	-18.13
17385.00	Peak	28.90	25.27	54.17	68.20	-14.03
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5775 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11550.00	Peak	30.07	12.51	42.58	74.00	-31.42
11550.00	Average	23.59	12.51	36.09	54.00	-17.91
17325.00	Peak	29.47	25.79	55.26	68.20	-12.94
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ac VHT80 / 5775 MHz	Temp/Hum	24.1(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 16, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11550.00	Peak	30.44	12.51	42.95	74.00	-31.05
11550.00	Average	23.72	12.51	36.23	54.00	-17.77
17325.00	Peak	27.99	25.79	53.78	68.20	-14.42
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5745 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11490.00	Peak	32.74	12.39	45.13	74.00	-28.87
11490.00	Average	27.22	12.39	39.61	54.00	-14.39
17235.00	Peak	28.60	26.10	54.70	68.20	-13.50
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5745 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11490.00	Peak	32.18	12.39	44.57	74.00	-29.43
11490.00	Average	25.58	12.39	37.97	54.00	-16.03
17235.00	Peak	28.61	26.10	54.72	68.20	-13.48
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5785 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11570.00	Peak	31.41	12.49	43.90	74.00	-30.10
11570.00	Average	25.93	12.49	38.42	54.00	-15.58
17355.00	Peak	28.85	25.47	54.31	68.20	-13.89
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5785 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11570.00	Peak	30.64	12.49	43.13	74.00	-30.87
11570.00	Average	25.06	12.49	37.55	54.00	-16.45
17355.00	Peak	29.77	25.47	55.24	68.20	-12.96
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5825 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11650.00	Peak	32.20	12.43	44.63	74.00	-29.37
11650.00	Average	26.80	12.43	39.23	54.00	-14.77
17475.00	Peak	29.43	25.06	54.49	68.20	-13.71
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE20 / 5825 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11650.00	Peak	31.90	12.43	44.33	74.00	-29.67
11650.00	Average	26.93	12.43	39.36	54.00	-14.64
17475.00	Peak	29.10	25.06	54.16	68.20	-14.04
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5755 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
11510.00	Peak	31.60	12.43	44.03	74.00	-29.97
11510.00	Average	24.82	12.43	37.25	54.00	-16.75
17265.00	Peak	28.40	26.14	54.54	68.20	-13.66
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5755 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11510.00	Peak	32.18	12.43	44.61	74.00	-29.39
11510.00	Average	24.95	12.43	37.38	54.00	-16.62
17265.00	Peak	29.23	26.14	55.37	68.20	-12.83
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5795 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11590.00	Peak	30.58	12.48	43.05	74.00	-30.95
11590.00	Average	24.44	12.48	36.92	54.00	-17.08
17385.00	Peak	29.14	25.27	54.41	68.20	-13.79
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE40 / 5795 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11590.00	Peak	31.60	12.48	44.08	74.00	-29.92
11590.00	Average	23.80	12.48	36.28	54.00	-17.72
17385.00	Peak	29.15	25.27	54.42	68.20	-13.78
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5775 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11550.00	Peak	33.01	12.51	45.51	74.00	-28.49
11550.00	Average	23.32	12.51	35.83	54.00	-18.18
17325.00	Peak	29.15	25.79	54.94	68.20	-13.26
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	IEEE 802.11ax HE80 / 5775 MHz	Temp/Hum	24.5(℃)/ 57%RH
Test Item	Harmonic	Test Date	May 17, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak & Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBµV)	Factor (dB)	Actual FS (dBµV/m)	Limit @3m (dBµV/m)	Margin (dB)
11550.00	Peak	31.17	12.51	43.68	74.00	-30.32
11550.00	Average	23.18	12.51	35.69	54.00	-18.32
17325.00	Peak	29.63	25.79	55.42	68.20	-12.78
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。