



FCC RADIO TEST REPORT

Applicant : D-Link Corporation

Address : 14420 Myford Road Suite 100 Irvine California
United States 92606

Equipment : BE3600 Wi-Fi 7 Smart Mesh Router,
Wi-Fi 7 BE3600 Mesh Router

Model No. : M36

Trade Name : D-Link

FCC ID : KA2M36B1

I HEREBY CERTIFY THAT :

The sample was received on Dec. 24, 2024 and the testing was completed on May. 08, 2025 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Mark Liao / Supervisor

Laboratory Accreditation:

CerpPASS Technology Corporation Test Laboratory





Contents

1. Summary of Test Procedure and Test Results	5
1.1 Applicable Standards	5
2. Test Configuration of Equipment under Test	6
2.1 Feature of Equipment under Test	6
2.2 Carrier Frequency of Channels	7
2.3 Test Mode and Test Software	8
2.4 Description of Test System	10
2.5 General Information of Test	11
2.6 Measurement Uncertainty	12
3. Test Equipment and Ancillaries Used for Tests	13
4. Antenna Requirements	17
4.1 Standard Applicable	17
4.2 Antenna Construction and Directional Gain	17
5. Test of AC Power Line Conducted Emission	18
5.1 Test Limit	18
5.2 Test Procedures	18
5.3 Typical Test Setup	19
5.4 Test Result and Data	20
5.5 Test Photographs	22
6. Test of Radiated Spurious Emission	23
6.1 Test Limit	23
6.2 Test Procedures	24
6.3 Typical Test Setup	25
6.4 Test Result and Data (9KHz ~ 30MHz)	26
6.5 Test Result and Data (30MHz ~ 1GHz)	26
6.6 Test Result and Data (1GHz ~ 25GHz)	28
6.7 Restricted Bands of Operation	52
6.8 Test Photographs (30MHz ~ 1GHz)	53
6.9 Test Photographs (1GHz ~ 25GHz)	54
7. Test of Conducted Spurious Emission	56
7.1 Test Limit	56
7.2 Test Procedure	56
7.3 Test Setup Layout	56
7.4 Test Result and Data	56
8. On Time, Duty Cycle and Measurement methods	69
8.1 Test Limit	69
8.2 Test Procedure	69
8.3 Test Setup Layout	69
8.4 Test Result and Data	69
9. 6dB Bandwidth Measurement Data	71
9.1 Test Limit	71
9.2 Test Procedures	71



9.3	Test Setup Layout	71
9.4	Test Result and Data	71
10.	Maximum Average Output Power	76
10.1	Test Limit	76
10.2	Test Procedures	76
10.3	Test Setup Layout	76
10.4	Test Result and Data	77
11.	Power Spectral Density	78
11.1	Test Limit	78
11.2	Test Procedures	78
11.3	Test Setup Layout	78
11.4	Test Result and Data	79



History of this test report

Report No.	Issued Date	Description
24090397-TRFCC01	May. 19, 2025	Original



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

ANSI C63.10:2013

FCC Rules and Regulations Part 15 Subpart C §15.247

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	PASS
15.207	. AC Power Line Conducted Emission	PASS
15.209 15.205	. Radiated Spurious Emission	PASS
15.247(d)	. Conducted Spurious Emission	PASS
15.247(a)(2)	. 6dB Bandwidth	PASS
15.247(b)	. Output Power	PASS
15.247(e)	. Power Spectral Density	PASS
2.1091	. Radio Frequency Exposure	PASS

*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement, measurement uncertainty evaluation is not considered.



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Operation Frequency Range	802.11b/g/n(Turbo QAM)/ax/be : 2400-2483.5MHz 802.11a/n/ac/ax/be: 5150-5250MHz, 5250-5350MHz, 5470-5725MHz, 5725-5875MHz
Center Frequency Range	802.11b/g/n(Turbo QAM)/ax/be : 2412-2462MHz 802.11a/n/ac/ax/be: 5180-5240MHz, 5260-5320MHz, 5500-5720MHz, 5745-5825MHz
Modulation Type	2.4GHz: 802.11b: CCK, DQPSK, DBPSK 802.11g/n: BPSK, QPSK, 16QAM, 64QAM, 256QAM(TurboQAM) 802.11ax: BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM 802.11be: BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM 5GHz: 802.11n/a: BPSK, QPSK, 16QAM, 64QAM 802.11ac: BPSK, QPSK, 16QAM, 64QAM, 256QAM 802.11ax: BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM 802.11be: BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM
Modulation Technology	DSSS, OEDM, OFDMA
Data Rate	2.4GHz: 802.11b: 1, 2, 5.5, 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0 – MCS15,HT20/40 MCS0 – MCS9, VHT20/40(TurboQAM) 802.11ax: MCS0 – MCS11,HE20/40 802.11be: MCS0 – MCS13,EHT20/40 5GHz: 802.11a: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0 – MCS15, HT20/40 802.11ac: MCS0 – MCS9, VHT20/40/80/160 802.11ax: MCS0 – MCS11,HE20/40/80/160 802.11be: MCS0 – MCS13,EHT20/40/80/160
Antenna Type	Dipole Antenna
Antenna Gain	2412-2484MHz: ANT B:1.57dBi, ANT C: 1.58dBi 5180-5260MHz: ANT A 1.68dBi, ANT D: 1.82dBi 5260-5320MHz: ANT A 1.63dBi, ANT D: 1.89dBi 5500-5700MHz: ANT A 1.72dBi, ANT D: 2.01dBi 5745-5875MHz: ANT A 1.73dBi, ANT D: 1.97dBi
Adapter	1. Brand: AMIGO Model: AMS200-1201500FU 2. Brand: AMIGO Model: AMS200-1201500F
RJ45 Cable	Brand: Nienyi /Model: NYS6200

Note:

1. EUT support TPC Function.
2. EUT support AP Mode (Master)
3. EUT support Bridge/Extender/Mesh Mode(Master/Client).
4. EUT Only Support Full RU
5. WLAN 2.4GHz 802.11ax/be support beamforming Function.
6. WLAN 5GHz 802.11ax/be support beamforming Function.
7. For more details, please refer to the User's manual of the EUT.



2.2 Carrier Frequency of Channels

802.11b, 802.11g, 802.11n HT20, VHT20, 802.11ax HE20, 802.11be EHT20

Channel	Frequency(MHz)	Channel	Frequency(MHz)
*01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	*11	2462
*06	2437	---	---

802.11n HT40, VHT40, 802.11ax HE40, 802.11be EHT40

Channel	Frequency(MHz)	Channel	Frequency(MHz)
---	---	07	2442
---	---	08	2447
*03	2422	*09	2452
04	2427	---	---
05	2432	---	---
*06	2437	---	---

Note: Channels remarked * are selected to perform test.



2.3 Test Mode and Test Software

- During testing, the interface cables and equipment positions were varied according to ANSI C63.10.
- The complete test system included remote workstation and EUT for RF test. The remote workstation included Notebook.
- An executive program, "QSPR V6.00.00164.3" under Windows OS system was executed to transmit and receive data via WLAN.
- The following test modes were performed for the test:

Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
1	TX Mode, 802.11b, Power from Adapter.
2	TX Mode, 802.11g, Power from Adapter.
3	TX Mode, 802.11be EHT20, Power from Adapter.
4	TX Mode, 802.11be EHT40, Power from Adapter.
caused "Test Mode 3" generated the worst case, it was reported as the final data.	
Radiation Emissions (9KHz ~30MHz & 30MHz ~ 1GHz)	
Test Mode	Operating Description
1	TX Mode, 802.11b , Power from Adapter.
2	TX Mode, 802.11g, Power from Adapter.
3	TX Mode, 802.11be EHT20, Power from Adapter.
4	TX Mode, 802.11be EHT40, Power from Adapter.
caused "Test Mode 3" generated the worst case, they were reported as the final data.	
Radiation Emissions (1GHz ~ 25GHz)	
Test Mode	Operating Description
1	TX Mode, 802.11b , Power from Adapter.
2	TX Mode, 802.11g, Power from Adapter.
3	TX Mode, 802.11be EHT20, Power from Adapter.
4	TX Mode, 802.11be EHT40, Power from Adapter.
caused "Test Mode 1~4" generated the worst case, they were reported as the final data.	

Note:

1.Non-Beamforming was the worst case, so it was used for the test result.

2. There are two kinds of test voltage: AC 120V / 60Hz and AC 240V / 60Hz. worst case (V)

Test Item /test voltage	AC 120V / 60Hz	AC 240V / 60Hz.
AC Power Line Conducted Emission:	V	
Radiation Emissions (Below 1GHz)	V	

3.The EUT has Two types of Adapters. After engineering evaluation,
For AC Power Line Conducted Emission, AMS200-1202000F is worst case.
For Radiated Spurious Emission(Below 1GHz), AMS200-1202000FU is
worst case.

For Radiated Spurious Emission(Above 1GHz), AMS200-1202000FU is worst case.,
hence, are used at test report



The EUT incorporates a MIMO function

Modulation Type	TX CONFIGURATION
802.11b	2TX
802.11g	2TX
802.11n HT20	2TX
802.11n HT40	2TX
802.11n HT20(TurboQAM)	2TX
802.11n HT40(TurboQAM)	2TX
802.11ax HE20	2TX
802.11ax HE40	2TX
802.11be EHT20	2TX
802.11be EHT40	2TX



2.4 Description of Test System

Non-beamforming

RF Conducted				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	DELL	Latitude 7490	N/A	Adapter / 1.8m / NS
RJ45 Cable	TE CONNECTIVITY	CAT5E	1.2m / NS	N/A
Radiated Emissions				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	DELL	Latitude 7490	N/A	Adapter / 1.8m / NS
AC Power Line Conducted Emission				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	DELL	Latitude 7490	N/A	Adapter / 1.8m / NS

Beamforming

RF Conducted				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	DELL	Latitude 7490	N/A	Adapter / 1.8m / NS
RJ45 Cable	TE CONNECTIVITY	CAT5E	1.2m / NS	N/A



2.5 General Information of Test

Organization	CerpPASS Technology Corp.		
☒ Test Site	CerpPASS Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel: +886-3-3226-888 Fax: +886-3-3226-881		
	FCC	TW1439, TW1079	
	IC	4934E-1, 4934E-2	
Frequency Range Investigated	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 25,000MHz		
Test Distance	The test distance of radiated emission from antenna to EUT is 3 M.		

Non-beamforming

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2025/01/03	20.9°C / 54%	Leon Huang
RF Conducted	RFCON01-NK	2025/01/04	23.9°C / 45%	Leon Huang
RF Conducted	RFCON01-NK	2025/01/08	25°C / 50%	Leon Huang
RF Conducted	RFCON01-NK	2025/03/08	22.2°C / 49%	Leon Huang
RF Conducted	RFCON01-NK	2025/05/08	25.8°C / 47%	Leon Huang
Radiated Emissions	3M02-NK	2025/01/02	19.8°C / 50%	Park Chen
Radiated Emissions	3M02-NK	2025/03/20	20.3°C / 56%	Park Chen
AC Power Line Conducted Emission	CON02-NK	2025/03/20	17.1°C / 55%	Park Chen

Beamforming

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2025/01/11	22.4°C / 47%	Leon Huang
AC Power Line Conducted Emission	CON02-NK	2025/02/24	17.1°C / 55%	Leon Huang
AC Power Line Conducted Emission	CON02-NK	2025/02/24	17.1°C / 55%	Leon Huang



2.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Item	Uncertainty
AC Power Line Conduction(150K~30MHz)	±3.2dB
Radiated Spurious Emission(9KHz~30MHz)	±3.5dB
Radiated Spurious Emission(30MHz~1GHz)	±5.1dB
Radiated Spurious Emission(1GHz~40GHz)	±5.2dB
Conducted Spurious Emission	±2.1dB
6dB Bandwidth	±5.4%
20dB Bandwidth	±4.4%
Occupied Bandwidth	±4.5%
Peak Output Power(Conducted Power Meter)	±1.1dB
Dwell Time / Deactivation Time	±7.6%
Power Spectral Density	±2.0dB
Duty Cycle	±3.5%



3. Test Equipment and Ancillaries Used for Tests

Non-beamforming

Test Item	Radiated Emissions (2025/1/2)				
Test Site	Semi Anechoic Room(3M02-NK)				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Bilog Antenna	Schwarzbeck	VULB9168	369	2024/02/19	2025/02/18
Active Loop Antenna	Schwarzbeck	FMZB 1513	414	2024/01/16	2025/01/15
Horn Antenna	EMCO	3115	31589	2024/02/26	2025/02/25
Horn Antenna	EMCO	3116	31970	2024/02/23	2025/02/22
EMI Receiver	ROHDE & SCHWARZ	ESR 7	101906	2024/05/13	2025/05/12
Spectrum Analyzer	ROHDE & SCHWARZ	FSV 40-N	101329	2024/07/16	2025/07/15
Preamplifier	Agilent	8449B	3008A01954	2024/03/01	2025/02/28
Preamplifier	EMC INSTRUMENTS	EMC184045	980065	2024/10/15	2025/10/14
Preamplifier	EM Electronics corp.	EM330	60659	2024/12/16	2025/12/15
Cable-4m(9k-3G)	EMEC	RG-223	18274M	2024/08/08	2025/08/07
Cable-3in1(30M-1G)	HARBOUR INDUSTRIES	LL142	CCE1315	2024/02/23	2025/02/22
Cable-0.5m(1G-40G)	HUBER SUHNER	SUCOFLEX 104	805443/4	2024/03/05	2025/03/04
Cable-3m(1G-40G)	HUBER SUHNER	SUCOFLEX 104	805796/4	2024/03/05	2025/03/04
Cable-8m(1G-26.5G)	WOKEN	WCBA-WCA203SM	CCE1374	2024/03/05	2025/03/04
Cable-3m(10M-40G)	HUBER SUHNER	SF102	804619/2	2024/10/14	2025/10/13
Cable-1m(10M-40G)	HUBER SUHNER	SF102	804398/2	2024/10/14	2025/10/13
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA
High Pass Filter	WOKEN	WFIL-H3000-18000F-03	WR377WC2B1	2024/10/15	2025/10/14
Notch Filter	Warison	WFIL-N5925-7125F-04	WRQ4BFWC4M1	2024/03/11	2025/03/10
Hipass Filter	Warison	WFIL-H7500-18000F	WRQ4BFWC2J1	2024/03/11	2025/03/10



Test Item	Radiated Emissions (2025/3/20)				
Test Site	Semi Anechoic Room(3M02-NK)				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Bilog Antenna	Schwarzbeck	VULB9168	369	2025/02/17	2026/02/16
Active Loop Antenna	EMCO	6507	00040855	2024/05/02	2025/05/01
Horn Antenna	EMCO	3115	31589	2025/02/14	2026/02/13
Horn Antenna	EMCO	3116	31970	2025/02/20	2026/02/19
EMI Receiver	ROHDE & SCHWARZ	ESR 7	101906	2024/05/13	2025/05/12
Spectrum Analyzer	ROHDE & SCHWARZ	FSV 40-N	101329	2024/07/16	2025/07/15
Preamplifier	Agilent	8449B	3008A01954	2025/02/12	2026/02/11
Preamplifier	EMC INSTRUMENTS	EMC184045	980065	2024/10/15	2025/10/14
Preamplifier	EM Electronics corp.	EM330	60659	2024/12/16	2025/12/15
Cable-4m(9k-3G)	EMEC	RG-223	18274M	2024/08/08	2025/08/07
Cable-3in1(30M-1G)	HARBOUR INDUSTRIES	LL142	CCE1315	2025/02/21	2026/02/20
Cable-0.5m(1G-40G)	HUBER SUHNER	SUCOFLEX 104	805443/4	2025/02/26	2026/02/25
Cable-3m(1G-40G)	HUBER SUHNER	SUCOFLEX 104	805796/4	2025/02/26	2026/02/25
Cable-8m(1G-26.5G)	WOKEN	WCBA-WCA203SM	CCE1374	2025/02/26	2026/02/25
Cable-3m(10M-40G)	HUBER SUHNER	SF102	804619/2	2024/10/14	2025/10/13
Cable-1m(10M-40G)	HUBER SUHNER	SF102	804398/2	2024/10/14	2025/10/13
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA
High Pass Filter	WOKEN	WFIL-H3000-18000F-03	WR377WC2B1	2024/10/15	2025/10/14
Notch Filter	Warison	WFIL-N5925-7125F-04	WRQ4BFWC4M1	2025/02/21	2026/02/20
Hipass Filter	Warison	WFIL-H7500-18000F	WRQ4BFWC2J1	2025/02/21	2026/02/20

Test Item	RF Conducted(2025/01/3~2025/01/08)				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
CAX Signal Analyzer	KEYSIGHT	N9000B	MY57100339	2024/10/23	2025/10/22
Power Meter	Anritsu	ML2495A	1224005	2024/02/17	2025/02/16
Power Sensor	Anritsu	MA2411B	1207295	2024/02/17	2025/02/16
Attenuator	KEYSIGHT	8491B	MY39250703	2024/02/20	2025/02/19



Test Item	RF Conducted(2025/03/08~2025/05/08)				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
CAX Signal Analyzer	KEYSIGHT	N9000B	MY57100339	2024/10/23	2025/10/22
Power Meter	Anritsu	ML2495A	1224005	2025/02/12	2026/02/11
Power Sensor	Anritsu	MA2411B	1207295	2025/02/12	2026/02/11
Attenuator	KEYSIGHT	8491B	MY39250703	2025/02/12	2026/02/11

Test Item	AC Power Line Conducted Emission				
Test Site	CON02-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EMI Receiver	ROHDE & SCHWARZ	ESR 7	101906	2024/05/13	2025/05/12
Two-Line V-Network	ROHDE & SCHWARZ	ENV216	102185	2024/08/27	2025/08/26
Line Impedance Stabilization Network	Schwarzbeck	NSLK 8127	8127740	2024/08/27	2025/08/26
Cable-4m(9k-3G)	EMEC	RG-223	18274M	2024/08/08	2025/08/07
E3	AUDIX	v8.2014-8-6	RK-000536	NA	NA



Beamforming

Test Item	RF Conducted				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
CAX Signal Analyzer	KEYSIGHT	N9000B	MY57100339	2024/10/23	2025/10/22
Power Meter	Anritsu	ML2495A	1224005	2024/02/17	2025/02/16
Power Sensor	Anritsu	MA2411B	1207295	2024/02/17	2025/02/16
Attenuator	KEYSIGHT	8491B	MY39250703	2024/02/20	2025/02/19

Test Item	AC Power Line Conducted Emission				
Test Site	CON02-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EMI Receiver	ROHDE & SCHWARZ	ESR 7	101906	2024/05/13	2025/05/12
Cable-4m(9k-3G)	EMEC	RG-223	18274M	2024/08/08	2025/08/07
Line Impedance Stabilization Network	Schwarzbeck	NSLK 8127	8127740	2024/08/27	2025/08/26
Two-Line V-Network	ROHDE & SCHWARZ	ENV216	102185	2024/08/27	2025/08/26
E3	AUDIX	v8.2014-8-6	RK-000531	NA	NA



4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.2 Antenna Construction and Directional Gain

Antenna Type	Dipole Antenna
Antenna Gain	2412-2484MHz: ANT B: 1.57dBi ,ANT C: 1.58dBi

(Non-Beamforming)

2412-2484MHz

For Power directional gain= G_{ant} = 1.58 dBi

For PSD directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}]$
= 4.59 (dBi)

*MIMO type: Cyclic Delay Diversity (CDD) mode.

(Beamforming)

For Power directional gain= $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}]$
= 4.59 (dBi)

For PSD directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}]$
= 4.59 (dBi)



5. Test of AC Power Line Conducted Emission

5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz, according to the methods defined in ANSI C63.10-2013. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

5.2 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



5.3 Typical Test Setup






5.4 Test Result and Data

Test Mode : 2TX 11be20 CH06 NSS1 MCS0
Voltage : From Adapter(AC 120V/60Hz)
Phase : Line

Data: 21




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1562	9.63	8.48	18.11	55.66	-37.55	Average	P
2	0.1562	9.63	25.09	34.72	65.66	-30.94	QP	P
3	0.1850	9.63	6.48	16.11	54.26	-38.15	Average	P
4	0.1850	9.63	20.88	30.51	64.26	-33.75	QP	P
5	0.3995	9.65	23.49	33.14	47.86	-14.72	Average	P
6	0.3995	9.65	26.27	35.92	57.86	-21.94	QP	P
7	0.5970	9.66	4.91	14.57	46.00	-31.43	Average	P
8	0.5970	9.66	10.69	20.35	56.00	-35.65	QP	P
9	2.6571	9.71	9.42	19.13	46.00	-26.87	Average	P
10	2.6571	9.71	18.55	28.26	56.00	-27.74	QP	P
11	4.5632	9.75	7.04	16.79	46.00	-29.21	Average	P
12	4.5632	9.75	13.81	23.56	56.00	-32.44	QP	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



Test Mode : 2TX 11be20 CH06 NSS1 MCS0
Voltage : From Adapter(AC 120V/60Hz)
Phase : Neutral

Data: 22



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.2054	9.61	6.79	16.40	53.39	-36.99	Average	P
2	0.2054	9.61	21.73	31.34	63.39	-32.05	QP	P
3	0.3812	9.62	8.46	18.08	48.25	-30.17	Average	P
4	0.3812	9.62	23.24	32.86	58.25	-25.39	QP	P
5	0.5432	9.62	1.83	11.45	46.00	-34.55	Average	P
6	0.5432	9.62	13.01	22.63	56.00	-33.37	QP	P
7	0.9375	9.65	6.04	15.69	46.00	-30.31	Average	P
8	0.9375	9.65	14.41	24.06	56.00	-31.94	QP	P
9	2.6643	9.69	14.09	23.78	46.00	-22.22	Average	P
10	2.6643	9.69	25.01	34.70	56.00	-21.30	QP	P
11	7.4237	9.79	9.27	19.06	50.00	-30.94	Average	P
12	7.4237	9.79	16.98	26.77	60.00	-33.23	QP	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



6. Test of Radiated Spurious Emission

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3



6.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- i. "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.


Note:

- 1.The supporting fixture shall permit orientation of the EUT in each of three orthogonal axis positions such that emissions from the EUT are maximized.
- 2.Due to the test software function limit the operation band setting(200dBuV/m).
There's no corresponding limitation in the actual test item.




6.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup






6.4 Test Result and Data (9KHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

6.5 Test Result and Data (30MHz ~ 1GHz)

Test Mode : 2TX 11be20 CH06 NSS1 MCS0
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	43.58	-9.67	35.71	26.04	40.00	-13.96	Peak	400	0	P
2	84.32	-15.37	51.11	35.74	40.00	-4.26	QP	121	19	P
3	125.06	-12.02	46.17	34.15	43.50	-9.35	Peak	400	0	P
4	173.56	-10.13	40.95	30.82	43.50	-12.68	Peak	400	0	P
5	258.92	-10.18	37.34	27.16	46.00	-18.84	Peak	400	0	P
6	592.60	-0.45	27.43	26.98	46.00	-19.02	Peak	400	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 2TX 11be20 CH06 NSS1 MCS0
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	125.06	-12.02	45.72	33.70	43.50	-9.80	Peak	400	0	P
2	163.86	-9.66	40.93	31.27	43.50	-12.23	Peak	400	0	P
3	200.72	-12.37	38.67	26.30	43.50	-17.20	Peak	400	0	P
4	260.86	-10.14	38.27	28.13	46.00	-17.87	Peak	400	0	P
5	751.68	2.53	31.61	34.14	46.00	-11.86	Peak	400	0	P
6	837.04	3.65	28.63	32.28	46.00	-13.72	Peak	400	0	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



6.6 Test Result and Data (1GHz ~ 25GHz)

Test Mode : 2TX 11b CH01 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	46.32	43.99	54.00	-10.01	Average	233	83	P
2	2390.00	-2.33	57.27	54.94	74.00	-19.06	Peak	233	83	P
3	2412.00	-2.29	111.20	108.91	200.00	-91.09	Average	233	83	P
4	2412.00	-2.29	113.73	111.44	200.00	-88.56	Peak	233	83	P
5	4824.00	6.05	29.53	35.58	54.00	-18.42	Average	100	216	P
6	4824.00	6.05	41.52	47.57	74.00	-26.43	Peak	100	216	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 2TX 11b CH01 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	44.34	42.01	54.00	-11.99	Average	100	49	P
2	2390.00	-2.33	54.97	52.64	74.00	-21.36	Peak	100	49	P
3	2412.00	-2.29	105.04	102.75	200.00	-97.25	Average	100	49	P
4	2412.00	-2.29	107.43	105.14	200.00	-94.86	Peak	100	49	P
5	4824.00	6.05	29.20	35.25	54.00	-18.75	Average	100	315	P
6	4824.00	6.05	41.18	47.23	74.00	-26.77	Peak	100	315	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 2TX 11b CH06 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	46.17	43.84	54.00	-10.16	Average	155	97	P
2	2390.00	-2.33	56.45	54.12	74.00	-19.88	Peak	155	97	P
3	2437.00	-2.17	110.51	108.34	200.00	-91.66	Average	155	97	P
4	2437.00	-2.17	112.95	110.78	200.00	-89.22	Peak	155	97	P
5	2483.50	-2.01	42.66	40.65	54.00	-13.35	Average	155	97	P
6	2483.50	-2.01	54.88	52.87	74.00	-21.13	Peak	155	97	P
7	4874.00	6.21	28.70	34.91	54.00	-19.09	Average	100	214	P
8	4874.00	6.21	41.23	47.44	74.00	-26.56	Peak	100	214	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 2TX 11b CH06 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	43.86	41.53	54.00	-12.47	Average	100	41	P
2	2390.00	-2.33	55.12	52.79	74.00	-21.21	Peak	100	41	P
3	2437.00	-2.17	104.27	102.10	200.00	-97.90	Average	100	41	P
4	2437.00	-2.17	106.81	104.64	200.00	-95.36	Peak	100	41	P
5	2483.50	-2.01	42.29	40.28	54.00	-13.72	Average	100	41	P
6	2483.50	-2.01	55.25	53.24	74.00	-20.76	Peak	100	41	P
7	4874.00	6.21	29.68	35.89	54.00	-18.11	Average	100	311	P
8	4874.00	6.21	41.56	47.77	74.00	-26.23	Peak	100	311	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 2TX 11b CH11 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2462.00	-2.04	111.23	109.19	200.00	-90.81	Average	229	99	P
2	2462.00	-2.04	113.79	111.75	200.00	-88.25	Peak	229	99	P
3	2483.50	-2.01	43.05	41.04	54.00	-12.96	Average	229	99	P
4	2483.50	-2.01	55.19	53.18	74.00	-20.82	Peak	229	99	P
5	4924.00	6.38	29.41	35.79	54.00	-18.21	Average	100	218	P
6	4924.00	6.38	41.53	47.91	74.00	-26.09	Peak	100	218	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 2TX 11b CH11 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2462.00	-2.04	107.05	105.01	200.00	-94.99	Average	100	62	P
2	2462.00	-2.04	109.46	107.42	200.00	-92.58	Peak	100	62	P
3	2483.50	-2.01	42.35	40.34	54.00	-13.66	Average	100	62	P
4	2483.50	-2.01	55.24	53.23	74.00	-20.77	Peak	100	62	P
5	4924.00	6.38	29.54	35.92	54.00	-18.08	Average	100	317	P
6	4924.00	6.38	41.37	47.75	74.00	-26.25	Peak	100	317	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 2TX 11g CH01 6Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	44.72	42.39	54.00	-11.61	Average	180	95	P
2	2390.00	-2.33	60.38	58.05	74.00	-15.95	Peak	180	95	P
3	2412.00	-2.29	105.49	103.20	200.00	-96.80	Average	180	95	P
4	2412.00	-2.29	115.51	113.22	200.00	-86.78	Peak	180	95	P
5	4824.00	6.05	28.69	34.74	54.00	-19.26	Average	100	214	P
6	4824.00	6.05	41.33	47.38	74.00	-26.62	Peak	100	214	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 2TX 11g CH01 6Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	42.93	40.60	54.00	-13.40	Average	173	59	P
2	2390.00	-2.33	58.14	55.81	74.00	-18.19	Peak	173	59	P
3	2412.00	-2.29	100.55	98.26	200.00	-101.74	Average	173	59	P
4	2412.00	-2.29	110.63	108.34	200.00	-91.66	Peak	173	59	P
5	4824.00	6.05	28.18	34.23	54.00	-19.77	Average	100	317	P
6	4824.00	6.05	41.36	47.41	74.00	-26.59	Peak	100	317	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 2TX 11g CH06 6Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	44.00	41.67	54.00	-12.33	Average	151	96	P
2	2390.00	-2.33	57.37	55.04	74.00	-18.96	Peak	151	96	P
3	2437.00	-2.17	105.21	103.04	200.00	-96.96	Average	151	96	P
4	2437.00	-2.17	115.37	113.20	200.00	-86.80	Peak	151	96	P
5	2483.50	-2.01	41.24	39.23	54.00	-14.77	Average	151	96	P
6	2483.50	-2.01	56.32	54.31	74.00	-19.69	Peak	151	96	P
7	4874.00	6.21	28.77	34.98	54.00	-19.02	Average	100	214	P
8	4874.00	6.21	41.27	47.48	74.00	-26.52	Peak	100	214	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 2TX 11g CH06 6Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	42.02	39.69	54.00	-14.31	Average	164	61	P
2	2390.00	-2.33	55.19	52.86	74.00	-21.14	Peak	164	61	P
3	2437.00	-2.17	100.42	98.25	200.00	-101.75	Average	164	61	P
4	2437.00	-2.17	110.92	108.75	200.00	-91.25	Peak	164	61	P
5	2483.50	-2.01	40.85	38.84	54.00	-15.16	Average	164	61	P
6	2483.50	-2.01	54.85	52.84	74.00	-21.16	Peak	164	61	P
7	4874.00	6.21	28.57	34.78	54.00	-19.22	Average	100	311	P
8	4874.00	6.21	41.02	47.23	74.00	-26.77	Peak	100	311	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 2TX 11g CH11 6Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2462.00	-2.04	105.35	103.31	200.00	-96.69	Average	227	98	P
2	2462.00	-2.04	115.22	113.18	200.00	-86.82	Peak	227	98	P
3	2483.50	-2.01	44.35	42.34	54.00	-11.66	Average	227	98	P
4	2483.50	-2.01	59.02	57.01	74.00	-16.99	Peak	227	98	P
5	4924.00	6.38	28.38	34.76	54.00	-19.24	Average	100	212	P
6	4924.00	6.38	41.87	48.25	74.00	-25.75	Peak	100	212	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 2TX 11g CH11 6Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal




No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2462.00	-2.04	101.83	99.79	200.00	-100.21	Average	165	63	P
2	2462.00	-2.04	111.51	109.47	200.00	-90.53	Peak	165	63	P
3	2483.50	-2.01	43.98	41.97	54.00	-12.03	Average	165	63	P
4	2483.50	-2.01	58.08	56.07	74.00	-17.93	Peak	165	63	P
5	4924.00	6.38	28.84	35.22	54.00	-18.78	Average	100	315	P
6	4924.00	6.38	41.22	47.60	74.00	-26.40	Peak	100	315	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 2TX 11be EHT20 CH01 NSS1 MCS0
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	46.63	44.30	54.00	-9.70	Average	337	93	P
2	2390.00	-2.33	64.34	62.01	74.00	-11.99	Peak	337	93	P
3	2412.00	-2.29	104.21	101.92	200.00	-98.08	Average	337	93	P
4	2412.00	-2.29	116.64	114.35	200.00	-85.65	Peak	337	93	P
5	4824.00	6.05	29.15	35.20	54.00	-18.80	Average	100	212	P
6	4824.00	6.05	41.54	47.59	74.00	-26.41	Peak	100	212	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Test Mode : 2TX 11be EHT20 CH01 NSS1 MCS0
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	43.59	41.26	54.00	-12.74	Average	123	23	P
2	2390.00	-2.33	57.19	54.86	74.00	-19.14	Peak	123	23	P
3	2412.00	-2.29	99.78	97.49	200.00	-102.51	Average	123	23	P
4	2412.00	-2.29	110.99	108.70	200.00	-91.30	Peak	123	23	P
5	4824.00	6.05	29.60	35.65	54.00	-18.35	Average	100	310	P
6	4824.00	6.05	41.47	47.52	74.00	-26.48	Peak	100	310	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor