



TEST REPORT

No. 2014WLA0068

For

Client : D-Link Corporation

Production : EVDO Mobile Hotspot

Model Name : DWR-330

FCC ID: KA2WR330A1

Hardware Version: A1

Software Version: V1.00

Issued date: 2014-08-13

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of ECIT Shanghai.

Test Laboratory:

ECIT Shanghai, East China Institute of Telecommunications

Add: 7-8F, G Area, No.668, Beijing East Road, Huangpu District, Shanghai, P. R. China

Tel: (+86)-021-63843300, E-Mail: welcome@ecit.org.cn

CONTENTS

1.	TEST LABORATORY	4
1.1.	TESTING LOCATION.....	4
1.2.	TESTING ENVIRONMENT.....	4
1.3.	PROJECT DATA	4
1.4.	SIGNATURE	4
2.	CLIENT INFORMATION.....	5
2.1.	APPLICANT INFORMATION	5
2.2.	MANUFACTURER INFORMATION	5
3.	EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1.	ABOUT EUT	6
3.2.	INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	6
3.3.	INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	6
4.	REFERENCE DOCUMENTS	7
4.1.	REFERENCE DOCUMENTS FOR TESTING.....	7
5.	SUMMARY OF TEST RESULTS.....	8
5.1.	NOTES.....	9
5.2.	STATEMENTS	9
6.	TEST RESULT	10
6.1.	MAXIMUM OUTPUT POWER.....	10
6.1.1.	MAXIMUM PEAK OUTPUT POWER-CONDUCTED	10
6.1.2.	MAXIMUM AVERAGE OUTPUT POWER-CONDUCTED.....	11
6.2.	PEAK POWER SPECTRAL DENSITY	12
6.3.	OCCUPIED 6DB BANDWIDTH	15
6.4.	BAND EDGES COMPLIANCE	17

6.5.	TRANSMITTER SPURIOUS EMISSION-CONDUCTED.....	21
6.6.	TRANSMITTER SPURIOUS EMISSION-RADIATED.....	32
6.7.	AC POWERLINE CONDUCTED EMISSION.....	46
7.	TEST EQUIPPMENTS AND ANCILLARIES USED FOR TESTS.....	51
8.	TEST ENVIRONMENT	53
ANNEX A DEVIATIONS FROM PRESCRIBED TEST METHODS		55

1. Test Laboratory

1.1. Testing Location

Company Name:	ECIT Shanghai, East China Institute of Telecommunications
Address:	7-8F, G Area, No. 668, Beijing East Road, Huangpu District, Shanghai, P. R. China
Postal Code:	200001
Telephone:	(+86)-021-63843300
Fax:	(+86)-021-63843301


1.2. Testing Environment

Normal Temperature:	15-35°C
Extreme Temperature:	-10/+55°C
Relative Humidity:	20-75%

1.3. Project data

Project Leader:	Gong Yujuan
Testing Start Date:	2014-08-02
Testing End Date:	2014-08-12

1.4. Signature


Wang Daming
(Prepared this test report)


Liu Jianquan
(Reviewed this test report)


Zheng Zhongbin
Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: D-Link Corporation
Address: No.289,Sinhu 3rd rd., Neihu District, Taipei City114, Taiwan
Telephone: +886-2-66000123-5821
Postcode: 114

2.2. Manufacturer Information

Company Name: D-Link Corporation
Address: No.289,Sinhu 3rd rd., Neihu District, Taipei City114, Taiwan
Telephone: +886-2-66000123-5821
Postcode: 114

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

EUT Description	EVDO Mobile Hotspot
Model name	DWR-330
WLAN Frequency	2412MHz-2462MHz
WLAN Channel	Channel1-Channel11
WLAN type of modulation	802.11b:DSSS 802.11g/n: OFDM
Nominal Voltage	3.7V
Extreme High Voltage	4.1V
Extreme Low Voltage	3.3V

Note: Photographs of EUT are shown in ANNEX A of this test report.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
N04	N/A	A1	v1.00	2014-02-20

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	RF cable	---
AE2	---	---

*AE ID: is used to identify the test sample in the lab internally.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part15	FCC CFR 47, Part 15,Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.	2014
ANSI C63.10	American National Standard for Testing Unlicensed Wireless Devices	2009

5. Summary of Test Results

A brief summary of the tests carried out is shown as following.

Measurement Items	Sub-clause of Part15C	Sub-clause of IC	Verdict
Maximum Peak Output Power	15.247(a)	/	P
Peak Power Spectral Density	15.247(e)	/	P
Occupied 6dB Bandwidth	15.247(d)	/	P
Band Edges Compliance	15.247(b)	/	P
Transmitter Spurious Emission-Conducted	15.247	/	P
Transmitter Spurious Emission-Radiated	15.247,15.209,	/	P
AC Powerline Conducted Emission	15.107,15.207	/	P

Please refer to part 5 for detail.

The measurements are according to ANSI C63.10.

Terms used in Verdict column

P	Pass, the EUT complies with the essential requirements in the standard.
NP	Not Perform, the test was not performed by ECIT.
NA	Not Applicable, the test was not applicable.
F	Fail, the EUT does not comply with the essential requirements in the standard.

Test Conditions

Tnom	Normal temperature
Tmin	Low Temperature
Tmax	High Temperature
Vnom	Normal Voltage
Vmin	Low Voltage
Vmax	High Voltage
Hnom	Norm Humidity
Anom	Norm Air Pressure

For this report, all the test case listed above are tested under Normal Temperature and Normal Voltage, and also under norm humidity, the specific conditions as following:

Temperature	Tnom	22℃
Voltage	Vnom	3.7V
Humidity	Hnom	32%
Air Pressure	Anom	1010hPa

5.1. Notes

All reported tests were carried out on a sample equipment to demonstrate limited compliance with section 3.

The test results of this test report relate exclusively to the item(s) tested as specified in section 5.

The following deviation from, additions to, or exclusions from the test specifications have been made. See section 3.

5.2. Statements

The product name DWR-330 , supporting WLAN, manufactured by D-Link Corporation is a new product for testing.

ECIT has verified that the compliance of the tested device specified in section 5 of this test report is successfully evaluated according to the procedure and test methods as defined in type certification requirement listed in section 5 of this test report.

6. Test result

6.1. Maximum Output Power

Measurement Limit and method:

Standard	Limit(dBm)
FCC CRF 15.247(b)	< 30

The measurement is according to ANSI C63.10, and power output option 1 (RBW=20MHz) is used for the test. EUT is operated in continuous transmitting mode.

Measurement Uncertainty:

Measurement Uncertainty	0.75dB
-------------------------	--------

6.1.1. Maximum Peak Output Power-conducted

Measurement Results:

802.11b/g mode

Mode	Data Rate(Mbps)	Test Result(dBm)		
		2412MHz(Ch1)	2437MHz(Ch6)	2462MHz(Ch11)
802.11b	1	18.11	17.92	17.98
	2	17.56	/	/
	5.5	17.71	/	/
	11	17.84	/	/
802.11g	6	18.79	/	/
	9	18.94	18.82	18.68
	12	18.61	/	/
	18	18.63	/	/
	24	18.79	/	/
	36	18.57	/	/
	48	18.63	/	/
	54	18.71	/	/

The data rate 1Mbps and 9Mbps are selected as worse condition, and the following cases are performed with this condition.

802.11n mode

Mode	Data Rate(Index)	Teat Result(dBm)		
		2412MHz(Ch1)	2437MHz(Ch6)	2462MHz(Ch11)
802.11n(20MHz)	MCS0	18.63	/	/
	MCS1	18.46	/	/
	MCS2	18.61	/	/
	MCS3	18.35	/	/
	MCS4	17.92	/	/
	MCS5	18.41	/	/
	MCS6	18.59	/	/
	MCS7	18.80	18.17	18.23
802.11n(40MHz)	MCS0	/	/	/
	MCS1	/	/	/
	MCS2	/	/	/
	MCS3	/	/	/
	MCS4	/	/	/
	MCS5	/	/	/
	MCS6	/	/	/
	MCS7	/	/	/

The data rate MCS7 is selected as worse condition, and the following case are performed with this condition.

6.1.2. Maximum Average Output Power-conducted
802.11b/g mode

Mode	Test Result(dBm)		
	2412MHz(Ch1)	2437MHz(Ch6)	2462MHz(Ch11)
802.11b	15.28	14.95	14.87
802.11g	12.21	12.15	12.17

802.11n mode

Mode	Test Result(dBm)		
	2412MHz(Ch1)	2437MHz(Ch6)	2462MHz(Ch11)
802.11n(20MHz)	12.62	12.27	12.39
802.11n(40MHz)	/	/	/

Conclusion: PASS

6.2. Peak Power Spectral Density

Measure Limit:

Standard	Limit
FCC CFR Part 15.247(e)	< 8dBm/3 KHz

The measurement is according to ANSI C63.10.

Measurement Uncertainty:

Measurement Uncertainty	0.75dB
-------------------------	--------

Test procedures:

1. Connect the EUT to spectrum analyzer.
2. Set RBW=3KHz, VBW=10KHz,span more than 1.5 times channel bandwidth.

Detector =peak, sweep time=auto couple, trace mode=max hold.

Measurement Results:
802.11b/g mode

Mode	Channel	Power Spectral Density(dBm/3kHz)		Conclusion
802.11b	1	/	/	/
	6	Fig.1	-11.75	P
	11	/	/	/
802.11g	1	/	/	/
	6	/	/	/
	11	Fig.2	-6.39	P


802.11n mode

Mode	Channel	Power Spectral Density(dBm/3kHz)		Conclusion
802.11n(20MHz)	1	/	/	/
	6	/	/	/
	11	Fig.3	-16.05	P

802.11g(40MHz)	1	/	/	P
	6	/	/	P
	11	/	/	P


Conclusion: PASS

Test graphs as below:




Date: 13.AUG.2014 11:16:32

Fig.1 Power Spectral Density (802.1b,Ch6)



Date: 21.JAN.2014 14:00:40

Fig.2 Power Spectral Density (802.1g,Ch11)



Date: 13.AUG.2014 11:28:23

Fig.3 Power Spectral Density (802.1n-20MHz,Ch11)

6.3. Occupied 6dB Bandwidth

Measurement Limit:

Standard	Limit(KHz)
FCC 47 CFR Part 15.247(a)	≥500

The measurement is according to ANSI C63.10.

Measurement Uncertainty:

Measurement Uncertainty	60.80Hz
-------------------------	---------

Test procedures:

1. Connect the EUT to spectrum analyzer.
2. Set RBW=100KHz, VBW=300KHz,span more than 1.5 times channel bandwidth.
3. Detector =peak, sweep time=auto couple, trace mode=max hold.

Measurement Result:
802.11b/g mode


Mode	Channel	Occupied 6dB Bandwidth(MHz)		Conclusion
802.11b	1	Fig.4	10.25	P
	6	/	/	/
	11	/	/	/
802.11g	1	/	/	/
	6	Fig.5	16.50	P
	11	/	/	/

802.11n mode

Mode	Channel	Occupied 6dB Bandwidth(MHz)		Conclusion
802.11n(20MHz)	1	/	/	/
	6	Fig.6	17.87	P
	11	/	/	/
802.11n(40MHz)	1	/	/	/
	6	/	/	/
	11	/	/	/


Conclusion: PASS

Test graphs as below:




Date: 4.MAY.2014 09:59:16

Fig.4 Occupied 6dB Bandwidth (802.11b, Ch1)



Date: 4.MAY.2014 10:18:19

Fig.5 Occupied 6dB Bandwidth (802.11g, Ch6)



Date: 4.MAY.2014 10:30:01

Fig.6 Occupied 6dB Bandwidth (802.11n-20MHz, Ch6)

6.4. Band Edges Compliance

Measurement Limit:

Standard	Limited(dBc)
FCC 47 CFR Part 15.247(d)	>20

The measurement is according to ANSI C63.10.

Measurement Uncertainty:

Measurement Uncertainty	0.75dB
-------------------------	--------

Test procedures:

1. Connect the EUT to spectrum analyzer.
2. Set RBW=100KHz, VBW=300KHz.
3. Detector =peak, sweep time=auto couple, trace mode=max hold.

802.11b/g mode


Mode	Channel	Test Results	Conclusion
802.11b	1	Fig.7	P
	11	Fig.8	P
802.11g	1	Fig.9	P
	11	Fig.10	P

802.11n mode

Mode	Channel	Test Results	Conclusion
802.11n(20MHz)	1	Fig.11	P
	11	Fig.12	P
802.11(40MHz)	/	/	/
	/	/	/


Conclusion: PASS

Test graphs as blew:




Date: 4.MAY.2014 10:54:59

Fig.7 Band Edges (802.11b, Ch1)




Date: 4.MAY.2014 11:11:12

Fig.8 Band Edges (802.11b, Ch11)




Date: 4.MAY.2014 11:38:55

Fig.9 Band Edges (802.11g, Ch1)




Date: 4.MAY.2014 13:22:13

Fig.10 Band Edges (802.11g, Ch11)



Date: 4.MAY.2014 13:36:29

Fig.11 Band Edges (802.11n-20MHz, Ch1)



Date: 4.MAY.2014 13:37:25

Fig.12 Band Edges (802.11b-20MHz, Ch11)

6.5. Transmitter Spurious Emission-conducted

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(d)	20dB below peak output power in 100KHz bandwidth

This measurement is according to ANSI C63.10.

Measurement Uncertainty:

Frequency Range	Uncertainty
30MHz ≤ f ≤ 2GHz	0.63
2GHz ≤ f ≤ 3.6GHz	0.82
3.6GHz ≤ f ≤ 8GHz	1.55
8GHz ≤ f ≤ 20GHz	1.86
20GHz ≤ f ≤ 22GHz	1.90
22GHz ≤ f ≤ 26GHz	2.20

Measurement Result:

802.11b/g mode

Mode	Channel	Frequency Range	Test Results	Conclusion


802.11b	1	2.412GHz	Fig.13	P
		30MHz~26GHz	Fig.14	P
	6	2.437GHz	Fig.15	P
		30MHz~26GHz	Fig.16	P
	11	2.472GHz	Fig.17	P
		30MHz~26GHz	Fig.18	P
802.11g	1	2.412GHz	Fig.19	P
		30MHz~26GHz	Fig.20	P
	6	2.437GHz	Fig.21	P
		30MHz~26GHz	Fig.22	P
	11	2.472GHz	Fig.23	P
		30MHz~26GHz	Fig.24	P

802.11n mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n(20MHz)	1	2.412GHz	Fig.25	P
		30MHz~26GHz	Fig.26	P
	6	2.437GHz	Fig.27	P
		30MHz~26GHz	Fig.28	P
	11	2.472GHz	Fig.29	P
		30MHz~26GHz	Fig.30	P
802.11n(40MHz)	1	/	/	/
		/	/	/
	6	/	/	/
		/	/	/
	11	/	/	/
		/	/	/


Conclusion: PASS

Test graphs as below:




Date: 4.MAY.2014 14:12:34

Fig.13 Conducted Spurious Emission (802.11b, Ch1)




Date: 4.MAY.2014 14:15:38

Fig.14 Conducted Spurious Emission (802.11b, Ch1, 30MHz~26GHz)




Date: 4.MAY.2014 14:19:00

Fig.15 Conducted Spurious Emission (802.11b, Ch6)




Date: 4.MAY.2014 14:20:40

Fig.16 Conducted Spurious Emission (802.11b, Ch6, 30MHz~26GHz)




Date: 4.MAY.2014 14:23:34

Fig.17 Conducted Spurious Emission (802.11b, Ch11)




Date: 4.MAY.2014 14:24:09

Fig.18 Conducted Spurious Emission (802.11b, Ch11, 30MHz~26GHz)




Date: 4.MAY.2014 14:25:36

Fig.19 Conducted Spurious Emission (802.11g, Ch1)




Date: 4.MAY.2014 14:26:10

Fig.20 Conducted Spurious Emission (802.11g, Ch1, 30MHz~26GHz)




Date: 4.MAY.2014 14:28:35

Fig.21 Conducted Spurious Emission (802.11g, Ch6)




Date: 4.MAY.2014 14:29:10

Fig.22 Conducted Spurious Emission (802.11g, Ch6, 30MHz~26GHz)




Date: 4.MAY.2014 14:34:50

Fig.23 Conducted Spurious Emission (802.11g, Ch11)




Date: 4.MAY.2014 14:35:53

Fig.24 Conducted Spurious Emission (802.11g, Ch11, 30MHz~26GHz)




Date: 4.MAY.2014 14:38:41

Fig.25 Conducted Spurious Emission (802.11n-20MHz, Ch1)




Date: 4.MAY.2014 14:40:00

Fig.26 Conducted Spurious Emission (802.11n-20MHz, Ch1, 30MHz~26GHz)




Date: 4.MAY.2014 14:42:51

Fig.27 Conducted Spurious Emission (802.11n-20MHz, Ch6)




Date: 4.MAY.2014 14:44:37

Fig.28 Conducted Spurious Emission (802.11n-20MHz, Ch6, 30MHz~26GHz)



Date: 4.MAY.2014 14:45:43

Fig.29 Conducted Spurious Emission (802.11n-20MHz, Ch11)



Date: 4.MAY.2014 14:46:03

Fig.30 Conducted Spurious Emission (802.11n-20MHz, Ch11, 30MHz~26GHz)

6.6. Transmitter Spurious Emission-Radiated**Measurement Limit:**

Standard	Limit
FCC 47 CFR Part 15.247,15.205,15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in 25.205(a), must also comply with the radiated emission limits specified in 15.209(a)(see 15.205(c)). The measurement is according to ANSI C63.10

Limit in restricted band:

Frequency of emission(MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30~88	100	40
88~216	150	43.5
216~960	200	46
Above 960	500	54

Test condition:

Portable, small, lightweight, or modular devices that may be handheld, worn on the body, or placed on a table during operation shall be positioned on a nonconducting platform, the top of which is 80 cm above the reference ground plane. The preferred area occupied by the EUT arrangement is 1 m by 1.5 m, but it may be larger or smaller to accommodate various sized EUTs. For testing purposes, ceiling- and wall-mounted devices also shall be positioned on a tabletop (see also ANSI C63.10-2009 section 6.3.4 and 6.3.5). In making any tests involving handheld, body-worn, or ceiling-mounted equipment, it is essential to recognize that the measured levels may be dependent on the orientation (attitude) of the three orthogonal axes of the EUT. Thus, exploratory tests as specified in 8.3.1 shall be carried out for various axes orientations to determine the attitude having maximum or near-maximum emission level.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During testing, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emission from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Times (s)
30~1000	100KHz/300KHz	5
1000~4000	1MHz/1MHz	15

4000~18000	1MHz/1MHz	40
18000~26500	1MHz/1MHz	20

802.11b/g mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11b	Power	2.38GHz~2.45GHz	Fig.31	P
	Power	2.45GHz~2.5GHz	Fig.32	P
	1	30MHz~1GHz	Fig.33	P
		1GHz~3GHz	Fig.34	P
		3GHz~18GHz	Fig.35	P
802.11g	Power	2.38GHz~2.45GHz	Fig.36	P
	Power	2.45GHz~2.5GHz	Fig.37	P
	11	30MHz~1GHz	Fig.38	P
		1GHz~3GHz	Fig.39	P
		3GHz~18GHz	Fig.40	P

802.11n mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n(20MHz)	Power	2.38GHz~2.45GHz	Fig.41	P
	Power	2.45GHz~2.5GHz	Fig.42	P
	1	30MHz~1GHz	Fig.43	P
		1GHz~3GHz	Fig.44	P
		3GHz~18GHz	Fig.45	P
/	All channels	18GHz~26.5GHz	Fig.46	P

Conclusion: PASS

Note:

A "reference path loss" is established and A_{Rpi} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result= $P_{Mea} + A_{Rpi} = P_{Mea} + \text{Cable Loss}$.

802.11b mode

Ch1 30MHz~1GHz

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
34.410952	10.2	0.61	9.59	V
69.86642	23.7	0.86	22.84	V
209.14542	36.3	1.91	34.39	H
279.536352	32.2	2.66	29.54	H
419.852336	32.9	3.27	29.63	H

Ch1 1GHz~3GHz

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
2753.6116	52.5	12.64	39.86	V
2807.2464	52.4	12.99	39.41	V

Ch1 3GHz~18GHz

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
4924.019067	56.9	7.1	49.8	H
6565.254067	51.4	8.72	42.68	H
7385.022667	50.4	10.73	39.67	H

802.11g

Ch11 30MHz~1GHz

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
34.62038	12.4	0.61	11.79	V
69.726492	27.5	1.91	25.59	V
209.881872	36.7	2.66	34.04	H
279.866432	37.4	3.27	34.13	H
419.855224	32.5	4.29	28.21	V

Ch11 1GHz~3GHz

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
----------------	----------------	-----------	--------------	----------

2822.7226	53.3	12.99	40.31	V
2861.7572	53.3	13.93	39.37	H

Ch11 3GHz~18GHz

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
4928.856667	47.3	7.1	40.2	H
6565.1866	48.5	8.72	39.78	H
7380.408933	54.7	10.73	43.97	H

802.11n-20MHz

Ch1 30MHz~1GHz

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
34.475284	11.7	0.86	10.84	V
69.714792	27.3	1.56	25.74	V
209.871672	32.1	3.32	28.78	H

Ch1 1GHz~3GHz

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
1256.5016	43.2	12.64	30.56	V
2659.0316	51.5	12.99	38.51	V
2775.115	52.4	13.93	38.47	H

Ch1 3GHz~18GHz


Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
6565.2648	53.2	8.72	44.48	H
7393.170067	51.8	10.73	41.07	V
12201.12513	46.2	11.93	34.27	H
17275.01207	49.6	13.3	36.3	V

All Ch 18GHz~26.5GHz


Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
----------------	----------------	-----------	--------------	----------

19560.60	47.0	6.96	40.04	V
20440.35	43.0	6.96	36.04	V
22736.20	42.1	3.05	39.05	V
24072.40	43.0	3.05	39.95	V
26183.80	42.1	3.05	39.05	H

Test graphs as below:




Pk detector




Av detector

Fig.31 Radiated emission (Power): 802.11b, low channel



Pk detector



Av detector

Fig.32 Radiated emission (Power): 802.11b, high channel




Fig.33 Radiated Spurious Emission (802.11b,Ch1,30MHz~1GHz)




Fig.34 Radiated Spurious Emission (802.11b,Ch1,1GHz~3GHz)






Fig.35 Radiated Spurious Emission (802.11b,Ch1,3GHz~18GHz)




Pk detector




Av detector

Fig.36 Radiated emission (Power): 802.11g, low channel



Pk detector



Av detector

Fig.37 Radiated emission (Power): 802.11g, high channel




Fig.38 Radiated Spurious Emission (802.11g,Ch11,30MHz~1GHz)




Fig.39 Radiated Spurious Emission (802.11g,Ch11,1GHz~3GHz)






Fig.40 Radiated Spurious Emission (802.11g,Ch11,3GHz~18GHz)




Pk detector




Av detector

Fig.41 Radiated emission (Power): 802.11n, low channel



Pk detector



Av detector

Fig.42 Radiated emission (Power): 802.11n, high channel




Fig.43 Radiated Spurious Emission (802.11 n-20MHz,Ch1,30MHz~1GHz)




Fig.44 Radiated Spurious Emission (802.11 n-20MHz,Ch1,1GHz~3GHz)




Fig.45 Radiated Spurious Emission (802.11 n-20MHz,Ch1,3GHz~18GHz)




Fig.46 Radiated emission: GFSK, 18 GHz – 26.5 GHz

6.7. AC powerline Conducted Emission

Test condition:

Voltage (V)	Frequency (Hz)
120	60

Measurement Result and Limit:

WLAN (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBuV)	Result (dBuV)		Conclusion
		With charger		
		802.11n	Idle	
0.15 to 0.5	66 to 56	Fig.47	Fig.47	P
0.5 to 5	66			
5 to 30	60			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5MHz.

WLAN (Average Limit)

Frequency range (MHz)	Average Limit (dBuV)	Result (dBuV)		Conclusion
		With charger		
		802.11n	Idle	
0.15 to 0.5	55 to 46	Fig.48	Fig.48	P
0.5 to 5	46			
5 to 30	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5MHz.

The measurement is according to ANSI C63.4 and KDB558074.

Conclusion: PASS

Test graphs as below:




Fig.47 AC Powerline Conducted Emission 802.11n

Measurement result: "QP"

Frequency (MHz)	QuasiPeak (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.179850	43.1	1000.0	9.000	On	L1	10.2	21.4	64.5
0.623869	31.8	1000.0	9.000	On	L1	10.1	24.2	56.0
1.444744	36.6	1000.0	9.000	On	L1	9.9	19.4	56.0
2.254425	36.6	1000.0	9.000	On	L1	9.8	19.4	56.0
4.183481	26.8	1000.0	9.000	On	L1	9.8	29.2	56.0
17.892094	27.3	1000.0	9.000	On	L1	9.9	32.7	60.0

Measurement result: "AV"

Frequency (MHz)	Average (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.179850	31.8	1000.0	9.000	On	L1	10.2	22.7	54.5
0.623869	21.5	1000.0	9.000	On	L1	10.1	24.5	46.0
1.444744	25.8	1000.0	9.000	On	L1	9.9	20.2	46.0
2.254425	25.1	1000.0	9.000	On	L1	9.8	20.9	46.0
4.183481	17.4	1000.0	9.000	On	L1	9.8	28.6	46.0
17.892094	18.6	1000.0	9.000	On	L1	9.9	31.4	50.0




Fig.48 AC AC Powerline Conducted Emission Idle

Measurement result: "QP"

Frequency (MHz)	QuasiPeak (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.176119	35.0	1000.0	9.000	On	N	10.2	29.7	64.7
0.358950	34.9	1000.0	9.000	On	L1	10.1	23.9	58.8
1.008188	35.0	1000.0	9.000	On	L1	9.9	21.0	56.0
2.179800	36.3	1000.0	9.000	On	L1	9.8	19.7	56.0
14.556356	26.9	1000.0	9.000	On	L1	9.9	33.1	60.0
17.242856	27.0	1000.0	9.000	On	L1	9.9	33.0	60.0

Measurement result: "AV"

Frequency (MHz)	Average (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.176119	25.6	1000.0	9.000	On	N	10.2	29.1	54.7
0.358950	26.5	1000.0	9.000	On	L1	10.1	22.3	48.8
1.008188	24.2	1000.0	9.000	On	L1	9.9	21.8	46.0
2.179800	24.4	1000.0	9.000	On	L1	9.8	21.6	46.0
14.556356	17.3	1000.0	9.000	On	L1	9.9	32.7	50.0
17.242856	17.9	1000.0	9.000	On	L1	9.9	32.1	50.0

7. Test Equipments and Ancillaries Used For Tests

The test equipments and ancillaries used are as follows.

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date
1	Vector Signal Analyzer	FSQ26	101096	R&S	2014-08-30
2	DC Power Supply	ZUP60-14	LOC-220Z006	TDL-Lambda	2014-08-30

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date
1	Universal Radio Communication Tester	CMU200	123102	R&S	2014-08-30
2	Test Receiver	ESCI	101235	R&S	2014-08-30
3	Test Receiver	ESU40	100307	R&S	2014-10-29
4	Trilog Antenna	VULB9163	19-162515	Schwarzbeck	2014-11-11
5	Double Ridged Guide Antenna	ETS-3117	135885	ETS	2017-03-01
6	2-Line V-Network	ENV216	101380	R&S	2014-10-30

7	Single Phase Harmonic & Flicker	DPA500N	V112610998 8	EM Test	2014-10-28
8	Multifunction AC/DC Power Source	Netwave7	V112610998 9	EM Test	2014-10-28
9	Ultra Compact Simulator	UCS 500N7	V112610998 3	EM Test	2014-07-22
10	Motorized Variac	MV 2616	V112610998 7	EM Test	2014-07-22
11	Telecom Surge Module	TSurge7	V090210458 2	EM Test	2014-07-22
12	Audio Analyzer	UPV	101950	R&S	2014-08-30
13	Power Meter	NRP2	101804	R&S	2014-08-30
14	Signal Generator	SMB 100A	105563	R&S	2014-08-30
15	ESD Test Simulator	Dito	V112610998 2	EM Test	2014-10-31

Anechoic chamber

Fully anechoic chamber by Frankonia German.

8. Test Environment

Shielding Room1 (6.0 meters×3.0 meters×2.7 meters) did not exceed following limits along the conducted RF performance testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80MHz to 3000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber1 (6.8 meters×3.08 meters×3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80MHz to 3000 MHz

Fully-anechoic chamber2 (Tapered Section: 8.75 meters×3.66 meters×3.66 meters, Rectangular Section: 7.32 meters×3.97 meters×3.66 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %

Shielding effectiveness	> 110 dB
Electrical insulation	> 10 k Ω
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 30MHz to 40000MHz

ANNEX A Deviations from Prescribed Test Methods

No deviation from Prescribed Test Methods.

*******END OF REPORT*******