

EXHIBIT VI.

Supplemental Test Report WLAN

New Certification of Previously Certified OEM Module

FCC ID: KBCIX260A750MPIBT

IX260 Rugged Laptop with Aircard 750 GPRS radio modem

co-located with

WLAN & Bluetooth Intentional Radiators

This report is for the WLAN for

Certification Under Title 47 CFR, Part 15.247

ITRONIX, Corporation

South 801 Stevens St.
Spokane, WA 99204

Prepared

By

Spectrum Technology, Inc.
209 Dayton Street, Suite 205
Edmonds, WA 98020
425 771-4482

Prepared August 8, 2003

Supplemental Test Report

TABLE OF CONTENTS

Cover Page	1
Table Of Contents	2
Exhibit 6A – Conducted RF Power Output Part 15.247 (b) & Equivalent Isotropic Radiated Power	3
Exhibit 6A - Field Strength of Three Fundamental Operating Frequencies	4
Exhibit 6G – Radiated Harmonics and Spurious Emissions	5

Note: Please refer to the original Certification exhibits for all of the original OEM test report data for the ITRONIX Corporation, Intentional Radiator referenced herein:

1.) FCC ID: LDK102042 which is the OEM filing for the WLAN Compact Flash Card, Model: MPI-352 Series

EXHIBIT 6A - TEST: CONDUCTED RF POWER OUTPUT

Applicant: ITRONIX, Corporation

Model: IX260 Rugged Laptop with Aircard 750 GPRS radio modem
co-located with WLAN & Bluetooth Intentional Radiators

Minimum Standard Specified: Part 15.247(b)(1) is 1 Watt for DTS

Test Results: The measured output power level shows compliance with the
above limit and the power granted for the OEM module.

Authorization Procedure: Part 2.1046

Maximum Conducted Power Output: 21.2 dBm

Method of Measurement:

1. The output power levels above had been preset during production for this model.
2. The peak output power was measured by Celltech with a Gigatronics 8652A Universal Power Meter (S/N: 1835272). The measured channels cover the low, middle and top of the operational frequency range previously approved for this Intentional Radiator of 2412 – 2462 MHz.
4. Both antenna ports were measured, the results below were the maximum level measured.

Tabular Results of Conducted RF Output Power and EIRP

WLAN			Rangestar		
Serial No:			Antenna		
VMS06180144			P/N 100929		
Frequency	Power	Cable loss	Ant. Gain	EIRP	
GHz	dBm		dBi		
2.412	21.2	-inc-	4.5	25.7	*MAX
2.437	21.1	-inc-	4.5	25.6	
2.462	21.1	-inc-	4.5	25.6	

The maximum **WLAN** EIRP is 25.7 dBm with the Rangestar Antenna, P/N 100929, peak antenna gain of 4.5 dBi.

EXHIBIT 6G - TEST: FIELD STRENGTH OF THREE FUNDAMENTAL OPERATING FREQUENCIES

Applicant: ITRONIX, Corporation

Model: IX260 Rugged Laptop with Aircard 750 GPRS radio modem co-located with a WLAN & Bluetooth Intentional Radiators

Minimum Standard Specified: Part 15.247(c), 15.205 & 15.209(a)

Test Results: Equipment complies with standard

Authorization Procedure: Part 2.1053

Test Equipment Set Up: See Block Diagram in Exhibit 7

Test Frequencies **WLAN**: 2412, 2437, & 2462 MHz (2412 – 2462 MHz band)

Field Strength For Low Mid and High Channel

WLAN Frequency in GHz	Ant. Vert/ Horz	Spectrum Analyzer Reading dBuV	+ Ant Factor	- Amp Gain	+ Cable Loss	= dBuV/m @ 3 meters	or uV/m @ 3 meters
Ch. 1 Low 2.412	V	84.67	28.37	0	1.33	114.37	522997.96
Ch. 6 Mid 2.437	V	85.67	28.37	0	1.33	115.37	586813.36
Ch.11 High 2.462	V	86.33	28.37	0	1.33	116.03	633140.36

Measurements were made with the MPI350 feeding the left antenna in the PC display only, for this co-located model. The right antenna in the display is used by the Bluetooth Intentional radiator exclusively in this configuration and covered under a different test report.

EXHIBIT 6G - TEST: RADIATED HARMONICS AND SPURIOUS EMISSIONS

Applicant: ITRONIX, Corporation

Model: IX260 Rugged Laptop with Aircard 750 GPRS radio modem
co-located with a WLAN & Bluetooth Intentional Radiators

Minimum Standard Specified: Part 15.247(c), 15.205 & 15.209(a)

Authorization Procedure: Part 2.1053

Test Equipment Set Up: See Block Diagram in Exhibit 7

RADIATED HARMONIC AND SPURIOUS EMISSIONS & RESTRICTED BANDS									
Frequency GHz	Max. SA Rdg. dBuV	Ant. Vert. or Horz.	Peak or Average Detector	Antenna Factor dB	Cable & filter loss dB	Amp Gain	Corrected Reading dBuV/m	Limit 74 Peak 54 Avg dBuV	uV/m
Fo - 2.412									
4.824	35.83	V	Peak	32.83	3.95	23.2	49.41	74	295.46
4.824	23.17	V	Average	32.83	3.95	23.2	36.75	54	68.78
Fo - 2.437									
4.874	37.00	V	Peak	33.33	3.95	23.2	51.00	74	358.09
4.874	23.50	V	Average	33.33	3.95	23.2	37.58	54	75.68
Fo - 2.462									
4.924	37.0	V	Peak	33.33	3.95	23.2	51.00	74	358.09
4.924	23.33	V	Average	33.33	3.95	23.2	37.41	54	74.21
Harmonic emissions on all three channels (low, mid & high) 3Fo – 10Fo at or below noise floor									
Channel	Frequency in GHz	Harmonics observed		Limit 74 dBuV/m Peak & 54 dBuV/m Average					
Ch. 1 - Low Fo	2.412								
3Fo - 10Fo	7.236 – 24.120	None, At or < noise floor @3m		All emissions < 54 dBuV/m or 500 uV/m					
Ch. 6 - Mid Fo	2.437								
3Fo - 10Fo	7.311 – 24.370	None, At or < noise floor @3m		All emissions < 54 dBuV/m or 500 uV/m					
Ch. 11 - High Fo	2.462								
3Fo - 10Fo	7.386 – 24.620	None, At or < noise floor @3m		All emissions < 54 dBuV/m or 500 uV/m					

All harmonic and spurious emissions were below the limit. 2Fo and 3Fo were measurable during preliminary measurements at less than 1.0 meter with 100 kHz RBW only. Only 2 Fo was measurable at three meters with 1 MHz RBW and VBW. A HP preamplifier with over 20 dB of gain was used during the measurements of the harmonics. A high pass filter was used to reduce the fundamental signal and avoid the possibility of overloading the front end of the analyzer when using the preamp.

Test Notes:

- 1.) All harmonics in the restricted bands listed in Part 15.205 are below the Part 15.209(a) limit.
- 2.) No peak emissions above 1 GHz are more than 20 dB above the average limit.
- 3.) Peak measurements made with 1 MHz RBW & VBW, Average made with 1MHz RBW & 10 Hz VBW.
- 4.) The maximum levels reported above were with the MPI350 connected to and radiating from the left antenna within the PC display.