

DECLARATION OF COMPLIANCE MPE EVALUATION REPORT

Test Lab

CELLTECH LABS INC.

1955 Moss Court
Kelowna, B.C.
Canada V1Y 9L3
Phone: 250-448-7047
Fax: 250-448-7046
e-mail: info@celltechlabs.com
web site: www.celltechlabs.com

Applicant Information

ITRONIX CORPORATION

801 South Stevens Street
Spokane, WA 99204
United States

FCC IDENTIFIER:

KBCIX260PNL3AC555

IC IDENTIFIER:

1943A-IX260Pb

Model(s):

IX260PNL3AC555

FCC Rule Part(s):

47 CFR §24(E), §22(H); §2.1091; §1.1310

IC Rule Part(s):

RSS-133 Issue 2, RSS-132 Issue 1 (Provisional)

FCC Classification:

PCS Licensed Transmitter (PCB)

IC Classification:

2 GHz Personal Communication Services (RSS-133)

Device Description:

**800 MHz Cellular Telephones Employing New Technologies (RSS-132)
Rugged Laptop PC with Sierra Wireless AirCard 555/550 CDMA Modem,
External Swivel Dipole Antenna, Vehicle-Mount Antenna, & Vehicle Cradle
Senao NL-3054MP Mini-PCI 802.11b/g WLAN Card with Internal Antenna**

Co-located Transmitter(s):

Tx Frequency Range(s):

**1851.25 - 1908.75 MHz (PCS CDMA)
824.70 - 848.31 MHz (Cellular CDMA)**

Max. RF Output Power Measured:

**23.0 dBm Conducted (PCS CDMA)
23.0 dBm Conducted (Cellular CDMA)**

Antenna Type(s) Evaluated:

**Itronix IX260+ External Swivel Dipole (Dual-Band CDMA)
MaxRad 3 dBi Vehicle-Mount P/N: WMLPVDB800/1900 (Dual-Band CDMA)**

This mobile transmitting device was determined to be compliant with localized Maximum Permissible Exposure (MPE) for Uncontrolled Exposure / General Population limits specified in FCC 47 CFR §1.1310 and Industry Canada RSS-102 Issue 1 (Provisional), in accordance with the requirements of FCC OET Bulletin 65, Edition 97-01, Health Canada's Safety Code 6, ANSI / IEEE C95.1-1999, and ANSI / IEEE C95.3-2002.

I attest to the accuracy of data. All measurements and/or calculations were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

This evaluation report shall not be reproduced partially, or in full, without the prior written approval of Celltech Labs Inc. The results and statements contained in this report pertain only to the device(s) evaluated.



Russell Pipe
Senior Compliance Technologist
Celltech Labs Inc.



Duane M. Friesen
EMC Manager
Celltech Labs Inc.



1.1 MPE Calculation Data

1. Itronix IX260+ Swivel Dipole Antenna

a. PCS CDMA Band

Tx Frequency: **1880.00** (MHz)
 RF Output Power at Antenna Input Terminal: **23.0** (dBm)
 Antenna gain: **2.60** (dBi)

S = **1.00** (mW/cm²)
 P = **199.5262** (mW)
 G = **1.82** (numeric)

R = 5.38 (cm)

S (mw/cm²) at 20cm
 0.072153826

b. Cellular CDMA Band

Tx Frequency: **835.89** (MHz)
 RF Output Power at Antenna Input Terminal: **23.0** (dBm)
 Antenna gain: **2.60** (dBi)

S = **0.56** (mW/cm²)
 P = **199.5262** (mW)
 G = **1.82** (numeric)

R = 7.20 (cm)

S (mw/cm²) at 20cm
 0.072153826



Itronix IX260+ Swivel Dipole Antenna

MPE Calculation Data (Cont.)

2. MaxRad 3 dBi Gain Vehicle-Mount Antenna (P/N: WMLPVD800/1900)

a. PCS CDMA Band

Tx Frequency: **1880.00** (MHz)
 RF Output Power at Antenna Input Terminal: **23.0** (dBm)
 3 dBi Antenna Gain minus 2.80 dB cable loss for 17 ft cable: **0.20** (dBi)

S= **1.00** (mW/cm²)
 P= **199.5262** (mW)
 G= **1.05** (numeric)

R = 4.08 (cm)

S (mw/cm²) at 20cm

0.041520193

b. Cellular CDMA Band

Tx Frequency: **835.89** (MHz)
 RF Output Power at Antenna Input Terminal: **23.0** (dBm)
 3 dBi Antenna Gain minus 1.88 dB cable loss for 17 ft cable: **1.10** (dBi)

S= **0.56** (mW/cm²)
 P= **199.5262** (mW)
 G= **1.29** (numeric)

R = 6.06 (cm)

S (mw/cm²) at 20cm

0.051080997



MaxRad 3 dBi Gain
 Vehicle-Mount Antenna
 P/N: WMLPVD800/1900

2.1 Calculation to determine MPE

$$S = \frac{PG}{4\pi R^2}$$

$$R = \sqrt{\frac{PG}{4\pi S}}$$

S= power density
P= power input to the antenna
G= power gain of the antenna in the direction of interest relative to an isotropic radiator
R= distance to the center of radiation of the antenna

3.1 MPE Limits

According to FCC 47 CFR 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
30-300	61.4	0.163	1.0	6
300-1500	...	...	F/300	6
1500-100,000	...	...	5	6
(B)Limits For General Population / Uncontrolled Exposure				
30-300	27.5	0.073	0.2	30
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

4.1 Summary

The Maximum Permissible Exposure (MPE) limit (General Population / Uncontrolled Exposure environment) for the frequency range in the PCS CDMA band (1850-1910 MHz) is 1.0 mW/cm²; and the limit for the frequency range in the cellular CDMA band (824-849 MHz) is 0.6 mW/cm² (F/1500). The data in this report demonstrates that the Itronix Corporation Model: IX260PNL3AC555 Rugged Laptop PC with internal Sierra Wireless AirCard 555/550 Dual-Band CDMA Modem, utilizing an external swivel dipole antenna and vehicle-mount antenna, complies with the Maximum Permissible Exposure (MPE) requirements specified in FCC §2.1091, §1.1310, OET Bulletin 65 (Edition 97-01), and Health Canada's Safety Code 6 for the General Population / Uncontrolled Exposure environment.

Notes:

1. The 17 ft antenna cable is supplied with and connected to the vehicle antenna at time of purchase.
2. The dual-band CDMA modem, 802.11b/g WLAN, and respective antennas do not transmit simultaneously.
3. Please refer to the Part 15.247 EMC test report for MPE evaluation data of the 802.11b/g WLAN transmitter.