



September 14, 2000

Federal Communications Commission
Equipment Approval Services
7435 Oakland Mills Road
Columbia, MD 21046
Attn: Andy Leimer

SUBJECT: ITRONIX CORPORATION
FCC ID: KBCXC6250RIM801D
731 Confirmation No.: EA98559
Correspondence Reference No.: 16092

Dear Andy,

On behalf of Itronix Corporation we hereby submit the following amendment in response to your e-mail dated September 14 requesting additional information for the subject application.

1. The modem will only be operated in the 806-821 MHz frequency range in accordance with the emission mask limits specified in 90.210(g) of the FCC Rules. The modem is capable of operating up to 825MHz and therefore was tested accordingly. Please refer to the previously submitted frequency attestation statement from the applicant confirming the above.
2. Please find attached the calibration certificate and gain information for the dipole antenna used for the ERP measurements. The following is a detailed description of the ERP signal substitution measurement method used:

The EUT is first placed into the field test area at 3.0 meters. The field of maximum intensity is found by rotating the EUT approximately 360 degrees and changing the height of the receive antenna from 1 to 4 meters. Both horizontal and vertical polarizations are investigated. The field strength is recorded from a calibrated spectrum analyzer for each channel being performed. The EUT is then replaced with a calibrated dipole of a well-known gain. The dipole is fed through a directional coupler and the power at the coupler port is monitored. The field of maximum intensity is found for the dipole and the power adjusted in order to read the same on the spectrum analyzer that was found for the EUT. The feed point for the dipole is then connected to a calibrated power meter and the power adjusted to read the same as the coupler port previously recorded, to account for any mismatch in impedance, which may occur at the dipole antenna. The forward power for the dipole is then determined. The actual ERP level is determined by adding the forward power and the calibrated gain of the dipole.

If you have any further questions or comments, please contact the undersigned.

Sincerely,

A handwritten signature in black ink, appearing to read 'Shawn McMillen', is written over a vertical line.

Shawn McMillen
General Manager
Celltech Research Inc.
Testing & Engineering Lab

cc: Itronix Corporation



ITRONIX®

801 S. STEVENS STREET
SPOKANE, WA 99204

509.624.6600
800.441.1309
FAX 509.626.4203
www.itronix.com

August 29, 2000

Federal Communications Commission
Equipment Authorization Branch
7435 Oakland Mills Road
Columbia, MD 21046

Reference: ITRONIX CORPORATION
FCC ID: KBCXC6250RIM801D
731 CONFIRMATION NO.: EA98559

Gentlemen,

The RIM 801D radio incorporated in Itronix laptop PC was tested to its capability of 806-825MHz frequency range. In order to comply with the requirements of 90.210(g), all 801D radios in mass production will operate and be limited to the 806-821MHz frequency range, as requested on the submitted FCC Form 731 and to be listed on the FCC grant.

If you have any questions regarding this matter, please do not hesitate to contact me.

Sincerely,

Fred Phillips
Certification Engineer
Itronix Corporation



Cert I.D. 6557

Lab Code 115844/1207.01

P.O. Box 80589 78708-0589
2205 Kramer Lane, Austin, TX., 78753-4002
(512) 835-4684

Certificate of Calibration Conformance

Page 1 of 3

The instrument identified below has been individually calibrated in compliance with the following standard(s):

ANSI C63.5 - 1988, American National Standard for Electromagnetic Compatibility-Radiated Emission Measurements in Electromagnetic Interference (EMI) Control-Calibration of Antennas, American National Standards Institute, Inc.

Environment: Laboratory MTE is maintained in a temperature controlled environment with ambient conditions from 18 to 28 C, relative humidity less than 90%. The instrument under test has been calibrated on an open air test site (OATS) with environment temperature conditions ranging from 0 to 40 C which has no known influences on measurement quality.

Manufacturer:	EMCO	Operating Range:	400 - 1000 MHz
Model Number:	3121C-DB4	Instrument Type:	DIPOLE Balun 4
Date Code/SN:	0003 - 1494		
Tracking Number:	J 49718		
Date Completed:	04-Apr-00		
Test Type:	3 and 10 Meter, Horizontal		
Calibration Uncertainty:	03m	400 - 1000 MHz, +/-1.0 dB;	
(95% Confidence Level)	10m	400 - 1000 MHz, +/-1.0 dB;	

Test Remarks: None

Recall/Interval: 18 Month Factory Calibration Provided

Calibration Traceability: All Measuring and Test Equipment (MTE) identified below are traceable to the National Institute for Standards and Technology (NIST). Calibration Laboratory and Quality System controls are compliant with the objectives of MIL-STD 45662A, ISO/IEC Guide 25 and ANSI/NC SL Z540-1.

Standards and Equipment Used:

Make / Model / Name / S/N / Recall Date

Anritsu	MS4623A	Network Analyzer	992201	14-Jun-00
---------	---------	------------------	--------	-----------


Condition of Instrument

On Release:

In Tolerance


Calibration Completed By

Lee D. Thompson, Cal Lab Technician


Attested and Issued on 04-Apr-00

Rick Flores, Calibration Lab Manager



Gain and Antenna Factors for Dipole Antenna
Manufactured by EMC Test Systems
Model Number: DB-4 Serial Number: 1494
3.0 Meter Calibration Polarization: Horizontal

Frequency (MHz)	Antenna Factor (dB/m)	Gain Numeric	Gain dBi
400	21.0	1.35	1.3
425	21.3	1.42	1.5
450	21.6	1.48	1.7
475	21.9	1.54	1.9
500	22.2	1.58	2.0
525	22.9	1.48	1.7
550	23.6	1.38	1.4
575	24.3	1.28	1.1
600	25.0	1.19	0.7
625	25.2	1.24	0.9
650	25.4	1.29	1.1
675	25.5	1.34	1.3
700	25.7	1.39	1.4
725	26.2	1.31	1.2
750	26.8	1.24	0.9
775	27.3	1.17	0.7
800	27.9	1.10	0.4
825	27.9	1.15	0.6
850	28.0	1.20	0.8
875	28.1	1.26	1.0
900	28.1	1.31	1.2
925	28.4	1.30	1.1
950	28.7	1.28	1.1
975	29.0	1.26	1.0
1000	29.3	1.24	0.9