



318/433MHz V1.10
PROGRAMMING CARD

Press "PROG" button + [ENTER] + [INSTALLER CODE] + [SECTION]
+ *required data* + [ENTER]

* = DEFAULT SETTING

Section	Data	Description
[00]	__/_/_/_/_/_/_	Installer Code* (757575)
[01]	__/_/_/_/_/_/_	User Access Code 1
[02]	__/_/_/_/_/_/_	User Access Code 2
[03]	__/_/_/_/_/_/_	User Access Code 3
[04]	__/_/_/_/_/_/_	User Access Code 4
[05]	__/_/_/_/_/_/_	User Access Code 5
[06]	__/_/_/_/_/_/_	User Access Code 6
[07]	__/_/_/_/_/_/_	User Access Code 7
[08]	__/_/_/_/_/_/_	User Access Code 8

- [09] Press [ENTER] & button 1 twice to assign RC to User 1 ☐
- [10] Press [ENTER] & button 1 twice to assign RC to User 2 ☐
- [11] Press [ENTER] & button 1 twice to assign RC to User 3 ☐
- [12] Press [ENTER] & button 1 twice to assign RC to User 4 ☐
- [13] Press [ENTER] & button 1 twice to assign RC to User 5 ☐
- [14] Press [ENTER] & button 1 twice to assign RC to User 6 ☐
- [15] Press [ENTER] & button 1 twice to assign RC to User 7 ☐
- [16] Press [ENTER] & button 1 twice to assign RC to User 8 ☐

Remote Control Options

	Keys (on/off)							
	[1]	[2]	[3]	[4]	[5]	[6]	[7]	[8]
Section [17]:	User 1	__	__	__	__	__	__	__
Section [18]:	User 2	__	__	__	__	__	__	__
Section [19]:	User 3	__	__	__	__	__	__	__
Section [20]:	User 4	__	__	__	__	__	__	__
Section [21]:	User 5	__	__	__	__	__	__	__
Section [22]:	User 6	__	__	__	__	__	__	__
Section [23]:	User 7	__	__	__	__	__	__	__
Section [24]:	User 8	__	__	__	__	__	__	__

OFF	Key	On
	[1]	} Set arming methods see table on next page
	[2]	
	[3]	
Disabled	[4]	* Button 1 PGM Enabled
Disabled	[5]	* Button 2 PGM Enabled
Disabled	[6]	* Button 3 PGM Enabled
Disabled	[7]	* Button 4 PGM Enabled
Disabled	[8]	* Panic Enabled (simultaneously press buttons 1 and 2 to activate a panic alarm)

 = Button 1

 = Button 2

References to button 3 & 4 refer to 4-button remote controls.

Key [1]	Key [2]	Key [3]	Description
Off	Off	Off	No Arming & Disarming
On	Off	Off	* Button 1 = Regular Arming
Off	On	Off	Button 2 = Regular Arming
On	On	Off	Button 1 = Regular Arming Button 2 = Regular Arming
Off	Off	On	Button 1 = Away Arming
On	Off	On	Button 1 = Away Arming Button 2 = Stay Arming
Off	On	On	Button 1 = Regular Arming Button 2 = Stay Arming
On	On	On	Button 1 = Stay Arming

Panic Output Programming

Section [25]: (select one digit only)



- [0] = Disabled
- [1] = Activate output 1 on panic alarm
- [2] = Activate output 2 on panic alarm
- * [3] = Activate output 3 on panic alarm
- [4] = Activate output 4 on panic alarm

Panic Lockout Timer

Section [26]: (select one digit only)



- * [0] = Disabled
- [1] = 30 second signal lockout on panic alarm
- [2] = 60 second signal lockout on panic alarm
- [3] = 90 second signal lockout on panic alarm
- [4] = 120 second signal lockout on panic alarm

PGM Options Timing

Section [27]: PGM 1 (select one digit only)

Section [28]: PGM 2 (select one digit only)

Section [29]: PGM 3 (select one digit only)

Section [30]: PGM 4 (select one digit only)



- [0] = Latched [3] = 10 seconds [6] = 60 seconds
- [1] = 1 second [4] = 20 seconds [7] = 2 minutes
- * [2] = 5 seconds [5] = 40 seconds [8] = 4 minutes

PGM Options

Keys (on/off)

[1] [2] [3] [4]

PGM1 PGM2 PGM3 PGM4

Section [31]: Button 1 (default: [1] on)

Section [32]: Button 2 (default: [2] on)

Section [33]: Button 3 (default: [3] on)

Section [34]: Button 4 (default: [4] on)

Key ON activates corresponding PGM

Key OFF disables corresponding PGM

Section [35]: General Options

OFF	Key	ON
4-Digit [1]		* 6-Digit Access Codes
PGM only [2]		* Panic activates enabled PGM & sends panic command to control panel

P ▲ R ▲ D O X
 SECURITY SYSTEMS
 780 Industrial Blvd., St-Eustache, Montreal,
 Quebec, Canada J7R 5V3
 Fax: (450) 491-2313 <http://www.paradox.ca>

Paradox Security Systems
 Graphic Dept.
 PRINTED IN CANADA -11/98