

|                                |        |        |        |        |      |                      |      |       |      |          |      |          |      |                       |      |  |  |
|--------------------------------|--------|--------|--------|--------|------|----------------------|------|-------|------|----------|------|----------|------|-----------------------|------|--|--|
| Compliance Consulting Services |        |        |        |        |      | Radiated Emissions   |      |       |      |          |      |          |      | Date: 4 December 1998 |      |  |  |
| FCC Part 15.205                |        |        |        |        |      |                      |      |       |      |          |      |          |      |                       |      |  |  |
|                                |        |        |        |        |      |                      |      |       |      |          |      |          |      |                       |      |  |  |
| Company: P-COM                 |        |        |        |        |      | Test Distance: 1 ft. |      |       |      |          |      |          |      |                       |      |  |  |
| FCC ID: KINDM2                 |        |        |        |        |      |                      |      |       |      |          |      |          |      |                       |      |  |  |
| Model: 320                     |        |        |        |        |      |                      |      |       |      |          |      |          |      |                       |      |  |  |
| s/n: 196                       |        |        |        |        |      |                      |      |       |      |          |      |          |      |                       |      |  |  |
|                                |        |        |        |        |      | 16 dBi antenna       |      |       |      |          |      |          |      |                       |      |  |  |
|                                |        |        |        |        |      |                      |      |       |      |          |      |          |      |                       |      |  |  |
|                                |        |        |        |        |      |                      |      |       |      |          |      |          |      |                       |      |  |  |
| Ch.                            | P, dBm | F(MHz) | PK     | AV     | AF   | CL                   | Amp  | Dist  | DUTY | TOT      | AL   | LIM      | IT   | MARGIN                |      |  |  |
|                                |        |        | (dBuV) | (dBuV) | (dB) | (dB)                 | (dB) | (dB)  | (dB) | (dBuV/m) |      | (dBuV/m) |      | (dB)                  |      |  |  |
|                                |        |        |        |        |      |                      |      |       |      |          |      |          |      |                       |      |  |  |
|                                |        |        |        |        |      |                      |      |       |      | PK       | AV   | PK       | AV   | PK                    | AV   |  |  |
| 1                              | 27     | 2388   | 54.6   | 46.7   | 29   | 3                    | 0    | -20.0 | -6   | 66.6     | 52.7 | 74.0     | 54.0 | -7.4                  | -1.3 |  |  |
| 2                              | 28     | 2388   | 57     | 46.2   | 29   | 3                    | 0    | -20.0 | -6   | 69.0     | 52.2 | 74.0     | 54.0 | -5.0                  | -1.8 |  |  |
| 3                              | 29     | 2390   | 56     | 44     | 29   | 3                    | 0    | -20.0 | -6   | 68.0     | 50.0 | 74.0     | 54.0 | -6.0                  | -4.0 |  |  |
| 11                             | 29     | 2485   | 57     | 47     | 29   | 3                    | 0    | -20.0 | -6   | 69.0     | 53.0 | 74.0     | 54.0 | -5.0                  | -1.0 |  |  |
| 12                             | 27     | 2483.5 | 52     | 43.8   | 29   | 3                    | 0    | -20.0 | -6   | 64.0     | 49.8 | 74.0     | 54.0 | -10.0                 | -4.2 |  |  |
| 13                             | 26     | 2483.5 | 51     | 44.4   | 29   | 3                    | 0    | -20.0 | -6   | 63.0     | 50.4 | 74.0     | 54.0 | -11.0                 | -3.6 |  |  |
| 14                             | 7      | 2483.5 | 53.4   | 46.6   | 29   | 3                    | 0    | -20.0 | -6   | 65.4     | 52.6 | 74.0     | 54.0 | -8.6                  | -1.4 |  |  |