REPORT No. : SZ14090006W01

FCC RF TEST REPORT

APPLICANT	:	SHENZHEN SHIXINZHONGXIN TECHNOLOGY.CO.,LTD
PRODUCT NAME	:	Bluetooth module
MODEL NAME	:	F-6188
TRADE NAME	:	XINZHONGXIN
BRAND NAME	:	XINZHONGXIN
FCC ID	:	KKI-F-6188
STANDARD(S)	:	47 CFR Part 15 Subpart C
ISSUE DATE	:	2014-10-20

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB GROUP FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China Tel: 86-755-36698555 Http://www.morlab.com Fax: 86-755-36698525 E-mail: service@morlab.cn

DIRECTORY

TEST REPORT DECLARATION 5

1. TECHNICAL INFORMATION 6

1.1. APPLICANT INFORMATION 6
1.2. EQUIPMENT UNDER TEST (EUT) DESCRIPTION 6
1.2.1. IDENTIFICATION OF ALL USED EUTS 6
1.3. TEST STANDARDS AND RESULTS 7
1.3.1. TEST ENVIRONMENT CONDITIONS 7

2. 47 CFR PART 15C REQUIREMENTS 8

2.1. ANTENNA REQUIREMENT 8
2.1.1. APPLICABLE STANDARD 8
2.1.2. RESULT: COMPLIANT 8
2.2. NUMBER OF HOPPING FREQUENCY 8
2.2.1. REQUIREMENT 8
2.2.2. TEST DESCRIPTION 8
2.2.3. TEST PROCEDURE 9
2.2.4. TEST RESULT 10
2.3. PEAK OUTPUT POWER 14
2.3.1. REQUIREMENT 14
2.3.2. TEST DESCRIPTION 14
2.3.3. TEST RESULT 14
2.3.3.1. GFSK MODE 15
2.3.3.2. Π/4-DQPSK MODE 15
2.3.3.3. 8-DPSK MODE 15
2.4. 20DB BANDWIDTH 16
2.4.1. DEFINITION 16
2.4.2. TEST DESCRIPTION 16
2.4.3. TEST PROCEDURE 16
2.4.4. TEST RESULT 17
2.4.4.1. GFSK MODE 17
2.4.4.2. Π/4-DQPSK MODE 19
2.4.4.3. 8-DPSK MODE 21

2.5. CARRIED FREQUENCY SEPARATION 23
2.5.1. DEFINITION 23
2.5.2. TEST DESCRIPTION 23
2.5.3. TEST PROCEDURE 24
2.5.4. TEST RESULT 24
2.6. TIME OF OCCUPANCY (DWELL TIME) 26
2.6.1. REQUIREMENT 26
2.6.2. TEST DESCRIPTION 26
2.6.3. TEST PROCEDURE 27
2.6.4. TEST RESULT 27
2.6.4.1. GFSK MODE 27
2.6.4.2. Π/4-DQPSK MODE 31
2.6.4.3. 8-DPSK MODE 35
2.7. CONDUCTED SPURIOUS EMISSIONS 39
2.7.1. REQUIREMENT 39
2.7.2. TEST DESCRIPTION 39
2.7.3. TEST PROCEDURE 39
2.7.4. TEST RESULT 40
2.7.4.1. GFSK MODE 40
2.7.4.2. Π/4-DQPSK MODE 44
2.7.4.3. 8-DPSK MODE 48
2.8. RESTRICTED FREQUENCY BANDS 53
2.8.1. REQUIREMENT 53
2.8.2. TEST DESCRIPTION 53
2.8.3. TEST PROCEDURE 54
2.8.4. TEST RESULT 54
2.8.4.1. GFSK MODE 55
2.8.4.2. Π/4-DQPSK MODE 57
2.8.4.3. 8-DPSK MODE 60
2.9. CONDUCTED EMISSION 63
2.9.1. REQUIREMENT 63
2.9.2. TEST DESCRIPTION 63
2.9.3. TEST RESULT 64
2.10. RADIATED EMISSION 65
2.10.1. REQUIREMENT 65
2.10.2. TEST DESCRIPTION 65
2.10.3. TEST PROCEDURE 68
2.10.4. TEST RESULT 68

2.10.4.1. GFSK MODE: 69
2.10.4.2. Π/4-DQPSK MODE: 73
2.10.4.3. 8-DPSK MODE: 76
2.11. RF EXPOSURE EVALUATION 80

ANNEX A GENERAL INFORMATION 81

1.1 IDENTIFICATION OF THE RESPONSIBLE TESTING LABORATORY 81
1.2 IDENTIFICATION OF THE RESPONSIBLE TESTING LOCATION 81
1.3 FACILITIES AND ACCREDITATIONS 81
1.4 TEST EQUIPMENTS UTILIZED 82
1.4.1 CONDUCTED TEST EQUIPMENTS 82
1.4.2 CONDUCTED EMISSION TEST EQUIPMENTS 82
1.4.3 RADIATED TEST EQUIPMENTS 82
1.4.4 CLIMATE CHAMBER 83
1.4.5 VIBRATION TABLE 83
1.4.6 ANECHOIC CHAMBER 83

Change History		
Issue	Date	Reason for change
1.0	2014-10-20	First edition

Test Report Declaration

Applicant	SHENZHEN SHIXINZHONGXIN TECHNOLOGY.CO.,LTD
Applicant Address	Shenzhen City manhole town Nanpu road and East Ring Road Interchange Dong Industrial Zone
Manufacturer	SHENZHEN SHIXINZHONGXIN TECHNOLOGY.CO.,LTD
Manufacturer Address	Shenzhen City manhole town Nanpu road and East Ring Road Interchange Dong Industrial Zone A3
Product Name	Bluetooth module
Model Name	6188
Brand Name	XINZHONGXIN
HW Version	v1.0
SW Version	v1.0
Test Standards	47 CFR Part 15 Subpart C
Test Date	2014-09-1 to 2014-10-16
Test Result	PASS

Tested by : Nie Quan

Nie Quan

Reviewed by : Qiu Xiaojun

Qiu Xiaojun

Approved by : Zeng Dexin

Zeng Dexin

1. Technical Information

Note： Provide by applicant.

1.1. Applicant Information

Company：	SHENZHEN SHIXINZHONGXIN TECHNOLOGY.CO.,LTD
Address：	Shenzhen City manhole town Nanpu road and East Ring Road Interchange Dong Industrial Zone A3

1.2. Equipment under Test (EUT) Description

Brand Name:	XINZHONGXIN
Trade Name:	XINZHONGXIN
Model Name:	F-6188
Frequency Range:	The frequency range used is 2402MHz – 2480MHz (79 channels, at intervals of 1MHz); The frequency block is 2400MHz to 2483.5MHz.
Modulation Type:	Bluetooth: FHSS (GFSK(1Mbps), ∏/4-DQPSK(EDR 2Mbps), 8-DPSK(EDR 3Mbps))
Bluetooth Version:	2.1+EDR
Antenna Type:	PCB Antenna
Antenna Gain:	0dBi

NOTE:

The EUT is Bluetooth module, it contains Bluetooth Module operating at 2.4GHz ISM band; the frequencies allocated for the Bluetooth Module is F(MHz)=2402+1*n (0<=n<=78). The lowest, middle, highest channel numbers of the Bluetooth Module used and tested in this report are separately 0 (2402MHz), 38 (2440MHz) and 78 (2480MHz).

For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.2.1. Identification of all used EUTs

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
A01	V1.0	V1.0

1.3. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Bluetooth, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-13 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section in CFR 47	Description	Result
1	15.203	Antenna Requirement	**PASS**
2	15.247(a)	Number of Hopping Frequency	**PASS**
3	15.247(b)	Peak Output Power	**PASS**
4	15.247(a)	20dB Bandwidth	**PASS**
5	15.247(a)	Carrier Frequency Separation	**PASS**
6	15.247(a)	Time of Occupancy (Dwell time)	**PASS**
7	15.247(d)	Conducted Spurious Emission	**PASS**
8	15.247(d)	Restricted Frequency Bands	**PASS**
9	15.207	Conducted Emission	**N/A**
10	15.209 15.247(d)	Radiated Emission	**PASS**
11	15.247(i),1.1307& 2.1093	RF exposure evaluation	**PASS**

NOTE:

The tests were performed according to the method of measurements prescribed in DA-00-705.

1.3.1. Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106

2. 47 CFR PART 15C REQUIREMENTS

2.1. Antenna requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Number of Hopping Frequency

2.2.1. Requirement

According to FCC §15.247(a)(1)(iii), frequency hopping systems operating in the 2400MHz to 2483.5MHz bands shall use at least 15 hopping frequencies.

2.2.2. Test Description

A. Test Setup:



The Bluetooth Module of the EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Please reference ANNEX A(1.4).

2.2.3. Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = the frequency band of operation
RBW ≥ 1% of the span
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold
Allow the trace to stabilize

2.2.4. Test Result

The Bluetooth Module operates at hopping-on test mode; the frequencies number employed is counted to verify the Module's using the number of hopping frequency.

Test Verdict:

Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Refer to Plot	Verdict
GFSK	2400 - 2483.5	79	15	Plot A	PASS
∏/4-DQPSK	2400 - 2483.5	79	15	Plot B	PASS
8-DPSK	2400 - 2483.5	79	15	Plot C	PASS

A. Test Plots:




Agilent 17:24:52 16 Oct 2014
R T
Mkr1 Δ 39.24 MHz
-0.697 dB
Ref 0 dBm
Atten 5 dB
Peak
Log
10
dB/
Offst
11
dB
M1 S2
S3 FC
AA
Start 2.441 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 2.483 GHz
Sweep 6 ms (601 pts)

(Plot A: GFSK)


Agilent 17:22:59 16 Oct 2014
R T
Mkr1 Δ 39.36 MHz
0.222 dB
Ref 0 dBm
Atten 5 dB
Peak
Log
10
dB/
Offst
11
dB
M1 S2
S3 FC
AA
Start 2.4 GHz
#Res BW 1 MHz
#VBW 3 MHz
Stop 2.441 GHz
Sweep 6 ms (601 pts)



(Plot B: ∏/4-DQPSK)


Agilent 17:20:09 16 Oct 2014
R T
Mkr1 Δ 39.16 MHz
Ref 0 dBm
Atten 5 dB
-0.024 dB
Peak
Log
10
dB/
Offst
11
dB
M1 S2
S3 FC
AA
Start 2.4 GHz
Stop 2.441 GHz
#Res BW 1 MHz
#VBW 3 MHz
Sweep 6 ms (601 pts)
Agilent 17:21:11 16 Oct 2014
R T
Mkr1 Δ 39.24 MHz
Ref 0 dBm
Atten 5 dB
-0.535 dB
Peak
Log
10
dB/
Offst
11
dB
M1 S2
S3 FC
AA
Start 2.441 GHz
Stop 2.483 GHz
#Res BW 1 MHz
#VBW 3 MHz
Sweep 6 ms (601 pts)

(Plot C: 8- DPSK)

2.3. Peak Output Power

2.3.1. Requirement

According to FCC §15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

2.3.2. Test Description

A. Test Setup:



The Bluetooth Module of the EUT, which is powered by the Battery, is coupled to the Power meter and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm;the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Please reference ANNEX A(1.4).

2.3.3. Test Result

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.The

lowest, middle and highest channel were tested by Power meter.

2.3.3.1. GFSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	-6.193	0.00024	20.97	0.125	PASS
38	2440	-6.193	0.00024			PASS
78	2480	-6.652	0.00022			PASS

2.3.3.2. ∏/4-DQPSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	-6.159	0.000242	20.97	0.125	PASS
38	2440	-6.146	0.000243			PASS
78	2480	-6.603	0.000220			PASS

2.3.3.3. 8-DPSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	-6.211	0.000239	20.97	0.125	PASS
38	2440	-6.239	0.000238			PASS
78	2480	-6.690	0.000214			PASS

2.4. 20dB Bandwidth

2.4.1. Definition

According to FCC §15.247(a)(1), the 20dB bandwidth is known as the 99% emission bandwidth, or 20dB bandwidth (10*log1% = 20dB) taking the total RF output power.

2.4.2. Test Description

A. Test Setup:



The Bluetooth Module of the EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm;the path loss as the factor is calibrated to correct the reading.During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Please reference ANNEX A(1.4).

2.4.3. Test Procedure

Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW ≥ 1% of the 20 dB bandwidth

VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

2.4.4. Test Result

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to record the 20dB bandwidth of the Module.

2.4.4.1. GFSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Refer to Plot
0	2402	1.054	Plot A
38	2440	1.045	Plot B
78	2480	1.036	Plot C

B. Test Plots:



(Plot A: Channel = 2402 @ GFSK)



(Plot B: Channel = 2440 @ GFSK)



(Plot C: Channel = 2480 @ GFSK)

2.4.4.2. ∏/4-DQPSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Refer to Plot
0	2402	1.356	Plot D
38	2440	1.371	Plot E
78	2480	1.366	Plot F

B. Test Plots:



(Plot D: Channel = 2402 @ ∏/4-DQPSK)



(Plot E: Channel = 2440 @ ∏/4-DQPSK)



(Plot F: Channel = 2480 @ ∏/4-DQPSK)

2.4.4.3. 8-DPSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Refer to Plot
0	2402	1.337	Plot G
38	2440	1.336	Plot H
78	2480	1.355	Plot I

B. Test Plots:



(Plot G: Channel = 2402 @ 8-DPSK)



(Plot H: Channel = 2440 @ 8-DPSK)



(Plot I: Channel = 2480 @ 8-DPSK)

2.5. Carried Frequency Separation

2.5.1. Definition

According to FCC §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

2.5.2. Test Description

A. Test Setup:



The Bluetooth Module of the EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm;the path loss as the factor is

calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Please reference ANNEX A(1.4).

2.5.3. Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels
Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span
Video (or Average) Bandwidth (VBW) ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold
Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

2.5.4. Test Result

The Bluetooth Module operates at hopping-on test mode.
For any adjacent channels (e.g. the channel 38 and 40 as showed in the Plot A), the Module does have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel (refer to section 2.4.3), whichever is greater. So, the verdict is PASSING



(Plot A: GFSK)



(Plot B: ∏/4-DQPSK)



(Plot C: 8-DPSK)

2.6. Time of Occupancy (Dwell time)

2.6.1. Requirement

According to FCC §15.247(a) (1) (iii), frequency hopping systems in the 2400 - 2483.5MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

2.6.2. Test Description

A. Test Setup:



The Bluetooth Module of the EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm;the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Please reference ANNEX A(1.4).

2.6.3. Test Procedure

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.

The average time of occupancy in the specified 31.6 second period (79 channel * 0.4 s) is equal to 10 * (# of pulses in 3.16 s) * pulse width.

2.6.4. Test Result

2.6.4.1. GFSK Mode

A. Test Verdict:

DH Packet	Pulse Width (msec)	Number of pulse in 3.16 seconds	Refer to Plot	Average Time of Occupancy (sec)	Limit (sec)	Verdict

DH Packet	Pulse Width (msec)	Number of pulse in 3.16 seconds	Refer to Plot	Average Time of Occupancy (sec)	Limit (sec)	Verdict
DH1	0.466	27	Plot A	0.125	0.4	PASS
DH3	1.667	15	Plot B	0.250		PASS
DH5	2.800	10	Plot C	0.280		PASS

B. Test Plots:





(Plot A: DH1 @ GFSK)





(Plot B: DH3 @ GFSK)





(Plot C: DH5 @ GFSK)

2.6.4.2. ∏/4-DQPSK Mode

A. Test Verdict:

DH Packet	Pulse Width (msec)	Number of pulse in 3.16 seconds	Refer to Plot	Average Time of Occupancy (sec)	Limit (sec)	Verdict
DH1	0.333	27	Plot A	0.090	0.4	PASS
DH3	1.600	14	Plot B	0.224		PASS
DH5	2.865	10	Plot C	0.287		PASS

B. Test Plots:



(Plot D: DH1 @ ∏/4-DQPSK)





(Plot E: DH3 @ ∏/4-DQPSK)



(Plot F: DH5 @ ∏/4-DQPSK)

2.6.4.3. 8-DPSK mode

A. Test Verdict:

DH Packet	Pulse Width (msec)	Number of pulse in 3.16 seconds	Refer to Plot	Average Time of Occupancy (sec)	Limit (sec)	Verdict
DH1	0.367	26	Plot A	0.095	0.4	PASS
DH3	1.667	14	Plot B	0.234		PASS
DH5	2.700	11	Plot C	0.297		PASS

B. Test Plots:





(Plot G: DH1 @ 8-DPSK)





(Plot H: DH3 @ 8-DPSK)





(Plot I: DH5 @ 8-DPSK)

2.7. Conducted Spurious Emissions

2.7.1. Requirement

According to FCC §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.7.2. Test Description

A. Test Setup:



The Bluetooth Module of the EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm;the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Please reference ANNEX A(1.4).

2.7.3. Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold
Allow the trace to stabilize.

2.7.4. Test Result

The Bluetooth Module operates at hopping-off test mode. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.

2.7.4.1. GFSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
0	2402	-41.740	Plot A.1	-7.123	-27.1	PASS
38	2440	-42.360	Plot B.1	-7.549	-27.5	PASS
78	2480	-44.280	Plot C.1	-6.921	-26.9	PASS

B. Test Plots:

Note: the power of the Module transmitting frequency should be ignored.



(Plot A.1: Channel = 0, 30MHz to 25GHz @ GFSK Mode)



(Channel = 0, Band edge @ GFSK Mode)



(Channel = 0, Band edge with hopping on @ GFSK Mode)



(Plot B.1: Channel = 38, 30MHz to 25GHz @ GFSK Mode)



(Plot C.1: Channel = 78, 30MHz to 25GHz @ GFSK Mode)



(Channel = 78, Band edge @ GFSK Mode)



(Channel = 78, Band edge with hopping on @ GFSK Mode)

2.7.4.2. ∏/4-DQPSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
0	2402	-43.780	Plot D.1	-12.000	-32.0	PASS
38	2440	-42.640	Plot E.1	-12.610	-32.6	PASS
78	2480	-41.160	Plot F.1	-12.840	-32.8	PASS

B. Test Plots:

Note: the power of the Module transmitting frequency should be ignored.



(Plot D.1: Channel = 0, 30MHz to 25GHz @ ∏/4-DQPSK)



(Channel = 0, Band edge @ ∏/4-DQPSK)



(Channel = 0, Band edge with hopping on @ ∏/4-DQPSK)



(Plot E.1: Channel = 38, 30MHz to 25GHz @ ∏/4-DQPSK)



(Plot F.1: Channel = 78, 30MHz to 25GHz @ ∏/4-DQPSK)



(Channel = 78, Band edge @ ∏/4-DQPSK)



(Channel = 78, Band edge with hopping on @ ∏/4-DQPSK)

2.7.4.3. 8-DPSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
0	2402	-41.960	Plot G.1	-11.860	-31.9	PASS
38	2440	-41.200	Plot H.1	-11.590	-31.6	PASS
78	2480	-38.840	Plot I.1	-8.493	-28.5	PASS

B. Test Plots:

Note: the power of the Module transmitting frequency should be ignored.



(Plot G.1: Channel = 0, 30MHz to 25GHz @ 8-DPSK)



(Channel = 0, Band edge @ 8-DPSK)



(Channel = 0, Band edge with hopping on @ 8-DPSK)



(Plot H.1: Channel = 38, 30MHz to 25GHz @ 8-DPSK)



(Plot I.1: Channel = 78, 30MHz to 25GHz @ 8-DPSK)



(Plot I.1: Channel = 78, Band edge @ 8-DPSK)



(Plot I.1: Channel = 78, Band edge with hopping on @ 8-DPSK)

2.8. Restricted Frequency Bands

2.8.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.8.2. Test Description

A. Test Setup:



The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

For the Test Antenna:

Horn Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

B. Equipments List:

Please reference ANNEX A(1.4).

2.8.3. Test Procedure

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1GHz, 100 KHz for f < 1GHz
VBW = 3 MHz for peak and 10Hz for average
Sweep = auto
Detector function = peak
Trace = max hold
Allow the trace to stabilize.

2.8.4. Test Result

The lowest and highest channels are tested to verify Restricted Frequency Bands.
The measurement results are obtained as below:
E [dBμV/m] =UR + AT + AFactor [dB]; AT =LCable loss [dB]-Gpreamp [dB]
AT: Total correction Factor except Antenna
UR: Receiver Reading
Gpreamp: Preamplifier Gain
AFactor: Antenna Factor at 3m
Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

2.8.4.1. GFSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Detector PK/ AV	Receiver Reading UR (dBuV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
0	2356.53	PK	51.13	-33.63	32.56	50.06	74	Pass
0	2351.48	AV	38.91	-33.63	32.56	37.84	54	Pass
78	2489.39	PK	59.73	-33.18	32.5	59.05	74	Pass
78	2483.50	AV	48.77	-33.18	32.5	48.09	54	Pass

B. Test Plots:



(Plot A1:Channel = 0 PEAK @ GFSK)



(Plot A2:Channel = 0 AVERAGE @ GFSK)



(Plot B1:Channel = 78 PEAK @ GFSK)



(Plot B2: Channel = 78 AVERAGE @ GFSK)

2.8.4.2. ∏/4-DQPSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Detector PK/ AV	Receiver Reading UR (dBuV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBµV/m)	Limit (dBµV/m)	Verdict
0	2356.42	PK	51.12	-33.63	32.56	50.05	74	Pass
0	2355.12	AV	38.69	-33.63	32.56	37.62	54	Pass
78	2494.28	PK	60.50	-33.18	32.5	59.82	74	Pass
78	2483.50	AV	49.62	-33.18	32.5	48.94	54	Pass

B. Test Plots:



(Plot C1: Channel = 0 PEAK @ ∏/4-DQPSK)



(Plot C2: Channel = 0 AVERAGE @ ∏/4-DQPSK)



(Plot D1: Channel = 78 PEAK @ ∏/4-DQPSK)



(Plot D2: Channel = 78 AVERAGE@ ∏/4-DQPSK)

2.8.4.3. 8-DPSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Detector PK/ AV	Receiver Reading UR (dBuV)	AT (dB)	AFactor (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
0	2324.18	PK	49.66	-33.63	32.56	48.59	74	Pass
0	2348.88	AV	39.22	-33.63	32.56	38.15	54	Pass
78	2490.05	PK	60.94	-33.18	32.5	60.26	74	Pass
78	2483.50	AV	49.35	-33.18	32.5	48.67	54	Pass

B. Test Plots:



(Plot E1: Channel = 0 PEAK @ 8-DPSK Mode)



(Plot E2: Channel = 0 AVERAGE @ 8-DPSK Mode)



(Plot F1:Channel = 78 PEAK @ 8-DPSK Mode)



(Plot F2:Channel = 78 AVERAGE @ 8-DPSK Mode)

2.9. Conducted Emission

2.9.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5- 30	60	50

NOTE:

(a) The lower limit shall apply at the band edges.

(b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.9.2. Test Description

A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4:2009

The Bluetooth Module of the EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The factors of the site are calibrated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

B. Equipments List:

Please reference ANNEX A(1.4).

2.9.3. Test Result

This EUT designed can not to be connected to the public utility (AC) power line, so conducted emi ssion is unnecessary.

2.10. Radiated Emission

2.10.1. Requirement

According to FCC section 15.247(d) and RSS-A8.5, radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).
According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)

2.10.2. Test Description

A. Test Setup:

1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to1GHz



3) For radiated emissions above 1GHz



The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4 (2009). The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4.

The Bluetooth Module of the EUT is powered by the Battery. The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

For the Test Antenna:

(a) In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
(b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

B. Equipments List:

Please reference ANNEX A(1.4).

2.10.3. Test Procedure

Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

2.10.4. Test Result

According to ANSI C63.4 selection 4.2.2, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

E [dBμV/m] $= U_R + A_T + A_{Factor}$ [dB]; $A_T = L_{Cable\ loss}$ [dB]$-G_{preamp}$ [dB]

A_T: Total correction Factor except Antenna

U_R: Receiver Reading

G_{preamp}: Preamplifier Gain

A_{Factor}: Antenna Factor at 3m

During the test, the total correction Factor AT and A_{Factor} were built in test software.

Note: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

The low frequency, which started from 9KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

2.10.4.1. GFSK Mode:

A. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 0



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
334.788	39.06	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
477.506	39.55	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2402.000	40.02	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
3329.177	37.33	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
12546.135	39.70	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
14192.020	39.86	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ GFSK, channel 0)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
356.559	37.54	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
475.087	37.17	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2402.000	46.39	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
4810.474	37.41	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
7224.439	41.03	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
14192.020	40.04	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @ GFSK, channel 0)

Plot for Channel = 38



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
242.868	34.73	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
383.167	37.84	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
666.185	39.74	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2440.000	40.99	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
3329.177	37.05	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
14137.157	40.55	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ GFSK, channel 38)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
317.855	36.90	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
383.167	36.10	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2440.000	44.69	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
3329.177	39.90	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
7334.165	40.18	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
14246.883	40.22	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @ GFSK, channel 38)

Plot for Channel = 78



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
358.978	38.52	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
663.766	38.90	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2480.000	38.72	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
3329.177	36.56	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
14137.157	40.27	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
19129.676	39.62	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ GFSK, channel 78)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
334.788	34.23	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
554.913	34.78	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2480.000	42.60	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
3329.177	38.74	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
7443.890	39.27	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
19129.676	41.17	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @ GFSK, channel 78)

2.10.4.2. ∏/4-DQPSK Mode:

A. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 0



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
240.449	28.91	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
334.788	33.98	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
596.035	32.76	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2402.000	41.86	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
3329.177	37.21	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
14137.157	39.98	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ ∏/4-DQPSK, channel 0)



Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
192.070	33.89	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
383.167	37.87	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2402.000	46.69	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
3329.177	38.48	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
4810.474	37.40	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
7224.439	41.07	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Vertical @ ∏/4-DQPSK, channel 0)

Plot for Channel = 38



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
334.788	36.43	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
477.506	38.18	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
666.185	37.12	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2440.000	40.90	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
12546.135	39.62	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
14137.157	39.67	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ ∏/4-DQPSK, channel 38)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
317.855	37.60	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
383.167	36.67	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2440.000	45.01	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
3329.177	39.81	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
7334.165	40.06	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
14246.883	39.84	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @ ∏/4-DQPSK, channel 38)

Plot for Channel = 78



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
358.978	39.62	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
666.185	40.99	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2480.000	39.27	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
3329.177	36.54	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
14137.157	40.23	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
19184.539	39.74	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ ∏/4-DQPSK, channel 78)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
317.855	33.87	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
334.788	33.79	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2480.000	42.03	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
3329.177	39.23	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
14137.157	40.65	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
19074.813	39.15	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @ ∏/4-DQPSK, channel 78)

2.10.4.3. 8-DPSK Mode:

A. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 0



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
119.501	36.91	N.A	N.A	N.A	43.5	N.A	Horizontal	PASS
310.599	38.87	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
663.766	38.97	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2402.000	42.61	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
3329.177	35.48	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
14192.020	39.44	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @8-DPSK, channel 0)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
317.855	35.85	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
477.506	36.16	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2402.000	46.68	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
3329.177	38.78	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
4810.474	36.78	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
7224.439	40.38	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @8-DPSK, channel 0)

Plot for Channel = 38



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
383.167	38.69	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
397.681	39.47	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
477.506	37.64	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2440.000	41.30	N.A	N.A	N.A	N.A	N.A	Horizontal	N.A
3329.177	37.14	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
14137.157	39.71	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @8-DPSK, channel 38)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
192.070	32.56	N.A	N.A	N.A	43.5	N.A	Vertical	PASS
383.167	36.79	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2440.000	44.51	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
3329.177	39.11	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
7334.165	39.56	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
14137.157	39.60	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @8-DPSK, channel 38)

Plot for Channel = 78



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
383.167	38.39	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
477.506	40.01	N.A	N.A	N.A	46.0	N.A	Horizontal	PASS
2480.000	39.17	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
3329.177	36.70	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
14137.157	40.80	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
19129.676	40.17	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @8-DPSK, channel 78)



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
317.855	34.58	N.A	N.A	N.A	46.0	N.A	Vertical	PASS
2480.000	42.31	N.A	N.A	N.A	N.A	N.A	Vertical	N.A
3329.177	39.39	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
7443.890	37.55	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
14192.020	40.10	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
19074.813	40.09	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @8-DPSK, channel 78)

2.11. RF exposure evaluation

According to § 1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy lever in excess of Commission's guideline.

According to 447498 D01 General RF Exposure Guidance v05, exclusion threshold values at selected frequencies and distances table as following.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

MHz	30	35	40	45	50	mm
150	232	271	310	349	387	SAR Test Exclusion Threshold (mW)
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

Routine SAR evaluation refers to the specifically required by §2.1093, using measurements or computer simulation. When routine SAR evolution is not required, the portable transmitters with output power greater than the applicable low threshold SAR evolution to qualify for TCB approval.

Result:

This is portable device and the maximum output power is -6.046dBm (0.243mW). which is lower than the exclusion threshold 10mW, at frequency 2450MHz, and distance is 5mm.

The SAR measurement is not required.

Annex A General Information

1.1 Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

1.2 Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

1.3 Facilities and Accreditations

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at FL.1, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10 2009, ANSI C63.4 2009 and CISPR Publication 22; the FCC registration number is 695796.

The IC registration number is 7183A-2.

1.4 Test Equipments Utilized

1.4.1Conducted Test Equipments

Conducted Test Equipment						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
1	System Simulator	6K00006210	MT8852B	Anritsu	2014.02.26	2015.02.25
2	Spectrum Analyzer	US44210471	E7405A	Agilent	2014.02.26	2015.02.25
3	Power Splitter	NW521	1506A	Weinschel	2014.02.26	2015.02.25
4	Attenuator 1	(n.a.)	10dB	Resnet	2014.02.26	2015.02.25
5	Attenuator 2	(n.a.)	3dB	Resnet	2014.02.26	2015.02.25
6	EXA Signal Analzyer	MY51440152	N9010A	Agilent	2014.02.26	2015.02.25

1.4.2Conducted Emission Test Equipments

Conducted Emission Test Equipments						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
1	Receiver	US44210471	E7405A	Agilent	2014.02.26	2015.02.25
2	LISN	812744	NSLK 8127	Schwarzbeck	2014.02.26	2015.02.25
3	Service Supplier	100448	CMU200	R&S	2014.02.26	2015.02.25
4	Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2014.02.26	2015.02.25

1.4.3Radiated Test Equipments

Radiated Test Equipments						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal.Due Date
1	System Simulator	100448	CMU200	R&S	2014.02.26	2015.02.25
2	Receiver	US44210471	E7405A	Agilent	2014.02.26	2015.02.25
3	Test Antenna - Bi-Log	9163-274	9m*6m*6m	Albatross	2014.02.26	2015.02.25

4	Test Antenna - Horn	9120D-963	VULB 9163	Schwarzbeck	2014.02.26	2015.02.25
5	Test Antenna - Horn	71688	BBHA 9120D	Schwarzbeck	2014.02.26	2015.02.25
6	Test Antenna - Loop	1519-022	HL050S7	R&S	2014.02.26	2015.02.25

1.4.4Climate Chamber

Climate Chamber						
No.	**Equipment Name**	**Serial No.**	**Type**	**Manufacturer**	**Cal.Date**	**Cal.Due Date**
1	Climate Chamber	2004012	HL4003T	Yinhe	2014.02.26	2015.02.25

1.4.5Vibration Table

Vibration Table						
No.	**Equipment Name**	**Serial No.**	**Type**	**Manufacturer**	**Cal.Date**	**Cal.Due Date**
1	Vibration Table	N/A	ACT2000-S015L	CMI-COM	2014.02.26	2015.02.25

1.4.6Anechoic Chamber

Anechoic Chamber						
No.	**Equipment Name**	**Serial No.**	**Type**	**Manufacturer**	**Cal.Date**	**Cal.Due Date**
1	Anechoic Chamber	N/A	9m*6m*6m	Albatross	2014.02.26	2015.02.25

***** END OF REPORT *****