

## 6. Measurement Data (continued)

### 6.7. Public Exposure to Radio Frequency Energy Levels (1.1307 (b)(1))

#### 6.7.1. SAR Test Exclusion Calculation

Requirement: Portable devices as defined in § 2.1093 of this chapter operating under Part 15 are subject to radio frequency radiation exposure requirements as specified in §§ 1.1307(b) and 2.1093 of this chapter.

For a 1-g SAR, the test exclusion result must be  $\leq 3.0$ .

Test Notes: The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by the following formula:

$$\text{SAR Test Exclusion} = \frac{P_{\text{MAX}}}{d_{\text{MIN}}} \times \sqrt{f_{(\text{GHz})}} \quad (1)$$

$P_{\text{MAX}}$  mW Maximum power of channel, including tune-up tolerance

$d_{\text{MIN}}$  mm Minimum test separation distance, mm ( $\leq 50$  mm)

$f_{(\text{GHz})}$  GHz  $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz ( $>100$  MHz and  $<6$  GHz)

(1) FCC OET 447498 - Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

Result: The device under test meets the exclusion requirement detailed in FCC OET 447498.

| Channel 2        |                    |        |     |
|------------------|--------------------|--------|-----|
| Input:           | $P_{\text{MAX}}$   | 0.2730 | mW  |
|                  | $d_{\text{MIN}}$   | 5.00   | mm  |
|                  | $f_{(\text{GHz})}$ | 3.997  | GHz |
| Test Exclusion:  |                    | 0.109  |     |
| Limit Exemption: |                    | 3.000  |     |

<sup>1</sup> Taken from the peak data in Section 6.5 of this test report (converted to mW).

The device does not exceed the test limit exemption and therefore a routine SAR Evaluation is not required