



EMC Test Data

Client:	FreeWave Technologies, Inc.	PR Number:	PR167383
Model:	LRS455C	T-Log Number:	TL167383-RANA
Contact:	Ofer Fisher	Project Manager:	Deepa Shetty
Standard:	FCC Parts 15 & 90, RSS-119; EN55032	Project Engineer:	David Bare
		Class:	N/A

Maximum Permissible Exposure / SAR Exclusion

Specific Details

Objective: Evaluate the RF Exposure requirements per FCC 1.1310, 2.1091 and RSS-102.

Date of Test: 12/22/2022

Test Engineer: David Bare

General Test Configuration

Calculation uses the free space transmission formula:

$$S = (PG)/(4 \pi d^2)$$

Where: S is power density (W/m^2), P is output power (W), G is antenna gain relative to isotropic, d is separation distance from the transmitting antenna (m).

Summary of Results

Device complies with Power Density requirements at 20cm separation:	No	
If not, required separation distance (in cm):	72	US
If not, required separation distance (in cm):	95	Canada

Deviations From The Standard

No deviations were made from the requirements of the standard.



EMC Test Data

Client:	FreeWave Technologies, Inc.	PR Number:	PR167383
Model:	LRS455C	T-Log Number:	TL167383-RANA
Contact:	Ofer Fisher	Project Manager:	Deepa Shetty
Standard:	FCC Parts 15 & 90, RSS-119; EN55032	Project Engineer:	David Bare
		Class:	N/A

FCC MPE Calculation

Use: General

Antenna: Maximum 9.25 dBi

Freq. MHz	EUT Power (in. Tolerance)		Cable Loss Loss dB	Ant Gain dBi	Power at Ant dBm	EIRP mW	Power Density (S) at 72 cm mW/cm ²	MPE Limit at 72 cm mW/cm ²
	dBm	mW*						
435	33.5	2238.7	0	9.25	33.5	18836.49	0.289	0.290
450	33.5	2238.7	0	9.25	33.5	18836.49	0.289	0.300
470	33.5	2238.7	0	9.25	33.5	18836.49	0.289	0.313

For the cases where S > the MPE Limit

Freq. MHz	Power Density (S) at 95 cm mW/cm ²	MPE Limit at 95 cm mW/cm ²	Distance where S <= MPE Limit cm
435	0.289	0.290	71.9
450	0.289	0.300	70.7
470	0.289	0.313	69.2

Industry Canada MPE Calculation

Use: General

Antenna: Maximum 9.25 dBi

Freq. MHz	EUT Power (in. Tolerance)		Cable Loss Loss dB	Ant Gain dBi	Power at Ant dBm	EIRP mW	Power Density (S) at 95 cm W/cm ²	MPE Limit at 95 cm W/cm ²
	dBm	mW*						
450	33.5	2238.7	0	9.25	33.5	18836.49	1.661	1.703
460	33.5	2238.7	0	9.25	33.5	18836.49	1.661	1.729
470	33.5	2238.7	0	9.25	33.5	18836.49	1.661	1.755

For the cases where S > the MPE Limit

Freq. MHz	Power Density (S) at 95 cm mW/cm ²	MPE Limit at 95 cm mW/cm ²	Distance where S <= MPE Limit cm
450	1.661	1.703	93.8
460	1.661	1.729	93.1
470	1.661	1.755	92.4