

TABLE OF CONTENTS LIST

APPLICANT: DSI (HK) LTD.

FCC ID: KNZ48440

TEST REPORT CONTAINING:

PAGE 1.....TEST PROCEDURE
PAGE 2.....TEST PROCEDURE CONTD. & CIRCUIT DESCRIPTION
PAGE 3.....RADIATION INTERFERENCE TEST DATA
PAGE 5.....OCCUPIED BANDWIDTH TEST DATA
PAGE 6.....POWERLINE CONDUCTED TEST DATA

EXHIBITS CONTAINING:

EXHIBIT 1.....POWER OF ATTORNEY LETTER
EXHIBIT 2.....BLOCK DIAGRAM
EXHIBIT 3.....SCHEMATIC
EXHIBIT 4A-4C.....PARTS LIST
EXHIBIT 5A-5B.....INSTRUCTION MANUAL
EXHIBIT 6.....SAMPLE OF FCC ID LABEL
EXHIBIT 7.....LOCATION OF FCC ID LABEL
EXHIBIT 8.....EXTERNAL PHOTO - FRONT SIDE
EXHIBIT 9.....EXTERNAL PHOTO - BACK SIDE
EXHIBIT 10.....INTERNAL PHOTO - COMPONENT SIDE
EXHIBIT 11.....INTERNAL PHOTO - COPPER SIDE
EXHIBIT 12.....RADIATED TEST SET UP PHOTO
EXHIBIT 13.....POWERLINE CONDUCTED TEST SET UP PHOTO
EXHIBIT 14.....OCCUPIED BANDWIDTH PLOT - LOUD VOICE
EXHIBIT 15.....OCCUPIED BANDWIDTH PLOT - NO AUDIO INPUT
EXHIBIT 16.....POWERLINE CONDUCTED PLOT - LINE 1
EXHIBIT 17.....POWERLINE CONDUCTED PLOT - LINE 2

APPLICANT: DSI (HK) LTD.

FCC ID: KNZ48440

REPORT #: F:\CUS\D\DSI\DSI40A9.RPT

PAGE: TABLE OF CONTENTS LIST

APPLICANT: DSI (HK) LTD.
FCC ID: KNZ48440

TEST EQUIPMENT LIST

1. Spectrum Analyzer: Hewlett Packard 8566B - Opt 462, w/ preselector 85685A, & Quasi-Peak Adapter HP 85650A, & HP 8449B - OPT H02 Cal. 6/26/98
2. Signal Generator, Hewlett Packard 8640B, cal. 10/1/98
3. Eaton Biconnical Antenna Model 94455-1
20-200 MHz Serial No. 0997 Cal. 5/15/98
4. Electro-Metric Dipole Kit, 20-1000 MHz, Model TDA-30 10/15/98
5. Electro-Metric Horn 1-18 GHz, Model RGA-180, Cal. 8/15/98
6. Electro-Metric Antennas Model TDA-30/1-4, Cal. 10/15/98
7. Electro-Metric Line Impedance Stabilization Network Model No. EM-7821, Serial No. 101; 100KHz-30MHz 50uH. Cal. 11/19/98
8. Electro-Metric Line Impedance Stabilization Network Model No. EM-7820, Serial No. 2682; 10KHz-30MHz 50uH. Cal. 11/19/98
9. Special low loss cable was used above 1 GHz
10. Tenney Temperature Chamber

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz. The ambient temperature of the UUT was 80oC with a humidity of 76%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz)	METER READING + ACF = FS
33	20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-1992 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10kHz with an appropriate sweep speed. The ambient temperature of the UUT was 80oC with a humidity of 76%.

APPLICANT: DSI (HK) LTD.
FCC ID: KNZ48440
REPORT #: F:\CUS\D\DSI\DSI40A9.RPT
PAGE #: 1

TEST PROCEDURES CONTINUED

APPLICANT: DSI (HK) LTD.
FCC ID: KNZ48440

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSIC63.4-1992 with the EUT 40 cm from the vertical ground wall.

CIRCUIT_DESCRIPTION:

In the transmit mode the speaker is switched out of the circuit and the microphone is connected to the input of Q13 and Q15 and Q16 and the output of Q16 drives the transformer T2, which modulates the voltage of the crystal controlled oscillator, Q9. Q9 is connected to the output stage Q8 through T6. From Q6 the signal goes to T7 and then to the antenna. In the receive mode the signal comes in on the antenna to T7 and then to the superregenerative detector Q10. From Q10 the detected signal is amplified in Q11 & Q12 and then goes to the audio amplifiers Q13, Q15, Q16. Q16 drives the output transformer T2 which is connected to the speaker.

ANTENNA_AND_GROUND_CIRCUITRY

This unit makes use of a external 5" antenna. The antenna is inductively coupled. This unit is powered from a 9.0V battery.

No ground connection is provided. The unit relies on the ground tract of the printed circuit board.

APPLICANT: DSI (HK) LTD.
FCC ID: KNZ48440
REPORT #: F:\CUS\D\DSI\DSI40A9.RPT
PAGE #: 2

APPLICANT: DSI (HK) LTD.

FCC ID: KNZ48440

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.235

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEED 80 dBuV/m AT 3M.
OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

30 - 88 MHz	40.0 dBuV/M MEASURED AT 3 METERS
88 - 216 MHz	43.5 dBuV/M
216 - 960 MHz	46.0 dBuV/M
ABOVE 960 MHz	54.0 dBuV/M

TEST DATA:

EMISSION FREQUENCY MHz	METER READING AT 3 METERS dBuV	COAX LOSS dB	ANTENNA CORRECTION FACTOR dB	FIELD STRENGTH dBuV/m@3m	MARGIN dB	ANT. POL.
49.83	37.00	0.25	10.99	48.24	31.76	V
99.70	33.00	0.80	8.39	42.19	1.31	H
149.60	25.40	0.80	16.90	43.10	0.40	H
199.40	19.20	0.90	12.66	32.76	10.74	H
249.30	19.80	1.20	13.35	34.35	11.65	V

SAMPLE CALCULATION:

$FSdBuV/m = MR(dBuV) + ACFdB.$

TEST PROCEDURE: The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The UUT was tested in 3 orthogonal planes.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: S. S. SANDERS

DATE: FEBRUARY 12, 1999

APPLICANT: DSI (HK) LTD.

FCC ID: KNZ48440

REPORT #: F:\CUS\D\DSI\DSI40A9.RPT

PAGE #: 3

APPLICANT: DSI (HK) LTD.
FCC ID: KNZ48440
NAME OF TEST: Occupied Bandwidth
RULES PART NO.: 15.235
REQUIREMENTS: The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

THE GRAPHS IN EXHIBITS 14-15 REPRESENT THE EMISSIONS TAKEN FOR THE DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was taken. The vertical scale is set to -10 dBm per division. The horizontal scale is set to 5 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: S. S. SANDERS

DATE: FEBRUARY 12, 1999

APPLICANT: DSI (HK) LTD.
FCC ID: KNZ48440
REPORT #: F:\CUS\D\DSI\DSI40A9.RPT
PAGE #: 4

APPLICANT: DSI (HK) LTD.

FCC ID: KNZ48440

NAME OF TEST: POWER LINE CONDUCTED INTERFERENCE

RULES PART NUMBER: 15.107

MINIMUM REQUIREMENTS:	FREQUENCY	LEVEL
	___MHz___	__uV__
	0.450-30	250

TEST PROCEDURE: ANSI STANDARD C63.4-1992

THE HIGHEST EMISSION READ FOR LINE 1 WAS 7.490 uV @ 1.22 MHz.

THE HIGHEST EMISSION READ FOR LINE 2 WAS 16.768 uV @ 1.16 MHz.

THE GRAPHS IN EXHIBITS 16-17 REPRESENT THE EMISSIONS READ FOR POWERLINE CONDUCTED FOR THIS DEVICE.

TEST RESULTS: Both lines were observed. The measurements indicate that the unit DOES appear to meet the FCC requirements for this class of equipment.

PERFORMED BY: _____S.S. SANDERS_____DATE: FEBRUARY 12, 1999

APPLICANT: DSI (HK) LTD.
FCC ID: KNZ48440
REPORT #: F:\CUS\D\DSI\DSI40A9.RPT
PAGE #: 5