

RE051-20-104230-1-A Ed. 0

MPE test report

According to the standard:

CFR 47 FCC PART 15

Equipment under test:

Wireless seismic acquisition unit
AFU

FCC ID: KQ9-0800A

Company:

SERCEL Inc

Distribution: Mr TIJOU

(Company: SERCEL NANTES)

Number of pages: 5

Ed.	Date	Modified Page(s)	Technical Verification and Quality Approval	
			Name and Function	Visa
0	18-Mar-22	Creation	M. DUMESNIL, Radio Laboratory Manager	

Duplication of this document is only permitted for an integral photographic facsimile. It includes the number of pages referenced here above.
This document is the result of testing a specimen or a sample of the product submitted. It does not imply an assessment of the conformity of the whole manufactured products of the tested sample.



Siège Social : Emitech - 3, rue des Coudriers - Z.A. de l'Observatoire - 78180 MONTIGNY LE BX - France
Siret : 344 545 645 00022 - Tél. : 33 (0)1 30 57 55 55 - Fax : 33 (0)1 30 43 74 48 - E-mail : contact@emitech.fr - URL : www.emitech.fr
S.A. au capital de 1 560 000 € - R.C.S. VERSAILLES 344 545 645 - APE 7112B

DESIGNATION OF PRODUCT: *Wireless seismic acquisition unit*

Serial number (S/N): Sample 1: 1562674

Reference / model (P/N): AFU

Firmware version: 0.9.11

MANUFACTURER: SERCEL Inc

COMPANY CERTIFYING THE PRODUCT:

Company: SERCEL Inc

Address: 17200 Park Row
TEXAS 77084
UNITED STATES

Responsible: Mr PARRISH

COMPANY SUBMITTING THE PRODUCT:

Company: SERCEL NANTES

Address: 16, RUE DU BEL AIR
BP 30439
44470 CARQUEFOU
FRANCE

Responsible: Mr TIJOU


Person(s) present during the tests: Mr ALLAIN (the first day)

DATES OF TEST: From 2-Nov-20 to 4-Nov-20

TESTING LOCATION: EMITECH ANGERS laboratory at JUIGNE SUR LOIRE (49) FRANCE
FCC Accredited under US-EU MRA Designation Number: FR0009
Test Firm Registration Number: 873677

TESTED BY: S. LOUIS

VISA:



WRITTEN BY: S. LOUIS

CONTENTS

	<i>TITLE</i>	<i>PAGE</i>
1.	<i>INTRODUCTION.....</i>	<i>4</i>
2.	<i>PRODUCT DESCRIPTION</i>	<i>4</i>
3.	<i>NORMATIVE REFERENCE.....</i>	<i>5</i>
4.	<i>RF EXPOSURE.....</i>	<i>5</i>

1. INTRODUCTION

This report presents the results of radio test carried out on the following radio equipment: **Wireless seismic acquisition unit, AFU**, in accordance with normative reference.

The equipment under test integrates:

- SRD Multifrequencies proprietary transceiver operational in the band (2400MHz – 2483.5MHz).
Two different modulations are used (GFSK and FHSS).
- GNSS module operational in the band 1559MHz – 1610MHz

This report refers only of proprietary transceiver radio part.

2. PRODUCT DESCRIPTION

Class:	A
Utilization:	Industrial
Antenna type and gain:	2 dBi / integral antenna
Operating frequency band:	From 2400 MHz to 2483.5 MHz
Operating frequency range:	From 2402.5 MHz to 2478.5 MHz
Center frequency:	2439.5MHz
Channel spacing:	1MHz
Modulation:	GFSK & LoRa
Power source:	3.6Vdc by internal Li-ion Batteries Pack
Power soft adjusted to	7dBm

Power level, frequency range and channels characteristics are not user adjustable.
The details pictures of the product and the circuit boards are joined with this file.

3. **NORMATIVE REFERENCE**

The standards and testing methods related throughout this report are those listed below.

They are applied on the whole test report even though the extensions (version, date and amendment) are not repeated.

CFR 47 (2020) Radio Frequency Devices

ANSI C63.10 2013
Procedures for Compliance Testing of Unlicensed Wireless Devices.

447498 D01 General RF Exposure Guidance v06 RF Exposure procedures and equipment authorization policies for mobile and portable equipment

4. **RF EXPOSURE**

GFSK Modulation :

Maximum measured power = 105.2 dB μ V/m = 0.00993 W at 2439.5 MHz

with $P = (E \times d)^2 / (30 \times G_p)$ with $d = 3 \text{ m}$ and $G_p = 1$

LoRa Modulation :

Maximum measured power = 106 dB μ V/m = 0.01194 W at 2439.5 MHz

with $P = (E \times d)^2 / (30 \times G_p)$ with $d = 3 \text{ m}$ and $G_p = 1$

In accordance with KDB 447498 D01 General RF Exposure Guidance v06:

$$PSD = EIRP / (4 \times \pi \times R^2)$$

$$\Rightarrow 11.94 / (4 \times \pi \times (20 \text{ cm})^2) = 0.2375 \times 10^{-2} \text{ mW/cm}^2 \text{ (limit = 1 mW/cm}^2\text{)}$$

The equipment fulfils the requirements on power density for general population/uncontrolled exposure and therefore fulfils the requirements of 47 CFR §1.1310.