

15, rue de la Claie
Z.I. Angers-Beaucouzé
49070 BEAUCOUZÉ
Tél. 02 41 73 26 27
Fax 02 41 73 26 40
e-mail : atlantique@emitech.fr
R.C.S. ANGERS 95 B 543
SIRET 344 545 645 00055

RA-02-33183/01/A/ST

**FCC CERTIFICATION
E.M.C. Measurement
Technical Report**

**standard to apply:
FCC Part 15.209**

**Equipment under test:
RMP3-224**

FCC ID : KQG RMP3-224

**Company:
RENISHAW METROLOGY LTD**

DISTRIBUTION: Mr WOOLLETT

Company: RENISHAW METROLOGY LTD

Number of pages: 10

Ed.	Date	Modified pages	Editing		Verification Approval	
			Name	Visa	Name	Visa
0	31-May-02	Creation	D. GRATON	DG	P. BONNEFANT	

Duplication of this document is only permitted for an integral photographic facsimile. It includes the number of pages referenced hereabove.

This document is the result of testing a specimen or a sample of the product submitted. It does not imply an assessment of the conformity of the whole production to the item tested.
SIEGE SOCIAL : EMITECH S.A.
3, rue des Coudriers - Z.A. de l'Observatoire - 78180 MONTIGNY-LE-BRETONNEUX - Tél. 01 30 57 55 55 - Fax 01 30 43 74 48
S.A. AU CAPITAL DE 480 000 € - R.C. VERSAILLES B 344 545 645 - SIRET 344 545 645 000 22 - CODE APE 742 C

EQUIPMENT UNDER TEST

type: RMP3-224
serial number: V40810

MANUFACTURER: RENISHAW METROLOGY LTD

COORDINATES OF THE COMPANY SUBMITTING THE EQUIPMENT:

Company: RENISHAW METROLOGY LTD

Address: New Mills, Wotton Under Edge
Gloucestershire GL 12 8JR
ENGLAND

Responsible: Mr WOOLLETT

DATE (S) OF THE TEST: 21 and 22 May 2002

LOCALITY OF THE TEST: EMITECH ATLANTIQUE open area test site in LA POUEZE
(49) FRANCE

TESTED BY: D. GRATON

CONTENTS

TITLE	PAGE
1. INTRODUCTION	4
2. PRODUCT DESCRIPTION.....	4
3. NORMATIVE REFERENCE	4
4. TEST METHODOLOGY.....	5
5. RELATED SUBMITTAL GRANT	5
6. TEST UNIT CONFIGURATION.....	5
7. TESTS AND CONCLUSIONS	6
8. RADIATED EMISSION LIMITS; GENERAL REQUIREMENTS	7
9. PHOTOGRAPHIES OF THE EQUIPMENT UNDER TEST.....	9

1. INTRODUCTION

This document presents the result of E.M.C. test carried out on the following equipment: RMP3-224 in accordance with normative reference.

2. PRODUCT DESCRIPTION

ITU Emission code: 7K00F7D

Classe: A (paragraph FCC part 15.3)

Utilization: probe for machine tools telemetry, transmitter

Antenna type: internal antenna

Operating frequency range: from 224.500 MHz to 225.475 MHz

No of channels: 40

Channel spacing: 25 kHz

Frequency generation: ☒ SAW Resonator ☐ Crystal ☒ Synthetiser

Modulation: ☒ Amplitude ☒ Digital ☒ Frequency ☐ Phase

Frequency deviation: ± 3.5 kHz

Power source: 9 Vdc (battery)

Power level, frequency range and channels characteristics are not user adjustable.

The details pictures of the product and the circuit boards are joined with this file.

3. NORMATIVE REFERENCE

FCC Part 15 (2000) Code of Federal Regulations
Title 47 - Telecommunication
Chapter 1 - Federal Communications Commission
Part 15 - Radio frequency devices
Subpart C - Intentional Radiators

4. TEST METHODOLOGY

Radio performance tests procedures given in part 15:

Paragraph 209: radiated emission limits; general requirements

Paragraph 33: frequency range of radiated measurements

Paragraph 35: measurement detector functions and bandwidths

5. RELATED SUBMITTAL GRANT

The telemetry sensor RMP3-224 is used with the receiver MI16-224 (FCC ID: KQG MI16-224).

6. TEST UNIT CONFIGURATION

JOINED DOCUMENTATIONS

<i>“Synoptic”</i>	<i>RMP3 224 SYNOPTIC.pdf</i>
<i>“Block diagram”</i>	<i>RMP3 224 BREAK DOWN.pdf</i>
<i>“External photos and Product labeling”</i>	<i>RMP3 224 EXTERNAL PHOTOS.pdf</i>
<i>“Assembly of components”</i>	<i>RMP3 224 CAB.pdf</i>
<i>“Internal photos”</i>	<i>RMP3 224 INTERNAL PHOTOS.pdf</i>
<i>“Layout pcb”</i>	<i>RMP3 224 LAYOUT.pdf</i>
<i>“Bil of materials”</i>	<i>RMP3 224 PART LIST.pdf</i>
<i>“Schematics”</i>	<i>RMP3 224 SCHEMA.pdf</i>
<i>“Product description”</i>	<i>RMP3 224 TECHNICAL SPEC.pdf</i>
<i>“User guide”</i>	<i>RMP3 224 USER GUIDE.pdf</i>

7. TESTS AND CONCLUSIONS

Test procedure	Description of test	Criteria respected ?				Comment
		Yes	No	NAp	NAs	
FCC Part 15.209	RADIATED EMISSION LIMITS; general requirements	X				

NAp: Not Applicable

NAs: Not Asked

Conclusion:

The sample of RMP3-224 submitted to the tests complies with the regulations of the standard FCC Part 15 in accordance with the limits or criteria defined in this report.

8. RADIATED EMISSION LIMITS; GENERAL REQUIREMENTS

Standard: FCC Part 15 (2000)

Test procedure: paragraph 209

Test equipment:

TYPE	BRAND	REFERENCE
Test receiver	Rohde & Schwarz ESVS 10	1/02/12/049
Biconical antenna	Hewlet Packard 11966 C	3/24/18/117
Log periodic antenna	Rohde & Schwarz HL 223	3/24/18/194
Double ridged guide antenna	Electrometrics EM 6961	3/24/18/201
Spectrum analyser	Rohde & Schwarz FSEM30	1/02/12/050
Open area test site	EMITECH	3/16/12/016
Preamplifier	DBS Microwave DB97-1852	3/01/12/076
High pass filter	Micro-tronics HPM11630	3/18/12/146

Test set up:

The system is tested in an open area test site (OATS).

The test unit is placed on a rotating table, 1.5 m from a ground plane. Zero degree azimuth corresponds to the front of the equipment under test.

Frequency range: from 9 kHz to harmonic 10 ($F_{\text{carrier}} \leq 1 \text{ GHz}$)

Detection mode: Quasi-peak ($F < 1 \text{ GHz}$)
Average ($F > 1 \text{ GHz}$)

Bandwidth: 120 kHz ($F < 1 \text{ GHz}$)
1 MHz ($F > 1 \text{ GHz}$)

Distance of antenna: 3 meters

Antenna height: 1 to 4 meters

Antenna polarization: vertical and horizontal

Equipment under test operating condition:

The equipment is in continuous transmission mode.

Results:

Ambient temperature (°C): 20 | 17
Relative humidity (%): 62 | 72

Power source: 9 V

The polarity column refers to the antenna polarity at which the maximum emissions level is measured.

Lowest Channel Emission

FREQUENCIES (MHz)	Position of the transmitter	Antenna height (cm)	Polarization H: Horizontal V: Vertical	Azimuth (degrees)	Field strength (dBμV/m)	Limits (dBμV/m)
224.5	Horizontal	158	V	90	44.68	46.02
449	Vertical	108	H	0	30.02	46.02
673.5	Horizontal	100	V	80	32.68	46.02
898	Horizontal	142	V	130	45.93	46.02
1122.52	Horizontal	125	V	0	38.44	53.98
1347	Vertical	104	V	40	45.74	53.98
1571.5	Horizontal	102	H	210	45.47	53.98
1796	Vertical	118	V	60	37.43	53.98

Highest Channel Emission

FREQUENCIES (MHz)	Position of the transmitter	Antenna height (cm)	Polarization H: Horizontal V: Vertical	Azimuth (degrees)	Field strength (dBμV/m)	Limits (dBμV/m)
225.475	Horizontal	158	V	90	45.18	46.02
450.95	Vertical	108	H	0	29.82	46.02
676.425	Horizontal	100	V	80	32.68	46.02
901.901	Horizontal	142	V	130	45.93	46.02
1127.37	Horizontal	125	V	0	34.73	53.98
1352.85	Vertical	104	V	40	45.98	53.98
1578.32	Horizontal	102	H	210	47.21	53.98
1803.87	Vertical	118	V	60	38.44	53.98

Vertical: upright

Horizontal: to put flat

9. PHOTOGRAPHIES OF THE EQUIPMENT UNDER TEST

General view



Photography open area test site: weather protection enclosure

