

Test Report No.: <i>Prüfbericht-Nr.:</i>	JP26FG0V 002	Order No.: <i>Auftrags-Nr.:</i>	150319785	Page 1 of 69 <i>Seite 1 von 69</i>
Client Reference No.: <i>Kunden-Referenz-Nr.:</i>	N/A	Order Date: <i>Auftragsdatum:</i>	2025-12-09	
Client: <i>Auftraggeber:</i>	A&D Co Ltd 1-243 Asahi, Kitamoto-city, Saitama, 364-8585, Japan			
Test Item: <i>Prüfgegenstand:</i>	Digital Blood Pressure Monitor			
Identification / Type No.: <i>Bezeichnung / Typ-Nr.:</i>	UA-8010BLEWM	Serial No.: <i>Serien-Nr.:</i>	See clause 4.3	
Order Content: <i>Auftrags-Inhalt:</i>	Wireless Testing			
Test Specification: <i>Prüfgrundlage:</i>	FCC 47 CFR Part 15, Subpart C, Section 15.247			
Date of Sample Receipt: <i>Wareneingangsdatum:</i>	2026-01-16	-/-		
Test Sample No.: <i>Prüfmuster-Nr.:</i>	A004188055-003, -004			
Testing Period: <i>Prüfzeitraum:</i>	2026-02-05 to 2026-02-13			
Place of Testing: <i>Ort der Prüfung:</i>	Yokohama EMC Laboratory			
Testing Laboratory: <i>Prüflaboratorium:</i>	TÜV Rheinland Japan Ltd.			
Test Result*: <i>Prüfergebnis*:</i>	Pass			
compiled by: <i>zusammengestellt von:</i>		authorized by: <i>genehmigt von:</i>		
Date: 2026-03-16 <i>Datum:</i>	Yoshifuru Fujiwara	Issue Date: 2026-03-16 <i>Ausstellungsdatum:</i>	Hidetoshi Sasaki	
Position / Stellung:	Project Engineer	Position / Stellung:	Authorizer	
Other / Sonstiges:				
Condition of the test item at delivery: <i>Zustand des Prüfgegenstandes bei Anlieferung:</i>		Test item complete and undamaged <i>Prüfmuster vollständig und unbeschädigt</i>		
* Legend: P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested * Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet				
This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark. <i>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</i>				

v05

Revisions

Report No.	Issue date	Changes / Remarks
JP26FG0V 001	2026-02-26	Original document
JP26FG0V 002	2026-03-16	Corrected Antenna gain in section 3.2 Added a comment in Figure 1 Corrected typo in section 4.5

Remarks

1	The equipment used during the specified testing period was calibrated according to the test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of the laboratory's management system.
2	Unless otherwise specified by the applied standard(s), the decision rule used in this test report for statements of conformity based on numerical measurement results is the "Zero Guard Band"/"Simple Acceptance" rule in accordance with ILAC G8:2019 and IEC Guide 115:2021. When the "Zero Guard Band" rule is applied, measurement uncertainty is not taken in account. For additional information on the risk resulting from the application of the "Zero Guard Band" decision rule, refer to ILAC G8:2019.

Test Report No.:
Prüfbericht-Nr.:**JP26FG0V 002**Page 3 of 69
Seite 3 von 69

Contents

1.	General Remarks	5
1.1	Test Specifications	5
1.2	Test Report Purpose	6
1.3	Complementary Materials	6
2.	Test Sites	7
2.1	Test Facilities	7
2.2	List of Test and Measurement Instruments	7
2.3	Measurement Uncertainty	9
3.	General Product Information	10
3.1	Product Function and Intended Use	10
3.2	Ratings and System Details	10
3.3	Noise Generating and Noise Suppressing Parts	11
3.4	Submitted Documents and Information	11
4.	Test Setup and Operation Modes	12
4.1	Principle of Test Configuration Selection	12
4.2	Operation Modes	12
4.3	Physical Configuration for Testing	13
4.4	Test Software	14
4.5	Special Accessories and Auxiliary Equipment	14
4.6	Countermeasures to achieve Compliance	15
5.	Test Results RADIO	16
5.1	Supply Voltage Requirements	16
5.2	Antenna Requirements	17
5.3	Restricted Bands of Operation	18
5.4	Maximum Peak Output Power	19
5.5	6dB Bandwidth	21
5.6	99% Bandwidth	26
5.7	Conducted Spurious Emissions	31
5.8	Peak Power Spectral Density	38
5.9	Radiated Spurious Emissions of Transmitter	43
5.10	AC Power Line Conducted Emission of Transmitter	59

6.	Photographs of the Test Setup.....	61
7.	List of Tables.....	67
8.	List of Figures	67
9.	List of Photographs	68

1. General Remarks

1.1 Test Specifications

Table 1: Test Summary

Test	Specifications	Result
Radio: FCC 47 CFR Part 15, Subpart C, Section 15.247 ANSI C63.10-2020 KDB Publication No. 558074 D01 (v05r02): Guidance for Compliance Measurement on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operation under Section 15.247 of the FCC Rules		
Supply Voltage Requirements FCC §15.31(e)	See the section 5.1.	Pass
Antenna Requirements FCC §15.203	See the section 5.2.	Pass
Restricted Bands of Operation FCC §15.205	See the section 5.3.	Pass
Maximum Peak Output Power FCC §15.247(b)(3)	1W (30dBm) (Peak Conducted)	Pass
6dB Bandwidth FCC §15.247(a)(2) and §15.215(c)	Minimum 500kHz 6dB bandwidth shall be contained within the designated frequency band.	Pass
99% Bandwidth	-/-	For. Ref.
Conducted Spurious Emissions FCC §15.247(d)	20dBc 30MHz - 25GHz (10 th Harmonics)	Pass
Peak Power Spectral Density FCC §15.247(e)	8dBm in any 3kHz band	Pass
Radiated Spurious Emissions of Transmitter FCC §15.209 and §15.247(d)	9kHz - 25GHz	Pass
Conducted Emission on AC Power Ports of Transmitter FCC §15.207(a)	150kHz - 30MHz	Pass

Test Report No.:
Prüfbericht-Nr.:**JP26FG0V 002**Page 6 of 69
Seite 6 von 69

1.2 Test Report Purpose

The purpose of this test report is to show compliance of the EUT (Equipment Under Test) with the requirements of the standards listed in section 1.1.

This report is a replacement for the original report JP26FG0V 001.

1.3 Complementary Materials

There is no attachment to this test report.

Test Report No.:
Prüfbericht-Nr.:**JP26FG0V 002****Page 7 of 69**
Seite 7 von 69

2. Test Sites

2.1 Test Facilities

TÜV Rheinland Japan Ltd. – Global Technology Assessment Center
4-25-2 Kita-Yamata, Tsuzuki-ku, Yokohama 224-0021, Japan

The test facility is accredited by VLAC (member of ILAC) under accreditation number VLAC-017-1 according to ISO/IEC 17025:2017.

The test facility is recognized by the Federal Communications Commission (FCC) as a Conformity Assessment Body under designation number JP0017 and test firm registration number 386498.

2.2 List of Test and Measurement Instruments

Table 2: List of Test and Measurement Equipment

Kind of Equipment	Manufacturer	Model Name	Serial Number	Equip. ID	Cal. Interval	Cal. Date	Next Cal.
For Antenna Port Conducted Emission							
EMI Receiver	Rohde & Schwarz	ESW 26	101316	RF-0812	1 year	2025-06-10	2026-06-10
EMI Receiver	Rohde & Schwarz	ESW 44	103396	RF-1250	1 year	2025-05-22	2026-05-22
RF Power Meter	Agilent	N1911A	MY451017 37	RF-0393	1 year	2026-01-09	2027-01-09
RF Peak Power Sensor	Agilent	N1921A	MY452422 28	RF-0394	1 year	2026-01-09	2027-01-09
For Power Port Conducted Emission (CE)							
Path Loss Correction Factors for CE	-	-	-	RF-0597	1 year	2026-01-29	2027-01-29
CE Measurement Software	Toyo Corporation	ES10/CE-AJ	0700-0183-35	RF-1262	N/A	N/A	N/A
EMI Receiver EPL1000	Rohde & Schwarz	EPL1000	100969	RF-1249	1 year	2025-05-23	2026-05-23
LISN	Rohde & Schwarz	ENV216	101958	RF-0708	1 year	2025-05-21	2026-05-21
For Radiated Emission (RE)							
Path Loss Correction Factors for RE below 1GHz	-	-	-	RF-0596	1 year	2026-01-29	2027-01-29

Test Report No.:
Prüfbericht-Nr.:**JP26FG0V 002**Page 8 of 69
Seite 8 von 69

Kind of Equipment	Manufacturer	Model Name	Serial Number	Equip. ID	Cal. Interval	Cal. Date	Next Cal.
Path Loss Correction Factors for RE above 1GHz	-	-	-	RF-0995	1 year	2025-11-06	2026-11-06
RE Meas. Software	Toyo Corporation	ES10/RE-AJ	0600-0179-80	RF-1263	N/A	N/A	N/A
EMI Receiver	Rohde & Schwarz	ESW 44	103396	RF-1250	1 year	2025-05-22	2026-05-22
RF Selector (10m Chamber)	Toyo Corporation	NS4900	0703-182	RF-0029	N/A	N/A	N/A
Loop Antenna with Amplifier, 9kHz-30MHz	Rohde & Schwarz	HFH2-Z2	100139	RF-0048	1 year	2025-07-18	2026-07-18
Trilog Antenna No. 2, 30-1000MHz	Schwarzbeck	VULB 9168	9168-475	RF-0462	1 year	2025-05-26	2026-05-26
5dB Attenuator	Pasternack	PE7047-5	-	RF-0731	1 year	2025-05-30	2026-05-30
Low Noise Preamplifier, 9kHz-1GHz	TSJ	MLA-10K01-B01-35	1370750	RF-0253	1 year	2025-12-25	2026-12-25
Band Pass Filter	Microwave Factory	MBP301	224969	RF-1015	1 year	2025-03-14	2026-03-14
Horn Antenna, 1-8GHz	Schwarzbeck	BBHA9120 D	9120D-2280	RF-0845	1 year	2025-03-07	2026-03-07
MMW PreAmp 0-50GHz	NEXTEM	RFA-1050000-40	RFA-1905-01	RF-1140	1 year	2025-11-06	2026-11-06
Horn Antenna, 1-18GHz	Schwarzbeck	BBHA9120 D	9120D-2280	RF-0845	1 year	2025-03-07	2026-03-07
Horn Antenna, 6-18GHz (RX)	Schwarzbeck Mess-Elektronik	BBHA9120 C	00775	RF-1315	2 years	2025-10-31	2027-10-31
Pre-amplifier for RF-1315 (6-18 GHz)	TOYO Corporation	HAP06-18W	B1510452 210-123	RF-1318	1 year	2025-11-05	2026-11-05
High Pass Filter, 8-18GHz	Micro-Tronics	HPM50107	G089	RF-1094	N/A	N/A	N/A
Horn Antenna, 18-26.5GHz (RX)	AMETEK	ANT-SGH-18-26.5	11568	RF-1316	1 year	2025-10-31	2026-10-31
Pre-amplifier for RF-1316 (18-26.5 GHz)	Toyo Corporation	HAP18-26W	B2010482 210-125	RF-1319	1 year	2025-11-05	2026-11-05
Horn Antenna, 26.5 -40GHz (RX)	AMETEK	ANT-SGH-26.5-40	11894	RF-1317	1 year	2025-02-21	2026-02-21
Pre-amplifier for RF-1317, 26.5-40GHz	TOYO Corporation	HAP26-40W	B3208602 210-126	RF-1320	1 year	2025-03-14	2026-03-14
Band Reject Filter, 2.4-2.5GHz	Micro-Tronics	BRM50702	G488	RF-0933	1 year	2025-09-19	2026-09-19
Constant Voltage Constant Frequency Stabilizers and Power Accessories							
CVCF (Shielded Room)	NF Corporation	ES2000S	9075612	RF-0210	1 year	2025-03-10	2026-03-10
CVCF Booster (Shielded Room)	NF Corporation	ES2000B	9074403	RF-0211	1 year	2025-03-10	2026-03-10
CVCF (10m Chamber)	NF Corporation	ES2000U	9067307	RF-0212	1 year	2025-03-10	2026-03-10

Kind of Equipment	Manufacturer	Model Name	Serial Number	Equip. ID	Cal. Interval	Cal. Date	Next Cal.
CVCF Booster (10m Chamber)	NF Corporation	ES2000B	9074408	RF-0213	1 year	2025-03-10	2026-03-10
CVCF (Pulse Test Lab)	NF Corporation	ES2000U	9067195	RF-0122	1 year	2025-05-19	2026-05-19
CVCF Booster (Pulse Test Lab)	NF Corporation	ES2000B	9072108	RF-0121	1 year	2025-05-19	2026-05-19
True RMS Multimeter (10m Chamber)	Fluke	87V	97680450	RF-0282	1 year	2025-04-08	2026-04-08
True RMS Multimeter (Pulse Test Lab)	Fluke	87V	16110176	RF-0414	1 year	2025-06-25	2026-06-25

Conformance of the used measurement and test equipment with the requirements of ISO/IEC 17025 has been confirmed before testing.

2.3 Measurement Uncertainty

Table 3: Measurement Uncertainty

Measurement Type	Frequency Range	Uncertainty (k=2)
Conducted Emission on RF Ports	30MHz - 40GHz	±2.58dB
Conducted Emission on Power Ports	150kHz - 30MHz	±3.31dB
Magnetic Field Strength	9kHz - 30MHz	±4.79dB
Radiated Emission up to 1GHz	30MHz - 1GHz (3m Distance)	±6.05dB (Vertical) ±4.95dB (Horizontal)
Radiated Emission above 1GHz	1 - 6GHz	±5.17dB
	6 - 18GHz	±4.96dB
	18 - 40GHz	±5.05dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT (Equipment Under Test) is a digital blood pressure monitor with BLE connectivity.

3.2 Ratings and System Details

1) EUT

System Input Voltage:	DC 6V (4 x 1.5V batteries or from AC adaptor)
Typical Nominal Voltage:	AC 120V for North America (AC adaptor)
Frequency:	60Hz (AC adaptor)
Protection Class:	III
Rated temperature:	+10 to +40°C
Dimensions:	W 110mm x H 73.1mm x D139.2mm
Weight:	300g (excluding batteries)
Test Voltage:	Refer to each test item.
Test Frequency:	Refer to each test item.

2) AC Adaptor for EUT

Manufacturer:	A & D Medical
Model:	TB-304
Typical Nominal Voltage:	AC120V
Frequency:	60Hz
Input Current:	0.15A
Protection Class:	II

3) BLE Connectivity

Radio standard:	Bluetooth 5.1
Frequency range:	2402 – 2480MHz
Specified output power	-0.65dBm (conducted peak power)
Antenna number:	1

Antenna gain:	+0.89dBi
Antenna type:	PCB pattern antenna
Antenna mounting type:	Internal
Modulation type:	GFSK
Data rate:	1Mbps, 2Mbps
Channel spacing:	2MHz
Power setting:	0dBm

3.3 Noise Generating and Noise Suppressing Parts

The highest frequency generated or used by the EUT is 2480MHz for radio portion and 64MHz for digital interface portion.

3.4 Submitted Documents and Information

Following information provided in this test report has been submitted by the client:

- client name and address;
- EUT identification, ratings, system details, and description of product function and intended use;
- information related to noise generating and noise suppressing parts (if any).

4. Test Setup and Operation Modes

4.1 Principle of Test Configuration Selection

Radio: The test methodology used is based on the requirements of 47 CFR Part 15, sections 15.31, 15.33, 15.35, 15.205, 15.207, 15.209 and 15.247. The test methods, which have been used, are based on ANSI C63.10 and KDB 558074 D01.

For details, see under each test item.

4.2 Operation Modes

The operation modes used for testing are:

- L. Transmitting at the lowest frequency Channel with 100% Duty Cycle.
- M. Transmitting at the middle frequency Channel with 100% Duty Cycle.
- H. Transmitting at the highest frequency Channel with 100% Duty Cycle.

Above modes are coupled with the following Configurations:

Table 4: Setting of Test Frequencies

Radio	Mode L	Mode M	Mode H	Remark
BLE	2402MHz	2442MHz	2480MHz	Power setting= 0dBm

And the following configurations:

1. 1Mbps
2. 2Mbps

Both AC adaptor operation and battery operation were evaluated to determine the worst case configuration for conductive and radiated test and conducted test.


4.3 Physical Configuration for Testing

The test system was configured in a typical fashion (as a customer would normally use it).


The justification and manipulation of cables and equipment in order to simulate a worst-case behavior of the test setup has been carried out as prescribed in ANSI C63.10.

Figure 1: Block Diagram

1) Conducted Radio Testing



2) Radiated Radio Testing and Conducted Emission on AC Power Ports Testing



(*): No.2 cable was disconnected from EUT during the test.

(**): 80cm extension AC power cable (RF-0608) was used to connect measuring equipment in Conducted Emission test on AC Power Port.

Table 5: Interfaces present on the EUT

No.	Interface	Cable Length for Testing, Shielding	Interface Classification
1.	DC Cable	1.6m, un-shielded	DC input power port
2.	Control Cable	0.3m, un-shielded	Signal port

For more details, refer to section 6 “Photographs of the Test Setup”.

Table 6: EUT Serial Numbers

Test Items	Serial Number
Conducted Radio Testing	(21)7251200021
Radiated Spurious Emissions of Transmitter	(21)7251200020
AC Power Line Conducted Emission of Transmitter	(21)7251200020

4.4 Test Software

The EUT was provided by the manufacturer with suitable internal software to allow operation in all the required modes.

Software used for testing:

Tera Term version 4.106 by Tera Term Project.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed in section 4.2 as appropriate.


4.5 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

1. Product: Laptop PC
- Manufacturer: HP
- Model: HSN-I14C-5
- Rated Voltage: DC19.5V
- Input Current: 2.31A
- Protection Class: III
- Serial Number: JPH9029GYQ

Test Report No.:
Prüfbericht-Nr.:**JP26FG0V 002**Page 15 of 69
Seite 15 von 69

2. Product: AC Adapter
Manufacturer: HP
Model: HSTNN-CA41
Rated Voltage: AC100–240V
Input Current: 1.4A
Frequency: 50–60Hz
Protection Class: II
3. Product: USB Jig
Manufacturer: DESHIDE TECH CO. , LTD
Model: SH-U09C2



4.6 Countermeasures to achieve Compliance

No additional measures were employed to achieve compliance.

5. Test Results RADIO

5.1 Supply Voltage Requirements

RESULT:**Pass**

Requirements:

FCC §15.31(e)

For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

Verdict:

The EUT has an internal voltage regulator to supply the RF circuit. Hence it complies with the supply voltage requirements.

5.2 Antenna Requirements

RESULT:**Pass**

Requirements:

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

All antennas for use with the EUT must be listed in the application, including a test report.

Verdict:

As per the guidance by KDB Publication No. 353028 D01, three ways can be used for a Part 15 Intentional radiator. a) Antenna permanently addached is applicable to the EUT.

The EUT has an antenna permanently attached on the printed circuit board. Hence it complies with the antenna requirements.

5.3 Restricted Bands of Operation

RESULT:**Pass**

Requirements:

FCC §15.205

Only spurious emissions are permitted in any of the restricted frequency bands, unless otherwise specified.

Verdict:

The Operation frequency range of the EUT is 2400 – 2483.5MHz as Bluetooth Low Energy, only spurious emissions may be found in the restricted bands below 25GHz. Hence the EUT complies with the restricted frequency band requirement.

5.4 Maximum Peak Output Power

RESULT:**Pass**

Date of testing: 2026-02-13

Ambient temperature: 25°C

Relative humidity: 26%

Atmospheric pressure: 1011hPa

Requirements:

FCC §15.247(b)(3)

For systems using digital modulation in the 2400-2483.5MHz band, the maximum peak output power is 1W (30dBm).

If transmitting antennas of directional gain greater than 6dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Test procedure:

ANSI C63.10-2020 §11.9, KDB 558074 D01.

The maximum peak output power was measured at the antenna port with a broadband peak power meter.

The readings of the measurements take into account the loss generated by all the involved cables.

Both AC adapter operation and battery operation were evaluated to determine the worst-case configuration. Final measurements were performed under AC adapter operation in all operating modes (L, M, and H).

Table 7: Maximum Peak Output Power, BLE, 1Mbps

Freq. [MHz]	Peak Output Power [dBm]	Peak Output Power Limit [dBm]	Peak Output Power Margin [dB]
2402	-0.74	30.00	30.74
2442	-0.86	30.00	30.86
2480	-0.65	30.00	30.65

Note:

Cable (including temporary RF cable) and attenuator loss has been compensated for Peak Output Power

Table 8: Maximum Peak Output Power, BLE, 2Mbps

Freq. [MHz]	Peak Output Power [dBm]	Peak Output Power Limit [dBm]	Peak Output Power Margin [dB]
2402	-0.75	30.00	30.75
2442	-0.82	30.00	30.82
2480	-0.70	30.00	30.70

Note:

Cable (including temporary RF cable) and attenuator loss has been compensated for Peak Output Power

5.5 6dB Bandwidth

RESULT:**Pass**

Date of testing: 2026-02-13

Ambient temperature: 25°C

Relative humidity: 26%

Atmospheric pressure: 1011hPa

Requirements:

FCC §15.215(c), §15.247(a)(2)

For system using digital modulation techniques in the 2400-2483.5MHz band, the 6dB bandwidth shall be at least 500kHz.

Additionally, for FCC, the 6dB bandwidth shall be contained within the frequency band designated in the rule section under which the equipment is operated.

Test procedure:


ANSI C63.10-2020 §11.8 and KDB 558074 D01.

The 6dB bandwidth was measured at the antenna port with a spectrum analyzer using a peak detector with max-hold. The RBW was set to 100kHz and the VBW was set to 300kHz. Markers placed at the lowest and highest intersections of the trace with a 6dBc line were used to calculate the emission bandwidth.

Table 9: 6dB Bandwidth, BLE, 1Mbps


Operating Frequency [MHz]	6dB Bandwidth [MHz]	Limit [MHz]
2402	0.749	>0.5
2442	0.717	>0.5
2480	0.700	>0.5

Figure 2: 6dB Bandwidth, BLE, Mode L (2402MHz), 1Mbps




11:22:40 AM 02/13/2026

Figure 3: 6dB Bandwidth, BLE, Mode M (2442MHz), 1Mbps



11:31:27 AM 02/13/2026

Figure 4: 6dB Bandwidth, BLE, Mode H (2480MHz), 1Mbps




11:34:49 AM 02/13/2026

Table 10: 6dB Bandwidth, BLE, 2Mbps


Operating Frequency [MHz]	6dB Bandwidth [MHz]	Limit [MHz]
2402	1.26	>0.5
2442	1.13	>0.5
2480	1.29	>0.5

Figure 5: 6dB Bandwidth, BLE, Mode L (2402MHz), 2Mbps




11:33:09 AM 02/13/2026

Figure 6: 6dB Bandwidth, BLE, Mode M (2442MHz), 2Mbps



11:30:29 AM 02/13/2026

Figure 7: 6dB Bandwidth, BLE, Mode H (2480MHz), 2Mbps



05:01:43 PM 02/16/2026

5.6 99% Bandwidth

RESULT:

For. Ref.

Date of testing: 2026-02-13

Ambient temperature: 25°C

Relative humidity: 26%

Atmospheric pressure: 1011hPa

Test procedure:
ANSI C63.10-2020 §6.9.3

The 99% bandwidth was measured at the antenna port with a spectrum analyzer using with the following settings:

- RBW = 30kHz, VBW = 100kHz, Sample detector with Max Hold

The RBW was set in the range from 1% to 5% of the observed OBW, VBW was set to at least three times of RBW.

Markers were placed at the lowest and highest intersections of the trace by 99% OBW function to obtain the value of the 99% emission bandwidth.

Table 11: 99% Bandwidth, BLE, 1Mbps

Operating Frequency [MHz]	99% Bandwidth [MHz]	Remarks
2402	1.0571	
2442	1.0555	
2480	1.0656	Widest OBW for 1Mbps

Figure 8: 99% Bandwidth, BLE, Mode L (2402MHz), 1Mbps




Figure 9: 99% Bandwidth, BLE, Mode M (2442MHz), 1Mbps





Figure 10: 99% Bandwidth, BLE, Mode H (2480MHz), 1Mbps




11:42:43 AM 02/13/2026

Table 12: 99% Bandwidth, BLE, 2Mbps


Operating Frequency [MHz]	99% Bandwidth [MHz]	Remarks
2402	2.0918	
2442	2.1007	Widest OBW for 2Mbps
2480	2.0969	

Figure 11: 99% Bandwidth, BLE, Mode L (2402MHz), 2Mbps



11:49:43 AM 02/13/2026

Figure 12: 99% Bandwidth, BLE, Mode M (2442MHz), 2Mbps




11:47:33 AM 02/13/2026

Test Report No.:
Prüfbericht-Nr.:

JP26FG0V 002

Page 30 of 69
Seite 30 von 69

Figure 13: 99% Bandwidth, BLE, Mode H (2480MHz), 2Mbps



11:40:39 AM 02/13/2026

5.7 Conducted Spurious Emissions

RESULT:**Pass**

Date of testing: 2026-02-13

Ambient temperature: 25°C

Relative humidity: 26%

Atmospheric pressure: 1011hPa

Requirements:
FCC §15.247(d)

In any 100kHz bandwidth outside the frequency band in which the intentional radiator is operating, the RF power shall be at least 20dBc below that of the maximum in-band 100kHz emission.

Test procedure:


ANSI C63.10-2020 §6.7, §6.10 and KDB 558074 D01.

The conducted spurious emissions were measured at the antenna port with a spectrum analyzer using a peak detector. The RBW was set to 100kHz and the VBW was set to 300kHz. Measurements were performed from 30MHz to 25GHz (10th harmonics).

The readings of the measurements take into account the loss generated by all the involved cables.


Authorized-band band-edge measurements (relative method) were performed by conducted, as per §6.10.4 of ANSI C63.10-2020.

Figure 14: Conducted Spurious Emissions, 30MHz - 25GHz, BLE, Mode L (2402MHz), 1Mbps




01:34:42 PM 02/13/2026

Figure 15: Conducted Spurious Emissions, 30MHz - 25GHz, BLE, Mode M (2442MHz), 1Mbps




01:37:07 PM 02/13/2026

Figure 16: Conducted Spurious Emissions, 30MHz - 25GHz, BLE, Mode H (2480MHz), 1Mbps



01:43:27 PM 02/13/2026

Figure 17: Authorized-band band-edge, BLE, Mode L (2402MHz), 1Mbps




01:10:23 PM 02/13/2026

Test Report No.:
Prüfbericht-Nr.:

JP26FG0V 002


Page 34 of 69
Seite 34 von 69

Figure 18: Authorized-band band-edge, BLE, Mode H (2480MHz), 1Mbps




01:06:02 PM 02/13/2026

Figure 19: Conducted Spurious Emissions, 30MHz - 25GHz, BLE, Mode L (2402MHz), 2Mbps



01:33:02 PM 02/13/2026

Figure 20: Conducted Spurious Emissions, 30MHz - 25GHz, BLE, Mode M (2442MHz), 2Mbps



01:40:15 PM 02/13/2026

Figure 21: Conducted Spurious Emissions, 30MHz - 25GHz, BLE, Mode H (2480MHz), 2Mbps




Figure 22: Authorized-band band-edge, BLE, Mode L (2402MHz), 2Mbps





Figure 23: Authorized-band band-edge, BLE, Mode H (2480MHz), 2Mbps



12:56:57 PM 02/13/2026

5.8 Peak Power Spectral Density

RESULT:**Pass**

Date of testing: 2026-02-13

Ambient temperature: 25°C

Relative humidity: 26%

Atmospheric pressure: 1011hPa

Requirements:
FCC §15.247(e)

For digitally modulated systems, the power spectral density (PSD) conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

Test procedure:

ANSI C63.10-2020 §11.10, KDB 558074 D01.

The peak power spectral density was measured at the antenna port with a spectrum analyzer using a peak detector with a RBW of 3kHz and a VBW of 10kHz.


The readings of the measurements take into account the loss generated by all the involved cables.

Table 13: Peak Power Spectral Density, BLE, 1Mbps

Operating Frequency [MHz]	Max PSD [dBm]	Limit [dBm]	Margin [dB]
2402	-13.51	8.00	21.51
2442	-14.51	8.00	22.51
2480	-14.15	8.00	22.15

Note:
Cable (including temporary RF cable) and attenuator loss has been compensated for Peak Output Power

Figure 24: Power Spectral Density, BLE, Mode L (2402MHz), 1Mbps



12:00:17 PM 02/13/2026

Figure 25: Power Spectral Density, BLE, Mode M (2442MHz), 1Mbps




Figure 26: Power Spectral Density, BLE, Mode H (2480MHz), 1Mbps





Table 14: Peak Power Spectral Density, BLE, 2Mbps

Operating Frequency [MHz]	Max PSD [dBm]	Limit [dBm]	Margin [dB]
2402	-17.33	8.00	25.33
2442	-17.36	8.00	25.36
2480	-16.06	8.00	24.06

Note:
Cable (including temporary RF cable) and attenuator loss has been compensated for Peak Output Power

Figure 27: Power Spectral Density, BLE, Mode L (2402MHz), 2Mbps



12:01:30 PM 02/13/2026

Figure 28: Power Spectral Density, BLE, Mode M (2442MHz), 2Mbps





Figure 29: Power Spectral Density, BLE, Mode H (2480MHz), 2Mbps



5.9 Radiated Spurious Emissions of Transmitter

RESULT:**Pass**

Date of testing: 2026-02-05, 2026-02-06, 2026-02-10,
2026-02-12, 2026-02-13

Ambient temperature: 22, 21, 20, 18, 20°C

Relative humidity: 25, 31, 55, 35, 33%

Atmospheric pressure: 1011, 1005, 1015, 1012, 1012hPa

Frequency range: 9kHz - 25GHz

Measurement distance: 3m

Kind of test site: Semi Anechoic Chamber

Requirements:

FCC §15.205, §15.209, §15.247(d)

Radiated emissions which fall in the restricted bands, as defined in FCC §15.205(a) must comply with the radiated emission limits specified in FCC §15.209(a).

Radiated emissions which fall outside the operation frequency band and outside restricted bands shall either meet the limit specified in FCC §15.209(a) or be attenuated at least 20dB below the power level in the 100kHz bandwidth within the band that contains the highest level of the desired power (the less severe limit applies).

Test procedure:

ANSI C63.10-2020 §6.3, §6.4, §6.5, §6.6, §6.10 and KDB 558074 D01

The EUT was placed on a nonconductive turntable. The table height was 80cm for measurements below 1GHz and 1.5m for measurements above 1GHz. Before final measurements of radiated emissions were performed, the EUT was scanned to determine its emission spectrum profile. The physical arrangement of the test system, the associated cabling were varied in order to ensure that maximum emission amplitudes were attained.

The spectrum was examined from 9kHz to the 10th harmonic of the highest fundamental transmitter frequency (25GHz). Final radiated emission measurements were made at 3m distance.

At each frequency where a spurious emission was found, the EUT was rotated 360° in order to determine the emission's maximum level. For frequencies above 30MHz, the antenna was raised and lowered from 1 to 4m and measurements were taken using both horizontal and vertical antenna polarizations.

For emissions between 30MHz and 1GHz, measurements were performed with a test receiver operating in the CISPR quasi-peak detection mode with a 6dB bandwidth set to 120kHz.

For emissions above 1GHz, measurements were performed with a spectrum analyzer using the following settings: for peak field strength: RBW = 1MHz & VBW = 3MHz; for average field strength: RBW = 1MHz & VBW = 10Hz. Positive peak detector was applied.

Absorbers have been placed on the floor between the EUT and the measuring antenna for testing above 1GHz.

Both AC adapter operation and battery operation were evaluated to determine the worst-case configuration. Final measurements were performed under AC adapter operation in all operating modes (L, M, and H). X, Y, and Z axes were tested to determine the worst axis. The final measurements were performed on the X axis.

The highest emission amplitudes relative to the appropriate limit were recorded in this report. Emissions other than those mentioned are small or not detectable.

Table 15: Radiated Emissions, Quasi Peak Data, 9kHz - 30MHz, BLE, Mode H (2480MHz), 1Mbps

Freq. [MHz]	Antenna Orient.	Reading QP [dBµV]	Factor [dB(1/m)]	Level QP [dBµV/m]	Limit [dBµV/m]	Margin QP [dB]	Angle [°]
0.0093	V	18.5	19.9	38.4	128.2	89.8	219
0.0095	H	18.3	19.9	38.2	128.0	89.8	308
0.1688	H	11.4	19.5	30.9	103.1	72.2	322
0.1745	V	12.5	19.5	32.0	102.8	70.8	170
0.6263	V	4.9	19.4	24.3	71.6	47.3	236
0.6342	H	4.9	19.4	24.3	71.5	47.2	356
3.1377	H	3.7	19.5	23.2	69.5	46.3	337
3.7535	V	4.0	19.6	23.6	69.5	45.9	112
21.7928	H	4.4	20.1	24.5	69.5	45.0	326
25.2049	V	4.5	20.3	24.8	69.5	44.7	161

Note: Level QP = Reading QP + Factor

Table 16: Radiated Emissions, Quasi Peak Data, 30MHz - 1GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode H (2480MHz), 1Mbps

Freq. [MHz]	Antenna Orient.	Reading QP [dBµV]	Factor [dB(1/m)]	Level QP [dBµV/m]	Limit [dBµV/m]	Margin QP [dB]	Height [cm]	Angle [°]
43.359	V	46.5	-21.5	25.0	40.0	15.0	132	160
43.787	H	38.6	-21.5	17.1	40.0	22.9	100	273
54.636	H	36.3	-21.4	14.9	40.0	25.1	218	35
54.841	V	45.3	-21.5	23.8	40.0	16.2	100	240
99.996	H	44.1	-25.4	18.7	43.5	24.8	259	359
99.998	V	48.9	-25.4	23.5	43.5	20.0	145	149
133.983	V	45.1	-21.3	23.8	43.5	19.7	100	196
139.480	V	44.9	-20.8	24.1	43.5	19.4	100	183

Note: Level QP = Reading QP + Factor

Table 17: Radiated Emissions, Peak Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode L (2402MHz), 1Mbps

Freq. [MHz]	Antenna Orient.	Reading PK [dBμV]	Factor [dB(1/m)]	Level PK [dBμV/m]	Limit [dBμV/m]	Margin PK [dB]	Height [cm]	Angle [°]
2274.123	V	61.1	-16.0	45.1	74.0	28.9	199	38
2274.123	H	64.7	-16.0	48.7	74.0	25.3	190	338
4804.174	H	54.3	-10.3	44.0	74.0	30.0	100	270
4804.174	V	55.5	-10.3	45.2	74.0	28.8	199	173
7206.050	V	59.3	-3.5	55.8	74.0	18.2	110	51
7206.050	H	57.4	-3.5	53.9	74.0	20.1	101	102
11868.930	H	45.1	-0.3	44.8	74.0	29.2	399	1
12009.100	V	50.9	0.8	51.7	74.0	22.3	260	5
14408.850	H	46.5	0.8	47.3	74.0	26.7	400	359
14560.360	V	46.6	0.6	47.2	74.0	26.8	400	1

Note: Level PK = Reading PK + Factor

Table 18: Radiated Emissions, Average Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode L (2402MHz), 1Mbps

Freq. [MHz]	Antenna Orient.	Reading AV [dBμV]	Factor [dB(1/m)]	Level AV [dBμV/m]	Limit [dBμV/m]	Margin AV [dB]	Height [cm]	Angle [°]
2274.123	V	55.1	-16.0	39.1	54.0	14.9	199	38
2274.123	H	60.4	-16.0	44.4	54.0	9.6	190	338
4804.174	H	41.1	-10.3	30.8	54.0	23.2	100	270
4804.174	V	41.4	-10.3	31.1	54.0	22.9	199	173
7206.050	V	50.2	-3.5	46.7	54.0	7.3	110	51
7206.050	H	47.3	-3.5	43.8	54.0	10.2	101	102
11868.930	H	36.6	-0.3	36.3	54.0	17.7	399	1
12009.100	V	38.8	0.8	39.6	54.0	14.4	260	5
14408.850	H	37.6	0.8	38.4	54.0	15.6	400	359
14560.360	V	39.0	0.6	39.6	54.0	14.4	400	1

Note: Level AV = Reading AV + Factor

Table 19: Radiated Emissions, Peak Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode M (2442MHz), 1Mbps

Freq. [MHz]	Antenna Orient.	Reading PK [dBµV]	Factor [dB(1/m)]	Level PK [dBµV/m]	Limit [dBµV/m]	Margin PK [dB]	Height [cm]	Angle [°]
2295.876	H	61.3	-16.1	45.2	74.0	28.8	100	350
4884.142	H	55.6	-10.0	45.6	74.0	28.4	101	192
4884.142	V	55.4	-10.0	45.4	74.0	28.6	199	172
7326.010	V	60.1	-3.6	56.5	74.0	17.5	110	50
7326.010	H	58.4	-3.6	54.8	74.0	19.2	106	267
12208.998	H	50.0	-0.2	49.8	74.0	24.2	400	1
12210.997	V	51.3	-0.3	51.0	74.0	23.0	197	337
14654.353	V	49.3	0.6	49.9	74.0	24.1	166	44
14665.602	H	48.5	0.6	49.1	74.0	24.9	139	338

Note: Level PK = Reading PK + Factor

Table 20: Radiated Emissions, Average Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode M (2442MHz), 1Mbps

Freq. [MHz]	Antenna Orient.	Reading AV [dBµV]	Factor [dB(1/m)]	Level AV [dBµV/m]	Limit [dBµV/m]	Margin AV [dB]	Height [cm]	Angle [°]
2295.876	H	49.6	-16.1	33.5	54.0	20.5	100	350
4884.142	H	41.3	-10.0	31.3	54.0	22.7	101	192
4884.142	V	41.6	-10.0	31.6	54.0	22.4	199	172
7326.010	V	50.8	-3.6	47.2	54.0	6.8	110	50
7326.010	H	48.6	-3.6	45.0	54.0	9.0	106	267
12208.998	H	38.4	-0.2	38.2	54.0	15.8	400	1
12210.997	V	39.9	-0.3	39.6	54.0	14.4	197	337
14654.353	V	38.5	0.6	39.1	54.0	14.9	166	44
14665.602	H	37.2	0.6	37.8	54.0	16.2	139	338

Note: Level AV = Reading AV + Factor

Table 21: Radiated Emissions, Peak Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode H (2480MHz), 1Mbps

Freq. [MHz]	Antenna Orient.	Reading PK [dBμV]	Factor [dB(1/m)]	Level PK [dBμV/m]	Limit [dBμV/m]	Margin PK [dB]	Height [cm]	Angle [°]
4260.618	H	55.7	-11.8	43.9	74.0	30.1	135	337
4960.060	V	56.0	-9.6	46.4	74.0	27.6	198	167
4960.060	H	55.9	-9.6	46.3	74.0	27.7	188	161
7439.999	V	60.6	-3.9	56.7	74.0	17.3	201	180
7439.999	H	56.6	-3.9	52.7	74.0	21.3	198	259
12399.248	V	50.9	-0.7	50.2	74.0	23.8	185	336
12401.250	H	49.5	-0.7	48.8	74.0	25.2	354	346
14877.850	V	46.8	0.7	47.5	74.0	26.5	152	40
14878.500	H	48.2	0.7	48.9	74.0	25.1	167	251
19640.010	V	50.3	-9.2	41.1	74.0	32.9	400	359
19939.910	H	49.0	-8.8	40.2	74.0	33.8	400	46
22320.370	V	47.5	-6.4	41.1	74.0	32.9	400	359
22342.120	H	47.2	-6.4	40.8	74.0	33.2	400	110

Note: Level PK = Reading PK + Factor

Table 22: Radiated Emissions, Average Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode H (2480MHz), 1Mbps

Freq. [MHz]	Antenna Orient.	Reading AV [dBμV]	Factor [dB(1/m)]	Level AV [dBμV/m]	Limit [dBμV/m]	Margin AV [dB]	Height [cm]	Angle [°]
4260.618	H	41.1	-11.8	29.3	54.0	24.7	135	337
4960.060	V	41.2	-9.6	31.6	54.0	22.4	198	167
4960.060	H	40.9	-9.6	31.3	54.0	22.7	188	161
7439.999	V	52.3	-3.9	48.4	54.0	5.6	201	180
7439.999	H	45.0	-3.9	41.1	54.0	12.9	198	259
12399.248	V	38.1	-0.7	37.4	54.0	16.6	185	336
12401.250	H	36.8	-0.7	36.1	54.0	17.9	354	346
14877.850	V	33.4	0.7	34.1	54.0	19.9	152	40
14878.500	H	35.5	0.7	36.2	54.0	17.8	167	251
19640.010	V	44.3	-9.2	35.1	54.0	18.9	400	359
19939.910	H	44.2	-8.8	35.4	54.0	18.6	400	46
22320.370	V	42.1	-6.4	35.7	54.0	18.3	400	359
22342.120	H	41.8	-6.4	35.4	54.0	18.6	400	110


Note: Level AV = Reading AV + Factor

Test Report No.:
Prüfbericht-Nr.:**JP26FG0V 002**Page 49 of 69
Seite 49 von 69**Table 23: Restricted-band Band-edge, BLE, 1Mbps**

Operating Frequency [MHz]	Antenna Orient.	Level AV [dBμV/m]	Level PK [dBμV/m]	Limit AV [dBμV/m]	Limit PK [dBμV/m]	Margin AV [dB]	Margin PK [dB]
2402	H	52.65	55.64	54.00	74.00	1.35 (*)	18.36
2402	V	48.90	52.77	54.00	74.00	5.10 (*)	21.23
2480	H	36.32	47.33	54.00	74.00	17.68	26.67
2480	V	32.90	44.08	54.00	74.00	21.10	29.92

Note: All correction factors (antenna, cable, pre-amplifier) are included in the measurement values.
Average limit in dBμV/m is calculated as follows: Average limit = $20 \times \log_{10}(500\mu\text{V/m})$.
Peak limit in dBμV/m is calculated as follows: Peak limit = Average limit + 20dB.

(*) The measured result is below the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to determine compliance at a level of confidence of 95%. However, the measured result indicates a high probability that the tested product complies with the specification limit.

Figure 30: Restricted-band Band-edge, Spectral Diagram, BLE, Mode L (2402MHz), 1Mbps, Horizontal Antenna Orientation

Test Report No.:
Prüfbericht-Nr.:

JP26FG0V 002

Page 50 of 69
Seite 50 von 69

Figure 31: Restricted-band Band-edge, Spectral Diagram, BLE, Mode L (2402MHz), 1Mbps, Vertical Antenna Orientation




Figure 32: Restricted-band Band-edge, Spectral Diagram, BLE, Mode H (2480MHz), 1Mbps, Horizontal Antenna Orientation




Figure 33: Restricted-band Band-edge, Spectral Diagram, BLE, Mode H (2480MHz), 1Mbps, Vertical Antenna Orientation




Table 24: Radiated Emissions, Quasi Peak Data, 30MHz - 1GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode H (2480MHz), 2Mbps

Freq. [MHz]	Antenna Orient.	Reading QP [dBµV]	Factor [dB(1/m)]	Level QP [dBµV/m]	Limit [dBµV/m]	Margin QP [dB]	Height [cm]	Angle [°]
43.460	V	46.4	-21.5	24.9	40.0	15.1	132	158
43.672	H	39.5	-21.5	18.0	40.0	22.0	100	338
54.532	V	45.1	-21.4	23.7	40.0	16.3	100	242
59.566	V	45.6	-21.7	23.9	40.0	16.1	100	156
97.335	V	47.6	-25.7	21.9	43.5	21.6	157	188
99.999	V	51.2	-25.4	25.8	43.5	17.7	157	141
100.001	H	46.0	-25.4	20.6	43.5	22.9	258	54
139.203	V	44.9	-20.9	24.0	43.5	19.5	100	200

Note: Level QP = Reading QP + Factor

**Table 25: Radiated Emissions, Peak Data, 1 - 25GHz, Horizontal and Vertical
 Antenna Orientations, BLE, Mode L (2402MHz), 2Mbps**

Freq. [MHz]	Antenna Orient.	Reading PK [dBµV]	Factor [dB(1/m)]	Level PK [dBµV/m]	Limit [dBµV/m]	Margin PK [dB]	Height [cm]	Angle [°]
2274.020	H	65.4	-16.0	49.4	74.0	24.6	192	353
4804.000	H	56.1	-10.3	45.8	74.0	28.2	100	34
4804.000	V	56.1	-10.3	45.8	74.0	28.2	187	167
7207.167	V	59.4	-3.5	55.9	74.0	18.1	100	49
7207.197	H	57.0	-3.5	53.5	74.0	20.5	199	273
12012.150	V	51.1	0.0	51.1	74.0	22.9	210	332
12046.928	H	45.1	0.0	45.1	74.0	28.9	355	345
14414.795	V	48.8	0.4	49.2	74.0	24.8	295	45
14415.350	H	47.2	0.4	47.6	74.0	26.4	115	343

Note: Level PK = Reading PK + Factor

**Table 26: Radiated Emissions, Average Data, 1 - 25GHz, Horizontal and Vertical
 Antenna Orientations, BLE, Mode L (2402MHz), 2Mbps**

Freq. [MHz]	Antenna Orient.	Reading AV [dBµV]	Factor [dB(1/m)]	Level AV [dBµV/m]	Limit [dBµV/m]	Margin AV [dB]	Height [cm]	Angle [°]
2274.020	H	59.6	-16.0	43.6	54.0	10.4	192	353
4804.000	H	40.7	-10.3	30.4	54.0	23.6	100	34
4804.000	V	41.2	-10.3	30.9	54.0	23.1	187	167
7207.167	V	47.5	-3.5	44.0	54.0	10.0	100	49
7207.197	H	44.2	-3.5	40.7	54.0	13.3	199	273
12012.150	V	39.0	0.0	39.0	54.0	15.0	210	332
12046.928	H	36.2	0.0	36.2	54.0	17.8	355	345
14414.795	V	32.9	0.4	33.3	54.0	20.7	295	45
14415.350	H	34.1	0.4	34.5	54.0	19.5	115	343

Note: Level AV = Reading AV + Factor

Table 27: Radiated Emissions, Peak Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode M (2442MHz), 2Mbps

Freq. [MHz]	Antenna Orient.	Reading PK [dBµV]	Factor [dB(1/m)]	Level PK [dBµV/m]	Limit [dBµV/m]	Margin PK [dB]	Height [cm]	Angle [°]
2295.000	H	60.3	-16.1	44.2	74.0	29.8	150	350
4884.000	V	55.2	-10.0	45.2	74.0	28.8	100	192
4884.000	H	56.1	-10.0	46.1	74.0	27.9	200	172
7324.878	V	59.4	-3.6	55.8	74.0	18.2	106	46
7327.516	H	57.7	-3.6	54.1	74.0	19.9	105	261
12212.296	V	51.4	-0.3	51.1	74.0	22.9	187	340
12212.595	H	49.6	-0.3	49.3	74.0	24.7	373	11
14649.694	V	49.3	0.6	49.9	74.0	24.1	166	44
14654.694	H	46.7	0.6	47.3	74.0	26.7	136	338

Note: Level PK = Reading PK + Factor

Table 28: Radiated Emissions, Average Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode M (2442MHz), 2Mbps

Freq. [MHz]	Antenna Orient.	Reading AV [dBµV]	Factor [dB(1/m)]	Level AV [dBµV/m]	Limit [dBµV/m]	Margin AV [dB]	Height [cm]	Angle [°]
2295.000	H	48.8	-16.1	32.7	54.0	21.3	150	350
4884.000	V	41.8	-10.0	31.8	54.0	22.2	100	192
4884.000	H	41.7	-10.0	31.7	54.0	22.3	200	172
7324.878	V	47.8	-3.6	44.2	54.0	9.8	106	46
7327.516	H	45.8	-3.6	42.2	54.0	11.8	105	261
12212.296	V	39.4	-0.3	39.1	54.0	14.9	187	340
12212.595	H	38.2	-0.3	37.9	54.0	16.1	373	11
14649.694	V	36.4	0.6	37.0	54.0	17.0	166	44
14654.694	H	35.7	0.6	36.3	54.0	17.7	136	338

Note: Level AV = Reading AV + Factor

Table 29: Radiated Emissions, Peak Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode H (2480MHz), 2Mbps

Freq. [MHz]	Antenna Orient.	Reading PK [dBµV]	Factor [dB(1/m)]	Level PK [dBµV/m]	Limit [dBµV/m]	Margin PK [dB]	Height [cm]	Angle [°]
4960.000	V	54.7	-9.6	45.1	74.0	28.9	150	167
4960.000	H	55.3	-9.6	45.7	74.0	28.3	150	169
7441.217	H	56.2	-3.9	52.3	74.0	21.7	200	259
7441.217	V	60.6	-3.9	56.7	74.0	17.3	200	180
12397.847	V	49.8	-0.7	49.1	74.0	24.9	164	342
12402.205	H	48.2	-0.7	47.5	74.0	26.5	393	64
14882.759	H	47.8	0.7	48.5	74.0	25.5	167	251
14882.779	V	47.7	0.7	48.4	74.0	25.6	195	43
19394.960	H	49.8	-9.3	40.5	74.0	33.5	400	156
19638.830	V	49.7	-9.2	40.5	74.0	33.5	400	33
22408.990	V	47.9	-6.3	41.6	74.0	32.4	400	65
22415.935	H	47.2	-6.3	40.9	74.0	33.1	400	1

Note: Level PK = Reading PK + Factor

Table 30: Radiated Emissions, Average Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode H (2480MHz), 2Mbps

Freq. [MHz]	Antenna Orient.	Reading AV [dBµV]	Factor [dB(1/m)]	Level AV [dBµV/m]	Limit [dBµV/m]	Margin AV [dB]	Height [cm]	Angle [°]
4960.000	V	41.0	-9.6	31.4	54.0	22.6	150	167
4960.000	H	41.0	-9.6	31.4	54.0	22.6	150	169
7441.217	H	43.4	-3.9	39.5	54.0	14.5	200	259
7441.217	V	49.4	-3.9	45.5	54.0	8.5	200	180
12397.847	V	37.3	-0.7	36.6	54.0	17.4	164	342
12402.205	H	35.7	-0.7	35.0	54.0	19.0	393	64
14882.759	H	36.0	0.7	36.7	54.0	17.3	167	251
14882.779	V	35.7	0.7	36.4	54.0	17.6	195	43
19394.960	H	47.7	-9.3	38.4	54.0	15.6	400	156
19638.830	V	45.2	-9.2	36.0	54.0	18.0	400	33
22408.990	V	43.7	-6.3	37.4	54.0	16.6	400	65
22415.935	H	41.8	-6.3	35.5	54.0	18.5	400	1

Note: Level AV = Reading AV + Factor

Test Report No.:
Prüfbericht-Nr.:

JP26FG0V 002

Page 56 of 69
Seite 56 von 69


Table 31: Restricted-band Band-edge, BLE, 2Mbps

Operating Frequency [MHz]	Antenna Orient.	Level AV [dBµV/m]	Level PK [dBµV/m]	Limit AV [dBµV/m]	Limit PK [dBµV/m]	Margin AV [dB]	Margin PK [dB]
2402	H	51.67	55.63	54.00	74.00	2.33 (*)	18.37
2402	V	48.15	52.60	54.00	74.00	5.85	21.40
2480	H	42.46	52.91	54.00	74.00	11.54	21.09
2480	V	37.93	48.95	54.00	74.00	16.07	25.05

Note: All correction factors (antenna, cable, pre-amplifier) are included in the measurement values.
Average limit in dBµV/m is calculated as follows: Average limit = 20 x Log₁₀(500µV/m).
Peak limit in dBµV/m is calculated as follows: Peak limit = Average limit + 20dB.

(*) The measured result is below the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to determine compliance at a level of confidence of 95%. However, the measured result indicates a high probability that the tested product complies with the specification limit.

Figure 34: Restricted-band Band-edge, Spectral Diagram, BLE, Mode L (2402MHz), 2Mbps, Horizontal Antenna Orientation



Test Report No.:
Prüfbericht-Nr.:

JP26FG0V 002

Page 57 of 69
Seite 57 von 69

Figure 35: Restricted-band Band-edge, Spectral Diagram, BLE, Mode L (2402MHz), 2Mbps, Vertical Antenna Orientation




Figure 36: Restricted-band Band-edge, Spectral Diagram, BLE, Mode H (2480MHz), 2Mbps, Horizontal Antenna Orientation





Figure 37: Restricted-band Band-edge, Spectral Diagram, BLE, Mode H (2480MHz), 2Mbps, Vertical Antenna Orientation



5.10 AC Power Line Conducted Emission of Transmitter

RESULT:**Pass**

Date of testing: 2026-02-13

Ambient temperature: 25°C
Relative humidity: 26%
Atmospheric pressure: 1011hPa

Frequency range: 0.15 - 30MHz
Kind of test site: Shielded Room

Requirements:

FCC §15.207

The AC power line conducted emission on any frequency within the band 150kHz to 30MHz shall not exceed the limits specified in FCC §15.207(a).

Test procedure:

ANSI C63.10-2020 §6.2

The EUT was placed on an wooden table raised 80cm above the reference ground plane. A vertical conducting plane of the screened room was located 40cm to the rear of the EUT. The AC input port of the EUT was connected to a Line Impedance Stabilization Network (LISN).

The physical arrangement of the test system and associated cabling was varied to determine the effect on the EUT's emissions in amplitude and frequency in order to ensure that maximum emission amplitudes were attained.

The measurements were performed with a measurement receiver operating in the CISPR quasi-peak and average detection modes. The receiver's 6dB bandwidth was set to 9kHz.

Prechecks have been performed in the all operation modes to determine which mode produces the highest emission level. Final measurement was performed for the worst case operation mode.

The highest emission amplitudes relative to the appropriate limit were recorded in this report. Emissions other than those mentioned were small or not detectable.

Table 32: AC Power Line Conducted Emission, 0.15 - 30MHz, Quasi Peak and Average Data, Phase N (N) and L1 (L), BLE, 2M, Mode H, (2480MHz)

Freq. [MHz]	Phase	Reading QP [dBμV]	Reading AV [dBμV]	Factor [dB]	Level QP [dBμV]	Level AV [dBμV]	Limit QP [dBμV]	Limit AV [dBμV]	Margin QP [dB]	Margin AV [dB]
0.5055	N	22.2	14.0	9.9	32.1	23.9	56.0	46.0	23.9	22.1
0.5078	L	24.9	13.4	9.9	34.8	23.3	56.0	46.0	21.2	22.7
0.5303	N	18.7	11.2	9.9	28.6	21.1	56.0	46.0	27.4	24.9
0.5303	L	20.6	10.3	9.9	30.5	20.2	56.0	46.0	25.5	25.8
0.5438	N	21.4	12.1	9.9	31.3	22.0	56.0	46.0	24.7	24.0
0.5438	L	22.6	11.2	9.9	32.5	21.1	56.0	46.0	23.5	24.9
3.6960	N	21.8	12.1	10.0	31.8	22.1	56.0	46.0	24.2	23.9
3.6960	L	22.4	12.2	10.0	32.4	22.2	56.0	46.0	23.6	23.8
4.7108	L	22.9	13.4	10.1	33.0	23.5	56.0	46.0	23.0	22.5
4.7467	N	22.7	13.4	10.1	32.8	23.5	56.0	46.0	23.2	22.5
6.3398	L	27.9	17.6	10.1	38.0	27.7	60.0	50.0	22.0	22.3
6.3420	N	27.9	17.0	10.2	38.1	27.2	60.0	50.0	21.9	22.8
7.1183	N	28.0	17.4	10.2	38.2	27.6	60.0	50.0	21.8	22.4
7.1183	L	28.3	17.8	10.2	38.5	28.0	60.0	50.0	21.5	22.0
8.0340	N	28.3	17.9	10.3	38.6	28.2	60.0	50.0	21.4	21.8
8.0340	L	29.0	18.4	10.3	39.3	28.7	60.0	50.0	20.7	21.3
8.7113	L	27.6	17.3	10.3	37.9	27.6	60.0	50.0	22.1	22.4
8.7135	N	27.0	16.7	10.3	37.3	27.0	60.0	50.0	22.7	23.0
9.7282	L	26.6	15.2	10.3	36.9	25.5	60.0	50.0	23.1	24.5
9.7305	N	26.1	14.5	10.4	36.5	24.9	60.0	50.0	23.5	25.1
17.9003	N	23.9	9.4	10.7	34.6	20.1	60.0	50.0	25.4	29.9
17.9003	L	23.9	9.8	10.7	34.6	20.5	60.0	50.0	25.4	29.5
24.0000	N	22.2	15.9	11.0	33.2	26.9	60.0	50.0	26.8	23.1
24.0000	L	22.1	16.1	10.9	33.0	27.0	60.0	50.0	27.0	23.0

Note: Level QP = Reading QP + Factor, Level AV = Reading AV + Factor

7. List of Tables

Table 1: Test Summary.....	5
Table 2: List of Test and Measurement Equipment.....	7
Table 3: Measurement Uncertainty.....	9
Table 4: Setting of Test Frequencies.....	12
Table 5: Interfaces present on the EUT.....	14
Table 6: EUT Serial Numbers.....	14
Table 7: Maximum Peak Output Power, BLE, 1Mbps.....	20
Table 8: Maximum Peak Output Power, BLE, 2Mbps.....	20
Table 9: 6dB Bandwidth, BLE, 1Mbps.....	22
Table 10: 6dB Bandwidth, BLE, 2Mbps.....	24
Table 11: 99% Bandwidth, BLE, 1Mbps.....	27
Table 12: 99% Bandwidth, BLE, 2Mbps.....	29
Table 13: Peak Power Spectral Density, BLE, 1Mbps.....	39
Table 14: Peak Power Spectral Density, BLE, 2Mbps.....	41
Table 15: Radiated Emissions, Quasi Peak Data, 9kHz - 30MHz, BLE, Mode H (2480MHz), 1Mbps.....	45
Table 16: Radiated Emissions, Quasi Peak Data, 30MHz - 1GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode H (2480MHz), 1Mbps.....	45
Table 17: Radiated Emissions, Peak Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode L (2402MHz), 1Mbps.....	46
Table 18: Radiated Emissions, Average Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode L (2402MHz), 1Mbps.....	46
Table 19: Radiated Emissions, Peak Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode M (2442MHz), 1Mbps.....	47
Table 20: Radiated Emissions, Average Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode M (2442MHz), 1Mbps.....	47
Table 21: Radiated Emissions, Peak Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode H (2480MHz), 1Mbps.....	48
Table 22: Radiated Emissions, Average Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode H (2480MHz), 1Mbps.....	48
Table 23: Restricted-band Band-edge, BLE, 1Mbps.....	49
Table 24: Radiated Emissions, Quasi Peak Data, 30MHz - 1GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode H (2480MHz), 2Mbps.....	52
Table 25: Radiated Emissions, Peak Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode L (2402MHz), 2Mbps.....	53
Table 26: Radiated Emissions, Average Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode L (2402MHz), 2Mbps.....	53
Table 27: Radiated Emissions, Peak Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode M (2442MHz), 2Mbps.....	54
Table 28: Radiated Emissions, Average Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode M (2442MHz), 2Mbps.....	54
Table 29: Radiated Emissions, Peak Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode H (2480MHz), 2Mbps.....	55
Table 30: Radiated Emissions, Average Data, 1 - 25GHz, Horizontal and Vertical Antenna Orientations, BLE, Mode H (2480MHz), 2Mbps.....	55
Table 31: Restricted-band Band-edge, BLE, 2Mbps.....	56
Table 32: AC Power Line Conducted Emission, 0.15 - 30MHz, Quasi Peak and Average Data, Phase N (N) and L1 (L), BLE, 2M, Mode H, (2480MHz).....	60

8. List of Figures

Figure 1: Block Diagram.....	13
------------------------------	----

Figure 2: 6dB Bandwidth, BLE, Mode L (2402MHz), 1Mbps	22
Figure 3: 6dB Bandwidth, BLE, Mode M (2442MHz), 1Mbps	22
Figure 4: 6dB Bandwidth, BLE, Mode H (2480MHz), 1Mbps	23
Figure 5: 6dB Bandwidth, BLE, Mode L (2402MHz), 2Mbps	24
Figure 6: 6dB Bandwidth, BLE, Mode M (2442MHz), 2Mbps	24
Figure 7: 6dB Bandwidth, BLE, Mode H (2480MHz), 2Mbps	25
Figure 8: 99% Bandwidth, BLE, Mode L (2402MHz), 1Mbps	27
Figure 9: 99% Bandwidth, BLE, Mode M (2442MHz), 1Mbps	27
Figure 10: 99% Bandwidth, BLE, Mode H (2480MHz), 1Mbps	28
Figure 11: 99% Bandwidth, BLE, Mode L (2402MHz), 2Mbps	29
Figure 12: 99% Bandwidth, BLE, Mode M (2442MHz), 2Mbps	29
Figure 13: 99% Bandwidth, BLE, Mode H (2480MHz), 2Mbps	30
Figure 14: Conducted Spurious Emissions, 30MHz - 25GHz, BLE, Mode L (2402MHz), 1Mbps	32
Figure 15: Conducted Spurious Emissions, 30MHz - 25GHz, BLE, Mode M (2442MHz), 1Mbps	32
Figure 16: Conducted Spurious Emissions, 30MHz - 25GHz, BLE, Mode H (2480MHz), 1Mbps	33
Figure 17: Authorized-band band-edge, BLE, Mode L (2402MHz), 1Mbps	33
Figure 18: Authorized-band band-edge, BLE, Mode H (2480MHz), 1Mbps	34
Figure 19: Conducted Spurious Emissions, 30MHz - 25GHz, BLE, Mode L (2402MHz), 2Mbps	35
Figure 20: Conducted Spurious Emissions, 30MHz - 25GHz, BLE, Mode M (2442MHz), 2Mbps	35
Figure 21: Conducted Spurious Emissions, 30MHz - 25GHz, BLE, Mode H (2480MHz), 2Mbps	36
Figure 22: Authorized-band band-edge, BLE, Mode L (2402MHz), 2Mbps	36
Figure 23: Authorized-band band-edge, BLE, Mode H (2480MHz), 2Mbps	37
Figure 24: Power Spectral Density, BLE, Mode L (2402MHz), 1Mbps	39
Figure 25: Power Spectral Density, BLE, Mode M (2442MHz), 1Mbps	40
Figure 26: Power Spectral Density, BLE, Mode H (2480MHz), 1Mbps	40
Figure 27: Power Spectral Density, BLE, Mode L (2402MHz), 2Mbps	41
Figure 28: Power Spectral Density, BLE, Mode M (2442MHz), 2Mbps	42
Figure 29: Power Spectral Density, BLE, Mode H (2480MHz), 2Mbps	42
Figure 30: Restricted-band Band-edge, Spectral Diagram, BLE, Mode L (2402MHz), 1Mbps, Horizontal Antenna Orientation	49
Figure 31: Restricted-band Band-edge, Spectral Diagram, BLE, Mode L (2402MHz), 1Mbps, Vertical Antenna Orientation	50
Figure 32: Restricted-band Band-edge, Spectral Diagram, BLE, Mode H (2480MHz), 1Mbps, Horizontal Antenna Orientation	50
Figure 33: Restricted-band Band-edge, Spectral Diagram, BLE, Mode H (2480MHz), 1Mbps, Vertical Antenna Orientation	51
Figure 34: Restricted-band Band-edge, Spectral Diagram, BLE, Mode L (2402MHz), 2Mbps, Horizontal Antenna Orientation	56
Figure 35: Restricted-band Band-edge, Spectral Diagram, BLE, Mode L (2402MHz), 2Mbps, Vertical Antenna Orientation	57
Figure 36: Restricted-band Band-edge, Spectral Diagram, BLE, Mode H (2480MHz), 2Mbps, Horizontal Antenna Orientation	57
Figure 37: Restricted-band Band-edge, Spectral Diagram, BLE, Mode H (2480MHz), 2Mbps, Vertical Antenna Orientation	58

9. List of Photographs

Photograph 1: Set-up for Antenna Port Conducted Emission of Transmitter, General View	61
Photograph 2: Set-up for Radiated Spurious Emission below 30MHz	61
Photograph 3: Set-up for Radiated Spurious Emission below 1GHz, Front View	62
Photograph 4: Set-up for Radiated Spurious Emission below 1GHz, Rear View	62
Photograph 5: Set-up for Radiated Spurious Emission above 1GHz, Front View	63
Photograph 6: Set-up for Radiated Spurious Emission above 1GHz, Rear View	63

Test Report No.: <i>Prüfbericht-Nr.:</i>	JP26FG0V 002	Page 69 of 69 <i>Seite 69 von 69</i>
Photograph 7: Set-up for AC Power Line Conducted Emission, Front View.....64 Photograph 8: Set-up for AC Power Line Conducted Emission, Rear View64 Photograph 9: Set-up for X-Axis of the EUT65 Photograph 10: Set-up for Y-Axis of the EUT65 Photograph 11: Set-up for Z-Axis of the EUT.....66		
– End of test report –		